

AMENDMENT NO. 1 OCTOBER 2005
TO
IS 814 : 2004 COVERED ELECTRODES FOR
MANUAL METAL ARC WELDING OF CARBON AND
CARBON MANGANESE STEEL — SPECIFICATION

(Sixth Revision)

[*Foreword, para 3(a)*] — Substitute the following for the existing line:

‘Semibasic type (SB) of covering has been included and ‘S’ type of covering has been deleted.’

(*Foreword, para 3*) — Add ‘d)’ as follows:

‘d) Transverse bend test has been deleted’

[*Page 2, clause 5.1.2(a), and page 4, clause 5.7*] — Substitute ‘H₁, H₂, H₃’ for ‘H₁, H₂ and H₃’ wherever it appears.

[*Page 2, clause 5.1.2(b), lines 1 to 4*] — Substitute the following for the existing:

“Letters J, K and L indicating increased metal recovery, as ‘effective electrode efficiency (EE)’ as per IS 13043 in the following range (see 5.8)”.

(*Page 2, clause 5.5*) — Substitute ‘1,2,3.....’ for ‘a),b),c),.....’.

(*Page 5, Table 5, col 2*) — Substitute ‘As per manufacturers declaration’ for ‘Not specified’.

(*Page 6, clause 8.4, line 2*) — Substitute ‘see 8.3’ for ‘see 8.2’.

[*Page 6, clause 8.4(a)*] — Substitute ‘tensile and impact’ for ‘tensile or impact’.

(*Page 7, Table 6, col 3*) — Substitute ‘400’ for ‘360’ for all EX5.....classifications.

(*Page 9, Table 8, col 1 and 2*) — Substitute the following for the existing classifications:

EA 42	XX	
EB 542	X	
EB 542		
EB 562	X	Grade 1
EB 562	X	
EB 541	X	
EB 532	X	

Amend No. 1 to IS 814 : 2004 .

EC 4 X 10	- X	
EC 4 X 16	- X	
ER 4 XXX	- X	
ERR 4 XXX	- X	
ER 5 XXX	- JX	Grade 2
ERR 5 XXX	- JX	
ERR 5 XXX	- KX	
ERR 5 XXX	- LX	
EB 5 XXX	- HXX	
EB 5 XXX	- HLX	
ER 41 XX		Not
ER 42 XX		required

(Page 11, Table 9, col 4 row 1) — Substitute '410-540' for '410-510'.

(Page 11, Table 9, col 5, row 2) — Substitute '400' for '360'.

(Page 11, Table 9, col 6, row 2) — Substitute the following for the existing:

'Satisfactory for EX4XXX and unsatisfactory for EX5XXX classes'

(Page 11, Table 9, col 1, row 6) — Substitute 'Elongation' for 'Elogation'.

(Page 12, Table 10, col 4, row 1) — Substitute '410-540' for '410-510'.

(Page 12, Table 10, col 6, row 1) — Substitute the following for the existing:

'Satisfactory for both EX4XXX and EX5XXX classes'

(Page 12, Table 10, col 6, row 4) — Substitute the following for the existing:

'Unsatisfactory for both EX5XXX and EX4XXX classes'

(Page 12, Table 10, col 1, row 5) — Substitute 'Elongation' for 'Elogation'.

(Page 12, Table 10, col 5, row 2) — Substitute '400' for '360'.

(Page 12, Table 10, line diagram for classification EB 5426H1JX5, symbol 5) — Substitute 'YS=400' for 'YS = 360'.

Amend No. 1 to IS 814 : 2004

(*Page 12, Table 10, last line below line diagram*) — Substitute 'EB 5426 H, IX' for 'EB 5426 H1UX'.

(*Page 18, Annex F, clause F-2.7, line 5*) — Substitute 'Fig. 10' for 'Fig. 9'.

(*Page 19, Table 16, col 6, heading*) — Substitute 'Depth Below Notch' for 'Depth Between Notch'.

(*Page 24, Fig. 16*) — Delete 'THIS 15 mm FROM START SHOULD NOT BE CONSIDERED FOR VISUAL INSPECTION'.

(MTD 11)