

AMENDMENT NO. 2 DECEMBER 1983

TO

**IS : 943 - 1979 FUNCTIONAL REQUIREMENTS OF 680-1/min
TRAILER PUMP FOR FIRE BRIGADE USE**

(Second Revision)

Alterations

**(Page 5, clause 4.1, line 2) - Substitute
'IS:1601-1960*' for 'IS:1603-1960*'.**

**(Page 5, clause 4.1, line 3) - Substitute 'at
least 5 percent' for 'sufficient'.**

**(Page 5, clause 4.1.2, line 1) - Substitute
'4.1.2 In case of water cooled engine indirect' for
'4.1.2 Indirect'.**

**(Page 5, foot-note with '*' mark) - Substitute
the following for the existing foot-note:**

**'*Specification for performance of constant
speed internal combustion engines general purposes.'**

**(Page 6, clause 4.3.2) - Substitute the following
for the existing clause:**

**'4.3.2 The impeller shall be dynamically balanced
for maximum operating speed along with any other
unmachined rotating parts on proper balancing equipment.
The pump casing shall be of robust construction and
tested to withstand 1.5 times the shut off pressure at
maximum operating speed or twice the operating pressure,
whichever is higher.'**

**(Page 6, clause 4.3.3, line 2) - Substitute
'27 $\pm$ 2°C' for '16.5°C'.**

[Page 6, clause 4.3.3 (a)(3), second sentence] -
Substitute the following for the existing sentence:

'However, deduction at the rate of 1 percent of every 5 percent change in humidity shall be made when humidity changes from 75 percent to 95 percent.'

(Page 7, clause 4.3.5, lines 1 and 2) - Delete the following words '(with engine cover closed)'.

(Page 7, clause 4.4, lines 2 and 3) - Substitute '24 seconds from the time it is engaged' for '24 seconds and'.

(Page 7, clause 4.5, line 2) - Substitute 'clutch flexible couplings or any other suitable measure shall' for 'clutch shall'.

(BDC 22)