

AMENDMENT NO. 1 DECEMBER 1983

TO

**IS:944-1979 FUNCTIONAL REQUIREMENTS OF 1800-l/min
TRAILER PUMP FOR FIRE BRIGADE USE**

(Second Revision)

Alterations

(Page 4, clause 4.1, line 2) - Substitute 'IS:1601-1960' for 'IS:1603-1960'.

(Page 4, foot-note with 'W' mark) - Substitute the following for the existing foot-note:

'Specification for performance of constant speed internal combustion engines for automotive purposes.'

(Page 5, clause 4.1, line 1) - Substitute 'at least 5 percent' for 'sufficient'.

(Page 5, clause 4.1.2, line 1) - Substitute the following for the existing line:

'In case of water cooled engine indirect cooling system of the open-circuit type in which water is'.

(Page 6, clause 4.3.2) - Substitute the following for the existing clause:

'4.3.2 The 'impeller shall be dynamically balanced for maximum operating speed along with any other unmachined rotating parts on proper balancing equipment. The pump casing shall be of robust construction and tested to withstand 1.5 times the shut off pressure at maximum operating speed or twice the operating pressure, whichever is higher.'

(Page 6, clause 4.3.3, line 2) - Substitute '27 ± 2°C' for '16.5°C'.

[Page 6, clause 4.3.3(c), lines 2 and 3] - Substitute the following for the existing lines:

'However, deduction at the rate of 1 percent of every 5 percent change in humidity shall be made when humidity changes from 75 to 95 percent.'

(Page 6, clause 4.3.5, lines 1 and 2) - Delete the following words:

'(with engine cover closed)'.

(Page 7, clause 4.4, line 3) - Substitute the following for the existing line:

'not more than 24 seconds from the time it is engaged after 24 seconds and shall preferably the fully automat

(Page 7, clause 4.5, line 2) - Substitute the following for the existing line:

'compast as possible and preferably a clutch flexible couplings or any other suitable measure shall be incorporated between'.

(BDC 22)