

**AMENDMENT NO. 5 JULY 1990**  
**TO**  
**IS 8496 : 1977 SPECIFICATION FOR PROPOXUR,**  
**TECHNICAL**

[ *Page 6, clause A-1.4 ( see also Amendment No. 3 )* ] — Substitute the following for the existing clause:

‘A-1.4 Preparation of Standard, Sample and Blank Solutions’

[ *Page 6, clause A-1.4.2.2 ( see also Amendments No. 3 and 4 )* ] — Insert the following after A-1.4.2.2:

‘A-1.4.3 *Preparation of Blank Solution* — Prepare a blank solution exactly in the same manner as described in A-1.4.2.1 and A-1.4.2.2.’

[ *Page 6, clause A-1.5.1 ( see also Amendments No. 3 and 4 )* ] — Substitute the following for the existing clause:

‘A-1.5.1 Take out with the help of pipettes 10 ml each of *Standard Solution B* ( see A-1.4.1.2 ) and *Sample Solution B* ( see A-1.4.2.2 ) into two separate sets of 100-ml volumetric flasks. To one set of flasks comprising *Standard* and *Sample Solutions* add 20 ml 1N sulphuric acid solution while to another set of flasks add 20 ml 1N sodium methoxide solution. Make up the volume in each flask with methyl alcohol. Similarly **prepare** acidic and alkaline solutions of the *Blank Solution* ( see A-1.4.3 ). Use the acidic solution in the reference cell and the alkaline solution to adjust the zero of the spectrophotometer. After thorough mixing separately of the *Standard Solution* and *Sample Solution*, take the absorbance curve from 292 to 294 mm.

NOTE — The absorbance measurement of the *Standard and Sample Solutions* should agree within  $\pm 10$  percent each other.’

( FADC I )