

AMENDMENT NO. 1 OCTOBER 1995
TO
IS 8591 : 1980 SPECIFICATION FOR KOKUM FAT
(First Revision)

(Page 4, Foreword, clause 0.6) — Add the following clause 0.7 after clause 0.6 and renumber the subsequent clauses:

‘0.7 A scheme for labelling environment friendly products to be known as ECO Mark has been introduced at the instance of the Ministry of Environment and Forests (MEF). The ECO Mark shall be administered by the Bureau of Indian Standards (BIS) under the BIS Act, 1986 as per the Resolution No. 71 dated 20 February 1991 as published in the Gazette of the Government of India vide GSR 85(E) dated 21 February 1991. For a product to be eligible for marking with the ECO Mark it shall also carry the Standard Mark of BIS for quality besides meeting additional optional environment friendly (EF) requirements. The EF requirements for *KOKUM* fat are therefore being included through an amendment.

This amendment is based on the Gazette Notification No. 678 dated 30 August 1994 for Labelling Edible Oils, Tea and Coffee as environment friendly products, published by the Ministry of Environment and Forests.’

(Page 5, clause 4.4) — Add the following clauses after clause 4.4:

‘4.5 Optional Requirements for ECO Mark

4.5.1 General Requirements

4.5.1.1 The product shall conform to the requirements of quality prescribed under clauses 4.1 to 4.4.

4.5.1.2 The manufacturers shall produce to BIS environmental consent clearance from the concerned State Pollution Control Board as per the norms laid down under the *Water (Prevention and Control of Pollution) Act, 1974*; *Air (Prevention and Control of Pollution) Act, 1981*; *Water (Prevention and Control of Pollution) Cess Act, 1977* respectively, along with the authorization, if required under the *Environment (Protection) Act, 1986*, while applying for ECO Mark.

4.5.2 Specific Requirements

Amend No. 1 to IS 8591 : 1980

4.5.2.1 The product shall not contain aflatoxin, more than 5 mg/kg, when tested by the method prescribed in Appendix A.

4.5.2.2 The pesticide residues, if any, shall not exceed the tolerance limits as prescribed in the *Prevention of Food Adulteration Act, 1954* and *Rules* made thereunder.

4.5.2.3 Only permitted antioxidants not exceeding the quantities specified against each as prescribed under the *Prevention of Food Adulteration Act, 1954* and *Rules* made thereunder, shall be used, if required.

4.5.2.4 The product shall not contain any of the toxic metals in excess of the quantities prescribed in Table 2.

TABLE 2 LIMITS FOR TOXIC METALS

Sl No.	CHARACTERISTIC	REQUIREMENT	METHOD OF TEST, REF TO
i)	Lead, mg/kg, <i>Max</i>	5.0	15 of IS 1699 : 1995*
ii)	Arsenic, mg/kg, <i>Max</i>	0.5	do
iii)	Cadmium, mg/kg, <i>Max</i>	1.0	do
iv)	Mercury (total) mg/kg, <i>Max</i>	0.25	do

*Methods of sampling and test for food colours (*second revision*).

(*Page 5, clause 5.1*) — Add the following clause 5.1.1 after clause 5.1:

‘5.1.1 For ECO Mark the product shall be packed in such packages which are made from recyclable (that is which can be re-processed to manufacture any useful product) or biodegradable materials.’

(*Page 7, clause 6.2*) — Add the following clause 6.3 after clause 6.2:

“6.3 For ECO Mark the containers shall be marked with the following information:

- List of identified critical ingredients in descending order of quantity, percent by mass, which shall include ‘made from *KOKUM* fat’;
- The brief criteria for which the product has been labelled for ECO Mark; and
- Shelf life of the product.”

Amend No. 1 to IS 8591 : 1980

(Page 7, clause 8.1) — Add the following Appendix after clause 8.1:

**'APPENDIX A
(Clause 4.5.2.1)**

DETERMINATION OF AFLATOXIN

A-1 REAGENTS

A-1.1 Acetone, 70 Percent — 700 ml acetone in 300 ml distilled water.

A-1.2 Acetone, 20 Percent — 200 ml acetone in 800 ml distilled water.

A-1.3 Lead Acetate, 20 Percent — 200 g neutral acetate in distilled water and 3 ml glacial acetic acid, diluted to one litre.

A-2 PROCEDURE

A-2.1 Dissolve 30 g sample in 100 ml hexane.

A-2.2 Extract with 3 × 50 ml 70 percent acetone.

A-2.3 To the extract add 60 ml distilled water and 20 ml lead acetate.

A-2.4 Boil to reduce volume to 150 ml. Cool to about 20°C.

A-2.5 Filter and wash with 20 percent acetone.

A-2.6 Extract filtrate and washings with 3 × 50 ml chloroform.

A-2.7 Pass chloroform layer through anhydrous sodium sulphate.

A-2.8 Concentrate to 50 ml and spot on TLC plate.

A-3 CALCULATION

$$\text{Aflatoxin, mg/kg} = \frac{V \times s \times 1\,000}{v \times m}$$

where

V = volume of extract in ml,

v = volume of extract giving minimum observable fluorescence in μl ,

m = mass of sample in g, and

s = standard toxin giving minimum observable fluorescence in μg .'

(FAD 44)

Reprography Unit, BIS, New Delhi, India