

AMENDMENT NO. 3 MAY 2025
TO
IS 8737 : 2017 VALVE FITTINGS FOR USE WITH LIQUEFIED PETROLEUM GAS
(LPG) OF UPTO 250 LITRE WATER CAPACITY — SPECIFICATION
(Second Revision)

[Page 1, clause 1.1 (see also Amendment No. 2)] — Substitute the following for the existing:

‘This standard specifies the basic requirements of material, dimensions and testing of valve fittings for liquefied petroleum gas (LPG) gas cylinders of upto 250 litre water capacity. It covers valves with taper stems only. This standard also covers valves equipped with anti-pilferage device (APD).’

(Page 1, clause 3.1) — Substitute the following for the existing:

‘**3.1 Valve Body** — The major valve component which includes an inlet, an outlet and may include an anti-pilferage device as an integral part to the valve.’

(Page 2, clause 3.16) — Insert the following at the end:

‘**3.17 Anti-Pilferage Device (APD)** — It is a device which limits the withdrawal of liquified LPG from cylinders. The anti-pilferage device (APD) should reset automatically.

3.18 Anti-Pilferage Self Closing Valve (APSCV) — It is a self closing valve having added feature of anti-pilferage device in it.’

(Page 9, clause 8.3.3) — Insert the following at the end:

‘**8.3.4 Inclination Test**

This test is applicable to valves equipped with anti-pilferage device (APD) only.

The assembled valve shall be firmly screwed into a cylinder. Cylinder shall then be filled with water to its 80 percent water capacity and then pressurized to 7 kgf/cm² pressure with air. Cylinder shall be mounted on the fixture firmly. The fixture should be able to rotate the cylinder to 45°, 90° and 180° from its original vertical axis. The valve shall be kept in open position for the duration of the test. Now the cylinder shall be rotated to above three angles and observed for leakage of water. The rate of leakage of water, if any, shall be as agreed between the purchaser and manufacturer subject to a maximum of 40 mm³/s.

After the test, gently keep the cylinder in up-right position, The anti-pilferage device (APD) shall reset, and the valve shall come in normal operating position within 15 s without applying any external force. Air should flow out of the valve when the valve is put in open position to re-confirm the reset of APD.’

(Page 10, clause 9.5) — Insert the following at the end:

‘**9.6 Vibration Test**

This test is applicable to valves equipped with anti-pilferage device (APD) only.

9.6.1 Procedure

One valve shall be vibrated for 2 h in a test apparatus at 17 Hz with amplitude of 1.5 mm in each of the three axes (90 degree to each other).

9.6.2 Requirement

On completion of the 6 h vibration, the valve shall comply with the requirement of pneumatic test as per 8.3.’

Amendment No. 3 to IS 8737 : 2017

(Page 10, clause **10.1**) — Substitute the following for the existing:

‘10.1 Each valve shall be permanently marked with the following information:

- a) Quarter and year of manufacture;
- b) Manufacturer’s identification mark;
- c) Number of this standard;
- d) Maximum working pressure, in MPa;
- e) APV shall be marked [in case of ANTI-PILFERAGE SELF CLOSING VALVE (APSCV)];
- f) Batch No.; and
- g) BIS License No.’