

**AMENDMENT NO. 1 DECEMBER 2006
TO
IS 8764 : 1998 METHOD FOR DETERMINATION OF
POINT LOAD STRENGTH INDEX OF ROCKS**

(First Revision)

(Page 6, clause 7.1.1) — Substitute the following for the existing formula:

$$l_p (50) = \frac{P}{D^{1.5} \sqrt{D_{50}}}$$

where

$l_p(50)$ = point load strength index in MPa (for the standard core size),
 P = failure load in N,
 D = core diameter in mm, and
 D_{50} = standard core diameter (50 mm).

(Page 6, clause 7.3) — Substitute the following for the existing formula:

$$l_L (50) = \frac{P}{(DW)^{0.75} \sqrt{D_{50}}}$$

where

P = peak load in N at failure,
 (DW) = the minimum cross sectional area passing through point loads in mm^2 ,
 $l_L (50)$ = point load lump strength index in MPa,
 D_{50} = standard size of lump (50 mm),
 D = distance between point loads in mm, and
 W = average width of minimum cross sectional area in mm.

(Page 6, clause 7.4, last line) — Delete 'This ----- only' and insert the following Note:

NOTE — The correlations in 7.2 and 7.4 are approximate for the purpose of classification of rock masses and valid for mainly unweathered and isotropic rocks.

(CED 48)