

AMENDMENT NO. 1 MARCH 1999
TO
IS 8783 (PART 4/SEC 1) : 1995 WINDING WIRES FOR
SUBMERSIBLE MOTORS — SPECIFICATION
PART 4 SPECIFICATION FOR INDIVIDUAL WIRES

Section 1 HR PVC Insulated Wires

(First Revision)

(Page 1, clause 5) — Substitute 'spools/reels/coils' for 'spools/reels'.

[Page 2, clause 6, Sl No. (d)] — Substitute the following for the existing:

'd) Length of conductor on spool/reel/coil.'

[Page 2, clause 6, Sl No. (e)] — Substitute the following for the existing:

'e) Number of lengths on spool/reel/coil (if more than one).

(Page 3, Table 2, col 2, unit) — Substitute 'No./mm' for 'No. mm'.

(Page 3, Table 2, col 4) — Substitute '0.60' for '0.70' as the minimum thickness of insulation for the conductors of nominal cross sectional area 9.08, 10.00, 12.09 and 13.18.

(Page 3, Table 2, col 5) — Substitute '7.90' for '7.80' and '8.60' for '8.50' for the values of overall diameter, maximum, corresponding to nominal cross sectional area of conductors 21.30 and 25.50.

(ETD 33)