



AMENDMENT NO. 1 JANUARY 1984

TO

IS : 8901 - 1978 SPECIFICATION FOR LAMPS FOR AERODROME LIGHTING FITTINGS

Alterations

(Page 6, Table 1, col 7) — Substitute the following for the existing column:

RATED LUMENS

Min

(7)

360

650

620

1 050

1 260

2 100

4 400

4 200

4 300

4 300

(Page 6, Table 1, Note 2, line 2) — Substitute 'rated lumen values' for average lumen values '.

(Page 7, clause 4.3.1) — Substitute the following for the existing clause:

'4.3.1 Average life shall not be less than the life stated in Table 1. However, it shall be subject to an allowance of 9 percent to take into account the relatively small size of the samples taken for life test.'

(Page 7, foot-note with '*' mark) — Delete.

(Page 8, clause 6.2, 6.3 and 6.4) — Substitute the following for the existing clauses:

'6.2 Inspection Test Quantity (ITQ) — Inspection test quantity shall be as follows:

- | | |
|--|----|
| a) Normal for batch size up to and including 5 000 lamps | 35 |
| b) Special for batch size exceeding 5 000 lamps | 70 |

6.3 Rating Test Quantity (RTQ) — From the lamps which have passed the inspection test, there shall be selected at random a RTQ as follows:

- | | |
|--|----|
| a) Normal for batch size up to and including 5 000 lamps | 25 |
| b) Special for batch size exceeding 5 000 lamps | 50 |

6.4 Life Test Quantity (LTQ) — Form the lamps which have passed the rating test quantity, there shall be selected at random a life test quantity of 20 lamps both for normal as well as for special batch size.'

(Page 10, clauses 8.2 and 8.3) — Substitute the following for the existing clauses:

'8.2 Mechanical and Physical Requirements and Marking — All the lamps chosen for ITQ as prescribed in 4.2 shall be tested for mechanical, physical and marking requirements (see 4.1 and 5).

A batch shall be considered to comply with the requirements of this clause if the number of lamps failing does not exceed:

- a) For normal batch having ITQ of 35 lamps:
 - i) 3 for any one of the test (4.1.1 to 4.1.3 and 5), and
 - ii) 7 for all the tests.
- b) For special batch having ITQ of 70 lamps:
 - i) 5 for any one of the tests (4.1.1 to 4.1.3 and 5), and
 - ii) 12 for all the tests (4.1.1 to 4.1.3 and 5).

8.3 Initial Ratings — All the lamps chosen for RTQ shall be tested for initial wattage and lumen. A batch shall be considered to comply with the requirements of initial ratings if;

- a) For a normal batch having RTQ of 25 lamps:
 - i) the number of lamps where initial wattage is above the maximum values specified in Table 1, does not exceed 4; and
 - ii) the number of lamps where lumen values are below the minimum values specified in Table 1, does not exceed 4.
- b) For a special batch having RTQ of 50 lamps:
 - i) the number of lamps whose lumen values are below the maximum value specified in Table 1, does not exceed 6; and

- ii) the number of lamps whose lumen values are below the minimum values specified in Table 1, does not exceed 6.

[Page 10, clause **8.4(b)**] — Substitute the following for **8.4(b)**:

- 'b) The number of lamps failing in respect of individual life and lumens of individual lamps at 50 percent of the nominal rated life does not exceed 5.'

(ETDC 23)