

AMENDMENT NO. 1 MAY 2003
TO
IS 6092 (Part 1) : 1985 METHODS OF SAMPLING AND
TEST FOR FERTILIZERS

PART 1 SAMPLING

(First Revision)

(Page 4, clause 2.1.3) — Insert a new clause after 2.1.3 and renumber the subsequent clauses:

2.1.4 In case of high density polyethylene packing and also when the fertilizer material is not in free flowing condition, the use of sampling probe may not be possible. In such a case, selected bags for drawing samples may be opened and the fertilizers may be taken out of the bags and spread on a clean surface and samples drawn with the help of a suitable sampling device which may be made of stainless steel or brass cup.

(Page 6, clause 3.1.3.3) — Insert a new clause after 3.1.3.3:

3.1.4 In case of chelated micro-nutrients and mixtures of micro-nutrients, the three identical containers of the batch, grade, type and manufacturer, shall be selected which shall constitute the composite samples, provided it is not possible to draw a composite sample of the size given below:

Weight of one sample — One sample of fertilizer shall have the approximate weight, as specified below:

i)	For straight micro-nutrient fertilizers	— 100 g
ii)	For chelated micro-nutrient fertilizers and mixture of micro-nutrients	50 g or the maximum packing size of similar quantity
iii)	For other fertilizers and mixtures of fertilizers	400 g

Amend No. 1 to IS 6092 (Part 1) : 1985

(Page 7, Table 1) — Substitute the following Table 1 for the existing:

**Table 1 Number of Containers or Packages to be Selected for Sampling
(Clause 3.1.3.2)**

Lot Size <i>N</i>	No. of Bags Selected for Sampling <i>n</i>
Less than 10	1
10 to 100	2
101 - 200	3
201 - 400	4
401 - 600	5
601 - 800	6
801 - 1 000	7
1 001 - 1 300	8
1 301 - 1 600	9
1 601 - 2 000	10

(Page 12, clause 3.4.1.3) — Insert following new clauses after clause 3.4.1.3:

3.5 Sampling from Big Godown/High Stacking

If the procedure given in 3.1.3.2 is not possible to be adopted, the sample should be drawn from the randomly selected fertilizer bags from different layers, from top and from all open sides in a zig zag fashion.

3.6 Sampling from Small Godown

All the fertilizer bags of the same grade and type of each manufacturer though received on different dates shall be segregated and properly stacked. All bags of the same grade and type of fertilizer manufactured by a particular manufacturing unit may be considered as one lot based on their physical conditions and the sample shall be drawn as per procedure laid down in clauses 3.1.2, 3.1.3.2, 3.1.4 and 3.7.

3.7 Sampling from Damaged Stock

- In case of torn or lumpy bags, damaged fertilizer bags or sweepings, the stock should be arranged according to identifiable lots. From each lot the number of bags shall be selected as per procedure in Table 1. If the bags allow the use of sampling probe conveniently, the samples should be drawn by sampling probe.
- In case it is not possible to use the sampling probe, the bags may be opened and fertilizer material mixed together uniformly by hammering the big lumps or putting pressure, if required, and then samples drawn by using

(PCD 20)