



AMENDMENT NO. 4 JANUARY 1984

TO

IS : 6162 (Part II) - 1971 SPECIFICATION FOR PAPER-COVERED ALUMINIUM CONDUCTORS

PART II RECTANGULAR CONDUCTORS

Addenda

(Page 9, clause 9.13, Note) — Add the following new clauses after 9.1.3 (Note):

'10. SAMPLING

10.1 A recommendatory sampling plan and criteria for acceptance of lot are given in Appendix F.

10.2 Acceptance Tests — The following tests shall constitute acceptance tests:

- a) Conductor dimensions (see 4),
- b) Arrangement of paper layers (see 6.3),
- c) Increase in dimension (see 7.1), and
- d) Overall dimension (see 7.3).'

(Page 17, Fig. 3) — Add the following new Appendix after Fig. 3:

A P P E N D I X F

(Clause 10.1)

SAMPLING OF PAPER-COVERED ROUND ALUMINIUM CONDUCTORS

F-1. SCALE OF SAMPLING

F-1.1 Let — In a consignment, all the drums of paper covered round aluminium conductors of the same grade and size manufactured from the same material in the same factory under similar conditions of production shall be grouped together to constitute a lot.

F-1.2 The number of drums to be selected from each lot shall depend upon the size of the lot and shall be in accordance with col 1 and 2 of Table 3.

TABLE 3 SAMPLE SIZE AND ACCEPTANCE NUMBER

(Clauses F-1.2 and F-2.1)

LOTE SIZE	SAMPLE SIZE	ACCEPTANCE NUMBER
(1)	(2)	(3)
Up to 50	8	0
51 „ 100	13	0
101 „ 300	20	1
301 „ 500	32	2
501 and above	50	3

F-1.2.1 These drums shall be selected from the lot at random. In order to ensure the randomness of selection, procedure given in IS : 4905-1968* may be followed.

F-2. NUMBER OF TESTS AND CRITERIA FOR CONFORMITY

F-2.1 From each of the drums selected at random according to col 1 and 2 of Table 5, suitable lengths of test samples shall be taken after discarding approximately 1.5 metre of the wire. The number of tests to be carried out for each of the acceptance tests shall be in accordance with col 1 and 2 of Table 6. For this purpose suitable number of test samples shall be taken from each of the selected drums and subjected to the tests. A sample failing to satisfy any of the acceptance tests shall be considered as defective. The lot shall be considered as conforming to the requirements of acceptance tests if the number of defectives found in the sample is less than or equal to the corresponding acceptance number given in col 3 of Table 5, otherwise the lot shall be rejected.'

*Methods for random sampling.

(ETDC 33)