

AMENDMENT NO. 1 JUNE 2024
TO
IS 17191 (Part 1) : 2019 ELECTRIC POWER TRAIN VEHICLES
PART 1 MEASUREMENT OF ELECTRICAL ENERGY CONSUMPTION

(Page 1, clause 2) — Substitute the following for the existing clause:

‘2 REFERENCES

The standards given below contain provisions, which through reference in this text, constitute provisions of this standard. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this standard are encouraged to investigate the possibility of applying the most recent edition of these standards:

<i>IS No.</i>	<i>Title</i>
IS 14272 : 2011	Automotive vehicles — Types —Terminology
IS 17191 (Part 3) : 2019	Electric power train vehicles: Part 3 Measurement of net power and the maximum 30 minute power.’

(Page 2, clause 3.35) — Substitute the following for the existing clause:

‘3.35 Net Power — The power obtained on a test bench at the end of the crank shaft or its equivalent at the corresponding motor speed with the auxiliaries listed in IS 17191 (Part 3) and determined under reference atmospheric condition.’

(Page 4, clause 4.5.1) — Substitute the following for the existing clause:

‘4.5.1 Discharge of the Rechargeable Energy Storage System (REESS)

The procedure starts with the discharge of the battery of the vehicle while driving (on the test track, on a chassis dynamometer etc at a steady speed of 70 percent $\pm$ 5 percent of the maximum thirty minutes speed of the vehicle. Stopping the discharge occurs:

- a) When the vehicle is not able to run at 65 percent of the maximum thirty minutes speed ; or
- b) When an indication to stop the vehicle is given to the driver by the standard on-board instrumentation;
or
- c) After covering the distance of 100 km.’

(Page 5, clause 6.4.1) — Substitute the following for the existing clause:

‘6.4.1 The end of charging t_0 (plug off) is reported.’

(Page 5, clause 6.4.2) — Substitute the following for the existing clause:

‘6.4.2 The chassis dynamometer shall be set as per the settings given in 6.2 Starting within 4 h from t_0 , 34 cycles of IDC (of 108 s duration each) or 22 cycles of part 1 of MIDC (of 195 s duration each) or 1 cycle of delhi driving cycle as applicable (*see* 6.1.1 or 6.1.2) are run. At the end, the covered distance (D), in km is recorded.’

Amendment No. 1 to IS 1791 (Part 1) : 2009

(Page 5, clause 6.4.3) — Substitute the following for the existing clause:

‘6.4.3 Charge of the Rechargeable Energy Storage System (REESS)

The vehicle shall be connected to the mains within 30 min after the conclusion of the driving cycle. The vehicle shall be charged according to normal overnight charge procedure (*see 4.5.2.1*). The energy measurement equipment, placed between the mains socket and the vehicle charger, measures the charge energy E delivered from the mains as well as its duration. Charging is stopped after 24 h from the previous end of charging time t_0 .

NOTE — In case of any power disruptions during charging, the 24 h period shall be exceeded according to the disruption duration. The maximum total power disruption of 30 min duration is allowed irrespective of the number of failures. Validity of the charge shall be discussed between the test agency and the vehicle manufacturer.’

(TED 27)

Publication, BIS, New Delhi