

AMENDMENT NO. 1 JANUARY 2026
TO
IS 17270 : 2019 INTELLIGENT TRANSPORT SYSTEMS (ITS) : REVERSE
PARKING ALERT SYSTEM (RPAS)

(Page 1, clause 1.2) — Substitute the following for the existing:

‘**1.2** The requirements of vehicle reverse parking alert system of this standard shall be applicable to all M and N category vehicles, as defined in IS 14272.’

(Page 2, clause 4.17) — Insert the following at the end:

‘4.18 Sensor Height

Height of the centre of the sensor mounted at the rear side of the vehicle above the ground.’

(Page 2, clause 6.2) — Substitute following for the existing:

‘**6.2** Reverse parking alert requirements for vehicles of category other than M1 category.

6.2.1 Vehicle reverse parking alert fitted on vehicles of categories other than M1 shall meet the requirements given in Annex B.

6.2.2 Wherever the rear end construction of vehicle is such that it is not possible to comply with the requirements of Annex B, it shall be permissible for vehicles of category other than M1 to comply with the requirements of Annex A after providing sufficient justification to the test agency.

Further, it shall be permissible to provide an audible warning system which is activated when the vehicle is driven in reverse, as an alternative to the reverse parking alert system, on fully-built or incomplete tippers. Further this alternative shall be also permissible for other fully built or incomplete vehicles such as ready-mix concrete (RMC) mixer trucks whose special function is incompatible with the use of reverse parking alert system.

6.2.3 Tractors including puller tractors of N category shall be exempted from the requirements of both Annex A and Annex B.’

(Page 3, clause 6.3) — Substitute the following for the existing:

‘**6.3** Component level validation requirements shall meet requirements of Annex C.

Additionally, manufacturer may need to submit data which may be relevant to application for approval, for example frame height or sensor height when seeking exemption.’

(Page 8, clause B-1.6) — Substitute the following for the existing:

‘**B-1.6** Incomplete vehicles shall also be equipped with reverse park assist system. Where the cabin build level of the incomplete vehicles prevents the fitment of the reverse park assist system, the vehicle manufacturer shall provide these items as a type approved kit along with the vehicle and accompanied with suitable guidelines to facilitate the body builder in installing the items.’

Price Group 2

Amendment No. 1 to IS 17270 : 2019

(Page 8, clause **B-2.5.3**) — Substitute following for the existing:

‘B-2.5.3 In case of vehicles where the frame height does not exceed 800 mm, the test at 1 100 mm level shall not be performed and in case of vehicles where the frame height exceeds 800 mm, the test at 500 mm level shall not be performed. Frame height shall be measured up to the topmost point of the frame from ground.

Alternatively, the request of the manufacturer, in case of vehicles where RPAS sensors are mounted on any part on the rear side of the vehicle other than frame, the manufacturer shall have the choice to apply these conditions based on ‘sensor height’ (as defined in **4.18**) instead of ‘frame height’, without compromising monitoring ranges.’

(Page 11, clause **C-1.5**) — Substitute the following for the existing:

‘C-1.5 Salt Spray Test

The salt spray test is conducted to check corrosion resistance of device. The device shall be tested according to **4.8** of IS 10250 for 96 h.

Acceptance Criteria: The device shall meet functional class A.

NOTE — This test shall not be applicable for interior fitments (parts fitted/placed within the OEM-built cabin), while it will remain mandatory for all exterior fitments.’

(Page 11, clause **C-1.6**) — Substitute the following for the existing:

‘C-1.6 High Voltage Test

The test is conducted to ensure service life requirements and functionality. The device under test shall be operated for 60 min at manufacturer suggested voltage as per design considerations. This test is as per ISO 16750-2.

Acceptance Criteria: Device during and after the test the device shall meet functional class A.’

(Page 11, clause **C-2.3**) — Substitute the following for the existing:

‘C-2.3 Ingress Protection (IP)

The device must be able to work in dusty environment that are typically encountered by the vehicles where these would be installed. IP rating (IS/IEC 60529 : 2001) is used for specifying the environmental protection characteristics of the device.

The device shall be tested for dust and water ingress as per following requirement:

IP	Dust	Water
For exterior parts	6	7
For internal parts	4	2
NOTE — During component level approval, supplier should declare the fitment of part in vehicle as internal or exterior part. For parts fitted/placed inside cabin (that is, internal parts), IP 42 is acceptable.		

Acceptance Criteria: The device shall meet functional class A.’

(Page 12, clause **C-2.4**) — Substitute the following for the existing:

‘C-2.4 EMI/EMC Test

The electromagnetic interference (EMI) and electromagnetic compatibility (EMC) tests are performed to assess whether the device performs its intended functions in the electromagnetic environment to which it would be exposed. Further, the device shall not generate electromagnetic disturbances that may influence other equipment in the vicinity.

Acceptance Criteria: The device shall meet the EMI/EMC requirements as per AIS 004 (Part 3).

NOTE — Vehicle level compliance with AIS 004 (Part 3) can be used as an alternative to the EMI/EMC test outlined in **C-2.4**.’

(Page 12, clause **C-2.6**) — Substitute the following for the existing:

‘C-2.6 Load Dump Test Pulse 5a

As per standard ISO 7637-2 : 2004:

- a) For 12 V System — A voltage spike of 65 V, 4 Ω , 200 ms; and
- b) For 24 V System — A voltage spike of 123 V, 8 Ω , 200 ms.

NOTE — Load dump test pulse 5a is not applicable if the system is equipped with centralised suppressor. Pulse 5b will be applicable for system equipped with centralised suppressor in line with ISO 16750-2.

Acceptance Criteria: Device shall meet functional class A.’

[Page 13, clause **C-4**, *Sl No.* (e)] — Substitute the following for the existing:

- e) Load dump test (pulse 5a) or (pulse 5b); and’.

[Page 13, Table 3, *Sl No.* (iii), *col* (2)] — Substitute the following for the existing:

‘Load dump test, pulse 5a or pulse 5b’.