

AMENDMENT NO. 1 SEPTEMBER 2021

TO

**IS 17427 : 2020 WOODEN (TIMBER) PALLETS FOR
PACKAGING, STORAGE AND TRANSPORTATION —
SPECIFICATION**

[*National Foreword, Para 5*] — add following:

<i>‘International Standard</i>	<i>Title</i>
ISO 8611-1 : 2011	Pallets for materials handling — flat pallets — Part 1: Test methods
ISO 8611-2 : 2011	Pallets for materials handling — flat pallets — Part 2: Performance requirements and selection of tests
ISO 8611-3 : 2011	Pallets for materials handling — flat pallets — Part 3: Maximum working loads’

[*Page 1, clause 2*] — Delete IS 13609 : 1992 Pallets-quality of timber —
Guideline

[*Page 1, clause 3.2 (a)*] — Replace ‘Non-Expandable’ with ‘Non-
Expendable’.

[*Page 1, clause 3.3 (a)*] — Replace ‘Expandable’ with ‘Expendable’.

[*Page 1, clause 3.6*] — Replace ‘Expandable’ with ‘Expendable’.

[*Page 2, clause 3.9*] — Replace ‘springers’ with ‘stringers’.

[*Page 2, clause 4.1 (a)*] — Replace ‘Decks — the top and bottom planks on
both surfaces of the pallet

[Page 2, clause 4.1 (b)] — Replace ‘Expandable’ with ‘Expendable’.

(Page 2, clause 5.2) — Replace ‘Non-Expandable’ with ‘Non-Expendable’.

(Page 2, clause 5.2) — Replace ‘Expandable’ with ‘Expendable’.

(Page 2, clause 6) — Replace ‘Non-Expandable’ with ‘Non-Expendable’.

(Page 2, clause 6) — Replace ‘Expandable’ with ‘Expendable’.

(Page 4, clause 6.2) — Replace ‘Expandable’ with ‘Expendable’.

(Page 4, clause 6.3) — Replace ‘Expandable’ with ‘Expendable’.

(Page 5, clause 6.4) — Replace ‘Non-Expandable’ with ‘Non-Expendable’.

(Page 8, clause 10) — Replace ‘Non-Expandable’ with ‘Non-Expendable’.

(Page 8, clause 10) — Replace ‘Expandable’ with ‘Expendable’.

(Page 8, clause 10.2) — Replace ‘Non-Expandable’ with ‘Non-Expendable’.

(Page 8, clause 10.2) — Replace ‘Expandable’ with ‘Expendable’.

(Page 2, clause 4.1) — Delete c) Box Pallet and d) Dunnage Pallet

[Page 11, Inclined Impact Plane Test (Shear Test), Performance Requirement] — Add-

‘After 3 impacts the increase of s at any point on the leading edges shall be 6 mm maximum. The mean increase of y shall be 4 mm maximum.’

[Page 11, Inclined Plane Test (Leading Edge Impact Test), Performance Requirement] — Add- After 3 impacts the mean increase each of x and y shall be 3 mm maximum.

[Page 11, Inclined Plane Test (Block Impact Test), Performance Requirement] — Add-

‘After 3 impacts the mean each of x (combined measurement of block displacement plus indentation depth), y and z shall be 3 mm maximum.’

[Page 12, Compression Test, Performance Requirement] — Replace-
‘Deformation of pallet with respect to ultimate load shall be 4mm under load and 1.5 mm after relaxation period.’

[Page 12, Fork Lifting Test, Performance Requirement] — Replace
‘Deflection “y” on pallet not exceeding 2% of distance between two supports, whichever is less.’