

AMENDMENT NO. 2 JULY 2024

TO

IS 17483 (PART 2) : 2020 GEOSYNTHETICS — GEOCELLS — SPECIFICATION

PART 2 SLOPE EROSION PROTECTION APPLICATION

[Page 1, clause 3.2, (see also Amendment No. 1)] — Substitute the following for the existing:

‘3.2 Style Number — A theoretical numerical identifier assigned to geocells, indicating their distinct design characteristics in terms of weld spacing (mm) and cell depth (mm). For instance, ‘a × b’ type geocell refers a geocell having weld spacing of 'a' mm and a cell depth of 'b' mm.’

[Page 1, clause 5.2, (see also Amendment No. 1)] — Substitute the following for the existing:

‘5.2 Geocells used for slope erosion protection application shall have a depth ranging from 75 mm to 125 mm (see Note) and weld spacing ranging from 445 mm to 712 mm. The expanded individual geocell and geocell panel are shown in Fig. 2 (a) and Fig. 2 (b) respectively for illustration. The following tolerance shall be permissible for depth and weld spacing:

<i>Sl No.</i>	<i>Dimension</i>	<i>Tolerance, Percent</i>
(1)	(2)	(3)
i)	Depth	$\left\{ \begin{array}{c} +3 \\ -2 \end{array} \right\}$
ii)	Weld spacing	$\left\{ \begin{array}{c} +3 \\ -3 \end{array} \right\}$

NOTE — In specific cases, geocells with 150 mm depth may also be used.’

[Page 1, Fig. 2 (c), (see also Amendment No. 1)] — Delete.