

AMENDMENT NO. 1 MAY 1984
TO
IS:10250-1982 SPECIFICATION FOR SEVERITIES FOR
ENVIRONMENTAL TESTS FOR AUTOMOTIVE
ELECTRICAL EQUIPMENT
Alterations

(Page 11, clause 4.12) - Substitute the following for the existing clause:

"4.12 Impact or Shock Test

4.12.0 This test is intended to determine the suitability of the equipment when mounted on vehicle and subjected to shocks as a result of suddenly applied forces or abrupt changes in motion.

4.12.1 The test shall be conducted for all the three groups as specified in IS:9000(Part 7/Sec 1)-1979 'Basic environmental testing procedures for electronic and electrical items: Part 7 Impact test, Section 1 Shock.'

4.12.2 Any one of the following severities shall be selected for the test depending on the location of the equipment and the vehicle to which it is intended:

5 g, 10 g, 15 g and 20 g.

4.12.3 Method of mounting and other details shall be as specified in relevant equipment specification. Components mounted on mounting brackets during normal operation shall be tested along with them."

(Page 11, clause 4.14) - Substitute the following for the existing clause:

"4.14 Simulated Solar Radiation Test

4.14.0 This test is intended to determine the effects (thermal mechanical, chemical, electrical, etc) produced on equipment as a result of exposure to solar radiation under conditions experienced on the surface of earth.

4.14.1 Any one of the following methods shall be selected for the test:

4.14.1.1 The equipment shall be mounted in the manner in which it is mounted on the vehicle exposing only parts which are normally exposed under actual working conditions and subjected to an exposure to direct sun light for a period of 90 days.

4.14.1.2 The equipment shall be exposed to the action of ultra violet light in a fadeometer as specified in IS:101-1964 'Methods of test for ready mixed paints and enamels (*second revision*)'. The period of exposure shall be 24 hours.

4.14.2 The test shall be applicable to group 2 and 3 equipment only."

(ETDC 14)