



AMENDMENT NO. 1 JANUARY 1984

TO

**IS : 9106 -1979 SPECIFICATION FOR
RISING BUTT HINGES**

Alterations

(Page 4, clause 4.1, line 2) — Substitute 'Tables 2 to 5' for 'Tables 2 to 4'.

(Page 9, clause 5.1, line 2) — Substitute 'Tables 2 to 5' for 'Tables 2 to 4'.

(Page 9, clause 5.4.2, line 2) — Substitute 'Tables 2 to 5' for 'Tables 2 to 4'.

Addenda

(Page 4, clause 2.1) — Add the following new matter at the end of 2.1:

'Type

Material

4

Extruded aluminium'

(Page 4, Table 1) — Add the following new matter after the second entry:

PART	MATERIAL	SUITABLE GRADE IN INDIAN STANDARD
(1)	(2)	(3)
Flap	Extruded aluminium sections	65032 WP or 63400 WP of IS : 733-1975**
Pin	Aluminium alloy	65032 WP or 63400 WP of IS : 733-1975**

(Page 4, Table 1, foot-note with '||' mark) — Add the following new foot-note after the existing foot-note:

'***Specification for wrought aluminium and aluminium alloy bars, rods and sections (for general engineering purposes) (second revision).'

(Page 5, Table 4) — Add the following new Table 5 after Table 4 and renumber the subsequent tables accordingly:

TABLE 5 DIMENSIONS OF ALUMINIUM RISING BUTT HINGES

(Clause 4.1)

All dimensions in millimetres.

SIZE OF HINGE	LENGTH OF JOINT	OPEN WIDTH OVER FLAPS B	DIA OF PIN C Min	THICK- NESS OF FLAP D Min	RISE OF FLAP WHEN OPEN 90°	RISE OF FLAP WHEN OPEN 180°	HOLES FOR SCREW DESIG- NATION	No. OF SCREW HOLES
(1)	(2)	(3)	(4)	(5)	(6)	(7)	(8)	(9)
75	75	60	7.1	4	6	12	10	6
100	100	65	7.9	4	6	12	10	8
100	100	75	9.5	4.7	6	12	12	8
125	125	100	9.5	6.7	6	12	12	8

NOTE — These hinges are handed and it is essential that purchasers indicate when ordering whether left hand or right hand hinges are required.

[Page 9, renunber Table 6, Sl No. iii)] — Add the following new tolerances after Sl No. iii):

SL No.	TYPE	LENGTH OF JOINT A	OPEN WIDTH OVER FLAPS B	DIA OF PIN C	THICK- NESS OF FLAP D	RISE OF FLAP WHEN OPEN 90°	RISE OF FLAP WHEN OPEN 180°
iv)	Aluminium alloy	± 0.5 mm	± 1 mm	—	—	± 0.5 mm	± 0.5 mm

(Page 10, clause 6.3) — Add the following new matter at the end of 6.3:

‘Aluminium alloy hinges shall be anodized and the quality of anodized finish shall not be less than Grade AC 10 of IS : 1868-1968*.’

(Page 10, clause 7.1.1, Note) — Add the following new foot-note after 7.1.1 Note:

“*Specification for anodic coating on aluminium (first revision)”.

(BDC 15)