

AMENDMENT NO. 2 MARCH 1989
TO
IS : 9206 - 1979 DIMENSIONS OF CAPS
FOR TUNGSTEN FILAMENT GENERAL
SERVICE ELECTRIC LAMPS

[*Page 4, clause 2.2 (see also Amendment No. 1)*] — Add the following new clauses after 2.2:

3. INSULATION RESISTANCE OF THE CAPS

3.1 The insulation resistance measured between the contacts and each of the contacts and shell of the cap shall be not less than 50 megohms. Insulation resistance shall be measured with 500 V dc applied for a period of one minute.

3.2 If the insulation resistance value is below the requirements of 3.1, then the caps shall be stored in a warm dry atmosphere for 24 hours and then retested for insulation.

4. MARKING

4.1 The caps may also be marked with the Standard Mark.

NOTE — The use of the Standard Mark is governed by the provisions of the Bureau of Indian Standards Act 1986 and the Rules and Regulations made thereunder. The Standard Mark on products covered by an Indian Standard conveys the assurance that they have been produced to comply with the requirements of that standard under a well defined system of inspection, testing and quality control which is devised and supervised by BIS and operated by the producer. Standard marked products are also continuously checked by BIS for conformity to that standard as a further safeguard. Details of conditions under which a licence for the use of the Standard Mark may be granted to manufacturers or producers may be obtained from the Bureau of Indian Standards.'

(ETDC 23)