

AMENDMENT NO. 1 APRIL 2026
TO
IS 9283 : 2024 LINE OPERATED a.c. MOTORS FOR SUBMERSIBLE PUMPSETS —
SPECIFICATION
(Third Revision)

(Page 1, clause 5.1.3) — Substitute the following for the existing:

‘The rotor of the wet type submersible motor shall be provided with suitable coating or any suitable arrangement to protect it from corrosion under water.’

(Page 7, clause 6.2, 6.2.1, 6.2.2) — Substitute the following for the both existing **6.2.1** and **6.2.2**:

‘The motors shall be capable to operate in the following range of voltage and supply frequency:

- a) The terminal voltage differing from this rated value by not more + 6 percent and – 15 percent;
- b) The frequency differing from its rated value by not more than ± 3 percent; and
- c) Any combination of above.’

(Page 8, clause 12.3) — Substitute the following for the existing:

‘The nominal values of performance are specified in Table 2 to Table 11.’

(Page 26, clause 15.1) — Insert the following after (r):

‘s) Capacitor rating.’

[Page 26, clause 15.1, (p)] — Substitute the following for the existing:

‘Bore size, in mm;’

(Page 26, clause 16.3) — Substitute ‘may’ for ‘shall’.

(Page 27, clause 19.1) — Delete Note.