

AMENDMENT NO. 1 AUGUST 2024
TO
IS 398 (PART 6) : 2021 ALUMINIUM CONDUCTORS FOR OVERHEAD
TRANSMISSION PURPOSES
PART 6 HIGH CONDUCTIVITY ALUMINIUM ALLOY STRANDED
CONDUCTORS — SPECIFICATION

(Page 2, Table 2) — Insert the following high conductivity aluminum alloy wires:

Diameter			Cross sectional area of nominal wire diameter mm ²	Mass kg/km	Minimum Breaking Load		Resistance at 20 °C Ω/km
Nom mm	Min mm	Max mm			Before Stranding kN	After Stranding kN	
(1)	(2)	(3)	(4)	(5)	(6)	(7)	(8)
4.17	4.13	4.21	13.657	36.874	3.14	2.98	2.127
4.36	4.32	4.40	14.930	40.311	3.43	3.26	1.946

(Page 3, Table 3) — Insert the following high conductivity aluminum alloy stranded conductors:

Sl No.	Actual Area mm ²	Stranding and Wire Diametre mm	Approx Overall Diametre mm	Approx Mass kg/ km	Calculated Maximum Resistance at 20 °C Ω/km	Approx Calculated UTS kN
(1)	(2)	(3)	(4)	(5)	(6)	(7)
18	833	61/4.17	37.53	2299.10	0.0356	182.0
19	911	61/4.36	39.24	2513.40	0.0326	199.0

(ETD 37)

Price Group 1

Publication, BIS, New Delhi