

AMENDMENT NO. 1 JUNE 1978
TO
IS : 417 (Part VI)-1976 SPECIFICATION FOR FOOTBALLS, VOLLEYBALLS,
BASKETBALLS, NETBALLS, THROWBALLS AND WATER-POLO BALLS

PART VI WATER-POLO BALLS

(Third Revision)

Alterations

(Page 1, clause 2.1, lines 1 and 2) — Delete the words 'and the other characteristics shall be as specified in Fig. 1 '.

(Page 1, Fig. 1) — Delete.

(Page 2, clause 3.1) — Substitute the following for the existing clause:

'3.1 Leather — The balls shall be manufactured from butt portion of tight-textured cowhide or buffalohide, free from flay cuts and grain defects, vegetable/semi-chrome or chrome tanned, dyed in any colour or pigmented as agreed to between the purchaser and the supplier. At the end of tanning operation, and before drying, suitable fungicides shall be incorporated into the leather for promoting resistance to mould growth in the leather, these shall be effective and non-toxic. The tanned leather shall be substantially fat-liquored or oiled or both and the surface obtained shall be smooth and well set.'

(Page 2, clause 4.2) — Substitute the following for the existing clause:

'4.2 Stitching — The ball shall be stitched with linen thread and shall have 24 ± 2 stitches per decimetre. The stitches shall be well stretched. When the ball is fully inflated, the visible threads shall be not more than 2 mm deep from the surface of the ball. The panels for water-polo balls should preferably be cut with self-cutting-cum-perforating dies.'

(Page 2, clause 4.3, first sentence) — Delete.

Addendum

(Page 1, clause 2.1) — Add the following new clause after 2.1:

'2.1.1 A tolerance of 1 percent in the circumference on sphericity shall be allowed.'