

**AMENDMENT NO. 2 JUNE 2007**  
**TO**  
**IS 418 : 2004 TUNGSTEN FILAMENT LAMPS FOR DOMESTIC AND**  
**SIMILAR GENERAL LIGHTING PURPOSES**  
**(Fourth Revision)**

(Second cover, Foreword, para 5, last sentence) — Insert the following at the end:

"For the sake of convenience, the data sheet numbers as given in IEC 60064 have been followed except for 75 W ratings which are presently not covered in IEC Standard."

(Page 16, Annex G, row 7) — Insert the following new entries after row 7:

| Sheet No.   | Watts | Bulb                         | Cap        | Finish <sup>1)</sup> | Life, h | Luminous Flux <sup>2)</sup> |
|-------------|-------|------------------------------|------------|----------------------|---------|-----------------------------|
| 418-IS-6000 | 75    | A55, A60, K60, M60 and PS 60 | B22d/25×26 | C, F                 | 1 000   | N                           |
| 418-IS-6001 | 75    | A50, A60, K60, M60 and PS 60 | B22d/25×26 | C, F                 | 1 000   | H                           |

(Page 16, Annex G, row 20) — Insert the following new entries after row 20:

| Sheet No.   | Watts | Bulb                         | Cap    | Finish <sup>1)</sup> | Life, h | Luminous Flux <sup>2)</sup> |
|-------------|-------|------------------------------|--------|----------------------|---------|-----------------------------|
| 418-IS-6002 | 75    | A55, A60, K60, M60 and PS 60 | E27/27 | C, F                 | 1 000   | N                           |
| 418-IS-6003 | 75    | A55, A60, K60, M60 and PS 60 | E27/27 | C, F                 | 1 000   | H                           |

**Amend No. 2 to IS 418 : 2004**

(Page 26, Data Sheet 418-IS-4055-1) – Insert the following new 4 data sheets after this:

**NORMAL LUMINOUS FLUX  
INCANDESCENT LAMP DATA SHEET**

**B22**

**75 W**

**1 000 h**

Dimensions in millimeters.

Bulb designation: A55, A60, K60, M60 and PS60

Bulb finish: Frosted or Clear

Cap: B22d/25 × 26

Rated wattage ( W ): 75

Dimensions: as defined in **13**

For reference in the requirements of **7**

| <i>C, Max</i> | <i>D, Max</i> |
|---------------|---------------|
| 108.5         | 62            |

Rated life ( h ): 1 000

For reference in the requirements of **10**

Lumen maintenance ( % ): 85

Conditions of **9** apply

Minimum rated luminous flux:

Conditions of **8** apply

| V   | 1m    |
|-----|-------|
| 110 | 1 010 |
| 230 | 840   |
| 240 | 830   |
| 250 | 820   |

Information for luminaire design:

Maximum outline: under consideration

418-IS-6000-1

**HIGH LUMINOUS FLUX  
INCANDESCENT LAMP DATA SHEET**  
**B22                      75 W                      1 000h**  
Dimensions in millimetres.

Bulb designation: A55, A60, K60, M60 and PS60

Bulb finish: Frosted or Clear

Cap: B22d/25 × 26

Rated wattage ( W ): 75

Dimensions: as defined in **13**

For reference in the requirements of 7

|               |               |
|---------------|---------------|
| <i>C, Max</i> | <i>D, Max</i> |
| 108.5         | 62            |

Rated life ( h ): 1 000

For reference in the requirements of **10**

Lumen maintenance ( % ): 85

Conditions of **9** apply

Minimum rated luminous flux:

Conditions of **8** apply

|     |       |
|-----|-------|
| V   | 1m    |
| 110 | 1 090 |
| 230 | 940   |
| 240 | 930   |
| 250 | 920   |

Information for luminaire design:

Maximum outline: under consideration

**418-IS-6001-1**

**Amend No. 2 to IS 418 : 2004**

(Page 39, Data Sheet 418-IS-4055-1) — Insert the following new data sheets after this:

**NORMAL LUMINOUS FLUX  
INCANDESCENT LAMP DATA SHEET**  
**E27                      75 W                      1 000 h**

Dimensions in millimeters.

Bulb designation: A55, A60, K60, M60 and PS60

Bulb finish: Frosted or Clear

Cap: E27/27

Rated wattage ( W ): 75

Dimensions: as defined in 13

For reference in the requirements of 7

| <i>C, Max</i> | <i>D, Max</i> |
|---------------|---------------|
| 110           | 62            |

Rated life ( h ): 1 000

For reference in the requirements of 10

Lumen maintenance ( % ): 85

Conditions of 9 apply

Minimum rated luminous flux:

Conditions of 8 apply

| V   | 1m    |
|-----|-------|
| 110 | 1 010 |
| 230 | 840   |
| 240 | 830   |
| 250 | 820   |

Information for luminaire design:

Maximum outline: under consideration

**418-IS-6002-1**

**GH LUMINOUS FLUX  
INCANDESCENT LAMP DATA SHEET**  
**E27                      75 W                      1 000 h**

Dimensions in millimeters.

Bulb designation: A55, A60, K60, M60 and PS60

Bulb finish: Frosted or Clear

Cap: E27/27

Rated wattage ( W ): 75

Dimensions: as defined in 13

For reference in the requirements of 7

| <i>C, Max</i> | <i>D, Max</i> |
|---------------|---------------|
| 110           | 62            |

Rated life ( h ): 1 000

For reference in the requirements of 10

Lumen maintenance ( % ): 85

Conditions of 9 apply

Minimum rated luminous flux:

Conditions of 8 apply

| V   | lm    |
|-----|-------|
| 110 | 1 090 |
| 230 | 940   |
| 240 | 930   |
| 250 | 920   |

Information for luminaire design:

Maximum outline: under consideration

**418-IS-6003-1**

( ETD 23 )