ETSI TS 124 283 V19.3.0 (2026-09)



TECHNICAL SPECIFICATION

5G;
Mission Critical Location Management (MCLoc);
Protocol Specification
(3GPP TS 24.283 version 19.3.0 Release 19)

Reference
RTS/TSGC-0124283vj30

Keywords
5G

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from the
ETSI Search & Browse Standards application.

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format on ETSI deliver repository.

Users should be aware that the present document may be revised or have its status changed, this information is available in the Milestones listing.

If you find errors in the present document, please send your comments to the relevant service listed under Committee Support Staff.

If you find a security vulnerability in the present document, please report it through our Coordinated Vulnerability Disclosure (CVD) program.

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.
No recommendation as to products and services or vendors is made or should be implied.
No representation or warranty is made that this deliverable is technically accurate or sufficient or conforms to any law and/or governmental rule and/or regulation and further, no representation or warranty is made of merchantability or fitness for any particular purpose or against infringement of intellectual property rights.
In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part of this document may be reproduced in any form, by any means and in any media, without the prior written authorization of ETSI and except as expressly permitted below.
By way of exception and when the document is a normative deliverable (European Standard (EN), Technical Specification (TS), Group Specification (GS) or ETSI Standard (ES)), ETSI authorizes to reproduce and incorporate into products, services and technical documentation only those extracts (e.g. templates) that are strictly necessary for the technical implementation of the normative deliverable, to ensure compliance with the latter.
Nothing in this notice shall be construed as limiting any mandatory exceptions to copyright provided by applicable law.

© ETSI 2026.
All rights reserved.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables (European Standard (EN), Technical Specification (TS), Group Specification (GS) or ETSI Standard (ES)) may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI IPR online database.

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™**, **LTE™** and **5G™** logo are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM**® and the GSM logo are trademarks registered and owned by the GSM Association.

Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found at 3GPP to ETSI numbering cross-referencing.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the ETSI Drafting Rules (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights 2
Legal Notice 2
Modal verbs terminology 2
Foreword 8
1 Scope 10
2 References 10
3 Definitions of terms, symbols and abbreviations 11
3.1 Terms 11
3.2 Symbols 11
3.3 Abbreviations 11
4 General 11
4.1 Overview 11
4.2 LMS Registration 12
4.3 Identities 12
4.3.1 General 12
4.3.2 MCLOC client ID 13
5 Functional entities and reference points 13
5.1 Introduction 13
5.2 Location management service functional architecture 13
5.3 Functional entities 14
5.3.1 MCLoc client (LMC) 14
5.3.2 MCLoc server (LMS) 14
5.3.3 void 15
5.3.4 Configuration management server (CMS) 15
5.4 Reference points 15
5.4.1 void 15
5.4.2 Reference point CSC-14 (between the LMS and the LMC) 15
5.4.3 Reference point CSC-15 (between the LMS and the MC service server) 15
5.4.4 Reference point CSC-22 (between the LMS and another LMS) 15
5.4.5 Reference point CSC-24 (between the LMS and the configuration management server) 15
5.4.6 Reference point IWF-4 (between the LMS and the IWF) 15
5.4.7 Reference points HTTP-1, HTTP-2 and HTTP-3 15
6 Services offered by the location management server 16
6.1 Introduction 16
6.2 LMS_Reporting service 16
6.2.1 Service description 16
6.2.2 Service operations 17
6.2.2.1 Introduction 17
6.2.2.2 RegistrationRequest 17
6.2.2.2.1 General 17
6.2.2.2.2 LMC register to LMS using RegistrationRequest operation 17
6.2.2.3 RegistrationUpdate 18
6.2.2.3.1 General 18
6.2.2.3.2 LMC updating registration using RegistrationUpdate operation 18
6.2.2.4 RegistrationDelete 19
6.2.2.4.1 General 19
6.2.2.4.2 LMC deregistering using RegistrationDelete operation 19
6.2.2.5 ConfigurationNotify 20
6.2.2.5.1 General 20
6.2.2.5.2 LMS send configuration using ConfigurationNotify operation 20
6.2.2.6 ConfigurationRequest 20
6.2.2.6.1 General 20

6.2.2.6.2 LMC request the location configuration using ConfigurationRequest operation 21
6.2.2.7 LocationReport 21
6.2.2.7.1 General 21
6.2.2.7.2 LMS send location request using LocationReportRequest 21
6.2.2.8 LocationReportPublish 22
6.2.2.8.1 General 22
6.2.2.8.2 LMC reports to LMS using LocationReportPublish 22
6.3 LMS_Information service 23
6.3.1 Service description 23
6.3.2 Service operations 24
6.3.2.1 Introduction 24
6.3.2.2 LocationRequest 24
6.3.2.2.1 General 24
6.3.2.2.2 Client request location information to LMS using LocationRequest operation 24
6.3.2.3 LocationInfoSubscribe 26
6.3.2.3.1 General 26
6.3.2.3.2 Client request subscription using LocationInfoSubscribe operation 27
6.3.2.4 LocationInfoNotify 28
6.3.2.4.1 General 28
6.3.2.4.2 LMS Notify clients using LocationInfoNotify operation 28
6.3.2.5 LocationInfoSubscribeUpdate 29
6.3.2.5.1 General 29
6.3.2.5.2 Client requests update of subscription using LocationInfoSubscribeUpdate operation 29
6.3.2.6 LocationInfoSubscribeDelete 30
6.3.2.6.1 General 30
6.3.2.6.2 Client requests unsubscribe using LMS_LocationInfoSubscribeDelete operation 30
6.3.2.7 LocationInfoConfigRequest 31
6.3.2.7.1 General 31
6.3.2.7.2 Client request location configuration change for another client from LMS using LocationInfoConfigRequest operation 31

7 LMS API Definitions 32
7.1 LMS_Reporting API 32
7.1.1 Introduction 32
7.1.2 Usage of HTTP 32
7.1.2.1 General 32
7.1.2.2 HTTP standard headers 33
7.1.2.2.1 General 33
7.1.2.2.2 Content type 33
7.1.2.3 HTTP custom headers 33
7.1.3 Resources 33
7.1.3.1 Overview 33
7.1.3.2 Resource: LMC Registrations 34
7.1.3.2.1 Description 34
7.1.3.2.2 Resource Definition 34
7.1.3.2.3 Resource Standard Methods 34
7.1.3.2.4 Resource Custom Operations 35
7.1.3.3 Resource: Individual LMC registration 35
7.1.3.3.1 Description 35
7.1.3.3.2 Resource Definition 35
7.1.3.3.3 Resource Standard Methods 35
7.1.3.3.4 Resource Custom Operations 38
7.1.3.4 Resource: LMC Configurations 38
7.1.3.4.1 Description 38
7.1.3.4.2 Resource Definition 38
7.1.3.4.3 Resource Standard Methods 38
7.1.3.4.4 Resource Custom Operations 39
7.1.3.5 Resource: LMC Location Reports 39
7.1.3.5.1 Description 39
7.1.3.5.2 Resource Definition 39
7.1.3.5.3 Resource Standard Methods 39
7.1.3.5.4 Resource Custom Operations 40

7.1.4 Custom Operations without associated resources 40
7.1.5 Notifications 40
7.1.5.1 General 40
7.1.5.2 ConfigurationNotify notification 40
7.1.5.2.1 Description 40
7.1.5.2.2 Target URI 40
7.1.5.2.3 Standard Methods 41
7.1.5.3 LocationReportRequest notification 41
7.1.5.3.1 Description 41
7.1.5.3.2 Target URI 41
7.1.5.3.3 Standard Methods 41
7.1.6 Data Model 42
7.1.6.1 General 42
7.1.6.2 Structured data types 43
7.1.6.2.1 Introduction 43
7.1.6.2.2 Type: LMCRegistration 43
7.1.6.2.3 Type: LocationConfiguration 43
7.1.6.2.4 Type: TriggeringCriteria 44
7.1.6.2.5 Type: CellChange 44
7.1.6.2.6 Type: AnyCellChange 44
7.1.6.2.7 Type: SpecificCellChange 45
7.1.6.2.8 Type: EutranCell 45
7.1.6.2.9 Type: NrCell 45
7.1.6.2.10 Type: GeographicalAreaChange 45
7.1.6.2.11 Type: MbsfnAreaChange 46
7.1.6.2.12 Type: AnyMbsfnAreaChange 46
7.1.6.2.13 Type: SpecificMbsfnArea 46
7.1.6.2.14 Type: MbsfnAreaId 46
7.1.6.2.15 Type: MbmsSaChange 46
7.1.6.2.16 Type: AnyMbmsSaChange 47
7.1.6.2.17 Type: SpecificMbmsSaIdentity 47
7.1.6.2.18 Type: MbmsSaIdentity 47
7.1.6.2.19 Type: NR5GMbsfsaAreaChange 47
7.1.6.2.20 Type: AnyNR5GMbsfsaAreaChange 47
7.1.6.2.21 Type: SpecificNR5GMbsfsaArea 48
7.1.6.2.22 Type: NR5GMbsfsaAreaIdentity 48
7.1.6.2.23 Type: PeriodicReport 48
7.1.6.2.24 Type: PlmnChange 48
7.1.6.2.25 Type: AnyPlmnChange 48
7.1.6.2.26 Type: SpecificPlmnChange 49
7.1.6.2.27 Type: Plmn 49
7.1.6.2.28 Type: TrackingAreaChange 49
7.1.6.2.29 Type: AnyTrackingAreaChange 49
7.1.6.2.30 Type: SpecificTrackingAreaChange 49
7.1.6.2.31 Type: TrackingArea 50
7.1.6.2.32 Type: TravelledDistance 50
7.1.6.2.33 Type: RequestedLocationInfo 50
7.1.6.2.34 Type: AdaptiveTrigger 51
7.1.6.2.35 Void 53
7.1.6.2.36 Type: SpecificArea 53
7.1.6.2.37 Type: RatTypeChange 53
7.1.6.2.38 Type: AnyRatTypeChange 53
7.1.6.2.39 Void 54
7.1.6.2.40 Type: SignallingEvent 54
7.1.6.2.41 Type: FunctionalAliasActivation 54
7.1.6.2.42 Type: FunctionalAliasDeactivation 54
7.1.6.2.43 Type: InitialLogOn 54
7.1.6.2.44 Type: GroupCallNonEmergency 55
7.1.6.2.45 Type: PrivateCallNonEmergency 55
7.1.6.2.46 Type: LocationConfigurationReceived 55
7.1.6.2.47 Type: LocationRequest 55
7.1.6.2.48 Type: RequestLocationHistory 56

7.1.6.2.49 Type: MCUELocation 56
7.1.6.2.50 Type: LocationInfo 57
7.1.6.2.51 Type: CurrentCoordinate 57
7.1.6.2.52 Type: LocationHistoryData 57
7.1.6.2.53 Type: LocationHistoryEvent 58
7.1.6.2.54 Type: LocationHistoryStatus 58
7.1.6.3 Simple data types and enumerations 58
7.1.6.3.1 Introduction 58
7.1.6.3.2 Simple data types 58
7.1.6.3.3 Enumeration: ConfigScope 58
7.1.6.3.4 Enumeration: ReportType 59
7.1.6.3.5 Enumeration: InterRatType 59
7.1.7 Error Handling 59
7.1.7.1 General 59
7.1.7.2 Protocol Errors 59
7.1.7.3 Application Errors 59
7.1.8 Feature negotiation 60
7.1.9 Security 60
7.1.10 HTTP redirection 60
7.2 LMS_Information API 60
7.2.1 Introduction 60
7.2.2 Usage of HTTP 61
7.2.2.1 General 61
7.2.2.2 HTTP standard headers 61
7.2.2.2.1 General 61
7.2.2.2.2 Content type 61
7.2.2.3 HTTP custom headers 61
7.2.3 Resources 61
7.2.3.1 Overview 61
7.2.3.2 Resource: Client location information request 62
7.2.3.2.1 Description 62
7.2.3.2.2 Resource Definition 62
7.2.3.2.3 Resource Standard Methods 63
7.2.3.3.4 Resource Custom Operations 63
7.2.3.3 Resource: Location information subscriptions 63
7.2.3.3.1 Description 63
7.2.3.3.2 Resource Definition 63
7.2.3.3.3 Resource Standard Methods 64
7.2.3.4 Resource: Individual location information subscription 65
7.2.3.4.1 Description 65
7.2.3.4.2 Resource Definition 65
7.2.3.4.3 Resource Standard Methods 65
7.2.3.4.4 Resource Custom Operations 67
7.2.3.5 Resource: Location information config request 68
7.2.3.5.1 Description 68
7.2.3.5.2 Resource Definition 68
7.2.3.5.3 Resource Standard Methods 68
7.2.4 Custom Operations without associated resources 68
7.2.5 Notifications 69
7.2.5.1 General 69
7.2.5.2 Location information notification 69
7.2.5.2.1 Description 69
7.2.5.2.2 Target URI 69
7.2.5.2.3 Standard Methods 69
7.2.6 Data Model 69
7.2.6.1 General 69
7.2.6.2 Structured data types 70
7.2.6.2.1 Introduction 70
7.2.6.2.2 Type: ClientOriginatingLocationRequest 70
7.2.6.2.3 Type: MCUserLocation 70
7.2.6.2.4 Type: LocationNotification 71
7.2.6.2.5 Type: LocationSubscriptionRequest 71

7.2.6.3 Simple data types and enumerations 71
7.2.7 Error Handling 71
7.2.7.1 General 71
7.2.7.2 Protocol Errors 71
7.2.7.3 Application Errors 71
7.2.8 Feature negotiation 72
7.2.9 Security 72
7.2.10 HTTP redirection 72

Annex A (normative): OpenAPI specification 73

A.1 General 73

A.2 LMS_Reporting API 73

A.3 LMS_Information API 89

Annex B (informative): Change history 96

History 97

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

x the first digit:

1 presented to TSG for information;

2 presented to TSG for approval;

3 or greater indicates TSG approved document under change control.

y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.

z the third digit is incremented when editorial only changes have been incorporated in the document.

In the present document, modal verbs have the following meanings:

shall indicates a mandatory requirement to do something

shall not indicates an interdiction (prohibition) to do something

The constructions "shall" and "shall not" are confined to the context of normative provisions, and do not appear in Technical Reports.

The constructions "must" and "must not" are not used as substitutes for "shall" and "shall not". Their use is avoided insofar as possible, and they are not used in a normative context except in a direct citation from an external, referenced, non-3GPP document, or so as to maintain continuity of style when extending or modifying the provisions of such a referenced document.

should indicates a recommendation to do something

should not indicates a recommendation not to do something

may indicates permission to do something

need not indicates permission not to do something

The construction "may not" is ambiguous and is not used in normative elements. The unambiguous constructions "might not" or "shall not" are used instead, depending upon the meaning intended.

can indicates that something is possible

cannot indicates that something is impossible

The constructions "can" and "cannot" are not substitutes for "may" and "need not".

will indicates that something is certain or expected to happen as a result of action taken by an agency the behaviour of which is outside the scope of the present document

will not indicates that something is certain or expected not to happen as a result of action taken by an agency the behaviour of which is outside the scope of the present document

might indicates a likelihood that something will happen as a result of action taken by some agency the behaviour of which is outside the scope of the present document

might not indicates a likelihood that something will not happen as a result of action taken by some agency the behaviour of which is outside the scope of the present document

In addition:

is (or any other verb in the indicative mood) indicates a statement of fact

is not (or any other negative verb in the indicative mood) indicates a statement of fact

The constructions "is" and "is not" do not indicate requirements.

1 Scope

The present document specifies the protocols needed to support the Mission Critical Location Management service (MCLoc).

Mission critical services are services that require particular features and preferential handling compared to normal telecommunication services, e.g. in support of police or fire brigade.

The MCLoc service can be used for public safety applications as well as for some specialized commercial applications (e.g. utility companies and railways).

In the 3GPP systems, the Mission Critical Location Management service described in this document is instantiated at the application layer and involves interactions between MCLoc application clients on UEs and MCLoc application servers.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

[1] 3GPP TR 21.900: "Technical Specification Group working methods".

[2] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".

[3] 3GPP TS 23.280: "Common functional architecture to support mission critical services; Stage 2".

[4] 3GPP TS 23.271: "Functional stage 2 description of Location Services (LCS)".

[5] 3GPP TS 23.273: "5G System (5GS) Location Services (LCS); Stage 2".

[6] 3GPP TS 23.283: "Mission Critical Communication Interworking with Land Mobile Radio Systems; Stage 2".

[7] 3GPP TS 24.281: "Mission Critical Video (MCVideo) signalling control; Protocol specification".

[8] 3GPP TS 24.282: "Mission Critical Data (MCData) signalling control; Protocol specification".

[9] 3GPP TS 24.379: "Mission Critical Push to Talk (MCPTT) call control Protocol specification".

[10] 3GPP TS 24.482: " Mission Critical Services (MCS) identity management; Protocol specification".

[11] 3GPP TS 24.483: "Mission Critical Services (MCS) Management Object (MO)".

[12] 3GPP TS 24.484: "Mission Critical Services (MCS) configuration management Protocol specification".

[13] 3GPP TS 29.500: "5G System; Technical Realization of Service Based Architecture; Stage 3".

[14] 3GPP TS 29.501: "5G System; Principles and Guidelines for Services Definition; Stage 3".

[15] 3GPP TS 29.571: "5G System; Common Data Types for Service Based Interfaces; Stage 3".

[16] 3GPP TS 29.572: "5G System; Location Management Services; Stage 3".

[17] 3GPP TS 33.180: "Security of the mission critical service".

[18] IETF RFC 9562: "Universally Unique IDentifiers (UUIDs)".

[19] IETF RFC 6750: "The OAuth 2.0 Authorization Framework: Bearer Token Usage".

[20] IETF RFC 8259: "The JavaScript Object Notation (JSON) Data Interchange Format".

[21] IETF RFC 9113: "HTTP/2".

[22] OpenAPI: "OpenAPI Specification Version 3.0.0", https://spec.openapis.org/oas/v3.0.0.

3 Definitions of terms, symbols and abbreviations

3.1 Terms

For the purposes of the present document, the terms given in 3GPP TR 21.905 [2], 3GPP TS 23.280 [3] or the following apply. A term defined in the present document takes precedence over the definition of the same term, if any, in 3GPP TR 21.905 [2] or 3GPP TS 23.280 [3].

Location management client: An entity typically associated with a mobile device (UE), that can request and receive location information from a location management server and can provide location information to the location management server.

Location management server: An entity that can request and receive location information from location management clients, from other location management servers and from IWFs and can provide location information to authorized location management clients, other location management servers and IWFs.

MCLOC client ID: is a globally unique identification of a specific location management client instance. MCLOC client ID is a UUID URN as specified in IETF RFC 9562 [18].

3.2 Symbols

No symbols are defined in the present document.

3.3 Abbreviations

For the purposes of the present document, the abbreviations given in 3GPP TR 21.905 [2], 3GPP TS 23.280 [3], or the following apply. An abbreviation defined in the present document takes precedence over the definition of the same abbreviation, if any, in 3GPP TR 21.905 [2] or 3GPP TS 23.280 [3].

IWF Interworking Function between a 3GPP Mission Critical system and an LMR system
LMR Land Mobile Radio

4 General

4.1 Overview

The Mission Critical Location (MCLoc) is an optional auxiliary mission critical service operating at the application plane layer and supporting the MC services: MCPTT, MCVideo and MCData. It is fully integrated with those services (see 3GPP TS 23.280 [3]) and is consistent with the general design principles of the mission critical system. Salient features include:

- **Trust domains.** MCLoc protects the privacy and confidentiality of operation for MC service users, including their identities, by having the ability to restrict the ingestion and dissemination of related information from/to only well trusted entities.
- **Controlled list of users.** MCLoc provides services only to associates of mission critical organizations (MCO) who are subscribed through their respective MCO. The MCOs have business agreements with the mission

critical system operator, which avail them of control mechanisms such as pre-configuration, policy rules and user and service profiles.

- **Multiple devices**. From a user perspective, the identification and addressing is by user, rather than by device. Multiple active devices simultaneously active for the same user are supported, allowing addressing to a user at a particular active device.

- **Support for aliases.** MCLoc supports addressing by, reporting from, and notifications to, users identified via mission critical aliases.

- **Support of group operations**. Group communications is a key feature of mission critical systems. The mission critical location service is in constant contact with specific mission critical services (i.e. MCPTT, MCVideo, MCData) and, when instructed, can limit the location data collection and distribution to the members of the respective MC service groups, based on their current status (e.g. currently affiliated, currently in an active communication).

- **Rich set of location trigger types and variables.** MCLoc supports location event triggering on many various conditions and reporting of values of location variables, beyond just longitude and latitude: for example, z-axis values, speed, etc. In addition, the time and accuracy of the measurement or data acquisition is also recorded and can be reported by the LMC and/or notified by the LMS.

- **Context sensitive and adaptive operation**. MCLoc can be informed by various subsystems of changes in the context of operations (e.g. emergency situations, changes of RRC states, etc.). In those cases, MCLoc may enable/disable certain location triggers, use different set of parameters, and report/notify different location variables.

- **Off-network / on-network operation.** The location of off-network MC users can also be determined using ProSe communications. If ProSe UE-to-Network relays are employed, the off-network and on-network populations of MC users can be notified of stay updated on each other locations, as appropriate.

- **Interworking with LMR systems.** Depending on the location features supported by an interworking LMR system (if any), MCLoc may be able to receive, process, and store location information from the LMR system and disseminate it to MC service users. If the LMR system supports notifications, location information about the MC service users could be sent via the IWF to the LMR system.

4.2 LMS Registration

In the context of this specification the LMC needs to register to the LMS prior the MCLoc services can be made available to the MC user. When the LMC has registered to the LMS, the LMC may continuously get location configuration notifications and location requests from the LMS. The LMS registration shall include a LMC contact address (as a callback URI) used by the LMS to send the requests or notifications to the LMC.

The time period during which an LMC is registered may end automatically when all other MC services have deregistered or ended their operation, at the end of the registration expiry time, or, based on local policy and configuration, may continue in order to assist with locating lost or misplaced MC UEs.

4.3 Identities

4.3.1 General

The LMC is provided with MC service IDs as defined 3GPPP TS 23.280 [3] from the IdMS during user authentication procedure according to 3GPP TS 33.180 [17]. The MC service IDs are provided in the access tokens and ID tokens. The MC UE can get one or several access tokens and ID tokens from the IdMS depending on implementation. The MC service IDs are used in the three MC services and there is no dedicated MC service ID used by the location management server or client.

In the interaction between the LMC and LMS (e.g. location information reports) the LMC shall provide all MC service IDs that are currently available to the LMC. Other entities requesting location information for a specific MC user might only know a specific MC service ID for the MC user of interest.

Additionally, a LMC sending a request to a LMS shall also include the MCLOC client ID as defined in clause 4.3.2. The MCLOC client ID is used to distinguish multiple location management clients used by a single MC user.

4.3.2 MCLOC client ID

The LMC assigns the MCLOC client ID when the LMC is used for the first time. The LMC generates the MCLOC client ID as specified in clause 4.2 of IETF RFC 9562 [18].

The LMC preserves the MCLOC client ID:

- while the LMC is service authorized in the LMS;
- while the LMC is not service authorized in the LMS and the UE serving the MCLOC client is switched on;
- while the UE serving the MCLOC client is switched off; and
- while the UE serving the MCLOC client is power-cycled.

NOTE: MCLOC client ID is not preserved when the UE is reset to factory settings.

Other network entities (e.g. IWF, MC service servers, other LMS) that consume location information shall also assign a MCLOC client ID to be used in the APIs defined in this specification.

5 Functional entities and reference points

5.1 Introduction

This clause describes the association of functional entities within a mission critical system with their roles in the mission critical location management service, consistent with the stage 2 architecture document (see 3GPP TS 23.280 [3]).

5.2 Location management service functional architecture

Figure 5.2-1 shows the functional model for the location management service in the application plane, based on the architecture in 3GPP TS 23.280 [3] clause 7.3.




Figure 5.2-1: Location management service functional architecture

The protocol used on reference point CSC-24 is not part of this specification.

5.3 Functional entities

5.3.1 MCLoc client (LMC)

The MCLoc client can exist in a UE or other device, such as a dispatcher's console. The MCLoc client:

- interacts with the user playing the role of user agent for all location management application transactions;
- interacts with the hosting device (e.g. UE) and its subsystems as well as with other mission critical clients co-located in the same device, to obtain necessary information; and
- interacts with the MCLoc server, executing procedures defined in 3GPP TS 23.280 [3] and in the present document to register, obtain service authorization, request, receive and report location information,

5.3.2 MCLoc server (LMS)

The MCLoc server executes location related procedures defined in 3GPP TS 23.280 [3] and in the present document. Specifically, the MCLoc server:

- interacts with the LMCs to handle requests for location information that it needs to acquire or has stored;
- interacts with the LMCs to handle reports of location information;
- interacts with MC service servers acting as authorized LMCs, to handle requests for location information that it needs to acquire or has stored;
- interacts with MC service servers acting as authorized LMCs, to acquire and store location information that was reported to the MC service servers by MC service clients;

- interacts with KMS and CMS to obtain proper functional parameters, as necessary;
- interacts with other LMSs to request or provide location information; and
- interacts with an IWF to request or provide location information.

5.3.3 void

5.3.4 Configuration management server (CMS)

See 3GPP TS 23.280 [3] clause 7.4.2.2.2.

5.4 Reference points

5.4.1 void

5.4.2 Reference point CSC-14 (between the LMS and the LMC)

The CSC-14 reference point, which exists between the LMC and the LMS, is described in 3GPP TS 23.280 [3] clause 7.5.2.14.

5.4.3 Reference point CSC-15 (between the LMS and the MC service server)

The CSC-15 reference point, which exists between the LMS and the MC service server, is described in 3GPP TS 23.280 [3] clause 7.5.2.15.

5.4.4 Reference point CSC-22 (between the LMS and another LMS)

The CSC-22 reference point, which exists between the LMS and another LMS, is described in 3GPP TS 23.280 [3] clause 7.5.2.23.

5.4.5 Reference point CSC-24 (between the LMS and the configuration management server)

The CSC-24 reference point, which exists between the LMS and the configuration management server, is described in 3GPP TS 23.280 [3] clause 7.5.2.25.

5.4.6 Reference point IWF-4 (between the LMS and the IWF)

The IWF-4 reference point, which exists between the LMS and the IWF, is described in 3GPP TS 23.283 [6] clause 7.4.4.

5.4.7 Reference points HTTP-1, HTTP-2 and HTTP-3

The HTTP-1, HTTP-2 and HTTP-3 reference points, which support the location management system in the signalling control plane (not shown in Figure 5.2-1) are described in 3GPP TS 23.280 [3] clause 7.5.3.

6 Services offered by the location management server

6.1 Introduction

The table 6.1-1 lists the location management server APIs below the service name. A service description clause for each API gives a general description of the related API.

Table 6.1-1: API Descriptions

Service Name	Service Operations	Operation Semantics	Consumer(s)
LMS_Reporting	RegistrationRequest	Request/Response	LMC
	RegistrationUpdate	Request/Response	LMC
	RegistrationDelete	Request/Response	LMC
	ConfigurationNotify	Request/Response	LMS
	ConfigurationRequest	Request/Response	LMC
	LocationReportRequest	Request/Response	LMS
	LocationReportPublish	Request/Response	LMC
LMS_Information	LocationInfoRequest	Request/Response	LMC, MC service server, IWF, LMS
	LocationInfoSubscribe	Subscribe/Notify	LMC, MC service server, IWF, LMS
	LocationInfoNotify	Subscribe/Notify	LMS
	LocationInfoSubscribeUpdate	Subscribe/Notify	LMC, MC service server, IWF, LMS
	LocationInfoSubscribeDelete	Subscribe/Notify	LMC, MC service server, IWF, LMS
	LocationInfoConfigRequest	Request/Response	LMC, MC service server, IWF, LMS

Table 6.1-2 summarizes the corresponding LMS APIs defined in this specification.

Table 6.1-2: API Descriptions

Service Name	Clause	Description	OpenAPI Specification File	apiName	Annex
LMS_Reporting	7.1	LMS registration and reporting	TS24283_Lms_Reporting.yaml	lms-reporting	A.2
LMS_Information	7.2	LMS location information	TS24283_Lms_Information.yaml	lms-information	A.3

6.2 LMS_Reporting service

6.2.1 Service description

The LMS_Reporting service allows the LMC to:

- Register, update the registration and to deregister in the LMS;
- Request location configuration and receive location configuration; and
- Receive location information requests and to send location information reports.

At registration the LMS performs the service authorization according to 3GPP TS 33.180 [17].

6.2.2 Service operations

6.2.2.1 Introduction

The service operation defined for LMS_Reporting service is shown in the table 6.2.2.1-1.

Table 6.2.2.1-1: Operations of the LMS_Reporting service

Service operation name	Description	Initiated by
RegistrationRequest	This service operation is used by the LMC to register in the LMS.	LMC
RegistrationUpdate	This service operation is used by the LMC to update a registration in the LMS.	LMC
RegistrationDelete	This service operation is used by the LMC to deregister in the LMS.	LMC
ConfigurationNotify	This service operation is a callback request used by the LMS to send location configuration to the LMC.	LMS
ConfigurationRequest	This service operation is used by the LMC to request the location configuration.	LMC
LocationReportRequest	This service operation is a callback request used by the LMS to send a location information request to the LMS.	LMS
LocationReportPublish	This service operation is used by the LMC to report the location information of the MC UE to the LMS.	LMC

6.2.2.2 RegistrationRequest

6.2.2.2.1 General

This service operation is used by LMC to register itself in a given LMS.

6.2.2.2.2 LMC register to LMS using RegistrationRequest operation

For a LMC to register in the LMS, the LMC shall send an HTTP POST message to the LMS on the LMS_Reporting collection resource (i.e. LMC registration) to create the resource associated to the registration in the LMC.

The request URI shall be set according to clause 7.1.1.

The HTTP request shall include an Authorization header field with the "Bearer" authentication scheme set to all access tokens of the "bearer" token type as specified in IETF RFC 6750 [19].

NOTE: The LMS registration is relevant for all valid MC service IDs, hence the request includes all access tokens.

Other HTTP headers shall be set according to clause 7.1.2.2.

The body of the HTTP POST message shall include the LMCRegistration as specified in clause 7.1.6.2.2. The LMCRegistration datatype:

1) shall include an expTime attribute containing the time and date for the registration expiry;

2) shall include a mclocClientId attribute identifying the instance of the LMC;

3) shall include a locationConfigUri attribute specifying the URI of the LMC to which location configuration request shall be sent to;

4) shall include a locationRequestUri attribute specifying the URI of the LMC to which location request shall be sent to;

5) may include a pei attribute specifying the imei of the MC UE; and

6) may include a supi attribute specifying the supi of the subscription.

Upon receiving the HTTP POST message from the LMC, the LMS:

1) shall validate the access tokens as specified in 3GPP TS 33.180 [17];

2) shall consider the MC service IDs derived from the bearer access tokens as the identities of the sender of the RegistrationRequest;

3) if the any access token is not validated successfully, the LMS shall reject the request with a HTTP 401 (Unauthorized) response and not continue with the remaining steps; and

4) if the access token validation is successful, then the LMS:

   a) shall create a new resource with the LMC registration information as specified in clause 7.1.3.3.2 together with all LMS authorized MC service IDs;

   b) may initiate a ConfigurationNotify notification as specified in clause 7.1.5.2; and

   c) shall send a HTTP 201 Created response message to the LMC with the following clarifications:

      i) include the LMC registration information in the body of the HTTP 201 (Created) message;

      ii) the response message may include an updated expiration time to indicate when the LMC registration will automatically expire; and

NOTE: The updated expiration time can be shorter than what was initially provided by the LMC.

      iii) the URI of the created resource shall be returned in the "Location" HTTP header.

While the LMC is registered in the LMS, the LMS may repeatedly send:

1) ConfigurationNotify as specified in clause 6.2.2.5; and

2) LocationReportRequest as specified in clause 6.2.2.7.

The LMC shall send a Registration Update request (as described in clause 6.2.2.3) prior to the expiration time, to maintain the registration state. If a successful Registration Update request is not received prior to the expiration time, then the LMS shall treat LMC as implicitly deregistered and remove the corresponding LMC registration resource.

The LMS may use the value of pei or supi attribute when interacting over the Le reference point to request location information from the LCS network, see reference 3GPP TS 23.271 [4] and 3GPP TS 23.273 [5].

6.2.2.3 RegistrationUpdate

6.2.2.3.1 General

This service operation is used by the LMC to update its registration information at the LMS.

6.2.2.3.2 LMC updating registration using RegistrationUpdate operation

To update the LMC registration information at the LMS, the LMC shall send an HTTP PUT message to the LMS on resource URI identifying the individual LMC registration resource representation as specified in clause 7.1.3.3.2. The HTTP PUT message shall replace all properties of the existing resource with the LMC registration information in the request.

The request URI shall be set according to clause 7.1.1.

The HTTP request shall include an Authorization header field with the "Bearer" authentication scheme set to all access tokens of the "bearer" token type as specified in IETF RFC 6750 [19].

NOTE: The LMS registration is relevant for all valid MC service IDs, hence the request includes all access tokens.

Other HTTP headers shall be set according to clause 7.1.2.2.

The body of the HTTP PUT message shall include the LMCRegistration as specified in clause 7.1.6.2.2. The LMCRegistration datatype shall include:

1) an expTime attribute containing the time and date for the registration expiry;

2) a mclocClientId attribute identifying the instance of the LMC as defined in clause 4.3.2;

3) a locationConfigUri attribute specifying the URI of the LMC to which location configuration request shall be sent to; and

4) a locationRequestUri attribute specifying the URI of the LMC to which location request shall be sent to.

Upon receiving the PUT message from the LMC, if the resource URI does not exist, the LMS shall respond 404 Not Found error to the LMC. Otherwise, the LMS:

1) shall validate the access tokens as specified in 3GPP TS 33.180 [17];

2) shall consider the MC service IDs derived from the bearer access tokens as the identities of the sender of the RegistrationRequest;

3) if any access token is not validated successfully, the LMS shall reject the request with a HTTP 401 (Unauthorized) response and not continue with the remaining steps; and

4) if the access token validation is successful, then:

   a) the LMS shall update the resource with the LMC registration information as specified in clause 7.1.3.3.2 together with all LMS authorized MC service IDs; and

   b) shall return the updated LMC registration information in the response. In the response message, the LMS may send "200 OK" response code to provide an updated expiration time to indicate to the LMC when the updated registration will automatically expire. The expTime attribute shall override the current expTime attribute maintained by the LMC. Otherwise, the LMS sends "204 No Content" response code.

The LMC shall send a RegistrationUpdate request prior to the expiration time, to maintain the registration state. If a successful RegistrationUpdate request is not received prior to the expiration time, then the LMS shall treat LMC as implicitly deregistered and remove the corresponding LMC Registration resource.

6.2.2.4 RegistrationDelete

6.2.2.4.1 General

This service operation is used by LMC to deregister itself from a given LMS.

6.2.2.4.2 LMC deregistering using RegistrationDelete operation

To deregister itself from the LMS, the LMC shall send HTTP DELETE message to the LMS, on the resource URI identifying the individual LMC registration resource representation as specified in clause 7.1.3.3.2.

The request URI shall be set according to clause 7.1.1.

The HTTP request shall include an Authorization header field with the "Bearer" authentication scheme set to the access tokens of the "bearer" token type as specified in IETF RFC 6750 [19].

NOTE: The LMS registration is relevant for all valid MC service IDs, hence the request includes all access tokens.

Other HTTP headers shall be set according to clause 7.1.2.2.

Upon receiving the HTTP DELETE request, the LMS shall:

1) verify the identity of the LMC and check if the LMC is authorized to deregister the LMS registration information; and

2) if the LMC is authorized to deregister the LMS registration information, then the LMS shall

   a) if the resource identified by registrationId is not found, return "404 Not Found" error message to the LMC;

b) otherwise, deregister the LMC from the LMS and delete the resource representing LMC registration information; and

c) return the "204 No Content" message to the LMC, indicating the successful deregistration of the LMC information.

6.2.2.5 ConfigurationNotify

6.2.2.5.1 General

This service operation is used by LMS to notify the LMC about a new location configuration.

6.2.2.5.2 LMS send configuration using ConfigurationNotify operation

The LMS may at any time determine to notify a registered LMC about a change in the location configuration. The location configuration is sent to the LMC according to this procedure.

To notify the LMC about a location configuration, the LMS shall send HTTP POST message to the LMC, using the Notification Destination URI received in the registration request, as specified in clause 7.1.5.2.2.

The body of the HTTP POST message shall include the LocationConfiguration data type set to the desired configuration as specified in clause 7.1.6.2.3, and with the following clarifications:

1) shall include the triggerId attribute, with its already assigned value, if existent and valid, or with a newly generated unique value, if not, where defined for the sub-elements defining the trigger criterion;

2) may include the mcServiceId attribute set to the identity of the user requesting the location information configuration;

3) may include the configScope attribute set to "FULL" or "UPDATE". The value "FULL" means that the configuration attributes contains the full location configuration which replaces any previous location configuration. The value "UPDATE" means that the location configuration is in addition to any previous location configuration. To remove configuration elements a "Full" configuration is needed; and

4) may include the locationHistory attribute set to true to indicate that location information shall be stored in the LMC during the state when the LMC is not able to report location information. If the attribute is not included or set to false location information may not be stored in the LMC if the LMC fails to report location information.

Upon receiving the HTTP POST request, the LMC shall:

When the LMC receives that location configuration, then the LMC:

1) shall replace or modify the stored contents of the locationConfiguration attribute, consistent with the attribute configScope value, and then store the location configuration;

NOTE: The LMC only needs to store the latest received location reporting configuration.

2) shall set the location reporting triggers accordingly;

3) shall start the minimumReportInterval timer; and

4) if the locationHistory attribute is set to true and if location information reports cannot be successfully sent to the LMS then the LMC shall locally store the location information reports in the MC UE for later submissions.

6.2.2.6 ConfigurationRequest

6.2.2.6.1 General

This service operation is used by LMC to request the location configuration from the LMS.

6.2.2.6.2 LMC request the location configuration using ConfigurationRequest operation

The LMC may at any time request to download the location configuration from the LMS. The location configuration is sent to the LMC according to this procedure.

To request the location configuration the LMC shall send HTTP GET message to the LMS on the LMS_Reporting collection resource (i.e. LMC configurations).

The request URI shall be set according to clause 7.1.1.

The HTTP request shall include an Authorization header field with the "Bearer" authentication scheme set to all access tokens of the "bearer" token type as specified in IETF RFC 6750 [19].

NOTE: The configuration request is relevant for all valid MC service IDs, hence the request includes all access tokens.

Other HTTP headers shall be set according to clause 7.1.2.2.

Upon receiving the HTTP GET message from the LMC, the LMS:

1) shall perform service authorization as described in 3GPP TS 33.180 [17];

2) if the LMC is service authorized, then the LMS shall send a HTTP 200 OK response message to the LMC with the body including the LocationConfiguration datatype set to the configuration that applies to the LMC service ID; and

3) If the LMC is not service authorized, the LMS shall reject the request with a HTTP 401 (Unauthorized) response.

6.2.2.7 LocationReport

6.2.2.7.1 General

This service operation is used by LMS to send a new location report request to a registered LMC.

6.2.2.7.2 LMS send location request using LocationReportRequest

The LMS may at any time determine to send a location report request to a registered LMC.

To request a new location report from an LMC, the LMS shall send HTTP POST message to the LMC, using the Notification Destination URI received in the registration request, as specified in clause 7.1.5.3.2.

The body of the HTTP POST message shall include the LocationRequest data type as specified in clause 7.1.6.2.47, and with the following clarifications:

1) shall include the requestedMcServiceId attribute set to the MC service identity of the MC user being requested to send a location report;

2) shall include the requestingMcServiceId attribute set to the MC service identity of the MC user that request the location information, if the request is initiated from an LMC;

NOTE: If the request is initiated from the LMS without initial triggered from an LMC then the requesting MCServiceId is not needed.

3) may include the requestedFunctionalAliasId attribute set to the activated functional alias of the MC user being requested to send a location report;

4) may include the requestingFunctionalAliasId attribute set to the activated functional alias of the MC user that request the location information;

5) may include the requestedLocationInfo attribute including details of what location information attributes that shall be included in the location report;

6) may include the requestedLocationHistory attribute including details of what location information history events that shall be included in the location report;

7) may include the requestedLocationStatus attribute indicating that the location history status should be included in the location report; and

8) may include the requestId attribute including the identifier of the request, which will also be used in the location report from the client.

Upon receiving the HTTP POST request, the LMC shall:

When the LMC receives that location request, then the LMC:

1) shall generate a HTTP 200 (OK) response;

2) shall include in the HTTP 200 (OK) message a location report body as specified in clause 6.2.2.8;

3) shall send the HTTP 200 (OK) response towards the LMS; and

4) shall reset the minimumReportInterval timer.

6.2.2.8 LocationReportPublish

6.2.2.8.1 General

This service operation is used by LMC to publish a location report to a given LMS.

If a location reporting trigger fires the LMC checks if the minimumReportInterval timer is running. If the timer is running the LMC waits until the timer expires. When the minimumReportInterval timer fires, the LMC:

1) shall, if any of the reporting triggers are still true, send a location report as specified in clause 6.2.2.8.2.

If the LMC receives a LocationReportRequest as specified in clause 7.1.5.3, the LMC shall publish a location report as specified in clause 6.2.2.8.2.

6.2.2.8.2 LMC reports to LMS using LocationReportPublish

For a LMC to publish a location report to the LMS, the LMC shall send an HTTP POST message to the LMS on the LMS_Reporting collection resource (i.e. LMC location reports) representing the location information of the MC UE.

The request URI shall be set according to clause 7.1.1.

The HTTP request shall include an Authorization header field with the "Bearer" authentication scheme set to all access tokens of the "bearer" token type as specified in IETF RFC 6750 [19].

NOTE: The location report is relevant for all valid MC service IDs, hence the request includes all access tokens.

Other HTTP headers shall be set according to clause 7.1.2.2.

The body of the HTTP POST message shall include the MCUELocation data type as specified in clause 7.1.6.2.49. The MCUELocation datatype shall include:

1) a reportID attribute if the report was triggered by a location request, set to the value of the requestID attribute in the received request;

2) a reportType attribute indicating if the report is sent during emergency state or not;

3) a locTimstamp attribute set to the date and time of the location measurement;

4) an array with triggerId attributes, where each item is set to the value associated with the trigger that have fired;

5) a mclocClientId attribute identifying the instance of the LMC; and

6) a locationData attribute including subitems corresponding to the location configuration, and shall include at least one of the following attributes:

   a) currentCoordinate, containing the geospatial coordinate of the MC UE, with the following clarification:

      i) shall include the geographicalCoordinates attribute coded as defined in 3GPP TS 29.572 [16];

ii) may include altitude attribute coded as defined in 3GPP TS 29.572 [16];

iii) may include the horizontalaccuracy attribute coded as defined in 3GPP TS 29.572 [16];

iv) may include the verticalaccuracy attribute coded as defined in 3GPP TS 29.572 [16]; and

v) may include the bearingAndSpeed attribute coded as defined in3GPP TS 29.572 [16].

b) ecgi attribute containing the current served EUTRAN cell;

c) neighbouringEcgi attribute containing an array of ECGI of any neighbouring cell the MC UE can detect;

d) mbmsSaiId attribute containing the MBMS Service Area Id the LMC is located in;

e) mbsfnArea attribute containing the MBSFN Area the LMC is located in;

f) ncgi attribute containing the current served NR cell;

g) neighbouringNcgi attribute containing an array of NCGI of any neighbouring cell the MC UE can detect; and

h) nr5GMbsfsaArea attribute containing the 5G MBSFSA the MC UE is located in;

and may include:

1) a functionalAlias attribute containing the functional alias ID related to the functional alias status change that triggered the location measurement;

2) an interRatType attribute containing the inter-RAT change type;

3) an mcServiceUELabel attribute containing the MC Service UE label;

4) a locationHistoryData attribute containing multiple historical location reports if the location request indicates that historical location reports shall be included; and

5) a locationHistoryStatus attribute containing a location history status summary.

When the Location report publish is sent the LMC shall set the minimumReportInterval timer to the minimumReportInterval time from the location configuration and start the timer.

Upon receiving the HTTP POST message from the LMC, the LMS:

1) shall perform service authorization as described in 3GPP TS 33.180 [17];

2) if the LMC is service authorized, then the LMS:

   a) shall store the location information received in the location report;

   b) shall use the location information as needed; and

   c) shall send a HTTP 201 Created to the LMC; and

3) If the LMC is not service authorized, the LMS shall reject the request with a HTTP 401 (Unauthorized) response.

6.3 LMS_Information service

6.3.1 Service description

The LMS_Information service allows an LMC, MC service server, IWF or an LMS to:

- request location information;
- subscribe to location notifications;
- receive location information notifications;

- update an existing subscription for location information notification;
- unsubscribe to an existing subscription for location information notifications; and
- change another LMC location configuration.

6.3.2 Service operations

6.3.2.1 Introduction

The service operation defined for LMS_Information service is shown in the table 6.3.2.1-1.

Table 6.3.2.1-1: Operations of the LMS_Information service

Service operation name	Description	Initiated by
LocationInfoRequest	This service operation is used to request location information from the LMS.	LMC, MC service server, IWF, LMS
LocationInfoSubscribe	This service operation is used by the LMC to subscribe to location information from the LMS.	LMC, MC service server, IWF, LMS
LocationInfoNotify	This service operation is used to send notification about location information.	LMS
LocationInfoSubscribeUpdate	This service operation is used by the LMC to update a subscription of location information from the LMS.	LMC, MC service server, IWF, LMS
LocationInfoSubscribeDelete	This service operation is used by the LMC to terminate the subscription of location information.	LMC, MC service server, IWF, LMS
LocationInfoConfigRequest	This services operation is used to change another LMC location configuration.	LMC, MC service server, IWF, LMS

6.3.2.2 LocationRequest

6.3.2.2.1 General

This service operation is used by the LMC, MC service server, IWF or another LMS to send a location information request to an LMS. In this clause and its sub clauses the sender of the request is referred to as the client.

6.3.2.2.2 Client request location information to LMS using LocationRequest operation

For a client to request location information from the LMS, the client shall send an HTTP POST message to the LMS on the LMS_Information collection resource (i.e. Client location information request) to create the resource associated to the request for location information.

The request URI shall be set according to clause 7.2.1.

If the client is an LMC, the HTTP request shall include an Authorization header field with the "Bearer" authentication scheme set to all access tokens of the "bearer" token type as specified in IETF RFC 6750 [19].

NOTE 1: The LocationRequest is relevant for all valid MC service IDs, hence the request includes all access tokens.

If the client is a network entity (e.g. an IWF, an MC service server or another LMS) then the client shall insert an X-3GPP-Asserted-Identity header field as specified in 3GPP TS 24.482 [10] clause A.2.1.3. The identity in the 3GPP-Asserted-Identity header field shall be set to the public service identity of the network entity.

Other HTTP headers shall be set according to clause 7.2.2.2.

The body of the HTTP POST message shall include the ClientOriginatingLocationRequest as specified in clause 7.2.6.2.2. The ClientOriginatingLocationRequest datatype shall include:

1) a mclocClientId attribute identifying the instance of the LMC;
2) a locationNotificationUri attribute specifying the URI of the LMC to which location information notification shall be sent to;

3) at least one of the following:

   a) an array of MC service IDs of MC users for which location information are requested;

   b) an array of activated functional alias IDs used to determine MC service IDs of MC users for which location information are requested; and

   c) an array of MC service group IDs used to determine the MC service groups' affiliated MC service IDs of MC users for which location information are requested;

4) may include a refresh attribute to indicate that the location information shall be updated immediately from the requested LMC;

5) may include the requestedLocationHistory attribute including details of what location information history events that shall be included in the location report; and

6) may include the requestedLocationStatus attribute indicating that the location history status should be included in the location report.

Upon receiving the HTTP POST message from the LMC, the LMS shall:

1) shall validate the access tokens as specified in 3GPP TS 33.180 [17];

2) consider the MC service IDs derived from the bearer access tokens as the identities of the sender of the Locationrequest;

3) if any access token is not validated successfully, the LMS shall reject the request with a HTTP 401 (Unauthorized) response and not continue with the remaining steps;

4) if the array of MC service IDs, the array of functional alias IDs and the array of MC service group IDs are all empty then the LMS shall respond with a HTTP 403 (Forbidden) response including warning text set to "Invalid location request target client list" in a Warning header field, and shall not continue with the rest of the steps; and

5) if the access token validation is successful, then:

   a) the LMS shall create a new resource with the client location information request as specified in clause 7.2.3.2.3; and

   b) shall send a HTTP 201 Created response message to the LMC;

6) determine that the initiating user is authorized to request group based location information for each MC service group ID in the array provided in the attribute mcServiceGroupIds according to the following:

   a) The initiating user's location user configuration data document according to 3GPP TS 24.484 [12] shall include a <rule> element that includes:

      i) a <condition> element containing an <identity> element that matches the MC service group ID; and

      ii) an <action> element containing an <allow-request-location-of-groups> element with the value set to "true"; and

   b) if the item a) above is not fulfilled the MC service group ID shall be ignored in the remaining steps;

7) subscribe to group dynamic data to for each MC service group ID that passes the authorization check in step 6) according to the following:

   a) if the MC service group is a MCPTT group send a SIP SUBSCRIBE request as specified in 3GPP TS 24.379 [9] clause 9.2.2.2.16 where the LMS takes the role of an MCPTT server serving the initiating user;

   b) if the MC service group is a MCVideo group send a SIP SUBSCRIBE request as specified in 3GPP TS 24.281 [7] clause 8.2.2.2.16 where the LMS takes the role of an MCVideo server serving the initiating user; and

   c) if the MC service group is a MCData group send a SIP SUBSCRIBE request as specified in 3GPP TS 24.282 [8] clause 8.3.3.8 where the LMS takes the role of an MCData server serving the initiating user;

8) identify all MC service IDs for which location information is requested, based on the following content of the incoming request:

   a) the MC service IDs from the array provided in the attribute mcServiceIDs;

   b) the MC service IDs of the MC users that have activated the functional alias IDs from the array provided in the attribute functionalAliasIds

NOTE 2: One way to do that is to use the functional alias status determination procedure defined in 3GPP TS 24.379 [9] clause 9A.2.1.3.

   c) the MC service IDs of each MC client that have affiliated to the MC service groups based on the notifications from the group dynamic data subscriptions;

9) verify that the initiating user is authorized to request the location of the MC service IDs identified in step 6, according to local policies or to the following:

   a) The initiating user's location user configuration data document according to 3GPP TS 24.484 [12] shall include a <rule> element that include:

      i) a <condition> element containing an <identity> element that match each of identified MC service ID; and

      ii) an <action> element containing an <allow-request-location-of-users> element with the value set to "true"; and

   b) if the item i) above is not fulfilled the MC service ID shall be ignored in the remaining steps;

10) If any MC Service IDs identified in the steps above are not owned by the LMS, the LMS shall, in accordance with the procedure in this clause, generate a new HTTP request to the LMS that owns those MC Service IDs;

NOTE 3: How the LMS determines the HTTP request URI of the LMS that owns those MC Service IDs is out of scope of this specification.

11) verify that each target user identified from step 7 is authorized to share the location information with the initiating MC user, according to local policies or to the following:

   a) Each target user's location user configuration data document according to 3GPP TS 24.484 [12] shall include a <rule> element that include:

      i) a <condition> element containing an <identity> element that match the identity of the initiating user MC service ID; and

      ii) an <action> element containing an <allow-to-share-location-information> element with the value set to "true"; and

   b) if the item i) above is not fulfilled the MC service ID shall be ignored in the remaining steps;

12) if the refresh attribute is present and set to true, initiate LocationReportRequest operations (see clause 6.2.2.7.2) to each LMC identified in step 8).

The LMS shall create one or multiple location information notification and send the notifications to the requesting LMC according to the procedure in clause 6.3.2.4. Each location information notification message may contain location information from one or several MC UEs.

The location information notification message shall include the MC UE location details.

6.3.2.3 LocationInfoSubscribe

6.3.2.3.1 General

This service operation is used by the LMC to subscribe to location information at the LMS.

6.3.2.3.2 Client request subscription using LocationInfoSubscribe operation

To request a subscription for location information, the client shall send an HTTP POST message to the LMS on LMS_Information collection resource (i.e, Location information subscription) to create the resources associated with the subscription in the LMS.

The request URI shall be set according to clause 7.2.1.

If the client is an LMC, The HTTP request shall include an Authorization header field with the "Bearer" authentication scheme set to all access tokens of the "bearer" token type as specified in IETF RFC 6750 [19].

NOTE: The LocationInfoSubscribe operation is relevant for all valid MC service IDs, hence the request includes all access tokens.

If the client is a network entity (e.g. an IWF, an MC service server or another LMS) then the client shall insert an x-3gpp-asserted-identity header field as specified in 3GPP TS 24.482 [10] clause A.2.1.3. The identity in the x-3gpp-asserted-identity header field shall be set to the public service identity of the network entity.

Other HTTP headers shall be set according to clause 7.2.2.2.

The body of the HTTP POST message shall include the LocationSubscriptionRequest as specified in clause 7.2.6.2.5.

The LocationSubscriptionRequest data object shall include:

1) a mclocClientId attribute identifying the instance of the LMC;

2) a locationNotificationUri attribute specifying the URI of the LMC to which location notifications shall be sent to;

3) at least one of the following:

   a) an array of MC service IDs of MC users for which location information are requested;

   b) an array of activated functional alias IDs used to determine MC service IDs of MC users for which location information are requested; or

   c) an array of MC service group IDs used to determine the MC service groups' affiliated MC service IDs of MC users for which location information are requested; and

4) an expTime attribute containing the time and date for the subscription expiry;

Upon receiving the HTTP POST message from the LMC, the LMS shall:

1) validate the access tokens as specified in 3GPP TS 33.180 [17];

2) consider the MC service IDs derived from the bearer access tokens as the identities of the sender of the LMS_LocationInformation_request;

3) if the received HTTP request does not contain an Authorization header field with the "Bearer" authentication scheme and a bearer access token and the received HTTP request contains an x-3gpp-asserted-identity header field, the LMS shall consider the URI in the x-3gpp-asserted-identity header field as the identity of the sender of the HTTP request.

4) if the received HTTP request does contain an Authorization header field with the "Bearer" authentication scheme and bearer access token then:

   a) if the received request also includes an x-3gpp-asserted-identity header field, the LMS shall reject the request with a HTTP 401 (Unauthorized) response and not continue with the remaining steps; and

   b) if any access token is not validated successfully, the LMS shall reject the request with a HTTP 401 (Unauthorized) response and not continue with the remaining steps;

5) if the array of MC service IDs, the array of functional alias IDs and the array of MC service group IDs are all empty then the LMS shall respond with a HTTP 403 (Forbidden) response including warning text set to "Invalid subscription request target client list" in a Warning header field, and shall not continue with the rest of the steps;

6) if the MC user's location user configuration data document does not include a <rule> element including a <action> element including a <allow-subscription-on-location-information> element set to true the LMS shall respond with a HTTP 403 (Forbidden) response including warning text set to "Unauthorized for location subscription" in a Warning header field, and shall not continue with the rest of the steps;

7) generate a unique subscription identifier;

8) create a new resource with the location subscription request as specified in clause 7.2.3.3.3; and

9) send a HTTP 201 Created response message to the LMC and include the subscription identifier in the Location header;

The LMS shall identify all MC service IDs for which the subscription request applies according to step 6-11 in the procedure for a one-time location information request as specified in clause 6.3.2.2.2.

The LMS shall create location information notifications and send the notifications to the requesting LMC according to the procedure in clause 6.3.2.4. Each location information notification message shall contain location information for the MC UEs of the identified MC service IDs.

The identified MC service IDs may change during the subscription time if the MC service IDs are determine based on affiliated group members or activated functional aliases.

The LMS may need to update the location reporting configuration for the subscribed LMCs according to clause 6.2.2.5.

The notifications shall be sent repeatedly until the subscription expires based on the attribute expTime or until a unsubscribe message is received.

6.3.2.4 LocationInfoNotify

6.3.2.4.1 General

This service operation is used by LMS to notify the clients of a location information.

6.3.2.4.2 LMS Notify clients using LocationInfoNotify operation

The LMS use this procedure to notify an authorized user about other users' location information. The notification is used both because of a one-time location information request as well as repeatedly during a location information subscription.

To notify the LMC about other MC UEs' location information, the LMS shall send HTTP POST message to the LMC, using the notification URI received in the subscription request or in the location information request, as specified in clause 7.2.5.2.2.

The body of the HTTP POST message shall include the LocationNotification data type set to the MC UEs location information as specified in clause 7.2.6.2.4, and with the following clarifications:

1) shall include the requestingMcServiceId attribute set to the identity of the user requesting the location information;

2) may include the requestingfunctionalAliasId attribute set to the activated functional alias identity of the user requesting the location information;

3) shall include the mcUserResponseList attribute set to an array of MCUserLocation objects for each MC user's MC UE location.

When the LMC receives that location notification then the LMC:

1) shall send a HTTP 201 Created response message to the LMS; and

2) may use the location information as desired.

6.3.2.5 LocationInfoSubscribeUpdate

6.3.2.5.1 General

This service operation is used by clients to update the subscription of a location information.

6.3.2.5.2 Client requests update of subscription using LocationInfoSubscribeUpdate operation

To update an existing subscription the client shall send an HTTP PUT message to the LMS on the resource URI identifying the individual LMC subscription resource representation as specified in clause 7.2.3.4.2. The HTTP PUT message shall replace all properties of the existing resource with the LMS Location information subscribe request.

The request URI shall be set according to clause 7.2.1.

If the client is an LMC, The HTTP request shall include an Authorization header field with the "Bearer" authentication scheme set to all access tokens of the "bearer" token type as specified in IETF RFC 6750 [19].

NOTE: The LocationInfoSubscribeUpdate operation is relevant for all valid MC service IDs, hence the request includes all access tokens.

If the client is a network entity (e.g. an IWF, an MC service server or another LMS) then the client shall insert an x-3gpp-asserted-identity header field as specified in 3GPP TS 24.482 [10] clause A.2.1.3. The identity in the x-3gpp-asserted-identity header field shall be set to the public service identity of the network entity.

Other HTTP headers shall be set according to clause 7.2.2.2.

The body of the HTTP PUT message shall include the LocationSubscriptionRequest datatype as specified in clause 7.2.6.2.5.

The LocationSubscriptionRequest data object shall include:

1) a mclocClientId attribute identifying the instance of the LMC;

2) a locationNotificationUri attribute specifying the URI of the LMC to which location notifications shall be sent to;

3) at least one of the following:

   a) an array of MC service IDs of MC users for which location information are requested;

   b) an array of activated functional alias IDs used to determine MC service IDs of MC users for which location information are requested; or

   c) an array of MC service group IDs used to determine the MC service groups' affiliated MC service IDs of MC users for which location information are requested; and

4) an expTime attribute containing the time and date for the subscription expiry;

Upon receiving the HTTP PUT message from the LMC, the LMS shall:

1) validate the access tokens as specified in 3GPP TS 33.180 [17];

2) consider the MC service IDs derived from the bearer access tokens as the identities of the sender of the LMS_LocationInformation_request;

3) if the received HTTP request does not contain an Authorization header field with the "Bearer" authentication scheme and a bearer access token and the received HTTP request contains an x-3gpp-asserted-identity header field, the LMS shall consider the URI in the x-3gpp-asserted-identity header field as the identity of the sender of the HTTP request.

4) if the received HTTP request does contain an Authorization header field with the "Bearer" authentication scheme and bearer access token then:

a) if the received request also includes an x-3gpp-asserted-identity header field, the LMS shall reject the request with a HTTP 401 (Unauthorized) response and not continue with the remaining steps; and

b) if any access token is not validated successfully, the LMS shall reject the request with a HTTP 401 (Unauthorized) response and not continue with the remaining steps;

5) if the array of MC service IDs, the array of functional alias IDs and the array of MC service group IDs are all empty then the LMS shall respond with a HTTP 403 (Forbidden) response including warning text set to "Invalid subscription request target client list" in a Warning header field, and shall not continue with the rest of the steps;

6) if the MC user's location user configuration data document does not include a <rule> element including a <action> element including a <allow-subscription-on-location-information> element set to true the LMS shall respond with a HTTP 403 (Forbidden) response including warning text set to "Unauthorized for location subscription" in a Warning header field, and shall not continue with the rest of the steps;

7) update the complete subscription resource with the location subscription information as specified in clause 7.2.3.3.3; and

8) send a HTTP 204 No Content response message to the LMC.

The LMS shall identify all MC service IDs for which the subscription request applies according to step 6-11 in the procedure for a one-time location information request as specified in clause 6.3.2.2.2.

The LMS shall create location information notifications and send the notifications to the requesting LMC according to the procedure in clause 6.3.2.4. Each location information notification message shall contain location information for the MC UEs of the identified MC service IDs.

The identified MC service IDs may change during the subscription time if the MC service IDs are determine based on affiliated group members or activated functional aliases.

The notifications shall be sent repeatedly until the subscription expires based on the attribute expTime or until a unsubscribe message is received.

6.3.2.6 LocationInfoSubscribeDelete

6.3.2.6.1 General

This service operation is used by clients to delete a subscription of a location information.

6.3.2.6.2 Client requests unsubscribe using LMS_LocationInfoSubscribeDelete operation

To delete an subscription in the LMS, the LMC shall send HTTP DELETE message to the LMS, on the resource URI identifying the individual LMC subscription resource representation as specified in clause 7.2.3.4.2.

The request URI shall be set according to clause 7.2.1.

The HTTP request shall include an Authorization header field with the "Bearer" authentication scheme set to the access tokens of the "bearer" token type as specified in IETF RFC 6750 [19].

NOTE: The LMS subscription is relevant for all valid MC service IDs, hence the request includes all access tokens.

Other HTTP headers shall be set according to clause 7.2.2.2.

Upon receiving the HTTP DELETE request, the LMS shall:

1) verify the identity of the LMC and check if the LMC is authorized to delete the location information subscription; and

2) if the LMC is authorized to delete the location information subscription, then the LMS shall

a) if the resource identified by subscription id is not found, return "404 Not Found" error message to the LMC;

b) otherwise, delete the location information subscription from the LMS and delete the resource representing location information subscription; and

c) return the "204 No Content" message to the LMC, indicating the successful deletion of the LMC location information subscription.

6.3.2.7 LocationInfoConfigRequest

6.3.2.7.1 General

This service operation is used by the LMC, MC service server, IWF or another LMS to request an LMS to send a location configuration change request to an LMC. In this clause and its sub clauses the sender of the request is referred to as the client.

6.3.2.7.2 Client request location configuration change for another client from LMS using LocationInfoConfigRequest operation

For a client to request location configuration change for another client via the LMS, the client shall send an HTTP POST message to the LMS on the LMS_LocationInformation collection resource (i.e. Location Info Config request) to create the resource associated to the request for configuration change.

The request URI shall be set according to clause 7.2.2.

If the client is an LMC, the HTTP request shall include an Authorization header field with the "Bearer" authentication scheme set to all access tokens of the "bearer" token type as specified in IETF RFC 6750 [19].

NOTE: The LocationInfoConfigRequest is relevant for all valid MC service IDs, hence the request includes all access tokens.

If the client is a network entity (e.g. an IWF, an MC service server or another LMS) then the client shall insert an X-3GPP-Asserted-Identity header field as specified in 3GPP TS 24.482 [10] clause A.2.1.3. The identity in the 3GPP-Asserted-Identity header field shall be set to the public service identity of the network entity.

Other HTTP headers shall be set according to clause 7.2.2.2.

The body of the HTTP POST message shall include the LocationConfiguration as specified in clause 7.1.6.2.3. The LocationConfiguration datatype shall include:

1) shall include the triggerId attribute, with its already assigned value, if existent and valid, or with a newly generated unique value, if not, where defined for the sub-elements defining the trigger criterion;

2) shall include the mcServiceId attribute set to the identity of the target user for the location information configuration update; and

3) may include the locationHistory attribute set to true to indicate that location information shall be stored in the LMC during the state when the LMC is not able to report location information. If the attribute is not included or set to false location information may not be stored in the LMC if the LMC fails to report location information.

Upon receiving the HTTP POST message from the LMC, the LMS shall:

1) shall validate the access tokens as specified in 3GPP TS 33.180 [17];

2) consider the MC service IDs derived from the bearer access tokens as the identities of the sender of the LocationInfoConfigRequest;

3) if any access token is not validated successfully, the LMS shall reject the request with a HTTP 401 (Unauthorized) response and not continue with the remaining steps;

4) if the access token validation is successful, then:

   a) shall send a HTTP 200 OK response message to the LMC;

5) identify MC service ID for which location information configuration update is requested, based on content of the attribute mcServiceId;

6) verify that the initiating user is authorized to update the location information configuration of the MC service ID identified in step 5, according to local policies or to the following:

a) The initiating user's location user configuration data document according to 3GPP TS 24.484 [12] shall include a <rule> element that include:

i) a <condition> element containing an <identity> element that matches identified MC service ID; and

ii) an <action> element containing an <allow-change-location-configuration-of-users> element with the value set to "true"; and

b) if the item a) above is not fulfilled the MC service ID shall be ignored in the remaining steps;

7) Location information configuration for the target MC Service Id shall be updated with information LMS received in LocationConfiguration element:

a) Replace value of mcServiceId attribute in the LocationConfiguration element with the MC Service ID value derived from the bearer access tokens as the identity of the requestor of location information configuration update; and

8) Upon successful completion of the previous steps, the LMS shall:

a) Replace value of mcServiceId attribute in the LocationConfiguration element with the MC Service ID value derived from the bearer access tokens as the identity of the requestor of location information configuration update; and

b) create ConfigurationNotify message using updated configuration information, also taking into account existing LMS policies.

LMS shall send ConfigurationNotify message to the target LMC according to the procedure in clause 6.2.2.5.

7 LMS API Definitions

7.1 LMS_Reporting API

7.1.1 Introduction

The LMS_Reporting shall use the LMS_Reporting Service API.

The API URI of the LMS_Reporting API shall be:

{apiRoot}/<apiName>/<apiVersion>

The request URIs used in HTTP requests from the LMC towards the LMS shall have the Resource URI structure defined in clause 4.4.1 of 3GPP TS 29.501 [14], i.e.:

{apiRoot}/<apiName>/<apiVersion>/<apiSpecificResourceUriPart>

with the following components:

- The {apiRoot} shall be set as described in 3GPP TS 24.483 [11] clause 8.2.44D1.
- The <apiName> shall be "lms-reporting".
- The <apiVersion> shall be "v1".
- The <apiSpecificResourceUriPart> shall be set as described in clause 7.1.3.

7.1.2 Usage of HTTP

7.1.2.1 General

HTTP/2, IETF RFC 9113 [21], shall be used as specified in clause 5 of 3GPP TS 29.500 [13].

HTTP/2 shall be transported as specified in clause 5.3 of 3GPP TS 29.500 [13].

The OpenAPI [22] specification of HTTP messages and content bodies for the LMS_Reporting API is contained in clause A.2.

7.1.2.2 HTTP standard headers

7.1.2.2.1 General

See clause 5.2.2 of 3GPP TS 29.500 [13] for the usage of HTTP standard headers.

7.1.2.2.2 Content type

JSON, IETF RFC 8259 [20], shall be used as content type of the HTTP bodies specified in the present specification as specified in clause 5.4 of 3GPP TS 29.500 [13]. The use of the JSON format shall be signalled by the content type "application/json".

7.1.2.3 HTTP custom headers

The mandatory HTTP custom header fields specified in clause 5.2.3.2 of 3GPP TS 29.500 [13] shall be supported, and the optional HTTP custom header fields specified in clause 5.2.3.3 of 3GPP TS 29.500 [13] may be supported.

7.1.3 Resources

7.1.3.1 Overview

This clause describes the structure for the Resource URIs and the resources and methods used for the service.

Figure 7.1.3.1-1 depicts the resource URIs structure for the LMS_Reporting API.




Figure 7.1.3.1-1: Resource URI structure of the LMS_Reporting API

Table 7.1.3.1-1 provides an overview of the resources and applicable HTTP methods.

Table 7.1.3.1-1: Resources and methods overview

Resource name	Resource URI	HTTP method or custom operation	Description
LMC registrations	/registrations	POST	Create a new LMC registration.
Individual LMC registration	/registrations/{registrationId}	PUT	Update an existing LMC registration in the LMS.
		DELETE	Delete an existing LMC registration in the LMS.
LMC configurations	/configurations	GET	LMC request its location configuration from the LMS.
LMC location reports	/locationreports	POST	LMC published its location report in the LMS.

7.1.3.2 Resource: LMC Registrations

7.1.3.2.1 Description

The resource represents all LMC registrations.

7.1.3.2.2 Resource Definition

Resource URI: **{apiRoot}/lms-reporting/<apiVersion>/registrations**

This resource shall support the resource URI variables defined in table 7.1.3.2.2-1.

Table 7.1.3.2.2-1: Resource URI variables for this resource

Name	Data type	Definition
apiRoot	String	See clause 7.1.1

7.1.3.2.3 Resource Standard Methods

7.1.3.2.3.1 POST

This method shall support the URI query parameters specified in table 7.1.3.2.3.1-1.

Table 7.1.3.2.3.1-1: URI query parameters supported by the POST method on this resource

Name	Data type	P	Cardinality	Description	Applicability
n/a					

This method shall support the request data structures specified in table 7.1.3.2.3.1-2 and the response data structures and response codes specified in table 7.1.3.2.3.1-3.

Table 7.1.3.2.3.1-2: Data structures supported by the POST Request Body on this resource

Data type	P	Cardinality	Description
LMCRegistration	M	1	LMC registration details information

Table 7.1.3.2.3.1-3: Data structures supported by the POST Response Body on this resource

Data type	P	Cardinality	Response codes	Description
LMCRegistration	M	1	201 Created	LMC registration is successfully performed to the LMS. The URI of the created resource shall be returned in the "Location" HTTP header.
NOTE: The mandatory HTTP error status code for the POST method listed in table 5.2.7.1-1 of 3GPP TS 29.500 [13] also apply.				

Table 7.1.3.2.3.1-4: Headers supported by the POST method on this resource

Name	Data type	P	Cardinality	Description
n/a				

Table 7.1.3.2.3.1-5: Headers supported by the 201 response code on this resource

Name	Data type	P	Cardinality	Description
n/a				

7.1.3.2.4 Resource Custom Operations

None.

7.1.3.3 Resource: Individual LMC registration

7.1.3.3.1 Description

This resource represents an individual registration of an LMC.

7.1.3.3.2 Resource Definition

Resource URI: **{apiRoot}/lms-reporting//<apiVersion>/registrations/{registrationId}**

This resource shall support the resource URI variables defined in table 7.1.3.3.2-1.

Table 7.1.3.3.2-1: Resource URI variables for this resource

Name	Data Type	Definition
apiRoot	string	See clause 7.1.1
registrationId	string	The Identifier of a specific LMC registration.

7.1.3.3.3 Resource Standard Methods

7.1.3.3.3.1 PUT

This method updates the LMC registration data by completely replacing the existing registration data. This method shall support the URI query parameters specified in table 7.1.3.3.3.1-1.

Table 7.1.3.3.3.1-1: URI query parameters supported by the PUT method on this resource

Name	Data type	P	Cardinality	Description
n/a				

This method shall support the request data structures specified in table 7.1.3.3.3.1-2 and the response data structures and response codes specified in table 7.1.3.3.3.1-3.

Table 7.1.3.3.3.1-2: Data structures supported by the PUT Request Body on this resource

Data type	P	Cardinality	Description
LMCRegistration	M	1	An Individual registration resource to be updated.

Table 7.1.3.3.3.1-3: Data structures supported by the PUT Response Body on this resource

Data type	P	Cardinality	Response codes	Description
LMCRegistration	M	1	200 OK	An individual LMC registration resource updated successfully and the LMCRegistration data shall be included in the response.
n/a			204 No Content	An individual LMC registration resource updated successfully.
n/a			307 Temporary Redirect	Temporary redirection, during resource modification. The response shall include a Location header field containing an alternative URI of the resource located in an alternative LMS.
n/a			308 Permanent Redirect	Permanent redirection, during resource modification. The response shall include a Location header field containing an alternative URI of the resource located in an alternative LMS.
NOTE: The mandatory HTTP error status code for the PUT method listed in 5.2.7.1-1 of 3GPP TS 29.500 [13] also apply.				

Table 7.1.3.3.3.1-4: Headers supported by the PUT method on this resource

Name	Data type	P	Cardinality	Description
n/a				

Table 7.1.3.3.3.1-5: Headers supported by the 200 response code on this resource

Name	Data type	P	Cardinality	Description
n/a				

Table 7.1.3.3.3.1-6: Links supported by the 200 Response Code on this endpoint

Name	Resource name	HTTP method or custom operation	Link parameter(s)	Description
n/a				

Table 7.1.3.3.3.1-7: Headers supported by the 307 Response Code on this resource

Name	Data type	P	Cardinality	Description
Location	String	M	1	An alternative URI of the resource located in an alternative LMS.

Table 7.1.3.3.3.1-8: Headers supported by the 308 Response Code on this resource

Name	Data type	P	Cardinality	Description
Location	String	M	1	An alternative URI of the resource located in an alternative LMS.

7.1.3.3.3.2 DELETE

This method deregisters (removes) an existing LMC registration. This method shall support the URI query parameters specified in table 7.1.3.3.3.2-1.

Table 7.1.3.3.3.2-1: URI query parameters supported by the DELETE method on this resource

Name	Data type	P	Cardinality	Description
n/a				

This method shall support the request data structures specified in table 7.1.3.3.3.2-2 and the response data structures and response codes specified in table 7.1.3.3.3.2-3.

Table 7.1.3.3.3.2-2: Data structures supported by the DELETE Request Body on this resource

Data type	P	Cardinality	Description
n/a			

Table 7.1.3.3.3.2-3: Data structures supported by the DELETE Response Body on this resource

Data type	P	Cardinality	Response codes	Description
n/a			204 No Content	An individual LMC registration resource deleted successfully.
n/a			307 Temporary Redirect	Temporary redirection, during resource termination. The response shall include a Location header field containing an alternative URI of the resource located in an alternative LMS.
n/a			308 Permanent Redirect	Permanent redirection, during resource termination. The response shall include a Location header field containing an alternative URI of the resource located in an alternative LMS.
NOTE: The mandatory HTTP error status code for the DELETE method listed in table 5.2.7.1-1 of 3GPP TS 29.500 [13] also apply.				

Table 7.1.3.3.3.2-4: Headers supported by the DELETE method on this resource

Name	Data type	P	Cardinality	Description
n/a				

Table 7.1.3.3.3.2.-5: Headers supported by the 204 response code on this resource

Name	Data type	P	Cardinality	Description
n/a				

Table 7.1.3.3.3.2-6: Links supported by the 200 Response Code on this endpoint

Name	Resource name	HTTP method or custom operation	Link parameter(s)	Description
n/a				

Table 7.1.3.3.3.2-7: Headers supported by the 307 Response Code on this resource

Name	Data type	P	Cardinality	Description
Location	String	M	1	An alternative URI of the resource located in an alternative LMS.

Table 7.1.3.3.3.2-8: Headers supported by the 308 Response Code on this resource

Name	Data type	P	Cardinality	Description
Location	String	M	1	An alternative URI of the resource located in an alternative LMS.

7.1.3.3.4 Resource Custom Operations

None.

7.1.3.4 Resource: LMC Configurations

7.1.3.4.1 Description

The resource represents the LMC location reports collection.

7.1.3.4.2 Resource Definition

Resource URI: **{apiRoot}/lms-reporting/<apiVersion>/configurations**

This resource shall support the resource URI variables defined in table 7.1.3.4.2-1.

Table 7.1.3.4.2-1: Resource URI variables for this resource

Name	Data type	Definition
apiRoot	String	See clause 7.1.1

7.1.3.4.3 Resource Standard Methods

7.1.3.4.3.1 GET

This method shall support the URI query parameters specified in table 7.1.3.4.3.1-1.

Table 7.1.3.4.3.1-1: URI query parameters supported by the GET method on this resource

Name	Data type	P	Cardinality	Description	Applicability
n/a					

This method shall support the request data structures specified in table 7.1.3.4.3.1-2 and the response data structures and response codes specified in table 7.1.3.4.3.1-3.

Table 7.1.3.4.3.1-2: Data structures supported by the GET Request Body on this resource

Data type	P	Cardinality	Description
n/a			

Table 7.1.3.4.3.1-3: Data structures supported by the GET Response Body on this resource

Data type	P	Cardinality	Response codes	Description
LocationConfiguration	M	1	200 Ok	The location configuration applicable for the MC UE.
NOTE: The manadatory HTTP error status code for the GET method listed in table 5.2.7.1-1 of 3GPP TS 29.500 [13] also apply.				

Table 7.1.3.4.3.1-4: Headers supported by the GET method on this resource

Name	Data type	P	Cardinality	Description
n/a				

7.1.3.4.4 Resource Custom Operations

None.

7.1.3.5 Resource: LMC Location Reports

7.1.3.5.1 Description

The resource represents the LMC location reports collection.

7.1.3.5.2 Resource Definition

Resource URI: **{apiRoot}/lms-reporting/<apiVersion>/locationreports**

This resource shall support the resource URI variables defined in table 7.1.3.5.2-1.

Table 7.1.3.5.2-1: Resource URI variables for this resource

Name	Data type	Definition
apiRoot	String	See clause 7.1.1

7.1.3.5.3 Resource Standard Methods

7.1.3.5.3.1 POST

This method shall support the URI query parameters specified in table 7.1.3.5.3.1-1.

Table 7.1.3.5.3.1-1: URI query parameters supported by the POST method on this resource

Name	Data type	P	Cardinality	Description	Applicability
n/a					

This method shall support the request data structures specified in table 7.1.3.5.3.1-2 and the response data structures and response codes specified in table 7.1.3.5.3.1-3.

Table 7.1.3.5.3.1-2: Data structures supported by the POST Request Body on this resource

Data type	P	Cardinality	Description
MCUELocation	M	1	MC UE Location information

Table 7.1.3.5.3.1-3: Data structures supported by the POST Response Body on this resource

Data type	P	Cardinality	Response codes	Description
MCUELocation	M	1	201 Created	MC UE Location report is successfully submitted to the LMS. The LMC location data submitted to the LMS is provided in the response body. The URI of the created resource shall be returned in the "Location" HTTP header.
NOTE: The manadatory HTTP error status code for the POST method listed in table 5.2.7.1-1 of 3GPP TS 29.500 [13] also apply.				

Table 7.1.3.5.3.1-4: Headers supported by the POST method on this resource

Name	Data type	P	Cardinality	Description
n/a				

Table 7.1.3.5.3.1-5: Headers supported by the 201 response code on this resource

Name	Data type	P	Cardinality	Description
Location	String	M	1	Contains the URI of the newly created resource, according to the structure: {apiRoot}/lms-location-report/<apiVersion>/locationreports/{locationreportId}

7.1.3.5.4 Resource Custom Operations

None.

7.1.4 Custom Operations without associated resources

None.

7.1.5 Notifications

7.1.5.1 General

Table 7.1.5.1-1: Notifications overview

Notification	Callback URI	HTTP method or custom operation	Description (service operation)
ConfigurationNotify	{locationConfigUri}	POST	Notification to an LMC about a new Location configuration.
LocationReportRequest	{locationRequestUri}	POST	Request to an LMC about a new location report.

7.1.5.2 ConfigurationNotify notification

7.1.5.2.1 Description

ConfigurationNotify notification is used by the LMS to notify an LMC on a new location configuration.

7.1.5.2.2 Target URI

The Callback URI **"{**locationConfigUri**}"** shall be used with the callback URI variables defined in table 7.1.5.2.2-1.

Table 7.1.5.2.2-1: Callback URI variables

Name	Definition
locationConfigUri	String formatted as URI with the Callback Uri.

7.1.5.2.3 Standard Methods

7.1.5.2.3.1 POST

This method shall support the request data structures specified in table 7.1.5.2.3.1-1 and the response data structures and response codes specified in table 7.1.5.2.3.1-2.

Table 7.1.5.2.3.1-1: Data structures supported by the POST Request Body on this resource

Data type	P	Cardinality	Description
LocationConfiguration	M	1	Notification of LMC about a new location configuration.

Table 7.1.5.2.3.1-2: Data structures supported by the POST Response Body on this resource

Data type	P	Cardinality	Response codes	Description
n/a			204 No Content	The receipt of the Location configuration is acknowledged.
NOTE: The mandatory HTTP error status code for the POST method listed in table 5.2.7.1-1 of 3GPP TS 29.500 [13] also apply.				

7.1.5.3 LocationReportRequest notification

7.1.5.3.1 Description

LocationReportRequest notification is used by the LMS to request an LMC on a new location report.

7.1.5.3.2 Target URI

The Callback URI **"{locationR**equestUri**}"** shall be used with the callback URI variables defined in table 7.1.5.3.2-1.

Table 7.1.5.3.2-1: Callback URI variables

Name	Definition
locationRequestUri	String formatted as URI with the Callback Uri.

7.1.5.3.3 Standard Methods

7.1.5.3.3.1 POST

This method shall support the request data structures specified in table 7.1.5.3.3.1-1 and the response data structures and response codes specified in table 7.1.5.3.3.1-2.

Table 7.1.5.3.3.1-1: Data structures supported by the POST Request Body on this resource

Data type	P	Cardinality	Description
LocationRequest	M	1	Request an LMC to send a new location report.

Table 7.1.5.3.3.1-2: Data structures supported by the POST Response Body on this resource

Data type	P	Cardinality	Response codes	Description
n/a			204 No Content	The receipt of the location request is acknowledged.
NOTE: The mandatory HTTP error status code for the POST method listed in table 5.2.7.1-1 of 3GPP TS 29.500 [13] also apply.				

7.1.6 Data Model

7.1.6.1 General

This clause specifies the application data model supported by the LMS_Reporting Service API.

Table 7.1.6.1-1 specifies the data types defined for the LMS_Reporting Service interface protocol.

Table 7.1.6.1-1: LMS_Reporting Service specific Data Types

Data type	Clause defined	Description	Applicability
LMCRegistration	7.1.6.2.2	Includes details of a LMC registration request	
LocationConfiguration	7.1.6.2.3	Contains the location configuration details sent as a callback request to the LMC.	
LocationRequest	7.1.6.2.47	Contains the location request data type sent as a callback request to the LMC.	
MCUELocation	7.1.6.2.49	Includes detailed location information about a MC UE.	
LocationInfo	7.1.6.2.50	Includes all location data provided in the location report.	

Table 7.1.6.1-2 specifies data types re-used by the LMS_Reporting service based interface protocol from other specifications, including a reference to their respective specifications and when needed, a short description of their use within the LMS_Reporting service based interface.

Table 7.1.6.1-2: LMS_Registration Service re-used Data Types

Data type	Reference	Comments	Applicability
DateTime	3GPP TS 29.571 [15]	String with format "date-time" as defined in OpenAPI Specification [22]	
Ecgi	3GPP TS 29.571 [15]	E-Utran Cell Global Identity.	
GeographicalArea	3GPP TS 29.572 [16]	Geographical area defined as Polygon or EllipsoidArc	
MbsFsaId	3GPP TS 29.571 [15]	List of MBS Frequency Selection Area Identifiers, for a broadcast MBS session.	
Ncgi	3GPP TS 29.571 [15]	NR Cell Global Identity.	
Pei	3GPP TS 29.571 [15]	Permanent equipment identity.	
PlmnId	3GPP TS 29.571 [15]	PLMN Identity	
Supi	3GPP TS 29.571 [15]	Subscription permanent identifier.	
Tac	3GPP TS 29.571 [15]	Tracking Area	
Uri	3GPP TS 29.571 [15]	String providing an URI.	
MbsfnArea	3GPP TS 29.571 [15]	Represents an MBSFN area Identifier	
Altitude	3GPP TS 29.572 [16]	Double-precision float value of the altitude, expressed in meters.	
HorizontalWithVerticalVelocity	3GPP TS 29.572 [16]	Velocity estimate including horizontal speed and bearing, and also vertical speed and vertical direction.	
GeographicalCoordinates	3GPP TS 29.572 [16]	Geographical coordinates.	
Accuracy	3GPP TS 29.572 [16]	Float value of accuracy, expressed in meters.	

7.1.6.2 Structured data types

7.1.6.2.1 Introduction

This clause defines the structures to be used in resource representations.

7.1.6.2.2 Type: LMCRegistration

Table 7.1.6.2.2-1: Definition of type LMCRegistration

Attribute name	Data type	P	Cardinality	Description	Applicability
expTime	DateTime	M	1	Time and date for the registration expiry.	
mclocClientID	String	M	1	Used to identify the LMC that request registration	
locationConfigUri	Uri	M	1	URI where the Location Configuration should be delivered to.	
locationRequestUri	Uri	M	1	URI where the Location request should be delivered to.	
pei	Pei	O	0..1	Includes the permanent equipment identity.	
supi	Supi	O	0..1	Includes the imsi number.	

7.1.6.2.3 Type: LocationConfiguration

Table 7.1.6.2.3-1: Definition of type LocationConfiguration

Attribute name	Data type	P	Cardinality	Description	Applicability
emergencyTriggeringCriteria	TriggeringCriteria	O	0..1	Contains the location reporting trigger criteria used when the MC UE is in emergency state.	
emergencyLocationInformation	RequestedLocationInfo	O	0..1	Contains the details of what the location report shall include when the MC UE is in the emergency state.	
triggeringCriteria	TriggeringCriteria	O	0..1	Contains the location reporting trigger criteria used when the MC UE is not in emergency state.	
nonEmergencyLocationInformation	RequestedLocationInfo	O	0..1	Contains the details of what the location report shall include when the MC UE is not in the emergency state.	
mcServiceId	Uri	O	0..1	Optional attribute that is used to indicate the identity of the MC user requesting to set the location configuration or an identity of the MC user for which location configuration needs to be updated.	
configScope	ConfigScope	O	0..1	Used to indicate a full new location configuration or a subsequent upate of an existing.	
locationHistory	boolean	O	0..1	Optional attribute that if set to true indicates that location information shall be stored in LMC if location reporting can not be done.	
NOTE: At least one of emergencyTriggeringCriteria and triggeringCriteria shall be included.					

7.1.6.2.4 Type: TriggeringCriteria

Table 7.1.6.2.4-1: Definition of type TriggeringCriteria

Attribute name	Data type	P	Cardinality	Description	Applicability
adaptiveTrigger	AdaptiveTrigger	O	0..1	This attribute specifies parameters controlling adaptive combined time and distance triggers for location reporting.	
cellChange	CellChange	O	0..1	The attribute specifies which cell changes trigger location reporting.	
geographicalAreaChange	GeographicalAreaChange	O	0..1	The attribute specifies which geographical area changes trigger location reporting.	
mbsfnAreaChange	MbsfnAreaChange	O	0..1	The attribute specifies which Mbsfn area changes trigger location reporting.	
mbmsSaChange	MbmsSaChange	O	0..1	The attribute specifies which Mbms SA changes trigger location reporting.	
nr5GMbsfsaAreaChange	nr5GMbsfsaAreaChange	O	0..1	The attribute specifies which 5G Mbsfsa area changes trigger location reporting.	
periodicReport	PeriodicReport	O	0..1	The attribute specifies how frequent periodic location reports shall be sent.	
plmnChange	PlmnChange	O	0..1	The attribute specifies which PLMN changes trigger location reporting.	
ratTypeChange	RatTypeChange	O	0..1	An optional attribute specifying what inter-RAT changes triggers a location report.	
signallingEvent	SignallingEvent	O	0..1	An optional attribute specifying what signalling events triggers a location report.	
trackingAreaChange	TrackingAreaChange	O	0..1	The attribute specifies which tracking area changes trigger location reporting.	
travelledDistance	TravelledDistance	O	0..1	The attribute specifies the required travelled distance for a trigger for location reporting.	

7.1.6.2.5 Type: CellChange

Table 7.1.6.2.5-1: Definition of type CellChange

Attribute name	Data type	P	Cardinality	Description	Applicability
anyCellChange	AnyCellChange	O	1	The presence of this attribute specifies that any cell change is a trigger for location reporting.	
enterSpecificCell	SpecificCellChange	O	1	A list of cell Ids which triggers location reporting when entering the cells.	
exitSpecificCell	SpecificCellChange	O	1	A list of cell Ids which triggers location reporting when exiting the cells.	

7.1.6.2.6 Type: AnyCellChange

Table 7.1.6.2.6-1: Definition of type AnyCellChange

Attribute name	Data type	P	Cardinality	Description	Applicability
triggerId	TriggerId	M	1	The triggerId shall be set to a unique value and is returned in the location report.	

7.1.6.2.7 Type: SpecificCellChange

Table 7.1.6.2.7-1: Definition of type SpecificCellChange

Attribute name	Data type	P	Cardinality	Description	Applicability
eutranCells	array(EutranCell)	O	1..N	A list of Eutran or NR cell id that triggers a location reporting. (NOTE)	
nrCells	array(NrCell)	O	1..N	A list of Nr cell id that triggers a location reporting.(NOTE)	
NOTE: At least on of eutranCells and nrCells shall be present.					

7.1.6.2.8 Type: EutranCell

Table 7.1.6.2.8-1: Definition of type EutranCell

Attribute name	Data type	P	Cardinality	Description	Applicability
eutranCell	Ecgi	M	1	A list of Eutran or NR cell id that triggers a location reporting.	
triggerId	TriggerId	M	1	The triggerId shall be set to a unique value and is returned in the location report.	

7.1.6.2.9 Type: NrCell

Table 7.1.6.2.9-1: Definition of type NrCell

Attribute name	Data type	P	Cardinality	Description	Applicability
nrCell	Ncgi	M	1	A list of Nr cell id that triggers a location reporting.	
triggerId	TriggerId	M	1	The triggerId shall be set to a unique value and is returned in the location report.	

7.1.6.2.10 Type: GeographicalAreaChange

Table 7.1.6.2.10-1: Definition of type GeographicalAreaChange

Attribute name	Data type	P	Cardinality	Description	Applicability
enterSpecificArea	SpecificArea	O	0..1	A geographical area which triggers location reporting when entering or exiting the defined geographical area.	
exitSpecificArea	SpecificArea	O	0..1	A geographical area which triggers location reporting when entering or exiting the defined geographical area.	

7.1.6.2.11 Type: MbsfnAreaChange

Table 7.1.6.2.11-1: Definition of type MbsfnAreaChange

Attribute name	Data type	P	Cardinality	Description	Applicability
anyMbfsnAreaChange	AnyMbfsnAreaChange	O	1	The presence of this attribute specifies that any MBSFN area change is a trigger for location reporting.	
enterSpecificMbsfnArea	SpecificMbsfnArea	O	1	A list of MBSFN area Ids which triggers location reporting when entering the MBSFN area Ids.	
exitSpecificMbsfnArea	SpecificMbsfnArea	O	1	A list of MBSFN area Ids which triggers location reporting when exiting the MBSFN area Ids.	

7.1.6.2.12 Type: AnyMbsfnAreaChange

Table 7.1.6.2.12-1: Definition of type AnyMbsfnAreaChange

Attribute name	Data type	P	Cardinality	Description	Applicability
triggerId	TriggerId	M	1	The triggerId shall be set to a unique value and is returned in the location report.	

7.1.6.2.13 Type: SpecificMbsfnArea

Table 7.1.6.2.13-1: Definition of type SpecificMbsfnArea

Attribute name	Data type	P	Cardinality	Description	Applicability
mbsfnAreas	array(MbsfnAreaId)	M	1..N	A list of MBSFN area Ids that triggers location reporting when entering or exiting the MBSFN area Ids.	

7.1.6.2.14 Type: MbsfnAreaId

Table 7.1.6.2.14-1: Definition of type MbsfnAreaId

Attribute name	Data type	P	Cardinality	Description	Applicability
mbsfnArea	integer	M	1	The MBSFN area identity. Integer between 0 and 255.	
triggerId	TriggerId	M	1	The triggerId shall be set to a unique value and is returned in the location report.	

7.1.6.2.15 Type: MbmsSaChange

Table 7.1.6.2.15-1: Definition of type MbmsSaChange

Attribute name	Data type	P	Cardinality	Description	Applicability
anyMbmsSaChange	AnyMbmsSaChange	O	1	The presence of this attribute specifies that any MBMS SA change is a trigger for location reporting.	
enterSpecificMbmsSa	SpecificMbmsSaIdentity	O	1	A list of MBMS SAI which triggers location reporting when entering the MBMS SAI.	
exitSpecificMbmsSa	SpecificMbmsSaIdentity	O	1	A list of MBMS SAI which triggers location reporting when exiting the MBMS SAI.	

7.1.6.2.16 Type: AnyMbmsSaChange

Table 7.1.6.2.16-1: Definition of type AnyMbmsSaChange

Attribute name	Data type	P	Cardinality	Description	Applicability
triggerId	TriggerId	M	1	The triggerId shall be set to a unique value and is returned in the location report.	

7.1.6.2.17 Type: SpecificMbmsSaIdentity

Table 7.1.6.2.17-1: Definition of type SpecificMbmsSaIdentity

Attribute name	Data type	P	Cardinality	Description	Applicability
mbmsSaIdentities	array(MbmsSaIdentity)	M	1..N	A list of MBMS SAI that triggers location reporting when entering or exiting the MBMS SAI.	

7.1.6.2.18 Type: MbmsSaIdentity

Table 7.1.6.2.18-1: Definition of type MbmsSaIdentity

Attribute name	Data type	P	Cardinality	Description	Applicability
mbmsSaIdentity	Integer	M	1	The MBMS SA identity. Integer between 0 and 65535.	
triggerId	TriggerId	M	1	The triggerId shall be set to a unique value and is returned in the location report.	

7.1.6.2.19 Type: NR5GMbsfsaAreaChange

Table 7.1.6.2.19-1: Definition of type NR5GMbsfsaAreaChange

Attribute name	Data type	P	Cardinality	Description	Applicability
anyNR5GMbsfsaAreaChange	AnyNR5GMbsfsaAreaChange	O	1	The presence of this element specifies that any 5G Mbsfsa area change is a trigger for location reporting.	
enterSpecificNR5GMbsfsaArea	SpecificNR5GMbsfsaArea	O	1	A list of 5G Mbsfsa area that triggers a location reporting when entering the 5G Mbsfsa area.	
exitSpecificNR5GMbsfsaArea	SpecificNR5GMbsfsaArea	O	1	A list of 5G Mbsfsa area that triggers a location reporting when exiting the 5G Mbsfsa area.	

7.1.6.2.20 Type: AnyNR5GMbsfsaAreaChange

Table 7.1.6.2.20-1: Definition of type AnyNR5GMbsfsaAreaChange

Attribute name	Data type	P	Cardinality	Description	Applicability
triggerId	TriggerId	M	1	The triggerId shall be set to a unique value and is returned in the location report.	

7.1.6.2.21 Type: SpecificNR5GMbsfsaArea

Table 7.1.6.2.21-1: Definition of type SpecificNR5GMbsfsaArea

Attribute name	Data type	P	Cardinality	Description	Applicability
nr5GMbsFsaIdentities	array(NR5GMbsfsaAreaIdentity)	M	1..N	A list of 5G Mbsfsa area that triggers a location reporting when entering or exiting the 5G Mbsfsa area.	

7.1.6.2.22 Type: NR5GMbsfsaAreaIdentity

Table 7.1.6.2.22-1: Definition of type NR5GMbsfsaAreaIdentity

Attribute name	Data type	P	Cardinality	Description	Applicability
mbsfsa AreaIdentity	MbsFsaId	M	1	An 5G Mbsfsa area identity that triggers location reporting.	
triggerId	TriggerId	M	1	The triggerId shall be set to a unique value and is returned in the location report.	

7.1.6.2.23 Type: PeriodicReport

Table 7.1.6.2.23-1: Definition of type PeriodicReport

Attribute name	Data type	P	Cardinality	Description	Applicability
periodicReport	integer	M	1	Value in seconds specifies the reporting interval.	
triggerId	TriggerId	M	1	The triggerId shall be set to a unique value and is returned in the location report.	

7.1.6.2.24 Type: PlmnChange

Table 7.1.6.2.24-1: Definition of type PlmnChange

Attribute name	Data type	P	Cardinality	Description	Applicability
anyPlmnChange	AnyPlmnChange	O	1	The presence of this element specifies that any PLMN change is a trigger for location reporting.	
enterSpecificPlmnArea	SpecificPlmnChange	O	1	A list of PLMNs that triggers a location reporting when entering the PLMN.	
exitSpecificPlmnArea	SpecificPlmnChange	O	1	A list of PLMNs that triggers a location reporting when exiting the PLMN.	

7.1.6.2.25 Type: AnyPlmnChange

Table 7.1.6.2.25-1: Definition of type AnyPlmnChange

Attribute name	Data type	P	Cardinality	Description	Applicability
triggerId	TriggerId	M	1	The triggerId shall be set to a unique value and is returned in the location report.	

7.1.6.2.26 Type: SpecificPlmnChange

Table 7.1.6.2.26-1: Definition of type SpecificPlmnChange

Attribute name	Data type	P	Cardinality	Description	Applicability
plmnIds	array(Plmn)	M	1..N	A list of PLMNs that triggers a location reporting when entering or exiting the PLMN.	

7.1.6.2.27 Type: Plmn

Table 7.1.6.2.27-1: Definition of type Plmn

Attribute name	Data type	P	Cardinality	Description	Applicability
plmn	PlmnId	M	1	A PLMN identity that triggers location reporting.	
triggerId	TriggerId	M	1	The triggerId shall be set to a unique value and is returned in the location report.	

7.1.6.2.28 Type: TrackingAreaChange

Table 7.1.6.2.28-1: Definition of type TrackingAreaChange

Attribute name	Data type	P	Cardinality	Description	Applicability
anyTrackingAreaChange	AnyTrackingAreaChange	O	1	The presence of this element specifies that any tracking area change is a trigger for location reporting.	
enterSpecificTrackingArea	SpecificTrackingAreaChange	O	1	A list of tracking areas that triggers a location reporting when entering the tracking area.	
exitSpecificTrackingArea	SpecificTrackingAreaChange	O	1	A list of tracking areas that triggers a location reporting when exiting the tracking area.	

7.1.6.2.29 Type: AnyTrackingAreaChange

Table 7.1.6.2.29-1: Definition of type AnyTrackingAreaChange

Attribute name	Data type	P	Cardinality	Description	Applicability
triggerId	TriggerId	M	1	The triggerId shall be set to a unique value and is returned in the location report.	

7.1.6.2.30 Type: SpecificTrackingAreaChange

Table 7.1.6.2.30-1: Definition of type SpecificTrackingAreaChange

Attribute name	Data type	P	Cardinality	Description	Applicability
trackingAreas	array(TrackingArea)	M	1..N	A list of tracking areas that triggers a location reporting when entering or exiting the tracking area.	

7.1.6.2.31 Type: TrackingArea

Table 7.1.6.2.31-1: Definition of type TrackingArea

Attribute name	Data type	P	Cardinality	Description	Applicability
trackingArea	Tac	M	1	A tracking area identity that triggers location reporting.	
triggerId	TriggerId	M	1	The triggerId shall be set to a unique value and is returned in the location report.	

7.1.6.2.32 Type: TravelledDistance

Table 7.1.6.2.32-1: Definition of type TravelledDistance

Attribute name	Data type	P	Cardinality	Description	Applicability
travelledDistance	Integer	M	1	Value in meter specifies the travelled distance for location reporting.	
triggerId	TriggerId	M	1	The triggerId shall be set to a unique value and is returned in the location report.	

7.1.6.2.33 Type: RequestedLocationInfo

Table 7.1.6.2.33-1: Definition of type RequestedLocationInfo

Attribute name	Data type	P	Cardinality	Description	Applicability
bearingAndSpeed	boolean	O	1	The presence of this attribute indicates that the item shall be included in the location report.	
Coordinate	boolean	O	1	The presence of this attribute indicates that the item shall be included in the location report.	
mbmsSaId	boolean	O	1	The presence of this attribute indicates that the item shall be included in the location report.	
mbsfnArea	boolean	O	1	The presence of this attribute indicates that the item shall be included in the location report.	
minimumIntervalLength	integer	O	1	Value in seconds, the minimum time between location reports.	
neigbouringEcgi	boolean	O	1	The presence of this attribute indicates that the item shall be included in the location report.	
neigbouringNcgi	boolean	O	1	The presence of this attribute indicates that the item shall be included in the location report.	
nr5GmbsfsaArea	boolean	O	1	The presence of this attribute indicates that the item shall be included in the location report.	
servingEcgi	boolean	O	1	The presence of this attribute indicates that the item shall be included in the location report.	
servingNcgi	boolean	O	1	The presence of this attribute indicates that the item shall be included in the location report.	

7.1.6.2.34 Type: AdaptiveTrigger

Table 7.1.6.2.34-1: Definition of type AdaptiveTrigger

Attribute name	Data type	P	Cardinality	Description	Applicability
triggerId	TriggerId	M	1	The triggerId shall be set to a unique value and is returned in the location report.	
minPeriod	integer	O	0..1	An optional attribute specified as a positive or 0 integer number of seconds and defaulting at 0, if not present. This attribute specifies the minimum wait period between consecutive location reports, irrespective of changes in the distance between the current location and the location of the most recent sending of a location report.	
minDistance	integer	O	0..1	An optional attribute specified as a strictly positive integer number of meters and defaulting at infinity, if not present. This attribute is used in the decision of sending a location report based on travelled distance, and specifies the minimum required distance, between the current location and the location of the most recent sending of a location report.	
persistencePeriod	integer	O	0..1	An optional attribute specified as a positive or 0 integer number of seconds and defaulting at 0, if not present. This attribute specifies the time between the moment when the LMC detected that the distance between the current location and the location of the most recent sending of a location report exceeded the minDistance attribute and the moment when the LMC will check again that the updated current location is still farther away by at least minDistance from the location of the mentioned sending of the location report. If the check is positive, a location report based on travelled distance will be sent.	
additionalTime	integer	O	0..1	An optional attribute, specified as a strictly positive integer number of seconds and defaulting at 1. If a location report is not sent based on the travelled distance, the LMC will send a location report after minPeriod + PersistencePeriod + AdditionalTime seconds after the previous location report.	
rrcInactiveMinPeriod	integer	O	0..1	An optional attribute with the same semantics and behaviour as described above for the corresponding parameter, but applicable when the UE receives MBS traffic in RRC_INACTIVE state.	
rrcInactiveMinDistance	integer	O	0..1	An optional attribute with the same semantics and behaviour as described above for the corresponding parameter, but applicable when the UE receives MBS traffic in RRC_INACTIVE state.	
rrcInactivePersistencePeriod	integer	O	0..1	An optional attribute with the same semantics and behaviour as described above for the corresponding parameter, but applicable when the UE receives MBS traffic in RRC_INACTIVE state.	

rrcInactiveadditional Time	integer	O	0..1	An optional attribute with the same semantics and behaviour as described above for the corresponding parameter, but applicable when the UE receives MBS traffic in RRC_INACTIVE state.	

7.1.6.2.35 Void

7.1.6.2.36 Type: SpecificArea

Table 7.1.6.2.36-1: Definition of type SpecificArea

Attribute name	Data type	P	Cardinality	Description	Applicability
geoAreas	array(Geographic Area)	M	1..N	A list of geographical areas that triggers a location reporting when entering or exiting the the geographical areas.	

7.1.6.2.37 Type: RatTypeChange

Table 7.1.6.2.37-1: Definition of type RatTypeChange

Attribute name	Data type	P	Cardinality	Description	Applicability
anyRatTypeChange	AnyRatType Change	O	0..1	The presence of this optional attribute specifying that any inter-RAT change triggers a location report.	

7.1.6.2.38 Type: AnyRatTypeChange

Table 7.1.6.2.38-1: Definition of type AnyRatTypeChange

Attribute name	Data type	P	Cardinality	Description	Applicability
triggerId	TriggerId	M	1	The triggerId shall be set to a unique value and is returned in the location report.	

7.1.6.2.39 Void

7.1.6.2.40 Type: SignallingEvent

Table 7.1.6.2.40-1: Definition of type SignallingEvent

Attribute name	Data type	P	Cardinality	Description	Applicability
functionalAliasActivation	FunctionalAliasActivation	O	0..1	This attribute specifies that a functional alias activation triggers a location report.	
functionalAliasDeactivation	FunctionalAliasDeactivation	O	0..1	This attribute specifies that a functional alias deactivation triggers a location report.	
initialLogOn	InitialLogOn	O	0..1	This attribute specifies that an initial log on triggers a location report.	
groupCallNonEmergency	GroupCallNonEmergency	O	0..1	This attribute specifies that a non-emergency group call triggers a location report.	
privateCallNonEmergency	PrivateCallNonEmergency	O	0..1	This attribute specifies that a non-emergency private call triggers a location report.	
locationConfigurationReceived	LocationConfigurationReceived	O	0..1	This attribute specifies that a received location configuration triggers a location report.	

7.1.6.2.41 Type: FunctionalAliasActivation

Table 7.1.6.2.41-1: Definition of type FunctionalAliasActivation

Attribute name	Data type	P	Cardinality	Description	Applicability
triggerId	TriggerId	M	1	The triggerId shall be set to a unique value and is returned in the location report.	

7.1.6.2.42 Type: FunctionalAliasDeactivation

Table 7.1.6.2.42-1: Definition of type FunctionalAliasDeactivation

Attribute name	Data type	P	Cardinality	Description	Applicability
triggerId	TriggerId	M	1	The triggerId shall be set to a unique value and is returned in the location report.	

7.1.6.2.43 Type: InitialLogOn

Table 7.1.6.2.43-1: Definition of type InitialLogOn

Attribute name	Data type	P	Cardinality	Description	Applicability
triggerId	TriggerId	M	1	The triggerId shall be set to a unique value and is returned in the location report.	

7.1.6.2.44 Type: GroupCallNonEmergency

Table 7.1.6.2.44-1: Definition of type GroupCallNonEmergency

Attribute name	Data type	P	Cardinality	Description	Applicability
triggerId	TriggerId	M	1	The triggerId shall be set to a unique value and is returned in the location report.	

7.1.6.2.45 Type: PrivateCallNonEmergency

Table 7.1.6.2.45-1: Definition of type PrivateCallNonEmergency

Attribute name	Data type	P	Cardinality	Description	Applicability
triggerId	TriggerId	M	1	The triggerId shall be set to a unique value and is returned in the location report.	

7.1.6.2.46 Type: LocationConfigurationReceived

Table 7.1.6.2.46-1: Definition of type LocationConfigurationReceived

Attribute name	Data type	P	Cardinality	Description	Applicability
triggerId	TriggerId	M	1	The triggerId shall be set to a unique value and is returned in the location report.	

7.1.6.2.47 Type: LocationRequest

Table 7.1.6.2.47-1: Definition of type LocationRequest

Attribute name	Data type	P	Cardinality	Description	Applicability
requestedMcServiceId	Uri	M	1	The MC service ID of the MC user being requested to send a location report.	
requestingMcServiceId	Uri	O	0..1	The MC service ID of the MC user from which location information is being requested.	
requestId	string	O	0..1	The request ID of the request which is used to identify the response from the client.	
requestedFunctionalAliasId	Uri	O	0..1	The activated functional alias ID of the MC user being requested to send a location report.	
requestingFunctionalAliasId	Uri	O	0..1	The activated functional alias ID of the MC user from which location information is being requested.	
requestedLocationInfo	RequestedLocationInfo	O	0..1	Contains the details of what the location report shall include.	
requestLocationHistory	RequestLocationHistory	O	0..1	Includes details on requested location history information.	
requestHistoryStatus	booelan	O	0..1	Indicates that a location history status is requested.	

7.1.6.2.48 Type: RequestLocationHistory

Table 7.1.6.2.48-1: Definition of type RequestLocationHistory

Attribute name	Data type	P	Cardinality	Description	Applicability
numberOfReports	integer	O	0..1	Indicates the number of requested stored reports.	
startTime	DateTime	O	0..1	Indicates that the report shall include location information reports newer than this time.	
endTime	DateTime	O	0..1	Indicates that the report shall include location information reports older than this time.	
triggerCriteria	TriggerCriteria	O	0..1	Identifies the criteria when the location management client generated location information, while not reporting location information.	
minimumIntervalLength	integer	O	0..1	Value in seconds, the minimum time between location reports.	

7.1.6.2.49 Type: MCUELocation

Table 7.1.6.2.49-1: Definition of type MCUELocation

Attribute name	Data type	P	Cardinality	Description	Applicability
functionalAlias	Uri	O	0..1	Includes functional alias change that triggered the location report.	
interRatType	InterRatType	O	0..1	Includes the RAT change type.	
locationData	LocationInfo	M	1	Includes all location data provided in the location report.	
locTimestamp	DateTime	M	1	Includes the date and time the location measurement was made	
mclocClientId	MclocClientId	M	1	Used to identify the reporting LMC	
mcServiceUELabel	string	O	0..1	Used to identify the MC service UE.	
reportId	string	O	0..1	Used to return the request id when the location report is triggered by a location request.	
reportType	ReportType	M	1	Used to inform whether the LMC is sending the report in an emergency situation or not.	
triggerId	array(string)	O	1..N	TriggerId attribute associated with the location trigger that triggered the location report.	
locationHistoryData	LocationHistoryData	O	0..1	This attribute contains one or multiple time stamped location information reports.	
locationHistoryStatus	LocationHistoryStatus	O	0..1	This attribute contains a location history status information.	

7.1.6.2.50 Type: LocationInfo

Table 7.1.6.2.50-1: Definition of type locationInfo

Attribute name	Data type	P	Cardinality	Description	Applicability
currentCoordinate	CurrentCoordinate	O	0..1	Object that includes the current coordination data.	
ecgi	Ecgi	O	0..1	Attribute containing the ECGI that the LMC is located in.	
mbmsSaiId	string	O	0..1	Attribute containing the MBMS Service Area Id the LMC is located in.	
mbsfnArea	MbsfnArea	O	0..1	Attribute containing the MBSFN Area the LMC is located in.	
ncgi	Ncgi	O	0..1	Attribute containing the NGCI that the LMC is located in.	
neighbouringEcgi	array(Ecgi)	O	1..N	Attribute containing a list of ECGI of any neighbouring cell the LMC detects.	
neighbouringNcgi	array(Ncgi)	O	1..N	Attribute containing a list of NCGI of any neighbouring cell the LMC detects.	
nr5GMbsfsaArea	MbsFsaId	O	0..1	Attribute containing the 5G MBS Frequency Selection Area Id the LMC is located in.	

7.1.6.2.51 Type: CurrentCoordinate

Table 7.1.6.2.51-1: Definition of type CurrentCoordinate

Attribute name	Data type	P	Cardinality	Description	Applicability
altitude	Altitude	O	0..1	Attribute containing the altitude.	
bearingAndSpeed	HorizontalWithVerticalVelocity	O	0..1	Attribute containing the horizontal and vertical velocity as well as the bearing.	
horizonalaccuracy	Accuracy	O	0..1	Attribute containing the accuracy expressed in meter.	
geographicalCoordinates	GeographicalCoordinates	M	1	Attribute containing the geographical coordinates e.g. in latitude and longitude.	
verticalaccuracy	Accuracy	O	0..1	Attribute containing the accuracy expressed in meter.	

7.1.6.2.52 Type: LocationHistoryData

Table 7.1.6.2.52-1: Definition of type LocationHistoryData

Attribute name	Data type	P	Cardinality	Description	Applicability
locationHistoryEvent	array(LocationHistoryEvent)	M	1..N	This object contains one or multiple time stamped location information reports.	

7.1.6.2.53 Type: LocationHistoryEvent

Table 7.1.6.2.53-1: Definition of type LocationHistoryEvent

Attribute name	Data type	P	Cardinality	Description	Applicability
locationData	LocationInfo	M	1..N	Includes location data provided in the historical location report.	
locTimestamp	DateTime	M	1	Includes the date and time the location measurements were made	
triggerId	array(string)	O	0..N	TriggerId attribute associated with the location triggers that triggered the location report.	

7.1.6.2.54 Type: LocationHistoryStatus

Table 7.1.6.2.54-1: Definition of type LocationHistoryStatus

Attribute name	Data type	P	Cardinality	Description	Applicability
storedReports	integer	M	1	Indicates the number of stored location reports that has not been reported.	
startTime	DateTime	M	1	Includes the date and time of the oldest stored location report.	
endTime	DateTime	M	1	Includes the date and time of the newest stored location report.	
triggerId	array(string)	M	0..N	TriggerId attribute associated with the location triggers that triggered the location report.	

7.1.6.3 Simple data types and enumerations

7.1.6.3.1 Introduction

This clause defines simple data types and enumerations that can be referenced from data structures defined in the previous clauses.

7.1.6.3.2 Simple data types

The simple data types defined in table 7.1.6.3.2-1 shall be supported.

Table 7.1.6.3.2-1: Simple data types

Type Name	Type Definition	Description	Applicability
TriggerId	string	The triggerId shall be set to a unique value and is returned in the location report.	

7.1.6.3.3 Enumeration: ConfigScope

The enumeration ConfigScope indicates how the location configuration shall be updated. To remove configuration elements a "Full" configuration is needed. It shall comply with the provisions defined in table 7.2.6.3.3-1.

Table 7.2.6.3.3-1: Enumeration ConfigScope

Enumeration value	Description	Applicability
FULL	The value "FULL" means that LocationConfiguration attributes contains the full location configuration which replaces any previous location configuration.	
UPDATE	The value "UPDATE" means that the LocationConfiguration is in addition to any previous location configuration.	

7.1.6.3.4 Enumeration: ReportType

The enumeration ReportType indicates if the report is done during an emergency situation or not. It shall comply with the provisions defined in table 7.1.6.3.4-1.

Table 7.1.6.3.4-1: Enumeration ReportType

Enumeration value	Description	Applicability
EMERGENCY	Indicates that the MC UE that sends the Location reports is in emergency state.	
NONEMERGENCY	Indicates that the MC UE that sends the Location reports is not in emergency state.	

7.1.6.3.5 Enumeration: InterRatType

The enumeration InterRatType indicates type of inter RAT status change. It shall comply with the provisions defined in table 7.1.6.3.5-1.

Table 7.1.6.3.5-1: Enumeration InterRatType

Enumeration value	Description	Applicability
5G_MBS_TO_LTE_MBMS	The inter RAT change is from 5G-MBS to LTE-MBMS	
5G_MBS_TO_LTE_UNICAST	The inter RAT change is from 5G-MBS to LTE-unicast	
LTE_MBMS_TO_5G_MBS	The inter RAT change is from LTE-MBMS to 5G-MBS	
LTE_MBMS_TO_5G_UNICAST	The inter RAT change is from LTE-MBMS to 5G-unicast	

7.1.7 Error Handling

7.1.7.1 General

For the LMS_Registration API, HTTP error responses shall be supported as specified in clause 4.8 of 3GPP TS 29.501 [14]. Protocol errors and application errors specified in table 5.2.7.2-1 of 3GPP TS 29.500 [13] shall be supported for an HTTP method if the corresponding HTTP status codes are specified as mandatory for that HTTP method in table 5.2.7.1-1 of 3GPP TS 29.500 [13].

In addition, the requirements in the following clauses are applicable for the LMS_Registration API.

7.1.7.2 Protocol Errors

No specific procedures for the LMS_Reporting service are specified.

7.1.7.3 Application Errors

The application errors defined for the LMS_Reporting service are listed in table 7.1.7.3-1.

Table 7.1.7.3-1: Application errors

Application Error	HTTP status code	Description

7.1.8 Feature negotiation

Table 7.1.8-1 defines the features supported by the LMS_Reporting API. They shall be negotiated using the extensibility mechanism defined in clause 6.6 of 3GPP TS 29.500 [13].

No feature is defined in this release of the specification.

Table 7.1.8-1: Supported Features

Feature number	Feature Name	M/O	Description

7.1.9 Security

The LMC shall send HTTP requests over TLS connection as specified for the HTTP client in the UE in annex A of 3GPP TS 24.482 [10].

Authentication and authorization shall be as specified in 3GPP TS 33.180 [17].

The LMS shall be configured with an authorized MC service server list, containing public service identities of MC service servers.

When handling an HTTP request, the LMS shall determine the identity of the sender of the HTTP request as specified in 3GPP TS 24.482 [10], and shall use the identity of the sender of the HTTP request as an authenticated identity when performing the authorization.

7.1.10 HTTP redirection

An HTTP request may be redirected to a different LMS service instance, within the same LMS. When an HTTP server redirects an HTTP request (i.e. service request or notification/callback request) to a different target LMS service instance, the URI of the target LMS service instance towards which the request is redirected shall be given by the Location header field of the 307 Temporary Redirect or 308 Permanent Redirect response. Further details on HTTP redirection are found in 3GPP TS 29.500 [13].

7.2 LMS_Information API

7.2.1 Introduction

The LMS_Information shall use the LMS_Information Service API.

The API URI of the LMS_Information API shall be:

{apiRoot}/<apiName>/<apiVersion>

The request URIs used in HTTP requests from the LMC towards the LMS shall have the Resource URI structure defined in clause 4.4.1 of 3GPP TS 29.501 [14], i.e.:

{apiRoot}/<apiName>/<apiVersion>/<apiSpecificResourceUriPart>

with the following components:

- The {apiRoot} shall be set as described in 3GPP TS 24.483 [11] clause 8.2.44D1.

- The <apiName> shall be "lms-information".
- The <apiVersion> shall be "v1".
- The <apiSpecificResourceUriPart> shall be set as described in clause 7.2.3.

7.2.2 Usage of HTTP

7.2.2.1 General

HTTP/2, IETF RFC 9113 [21], shall be used as specified in clause 5 of 3GPP TS 29.500 [13].

HTTP/2 shall be transported as specified in clause 5.3 of 3GPP TS 29.500 [13].

The OpenAPI [22] specification of HTTP messages and content bodies for the LMS_Information API is contained in clause A.4.

7.2.2.2 HTTP standard headers

7.2.2.2.1 General

See clause 5.2.2 of 3GPP TS 29.500 [13] for the usage of HTTP standard headers.

7.2.2.2.2 Content type

JSON, IETF RFC 8259 [20], shall be used as content type of the HTTP bodies specified in the present specification as specified in clause 5.4 of 3GPP TS 29.500 [13]. The use of the JSON format shall be signalled by the content type "application/json".

7.2.2.3 HTTP custom headers

The mandatory HTTP custom header fields specified in clause 5.2.3.2 of 3GPP TS 29.500 [13] shall be supported, and the optional HTTP custom header fields specified in clause 5.2.3.3 of 3GPP TS 29.500 [13] may be supported.

7.2.3 Resources

7.2.3.1 Overview

This clause describes the structure for the Resource URIs and the resources and methods used for the service.

Figure 7.2.3.1-1 depicts the resource URIs structure for the LMS_Information API.




Figure 7.2.3.1-1: Resource URI structure of the LMS_Information API

Table 7.2.3.1-1 provides an overview of the resources and applicable HTTP methods.

Table 7.2.3.1-1: Resources and methods overview

Resource name	Resource URI	HTTP method or custom operation	Description
Client location information request	/requests	POST	Create a new client location information request.
Location information subscription	/subscriptions	POST	Create a new client location information subscription.
Individual location information subscription	/subscriptions/{subscriptionId}	PUT	Update an existing subscription.
		DELETE	Delete an existing subscription.
Location information config request	/configrequest	POST	Update location configuration information of a target user

7.2.3.2 Resource: Client location information request

7.2.3.2.1 Description

The resource represents all client location information request.

7.2.3.2.2 Resource Definition

Resource URI: **{apiRoot}/lms-information/<apiVersion>/requests**

This resource shall support the resource URI variables defined in table 7.2.3.2.2-1.

Table 7.2.3.2.2-1: Resource URI variables for this resource

Name	Data type	Definition
apiRoot	String	See clause 7.2.1

7.2.3.2.3 Resource Standard Methods

7.2.3.2.3.1 POST

This method shall support the URI query parameters specified in table 7.2.3.2.3.1-1.

Table 7.2.3.2.3.1-1: URI query parameters supported by the POST method on this resource

Name	Data type	P	Cardinality	Description	Applicability
n/a					

This method shall support the request data structures specified in table 7.2.3.2.3.1-2 and the response data structures and response codes specified in table 7.2.3.2.3.1-3.

Table 7.2.3.2.3.1-2: Data structures supported by the POST Request Body on this resource

Data type	P	Cardinality	Description
ClientOriginatingLocationRequest	M	1	Client originating location information details

Table 7.2.3.2.3.1-3: Data structures supported by the POST Response Body on this resource

Data type	P	Cardinality	Response codes	Description
ClientOriginatingLocationRequest	M	1	201 Created	Client location information request is successfully created in the LMS. The URI of the created resource shall be returned in the "Location" HTTP header.
NOTE: The manadatory HTTP error status code for the POST method listed in table 5.2.7.1-1 of 3GPP TS 29.500 [13] also apply.				

Table 7.2.3.2.3.1-4: Headers supported by the POST method on this resource

Name	Data type	P	Cardinality	Description
n/a				

Table 7.2.3.2.3.1-5: Headers supported by the 201 response code on this resource

Name	Data type	P	Cardinality	Description
n/a				

7.2.3.3.4 Resource Custom Operations

None.

7.2.3.3 Resource: Location information subscriptions

7.2.3.3.1 Description

The resource represents all location information subscriptions.

7.2.3.3.2 Resource Definition

Resource URI: **{apiRoot}/lms-information/<apiVersion>/subscriptions**

This resource shall support the resource URI variables defined in table 7.2.2.3.2-1.

Table 7.2.2.3.2-1: Resource URI variables for this resource

Name	Data Type	Definition
apiRoot	String	See clause 7.2.1

7.2.3.3.3 Resource Standard Methods

7.2.3.3.3.1 POST

This method creates the location information subscription. This method shall support the URI query parameters specified in table 7.2.3.3.3.1-1.

Table 7.2.3.3.3.1-1: URI query parameters supported by the POST method on this resource

Name	Data type	P	Cardinality	Description
n/a				

This method shall support the request data structures specified in table 7.2.3.3.3.1-2 and the response data structures and response codes specified in table 723.3.3.3.1-3.

Table 7.2.3.3.3.1-2: Data structures supported by the POST Request Body on this resource

Data type	P	Cardinality	Description
LocationSubscription Request	M	1	Location information subscription details

Table 7.2.3.3.3.1-3: Data structures supported by the POST Response Body on this resource

Data type	P	Cardinality	Response codes	Description
LocationSubscriptionRequest	M	1	201 Created	A location information subscription resource created successfully.
NOTE: The manadatory HTTP error status code for the POST method listed in 5.2.7.1-1 of 3GPP TS 29.500 [13] also apply.				

Table 7.2.3.3.3.1-4: Headers supported by the POST method on this resource

Name	Data type	P	Cardinality	Description
n/a				

Table 7.2.3.3.3.1-5: Headers supported by the 201 response code on this resource

Name	Data type	P	Cardinality	Description
Locationn	String	M	1	Contains the URI of the newly created resource, according to the structure: {apiRoot}/lms-location-information/<apiVersion>/subscriptions/{subscriptionId}

Table 7.2.3.3.3.1-6: Headers supported by the 307 Response Code on this resource

Name	Data type	P	Cardinality	Description
Location	String	M	1	An alternative URI of the resource located in an alternative LMS.

Table 7.2.3.3.3.1-7: Headers supported by the 308 Response Code on this resource

Name	Data type	P	Cardinality	Description
Location	String	M	1	An alternative URI of the resource located in an alternative LMS.

7.2.3.4 Resource: Individual location information subscription

7.2.3.4.1 Description

The resource represents a location information subscription.

7.2.3.4.2 Resource Definition

Resource URI: **{apiRoot}/lms-information/<apiVersion>/subscription/{subscriptionID}**

This resource shall support the resource URI variables defined in table 7.2.2.3.2-1.

Table 7.2.2.3.2-1: Resource URI variables for this resource

Name	Data Type	Definition
apiRoot	String	See clause 7.w.1

7.2.3.4.3 Resource Standard Methods

7.2.3.4.3.1 PUT

This method updates a location information subscription. This method shall support the URI query parameters specified in table 7.2.3.4.3.1-1.

Table 7.2.3.4.3.1-1: URI query parameters supported by the PUT method on this resource

Name	Data type	P	Cardinality	Description
n/a				

This method shall support the request data structures specified in table 7.2.3.4.3.1-2 and the response data structures and response codes specified in table 7.2.3.4.3.1-3.

Table 7.2.3.4.3.1-2: Data structures supported by the PUT Request Body on this resource

Data type	P	Cardinality	Description
LocationSubscription Request	M	1	Client location information subscription details to be updated

Table 7.2.3.4.3.1-3: Data structures supported by the PUT Response Body on this resource

Data type	P	Cardinality	Response codes	Description
n/a			204 No Content	An individual location information subscription resource updated successfully.
n/a			307 Temporary Redirect	Temporary redirection, during resource modification. The response shall include a Location header field containing an alternative URI of the resource located in an alternative LMS.
n/a			308 Permanent Redirect	Permanent redirection, during resource modification. The response shall include a Location header field containing an alternative URI of the resource located in an alternative LMS.
NOTE: The manadatory HTTP error status code for the PUT method listed in 5.2.7.1-1 of 3GPP TS 29.500 [13] also apply.				

Table 7.2.3.4.3.1-4: Headers supported by the PUT method on this resource

Name	Data type	P	Cardinality	Description
n/a				

Table 7.2.3.4.3.1-5: Headers supported by the 204 response code on this resource

Name	Data type	P	Cardinality	Description
n/a				

Table 7.2.3.4.3.1-6: Links supported by the 204 Response Code on this endpoint

Name	Resource name	HTTP method or custom operation	Link parameter(s)	Description
n/a				

Table 7.2.3.4.3.1-7: Headers supported by the 307 Response Code on this resource

Name	Data type	P	Cardinality	Description
Location	String	M	1	An alternative URI of the resource located in an alternative LMS.

Table 7.2.3.4.3.1-8: Headers supported by the 308 Response Code on this resource

Name	Data type	P	Cardinality	Description
Location	String	M	1	An alternative URI of the resource located in an alternative LMS.

7.2.3.4.3.2 DELETE

This method deletes a location information subscription. This method shall support the URI query parameters specified in table 7.2.3.4.3.2-1.

Table 7.2.3.4.3.2-1: URI query parameters supported by the DELETE method on this resource

Name	Data type	P	Cardinality	Description
n/a				

This method shall support the request data structures specified in table 7.2.3.4.3.2-2 and the response data structures and response codes specified in table 7.2.3.4.3.2-3.

Table 7.2.3.4.3.2-2: Data structures supported by the DELETE Request Body on this resource

Data type	P	Cardinality	Description
n/a	M	1	Client location information subscription details to be updated

Table 7.2.3.4.3.2-3: Data structures supported by the DELETE Response Body on this resource

Data type	P	Cardinality	Response codes	Description
n/a	M	1	204 No Content	An individual location information subscription resource deleted successfully.
n/a			307 Temporary Redirect	Temporary redirection, during resource modification. The response shall include a Location header field containing an alternative URI of the resource located in an alternative LMS.
n/a			308 Permanent Redirect	Permanent redirection, during resource modification. The response shall include a Location header field containing an alternative URI of the resource located in an alternative LMS.
NOTE: The manadatory HTTP error status code for the DELETE method listed in 5.2.7.1-1 of 3GPP TS 29.500 [13] also apply.				

Table 7.2.3.4.3.2-4: Headers supported by the POST method on this resource

Name	Data type	P	Cardinality	Description
n/a				

Table 7.2.3.4.3.2-5: Headers supported by the 200 response code on this resource

Name	Data type	P	Cardinality	Description
n/a				

Table 7.2.3.4.3.2-6: Links supported by the 200 Response Code on this endpoint

Name	Resource name	HTTP method or custom operation	Link parameter(s)	Description
n/a				

Table 7.2.3.4.3.2-7: Headers supported by the 307 Response Code on this resource

Name	Data type	P	Cardinality	Description
Location	String	M	1	An alternative URI of the resource located in an alternative LMS.

Table 7.2.3.4.3.2-8: Headers supported by the 308 Response Code on this resource

Name	Data type	P	Cardinality	Description
Location	String	M	1	An alternative URI of the resource located in an alternative LMS.

7.2.3.4.4 Resource Custom Operations

None.

7.2.3.5 Resource: Location information config request

7.2.3.5.1 Description

The resource represents all location information config requests.

7.2.3.5.2 Resource Definition

Resource URI: **{apiRoot}/lms-information/<apiVersion>/configrequest**

This resource shall support the resource URI variables defined in table 7.2.3.5.2-1.

Table 7.2.3.5.2-1: Resource URI variables for this resource

Name	Data Type	Definition
apiRoot	String	See clause 7.2.1

7.2.3.5.3 Resource Standard Methods

7.2.3.5.3.1 POST

This method updates the location configuration information of a target user. This method shall support the URI query parameters specified in table 7.2.3.5.3.1-1.

Table 7.2.3.5.3.1-1: URI query parameters supported by the POST method on this resource

Name	Data type	P	Cardinality	Description
n/a				

This method shall support the request data structures specified in table 7.2.3.5.3.1-2 and the response data structures and response codes specified in table 7.2.3.5.3.1-3.

Table 7.2.3.5.3.1-2: Data structures supported by the POST Request Body on this resource

Data type	P	Cardinality	Description
LocationConfiguration	M	1	Location configuration details.

Table 7.2.3.5.3.1-3: Data structures supported by the POST Response Body on this resource

Data type	P	Cardinality	Response codes	Description
LocationInfoConfigRequest	M	1	201 Created	A location configuration resource updated successfully.
NOTE: The manadatory HTTP error status code for the POST method listed in 5.2.7.1-1 of 3GPP TS 29.500 [13] also apply.				

Table 7.2.3.5.3.1-4: Headers supported by the POST method on this resource

Name	Data type	P	Cardinality	Description
n/a				

7.2.4 Custom Operations without associated resources

None.

7.2.5 Notifications

7.2.5.1 General

Table 7.2.5.1-1: Notifications overview

Notification	Callback URI	HTTP method or custom operation	Description (service operation)
Location Notification	{locationNotificationUri}	POST	Notification to a client containing location information.

7.2.5.2 Location information notification

7.2.5.2.1 Description

Location configuration notification is used by the LMS to notify a client on a new location information.

7.2.5.2.2 Target URI

The Callback URI "{locationNotificationUri}" shall be used with the callback URI variables defined in table 7.2.5.2.2-1.

Table 7.2.5.2.2-1: Callback URI variables

Name	Definition
locationNotificationUri	String formatted as URI with the Callback Uri.

7.2.5.2.3 Standard Methods

7.2.5.2.3.1 POST

This method shall support the request data structures specified in table 7.2.5.2.3.1-1 and the response data structures and response codes specified in table 7.2.5.2.3.1-2.

Table 7.2.5.2.3.1-1: Data structures supported by the POST Request Body on this resource

Data type	P	Cardinality	Description
LocationNotification	M	1	Notification containing location information.

Table 7.2.5.2.3.1-2: Data structures supported by the POST Response Body on this resource

Data type	P	Cardinality	Response codes	Description
n/a			204 No Content	The receipt of the Location notification is acknowledged.
NOTE: The mandatory HTTP error status code for the POST method listed in table 5.2.7.1-1 of 3GPP TS 29.500 [13] also apply.				

7.2.6 Data Model

7.2.6.1 General

This clause specifies the application data model supported by the LMS_Information Service API.

Table 7.2.6.1-1 specifies the data types defined for the LMS_Information Service interface protocol.

Table 7.2.6.1-1: LMS_Information Service specific Data Types

Data type	Clause defined	Description	Applicability
ClientOriginatingLocationRequest	7.2.6.2.2	Includes detailed of a client location information request	

Table 7.2.6.1-2 specifies data types re-used by the LMS_Information service based interface protocol from other specifications, including a reference to their respective specifications and when needed, a short description of their use within the LMS_Information service based interface.

Table 7.2.6.1-2: LMS_Information Service re-used Data Types

Data type	Reference	Comments	Applicability
n/a			

7.2.6.2 Structured data types

7.2.6.2.1 Introduction

This clause defines the structures to be used in resource representations.

7.2.6.2.2 Type: ClientOriginatingLocationRequest

Table 7.2.6.2.2-1: Definition of type ClientOriginatingLocationRequest

Attribute name	Data type	P	Cardinality	Description	Applicability
functionalAliasIds	array(Uri)	O	1..N	A list of activated Functional Alias Id of requested MC Users. (NOTE)	
locationNotificationUri	Uri	M	1	URI where the Location Notifications should be delivered to.	
mclocClientID	string	M	1	Used to identify the LMC that makes a subscription request.	
mcServiceIds	array(Uri)	O	1..N	A list of MC service IDs of the MC users for which location information is requested MC Users.(NOTE)	
mcServiceGroupIds	array(Uri)	O	1..N	A list of MC service group IDs of which all affiliated members' location information are being requested.	
refresh	boolean	O	0..1	Indicates that the location report shall be refreshed immediately.	
requestLocationHistory	RequestLocationHistory	O	0..1	Includes details on requested location history information.	
requestHistoryStatus	booelan	O	0..1	Indicates that a location history status is requested.	
NOTE: At least one of functionalAliasIDs, mcServiceIds or mcServiceGroupIds shall be present.					

7.2.6.2.3 Type: MCUserLocation

Table 7.2.6.2.3-1: Definition of type MCUserLocation

Attribute name	Data type	P	Cardinality	Description	Applicability
mcServiceIds	array(Uri)	M	1..N	A list of MC service IDs of the MC user for which location information is reported.	
functionalAliasIds	array(Uri)	O	1..N	A list of activated Functional Alias Id of the MC user for which location information is reported.	
mcServiceUELabel	String	O	0..1	Used to identify the MC service UE.	
locationInfo	LocationInfo	M	1	As defined in clause 7.2.6.2.3	

7.2.6.2.4 Type: LocationNotification

Table 7.2.6.2.4-1: Definition of type LocationNotification

Attribute name	Data type	P	Cardinality	Description	Applicability
mcUEResponseList	array(MCUser Location)	M	1..N	Represents one array of MC Users' device location information.	
requestingMcServiceId	Uri	M	1	The MC service ID of the LMC that requested the location report.	
requestingfunctionalAliasId	Uri	O	0..1	The activated Functional Alias Id of the LMC that requested the location report.	
subscriptionID	string	O	0..1	Optional attribute including the subscriptionID when the location notification is related to an existing subscription. (NOTE)	
NOTE: The subscriptionID is mandatory if the location notification is sent due to a location subscription.					

7.2.6.2.5 Type: LocationSubscriptionRequest

Table 7.2.6.2.5-1: Definition of type LocationSubscriptionRequest

Attribute name	Data type	P	Cardinality	Description	Applicability
expTime	DateTime	M	1	The subscription expiry time and date.	
functionalAliasIds	array(Uri)	O	1..N	A list of activated Functional Alias Id of subscribed MC Users. (NOTE)	
locationNotificationUri	Uri	M	1	URI where the Location Notifications should be delivered to.	
mclocClientID	string	M	1	Used to identify the LMC that makes a subscription request.	
mcServiceIds	array(Uri)	O	1..N	A list of MC service IDs of the MC users for which location information is subscribed. (NOTE)	
mcServiceGroupIds	array(Uri)	O	1..N	A list of MC service group IDs of which all affiliated members' location information are subscribed. (NOTE)	
NOTE: At least one of functionalAliasIDs, mcServiceIds or mcServiceGroupIds shall be present.					

7.2.6.3 Simple data types and enumerations

No simple data types or enumerations defined.

7.2.7 Error Handling

7.2.7.1 General

For the LMS_Information API, HTTP error responses shall be supported as specified in clause 4.8 of 3GPP TS 29.501 [14]. Protocol errors and application errors specified in table 5.2.7.2-1 of 3GPP TS 29.500 [13] shall be supported for an HTTP method if the corresponding HTTP status codes are specified as mandatory for that HTTP method in table 5.2.7.1-1 of 3GPP TS 29.500 [13].

In addition, the requirements in the following clauses are applicable for the LMS_Information API.

7.2.7.2 Protocol Errors

No specific procedures for the LMS_Information service are specified.

7.2.7.3 Application Errors

The application errors defined for the LMS_Information service are listed in table 7.2.7.3-1.

Table 7.2.7.3-1: Application errors

Application Error	HTTP status code	Description

7.2.8 Feature negotiation

Table 7.2.8-1 defines the features supported by the LMS_Information API. They shall be negotiated using the extensibility mechanism defined in clause 6.6 of 3GPP TS 29.500 [13].

No feature is defined in this release of the specification.

Table 7.2.8-1: Supported Features

Feature number	Feature Name	M/O	Description

7.2.9 Security

The LMC shall send HTTP requests over TLS connection as specified for the HTTP client in the UE in annex A of 3GPP TS 24.482 [10].

Authentication and authorization shall be as specified in 3GPP TS 33.180 [17].

The LMS shall be configured with an authorized MC service server list, containing public service identities of MC service servers.

When handling an HTTP request, the LMS shall determine the identity of the sender of the HTTP request as specified in 3GPP TS 24.482 [10], and shall use the identity of the sender of the HTTP request as an authenticated identity when performing the authorization.

7.2.10 HTTP redirection

An HTTP request may be redirected to a different LMS service instance, within the same LMS. When an HTTP server redirects an HTTP request (i.e. service request or notification/callback request) to a different target LMS service instance, the URI of the target LMS service instance towards which the request is redirected shall be given by the Location header field of the 307 Temporary Redirect or 308 Permanent Redirect response. Further details on HTTP redirection are found in 3GPP TS 29.500 [13].

Annex A (normative): OpenAPI specification

A.1 General

This Annex specifies the formal definition of the API(s) defined in the present specification. It consists of OpenAPI specifications in YAML format.

This Annex takes precedence when being discrepant to other parts of the specification with respect to the encoding of information elements and methods within the API(s).

NOTE: The semantics and procedures, as well as conditions, e.g. for the applicability and allowed combinations of attributes or values, not expressed in the OpenAPI definitions but defined in other parts of the specification also apply.

Informative copies of the OpenAPI specification files contained in this 3GPP Technical Specification are available on a Git-based repository that uses the GitLab software version control system (see clause 5.3.1 of 3GPP TS 29.501 [14] and clause 5B of 3GPP TR 21.900 [1]).

A.2 LMS_Reporting API

```
openapi: 3.0.0

info:
  title: LMS_Reporting
  version: 1.0.1
  description: |
    API for Registration and location reporting to LMS Service.
    © 2025, 3GPP Organizational Partners (ARIB, ATIS, CCSA, ETSI, TSDSI, TTA, TTC).
    All rights reserved.

externalDocs:
  description: 3GPP TS 24.283 V19.3.0; Mission Critical Location Management (MCLoc).
  url: http://www.3gpp.org/ftp/Specs/archive/24_series/24.283/

servers:
  - url: '{apiRoot}/lms-reporting/v1'
    variables:
      apiRoot:
        default: https://example.com
        description: apiRoot as defined in clause 8.2.44D1 of 3GPP TS 24.483

security:
  - BearerAuth: []

paths:
  /registrations:
    post:
      description: Creates a new indiviual LMC registration in the LMS.
      security:
        - BearerAuth: []
      operationId: registerLMC
      tags:
        - LMS Registration (Collection)
      requestBody:
        required: true
        content:
          application/json:
            schema:
              $ref: '#/components/schemas/LMCRegistration'
      responses:
        '201':
          description: Successful regitration of LMC.
          content:
            application/json:
              schema:
                $ref: '#/components/schemas/LMCRegistration'
```

```
      headers:
        Location:
          description: Contains the URI of the newly created resource.
          required: true
          schema:
            type: string
    '400':
      $ref: 'TS29571_CommonData.yaml#/components/responses/400'
    '401':
      $ref: 'TS29571_CommonData.yaml#/components/responses/401'
    '403':
      $ref: 'TS29571_CommonData.yaml#/components/responses/403'
    '404':
      $ref: 'TS29571_CommonData.yaml#/components/responses/404'
    '411':
      $ref: 'TS29571_CommonData.yaml#/components/responses/411'
    '413':
      $ref: 'TS29571_CommonData.yaml#/components/responses/413'
    '415':
      $ref: 'TS29571_CommonData.yaml#/components/responses/415'
    '429':
      $ref: 'TS29571_CommonData.yaml#/components/responses/429'
    '500':
      $ref: 'TS29571_CommonData.yaml#/components/responses/500'
    '503':
      $ref: 'TS29571_CommonData.yaml#/components/responses/503'
    default:
      $ref: 'TS29571_CommonData.yaml#/components/responses/default'
  callbacks:
    locationConfiguration:
      '{request.body#/locationConfigUri}':
        post:
          requestBody:
            required: true
            content:
              application/json:
                schema:
                  $ref: '#/components/schemas/LocationConfiguration'
          responses:
            '204':
              description: No Content (The receipt of the Configuration is acknowledged).
            '307':
              $ref: 'TS29571_CommonData.yaml#/components/responses/307'
            '308':
              $ref: 'TS29571_CommonData.yaml#/components/responses/308'
            '400':
              $ref: 'TS29571_CommonData.yaml#/components/responses/400'
            '401':
              $ref: 'TS29571_CommonData.yaml#/components/responses/401'
            '403':
              $ref: 'TS29571_CommonData.yaml#/components/responses/403'
            '404':
              $ref: 'TS29571_CommonData.yaml#/components/responses/404'
            '411':
              $ref: 'TS29571_CommonData.yaml#/components/responses/411'
            '413':
              $ref: 'TS29571_CommonData.yaml#/components/responses/413'
            '415':
              $ref: 'TS29571_CommonData.yaml#/components/responses/415'
            '429':
              $ref: 'TS29571_CommonData.yaml#/components/responses/429'
            '500':
              $ref: 'TS29571_CommonData.yaml#/components/responses/500'
            '503':
              $ref: 'TS29571_CommonData.yaml#/components/responses/503'
            default:
              $ref: 'TS29571_CommonData.yaml#/components/responses/default'
    locationRequest:
      '{request.body#/locationRequestUri}':
        post:
          requestBody:
            required: true
            content:
              application/json:
                schema:
                  $ref: '#/components/schemas/LocationRequest'
          responses:
            '200':
```

```
                description: Location report.
                content:
                  application/json:
                    schema:
                      $ref: '#/components/schemas/MCUELocation'
              '307':
                $ref: 'TS29571_CommonData.yaml#/components/responses/307'
              '308':
                $ref: 'TS29571_CommonData.yaml#/components/responses/308'
              '400':
                $ref: 'TS29571_CommonData.yaml#/components/responses/400'
              '401':
                $ref: 'TS29571_CommonData.yaml#/components/responses/401'
              '403':
                $ref: 'TS29571_CommonData.yaml#/components/responses/403'
              '404':
                $ref: 'TS29571_CommonData.yaml#/components/responses/404'
              '411':
                $ref: 'TS29571_CommonData.yaml#/components/responses/411'
              '413':
                $ref: 'TS29571_CommonData.yaml#/components/responses/413'
              '415':
                $ref: 'TS29571_CommonData.yaml#/components/responses/415'
              '429':
                $ref: 'TS29571_CommonData.yaml#/components/responses/429'
              '500':
                $ref: 'TS29571_CommonData.yaml#/components/responses/500'
              '503':
                $ref: 'TS29571_CommonData.yaml#/components/responses/503'
              default:
                $ref: 'TS29571_CommonData.yaml#/components/responses/default'


  /registrations/{registrationId}:
    put:
      description: >
        Updates an existing LMC registration in the LMS
      tags:
        - Individual LMS registration (Document)
      parameters:
        - name: registrationId
          in: path
          description: Identifies an individual LMC registration resource.
          required: true
          schema:
            type: string
      requestBody:
        description: Parameters to replace the existing subscription.
        required: true
        content:
          application/json:
            schema:
              $ref: '#/components/schemas/LMCRegistration'
      responses:
        '200':
          description: >
            OK. The individual LMC registration resource was updated successfully.
          content:
            application/json:
              schema:
                $ref: '#/components/schemas/LMCRegistration'
        '204':
          description: No Content (updated successfully).
        '400':
          $ref: 'TS29571_CommonData.yaml#/components/responses/400'
        '401':
          $ref: 'TS29571_CommonData.yaml#/components/responses/401'
        '403':
          $ref: 'TS29571_CommonData.yaml#/components/responses/403'
        '404':
          $ref: 'TS29571_CommonData.yaml#/components/responses/404'
        '411':
          $ref: 'TS29571_CommonData.yaml#/components/responses/411'
        '413':
          $ref: 'TS29571_CommonData.yaml#/components/responses/413'
        '415':
          $ref: 'TS29571_CommonData.yaml#/components/responses/415'
        '429':
```

```
        $ref: 'TS29571_CommonData.yaml#/components/responses/429'
      '500':
        $ref: 'TS29571_CommonData.yaml#/components/responses/500'
      '503':
        $ref: 'TS29571_CommonData.yaml#/components/responses/503'
      default:
        $ref: 'TS29571_CommonData.yaml#/components/responses/default'

  delete:
    description: >
      Deletes an existing LMC reigstration identified by the registrationId.
    operationId: DeleteLMCRegistration
    tags:
      - Individual LMC registration (Document)
    parameters:
      - name: registrationId
        in: path
        description: Identifies an LMC registration resource.
        required: true
        schema:
          type: string
    responses:
      '204':
        description: >
          An individual LMC registration resource deleted successfully.
      '307':
        $ref: 'TS29571_CommonData.yaml#/components/responses/307'
      '308':
        $ref: 'TS29571_CommonData.yaml#/components/responses/308'
      '400':
        $ref: 'TS29571_CommonData.yaml#/components/responses/400'
      '401':
        $ref: 'TS29571_CommonData.yaml#/components/responses/401'
      '403':
        $ref: 'TS29571_CommonData.yaml#/components/responses/403'
      '404':
        $ref: 'TS29571_CommonData.yaml#/components/responses/404'
      '429':
        $ref: 'TS29571_CommonData.yaml#/components/responses/429'
      '500':
        $ref: 'TS29571_CommonData.yaml#/components/responses/500'
      '503':
        $ref: 'TS29571_CommonData.yaml#/components/responses/503'
      default:
        $ref: 'TS29571_CommonData.yaml#/components/responses/default'

/locationreports:
  post:
    summary: submit a MC UE location report
    security:
      - BearerAuth: []
    operationId: submitLocationReport
    tags:
      - MC UE Location Report (Collection)
    requestBody:
      required: true
      content:
        application/json:
          schema:
            $ref: '#/components/schemas/MCUELocation'
    responses:
      '201':
        description: Successful submission of location report.
        content:
          application/json:
            schema:
              $ref: '#/components/schemas/MCUELocation'
      '400':
        $ref: 'TS29571_CommonData.yaml#/components/responses/400'
      '401':
        $ref: 'TS29571_CommonData.yaml#/components/responses/401'
      '403':
        $ref: 'TS29571_CommonData.yaml#/components/responses/403'
      '404':
        $ref: 'TS29571_CommonData.yaml#/components/responses/404'
      '411':
        $ref: 'TS29571_CommonData.yaml#/components/responses/411'
      '413':
```

```
        $ref: 'TS29571_CommonData.yaml#/components/responses/413'
      '415':
        $ref: 'TS29571_CommonData.yaml#/components/responses/415'
      '429':
        $ref: 'TS29571_CommonData.yaml#/components/responses/429'
      '500':
        $ref: 'TS29571_CommonData.yaml#/components/responses/500'
      '503':
        $ref: 'TS29571_CommonData.yaml#/components/responses/503'
      default:
        $ref: 'TS29571_CommonData.yaml#/components/responses/default'

  /configurations:
    get:
      summary: request to download the location configuration
      security:
        - BearerAuth: []
      operationId: ConfigurationRequest
      tags:
        - LMC configurations (Collection)
      responses:
        '200':
          description: Successful submission of location report.
          content:
            application/json:
              schema:
                $ref: '#/components/schemas/LocationConfiguration'
        '307':
          $ref: 'TS29571_CommonData.yaml#/components/responses/307'
        '308':
          $ref: 'TS29571_CommonData.yaml#/components/responses/308'
        '400':
          $ref: 'TS29571_CommonData.yaml#/components/responses/400'
        '401':
          $ref: 'TS29571_CommonData.yaml#/components/responses/401'
        '403':
          $ref: 'TS29571_CommonData.yaml#/components/responses/403'
        '404':
          $ref: 'TS29571_CommonData.yaml#/components/responses/404'
        '406':
          $ref: 'TS29571_CommonData.yaml#/components/responses/406'
        '429':
          $ref: 'TS29571_CommonData.yaml#/components/responses/429'
        '500':
          $ref: 'TS29571_CommonData.yaml#/components/responses/500'
        '503':
          $ref: 'TS29571_CommonData.yaml#/components/responses/503'
        default:
          $ref: 'TS29571_CommonData.yaml#/components/responses/default'


components:
  securitySchemes:
    BearerAuth:
      type: http
      scheme: bearer

# API specific definitions

  schemas:

    LMCRegistration:
      description: Respresents an individual LMS registration resource.
      type: object
      properties:
        expTime:
          type: string
          format: date-time
        mclocClientID:
          type: string
          description: Identify the LMC of the MC UE
        locationConfigUri:
          $ref: 'TS29571_CommonData.yaml#/components/schemas/Uri'
        locationRequestUri:
          $ref: 'TS29571_CommonData.yaml#/components/schemas/Uri'
        pei:
          $ref: 'TS29571_CommonData.yaml#/components/schemas/Pei'
        supi:
```

```
        $ref: 'TS29571_CommonData.yaml#/components/schemas/Supi'
    required:
      - mclocClientID
      - expTime
      - locationConfigUri
      - locationRequestUri

  LocationConfiguration:
    description: Represents an location configuraion objects sent from LMS to an LMC
    type: object
    properties:
      emergencyTriggeringCriteria:
        $ref: '#/components/schemas/TriggeringCriteria'
      emergencyLocationInformation:
        $ref: '#/components/schemas/RequestedLocationInfo'
      triggeringCriteria:
        $ref: '#/components/schemas/TriggeringCriteria'
      nonEmergencyLocationInformation:
        $ref: '#/components/schemas/RequestedLocationInfo'
      mcServiceId:
        type: string
        format: Uri
        description: Optional attribute that is used to indicate the identity of the
          MC user requesting to set the location configuration.
      configScope:
        $ref: '#/components/schemas/ConfigScope'
      historyReporting:
        type: boolean
        description: The attribute indicates that the LMC shall store location
          information if location reporting can not be done, for example if the MC UE is out of
          coverage. The stored location information can be reported at a later time.



  TriggeringCriteria:
    description: Contains the location reporting trigger criteria.
    type: object
    properties:
      adaptiveTrigger:
        $ref: '#/components/schemas/AdaptiveTrigger'
      cellChange:
        $ref: '#/components/schemas/CellChange'
      geographicalAreaChange:
        $ref: '#/components/schemas/GeographicalAreaChange'
      mbsfnAreaChange:
        $ref: '#/components/schemas/MbsfnAreaChange'
      mbmsSaChange:
        $ref: '#/components/schemas/MbmsSaChange'
      nr5GMbsfsaAreaChange:
        $ref: '#/components/schemas/NR5GMbsfsaAreaChange'
      periodicReport:
        $ref: '#/components/schemas/PeriodicReport'
      plmnChange:
        $ref: '#/components/schemas/PlmnChange'
      ratTypeChange:
        $ref: '#/components/schemas/RatTypeChange'
      signallingEvent:
        $ref: '#/components/schemas/SignallingEvent'
      trackingAreaChange:
        $ref: '#/components/schemas/TrackingAreaChange'
      travelledDistance:
        $ref: '#/components/schemas/TravelledDistance'


  AdaptiveTrigger:
    description: This attribute specifies parameters controlling adaptive combined time
      and distance triggers for location reporting.
    type: object
    properties:
      triggerId:
        $ref: '#/components/schemas/TriggerId'
      minPeriod:
        type: integer
        description: An optional attribute specified as a positive or 0 integer number
          of seconds and defaulting at 0, if not present. This attribute specifies the minimum
          wait period between consecutive location reports, irrespective of changes in the
          distance between the current location and the location of the most recent sending of a
```

```
        location report.
      minDistance:
       type: integer
       description: An optional attribute specified as a strictly positive integer number of
         meters and defaulting at infinity, if not present. This attribute is used in the
         decision of sending a location report based on travelled distance, and specifies the
         minimum required distance, between the current location and the location of the most
         recent sending of a location report.
      persistencePeriod:
        type: integer
        description: An optional attribute specified as a positive or 0 integer number of
          seconds and defaulting at 0, if not present. This attribute specifies the time between
          the moment when the LMC detected that the distance between the current location and
          the location of the most recent sending of a location report exceeded the minDistance
          attribute and the moment when the LMC will check again that the updated current
          location is still farther away by at least minDistance from the location of the
          mentioned sending of the location report. If the check is positive, a location report
          based on travelled distance will be sent.
      additionalTime:
        type: integer
        description: An optional attribute, specified as a strictly positive integer number of
          seconds and defaulting at 1. If a location report is not sent based on the travelled
          distance, the LMC will send a location report after minPeriod + PersistencePeriod
          + AdditionalTime seconds after the previous location report.
      rrcInactiveMinPeriod:
        type: integer
        description: An optional attribute with the same semantics and behaviour as described
          above for the corresponding parameter, but applicable when the UE receives MBS traffic
          in RRC_INACTIVE state.
      rrcInactiveMinDistance:
        type: integer
        description: An optional attribute with the same semantics and behaviour as described
          above for the corresponding parameter, but applicable when the UE receives MBS traffic
          in RRC_INACTIVE state.
      rrcInactivePersistencePeriod:
        type: integer
        description: An optional attribute with the same semantics and behaviour as described
          above for the corresponding parameter, but applicable when the UE receives MBS traffic
          in RRC_INACTIVE state.
      rrcInactiveadditionalTime:
        type: integer
        description: An optional attribute with the same semantics and behaviour as described
          above for the corresponding parameter, but applicable when the UE receives MBS traffic
          in RRC_INACTIVE state.


  CellChange:
    description: The attribute specifies which cell changes trigger location reporting.
    type: object
    properties:
      anyCellChange:
        $ref: '#/components/schemas/AnyCellChange'
      enterSpecificCell:
        $ref: '#/components/schemas/SpecificCellChange'
      exitSpecificCell:
        $ref: '#/components/schemas/SpecificCellChange'

  AnyCellChange:
    description: The presence of this attribute specifies that any cell change
      is a trigger for location reporting.
    type: object
    properties:
      triggerId:
        $ref: '#/components/schemas/TriggerId'

  SpecificCellChange:
    description: A list of cell Ids which triggers location reporting when
      entering or exiting the cells.
    type: object
    properties:
      eutranCells:
        $ref: '#/components/schemas/EutranCells'
      nrCells:
        $ref: '#/components/schemas/NrCells'
    anyOf:
      - required: [eutranCells]
      - required: [nrCells]
```

```
    EutranCells:
      description: A list of Eutran cell Ids which triggers location reporting when
        entering or exiting the cells.
      type: array
      items:
        $ref: '#/components/schemas/EutranCell'

    NrCells:
      description: A list of NR cell Ids which triggers location reporting when
        entering or exiting the cells.
      type: array
      items:
        $ref: '#/components/schemas/NrCell'

    EutranCell:
      description: An Eutran cell id that triggers a location reporting.
      type: object
      properties:
        triggerId:
          $ref: '#/components/schemas/TriggerId'
        eutranCell:
          $ref: 'TS29571_CommonData.yaml#/components/schemas/Ecgi'

    NrCell:
      description: A NR cell id that triggers location reporting.
      type: object
      properties:
        triggerId:
          $ref: '#/components/schemas/TriggerId'
        nrCell:
          $ref: 'TS29571_CommonData.yaml#/components/schemas/Ncgi'



    GeographicalAreaChange:
      description: The attribute specifies which geographical area changes that
        trigger location reporting.
      type: object
      properties:
        enterSpecifcArea:
          $ref: '#/components/schemas/SpecificArea'
        exitSpecifcArea:
          $ref: '#/components/schemas/SpecificArea'



    SpecificArea:
      description: A geographical area which triggers location reporting when
        entering or exiting the defined geographical area.
      type: object
      properties:
        geoAreas:
          type: array
          items:
            $ref: 'TS29572_Nlmf_Location.yaml#/components/schemas/GeographicArea'


    MbsfnAreaChange:
      description: The attribute specifies which MBSFN area changes trigger
        location reporting.
      type: object
      properties:
        anyMbfsnAreaChange:
          $ref: '#/components/schemas/AnyMbsfnAreaChange'
        enterSpecificMbsfnArea:
          $ref: '#/components/schemas/SpecificMbsfnArea'
        exitSpecificMbsfnArea:
          $ref: '#/components/schemas/SpecificMbsfnArea'

    AnyMbsfnAreaChange:
      description: The precense of this attribute specifies that any MBSFN area change
        is a trigger for location reporting.
      type: object
      properties:
        triggerId:
          $ref: '#/components/schemas/TriggerId'

    SpecificMbsfnArea:
```

```
    description: A list of MBSFN area Ids that triggers location reporting when
      entering or exiting the MBSFN area Ids.
    type: object
    properties:
      mbsfnAreas:
        type: array
        items:
          $ref: '#/components/schemas/MbsfnAreaId'


  MbsfnAreaId:
    description: An MBFSN area id that triggers location reporting.
    type: object
    properties:
      triggerId:
        $ref: '#/components/schemas/TriggerId'
      mbsfnArea:
        type: integer
        minimum: 0
        maximum: 255
        description: The MBSFN area identity.



  MbmsSaChange:
    description: The attribute specifies which MBMS SA area changes trigger
      location reporting.
    type: object
    properties:
      anyMbmsSaChange:
        $ref: '#/components/schemas/AnyMbmsSaChange'
      enterSpecificMbmsSa:
        $ref: '#/components/schemas/SpecificMbmsSaIdentity'
      exitSpecificMbmsSa:
        $ref: '#/components/schemas/SpecificMbmsSaIdentity'

  AnyMbmsSaChange:
    description: The presence of this element specifies that any MBMS SA change
      is a trigger for location reporting.
    type: object
    properties:
      triggerId:
        $ref: '#/components/schemas/TriggerId'

  SpecificMbmsSaIdentity:
    description: A list of MBMS SAI that triggers location reporting when
      entering or exiting the MBMS SAI.
    type: object
    properties:
      mbmsSaIdentities:
        type: array
        items:
          $ref: '#/components/schemas/MbmsSaIdentity'


  MbmsSaIdentity:
    description: An MBMS SA identity that triggers location reporting.
    type: object
    properties:
      triggerId:
        $ref: '#/components/schemas/TriggerId'
      mbmsSaIdentity:
        type: integer
        minimum: 0
        maximum: 65535
        description: The MBMS SA identity.



  NR5GMbsfsaAreaChange:
    description: The attribute specifies which 5G Mbsfsa area changes trigger
      location reporting.
    type: object
    properties:
      anyNR5GMbsfsaAreaChange:
        $ref: '#/components/schemas/AnyNR5GMbsfsaAreaChange'
      enterSpecificNR5GMbsfsaArea:
```

```
      $ref: '#/components/schemas/SpecificNR5GMbsfsaArea'
    exitSpecificNR5GMbsfsaArea:
      $ref: '#/components/schemas/SpecificNR5GMbsfsaArea'

AnyNR5GMbsfsaAreaChange:
  description: The presence of this element specifies that any 5G Mbsfsa area change
    is a trigger for location reporting.
  type: object
  properties:
    triggerId:
      $ref: '#/components/schemas/TriggerId'

SpecificNR5GMbsfsaArea:
  description: A list of 5G Mbsfsa area that triggers a location reporting when
    entering or exiting the 5G Mbsfsa area.
  type: object
  properties:
    nr5GMbsFsaIdentities:
      type: array
      items:
        $ref: '#/components/schemas/NR5GMbsfsaAreaIdentity'

NR5GMbsfsaAreaIdentity:
  description: An 5G Mbsfsa area identity that triggers location reporting.
  type: object
  properties:
    triggerId:
      $ref: '#/components/schemas/TriggerId'
    mbsfnAreaIdentity:
      $ref: 'TS29571_CommonData.yaml#/components/schemas/MbsFsaId'



PeriodicReport:
  description: The attribute specifies how frequent periodic location reports
    shall be sent.
  type: object
  properties:
    triggerId:
      $ref: '#/components/schemas/TriggerId'
    periodicReport:
      type: integer
      description: Value in seconds specifies the reporting interval.



PlmnChange:
  description: The attribute specifies which PLMN changes trigger
    location reporting.
  type: object
  properties:
    anyPlmnChange:
      $ref: '#/components/schemas/AnyPlmnChange'
    enterSpecificPlmnArea:
      $ref: '#/components/schemas/SpecificPlmnChange'
    exitSpecificPlmnArea:
      $ref: '#/components/schemas/SpecificPlmnChange'

AnyPlmnChange:
  description: The presence of this element specifies that any PLMN change
    is a trigger for location reporting.
  type: object
  properties:
    triggerId:
      $ref: '#/components/schemas/TriggerId'

SpecificPlmnChange:
  description: A list of PLMNs that triggers a location reporting when
    entering or exiting the PLMN.
  type: object
  properties:
    plmnIds:
      type: array
      items:
        $ref: '#/components/schemas/Plmn'

Plmn:
  description: A PLMN identity that triggers location reporting.
```

```
      type: object
      properties:
        triggerId:
          $ref: '#/components/schemas/TriggerId'
        plmn:
          $ref: 'TS29571_CommonData.yaml#/components/schemas/PlmnId'



    RatTypeChange:
      description: An optional attribute specifying what inter-RAT changes triggers
        a location report.
      type: object
      properties:
        anyRatTypeChange:
          $ref: '#/components/schemas/AnyRatTypeChange'

    AnyRatTypeChange:
      description: This attribute specifies that any inter-RAT change triggers a location report.
      type: object
      properties:
        triggerId:
          $ref: '#/components/schemas/TriggerId'



    SignallingEvent:
      description: An optional attribute specifying what signalling events triggers
        a location report.
      type: object
      properties:
        functionalAliasActivation:
          $ref: '#/components/schemas/FunctionalAliasActivation'
        functionalAliasDeactivation:
          $ref: '#/components/schemas/FunctionalAliasDeactivation'
        initialLogOn:
          $ref: '#/components/schemas/InitialLogOn'
        groupCallNonEmergency:
          $ref: '#/components/schemas/GroupCallNonEmergency'
        privateCallNonEmergency:
          $ref: '#/components/schemas/PrivateCallNonEmergency'
        locationConfigurationReceived:
          $ref: '#/components/schemas/LocationConfigurationReceived'

    FunctionalAliasActivation:
      description: This attribute specifies that a functional alias activation
        triggers a location report.
      type: object
      properties:
        triggerId:
          $ref: '#/components/schemas/TriggerId'

    FunctionalAliasDeactivation:
      description: This attribute specifies that a functional Alias deactivation
        triggers a location report.
      type: object
      properties:
        triggerId:
          $ref: '#/components/schemas/TriggerId'

    InitialLogOn:
      description: This attribute specifies that an initial log on triggers a location report.
      type: object
      properties:
        triggerId:
          $ref: '#/components/schemas/TriggerId'

    GroupCallNonEmergency:
      description: This attribute specifies that a non-emergency group call triggers
        a location report.
      type: object
      properties:
        triggerId:
          $ref: '#/components/schemas/TriggerId'

    PrivateCallNonEmergency:
      description: This attribute specifies that a non-emergency private call triggers
        a location report.
```

```
    type: object
    properties:
      triggerId:
        $ref: '#/components/schemas/TriggerId'

  LocationConfigurationReceived:
    description: This attribute specifies that a received location configuration triggers
      a location report.
    type: object
    properties:
      triggerId:
        $ref: '#/components/schemas/TriggerId'



  TrackingAreaChange:
    description: The attribute specifies which tracking area changes trigger
      location reporting.
    type: object
    properties:
      anyTrackingAreaChange:
        $ref: '#/components/schemas/AnyTrackingAreaChange'
      enterSpecificTrackingArea:
        $ref: '#/components/schemas/SpecificTrackingAreaChange'
      exitSpecificTrackingArea:
        $ref: '#/components/schemas/SpecificTrackingAreaChange'

  AnyTrackingAreaChange:
    description: The presence of this element specifies that any tracking area change
      is a trigger for location reporting.
    type: object
    properties:
      triggerId:
        $ref: '#/components/schemas/TriggerId'

  SpecificTrackingAreaChange:
    description: A list of tracking areas that triggers a location reporting when
      entering or exiting the tracking area.
    type: object
    properties:
      trackingAreas:
        type: array
        items:
          $ref: '#/components/schemas/TrackingArea'

  TrackingArea:
    description: A tracking area identity that triggers location reporting.
    type: object
    properties:
      triggerId:
        $ref: '#/components/schemas/TriggerId'
      trackingArea:
        $ref: 'TS29571_CommonData.yaml#/components/schemas/Tac'



  TravelledDistance:
    description: The attribute specifies the required travelled distance for a
      trigger for location reporting.
      shall be sent.
    type: object
    properties:
      triggerId:
        $ref: '#/components/schemas/TriggerId'
      travelledDistance:
        type: integer
        description: Value in meter specifies the travelled distance
          for location reporting.



  RequestedLocationInfo:
    description: Contains the details of what the location report shall include.
    type: object
    properties:
      bearingAndSpeed:
        type: boolean
        nullable: true
```

```
      description: The presence of this attribute indicates that the
        item shall be included in the location report.
    coordinate:
      type: boolean
      nullable: true
      description: The presence of this attribute indicates that the
        item shall be included in the location report.
    mbmsSaiId:
      type: boolean
      nullable: true
      description: The presence of this attribute indicates that the
        item shall be included in the location report.
    mbsfnArea:
      type: boolean
      nullable: true
      description: The presence of this attribute indicates that the
        item shall be included in the location report.
    minimumIntervalLength:
      type: integer
      description: Value in seconds, the minimum time between location reports.
    neigbouringEcgi:
      type: boolean
      nullable: true
      description: The presence of this attribute indicates that the
        item shall be included in the location report.
    neigbouringNcgi:
      type: boolean
      nullable: true
      description: The presence of this attribute indicates that the
        item shall be included in the location report.
    nr5GmbsfsaArea:
      type: boolean
      nullable: true
      description: The presence of this attribute indicates that the
        item shall be included in the location report.
    servingEcgi:
      type: boolean
      nullable: true
      description: The presence of this attribute indicates that the
        item shall be included in the location report.
    servingNcgi:
      type: boolean
      nullable: true
      description: The presence of this attribute indicates that the
        item shall be included in the location report.



TriggerId:
  type: string
  description: The triggerId shall be set to a unique value and is
    returned in the location report.



LocationRequest:
  description: Represents an location request object used by LMS to
    request a location report from an LMC.
  type: object
  properties:
    requestedMcServiceId:
      type: string
      format: uri
      description: The MC service ID of the MC user being requested to send a
        location report.
    requestingMcServiceId:
      type: string
      format: uri
      description: The MC service ID of the MC user from which location information
        is being requested.
    requestId:
      type: string
      description: Attribute is used as identifier of the location request and in the
        response to the request.
    requestedFunctionalAliasId:
      type: string
      format: uri
      description: The activated functional alias ID of the MC user being requested
```

```
        to send a location report.
    requestingFunctionalAliasId:
      type: string
      format: uri
      description: The activated functional alias ID of the MC user from which location
        information is being requested.
    requestedLocationInfo:
      $ref: '#/components/schemas/RequestedLocationInfo'
    requestLocationHistory:
      $ref: '#/components/schemas/RequestedLocationHistory'
    requestHistoryStatus:
      type: boolean
      description: This attribute indicates that a location history status report is requested.


ConfigScope:
  description: Indicates if the location configuration shall be updated fully and replace
    existing configration, or if the location configuration is added to the exsting.
  anyOf:
    - type: string
      enum:
        - FULL
        - UPDATE
    - type: string
      description: This string provides forward-compatibility with future extensions to the
        enumeration and is not used to encode content defined in the present version
        of this API.


RequestedLocationHistory:
  description: Includes details on requested location history information
  type: object
  properties:
    numberOfReports:
      type: integer
      description: Indicates the number of requested stored reports.
    startTime:
      $ref: 'TS29571_CommonData.yaml#/components/schemas/DateTime'
    endTime:
      $ref: 'TS29571_CommonData.yaml#/components/schemas/DateTime'
    triggerCriteria:
      $ref: '#/components/schemas/TriggeringCriteria'
    minimumIntervalLength:
      type: integer
      description: Value in seconds, the minimum time between location reports.


MCUELocation:
  description: Describes the parameters to perform LMS Location reports.
  type: object
  properties:
    functionalAlias:
      $ref: 'TS29571_CommonData.yaml#/components/schemas/Uri'
    interRatType:
      $ref: '#/components/schemas/InterRatType'
    locationData:
      $ref: '#/components/schemas/LocationInfo'
    locTimestamp:
      $ref: 'TS29571_CommonData.yaml#/components/schemas/DateTime'
    mclocClientId:
      $ref: '#/components/schemas/MclocClientId'
    mcServiceUELabel:
      type: string
      description: Used to identify the reporting MC UE for the end users, this may be used
        when multiple MC UEs are used by the same MC service user.
    reportId:
      type: string
      description: Attribute is used to return the value from the RequestId attribute
        in the Location Request.
    reportType:
      $ref: '#/components/schemas/ReportType'
    triggerId:
      type: array
      items:
        type: string
        description: Attribute which can occur multiple times that contain the value
          of the TriggerId attribute associated with a trigger that has fired.
```

```
      locationHistoryData:
        $ref: '#/components/schemas/LocationHistoryData'
      locationHistoryStatus:
        $ref: '#/components/schemas/LocationHistoryStatus'
  MclocClientId:
    type: string
    format: uuid
    description: Used to identify the reporting LMC, this is required when multiple location
      information responses for different requested LMC are sent.

  LocationInfo:
    description: object that includes coordinates typically obtained from GPS.
    type: object
    properties:
      currentCoordinate:
        $ref: '#/components/schemas/CurrentCoordinate'
      ecgi:
        $ref: 'TS29571_CommonData.yaml#/components/schemas/Ecgi'
      mbmsSaiId:
        type: integer
        minimum: 0
        maximum: 65535
        description: Attribute containing the MBMS Service Area Id the LMC is located in.
      mbsfnArea:
        $ref: 'TS29571_CommonData.yaml#/components/schemas/MbsfnArea'
      ncgi:
        $ref: 'TS29571_CommonData.yaml#/components/schemas/Ncgi'
      neighbouringEcgi:
        type: array
        items:
          $ref: 'TS29571_CommonData.yaml#/components/schemas/Ecgi'
      neighbouringNcgi:
        type: array
        items:
          $ref: 'TS29571_CommonData.yaml#/components/schemas/Ncgi'
      nr5GMbsfsaArea:
        $ref: 'TS29571_CommonData.yaml#/components/schemas/MbsFsaId'

  CurrentCoordinate:
    description: This object contains one specific location point, speed and bearing (e.g.
      received from a GPS reciever).
    type: object
    properties:
      altitude:
        anyOf:
          - $ref: 'TS29572_Nlmf_Location.yaml#/components/schemas/Altitude'
      bearingAndSpeed:
        anyOf:
          - $ref: 'TS29572_Nlmf_Location.yaml#/components/schemas/HorizontalWithVerticalVelocity'
      geographicalCoordinate:
        anyOf:
          - $ref: 'TS29572_Nlmf_Location.yaml#/components/schemas/GeographicalCoordinates'
      horizontalaccuracy:
        anyOf:
          - $ref: 'TS29572_Nlmf_Location.yaml#/components/schemas/Accuracy'
      verticalaccuracy:
        anyOf:
          - $ref: 'TS29572_Nlmf_Location.yaml#/components/schemas/Accuracy'



  LocationHistoryData:
    description: This object contains one or multiple time stamped location information reports.
    type: array
    items:
      $ref: '#/components/schemas/LocationHistoryEvent'


  LocationHistoryEvent:
    description: This object respresents a single location information report that has been
      stored in the LMC.
    type: object
    properties:
      locationData:
        $ref: '#/components/schemas/LocationInfo'
      locTimestamp:
        $ref: 'TS29571_CommonData.yaml#/components/schemas/DateTime'
      triggerId:
```

```
          type: array
          items:
            type: string
            description: Attribute which can occur multiple times that contain the value
              of the TriggerId attribute associated with a trigger that has fired.



    LocationHistoryStatus:
      description: This object respresents Location history summary status of the location reports
        that has been stored in the LMC and has not yet been reporeted.
      type: object
      properties:
        storedReports:
          type: integer
          description: set to the number of stored reports.
        startTime:
          $ref: 'TS29571_CommonData.yaml#/components/schemas/DateTime'
        endTime:
          $ref: 'TS29571_CommonData.yaml#/components/schemas/DateTime'
        triggerId:
          type: array
          items:
            type: string
            description: Attribute which can occur multiple times that contain the value
              of the TriggerId attribute associated with a trigger that has fired.


#
# Simple Types:
#


#
# Enumeration data types
#
    InterRatType:
      description: Attribute containing the inter-RAT change type.
      anyOf:
        - type: string
          enum:
            - 5G_MBS_TO_LTE_MBMS
            - 5G_MBS_TO_LTE_UNICAST
            - LTE_MBMS_TO_5G_MBS
            - LTE_MBMS_TO_5G_UNICAST
        - type: string
          description: This string provides forward-compatibility with future extensions to the
            enumeration and is not used to encode content defined in the present version
            of this API.

    ReportType:
      description: Used to inform whether the LMC is sending the report in an emergency
        situation or not.
      anyOf:
        - type: string
          enum:
            - EMERGENCY
            - NONEMERGENCY
        - type: string
          description: This string provides forward-compatibility with future extensions to the
            enumeration and is not used to encode content defined in the present version
            of this API.
```

A.3 LMS_Information API

```
openapi: 3.0.0

info:
  title: LMS_Information
  version: 1.0.0
  description: |
    API for Requesting and subscribing on Location Information from LMS Service.
    © 2025, 3GPP Organizational Partners (ARIB, ATIS, CCSA, ETSI, TSDSI, TTA, TTC).
    All rights reserved.

externalDocs:
  description: 3GPP TS 24.283 V19.1.0; Mission Critical Location Management (MCLoc).
  url: http://www.3gpp.org/ftp/Specs/archive/24_series/24.283/

servers:
  - url: '{apiRoot}/lms-information/v1'
    variables:
      apiRoot:
        default: https://example.com
        description: apiRoot as defined in clause 8.2.44D1 of 3GPP TS 24.483

security:
  - BearerAuth: []

paths:
  /requests:
    post:
      description: Creates a new indiviual client location request in the LMS.
      security:
        - BearerAuth: []
      operationId: requestLMC
      tags:
        - LMS Location Request (Collection)
      requestBody:
        required: true
        content:
          application/json:
            schema:
              $ref: '#/components/schemas/ClientOriginatingLocationRequest'
      responses:
        '201':
          description: Successful location request submitted from LMC.
          content:
            application/json:
              schema:
                $ref: '#/components/schemas/ClientOriginatingLocationRequest'
          headers:
            Location:
              description: Contains the URI of the newly created resource.
              required: true
              schema:
                type: string
        '400':
          $ref: 'TS29571_CommonData.yaml#/components/responses/400'
        '401':
          $ref: 'TS29571_CommonData.yaml#/components/responses/401'
        '403':
          $ref: 'TS29571_CommonData.yaml#/components/responses/403'
        '404':
          $ref: 'TS29571_CommonData.yaml#/components/responses/404'
        '411':
          $ref: 'TS29571_CommonData.yaml#/components/responses/411'
        '413':
          $ref: 'TS29571_CommonData.yaml#/components/responses/413'
        '415':
          $ref: 'TS29571_CommonData.yaml#/components/responses/415'
        '429':
          $ref: 'TS29571_CommonData.yaml#/components/responses/429'
        '500':
          $ref: 'TS29571_CommonData.yaml#/components/responses/500'
        '503':
          $ref: 'TS29571_CommonData.yaml#/components/responses/503'
        default:
          $ref: 'TS29571_CommonData.yaml#/components/responses/default'
      callbacks:
```

```
        locationRequestResponse:
          '{request.body#/locationNotificationUri}':
            post:
              requestBody:
                required: true
                content:
                  application/json:
                    schema:
                      $ref: '#/components/schemas/LocationNotification'
              responses:
                '204':
                  description: No Content (The receipt of the Configuration is acknowledged).
                '307':
                  $ref: 'TS29571_CommonData.yaml#/components/responses/307'
                '308':
                  $ref: 'TS29571_CommonData.yaml#/components/responses/308'
                '400':
                  $ref: 'TS29571_CommonData.yaml#/components/responses/400'
                '401':
                  $ref: 'TS29571_CommonData.yaml#/components/responses/401'
                '403':
                  $ref: 'TS29571_CommonData.yaml#/components/responses/403'
                '404':
                  $ref: 'TS29571_CommonData.yaml#/components/responses/404'
                '411':
                  $ref: 'TS29571_CommonData.yaml#/components/responses/411'
                '413':
                  $ref: 'TS29571_CommonData.yaml#/components/responses/413'
                '415':
                  $ref: 'TS29571_CommonData.yaml#/components/responses/415'
                '429':
                  $ref: 'TS29571_CommonData.yaml#/components/responses/429'
                '500':
                  $ref: 'TS29571_CommonData.yaml#/components/responses/500'
                '503':
                  $ref: 'TS29571_CommonData.yaml#/components/responses/503'
                default:
                  $ref: 'TS29571_CommonData.yaml#/components/responses/default'

  /subscriptions:
    post:
      description: Creates a new location subscription in the LMS.
      security:
        - BearerAuth: []
      operationId: LMSsubscriptions
      tags:
        - Location Subscription Request (Collection)
      requestBody:
        required: true
        content:
          application/json:
            schema:
              $ref: '#/components/schemas/LocationSubscriptionRequest'
      responses:
        '201':
          description: Successful location subscription request submitted to LMS.
          content:
            application/json:
              schema:
                $ref: '#/components/schemas/LocationSubscriptionRequest'
          headers:
            Location:
              description: Contains the URI of the newly created resource.
              required: true
              schema:
                type: string
        '400':
          $ref: 'TS29571_CommonData.yaml#/components/responses/400'
        '401':
          $ref: 'TS29571_CommonData.yaml#/components/responses/401'
        '403':
          $ref: 'TS29571_CommonData.yaml#/components/responses/403'
        '404':
          $ref: 'TS29571_CommonData.yaml#/components/responses/404'
        '411':
          $ref: 'TS29571_CommonData.yaml#/components/responses/411'
        '413':
          $ref: 'TS29571_CommonData.yaml#/components/responses/413'
```

```
      '415':
        $ref: 'TS29571_CommonData.yaml#/components/responses/415'
      '429':
        $ref: 'TS29571_CommonData.yaml#/components/responses/429'
      '500':
        $ref: 'TS29571_CommonData.yaml#/components/responses/500'
      '503':
        $ref: 'TS29571_CommonData.yaml#/components/responses/503'
      default:
        $ref: 'TS29571_CommonData.yaml#/components/responses/default'
    callbacks:
      subscriptionNotification:
        '{request.body#/subscriptionResponseUri}':
          post:
            requestBody:
              required: true
              content:
                application/json:
                  schema:
                    $ref: '#/components/schemas/LocationNotification'
            responses:
              '204':
                description: No Content (The receipt of the subscription notification
                  is acknowledged).
              '307':
                $ref: 'TS29571_CommonData.yaml#/components/responses/307'
              '308':
                $ref: 'TS29571_CommonData.yaml#/components/responses/308'
              '400':
                $ref: 'TS29571_CommonData.yaml#/components/responses/400'
              '401':
                $ref: 'TS29571_CommonData.yaml#/components/responses/401'
              '403':
                $ref: 'TS29571_CommonData.yaml#/components/responses/403'
              '404':
                $ref: 'TS29571_CommonData.yaml#/components/responses/404'
              '411':
                $ref: 'TS29571_CommonData.yaml#/components/responses/411'
              '413':
                $ref: 'TS29571_CommonData.yaml#/components/responses/413'
              '415':
                $ref: 'TS29571_CommonData.yaml#/components/responses/415'
              '429':
                $ref: 'TS29571_CommonData.yaml#/components/responses/429'
              '500':
                $ref: 'TS29571_CommonData.yaml#/components/responses/500'
              '503':
                $ref: 'TS29571_CommonData.yaml#/components/responses/503'
              default:
                $ref: 'TS29571_CommonData.yaml#/components/responses/default'


  /subscriptions/{subscriptionId}:
    put:
      description: >
        Updates an existing location subscription identified by the subscriptionId.
      operationId: UpdateLocationSub
      tags:
        - Update Location subscription (Document)
      parameters:
        - name: subscriptionId
          in: path
          description: Identifies an individual location subscription resource.
          required: true
          schema:
            type: string
      requestBody:
        description: Parameters to replace the existing subscription.
        required: true
        content:
          application/json:
            schema:
              $ref: '#/components/schemas/LocationSubscriptionRequest'
      responses:
        '200':
          description: >
            OK. The location subcsription resource was updated successfully.
          content:
```

```
          application/json:
            schema:
              $ref: '#/components/schemas/LocationSubscriptionRequest'
      '204':
        description: No Content (updated successfully).
      '400':
        $ref: 'TS29571_CommonData.yaml#/components/responses/400'
      '401':
        $ref: 'TS29571_CommonData.yaml#/components/responses/401'
      '403':
        $ref: 'TS29571_CommonData.yaml#/components/responses/403'
      '404':
        $ref: 'TS29571_CommonData.yaml#/components/responses/404'
      '411':
        $ref: 'TS29571_CommonData.yaml#/components/responses/411'
      '413':
        $ref: 'TS29571_CommonData.yaml#/components/responses/413'
      '415':
        $ref: 'TS29571_CommonData.yaml#/components/responses/415'
      '429':
        $ref: 'TS29571_CommonData.yaml#/components/responses/429'
      '500':
        $ref: 'TS29571_CommonData.yaml#/components/responses/500'
      '503':
        $ref: 'TS29571_CommonData.yaml#/components/responses/503'
      default:
        $ref: 'TS29571_CommonData.yaml#/components/responses/default'

  delete:
    description: >
      Deletes an location subscription identified by the subscriptionId.
    operationId: DeleteLocationSub
    tags:
      - Delete location Subscription (Document)
    parameters:
      - name: subscriptionId
        in: path
        description: Identifies an individual location subscription resource.
        required: true
        schema:
          type: string
    responses:
      '204':
        description: >
          A location subscription resource deleted successfully.
      '307':
        $ref: 'TS29571_CommonData.yaml#/components/responses/307'
      '308':
        $ref: 'TS29571_CommonData.yaml#/components/responses/308'
      '400':
        $ref: 'TS29571_CommonData.yaml#/components/responses/400'
      '401':
        $ref: 'TS29571_CommonData.yaml#/components/responses/401'
      '403':
        $ref: 'TS29571_CommonData.yaml#/components/responses/403'
      '404':
        $ref: 'TS29571_CommonData.yaml#/components/responses/404'
      '429':
        $ref: 'TS29571_CommonData.yaml#/components/responses/429'
      '500':
        $ref: 'TS29571_CommonData.yaml#/components/responses/500'
      '503':
        $ref: 'TS29571_CommonData.yaml#/components/responses/503'
      default:
        $ref: 'TS29571_CommonData.yaml#/components/responses/default'

/configrequest:
  post:
    description: Requests server to update location reporting configuraton for a target user
    security:
      - BearerAuth: []
    operationId: configrequestLMC
    tags:
      - LMS Location Info Config Request (Collection)
    requestBody:
      required: true
      content:
        application/json:
```

```
            schema:
              $ref: 'TS24283_Lms_Reporting.yaml#/components/schemas/LocationConfiguration'
      responses:
        '201':
          description: Successful configuration update request submitted to LMS
          content:
            application/json:
              schema:
                $ref: 'TS24283_Lms_Reporting.yaml#/components/schemas/LocationConfiguration'
        '400':
          $ref: 'TS29571_CommonData.yaml#/components/responses/400'
        '401':
          $ref: 'TS29571_CommonData.yaml#/components/responses/401'
        '403':
          $ref: 'TS29571_CommonData.yaml#/components/responses/403'
        '404':
          $ref: 'TS29571_CommonData.yaml#/components/responses/404'
        '411':
          $ref: 'TS29571_CommonData.yaml#/components/responses/411'
        '413':
          $ref: 'TS29571_CommonData.yaml#/components/responses/413'
        '415':
          $ref: 'TS29571_CommonData.yaml#/components/responses/415'
        '429':
          $ref: 'TS29571_CommonData.yaml#/components/responses/429'
        '500':
          $ref: 'TS29571_CommonData.yaml#/components/responses/500'
        '503':
          $ref: 'TS29571_CommonData.yaml#/components/responses/503'
        default:
          $ref: 'TS29571_CommonData.yaml#/components/responses/default'


components:
  securitySchemes:
    BearerAuth:
      type: http
      scheme: bearer

# API specific definitions
  schemas:

    ClientOriginatingLocationRequest:
      description: Represents an location request object used to request
        location infromation from the LMS.
      type: object
      properties:
        functionalAliasIds:
          type: array
          items:
            type: string
            format: uri
            description: A list of activated Functional Alias Id of requested MC Users.
        locationNotificationUri:
          $ref: 'TS29571_CommonData.yaml#/components/schemas/Uri'
        mclocClientID:
          type: string
          description: Identifies the LMC of the MC UE.
        mcServiceIds:
          type: array
          items:
            type: string
            format: uri
            description: A list of MC service IDs of the MC users for which
              location information is requested MC Users.
        mcServiceGroupIds:
          type: array
          items:
            type: string
            format: uri
            description: A list of MC service Group IDs for which
              location information is requested for the affiliated MC Users.
        refresh:
          type: boolean
          nullable: true
          description: The presence of this attribute indicates that the
            location report shall be refreshed immediately.
```

```
      requestLocationHistory:
        $ref: 'TS24283_Lms_Reporting.yaml#/components/schemas/RequestedLocationHistory'
      requestHistoryStatus:
        type: boolean
        description: This attributes indicates that a location history status report is requested.
    required:
      - mclocClientID
      - locationNotificationUri
    anyOf:
      - required: [functionalAliasIds]
      - required: [mcServiceIds]
      - required: [mcServiceGroupIds]


  LocationSubscriptionRequest:
    description: Represents a location subscription request.
    type: object
    properties:
      expTime:
        $ref: 'TS29571_CommonData.yaml#/components/schemas/DateTime'
      functionalAliasIds:
        type: array
        items:
          type: string
          format: uri
          description: A list of Functional Alias Id which are actived for the MC Users
            for which location is subscribed.
      locationNotificationUri:
        $ref: 'TS29571_CommonData.yaml#/components/schemas/Uri'
      mclocClientID:
        type: string
        description: Identifies the LMC of the MC UE.
      mcServiceIds:
        type: array
        items:
          type: string
          format: uri
          description: A list of MC service IDs of the MC users for which
            location information is subscribed MC Users.
      mcServiceGroupIds:
        type: array
        items:
          type: string
          format: uri
          description: A list of MC service Group IDs for which
            location information is subscribed for the affiliated MC Users.
    required:
      - expTime
      - mclocClientID
      - locationNotificationUri
    anyOf:
      - required: [functionalAliasIds]
      - required: [mcServiceIds]
      - required: [mcServiceGroupIds]

  MCUserLocation:
    description: Represents one MC User's device location information.
    type: object
    properties:
      mcServiceIds:
        type: array
        items:
          type: string
          format: uri
          description: A list of MC service IDs of the MC user for which
            location information is reported.
      functionalAliasIds:
        type: array
        items:
          type: string
          format: uri
          description: A list of activated Functional Alias Id of the MC user
            for which location information is reported.
      mcServiceUELabel:
        type: string
        description: Used to identify the reporting MC UE for the end user, this may be used
          when multiple MC UEs are reporting by the same MC service user.
      locationInfo:
```

```
        $ref: 'TS24283_Lms_Reporting.yaml#/components/schemas/LocationInfo'


    LocationNotification:
      description: Represents an location notification response.
      type: object
      properties:
        mcUEResponseList:
          type: array
          items:
            $ref: '#/components/schemas/MCUserLocation'
        requestingMcServiceId:
          type: string
          format: uri
          description: The MC service ID of the LMC that requested the location report.
        requestingfunctionalAliasId:
          type: string
          format: uri
          description: The activated Functional Alias Id of the LMC that requested
            the location report.
        subscriptionID:
          type: string
          description: Attribute including the subscriptionID when the location notification
            is related to an existing subscription.
```

Annex B (informative): Change history

Change history							
Date	Meeting	TDoc	CR	Rev	Cat	Subject/Comment	New version
2023-08	CT1#143	C1-235054				Based on initial skeleton C1-235054. Incorporates agreed pCRs C1-235056, C1-236139	0.1.0
2024-08	CT1#150					Incorporates agreed pCR C1-244202	0.2.0
2024-10	CT1#151					Incorporates agreed pCRs C1-245350, C1-245847. C1-245917	0.3.0
2024-11	CT1#152					Incorporates agreed pCRs C1-246230, C1-246350, C1-246352, C1-246353, C1-246913, C1-246940, C1-246941, C1-246942	0.4.0
2025-02	CT1#153					Incorporates agreed pCRs C1-250267, C1-250268, C1-250270, C1-250271, C1-250857	0.5.0
2025-04	CT1#154					Incorporates agreed pCRs C1-251684, C1-251685, C1-252277	0.6.0
2025-05	CT1#155					Incorporates agreed pCRs C1-253124, C1-253158, C1-253159, C1-253161, C1-253773, C1-253776, C1-253777	0.7.0
2025-06	CT#108	CP-251216				TS presented for information in CT#108	1.0.0
2025-09	CT1#156					Incorporates agreed pCRs C1-254710, C1-254711, C1-254712, C1-254713, C1-254714, C1-254718, C1-255367, C1-255369, C1-255392	1.1.0
2025-09	CT#109	CP-252118				Presenting 3GPP TS 24.283 to CT#109 for approval	2.0.0
2025-09	CT#109	CP-252118				Approved by TSG CT#109	19.0.0
2025-12	CT#110	CP-253088	0001	1	F	Correction to reference points	19.1.0
2025-12	CT#110	CP-253088	0002	1	F	Miscellaneous corrections to MCLoc	19.1.0
2025-12	CT#110	CP-253088	0003	1	F	Resolving EN on X-3GPP-P-Asserted-Identity	19.1.0
2025-12	CT#110	CP-253088	0004	1	F	Resolving EN on anyAreaChange	19.1.0
2025-12	CT#110	CP-253088	0005	1	F	Resolving an FFS and an Editor's note	19.1.0
2025-12	CT#110	CP-253088	0006	1	F	Update of info and externalDocs fields	19.1.0
2026-06	CT#112	CP-261103	0007	1	F	Location resource correction	19.2.0
2026-09	CT#113	CP-262064	0010	-	F	Response to location reporting request	19.3.0
2026-09	CT#113	CP-262094	0011	-	F	Update of info and externalDocs fields	19.3.0

History

Version	Date	Status
V19.0.0	January 2026	Publication
V19.1.0	February 2026	Publication
V19.2.0	August 2026	Publication
V19.3.0	September 2026	Publication