# ETSI GS MEC 030 V3.1.1 (2023-03)




# Multi-access Edge Computing (MEC); V2X Information Services API

***Disclaimer***

The present document has been produced and approved by the Multi-access Edge Computing (MEC) ETSI Industry Specification Group (ISG) and represents the views of those members who participated in this ISG.
It does not necessarily represent the views of the entire ETSI membership.

Reference
RGS/MEC-0030v311V2XAPI

Keywords
API, MEC, service, V2X

***ETSI***

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

***Important notice***

The present document can be downloaded from:
http://www.etsi.org/standards-search

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status.
Information on the current status of this and other ETSI documents is available at
https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx

If you find errors in the present document, please send your comment to one of the following services:
https://portal.etsi.org/People/CommiteeSupportStaff.aspx

If you find a security vulnerability in the present document, please report it through our
Coordinated Vulnerability Disclosure Program:
https://www.etsi.org/standards/coordinated-vulnerability-disclosure

***Notice of disclaimer & limitation of liability***

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.
No recommendation as to products and services or vendors is made or should be implied.
No representation or warranty is made that this deliverable is technically accurate or sufficient or conforms to any law and/or governmental rule and/or regulation and further, no representation or warranty is made of merchantability or fitness for any particular purpose or against infringement of intellectual property rights.
In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

***Copyright Notification***

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.
The content of the PDF version shall not be modified without the written authorization of ETSI.
The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2023.
All rights reserved.

# Contents

Intellectual Property Rights ..... 7
Foreword ..... 7
Modal verbs terminology ..... 7
1 Scope ..... 8
2 References ..... 8
2.1 Normative references ..... 8
2.2 Informative references ..... 9
3 Definition of terms, symbols and abbreviations ..... 10
3.1 Terms ..... 10
3.2 Symbols ..... 10
3.3 Abbreviations ..... 10
4 Overview ..... 11
5 Description of the service (informative) ..... 11
5.1 Reference scenarios for the VIS service ..... 11
5.2 Multi-operator scenarios and V2X services ..... 12
5.3 V2X service continuity in multi-operator operation scenarios ..... 12
5.3.1 Introduction ..... 12
5.4 VIS functionalities ..... 13
5.4.1 Overview ..... 13
5.4.2 Communication between V2X Control Function (3GPP) and VIS (MEC) ..... 14
5.4.3 Inter-MEC system V2X application communication ..... 15
5.4.4 Inter-MEC system service exposure ..... 15
5.4.5 The VIS and its role in producing journey-specific predictive QoS notifications ..... 15
5.4.6 The VIS and its role in multi-domain end-to-end predictive QoS notifications ..... 17
5.4.7 Interaction between the VIS and non-session based V2X services ..... 18
5.4.8 The VIS and the provision of information about V2X Message Distribution Servers ..... 19
5.5 Sequence diagrams ..... 19
5.5.1 Sending a request for provisioning information for V2X communication over Uu unicast ..... 19
5.5.2 Sending a request for provisioning information for V2X communication over Uu MBMS ..... 20
5.5.3 Sending a request for provisioning information for V2X communication over PC5 ..... 20
5.5.4 Sending a request for provisioning information for direct communication with V2X Message Distribution Servers ..... 21
5.5.5 Sending a request for journey-specific QoS predictions ..... 21
5.5.6 REST based subscribe-notify model ..... 22
5.5.6.1 Subscribing to event notifications ..... 22
5.5.6.2 Receiving notification on expiry of V2X information event subscription ..... 23
5.5.6.3 Updating subscription for V2X information event notifications ..... 23
5.5.6.4 Unsubscribing from V2X information event notifications ..... 24
5.5.7 Receiving V2X information event notifications about the provisioning information changes for V2X communication over Uu unicast ..... 24
5.5.8 Receiving V2X information event notifications about the provisioning information changes for V2X communication over Uu MBMS ..... 25
5.5.9 Receiving V2X information event notifications about the provisioning information changes for V2X communication over PC5 ..... 26
5.5.10 V2X message interoperability ..... 26
5.5.10.1 V2X message subscribe ..... 26
5.5.10.2 V2X message publication ..... 27
5.5.10.3 V2X message notification ..... 27
5.6 Conclusions on VIS ..... 28
6 Data model ..... 28
6.1 Introduction ..... 28
6.2 Resource data types ..... 28
6.2.1 Introduction ..... 28

6.2.2 Type: UuUnicastProvisioningInfo ..... 28
6.2.3 Type: UuMbmsProvisioningInfo ..... 29
6.2.4 Type: Pc5ProvisioningInfo ..... 29
6.2.5 Type: V2xMsgDistributionServerInfo ..... 29
6.2.6 Type: PredictedQos ..... 30
6.2.7 Type: V2xMsgPublication ..... 31
6.3 Subscription data types ..... 31
6.3.1 Introduction ..... 31
6.3.2 Type: ProvChgUuUniSubscription ..... 31
6.3.3 Type: ProvChgUuMbmsSubscription ..... 32
6.3.4 Type: ProvChgPc5Subscription ..... 33
6.3.5 Type: V2xMsgSubscription ..... 33
6.3.6 Type: PredQosSubscription ..... 34
6.3.7 Type: SubscriptionLinkList ..... 34
6.4 Notifications data types ..... 35
6.4.1 Introduction ..... 35
6.4.2 Type: ProvChgUuUniNotification ..... 35
6.4.3 Type: ProvChgUuMbmsNotification ..... 35
6.4.4 Type: ProvChgPc5Notification ..... 36
6.4.5 Type: V2xMsgNotification ..... 36
6.4.6 Type: TestNotification ..... 36
6.5 Referenced structured data types ..... 37
6.5.1 Introduction ..... 37
6.5.2 Type: TimeStamp ..... 37
6.5.3 Type: LocationInfo ..... 37
6.5.4 Type: Plmn ..... 37
6.5.5 Type: Ecgi ..... 37
6.5.6 Type: FddInfo ..... 38
6.5.7 Type: TddInfo ..... 38
6.5.8 Type: V2xApplicationServer ..... 38
6.5.9 Type: UuUniNeighbourCellInfo ..... 38
6.5.10 Type: V2xServerUsd ..... 39
6.5.11 Type: UuMbmsNeighbourCellInfo ..... 39
6.5.12 Type: Pc5NeighbourCellInfo ..... 39
6.5.13 Type: LinkType ..... 39
6.5.14 Type: V2xMsgPropertiesValues ..... 40
6.5.15 Type: V2xMsgFilterCriteria ..... 40
6.5.16 Type: V2xMsgDistributionServer ..... 40
6.5.17 Type: QosPredFilterCriteria ..... 41
6.5.18 Type: WebsockNotifConfig ..... 41
6.6 Referenced simple data types and enumerations ..... 41
6.6.1 Introduction ..... 41
6.6.2 Type: CellId ..... 42
6.6.3 Type: Earfcn ..... 42
6.6.4 Type: TransmissionBandwidth ..... 42
7 API definition ..... 42
7.1 Introduction ..... 42
7.2 Global definitions and resource structure ..... 42
7.3 Resource: uu_unicast_provisioning_info ..... 44
7.3.1 Description ..... 44
7.3.2 Resource definition ..... 44
7.3.3 Resource methods ..... 45
7.3.3.1 GET ..... 45
7.3.3.2 PUT ..... 46
7.3.3.3 PATCH ..... 46
7.3.3.4 POST ..... 46
7.3.3.5 DELETE ..... 46
7.4 Resource: uu_mbms_provisioning_info ..... 46
7.4.1 Description ..... 46
7.4.2 Resource definition ..... 46
7.4.3 Resource methods ..... 47

7.4.3.1 GET ..... 47
7.4.3.2 PUT ..... 48
7.4.3.3 PATCH ..... 48
7.4.3.4 POST ..... 48
7.4.3.5 DELETE ..... 48
7.5 Resource: pc5_provisioning_info ..... 48
7.5.1 Description ..... 48
7.5.2 Resource definition ..... 48
7.5.3 Resource methods ..... 49
7.5.3.1 GET ..... 49
7.5.3.2 PUT ..... 50
7.5.3.3 PATCH ..... 50
7.5.3.4 POST ..... 50
7.5.3.5 DELETE ..... 50
7.6 Resource: provide_v2x_msg_distribution_server_info ..... 50
7.6.1 Description ..... 50
7.6.2 Resource definition ..... 50
7.6.3 Resource methods ..... 51
7.6.3.1 GET ..... 51
7.6.3.2 PUT ..... 51
7.6.3.3 PATCH ..... 51
7.6.3.4 POST ..... 51
7.6.3.5 DELETE ..... 52
7.7 Resource: provide_predicted_qos ..... 52
7.7.1 Description ..... 52
7.7.2 Resource definition ..... 52
7.7.3 Resource methods ..... 52
7.7.3.1 GET ..... 52
7.7.3.2 PUT ..... 52
7.7.3.3 PATCH ..... 52
7.7.3.4 POST ..... 52
7.7.3.5 DELETE ..... 53
7.8 Resource: publish_v2x_message ..... 53
7.8.1 Description ..... 53
7.8.2 Resource definition ..... 53
7.8.3 Resource methods ..... 54
7.8.3.1 GET ..... 54
7.8.3.2 PUT ..... 54
7.8.3.3 PATCH ..... 54
7.8.3.4 POST ..... 54
7.8.3.5 DELETE ..... 55
7.9 Resource: subscriptions ..... 55
7.9.1 Description ..... 55
7.9.2 Resource definition ..... 55
7.9.3 Resource methods ..... 55
7.9.3.1 GET ..... 55
7.9.3.2 PUT ..... 56
7.9.3.3 PATCH ..... 56
7.9.3.4 POST ..... 56
7.9.3.5 DELETE ..... 58
7.10 Resource: existing subscription ..... 58
7.10.1 Description ..... 58
7.10.2 Resource definition ..... 58
7.10.3 Resource methods ..... 58
7.10.3.1 GET ..... 58
7.10.3.2 PUT ..... 59
7.10.3.3 PATCH ..... 61
7.10.3.4 POST ..... 61
7.10.3.5 DELETE ..... 61

**Annex A (informative): Mapping of permissions for RESTful API and topic based alternative transport ..... 63**

A.1 Overview ....63
A.2 Mapping of permissions - RESTful and topic based alternative transport ....63
**Annex B (informative): Complementary material for API utilization ....65**
**Annex C (informative): Radio access network scenario options for V2X communication ....66**
**Annex D (informative): State-of-the-art of using a Message Broker as V2X Message Distribution Server for exchanging non-session based V2X messages ....67**
History ....68

# Intellectual Property Rights

## Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (https://ipr.etsi.org/).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

## Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

**DECT™**, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM**® and the GSM logo are trademarks registered and owned by the GSM Association.

# Foreword

This Group Specification (GS) has been produced by ETSI Industry Specification Group (ISG) Multi-access Edge Computing (MEC).

# Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the ETSI Drafting Rules (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

# 1 Scope

The present document focuses on a MEC V2X Information Services (VIS), in order to facilitate V2X interoperability in a multi-vendor, multi-network and multi-access environment, considering the relevant work of other industry bodies relating to V2X communication (e.g. ETSI ITS, 5GAA). It describes the V2X-related information flows, required information and operations. The present document also specifies the necessary API with the data model and data format.

# 2 References

## 2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at https://docbox.etsi.org/Reference.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

[1] Void.

[2] Void.

[3] IETF RFC 5246: "The Transport Layer Security (TLS) Protocol Version 1.2".

[4] IETF RFC 6749: "The OAuth 2.0 Authorization Framework".

[5] IETF RFC 6750: "The OAuth 2.0 Authorization Framework: Bearer Token Usage".

[6] ETSI TS 102 894-2: "Intelligent Transport Systems (ITS); Users and applications requirements; Part 2: Applications and facilities layer common data dictionary".

[7] IETF RFC 8446: "The Transport Layer Security (TLS) Protocol Version 1.3".

[8] ETSI TS 133 210: "Digital cellular telecommunications system (Phase 2+) (GSM); Universal Mobile Telecommunications System (UMTS); LTE; 5G; Network Domain Security (NDS); IP network layer security (3GPP TS 33.210)".

[9] ETSI GS MEC 009: "Multi-access Edge Computing (MEC); General principles, patterns and common aspects of MEC Service APIs".

[10] ETSI TS 123 285: "Universal Mobile Telecommunications System (UMTS); LTE; Architecture enhancements for V2X services (3GPP TS 23.285)".

[11] ETSI TS 136 300: "LTE; Evolved Universal Terrestrial Radio Access (E-UTRA) and Evolved Universal Terrestrial Radio Access Network (E-UTRAN); Overall description; Stage 2 (3GPP TS 36.300)".

[12] ETSI TS 136 423: "LTE; Evolved Universal Terrestrial Radio Access Network (E-UTRAN); X2 Application Protocol (X2AP) (3GPP TS 36.423)".

[13] ETSI TS 136 413: "LTE; Evolved Universal Terrestrial Radio Access Network (E-UTRAN); S1 Application Protocol (S1AP) (3GPP TS 36.413)".

[14] ETSI TS 136 331: "LTE; Evolved Universal Terrestrial Radio Access (E-UTRA); Radio Resource Control (RRC); Protocol specification (3GPP TS 36.331)".

[15] ETSI TS 136 321: "LTE; Evolved Universal Terrestrial Radio Access (E-UTRA); Medium Access Control (MAC) protocol specification (3GPP TS 36.321)".

## 2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

[i.1] Void.

[i.2] Void.

[i.3] OpenAPI™ Specification.

[i.4] ETSI GR MEC 022: "Multi-access Edge Computing (MEC); Study on MEC Support for V2X Use Cases".

[i.5] Void.

[i.6] ETSI TS 129 388: "LTE; V2X Control Function to Home Subscriber Server (HSS) aspects (V4); Stage 3 (3GPP TS 29.388)".

[i.7] ETSI TS 129 389: "LTE; Inter-V2X Control Function Signalling aspects (V6); Stage 3 (3GPP TS 29.389)".

[i.8] Void.

[i.9] Void.

[i.10] Void.

[i.11] Void.

[i.12] Void.

[i.13] Void.

[i.14] ETSI GS MEC 003: "Multi-access Edge Computing (MEC); Framework and Reference Architecture".

[i.15] ETSI GS MEC 012: "Multi-access Edge Computing (MEC); Radio Network Information API".

[i.16] ETSI GS MEC 013: "Multi-access Edge Computing (MEC); Location API".

[i.17] ETSI GS MEC 028: "Multi-access Edge Computing (MEC); WLAN Access Information API".

[i.18] Autopilot.

[i.19] MQTT: "The Standard for IoT Messaging".

[i.20] Fifth Generation Cross-Border Control (5GCroCo).

[i.21] 5G Carmen.

[i.22] Advanced Message Queuing Protocol.

[i.23] 5G Car-captured data.

[i.24] C-ROADS - The Platform of Harmonised C-ITS Deployment in Europe.

[i.25] ICT4cart.

[i.26] Developers.

[i.27] ETSI TS 123 288: "5G; Architecture enhancements for 5G System (5GS) to support network data analytics services (3GPP TS 23.288)".

[i.28] ETSI TS 123 502: "5G; Procedures for the 5G System (5GS) (3GPP TS 23.502)".

[i.29] Void.

[i.30] 5GAA TR-200055: "5G Automative Association; Working Group System Architecture and Solution Development; 5GS Enhancements for Providing Predictive QoS in C-V2X".

[i.31] 5GAA White Paper: "Making 5G Proactive and Predictive for the Automotive Industry".

[i.32] ETSI GR MEC 001: "Multi-access Edge Computing (MEC); Terminology".

# 3 Definition of terms, symbols and abbreviations

## 3.1 Terms

For the purposes of the present document, the terms given in ETSI GR MEC 001 [i.32] apply.

## 3.2 Symbols

Void.

## 3.3 Abbreviations

For the purposes of the present document, the abbreviations given in ETSI GR MEC 001 [i.32] and the following apply:

| | |
|---|---|
| 5GAA | 5G Automotive Association |
| 5QI | 5G QoS Identifier |
| AMQP | Advanced Message Queuing Protocol |
| CDF | Cumulative Distribution Function |
| CN | Core Network |
| C-V2X | Cellular V2X |
| DL | Downlink |
| DN | Data Network |
| E2E | End-to-End |
| eNB | evolved Node B |
| E-UTRAN | Evolved UMTS Terrestrial Radio Access Network |
| FDD | Frequency Division Duplex |
| FOTA | Firmware Over The Air |
| gNB | 5G Node B |
| HSS | Home Subscriber Server |
| IoT | Internet of Things |
| ITS | Intelligent Transport Systems |
| KPI | Key Performance Indicator |
| MaaS | Mobility-as-a-Service |
| MBMS | Multimedia Broadcast Multicast Services |
| MQTT | Message Queuing Telemetry Transport |
| NEF | Network Exposure Function |
| NF | Network Function |
| NWDAF | Network Data Analytics Function |
| OEM | Original Equipment Manufacturer |
| PF | Prediction Function |
| PoP | Point-of-Presence |

| | |
|---|---|
| RSU | Road Side Unit |
| SLA | Service-Level Agreement |
| ToD | Teleoperated Driving |
| SDP | Session Description Protocol |
| SOTA | Software Over The Air |
| TDD | Time Division Duplex |
| UDP | User Datagram Protocol |
| UL | Uplink |
| V2N2I | Vehicle-to-Network-to-Infrastructure |
| V2N2V | Vehicle-to-Network-to-Vehicle |
| VIS | V2X Information Services |

# 4 Overview

The present document specifies the VIS API to facilitate V2X interoperability in a multi-vendor, multi-network and multi-access environment.

Clause 5 presents reference scenarios for the VIS service and lists the functionalities of the service. It also describes the information flows used for VIS.

The information that can be exchanged over the VIS API is described in clause 6 which provides detailed descriptions of all information elements that are used for VIS.

Clause 7 describes the actual VIS API providing detailed information of how information elements are mapped into a RESTful API design.

# 5 Description of the service (informative)

## 5.1 Reference scenarios for the VIS service

According to recommendations in ETSI GR MEC 022 [i.4], multi-access, multi-network and multi-operator scenarios are the reference assumptions motivating the need for MEC normative work on this area. Figure 5.1-1 shows all the scenarios applicable to V2X services. In particular:

- Some V2X services can be managed by OEMs (the so called "Vehicle OEMs scenario"), and, thus, it is reasonable to consider both single and multi-operator scenarios for such services. Note that V2X services are expected to be provided by different network operators in the same country and/or in different countries.
- Similarly, the same applies when the "ITS Operator scenario" is considered, that may additionally provide services for different vehicle OEMs. An ITS operator may need to provide a country-wide V2X service, by exploiting different operators' networks (deploying different MEC systems), and offering this service to vehicles belonging to different OEMs. Note that also in this case, V2X services are expected to be provided by different network operators in the same country and/or in different countries.





**Figure 5.1-1: Reference scenarios relevant to the VIS service**

As a consequence, in order to enable all use cases, the MEC V2X Information Services (VIS) should support C-V2X systems implemented in the most general scenarios. In particular, these scenarios should assume the presence of multiple MEC vendors and the need to enable interoperable data exchange between them. Moreover, multi-operator interoperability is a key aspect for ensuring service continuity, and it is described in clause 5.2.

## 5.2 Multi-operator scenarios and V2X services

The left hand side of figure 5.2-1 shows a typical multi-operator scenario, highlighting the case of temporary absence of radio coverage, e.g. in roaming situations. As showed in the right-hand side of figure 5.2-1, in a traditional V2X system (without the VIS service) the interconnection between MNOs is terminated at the remote side, with clear disadvantages in terms of high E2E latency; on the other hand, thanks to the exploitation of the VIS service (enabling also a "horizontal communication" between MEC systems), the interconnection between MNOs can be realized with low E2E latency.





**Figure 5.2-1: (left): Example of a multi-operator scenario for V2X services; (right): Example of path for data exchange without the VIS service (in red) and with the VIS service (in green)**

V2X service needs to be provided across all the territory including both operators' coverage areas, as well as when leaving the coverage area of one operator and entering the coverage area of the other operator without any service disruption and guaranteeing E2E performance. For that purpose, VIS exposes information on PC5 configuration parameters and manages the multi-operator environment, especially when a UE is out of coverage.

## 5.3 V2X service continuity in multi-operator operation scenarios

### 5.3.1 Introduction

Wireless communication is a key enabling technology of co-operative intelligent transportation systems. Road users (including vehicles, cyclists, pedestrians) involved in the communication may use services provided by different operators.

A mobile operator network is typically region specific or country specific, which provides services directly to its own customers (subscribers), while providing communications to other operators' customers via the core network level interworking between two operators' networks. To maintain the V2X service continuity (often with low latency requirement) for road users becomes very challenging especially when such road users (e.g. vehicular UEs) move from one PLMN to another.





**Figure 5.3.1-1: Example V2X use case: inter-PLMN service continuity**

To enable service continuity in such use cases, mobile network level interworking among different PLMNs is necessary as specified in 3GPP specifications ETSI TS 123 285 [10], ETSI TS 129 388 [i.6] and ETSI TS 129 389 [i.7]. Furthermore, inter-MEC system coordination is also required to prepare in advance the UEs in transit (based on the agreements among operators, roam or handover to a new PLMN) and reduce the interruption time.

The service consumers communicate with VIS over the VIS API to get the necessary V2X service provisioning information for the visiting PLMN in support of inter-PLMN service continuity. Both the MEC applications and the MEC platform may consume the VIS; and both the MEC platform and the MEC applications may be the providers of the V2X information.

The VIS API supports both queries and subscriptions (pub/sub mechanism) that are used over the RESTful API or over alternative transports such as message bus. Alternative transports are not specified in detail in the present document. For RESTful architectural style, the present document defines the HTTP protocol bindings.

## 5.4 VIS functionalities

### 5.4.1 Overview

The MEC standards have been designed to facilitate V2X interoperability in a multi-vendor, multi-network and multi-access environment. The introduction of the VIS API is aimed at helping the ecosystem adopt MEC for automotive use cases. These use cases may involve different car makers, OEM suppliers, network infrastructure vendors, MEC vendors, application/content providers and other stakeholders. Therefore, it is critical that all MEC related interoperability reference points involving the potential stakeholders are fully specified.

In particular, the VIS defined in the present document will permit information exposure, pertinent to the support of automotive use cases, to MEC application instances. It will also permit a single ITS operator to offer a V2X service over a region that may span different countries and involve multiple network operators, MEC systems and MEC application providers.

For that purpose, the MEC VIS includes the following functionalities:

1) Gathering of PC5 V2X relevant information from the 3GPP network (e.g. the list of authorized UEs, the relevant information about the authorization based on the UE subscription and the relevant PC5 configuration parameters).

2) Exposure of this information to MEC apps (also potentially belonging to different MEC systems).

3) Enablement of MEC apps to communicate securely with the V2X-related 3GPP core network logical functions (e.g. V2X control function).

4) Enablement of MEC apps in different MEC systems to communicate securely with each other.

5) Possibly gathering and processing information available in other MEC APIs (e.g. RNI API, see ETSI GS MEC 012 [i.15], Location API, see ETSI GS MEC 013 [i.16], WLAN API, see ETSI GS MEC 028 [i.17], etc.) in order to predict radio network congestion and provide suitable notifications to the UE.

From that perspective, the VIS service is relevant to Mp1 and Mp3 reference points in the MEC architecture. In particular, the relevant information is exposed to MEC apps via the Mp1 reference point. Potential impacts on Mp3 reference point (e.g. enabling the possibility to transfer this information between different MEC platforms) are introduced in ETSI GS MEC 003 [i.14] and are out of the scope of the present document.

NOTE 1: The VIS API provides information to MEC applications in a standardized way; this is essential for interoperability in multi-vendor scenarios; nevertheless, it is acknowledged that MEC applications may communicate in a direct way (i.e. without the use of MEC platform).

NOTE 2: Inter-system communication may be realized between MEOs. As an alternative, or, in addition to that, possible Mp3 enhancements (or new reference points between MEC systems) may be defined. This is out of the scope of the present document.





**Figure 5.4.1-1: Example of application instances in a V2X service with VIS API**

Figure 5.4.1-1 illustrates a typical V2X system involving multiple MEC hosts and the use of the VIS service. In the framework of V2X services, a car is hosting a client application, and is connected to a certain MEC host (and a related MEC application). In presence of multiple MEC hosts, the VIS permits to expose information between MEC applications running on different MEC hosts. In addition, other remote application server instances can be located somewhere else (e.g. private clouds owned by the operator or by the OEM). The VIS service may be produced by the MEC platform or by the MEC application.

## 5.4.2 Communication between V2X Control Function (3GPP) and VIS (MEC)

In a 3GPP network, V2X applications can be deployed on V2X Application Server. The V2X Control Function is the NF in core network part, which is used for network-related actions required for V2X. The HSS provides the list of the PLMNs, where the UE is authorized to perform V2X communication over PC5 reference point to the V2X Control Function, see ETSI TS 123 285 [10]. V2 is the reference point between the V2X Application Server and the V2X Control Function in the operator's network.

The VIS defined in MEC is used to facilitate V2X interoperability in a multi-vendor, multi-network and multi-access environment. Therefore, the VIS should obtain the UE's subscription data (e.g. PC5 based V2X communication allowed PLMN), from the V2X Control Function.

Because the V2X Application Server bears multiple V2X applications, it can, therefore, be deployed in MEC platform as a MEC application. The VIS can communicate with the V2X Application Server through Mp1, and it can obtain the UE's V2X subscription data from the V2X Control Function through the V2X Application Server.

NOTE: The VIS, or generic parts of it, can be deployed in the MEC Platform.





**Figure 5.4.2-1: Example of architecture enabling the communication between the VIS and the V2X Control Function**

## 5.4.3 Inter-MEC system V2X application communication

A V2X MEC application may be required to communicate with its peer applications in other MEC systems in order to fulfil the intended purpose of the application use case. The involved MEC systems need to enable the authorized applications in one MEC system to communicate with their peers in another MEC system.

The discovery of the application peers may be facilitated by the VIS API by exposing the available communication end point information for peer to peer connectivity. Alternatively, the configured traffic rules for the V2X MEC application together with the underlying inter-MEC system connectivity arrangements may support the application peers' communication. Lastly, the V2X MEC application may rely on non-MEC-specific means for its peer discovery and then rely on its authorized access to external interface for the communication.

The required arrangements between the involved MEC systems for realizing secure connectivity with the application specific requirements are deployment specific and beyond the scope of the present document.

## 5.4.4 Inter-MEC system service exposure

A V2X MEC application in one MEC system may be required to consume a service in another MEC system in order to fulfil the intended purpose of the application use case. The V2X MEC application discovers the service in question in the service registry in its local MEC host.


The required arrangements between the involved MEC systems for mapping a service produced in one MEC system to an endpoint in another MEC system are deployment specific and beyond the scope of the present document.

## 5.4.5 The VIS and its role in producing journey-specific predictive QoS notifications

Accurate and timely predictions of the radio environment at locations planned to be visited by vehicles can either trigger, modify or postpone:

i) the application of certain V2X functionalities; and/or

ii) the download of content delivery/ software packages.




NOTE: Figure 5.4.5-1 illustrates an exemplary V2X system scenario, where the MEC host is deployed in collocation with a Roadside Unit (RSU)/ eNB providing coverage (V2X communication); the RNI Service (RNIS) is running at the MEC host - it is assumed that the planned trajectory of vehicle #1 and vehicle #2 is not known at the RSU.

**Figure 5.4.5-1: Exemplary V2X system scenario (see note)**

However, focusing on V2X system scenarios characterized by high mobility and dynamic topology (as in figure 5.4.5-1), the accuracy and the timeliness of information (e.g. radio network, location information, etc.) may be hampered by:

- the environmental situation, e.g. the occurrence of network congestion events when, for example, many vehicles attempt to provide radio measurements to the connected eNB/gNB, which is collocated with a MEC host, as well as by
- the deployment density of the cellular network, together with the capabilities of the deployed MEC infrastructure.

An example illustrating the impact of the above mentioned limitations on system performance is the one of a vehicle planning to follow a trajectory from location A to location B and a related MEC application which would need to be informed of radio conditions "en route", ahead of the vehicle's passing time, before reaching a decision. Decisions may consist in e.g. enabling/disabling autonomous driving features, downloading infotainment content, scheduling Software/Firmware Over-the-Air (SOTA/FOTA) updates, etc.

To address such challenges, the VIS service may assist in implementing a framework for cooperative acquisition, partitioning and distribution of information for efficient, journey-specific QoS prediction. That is, the VIS service may be utilized to identify space/time correlations between radio quality data collected by different vehicles in a V2X system and a specific vehicle's planned journey for better prediction of the quality of the communication network along the designated route. As a consequence, the VIS may expose relevant (i.e. journey-specific) information about the QoS prediction to authorized UEs.

In addition, QoS predictions might be useful to V2X applications or service providers, e.g. a Mobility-as-a-Service (MaaS) provider, a fleet management company, a vehicle OEM, a MNO, or a third party at the infrastructure side. For example, the predictive QoS notifications can be exploited by a fleet management company, or an OEM as information useful to decide upon the means to reduce the incurred service consumption cost. This is because in some situations, radio or network bottlenecks may appear, including MEC Points-of-Presence (PoP) computing resource availability, if many vehicles converge to a certain geographical area, or because some specific road traffic event happened. In such cases, MEC PoP optimization might be required (e.g. relocating the VM of a V2X MEC application instance to another MEC host in the MEC system, or performing a VM scale-up of a V2X MEC application instance in the same MEC host). Furthermore, such QoS predictions could be a useful input in workload offloading decisions from a vehicle to a MEC host.

### 5.4.6 The VIS and its role in multi-domain end-to-end predictive QoS notifications

In addition to the data collected by the different vehicles, VIS may also enable support for predictive QoS notifications in multi-domain MEC deployments by collecting and distributing analytics from external Prediction Functions (PFs) located in the different network domains. The sourcing of analytics from external PFs, such as the Network Data Analytics Function (NWDAF) in the 3GPP network domains may help in providing more accurate QoS predictions to the service consumers.

In 5G Automotive Association (5GAA) activities, multiple scenarios are studied, where the service consumer may benefit from the information related to the QoS prediction of an E2E user plane link between two specific endpoints. These scenarios are ranging from Teleoperated Driving (ToD), towards coordinated manoeuvres scenarios and use cases, such as lane merge, platooning, etc. as well as high definition map collection/sharing and in-vehicle infotainment, as described in [i.30] and [i.31]. In this context, a service consumer may be a MEC application, a MEC platform, a V2X application server or an "ultimate" QoS prediction consumer, such as a vehicle or an OEM application accessing the VIS via a MEC application. According to the different scenarios studied by 5GAA (V2N2V and V2N2I [i.31]), these two endpoints may be application instances deployed in two vehicles and exchanging V2X messages or an application instance in a vehicle exchanging V2X messages with the road infrastructure, in both cases with the support of the MEC infrastructure. Two exemplary scenarios are described in figures 5.4.6-1 and 5.4.6-2, where the QoS prediction of the E2E user plane link should consider up to 5 different network domains. In figure 5.4.6-1 (V2N2V), those domains are specifically: the 3GPP network domains of the two operators (MNO A an MNO B), the Data Networks (DN A) and (DN B) where the MEC host is located, as well as the IP controlled network that is interconnecting the networks of the PLMN A and PLMN B.





**Figure 5.4.6-1: E2E scenario for multi-operator V2X deployment (case V2N2V)**

In figure 5.4.6-2 (case V2N2I), those network domains for E2E user plane link are instead 4 distinct domains: the 3GPP network domain of the operator that provides 5G connectivity to the vehicle (MNO A for vehicle 1), the DN (DN A for vehicle 1) where the MEC host is located, the interconnection domain and the 3rd party domain where the road infrastructure is located.





**Figure 5.4.6-2: E2E scenario for multi-operator V2X deployment (case V2N2I)**

In the case of 3GPP System domains, the VIS may cooperate with the analytics service provided by the NWDAF according to clause 6.9 of ETSI TS 123 288 [i.27]. Such analytics service can provide predictions for the 3GPP network domain (e.g. at the Radio Access Network - RAN level and Core Network segment between the UE and the User Plane Function - UPF node), such as the QoS Sustainability Analytics.

Other network domains, such as the IP interconnect domain or DNs in the Service Provider domain (including the MEC host) may also deploy a domain-specific PF that can provide analytics information to a calling service consumer via the VIS. These DN domain specific predictions may be provided by NWDAF, as described by the DN Performance Analytics described in clause 6.14 of ETSI TS 123 288 [i.27].

The 3GPP system domain specific predictions may include analytics for user plane performance (i.e. average/maximum traffic rate, average/maximum packet delay, average packet loss rate) in the form of statistics or predictions to a service consumer. VIS may aggregate such information to provide an E2E QoS prediction in the considered multi-domain scenario.

These user plane performance analytics may be obtained from the NWDAF directly or via the Network Exposure Function (NEF) according to clause 5.2.6.16 of ETSI TS 123 502 [i.28].

NOTE: In some cases, a V2X MEC application communicating with the VIS may also conveniently generate a prediction for one or more domains where the PF is not available based on collected information.

VIS may aggregate analytics sourced from external PFs, such as the NWDAF or other analytics provider in order to provide (predictions/estimations) of the QoS that cover the E2E user plane link between two V2X application instances.

It is out of scope how VIS can collect such information from the external PFs.

## 5.4.7 Interaction between the VIS and non-session based V2X services

Several V2X services, that are currently implemented, are non-session based services. These services concern the broadcasting of information related to events or warnings about potential danger (e.g. Road Status Notification, Warning Alert). This means that a single V2X message needs to be delivered to a set of locally relevant UEs or to a set of locally relevant V2X Application Servers.

As introduced in the Annex D of the 3GPP specification ETSI TS 123 285 [10], a possible deployment approach is based on the use of a V2X Message Distribution Server that is in charge to receive V2X messages from non-session based V2X services and to distribute them to the relevant destination entities.

This approach is widely adopted in several research projects and other initiatives for the implementation of the communication over the Uu interface for non-session based V2X services. In the specific, a Message Broker is typically deployed as V2X Message Distribution Server. Different application layer protocols, on which a Message Broker is based, can be used.. Details about the existing implementations are provided in Annex D of the present document.

The VIS should implement the required interactions with the Message Brokers, that are acting as V2X Message Distribution Servers, to correctly provide to the MEC applications the interaction with the non-session based V2X services (i.e. transmit and receive V2X messages related to non-session based V2X services). The definition of which type of Message Broker the VIS should interact with and how this interaction should be performed are beyond the scope of the present document.

### 5.4.8 The VIS and the provision of information about V2X Message Distribution Servers

A V2X MEC application implementing a non-session based V2X service, may require very low latency in the publication or notification of V2X messages. This strict latency requirement can be due to the specificities of the implemented V2X service that can be related to safety critical aspects.

The MEC application may need to directly interact with V2X Message Distribution Servers used for exchanging non-session based V2X messages to avoid any additional latency that is introduced by the VIS. The MEC application should, therefore, be provided with provisioning information about which V2X Message Distribution Servers are available, their characteristics, and how it can connect with them.

This information can be provided by the VIS upon the registration of the V2X Message Distribution Servers to the MEC platform, e.g. when these V2X Message Distribution servers are implemented as service-producing MEC applications. Each V2X Message Distribution Server can be based on a specific application layer protocol (e.g. MQTT, AMQP) and manage the exchange of V2X messages of a given geographical area. The MEC application can provide some criteria to select only the relevant V2X Message Distribution Servers based on application layer protocols that the MEC application supports or geographical areas of interest to the MEC application.

The way that the V2X Message Distribution Servers are registered to a MEC platform (e.g. as service-producing MEC applications) and the interactions among the VIS and the V2X Message Distribution Servers are beyond the scope of the present document.

## 5.5 Sequence diagrams

### 5.5.1 Sending a request for provisioning information for V2X communication over Uu unicast

Figure 5.5.1-1 shows a scenario where the service consumer (e.g. a MEC application or a MEC platform) sends a request to receive the provisioning information for V2X communication over Uu unicast for a particular location. The response contains the required information.




**Figure 5.5.1-1: Flow of service consumer requesting the Uu unicast provisioning information**

A service consumer requesting the Uu unicast provisioning information, as illustrated in figure 5.5.1-1, consists of the following steps:

1) Service consumer sends a GET request to the resource representing the Uu unicast provisioning information. The request contains the location information (e.g. the serving cell ID of or the geographical area information of the UE) as an input parameter.

2) VIS responds with "200 OK" with the message body containing the UuUnicastProvisioningInfo.

## 5.5.2 Sending a request for provisioning information for V2X communication over Uu MBMS

Figure 5.5.2-1 shows a scenario where the service consumer (e.g. a MEC application or a MEC platform) sends a request to receive the provisioning information for V2X communication over Uu MBMS for a particular location. The response contains the required information.





**Figure 5.5.2-1: Flow of service consumer requesting the Uu MBMS provisioning information**

A service consumer requesting the Uu MBMS provisioning information, as illustrated in figure 5.5.2-1, consists of the following steps:

1) Service consumer sends a GET request to the resource representing the Uu MBMS provisioning information. The request contains the location information (e.g. the serving cell ID of or the geographical area information of the UE) as an input parameter.

2) VIS responds with "200 OK" with the message body containing the UuMbmsProvisioningInfo.

## 5.5.3 Sending a request for provisioning information for V2X communication over PC5

Figure 5.5.3-1 shows a scenario where the service consumer (e.g. a MEC application or a MEC platform) sends a request to receive the provisioning information for V2X communication over PC5 for a particular location. The response contains the required information.





**Figure 5.5.3-1: Flow of service consumer requesting the PC5 provisioning information**

A service consumer requesting the PC5 provisioning information, as illustrated in figure 5.5.3-1, consists of the following steps:

1) Service consumer sends a GET request to the resource representing the PC5 provisioning information. The request contains the location information (e.g. the serving cell ID of or the geographical area information of the UE) as an input parameter.

2) VIS responds with "200 OK" with the message body containing the Pc5ProvisioningInfo.

## 5.5.4 Sending a request for provisioning information for direct communication with V2X Message Distribution Servers

Figure 5.5.4-1 shows a scenario where, the service consumer (e.g. a V2X application) sends a POST request to VIS to receive information about available V2X Message Distribution Servers. The response contains the required information.





**Figure 5.5.4-1: Flow of a V2X application requesting information about available V2X Message Distribution Servers**

The procedure of a V2X application requesting information about available V2X Message Distribution Servers, as illustrated in figure 5.5.4-1, consists of the following steps:

1) The service consumer sends a POST request to VIS. The message body contains the data structure V2xMsgDistributionServerInfo containing the information of the V2X Message Distribution Servers that the V2X application uses as criteria for direct interaction with relevant V2X Message Distribution Servers.

2) The VIS returns the "200 OK" response to the service consumer with the message body containing the V2xMsgDistributionServerInfo data structure.

## 5.5.5 Sending a request for journey-specific QoS predictions

Figure 5.5.5-1 shows a scenario where, the service consumer (e.g. a V2X application) sends a POST request to VIS to receive the predicted QoS correspondent to potential routes of a vehicular UE. The response contains the required information.





**Figure 5.5.5-1: Flow of a V2X application requesting the predicted QoS of a UE with potential routes**

The procedure of a V2X application requesting the predicted QoS for a vehicular UE with potential routes, as illustrated in figure 5.5.5-1, consists of the following steps:

1) The service consumer sends a POST request to VIS. The message body contains the data structure for the predicted QoS relevant to potential routes of the vehicular UE.

2) The VIS returns the "200 OK" response to the service consumer with the message body containing the predicted QoS data structure.

In addition to the request/response type of interaction for QoS predictions, VIS can use subscription/notification interactions with the service consumers that ensures more flexibility. In this context, the service consumer may subscribe to the journey-specific QoS prediction when the vehicle starts to drive towards a destination and VIS may continuously provide in-advance predictions on relevant events along the route, as such information becomes available.

Also in the case of multi-domain E2E predictive QoS notifications, VIS can use subscription/notification interactions with the service consumers that ensures more flexibility. In this context, the service consumer may subscribe to the multi-domain E2E predictive QoS notification when the vehicle enters a specific road traffic scenario (e.g. approaching an intersection, starting a lane merge operation, etc.) and VIS may continuously provide in-advance predictions on relevant events along the route, as such information becomes available.

## 5.5.6 REST based subscribe-notify model

### 5.5.6.1 Subscribing to event notifications

To receive notifications on selected V2X information events, the service consumer creates a subscription to certain specific V2X information event that is available at VIS. Figure 5.5.6.1-1 shows a scenario where the service consumer uses REST based procedures to create a subscription for V2X information event notifications.





**Figure 5.5.6.1-1: Flow of subscribing to the V2X information event notifications**

Subscribing to the V2X information event notifications, as illustrated in figure 5.5.6.1-1, consists of the following steps.

When the service consumer wants to receive notifications about the V2X information events, it creates a subscription to the V2X information event notifications:

1) The service consumer sends a POST request with the message body containing the {NotificationSubscription} data structure to the resource representing V2X information subscription. The variable {NotificationSubscription} is replaced with the data type specified for different V2X information event subscriptions, and it defines the subscribed event, the filtering criteria and the address where the service consumer wishes to receive the V2X information event notifications.

2) VIS sends "201 Created" response with the message body containing the data structure specific to that V2X information event subscription. The data structure contains the address of the resource created and the subscribed V2X information event type. The address of the resource created is also contained in the message header.

### 5.5.6.2 Receiving notification on expiry of V2X information event subscription

VIS may define an expiry time for the V2X information event subscription. In case expiry time is used, the time will be included in the {NotificationSubscription} data structure that is included in the response message to the subscription. Prior to the expiry, VIS will also send a notification to the service consumer that owns the subscription.

Figure 5.5.6.2-1 shows a scenario, where the service consumer receives a subscription expiry notification for the existing subscription.





**Figure 5.5.6.2-1: Flow of VIS sending a notification on expiry of the subscription**

Sending a notification on expiry of the subscription, as illustrated in figure 5.5.6.2-1 consists of the following steps. If VIS has defined an expiry time for the subscription, VIS will send a notification prior the expiry:

1) VIS sends a POST request to the callback reference address included by the service consumer in the subscription request. The POST request contains a data structure ExpiryNotification.

2) Service consumer sends a "204 No Content" response to the VIS.

### 5.5.6.3 Updating subscription for V2X information event notifications

Figure 5.5.6.3-1 shows a scenario where the service consumer needs to update an existing subscription for a V2X information event notification. The subscription update is triggered e.g. by the need to change the existing subscription, or due to the expiry of the subscription.





**Figure 5.5.6.3-1: Flow of service consumer updating subscription for V2X information event notifications**

Updating subscription for V2X information event notifications, as illustrated in figure 5.5.6.3-1, consists of the following steps.

When the service consumer needs to modify an existing subscription for V2X information event notifications, it can update the corresponding subscription as follows:

1) Service consumer updates the subscription resource by sending a PUT request to the resource representing the V2X information event subscription that was created with the modified data structure specific to that V2X information event subscription.

2) VIS returns "200 OK" with the message body containing the accepted data structure specific to that V2X information event subscription.

#### 5.5.6.4 Unsubscribing from V2X information event notifications

When the service consumer does not want to receive notifications anymore after subscribing to V2X information events, the service consumer unsubscribes from the V2X information event notifications. Figure 5.5.6.4-1 shows a scenario where the service consumer uses REST based procedures to delete the subscription for V2X information event notifications.





**Figure 5.5.6.4-1: Flow of unsubscribing from the V2X information event notifications**

Unsubscribing from the V2X information event notifications, as illustrated in figure 5.5.6.4-1, consists of the following steps.

When the service consumer does not want to receive the notifications anymore, it can unsubscribe from the V2X information notification events by deleting the subscription:

1) Service consumer sends a DELETE request to the resource representing the V2X information event subscription that was created.

2) VIS sends "204 No content" response.

### 5.5.7 Receiving V2X information event notifications about the provisioning information changes for V2X communication over Uu unicast

Figure 5.5.7-1 presents the scenario where the VIS sends V2X information event notification to the service consumer about the provisioning information changes for V2X communication over Uu unicast.





**Figure 5.5.7-1: Flow of receiving V2X information event notifications about the provisioning information changes for V2X communication over Uu unicast**

Receiving V2X information event notifications about the provisioning information changes for V2X communication over Uu unicast, as illustrated in figure 5.5.7-1, consists of the following steps:

1) VIS sends a POST request with the message body containing the ProvChgUuUniNotification data structure to the callback reference address included by the service consumer in the event subscription for the provisioning information changes for V2X communication over Uu unicast.

2) Service consumer sends a "204 No Content" response to the VIS.

## 5.5.8 Receiving V2X information event notifications about the provisioning information changes for V2X communication over Uu MBMS

Figure 5.5.8-1 presents the scenario where the VIS sends V2X information event notification to the service consumer about the provisioning information changes for V2X communication over Uu MBMS.





**Figure 5.5.8-1: Flow of receiving V2X information event notifications about the provisioning information changes for V2X communication over Uu MBMS**

Receiving V2X information event notifications about the provisioning information changes for V2X communication over Uu MBMS, as illustrated in figure 5.5.8-1, consists of the following steps:

1) VIS sends a POST request with the message body containing the ProvChgUuMbmsNotification data structure to the callback reference address included by the service consumer in the event subscription for the provisioning information changes for V2X communication over Uu MBMS.

2) Service consumer sends a "204 No Content" response to the VIS.

### 5.5.9 Receiving V2X information event notifications about the provisioning information changes for V2X communication over PC5

Figure 5.5.9-1 presents the scenario where the VIS sends V2X information event notification to the service consumer about the provisioning information changes for V2X communication over PC5.





**Figure 5.5.9-1: Flow of receiving V2X information event notifications about the provisioning information changes for V2X communication over PC5**

Receiving V2X information event notifications about the provisioning information changes for V2X communication over PC5, as illustrated in figure 5.5.9-1, consists of the following steps:

1) VIS sends a POST request with the message body containing the ProvChgPc5Notification data structure to the callback reference address included by the service consumer in the event subscription for the provisioning information changes for V2X communication over PC5.

2) Service consumer sends a "204 No Content" response to the VIS.

### 5.5.10 V2X message interoperability

#### 5.5.10.1 V2X message subscribe

The V2X message subscribe is the procedure for a service consumer (e.g. a MEC application or a MEC platform) to request to subscribe the V2X messages which come from different vehicle OEMs or operators.




**Figure 5.5.10.1-1: Flow of V2X message subscribe**

A service consumer requesting the subscription of V2X message from VIS, as illustrated in figure 5.5.10.1-1, consists of the following steps:

1) The service consumer sends a POST request with the message body containing the V2xMsgSubscription data structure to the resource representing V2X message subscription. The data structure defines the subscribed event and the address where the service consumer wishes to receive the event notifications.

2) VIS sends "201 Created" response with the message body containing the data structure specific to this subscription. The data structure contains the address of the resource created and the subscribed event type.

### 5.5.10.2 V2X message publication

The V2X message publication is the procedure for a service consumer (e.g. a MEC application or a MEC platform) to publish a V2X message to VIS who will then notify the subscribed service consumers.




**Figure 5.5.10.2-1: Flow of V2X message publication**

A service consumer requesting the publication of V2X message to VIS, as illustrated in figure 5.5.10.2-1, consists of the following steps:

1) Service consumer sends POST request to publish a V2X message to VIS. The POST request contains a data structure V2xMsgPublication.

2) VIS sends a "204 No Content" response.

### 5.5.10.3 V2X message notification

The V2X message notification is the procedure for the VIS to send a notification to service consumer (e.g. a MEC application or a MEC platform).




**Figure 5.5.10.3-1: Flow of V2X message notification**

VIS sends a notification to the subscribed service consumer, as illustrated in figure 5.5.10.3-1, with the following steps:

1) VIS sends a POST request with the message body containing the V2xMsgNotification data structure to the callback reference address included by the service consumer in the V2xMsgSubscription event subscription.

2) Service consumer sends a "204 No Content" response to the VIS.

## 5.6 Conclusions on VIS

MEC facilitates V2X interoperability in a multi-vendor, multi-network and multi-access environment. As described in previous clauses, the VIS is a required service for a MEC platform for it to enable V2X applications in a distributed edge cloud potentially spanning multiple networks and operators' systems.

The VIS is a MEC service that exposes selected V2X related information, including information available on the V2 reference point in 3GPP network. The VIS may be produced by a MEC application, e.g. the V2X application server, or by MEC platform.

The VIS facilitates the interaction between the MEC applications and the V2X Message Distribution Server (e.g. Message Broker) which is needed to distribute V2X messages related to non-session based V2X services. Alternatively, the VIS can also provide to MEC applications upon request the details to connect to V2X Message Distribution Servers for a direct interaction between a MEC application and a V2X Message Distribution Server.

The MEC platform gathers information through VIS in order to determine the required remote services and communication end points for the authorized V2X MEC applications. The MEC platform makes the required service and communication end points discoverable in the local service registry of the MEC platform.

# 6 Data model

## 6.1 Introduction

The following clauses provide the description of the data model.

## 6.2 Resource data types

### 6.2.1 Introduction

This clause defines data structures that shall be used in the resource representations.

### 6.2.2 Type: UuUnicastProvisioningInfo

This type represents the provisioning information required for V2X communication over Uu unicast. This information is per location (e.g. a cell of a base station or a geographical area) based.

The attributes of the UuUnicastProvisioningInfo shall follow the notations provided in table 6.2.2-1, as defined in ETSI TS 123 285 [10], ETSI TS 136 300 [11] and ETSI TS 136 423 [12].

**Table 6.2.2-1: Attributes of the UuUnicastProvisioningInfo**

| Attribute name | Data type | Cardinality | Description |
|---|---|---|---|
| timeStamp | TimeStamp | 0..1 | Time stamp. |
| proInfoUuUnicast | Structure (inlined) | 1..N | The provisioning information per location as defined below. |
| >locationInfo | LocationInfo | 1 | Location information to identify a cell of a base station or a particular geographical area. |
| >v2xApplicationServer | V2xApplicationServer | 1 | V2X Application Server address (consisting of IP address and UDP port) for unicast. |
| >neighbourCellInfo | UuUniNeighbourCellInfo | 0..N | The information of the neighbour cells in a visiting PLMN that support V2X communication over Uu unicast. |

## 6.2.3 Type: UuMbmsProvisioningInfo

This type represents the provisioning information required for V2X communication over Uu MBMS. This information is per location (e.g. a cell of a base station or a geographical area) based.

The attributes of the UuMbmsProvisioningInfo shall follow the notations provided in table 6.2.3-1, as defined in ETSI TS 123 285 [10], ETSI TS 136 300 [11] and ETSI TS 136 423 [12].

**Table 6.2.3-1: Attributes of the UuMbmsProvisioningInfo**

| Attribute name | Data type | Cardinality | Description |
|---|---|---|---|
| timeStamp | TimeStamp | 0..1 | Time stamp. |
| proInfoUuMbms | Structure (inlined) | 1..N | The provisioning information per location as defined below. |
| >locationInfo | LocationInfo | 1 | Location information to identify a cell of a base station or a particular geographical area. |
| >v2xServerUsd | V2xServerUsd | 1 | User Service Description for V2X Application Server is used to configure the UE for receiving local V2X Application Server information when it is provided over MBMS. |
| >neighbourCellInfo | UuMbmsNeighbourCellInfo | 0..N | The information of the neighbour cells in a visiting PLMN that support V2X communication over Uu MBMS. |

## 6.2.4 Type: Pc5ProvisioningInfo

This type represents the provisioning information required for V2X communication over PC5. This information is per location (e.g. a cell of a base station or a geographical area) based.

The attributes of the Pc5ProvisioningInfo shall follow the notations provided in table 6.2.4-1, as defined in ETSI TS 123 285 [10], ETSI TS 136 300 [11], ETSI TS 136 331 [14] and ETSI TS 136 321 [15].

**Table 6.2.4-1: Attributes of the Pc5ProvisioningInfo**

| Attribute name | Data type | Cardinality | Description |
|---|---|---|---|
| timeStamp | TimeStamp | 0..1 | Time stamp. |
| proInfoPc5 | Structure (inlined) | 1..N | The provisioning information per location as defined below. |
| >locationInfo | LocationInfo | 1 | Location information to identify a cell of a base station or a particular geographical area. |
| >dstLayer2Id | String | 1 | For sidelink communication, the Destination Layer-2 ID is set to the ProSe Layer-2 Group ID or Prose UE ID, see ETSI TS 136 321 [15].<br>PLMN operators coordinate to make sure Destination Layer-2 ID(s) for different V2X services are configured in a consistent manner. |
| >neighbourCellInfo | Pc5NeighbourCellInfo | 0..N | The information of the neighbour cells in a visiting PLMN that support V2X communication over PC5. |

## 6.2.5 Type: V2xMsgDistributionServerInfo

This type represents the information of one or more V2X Message Distribution Servers that is exchanged between the VIS and a service consumer (e.g. a MEC application) to enable a direct interaction among the service consumer and one or multiple V2X Message Distribution Servers.

The attributes of the V2xMsgDistributionServerInfo shall follow the notations provided in table 6.2.5-1.

**Table 6.2.5-1: Attributes of the V2xMsgDistributionServerInfo**

| Attribute name | Data type | Cardinality | Description |
|---|---|---|---|
| v2xMsgDistributionServer | V2xMsgDistributionServer | 1..N | Describes the information of the V2X Message Distribution Servers supported by the service consumer for direct communication. |
| locationInfo | LocationInfo | 0..N | Location information to identify a particular geographical area of interest to the service consumer for receiving V2X messages. |

## 6.2.6 Type: PredictedQos

This type represents the predicted QoS of a vehicular UE. This information is per UE potential route based.

The attributes of the PredictedQos shall follow the notations provided in table 6.2.6-1.

**Table 6.2.6-1: Attributes of the PredictedQos**

| Name | Data type | Cardinality | Remarks |
|---|---|---|---|
| predictionTarget | Enum (inlined) | 1 | Indicates target of QoS prediction. Valid values:<br>1. SINGLE_UE_PREDICTION: The predicted QoS is to be intended as journey-specific for a requesting vehicular UE.<br>2. E2E_APPLICATION_INSTANCE_PREDICTION: The E2E user plane link between two V2X application instances, where one instance relates to a single vehicular UE and the other instance to an application instance within another network, i.e. either another vehicular UE as in the V2N2V case, or an infrastructure element as in the V2N2I case.<br>Shall only be included in the request. |
| timeGranularity | TimeStamp | 0..1 | Time granularity of visiting a location. |
| locationGranularity | String | 1 | Granularity of visited location. Measured in meters. |
| noticePeriod | TimeStamp | 0..1 | Information on when the predicted QoS is needed at the service consumer interface. The value of the notice period depends on the application reaction that has to be triggered by the service consumer. The value of the notice period shall be equal or a multiple of the timeGranularity, if it is present. If present, it shall only be included in the request. |
| predictionArea | Structure (inlined) | 0..1 | Geographical area including the two ends of the user plane link between two V2X application instances.<br>It shall only be present when "predictionTarget" = "E2E_APPLICATION_INSTANCE_PREDICTION". |
| >center | LocationInfo | 1 | Center of geographical area including the two ends of the user plane link between two V2X application instances. |
| >radius | String | 1 | Radius of geographical area including the two ends of the user plane link between two V2X application instances. Measured in meters. |
| routes | Structure (inlined) | 0..N | Information relating to the potential routes of a vehicular UE.<br>Shall only be present when "predictionTarget" = "SINGLE_UE_PREDICTION". |
| >routeInfo | Structure (inlined) | 1..N | Information relating to a specific route.<br>The first structure shall relate to the route origin and the last to the route destination. Intermediate waypoint locations may also be provided. |
| >>location | LocationInfo | 1 | Vehicular UE location. |
| >>time | TimeStamp | 0..1 | Estimated time at the location. |
| qos | Structure (inlined) | 1 | Predicted QoS at the related time and vehicular UE location.<br>Shall only be included in the response. |
| >stream | Structure (inlined) | 1..N | Predicted QoS at the related time and vehicular UE location for the specific data stream. In case of 3GPP network, this is mapped to a QoS flow. Stream needs to also contain the stream ID that, in case of the 3GPP network, can be mapped on to the 5QI or QCI. |

| Name | Data type | Cardinality | Remarks |
|---|---|---|---|
| >>qosKpi | Structure (inlined) | 1..N | This structure contains the prediction for a specific QoS KPI related to a given data stream. |
| >>>kpiName | String | 1 | The name of the KPI (e.g. latency, UL bitrate, etc.).<br>It can be included in the request and in the response. |
| >>>kpiValue | String | 1 | Information on the predicted value for the specific QoS KPI. It can be in different forms, such as upper bound and lower bound, CDF, actual value, etc.<br>Shall only be included in the response. |
| >>>confidence | String | 0..1 | Confidence of the prediction, as returned by the relevant domain PF. The value and the measurement of the confidence depends on the SLA. Shall only be included in the response. |
| NOTE: The data type of locationGranularity is a string which indicates the granularity of a visited location by means of latitudinal and longitudinal margins. | | | |

NOTE: It is possible to use the PredictedQoS data type when the target of the QoS prediction is a certain area of the territory (in addition to the existing route), e.g. by defining a certain point in the space and a radius. Such case may be used by the service consumer to request a QoS prediction for the area related to the execution of a specific use case (e.g. lane merge, lane change, cross of an intersection, etc.). Such QoS prediction may refer to the collection of all the possible E2E user plane links between the vehicular UE in question and all the potential vehicular UEs and/or road infrastructure elements in the area.

### 6.2.7 Type: V2xMsgPublication

This type represents the V2X message that a service consumer publishes to VIS.

The attributes of the V2xMsgPublication shall follow the notations provided in table 6.2.7-1.

**Table 6.2.7-1: Attributes of the V2xMsgPublication**

| Attribute name | Data type | Cardinality | Description |
|---|---|---|---|
| msgPropertiesValues | V2xMsgPropertiesValues | 1 | List of message properties that is associated to the V2X message publication that can be used for filtering messages at the reception of the V2X message. |
| msgRepresentationFormat | String | 1 | The representation format of the binary V2X message, for example base64 or hexadecimal representation. |
| msgContent | String | 1 | Published V2X message content. Its format is defined by the standardization organization indicated by the attribute stdOrganization of the msgPropertiesValues attribute. |

## 6.3 Subscription data types

### 6.3.1 Introduction

This clause defines data structures for subscriptions.

### 6.3.2 Type: ProvChgUuUniSubscription

This type represents a subscription to the notifications from VIS about the provisioning information changes for V2X communication over Uu unicast.

The attributes of the ProvChgUuUniSubscription shall follow the indications provided in table 6.3.2-1.

**Table 6.3.2-1: Attributes of the ProvChgUuUniSubscription**

| Attribute name | Data type | Cardinality | Description |
|---|---|---|---|
| subscriptionType | String | 1 | Shall be set to "ProvChgUuUniSubscription". |
| callbackReference | Uri | 0..1 | URI exposed by the client on which to receive notifications via HTTP. See note. |
| requestTestNotification | Boolean | 0..1 | Shall be set to TRUE by the service consumer to request a test notification via HTTP on the callbackReference URI, as described in ETSI GS MEC 009 [9], clause 6.12a. Default: FALSE. |
| websockNotifConfig | WebsockNotifConfig | 0..1 | Provides details to negotiate and signal the use of a Websocket connection between VIS and the service consumer for notifications. See note. |
| _links | Structure (inlined) | 0..1 | Hyperlink related to the resource. This shall be only included in the HTTP responses and in HTTP PUT requests. |
| >self | LinkType | 1 | Self-referring URI. The URI shall be unique within the VIS API as it acts as an ID for the subscription. |
| filterCriteria | Structure (inlined) | 1 | List of filtering criteria for the subscription. Any filtering criteria from below, which is included in the request, shall also be included in the response. |
| >locationInfo | LocationInfo | 1 | Location information to identify a cell of a base station or a particular geographical area. |
| >v2xApplicationServer | V2xApplicationServer | 1 | V2X Application Server address (consisting of IP address and UDP port) for unicast. |
| >neighbourCellInfo | UuUniNeighbourCellInfo | 0..N | The information of the neighbour cells in a visiting PLMN that support V2X communication over Uu unicast. |
| expiryDeadline | TimeStamp | 0..1 | Time stamp. |
| NOTE: At least one of callbackReference and websockNotifConfig shall be provided by the service consumer. If both are provided, it is up to VIS to choose an alternative and return only that alternative in the response, as described in ETSI GS MEC 009 [9], clause 6.12a. | | | |

## 6.3.3 Type: ProvChgUuMbmsSubscription

This type represents a subscription to the notifications from VIS about the provisioning information changes for V2X communication over Uu MBMS.

The attributes of the ProvChgUuMbmsSubscription shall follow the indications provided in table 6.3.3-1.

**Table 6.3.3-1: Attributes of the ProvChgUuMbmsSubscription**

| Attribute name | Data type | Cardinality | Description |
|---|---|---|---|
| subscriptionType | String | 1 | Shall be set to "ProvChgUuMbmsSubscription". |
| callbackReference | Uri | 0..1 | URI exposed by the client on which to receive notifications via HTTP. See note. |
| requestTestNotification | Boolean | 0..1 | Shall be set to TRUE by the service consumer to request a test notification via HTTP on the callbackReference URI, as described in ETSI GS MEC 009 [9], clause 6.12a. Default: FALSE. |
| websockNotifConfig | WebsockNotifConfig | 0..1 | Provides details to negotiate and signal the use of a Websocket connection between VIS and the service consumer for notifications. See note. |
| _links | Structure (inlined) | 0..1 | Hyperlink related to the resource. This shall be only included in the HTTP responses and in HTTP PUT requests. |
| >self | LinkType | 1 | Self-referring URI. The URI shall be unique within the VIS API as it acts as an ID for the subscription. |
| filterCriteria | Structure (inlined) | 1 | List of filtering criteria for the subscription. Any filtering criteria from below, which is included in the request, shall also be included in the response. |
| >locationInfo | LocationInfo | 1 | Location information to identify a cell of a base station or a particular geographical area. |

| Attribute name | Data type | Cardinality | Description |
|---|---|---|---|
| >v2xServerUsd | V2xServerUsd | 1 | User Service Description for V2X Application Server is used to configure the UE for receiving local V2X Application Server information when it is provided over MBMS. |
| >neighbourCellInfo | UuMbmsNeighbourCellInfo | 0..N | The information of the neighbour cells in a visiting PLMN that support V2X communication over Uu MBMS. |
| expiryDeadline | TimeStamp | 0..1 | Time stamp. |
| NOTE: At least one of callbackReference and websockNotifConfig shall be provided by the service consumer. If both are provided, it is up to VIS to choose an alternative and return only that alternative in the response, as described in ETSI GS MEC 009 [9], clause 6.12a. | | | |

## 6.3.4 Type: ProvChgPc5Subscription

This type represents a subscription to the notifications from VIS about the provisioning information changes for V2X communication over PC5.

The attributes of the ProvChgPc5Subscription shall follow the indications provided in table 6.3.4-1.

**Table 6.3.4-1: Attributes of the ProvChgPc5Subscription**

| Attribute name | Data type | Cardinality | Description |
|---|---|---|---|
| subscriptionType | String | 1 | Shall be set to "ProvChgPc5Subscription". |
| callbackReference | Uri | 0..1 | URI exposed by the client on which to receive notifications via HTTP. See note. |
| requestTestNotification | Boolean | 0..1 | Shall be set to TRUE by the service consumer to request a test notification via HTTP on the callbackReference URI, as described in ETSI GS MEC 009 [9], clause 6.12a. Default: FALSE. |
| websockNotifConfig | WebsockNotifConfig | 0..1 | Provides details to negotiate and signal the use of a Websocket connection between VIS and the service consumer for notifications. See note. |
| _links | Structure (inlined) | 0..1 | Hyperlink related to the resource. This shall be only included in the HTTP responses and in HTTP PUT requests. |
| >self | LinkType | 1 | Self-referring URI. The URI shall be unique within the VIS API as it acts as an ID for the subscription. |
| filterCriteria | Structure (inlined) | 1 | List of filtering criteria for the subscription. Any filtering criteria from below, which is included in the request, shall also be included in the response. |
| >locationInfo | LocationInfo | 1 | Location information to identify a cell of a base station or a particular geographical area. |
| >dstLayer2Id | String | 1 | For sidelink communication, the Destination Layer-2 ID is set to the ProSe Layer-2 Group ID or Prose UE ID, see ETSI TS 136 321 [15]. |
| >neighbourCellInfo | Pc5NeighbourCellInfo | 0..N | The information of the neighbour cells in a visiting PLMN that support V2X communication over PC5. |
| expiryDeadline | TimeStamp | 0..1 | Time stamp. |
| NOTE: At least one of callbackReference and websockNotifConfig shall be provided by the service consumer. If both are provided, it is up to VIS to choose an alternative and return only that alternative in the response, as described in ETSI GS MEC 009 [9], clause 6.12a. | | | |

## 6.3.5 Type: V2xMsgSubscription

This type represents a subscription to notification of V2X message.

The attributes of the V2xMsgSubscription shall follow the notations provided in table 6.3.5-1.

**Table 6.3.5-1: Attributes of the V2xMsgSubscription**

| Attribute name | Data type | Cardinality | Description |
|---|---|---|---|
| subscriptionType | String | 1 | Shall be set to "V2xMsgSubscription". |
| callbackReference | Uri | 0..1 | URI exposed by the client on which to receive notifications via HTTP. See note. |
| requestTestNotification | Boolean | 0..1 | Shall be set to TRUE by the service consumer to request a test notification via HTTP on the callbackReference URI, as described in ETSI GS MEC 009 [9], clause 6.12a. Default: FALSE. |
| websockNotifConfig | WebsockNotifConfig | 0..1 | Provides details to negotiate and signal the use of a Websocket connection between VIS and the service consumer for notifications. See note. |
| _links | Structure (inlined) | 0..1 | Hyperlink related to the resource. This shall be only included in the HTTP responses and in HTTP PUT requests. |
| >self | LinkType | 1 | Self-referring URI. The URI shall be unique within the VIS API as it acts as an ID for the subscription. |
| filterCriteria | V2xMsgFilterCriteria | 1 | List of filtering criteria aimed to filter V2X messages at the reception. Any filtering criteria which is included in the request, shall also be included in the response. |
| expiryDeadline | TimeStamp | 0..1 | Time stamp. |
| NOTE: At least one of callbackReference and websockNotifConfig shall be provided by the service consumer. If both are provided, it is up to VIS to choose an alternative and return only that alternative in the response, as described in ETSI GS MEC 009 [9], clause 6.12a. | | | |

## 6.3.6 Type: PredQosSubscription

This type represents a subscription to notification of predicted QoS information.

The attributes of the PredQosSubscription shall follow the notations provided in table 6.3.6-1.

**Table 6.3.6-1: Attributes of the PredQosSubscription**

| Attribute name | Data type | Cardinality | Description |
|---|---|---|---|
| subscriptionType | String | 1 | Shall be set to "PredQosSubscription". |
| callbackReference | Uri | 0..1 | URI exposed by the client on which to receive notifications via HTTP. See note. |
| requestTestNotification | Boolean | 0..1 | Shall be set to TRUE by the service consumer to request a test notification via HTTP on the callbackReference URI, as described in ETSI GS MEC 009 [9], clause 6.12a. Default: FALSE. |
| websockNotifConfig | WebsockNotifConfig | 0..1 | Provides details to negotiate and signal the use of a Websocket connection between VIS and the service consumer for notifications. See note. |
| _links | Structure (inlined) | 0..1 | Hyperlink related to the resource. This shall be only included in the HTTP responses and in HTTP PUT requests. |
| >self | LinkType | 1 | Self-referring URI. The URI shall be unique within the VIS API as it acts as an ID for the subscription. |
| filterCriteria | QosPredFilterCriteria | 1 | List of filtering criteria aimed to filter QoS predictions at the reception. Any filtering criteria included in the request, shall also be included in the response. |
| expiryDeadline | TimeStamp | 0..1 | Time stamp. |
| NOTE: At least one of callbackReference and websockNotifConfig shall be provided by the service consumer. If both are provided, it is up to VIS to choose an alternative and return only that alternative in the response, as described in ETSI GS MEC 009 [9], clause 6.12a. | | | |

## 6.3.7 Type: SubscriptionLinkList

This type represents a list of links related to currently existing subscriptions for the service consumer. This information is returned when sending a request to receive current subscriptions.

**Table 6.3.7-1: Attributes of the SubscriptionLinkList**

| Attribute name | Data type | Cardinality | Description |
|---|---|---|---|
| _links | Structure (inlined) | 1 | List of hyperlinks related to the resource. |
| >self | LinkType | 1 | URI of this resource. |
| >subscriptions | Structure (inlined) | 0..N | The service consumer's subscriptions. |
| >>href | Uri | 1 | The URI referring to the subscription. |
| >>subscriptionType | String | 1 | Type of the subscription. The values are as defined in the "subscriptionType" attribute for each different V2X information event subscription data type. |

# 6.4 Notifications data types

## 6.4.1 Introduction

This clause defines data structures that define notifications.

## 6.4.2 Type: ProvChgUuUniNotification

This type represents a notification from VIS with regards to the provisioning information changes for V2X communication over Uu unicast. The notification is sent by the VIS to inform about the changes.

The attributes of the ProvChgUuUniNotification shall follow the indications provided in table 6.4.2-1.

**Table 6.4.2-1: Attributes of the ProvChgUuUniNotification**

| Attribute name | Data type | Cardinality | Description |
|---|---|---|---|
| notificationType | String | 1 | Shall be set to "ProvChgUuUniNotification". |
| timeStamp | TimeStamp | 0..1 | Time stamp. |
| locationInfo | LocationInfo | 1 | Location information to identify a cell of a base station or a particular geographical area. |
| v2xApplicationServer | V2xApplicationServer | 0..1 | V2X Application Server address (consisting of IP address and UDP port) for unicast. |
| neighbourCellInfo | UuUniNeighbourCellInfo | 0..N | The information of the neighbour cells in a visiting PLMN that support V2X communication over Uu unicast. |

## 6.4.3 Type: ProvChgUuMbmsNotification

This type represents a notification from VIS with regards to the provisioning information changes for V2X communication over Uu MBMS. The notification is sent by the VIS to inform about the changes.

The attributes of the ProvChgUuMbmsNotification shall follow the indications provided in table 6.4.3-1.

**Table 6.4.3-1: Attributes of the ProvChgUuMbmsNotification**

| Attribute name | Data type | Cardinality | Description |
|---|---|---|---|
| notificationType | String | 1 | Shall be set to "ProvChgUuMbmsNotification". |
| timeStamp | TimeStamp | 0..1 | Time stamp. |
| locationInfo | LocationInfo | 1 | Location information to identify a cell of a base station or a particular geographical area. |
| v2xServerUsd | V2xServerUsd | 0..1 | User Service Description for V2X Application Server is used to configure the UE for receiving local V2X Application Server information when it is provided over MBMS. |
| neighbourCellInfo | UuMbmsNeighbourCellInfo | 0..N | The information of the neighbour cells in a visiting PLMN that support V2X communication over Uu MBMS. |

### 6.4.4 Type: ProvChgPc5Notification

This type represents a notification from VIS with regards to the provisioning information changes for V2X communication over PC5. The notification is sent by the VIS to inform about the changes.

The attributes of the ProvChgPc5Notification shall follow the indications provided in table 6.4.4-1.

**Table 6.4.4-1: Attributes of the ProvChgPc5Notification**

| Attribute name | Data type | Cardinality | Description |
|---|---|---|---|
| notificationType | String | 1 | Shall be set to "ProvChgPc5Notification". |
| timeStamp | TimeStamp | 0..1 | Time stamp. |
| locationInfo | LocationInfo | 1 | Location information to identify a cell of a base station or a particular geographical area. |
| dstLayer2Id | String | 0..1 | For sidelink communication, the Destination Layer-2 ID is set to the ProSe Layer-2 Group ID or Prose UE ID, see ETSI TS 136 321 [15]. |
| neighbourCellInfo | Pc5NeighbourCellInfo | 0..N | The information of the neighbour cells in a visiting PLMN that support V2X communication over PC5. |

### 6.4.5 Type: V2xMsgNotification

This type represents a notification for informing the subscribers about the V2X message.

The attributes of the V2xMsgNotification shall follow the notations provided in table 6.4.5-1.

**Table 6.4.5-1: Attributes of the V2xMsgNotification**

| Attribute name | Data type | Cardinality | Description |
|---|---|---|---|
| notificationType | String | 1 | Shall be set to "V2xMsgNotification". |
| timeStamp | TimeStamp | 1 | Date and time of the notification generation. |
| msgPropertiesValues | V2xMsgPropertiesValues | 1 | List of message properties that is associated to the V2X message. |
| msgRepresentationFormat | String | 1 | The representation format of the binary V2X message, for example base64 or hexadecimal representation. |
| msgContent | String | 1 | Published V2X message content. The format of the string is defined by the standardization organization indicated by the attribute stdOrganization of the msgPropertiesValues attribute. |
| _links | Structure (inlined) | 1 | Links to resources related to this notification. |
| >subscription | LinkType | 1 | A link to the related subscription. |

### 6.4.6 Type: TestNotification

This type represents a test notification from VIS to determine if the Websocket method is to be utilized for the VIS to issue notifications for a subscription, as defined in clause 6.12a of ETSI GS MEC 009 [9].

**Table 6.4.6-1: Attributes of the TestNotification**

| Attribute name | Data type | Cardinality | Description |
|---|---|---|---|
| notificationType | String | 1 | Shall be set to "TestNotification". |
| _links | Structure (inlined) | 1 | Hyperlink related to the resource. |
| >subscription | LinkType | 1 | URI identifying the subscription for the test notification. |

# 6.5 Referenced structured data types

## 6.5.1 Introduction

This clause defines data structures that are referenced from data structures defined in the previous clauses, but are neither resource representations nor bound to any pub/sub mechanism.

## 6.5.2 Type: TimeStamp

This type represents a time stamp.

**Table 6.5.2-1: Attributes of the TimeStamp**

| Attribute name | Data type | Cardinality | Description |
|---|---|---|---|
| seconds | Uint32 | 1 | The seconds part of the time. Time is defined as Unix-time since January 1, 1970, 00:00:00 UTC. |
| nanoSeconds | Uint32 | 1 | The nanoseconds part of the time. Time is defined as Unix-time since January 1, 1970, 00:00:00 UTC. |

## 6.5.3 Type: LocationInfo

This type represents the location information.

The attributes of the LocationInfo shall follow the notations provided in table 6.5.3-1.

**Table 6.5.3-1: Attributes of the LocationInfo**

| Attribute name | Data type | Cardinality | Description |
|---|---|---|---|
| ecgi | Ecgi | 0..1 | E-UTRAN Cell Global Identifier of the serving cell |
| geoArea | Structure (inlined) | 0..1 | Information of a geographical area |
| >latitude | Float | 1 | Latitude (DATUM = WGS84)<br>-90 to 90 in decimal degree format DDD.ddd |
| >longitude | Float | 1 | Longitude (DATUM = WGS84)<br>-180 to 180 in decimal degree format DDD.ddd |
| NOTE: Either ecgi or geoArea shall be present, but not both. | | | |

## 6.5.4 Type: Plmn

This type represents a PLMN Identity.

The attributes of the Plmn shall follow the notations provided in table 6.5.4-1, as defined in ETSI TS 136 413 [13].

**Table 6.5.4-1: Attributes of the Plmn**

| Attribute name | Data type | Cardinality | Description |
|---|---|---|---|
| mcc | String | 1 | The Mobile Country Code part of PLMN Identity. |
| mnc | String | 1 | The Mobile Network Code part of PLMN Identity. |

## 6.5.5 Type: Ecgi

This type represents an E-UTRAN Cell Global Identifier.

The attributes of the Ecgi shall follow the notations provided in table 6.5.5-1, as defined in ETSI TS 136 423 [12] and ETSI TS 136 413 [13].

**Table 6.5.5-1: Attributes of the Ecgi**

| Attribute name | Data type | Cardinality | Description |
|---|---|---|---|
| plmn | Plmn | 1 | Public Land Mobile Network Identity. |
| cellId | CellId | 1 | The E-UTRAN Cell Identity. |

## 6.5.6 Type: FddInfo

This type represents an FDD information.

The attributes of the FddInfo shall follow the notations provided in table 6.5.6-1, as defined in ETSI TS 136 423 [12].

**Table 6.5.6-1: Attributes of the FddInfo**

| Attribute name | Data type | Cardinality | Description |
|---|---|---|---|
| ulEarfcn | Earfcn | 1 | |
| dlEarfcn | Earfcn | 1 | |
| ulTransmissionBandwidth | TransmissionBandwidth | 1 | |
| dlTransmissionBandwidth | TransmissionBandwidth | 1 | |

## 6.5.7 Type: TddInfo

This type represents a TDD information.

The attributes of the TddInfo shall follow the notations provided in table 6.5.7-1, as defined in ETSI TS 136 423 [12].

**Table 6.5.7-1: Attributes of the TddInfo**

| Attribute name | Data type | Cardinality | Description |
|---|---|---|---|
| earfcn | Earfcn | 1 | |
| transmissionBandwidth | TransmissionBandwidth | 1 | |
| subframeAssignment | String | 1 | Uplink-downlink subframe configuration information. |

## 6.5.8 Type: V2xApplicationServer

This type represents a V2X Application Server address (consisting of IP address and UDP port) for unicast.

**Table 6.5.8-1: Attributes of the V2xApplicationServer**

| Attribute name | Data type | Cardinality | Description |
|---|---|---|---|
| ipAddress | String | 1 | |
| udpPort | String | 1 | |

## 6.5.9 Type: UuUniNeighbourCellInfo

This type represents a neighbour cell information in a visiting PLMN that supports V2X communication over Uu unicast.

**Table 6.5.9-1: Attributes of the UuUniNeighbourCellInfo**

| Attribute name | Data type | Cardinality | Description |
|---|---|---|---|
| plmn | Plmn | 1 | Public Land Mobile Network Identity. |
| ecgi | Ecgi | 1 | E-UTRAN Cell Global Identifier. |
| pci | Integer | 1 | Physical Cell Identifier. |
| fddInfo | FddInfo | 1 | Information for FDD operation. |
| tddInfo | TddInfo | 1 | Information for TDD operation. |

## 6.5.10 Type: V2xServerUsd

This type represents a User Service Description for V2X Application Server.

**Table 6.5.10-1: Attributes of the V2xServerUsd**

| Attribute name | Data type | Cardinality | Description |
|---|---|---|---|
| tmgi | Structure (inlined) | | Temporary Mobile Group Identity (TMGI), which is used within MBMS to uniquely identify Multicast and Broadcast bearer services. |
| >mbmsServiceId | String | 1 | MBMS Service ID consisting of three octets. |
| >mcc | String | 1 | The Mobile Country Code part of PLMN Identity. |
| >mnc | String | 1 | The Mobile Network Code part of PLMN Identity. |
| serviceAreaIdentifier | String | 1..N | A list of service area identifier for the applicable MBMS broadcast area. |
| sdpInfo | Structure (inlined) | 1 | SDP with IP multicast address and port number used for V2X communication via MBMS. |
| >ipMulticastAddress | String | 1 | |
| >portNumber | String | 1 | |

## 6.5.11 Type: UuMbmsNeighbourCellInfo

This type represents a neighbour cell information in a visiting PLMN that supports V2X communication over Uu MBMS.

**Table 6.5.11-1: Attributes of the UuMbmsNeighbourCellInfo**

| Attribute name | Data type | Cardinality | Description |
|---|---|---|---|
| plmn | Plmn | 1 | Public Land Mobile Network Identity. |
| ecgi | Ecgi | 1 | E-UTRAN Cell Global Identifier. |
| pci | Integer | 1 | Physical Cell Identifier. |
| fddInfo | FddInfo | 1 | Information for FDD operation. |
| tddInfo | TddInfo | 1 | Information for TDD operation. |
| mbmsServiceAreaIdentity | String | 1..N | Supported MBMS Service Area Identities in the cell. |

## 6.5.12 Type: Pc5NeighbourCellInfo

This type represents a neighbour cell information in a visiting PLMN that supports V2X communication over PC5.

**Table 6.5.12-1: Attributes of the Pc5NeighbourCellInfo**

| Attribute name | Data type | Cardinality | Description |
|---|---|---|---|
| plmn | Plmn | 1 | Public Land Mobile Network Identity. |
| ecgi | Ecgi | 1 | E-UTRAN Cell Global Identifier. |
| siV2xConfig | SystemInformationBlockType21 | 1 | V2X sidelink communication configuration, as defined in ETSI TS 136 331 [14]. |

## 6.5.13 Type: LinkType

This type represents a type of link.

**Table 6.5.13-1: Attributes of the LinkType**

| Attribute name | Data type | Cardinality | Description |
|---|---|---|---|
| href | Uri | 1 | URI referring to a resource |

## 6.5.14 Type: V2xMsgPropertiesValues

This type represents the properties that can be associated to a V2X message when it is published, or a notification in relation to the V2X message is issued. These properties are also used to match the filter criteria defined in the message subscription.

**Table 6.5.14-1: Attributes of the V2xMsgPropertiesValues**

| Attribute name | Data type | Cardinality | Description |
|---|---|---|---|
| stdOrganization | Enum | 1 | Standardization organization which defines the published V2X message type:<br>• ETSI: European Telecommunications Standards Institute.<br>See note 1. |
| msgType | Enum | 1 | Published V2X message type. Its value is defined by the standardization organization indicated by the attribute stdOrganization. See note 2. |
| msgProtocolVersion | Integer | 1 | Protocol version of the V2X message (0..255). See note 3. |
| locationInfo | LocationInfo | 1 | Location information to identify a cell of a base station or a particular geographical area to which the V2X message can be associated. |
| NOTE 1: Other standardization organizations could be added as needed.<br>NOTE 2: The V2X message types of ETSI shall be used as specified in ETSI TS 102 894-2 [6], clause A.114.<br>NOTE 3: The message protocol version of ETSI shall be used as specified in ETSI TS 102 894-2 [6], clause A.114. | | | |

## 6.5.15 Type: V2xMsgFilterCriteria

This type represents the filter criteria that can be used when performing a subscription to notification of V2X messages.

**Table 6.5.15-1: Attributes of the V2xMsgFilterCriteria**

| Attribute name | Data type | Cardinality | Description |
|---|---|---|---|
| stdOrganization | Enum | 1 | Standardization organization which defines the published V2X message type:<br>• ETSI: European Telecommunications Standards Institute.<br>See note 1. |
| msgType | Enum | 0..N | Published V2X message type. Its value is defined by the standardization organization indicated by the attribute stdOrganization. See note 2. |
| msgProtocolVersion | Integer | 0..N | Protocol version of the V2X message (0..255). See note 3. |
| locationInfo | LocationInfo | 0..N | Location information to identify a cell of a base station or a particular geographical area to which the V2X message can be associated. |
| NOTE 1: Other standardization organizations could be added as needed.<br>NOTE 2: The V2X message types of ETSI shall be used as specified in ETSI TS 102 894-2 [6], clause A.114.<br>NOTE 3: The message protocol version of ETSI shall be used as specified in ETSI TS 102 894-2 [6], clause A.114. | | | |

## 6.5.16 Type: V2xMsgDistributionServer

This type represents the information about a V2X Message Distribution Server that can be exchanged between a service consumer (e.g. a MEC application) and the VIS. The service consumer uses this data structure for providing the criteria the V2X Message Distribution Server needs to fulfil for direct interaction with it. The VIS uses this data structure to provide to the service consumer the information needed to directly connect to V2X Message Distribution Servers fulfilling these criteria.

**Table 6.5.16-1: Attributes of the V2xMsgDistributionServer**

| Attribute name | Data type | Cardinality | Description |
|---|---|---|---|
| infoProtocol | Structure (inlined) | 1 | Specifics of the application layer protocol of V2X Message Distribution Server. |
| >msgProtocol | Enum | 1..N | Numerical value corresponding to the application layer protocol supported by the service consumer. For the msgProtocol, the following values are currently defined (see note):<br>0 = MQTT v3.1.0<br>1 = MQTT v3.1.1<br>2 = MQTT v5<br>3 = MQTT-SN<br>4 = AMQP 1.0 |
| >protImplementation | String | 1 | Implementation specifics of application layer protocol, e.g. programming language. |
| infoConnection | Structure (inlined) | 0..1 | Connection information of the V2X Message Distribution Server the service consumer can use for direct connection. Shall only be included in the response. |
| >ipAddress | String | 1 | IP address of the V2X Message Distribution Server. |
| >port_number | Integer (0..65535) | 1 | Port number of the V2X Message Distribution Server. |
| NOTE: Other application layer protocols (and versions thereof) may be added as needed. | | | |

## 6.5.17 Type: QosPredFilterCriteria

This type represents the filter criteria that can be used when performing a subscription to notification of QoS prediction messages.

**Table 6.5.17-1: Attributes of the QosPredFilterCriteria**

| Attribute name | Data type | Cardinality | Description |
|---|---|---|---|
| streamId | String | 0..1 | The predicted QoS at the related time and vehicular UE location is provided for a specific data stream. In case of 3GPP network, this is mapped to a QoS flow. Stream needs to also contain the stream ID which, in case of the 3GPP network, can be mapped on to the 5QI or QCI. See note. |
| NOTE: Other identifiers could be added as needed. | | | |

## 6.5.18 Type: WebsockNotifConfig

This type represents configuration for the delivery of subscription notifications over Websockets per the pattern defined in clause 6.12a of ETSI GS MEC 009 [9].

**Table 6.5.18-1: Attributes of the WebsockNotifConfig**

| Attribute name | Data type | Cardinality | Description |
|---|---|---|---|
| websocketUri | Uri | 0..1 | Set by VIS to indicate to the service consumer the Websocket URI to be used for delivering notifications. |
| requestWebsocketUri | Boolean | 0..1 | Set to TRUE by the service consumer to indicate that Websocket delivery is requested. |

# 6.6 Referenced simple data types and enumerations

## 6.6.1 Introduction

This clause defines simple data types and enumerations that can be referenced from data structures defined in the previous clauses.

### 6.6.2 Type: CellId

This type represents an E-UTRAN Cell Identifier.

The attributes of the CellId shall follow the notations provided in table 6.6.2-1, as defined in ETSI TS 136 413 [13].

**Table 6.6.2-1: Attributes of the CellId**

| Attribute name | Data type | Cardinality | Description |
|---|---|---|---|
| cellId | String | 1 | E-UTRAN Cell Identity as a bit string (size (28)). |

### 6.6.3 Type: Earfcn

This type represents an E-UTRA Absolute Radio Frequency Channel Number, which defines the carrier frequency used in a cell for a given direction (UL or DL) in FDD or for both UL and DL directions in TDD.

The attributes of the EARFCN shall follow the notations provided in table 6.6.3-1, as defined in ETSI TS 136 413 [13].

**Table 6.6.3-1: Attributes of the Earfcn**

| Attribute name | Data type | Cardinality | Description |
|---|---|---|---|
| earfcn | Integer | 1 | E-UTRA Absolute Radio Frequency Channel Number, range (0... 65535) |

### 6.6.4 Type: TransmissionBandwidth

This type represents a Transmission Bandwidth, which is used to indicate the UL or DL transmission bandwidth expressed in units of resource blocks. The values bw6, bw15, bw25, bw50, bw75, bw100 correspond to the number of resource blocks 6, 15, 25, 50, 75, 100.

The attributes of the TransmissionBandwidth shall follow the notations provided in table 6.6.4-1, as defined in ETSI TS 136 413 [13].

**Table 6.6.4-1: Attributes of the TransmissionBandwidth**

| Attribute name | Data type | Cardinality | Description |
|---|---|---|---|
| transmissionBandwidth | Enum | 1 | Numeric value corresponding to the transmission bandwidth expressed in units of resource blocks as follows:<br>1 = bw6 (6 resource blocks)<br>2 = bw15 (15 resource blocks)<br>3 = bw25 (25 resource blocks)<br>4 = bw50 (50 resource blocks)<br>5 = bw75 (75 resource blocks)<br>6 = bw100 (100 resource blocks) |

# 7 API definition

## 7.1 Introduction

This clause defines the resources and operations of the VIS API.

## 7.2 Global definitions and resource structure

All resource URIs of this API shall have the following root:

**{apiRoot}/{apiName}/{apiVersion}/**

"apiRoot" and "apiName" are discovered using the service registry. It includes the scheme ("https"), host and optional port, and an optional prefix string. The "apiName" shall be set to "vis" and "apiVersion" shall be set to "v2" for the present document.

The API shall support HTTP over TLS (also known as HTTPS) using TLS version 1.2 (as defined by IETF RFC 5246 [3]). TLS 1.3 (including the new specific requirements for TLS 1.2 implementations) defined by IETF RFC 8446 [7] should be supported. HTTP without TLS shall not be used. Versions of TLS earlier than 1.2 shall neither be supported nor used.

TLS implementations should meet or exceed the security algorithm, key length and strength requirements specified in clause 6.2.3 of ETSI GS MEC 009 [9] (if TLS version 1.2 as defined by IETF RFC 5246 [3] is used) or clause 6.2.2 of ETSI GS MEC 009 [9] (if TLS version 1.3 as defined by IETF RFC 8446 [7] is used) of ETSI TS 133 210 [8] (Release 16 or later).

The content format of JSON shall be supported. The JSON format is signalled by the content type "application/json".

This API shall require the use of the OAuth 2.0 client credentials grant type according to IETF RFC 6749 [4] with bearer tokens according to IETF RFC 6750 [5]. See clause 6.16 of ETSI GS MEC 009 [9] for more information. How the token endpoint and client credentials are provisioned into the MEC applications is out of scope of the present document.

This API supports additional application-related error information to be provided in the HTTP response when an error occurs. See clause 6.15 of ETSI GS MEC 009 [9] for more information.

Figure 7.2-1 illustrates the resource URI structure of this API. Table 7.2-1 provides an overview of the resources defined by the present document, and the applicable HTTP methods.





**Figure 7.2-1: Resource URI structure of the VIS API**

**Table 7.2-1: Resources and methods overview**

| Resource name | Resource URI | HTTP method | Meaning |
|---|---|---|---|
| Uu unicast provisioning information | /queries/uu_unicast_provisioning_info | GET | Retrieve provisioning information required for V2X communication over Uu unicast. |
| Uu MBMS provisioning information | /queries/uu_mbms_provisioning_info | GET | Retrieve provisioning information required for V2X communication over Uu MBMS. |
| PC5 provisioning information | /queries/pc5_provisioning_info | GET | Retrieve provisioning information required for V2X communication over PC5. |
| Provide V2X Message Distribution Server information | /provide_v2x_msg_distribution_server_info | POST | Provide V2X Message Distribution Servers information required for direct connection with a service consumer. |
| Provide predicted QoS task | /provide_predicted_qos | POST | Provide predicted QoS based on route information. |
| Publish V2X message task | /publish_v2x_message | POST | Publish a V2X message to VIS. |
| All subscriptions for a subscriber | /subscriptions | GET | Retrieve a list of active subscriptions for this subscriber. |
| | | POST | Create a new subscription. |
| Existing subscription | /subscriptions/{subscriptionId} | GET | Retrieve information on current specific subscription. |
| | | PUT | Modify existing subscription by sending a new data structure. |
| | | DELETE | Cancel the existing subscription. |
| Notification callback | Client provided callback reference | POST | Send a notification. |

NOTE: The present document supports a single VIS consumer requesting QoS predictions based on either alternative planned routes of the corresponding single vehicular UE or based on a prediction area involving possibly multiple E2E data paths between application instances.

# 7.3 Resource: uu_unicast_provisioning_info

## 7.3.1 Description

This resource is queried to retrieve information required for V2X communication over Uu unicast.

## 7.3.2 Resource definition

Resource URI: **{apiRoot}/vis/v2/queries/uu_unicast_provisioning_info**

This resource shall support the resource URI variables defined in table 7.3.2-1.

**Table 7.3.2-1: Resource URI variables for resource "uu_unicast_provisioning_info"**

| Name | Definition |
|---|---|
| apiRoot | See clause 7.2 |

## 7.3.3 Resource methods

### 7.3.3.1 GET

The GET method is used to query provisioning information for V2X communication over Uu unicast.

This method shall support the URI query parameters, request and response data structures, and response codes, as specified in tables 7.3.3.1-1 and 7.3.3.1-2.

**Table 7.3.3.1-1: URI query parameters supported by the GET method on this resource**

| Name | Data type | Cardinality | Remarks |
|---|---|---|---|
| location_info | String | 1 | Comma separated list of locations to identify a cell of a base station or a particular geographical area, formatted as follows for the two cases:<br><br>…/uu_unicast_provisioning_info?location_info=ecgi,{String}<br><br>Where the String is made up of 1 to N comma separated ecgi values (reference clause 6.5.5).<br><br>…/uu_unicast_provisioning_info?location_info=latitude,{String},longitude,{String}<br><br>Where the two strings are made up of 1 to N comma separated latitude and longitude values respectively (reference clause 6.5.3), such that the number of latitude and longitude values shall be equal.<br><br>Examples of query formats when N=2 locations are provided below:<br><br>…/uu_unicast_provisioning_info?location_info=ecgi,1357924680,1357924681<br><br>…/uu_unicast_provisioning_info?location_info=latitude,000.000,001.000,longitude,000.000,001.000 |

**Table 7.3.3.1-2: Data structures supported by the GET request/response on this resource**

| Request body | Data type | Cardinality | Remarks | |
|---|---|---|---|---|
| | n/a | | | |
| **Response body** | **Data type** | **Cardinality** | **Response Codes** | **Remarks** |
| | UuUnicastProvisioningInfo | 1 | 200 OK | Upon success, a response body containing the Uu unicast provisioning information is returned. |
| | ProblemDetails | 0..1 | 400 Bad Request | It is used to indicate that incorrect parameters were passed to the request.<br><br>In the returned ProblemDetails structure, the "detail" attribute should convey more information about the error. |
| | ProblemDetails | 0..1 | 401 Unauthorized | It is used when the client did not submit credentials.<br><br>In the returned ProblemDetails structure, the "detail" attribute should convey more information about the error. |
| | ProblemDetails | 1 | 403 Forbidden | The operation is not allowed given the current status of the resource.<br><br>More information shall be provided in the "detail" attribute of the "ProblemDetails" structure. |

| | Data type | Cardinality | Response Codes | Remarks |
|---|---|---|---|---|
| **Response body** | ProblemDetails | 0..1 | 404 Not Found | It is used when a client provided a URI that cannot be mapped to a valid resource URI.<br><br>In the returned ProblemDetails structure, the "detail" attribute should convey more information about the error. |
| | ProblemDetails | 0..1 | 406 Not Acceptable | It is used to indicate that the server cannot provide any of the content formats supported by the client.<br><br>In the returned ProblemDetails structure, the "detail" attribute should convey more information about the error. |
| | ProblemDetails | 0..1 | 429 Too Many Requests | It is used when a rate limiter has triggered.<br><br>In the returned ProblemDetails structure, the "detail" attribute should convey more information about the error. |

#### 7.3.3.2 PUT

Not applicable.

#### 7.3.3.3 PATCH

Not applicable.

#### 7.3.3.4 POST

Not applicable.

#### 7.3.3.5 DELETE

Not applicable.

## 7.4 Resource: uu_mbms_provisioning_info

### 7.4.1 Description

This resource is queried to retrieve information required for V2X communication over Uu MBMS.

### 7.4.2 Resource definition

Resource URI: **{apiRoot}/vis/v2/queries/uu_mbms_provisioning_info**

This resource shall support the resource URI variables defined in table 7.4.2-1.

**Table 7.4.2-1: Resource URI variables for resource "uu_mbms_provisioning_info"**

| Name | Definition |
|---|---|
| apiRoot | See clause 7.2 |

## 7.4.3 Resource methods

### 7.4.3.1 GET

The GET method is used to query provisioning information for V2X communication over Uu MBMS.

This method shall support the URI query parameters, request and response data structures, and response codes, as specified in tables 7.4.3.1-1 and 7.4.3.1-2.

**Table 7.4.3.1-1: URI query parameters supported by the GET method on this resource**

| Name | Data type | Cardinality | Remarks |
|---|---|---|---|
| location_info | String | 1 | Comma separated list of locations to identify a cell of a base station or a particular geographical area, formatted as follows for the two cases:<br><br>…/uu_mbms_provisioning_info?location_info=ecgi,{String}<br><br>Where the String is made up of 1 to N comma separated ecgi values (reference clause 6.5.5).<br><br>…/uu_mbms_provisioning_info?location_info=latitude,{String},longitude,{String}<br><br>Where the two strings are made up of 1 to N comma separated latitude and longitude values respectively (reference clause 6.5.3), such that the number of latitude and longitude values shall be equal.<br><br>Examples of query formats when N=2 locations are provided below:<br><br>…/uu_mbms_provisioning_info?location_info=ecgi,1357924680,1357924681<br>…/uu_mbms_provisioning_info?location_info=latitude,000.000,001.000,longitude,000.000,001.000 |

**Table 7.4.3.1-2: Data structures supported by the GET request/response on this resource**

| Request body | Data type | Cardinality | Remarks | |
|---|---|---|---|---|
| | n/a | | | |
| **Response body** | **Data type** | **Cardinality** | **Response Codes** | **Remarks** |
| | UuMbmsProvisioningInfo | 1 | 200 OK | Upon success, a response body containing the Uu MBMS provisioning information is returned. |
| | ProblemDetails | 0..1 | 400 Bad Request | It is used to indicate that incorrect parameters were passed to the request.<br><br>In the returned ProblemDetails structure, the "detail" attribute should convey more information about the error. |
| | ProblemDetails | 0..1 | 401 Unauthorized | It is used when the client did not submit credentials.<br><br>In the returned ProblemDetails structure, the "detail" attribute should convey more information about the error. |
| | ProblemDetails | 1 | 403 Forbidden | The operation is not allowed given the current status of the resource.<br><br>More information shall be provided in the "detail" attribute of the "ProblemDetails" structure. |

| | Data type | Cardinality | Response Codes | Remarks |
|---|---|---|---|---|
| **Response body** | ProblemDetails | 0..1 | 404 Not Found | It is used when a client provided a URI that cannot be mapped to a valid resource URI.<br><br>In the returned ProblemDetails structure, the "detail" attribute should convey more information about the error. |
| | ProblemDetails | 0..1 | 406 Not Acceptable | It is used to indicate that the server cannot provide any of the content formats supported by the client.<br><br>In the returned ProblemDetails structure, the "detail" attribute should convey more information about the error. |
| | ProblemDetails | 0..1 | 429 Too Many Requests | It is used when a rate limiter has triggered.<br><br>In the returned ProblemDetails structure, the "detail" attribute should convey more information about the error. |

#### 7.4.3.2 PUT

Not applicable.

#### 7.4.3.3 PATCH

Not applicable.

#### 7.4.3.4 POST

Not applicable.

#### 7.4.3.5 DELETE

Not applicable.

## 7.5 Resource: pc5_provisioning_info

### 7.5.1 Description

This resource is queried to retrieve information required for V2X communication over PC5.

### 7.5.2 Resource definition

Resource URI: **{apiRoot}/vis/v2/queries/pc5_provisioning_info**

This resource shall support the resource URI variables defined in table 7.5.2-1.

**Table 7.5.2-1: Resource URI variables for resource "pc5_provisioning_info"**

| Name | Definition |
|---|---|
| apiRoot | See clause 7.2 |

## 7.5.3 Resource methods

### 7.5.3.1 GET

The GET method is used to query provisioning information for V2X communication over PC5.

This method shall support the URI query parameters, request and response data structures, and response codes, as specified in tables 7.5.3.1-1 and 7.5.3.1-2.

**Table 7.5.3.1-1: URI query parameters supported by the GET method on this resource**

| Name | Data type | Cardinality | Remarks |
|---|---|---|---|
| location_info | String | 1 | Comma separated list of locations to identify a cell of a base station or a particular geographical area, formatted as follows for the two cases:<br><br>…/pc5_provisioning_info?location_info=ecgi,{String}<br><br>Where the String is made up of 1 to N comma separated ecgi values (reference clause 6.5.5).<br><br>…/pc5_provisioning_info?location_info=latitude,{String},longitude,{String}<br><br>Where the two strings are made up of 1 to N comma separated latitude and longitude values respectively (reference clause 6.5.3), such that the number of latitude and longitude values shall be equal.<br><br>Examples of query formats when N=2 locations are provided below:<br><br>…/pc5_provisioning_info?location_info=ecgi,1357924680,1357924681<br><br>…/pc5_provisioning_info?location_info=latitude,000.000,001.000,longitude,000.000,001.000 |

**Table 7.5.3.1-2: Data structures supported by the GET request/response on this resource**

| Request body | Data type | Cardinality | Remarks | |
|---|---|---|---|---|
| | n/a | | | |
| **Response body** | **Data type** | **Cardinality** | **Response Codes** | **Remarks** |
| | Pc5ProvisioningInfo | 1 | 200 OK | Upon success, a response body containing the PC5 provisioning information is returned. |
| | ProblemDetails | 0..1 | 400 Bad Request | It is used to indicate that incorrect parameters were passed to the request.<br><br>In the returned ProblemDetails structure, the "detail" attribute should convey more information about the error. |
| | ProblemDetails | 0..1 | 401 Unauthorized | It is used when the client did not submit credentials.<br><br>In the returned ProblemDetails structure, the "detail" attribute should convey more information about the error. |
| | ProblemDetails | 1 | 403 Forbidden | The operation is not allowed given the current status of the resource.<br><br>More information shall be provided in the "detail" attribute of the "ProblemDetails" structure. |

| | Data type | Cardinality | Response Codes | Remarks |
|---|---|---|---|---|
| **Response body** | ProblemDetails | 0..1 | 404 Not Found | It is used when a client provided a URI that cannot be mapped to a valid resource URI.<br><br>In the returned ProblemDetails structure, the "detail" attribute should convey more information about the error. |
| | ProblemDetails | 0..1 | 406 Not Acceptable | It is used to indicate that the server cannot provide any of the content formats supported by the client.<br><br>In the returned ProblemDetails structure, the "detail" attribute should convey more information about the error. |
| | ProblemDetails | 0..1 | 429 Too Many Requests | It is used when a rate limiter has triggered.<br><br>In the returned ProblemDetails structure, the "detail" attribute should convey more information about the error. |

#### 7.5.3.2 PUT

Not applicable.

#### 7.5.3.3 PATCH

Not applicable.

#### 7.5.3.4 POST

Not applicable.

#### 7.5.3.5 DELETE

Not applicable.

## 7.6 Resource: provide_v2x_msg_distribution_server_info

### 7.6.1 Description

This task resource represents V2X Message Distribution Servers information required for the direct connection of a service consumer to V2X Message Distribution Servers.

### 7.6.2 Resource definition

Resource URI: **{apiRoot}/vis/v2/provide_v2x_msg_distribution_server_info**

This resource shall support the resource URI variables defined in table 7.6.2-1.

**Table 7.6.2-1: Resource URI variables for resource "provide_v2x_msg_distribution_server_info"**

| Name | Definition |
|---|---|
| apiRoot | See clause 7.2 |

## 7.6.3 Resource methods

### 7.6.3.1 GET

Not applicable.

### 7.6.3.2 PUT

Not applicable.

### 7.6.3.3 PATCH

Not applicable.

### 7.6.3.4 POST

The POST method is used to request the information about available V2X Message Distribution Servers that can be supported by the service consumer (e.g. a MEC application).

This method shall support the URI query parameters, request and response data structures, and response codes, as specified in tables 7.6.3.4-1 and 7.6.3.4-2.

**Table 7.6.3.4-1: URI query parameters supported by the POST method on this resource**

| Name | Data type | Cardinality | Remarks |
|---|---|---|---|
| n/a | | | |

**Table 7.6.3.4-2: Data structures supported by the POST request/response on this resource**

| | Data type | Cardinality | Response Codes | Remarks |
|---|---|---|---|---|
| **Request body** | V2xMsgDistributionServerInfo | 1 | | Entity body in the request contains the information of the V2X Message Distribution Servers supported by the service consumer for direct communication. |
| **Response body** | **Data type** | **Cardinality** | **Response Codes** | **Remarks** |
| | V2xMsgDistributionServerInfo | 1 | 200 OK | The response body shall contain the connection information of the V2X Message Distribution Servers that the service consumer can use for direct connection. |
| | ProblemDetails | 0..1 | 400 Bad Request | It is used to indicate that incorrect parameters were passed to the request.<br><br>In the returned ProblemDetails structure, the "detail" attribute should convey more information about the error. |
| | ProblemDetails | 0..1 | 401 Unauthorized | It is used when the client did not submit credentials.<br><br>In the returned ProblemDetails structure, the "detail" attribute should convey more information about the error. |
| | ProblemDetails | 1 | 403 Forbidden | The operation is not allowed given the current status of the resource.<br><br>More information shall be provided in the "detail" attribute of the "ProblemDetails" structure. |
| | ProblemDetails | 0..1 | 404 Not Found | It is used when a client provided a URI that cannot be mapped to a valid resource URI.<br><br>In the returned ProblemDetails structure, the "detail" attribute should convey more information about the error. |

#### 7.6.3.5 DELETE

Not applicable.

## 7.7 Resource: provide_predicted_qos

### 7.7.1 Description

This task resource represents predicted QoS information for a vehicular UE with potential routes.

### 7.7.2 Resource definition

Resource URI: **{apiRoot}/vis/v2/provide_predicted_qos**

This resource shall support the resource URI variables defined in table 7.7.2-1.

**Table 7.7.2-1: Resource URI variables for resource "provide_predicted_qos"**

| Name | Definition |
|---|---|
| apiRoot | See clause 7.2 |

### 7.7.3 Resource methods

#### 7.7.3.1 GET

Not applicable.

#### 7.7.3.2 PUT

Not applicable.

#### 7.7.3.3 PATCH

Not applicable.

#### 7.7.3.4 POST

The POST method is used to request the predicted QoS correspondent to potential routes of a vehicular UE.

This method shall support the URI query parameters, request and response data structures, and response codes, as specified in tables 7.7.3.4-1 and 7.7.3.4-2.

**Table 7.7.3.4-1: URI query parameters supported by the POST method on this resource**

| Name | Data type | Cardinality | Remarks |
|---|---|---|---|
| n/a | | | |

**Table 7.7.3.4-2: Data structures supported by the POST request/response on this resource**

| | | | | |
|---|---|---|---|---|
| **Request body** | **Data type** | **Cardinality** | **Remarks** | |
| | PredictedQos | 1 | Entity body in the request contains the predicted QoS as requested by the VIS service consumer. | |
| **Response body** | **Data type** | **Cardinality** | **Response Codes** | **Remarks** |
| | PredictedQos | 1 | 200 OK | The response body shall contain the predicted QoS corresponding to potential routes of a vehicular UE. |
| | ProblemDetails | 0..1 | 400 Bad Request | It is used to indicate that incorrect parameters were passed to the request.<br><br>In the returned ProblemDetails structure, the "detail" attribute should convey more information about the error. |
| | ProblemDetails | 0..1 | 401 Unauthorized | It is used when the client did not submit credentials.<br><br>In the returned ProblemDetails structure, the "detail" attribute should convey more information about the error. |
| | ProblemDetails | 1 | 403 Forbidden | The operation is not allowed given the current status of the resource.<br><br>More information shall be provided in the "detail" attribute of the "ProblemDetails" structure. |
| | ProblemDetails | 0..1 | 404 Not Found | It is used when a client provided a URI that cannot be mapped to a valid resource URI.<br><br>In the returned ProblemDetails structure, the "detail" attribute should convey more information about the error. |

### 7.7.3.5 DELETE

Not applicable.

## 7.8 Resource: publish_v2x_message

### 7.8.1 Description

This resource represents a V2X message that is published by a service consumer (e.g. a MEC application or a MEC platform) to VIS.

### 7.8.2 Resource definition

Resource URI: **{apiRoot}/vis/v2/publish_v2x_message**

This resource shall support the resource URI variables defined in table 7.8.2-1.

**Table 7.8.2-1: Resource URI variables for resource "publish_v2x_message"**

| Name | Definition |
|---|---|
| apiRoot | See clause 7.2 |

## 7.8.3 Resource methods

### 7.8.3.1 GET

Not applicable.

### 7.8.3.2 PUT

Not applicable.

### 7.8.3.3 PATCH

Not applicable.

### 7.8.3.4 POST

The POST method is used to publish a V2X message.

This method shall support the URI query parameters, request and response data structures, and response codes, as specified in tables 7.8.3.4-1 and 7.8.3.4-2.

**Table 7.8.3.4-1: URI query parameters supported by the POST method on this resource**

| Name | Data type | Cardinality | Remarks |
|---|---|---|---|
| n/a | | | |

**Table 7.8.3.4-2: Data structures supported by the POST request/response on this resource**

| | Data type | Cardinality | Remarks | |
|---|---|---|---|---|
| **Request body** | V2xMsgPublication | 1 | Entity body in the request contains the V2X message to be published. | |
| **Response body** | **Data type** | **Cardinality** | **Response Codes** | **Remarks** |
| | n/a | | 204 No Content | Upon success, a response 204 No Content without any response body is returned. |
| | ProblemDetails | 0..1 | 400 Bad Request | It is used to indicate that incorrect parameters were passed to the request.<br><br>In the returned ProblemDetails structure, the "detail" attribute should convey more information about the error. |
| | ProblemDetails | 0..1 | 401 Unauthorized | It is used when the client did not submit credentials.<br><br>In the returned ProblemDetails structure, the "detail" attribute should convey more information about the error. |
| | ProblemDetails | 1 | 403 Forbidden | The operation is not allowed given the current status of the resource.<br><br>More information shall be provided in the "detail" attribute of the "ProblemDetails" structure. |
| | ProblemDetails | 0..1 | 404 Not Found | It is used when a client provided a URI that cannot be mapped to a valid resource URI.<br><br>In the returned ProblemDetails structure, the "detail" attribute should convey more information about the error. |
| | ProblemDetails | 0..1 | 406 Not Acceptable | It is used to indicate that the server cannot provide any of the content formats supported by the client. |
| | ProblemDetails | 0..1 | 429 Too Many Requests | It is used when a rate limiter has triggered. |

#### 7.8.3.5 DELETE

Not applicable.

## 7.9 Resource: subscriptions

### 7.9.1 Description

This resource contains various resources related to subscriptions for notifications.

### 7.9.2 Resource definition

Resource URI: **{apiRoot}/vis/v2/subscriptions**

This resource shall support the resource URI variables defined in table 7.9.2-1.

**Table 7.9.2-1: Resource URI variables for resource "subscriptions"**

| Name | Definition |
|---|---|
| apiRoot | See clause 7.2 |

### 7.9.3 Resource methods

#### 7.9.3.1 GET

The GET method is used to request information about the subscriptions for this requestor. Upon success, the response contains an entity body with the list of links to the subscriptions that are present for the requestor.

This method shall support the URI query parameters, request and response data structures and response codes, as specified in tables 7.9.3.1-1 and 7.9.3.1-2.

**Table 7.9.3.1-1: URI query parameters supported by the GET method on this resource**

| Name | Data type | Cardinality | Remarks |
|---|---|---|---|
| subscription_type | String | 0..1 | Query parameter to filter on a specific subscription type. Permitted values:<br><br>prov_chg_uu_uni: provisioning information change for V2X communication over Uu unicast<br><br>prov_chg_uu_mbms: provisioning information change for V2X communication over Uu MBMS<br><br>prov_chg_pc5: provisioning information change for V2X communication over PC5<br><br>v2x_msg: V2X interoperability message<br><br>pred_qos: information on the predicted QoS |

**Table 7.9.3.1-2: Data structures supported by the GET request/response on this resource**

| Request body | Data type | Cardinality | Remarks | |
|---|---|---|---|---|
| | n/a | | | |
| Response body | **Data type** | **Cardinality** | **Response Codes** | **Remarks** |
| | SubscriptionLinkList | 1 | 200 OK | Upon success, a response body containing the list of links to requestor's subscriptions is returned. |
| | ProblemDetails | 0..1 | 400 Bad Request | It is used to indicate that incorrect parameters were passed to the request.<br><br>In the returned ProblemDetails structure, the "detail" attribute should convey more information about the error. |
| | ProblemDetails | 0..1 | 401 Unauthorized | It is used when the client did not submit credentials.<br><br>In the returned ProblemDetails structure, the "detail" attribute should convey more information about the error. |
| | ProblemDetails | 1 | 403 Forbidden | The operation is not allowed given the current status of the resource.<br><br>More information shall be provided in the "detail" attribute of the "ProblemDetails" structure. |
| | ProblemDetails | 0..1 | 404 Not Found | It is used when a client provided a URI that cannot be mapped to a valid resource URI.<br><br>In the returned ProblemDetails structure, the "detail" attribute should convey more information about the error. |
| | ProblemDetails | 0..1 | 406 Not Acceptable | It is used to indicate that the server cannot provide any of the content formats supported by the client.<br><br>In the returned ProblemDetails structure, the "detail" attribute should convey more information about the error. |
| | ProblemDetails | 0..1 | 429 Too Many Requests | It is used when a rate limiter has triggered.<br><br>In the returned ProblemDetails structure, the "detail" attribute should convey more information about the error. |

### 7.9.3.2 PUT

Not applicable.

### 7.9.3.3 PATCH

Not applicable.

### 7.9.3.4 POST

The POST method is used to create a new subscription to VIS notifications. Upon success, the response contains an entity body describing the created subscription.

This method shall support the request and response data structures and response codes, as specified in table 7.9.3.4-1.

**Table 7.9.3.4-1: Data structures supported by the POST request/response on this resource**

| | Data type | Cardinality | Response Codes | Remarks |
|---|---|---|---|---|
| **Request body** | {NotificationSubscription} | 1 | | The entity body in the request contains the data type of the specific VIS event subscription that is to be created, where the data type options are listed below and defined in clause 6.3:<br>• ProvChgUuUniSubscription<br>• ProvChgUuMbmsSubscription<br>• ProvChgPc5Subscription<br>• V2xMsgSubscription<br>• PredQosSubscription |
| **Response body** | {NotificationSubscription} | 1 | 201 Created | Indicates successful resource creation, where the resource URI shall be returned in the HTTP Location header field.<br><br>In the returned NotificationSubscription structure, the created subscription is described using the appropriate data type from the list below and as defined in clause 6.3:<br>• ProvChgUuUniSubscription<br>• ProvChgUuMbmsSubscription<br>• ProvChgPc5Subscription<br>• V2xMsgSubscription<br>• PredQosSubscription |
| | ProblemDetails | 0..1 | 400 Bad Request | It is used to indicate that incorrect parameters were passed to the request.<br><br>In the returned ProblemDetails structure, the "detail" attribute should convey more information about the error. |
| | ProblemDetails | 0..1 | 401 Unauthorized | It is used when the client did not submit credentials.<br><br>In the returned ProblemDetails structure, the "detail" attribute should convey more information about the error. |
| | ProblemDetails | 1 | 403 Forbidden | The operation is not allowed given the current status of the resource.<br><br>More information shall be provided in the "detail" attribute of the "ProblemDetails" structure. |
| | ProblemDetails | 0..1 | 404 Not Found | It is used when a client provided a URI that cannot be mapped to a valid resource URI.<br><br>In the returned ProblemDetails structure, the "detail" attribute should convey more information about the error. |
| | ProblemDetails | 0..1 | 406 Not Acceptable | It is used to indicate that the server cannot provide any of the content formats supported by the client.<br><br>In the returned ProblemDetails structure, the "detail" attribute should convey more information about the error. |
| | ProblemDetails | 0..1 | 415 Unsupported Media Type | It is used to indicate that the server or the client does not support the content type of the entity body.<br><br>In the returned ProblemDetails structure, the "detail" attribute should convey more information about the error. |

| | Data type | Cardinality | Response Codes | Remarks |
|---|---|---|---|---|
| **Response body** | ProblemDetails | 0..1 | 422 Unprocessable Entity | It is used to indicate that the server understands the content type of the request entity and that the syntax of the request entity is correct but that the server is unable to process the contained instructions. This error condition can occur if an JSON request body is syntactically correct but semantically incorrect, for example if the target area for the request is considered too large. This error condition can also occur if the capabilities required by the request are not supported.<br><br>In the returned ProblemDetails structure, the "detail" attribute should convey more information about the error. |
| | ProblemDetails | 0..1 | 429 Too Many Requests | It is used when a rate limiter has triggered.<br><br>In the returned ProblemDetails structure, the "detail" attribute should convey more information about the error. |

#### 7.9.3.5 DELETE

Not applicable.

## 7.10 Resource: existing subscription

### 7.10.1 Description

This resource represents a subscription that the client has created to receive VIS event notifications.

### 7.10.2 Resource definition

Resource URI: **{apiRoot}/vis/v2/subscriptions/{subscriptionId}**

This resource shall support the resource URI variables defined in table 7.10.2-1.

**Table 7.10.2-1: Resource URI variables for resource "existing subscription"**

| Name | Definition |
|---|---|
| apiRoot | See clause 7.2. |
| subscriptionId | Refers to created subscription, where the VIS API allocates a unique resource name for this subscription. The resource name can be also used to identify the resource. |

### 7.10.3 Resource methods

#### 7.10.3.1 GET

The GET method is used to retrieve information about this subscription. Upon success, the response contains an entity body with the data type describing the subscription.

This method shall support the URI query parameters, request and response data structures, and response codes, as specified in tables 7.10.3.1-1 and 7.10.3.1-2.

**Table 7.10.3.1-1: URI query parameters supported by the GET method on this resource**

| Name | Data type | Cardinality | Remarks |
|---|---|---|---|
| n/a | | | |

**Table 7.10.3.1-2: Data structures supported by the GET request/response on this resource**

| Request body | Data type | Cardinality | Remarks | |
|---|---|---|---|---|
| | n/a | | | |
| Response body | **Data type** | **Cardinality** | **Response Codes** | **Remarks** |
| | {NotificationSubscription} | 1 | 200 OK | Upon success, a response body containing the data type describing the specific RNI event subscription is returned. The allowed data types for subscriptions are defined in clause 6.3 and are as follows:<br>• ProvChgUuUniSubscription<br>• ProvChgUuMbmsSubscription<br>• ProvChgPc5Subscription<br>• V2xMsgSubscription<br>• PredQosSubscription |
| | ProblemDetails | 0..1 | 400 Bad Request | It is used to indicate that incorrect parameters were passed to the request.<br><br>In the returned ProblemDetails structure, the "detail" attribute should convey more information about the error. |
| | ProblemDetails | 0..1 | 401 Unauthorized | It is used when the client did not submit credentials.<br><br>In the returned ProblemDetails structure, the "detail" attribute should convey more information about the error. |
| | ProblemDetails | 1 | 403 Forbidden | The operation is not allowed given the current status of the resource.<br><br>More information shall be provided in the "detail" attribute of the "ProblemDetails" structure. |
| | ProblemDetails | 0..1 | 404 Not Found | It is used when a client provided a URI that cannot be mapped to a valid resource URI.<br><br>In the returned ProblemDetails structure, the "detail" attribute should convey more information about the error. |
| | ProblemDetails | 0..1 | 406 Not Acceptable | It is used to indicate that the server cannot provide any of the content formats supported by the client.<br><br>In the returned ProblemDetails structure, the "detail" attribute should convey more information about the error. |
| | ProblemDetails | 0..1 | 429 Too Many Requests | It is used when a rate limiter has triggered.<br><br>In the returned ProblemDetails structure, the "detail" attribute should convey more information about the error. |

### 7.10.3.2 PUT

The PUT method is used to update the existing subscription. PUT method in this case has "replace" semantics. Upon successful operation, the target resource is updated with a new data type received within the message body of the PUT request.

This method shall support the URI query parameters, request and response data structures and response codes, as specified in tables 7.10.3.2-1 and 7.10.3.2-2.

**Table 7.10.3.2-1: URI query parameters supported by the PUT method on this resource**

| Name | Data type | Cardinality | Remarks |
|---|---|---|---|
| n/a | | | |

**Table 7.10.3.2-2: Data structures supported by the PUT request/response on this resource**

| | Data type | Cardinality | Response Codes | Remarks |
|---|---|---|---|---|
| **Request body** | {NotificationSubscription} | 1 | | New NotificationSubscription is included as entity body of the request. The allowed data types for subscriptions are defined in clause 6.3 and are as follows:<br>• ProvChgUuUniSubscription<br>• ProvChgUuMbmsSubscription<br>• ProvChgPc5Subscription<br>• V2xMsgSubscription<br>• PredQosSubscription |
| **Response body** | **Data type** | **Cardinality** | **Response Codes** | **Remarks** |
| | {NotificationSubscription} | 1 | 200 OK | Upon success, a response body containing the data type describing the updated subscription is returned. The allowed data types for subscriptions are defined in clause 6.3 and are as follows:<br>• ProvChgUuUniSubscription<br>• ProvChgUuMbmsSubscription<br>• ProvChgPc5Subscription<br>• V2xMsgSubscription<br>• PredQosSubscription |
| | ProblemDetails | 0..1 | 400 Bad Request | It is used to indicate that incorrect parameters were passed to the request.<br><br>In the returned ProblemDetails structure, the "detail" attribute should convey more information about the error. |
| | ProblemDetails | 0..1 | 401 Unauthorized | It is used when the client did not submit credentials.<br><br>In the returned ProblemDetails structure, the "detail" attribute should convey more information about the error. |
| | ProblemDetails | 1 | 403 Forbidden | The operation is not allowed given the current status of the resource.<br><br>More information shall be provided in the "detail" attribute of the "ProblemDetails" structure. |
| | ProblemDetails | 0..1 | 404 Not Found | It is used when a client provided a URI that cannot be mapped to a valid resource URI.<br><br>In the returned ProblemDetails structure, the "detail" attribute should convey more information about the error. |
| | ProblemDetails | 0..1 | 406 Not Acceptable | It is used to indicate that the server cannot provide any of the content formats supported by the client.<br><br>In the returned ProblemDetails structure, the "detail" attribute should convey more information about the error. |

| | Data type | Cardinality | Response Codes | Remarks |
|---|---|---|---|---|
| **Response body** | ProblemDetails | 0..1 | 412 Precondition Failed | It is used when a condition has failed during conditional requests, e.g. when using ETags to avoid write conflicts when using PUT.<br><br>In the returned ProblemDetails structure, the "detail" attribute should convey more information about the error. |
| | ProblemDetails | 0..1 | 422 Unprocessable Entity | It is used to indicate that the server understands the content type of the request entity and that the syntax of the request entity is correct but that the server is unable to process the contained instructions. This error condition can occur if an JSON request body is syntactically correct but semantically incorrect, for example if the target area for the request is considered too large. This error condition can also occur if the capabilities required by the request are not supported.<br><br>In the returned ProblemDetails structure, the "detail" attribute should convey more information about the error. |
| | ProblemDetails | 0..1 | 429 Too Many Requests | It is used when a rate limiter has triggered.<br><br>In the returned ProblemDetails structure, the "detail" attribute should convey more information about the error. |

### 7.10.3.3 PATCH

Not applicable.

### 7.10.3.4 POST

Not applicable.

### 7.10.3.5 DELETE

The DELETE method is used to cancel the existing subscription. Cancellation can be made by deleting the resource that represents the existing subscription.

This method shall support the URI query parameters, request and response data structures and response codes, as specified in tables 7.10.3.5-1 and 7.10.3.5-2.

**Table 7.10.3.5-1: URI query parameters supported by the DELETE method on this resource**

| Name | Data type | Cardinality | Remarks |
|---|---|---|---|
| n/a | | | |

**Table 7.10.3.5-2: Data structures supported by the DELETE request/response on this resource**

| Request body | Data type | Cardinality | Remarks | |
|---|---|---|---|---|
| | n/a | | | |
| Response body | **Data type** | **Cardinality** | **Response Codes** | **Remarks** |
| | n/a | | 204 No Content | Upon success, a response 204 No Content without any response body is returned. |
| | ProblemDetails | 0..1 | 401 Unauthorized | It is used when the client did not submit credentials.<br><br>In the returned ProblemDetails structure, the "detail" attribute should convey more information about the error. |
| | ProblemDetails | 1 | 403 Forbidden | The operation is not allowed given the current status of the resource.<br><br>More information shall be provided in the "detail" attribute of the "ProblemDetails" structure. |
| | ProblemDetails | 0..1 | 404 Not Found | It is used when a client provided a URI that cannot be mapped to a valid resource URI.<br><br>In the returned ProblemDetails structure, the "detail" attribute should convey more information about the error. |
| | ProblemDetails | 0..1 | 429 Too Many Requests | It is used when a rate limiter has triggered.<br><br>In the returned ProblemDetails structure, the "detail" attribute should convey more information about the error. |

# Annex A (informative): Mapping of permissions for RESTful API and topic based alternative transport

## A.1 Overview

This annex provides mappings of permissions for topics between RESTful API and topic based alternative transport. ETSI GS MEC 009 [9] describes how permissions for topics between RESTful API and alternative transport can be mapped with each other. This annex uses the template for permissions mapping as defined in the present document.

## A.2 Mapping of permissions - RESTful and topic based alternative transport

Table A.2-1 lists the permission categories for each topic currently included in VIS API specification.

**Table A.2-1: Definition of permissions for VIS**

| Permission identifier | Display name | Remarks |
|---|---|---|
| uu_unicast_provisioning_info | Uu Unicast Provisioning Info | Query |
| uu_mbms_provisioning_info | Uu MBMS Provisioning Info | Query |
| pc5_provisioning_info | PC5 Provisioning Info | Query |
| provide_v2x_msg_distribution_server_info | Provide V2X Message Distribution Server information | Task |
| provide_predicted_qos | Provide Predicted QoS | Task |
| publish_v2x_message | Publish V2X Message | Task |
| prov_chg_uu_uni | provisioning information change for V2X communication over Uu unicast | Subscribe-Notify |
| prov_chg_uu_mbms | provisioning information change for V2X communication over Uu MBMS | Subscribe-Notify |
| prov_chg_pc5 | provisioning information change for V2X communication over PC5 | Subscribe-Notify |
| v2x_msg | V2X interoperability message | Subscribe-Notify |
| pred_qos | information on the predicted QoS | Subscribe-Notify |

Table A.2-2 describes how permission identifiers can be mapped to resources in the VIS RESTful API as defined in the present document.

**Table A.2-2: Permission identifiers mapping for transport "REST"**

| Permission identifier | Specification |
|---|---|
| uu_unicast_provisioning_info | Resource: …/vis/v2/queries/uu_unicast_provisioning_info |
| uu_mbms_provisioning_info | Resource: …/vis/v2/queries/uu_mbms_provisioning_info |
| pc5_provisioning_info | Resource: …/vis/v2/queries/pc5_provisioning_info |
| provide_v2x_msg_distribution_server_info | Resource: …/vis/v2/provide_v2x_msg_distribution_server_info |
| provide_predicted_qos | Resource: …/vis/v2/provide_predicted_qos |
| publish_v2x_message | Resource: …/vis/v2/publish_v2x_message |
| prov_chg_uu_uni | Resource: …/vis/v2/subscriptions/prov_chg_uu_uni |
| prov_chg_uu_mbms | Resource: …/vis/v2/subscriptions/prov_chg_uu_mbms |
| prov_chg_pc5 | Resource: …/vis/v2/subscriptions/prov_chg_pc5 |
| v2x_msg | Resource: …/vis/v2/subscriptions/v2x_msg |
| pred_qos | Resource: …/vis/v2/subscriptions/pred_qos |

Table A.2-3 describes how the permission identifiers can be mapped to topics offered over topic-based message bus.

**Table A.2-3: Permission identifiers mapping for transport "Topic-based message bus"**

| Permission identifier | Specification |
|---|---|
| uu_unicast_provisioning_info | Topic: /vis/enb/uu_unicast_provisioning_info |
| uu_mbms_provisioning_info | Topic: /vis/enb/uu_mbms_provisioning_info |
| pc5_provisioning_info | Topic: /vis/enb/pc5_provisioning_info |
| provide_v2x_msg_distribution_server_info | Topic: /vis/ue/provide_v2x_msg_distribution_server_info |
| provide_predicted_qos | Topic: /vis/ue/provide_predicted_qos |
| publish_v2x_message | Topic: /vis/ue/publish_v2x_message |
| prov_chg_uu_uni | Topic: /vis/ue/chg/uu_uni |
| prov_chg_uu_mbms | Topic: /vis/ue/chg/uu_mbms |
| prov_chg_pc5 | Topic: /vis/ue/chg/pc5 |
| v2x_msg | Topic: /vis/ue/v2x_msg |
| pred_qos | Topic: /vis/ue/pred_qos |

# Annex B (informative): Complementary material for API utilization

To complement the definitions for each method and resource defined in the interface clauses of the present document, ETSI MEC ISG is providing for the VIS API a supplementary description file compliant to the OpenAPI Specification [i.3].

In case of discrepancies between the supplementary description file and the related data structure definitions in the present document, the data structure definitions take precedence.

# Annex C (informative): Radio access network scenario options for V2X communication

There are several radio access network options for V2X communications.

Scenario option 1: Only Operator A has eNBs in a specific area. Operator A's eNBs are shared with Operator B for all services including V2X.

Scenario option 2: Only Operator A owns the dedicated V2X spectrum in a specific area. Operator A's eNBs are shared with Operator B only for V2X service.

Scenario option 3: Both Operators A and B have eNBs in a specific area. V2X server distributes the V2X message to both operators' network.

All three options are valid, where option 1 requires least coordination among operators and option 3 may require coordination among operators.

Option 1 applies to the cases where one operator has no coverage in a specific area and has to use another operator's network through RAN sharing.

Option 2 is a potential choice when multiple operators are selected to provide V2X communication, where each operator provides V2X service in a certain area. Inter-working may be required at the "V2X service border" of two operators.

Option 3 maintains the separation of two operators. All levels (RAN, CN, Application) coordination may be required based on different use cases. It requires most effort, especially in deployment.

# Annex D (informative): State-of-the-art of using a Message Broker as V2X Message Distribution Server for exchanging non-session based V2X messages

One important achievement of the MEC solution is to allow low latency communications and, consequently, to cover use cases that, in the past, were only possible with direct communication among vehicles. For this reason, there is the need that MEC Apps can interact with UEs to exchange V2X messages.

Several V2X services are non-session based and a possible option to exchange the V2X messages related to these services over the Uu interface is to use a V2X Message Distribution Server as introduced in Annex D of [10]. A common implementation solution is to employ a Message Broker.

This method has been borrowed by the IoT world considering the vehicle as an IoT object, or, better, as a container of different objects that can send and consume data. In the last years, several experimentations have been performed and different application layer protocols for the implementation of the Message Brokers have been considered.

An example of this approach has been provided by the Autopilot project [i.18]. All the Pilot sites of this large scale H2020 project collected data on the cloud through the MQTT [i.19] protocol. Similar experimentation with a Message Broker located at the edge for the exchange of V2X messages can be found in 5GCroCo [i.20] (MQTT), 5G-Carmen [i.21] (AMQP 1.0 [i.22]) and 5G-META [i.23] (MQTT or AMQP 1.0) projects.

Although the objectives and the realized use cases of these projects are different, the proposed approach is the same as evidence of its goodness. A Message Broker can make possible to exchange non-session based V2X messages among vehicles, infrastructure (e.g. RSUs or fixed sensors) and other relevant sources.

The CROADS Platform [i.24] also performs different on-field test using the AMQP 1.0 protocol and dealing with interoperability among different Message Brokers, that may also belong to different countries. One example is provided by the tests on the Brenner pass between Italy and Austria that are underway by CROADS and by the H2020 ICT4CART project [i.25] that uses a similar communication architecture. The CROADS project has also detailed a set of filter criteria for the reception of only relevant V2X messages. In the specific document, they introduced a criterion to identify a geographical area of relevance exploiting a geospatial indexing based on quadkeys [i.26].

# History

| Document history | | |
|---|---|---|
| V2.1.1 | April 2020 | Publication |
| V2.2.1 | May 2022 | Publication |
| V3.1.1 | March 2023 | Publication |
| | | |
| | | |