ETSI EG 201 847 V1.1.1 (2000-12)

ETSI Guide

Bearer Independent Call Control (BICC); Operation of BICC protocol with Digital Subscriber System No. 2 (DSS2)

[Supplement to ITU-T Recommendation Q.1901, TRQ.3000 (1999), modified]



Reference
DEG/SPAN-01084

Keywords
AAL, protocol, bearer, control, DSS2, trunking, BICC

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

Individual copies of the present document can be downloaded from:
http://www.etsi.org

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at http://www.etsi.org/tb/status/

If you find errors in the present document, send your comment to:
editor@etsi.fr

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2000.
All rights reserved.

Contents

Intellectual Property Rights 4
Foreword 4
Endorsement notice 5
Clause 2 "References" 5
Throughout the text of ITU-T Supplement TRQ.3000 6
History 7

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (http://www.etsi.org/ipr).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This ETSI Guide (EG) has been produced by ETSI Technical Committee Services and Protocols for Advanced Networks (SPAN).

Endorsement notice

The elements of supplement to ITU-T Recommendation Q.1901, TRQ.3000 (1999) apply, with the following modifications.

Clause 2 "References"

Replace clause 2 by the following:

[1] ETSI EN 301 848-1 (V1.1.1): "Integrated Service Digital Network (ISDN) Signalling System No.7 (SS7); Bearer Independent Call Control (BICC); Signalling procedures in an ATM/IP/.. backbone network; Capability Set 1 (CS1); Part 1: Protocol specification [ITU-T Recommendations Q.1901 and Q.765.5, modified]".

[2] ETSI I-ETS 300 353 (1998) :"Broadband Integrated Services Digital Network (B-ISDN); Asynchronous Transfer Mode (ATM); Adaptation Layer (AAL) specification - type 1".

[3] ETSI ETS 300 404 (1997): "Broadband Integrated Services Digital Network (B-ISDN); B-ISDN Operation And Maintenance (OAM) principles and functions".

[4] ETSI EN 300 443-1 (V1.3.5): "Broadband Integrated Services Digital Network (B-ISDN); Digital Subscriber Signalling System No. two (DSS2) protocol; B-ISDN user-network interface layer 3 specification for basic call/bearer control; Part 1: Protocol specification [ITU-T Recommendation Q.2931 (1995), modified]".

[5] ITU-T Recommendation Q.2941.3 (06/00): "Broadband integrated services digital network (B-ISDN) digital subscriber signalling system No. 2 (DSS 2): Generic identifier transport extension for support of bearer independent call control".

[6] ETSI EN 300 485 (V1.2.3): "Integrated Services Digital Network (ISDN); Definition and usage of cause and location in Digital Subscriber Signalling System No. one (DSS1) and Signalling System No.7 ISDN User Part (ISUP) [ITU-T Recommendation Q.850 (1998), modified]".

[7] Void.

[8] ITU-T Recommendation Q.2965.1 (03/99): "Digital subscriber signalling system No. 2 - Support of Quality of Service classes".

[9] ETSI ETS 300 301 (1997): "Broadband Integrated Services Digital Network (B-ISDN); Traffic control and congestion control in B-ISDN [ITU-T Recommendation I.371 (1996)]".

[10] ETSI EN 301 068-1: "Broadband Integrated Services Digital Network (B-ISDN); Digital Subscriber Signalling System No. two (DSS2) protocol; Connection characteristics; ATM transfer capability and traffic parameter indication; Part 1: Protocol specification [ITU-T Recommendations Q.2961.1 (1995), Q.2961.2 (1997), Q.2961.3 (1997), Q.2961.4 (1997), modified]".

[11] ETSI EN 300 356-1 (V4.1.1): "Integrated Services Digital Network (ISDN); Signalling System No.7; ISDN User Part (ISUP) version 4 for the international interface; Part 1: Basic services [ITU-T Recommendations Q.761 to Q.764 (2000) modified]".

[12] ETSI I-ETS 300 464 (1996): "Broadband Integrated Services Digital Network (B-ISDN); Asynchronous Transfer Mode (ATM); ATM layer cell transfer performance for B-ISDN connection types".

[13] ETSI ETS 300 685 (1997): "Broadband Integrated Services Digital Network (B-ISDN); Usage of cause and location in Digital Subscriber Signalling System No. two (DSS2) and Signalling System No.7 B-ISDN User Part (B-ISUP) [ITU-T Recommendation Q.2610 (1995), modified]".

Throughout the text of ITU-T Supplement TRQ.3000

Replace references as shown in table 1.

Table 1

Reference in ITU-T Supplement TRQ.3010	Modified reference
ITU-T Recommendation Q.1901	ITU-T Recommendation as modified by EN 301 848-1 [1]
ITU-T Recommendation Q.765.5	ITU-T Recommendation as modified by EN 301 848-1 [1]
ITU-T Recommendation Q.763	ITU-T Recommendation as modified by EN 300 356-1 [11]
ITU-T Recommendation Q.850	ITU-T Recommendation as modified by EN 300 485 [6]
ITU-T Recommendation Q.2610	ITU-T Recommendation as modified by ETS 300 685 [13]
ITU-T Recommendation I.363.1	ITU-T Recommendation as modified by I-ETS 300 353 [2]
ITU-T Recommendation I.610	ITU-T Recommendation as modified by ETS 300 404 [3]
ITU-T Recommendation Q.2931	ITU-T Recommendation as modified by EN 300 443-1 [4]
ITU-T Recommendation I.371	ITU-T Recommendation as modified by ETS 300 301 [9]
ITU-T Recommendation Q.2691.2	ITU-T Recommendation as modified by EN 301 068-1 [10]
ITU-T Recommendation I.356	ITU-T Recommendation as modified by I-ETS 300 464 [12]

History

Document history		
V1.1.1	October 2000	Membership Approval Procedure MV 20001201: 2000-10-03 to 2000-12-01
V1.1.1	December 2000	Publication