ETSI TS 137 579-7 V17.6.0 (2026-08)



TECHNICAL SPECIFICATION

LTE;
5G;
Mission Critical (MC) services;
Part 7: Mission Critical Data (MCData) User Equipment (UE) Protocol conformance specification
(3GPP TS 37.579-7 version 17.6.0 Release 17)



Reference
RTS/TSGR-0537579-7vh60

Keywords
5G,LTE

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from the
ETSI Search & Browse Standards application.

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format on ETSI deliver repository.

Users should be aware that the present document may be revised or have its status changed, this information is available in the Milestones listing.

If you find errors in the present document, please send your comments to the relevant service listed under Committee Support Staff.

If you find a security vulnerability in the present document, please report it through our Coordinated Vulnerability Disclosure (CVD) program.

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.
No recommendation as to products and services or vendors is made or should be implied.
No representation or warranty is made that this deliverable is technically accurate or sufficient or conforms to any law and/or governmental rule and/or regulation and further, no representation or warranty is made of merchantability or fitness for any particular purpose or against infringement of intellectual property rights.
In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part of this document may be reproduced in any form, by any means and in any media, without the prior written authorization of ETSI and except as expressly permitted below.
By way of exception and when the document is a normative deliverable (European Standard (EN), Technical Specification (TS), Group Specification (GS) or ETSI Standard (ES)), ETSI authorizes to reproduce and incorporate into products, services and technical documentation only those extracts (e.g. templates) that are strictly necessary for the technical implementation of the normative deliverable, to ensure compliance with the latter.
Nothing in this notice shall be construed as limiting any mandatory exceptions to copyright provided by applicable law.

© ETSI 2026.
All rights reserved.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables (European Standard (EN), Technical Specification (TS), Group Specification (GS) or ETSI Standard (ES)) may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI IPR online database.

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™**, **LTE™** and **5G™** logo are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM**® and the GSM logo are trademarks registered and owned by the GSM Association.

Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found at 3GPP to ETSI numbering cross-referencing.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the ETSI Drafting Rules (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights 2
Legal Notice 2
Modal verbs terminology 2
Foreword 7
1 Scope 9
2 References 9
3 Definitions of terms, symbols and abbreviations 11
3.1 Terms 11
3.2 Symbols 12
3.3 Abbreviations 12
4 General 13
4.1 Test methodology 13
4.1.1 Testing of optional functions and procedures 13
4.1.2 Test interfaces and facilities 13
4.2 Implicit testing 13
4.3 Repetition of tests 13
4.4 Handling of differences between conformance requirements in different releases of cores specifications 13
4.5 Reference conditions 14
4.6 Generic setup procedures 14
5 MCData Client Configuration 14
5.1 Configuration / Authentication / User Authorization / UE Configuration / User Profile / Key Generation 14
5.2 Configuration / Group Creation / Group ReGroup Creation / Group ReGroup Teardown 29
5.3 Configuration / Group Affiliation / Remote change / De-affiliation / Home MCData system 31
5.4 Configuration / Determination of MCData Service Settings / Current Active MCData Settings / De-subscribe 35
5.5 Configuration / Pre-established Session Establishment / Pre-established Session Release 37
5.7 Configuration / Functional Alias / Functional alias status determination / Activate functional alias / Deactivate functional alias 46
5.8 Configuration / Rules based affiliation status change 49
5.9 Configuration / Functional Alias / Location based functional alias status change 53
6 On-Network Test Scenarios 56
6.1 Short Data Service 56
6.1.1 On-network / Short Data Service (SDS) / Standalone SDS Using Signalling Control Plane / One-to-one Standalone SDS / Client Originated (CO) 56
6.1.2 On-network / Short Data Service (SDS) / Standalone SDS Using Signalling Control Plane / One-to-one Standalone SDS / Client Terminated (CT) 64
6.1.3 On-network / Short Data Service (SDS) / Standalone SDS Using Signalling Control Plane / Group Standalone SDS / Client Originated (CO) 76
6.1.4 On-network / Short Data Service (SDS) / Standalone SDS Using Signalling Control Plane / Group Standalone SDS / Client Terminated (CT) 81
6.1.5 On-network / Short Data Service (SDS) / Standalone SDS Using Media Plane / One-to-one Standalone SDS / Client Originated (CO) 86
6.1.6 On-network / Short Data Service (SDS) / Standalone SDS Using Media Plane / One-to-one Standalone SDS / Client Terminated (CT) 95
6.1.7 On-network / Short Data Service (SDS) / Standalone SDS Using Media Plane / Group Standalone SDS / Client Originated (CO) 104
6.1.8 On-network / Short Data Service (SDS) / Standalone SDS Using Media Plane / Group Standalone SDS / Client Terminated (CT) 113
6.1.9 On-network / Short Data Service (SDS) / SDS Session / One-to-one SDS Session / Client Originated (CO) 123
6.1.10 On-network / Short Data Service (SDS) / SDS Session / One-to-one SDS Session / Client Terminated (CT) 133

6.1.11 On-network / Short Data Service (SDS) / SDS Session / Group SDS Session / Client Originated (CO) 143
6.1.12 On-network / Short Data Service (SDS) / SDS Session / Group SDS Session / Client Terminated (CT) 155
6.1.13 On-network / Short Data Service (SDS) / Standalone SDS Using Media Plane / One-to-one Standalone SDS / Pre-established session / Client Originated (CO) 165
6.1.14 On-network / Short Data Service (SDS) / Standalone SDS Using Media Plane / One-to-one Standalone SDS / Pre-established session / Client Terminated (CT) 175
6.1.15 On-network / Short Data Service (SDS) / SDS Session / One-to-one SDS Session / Pre-established session / Client Originated (CO) 184
6.1.16 On-network / Short Data Service (SDS) / SDS Session / One-to-one SDS Session / Pre-established session / Client Terminated (CT) 193
6.1.17 On-network / Short Data Service (SDS) / Standalone SDS Using Media Plane / Group Standalone SDS / Pre-established session / Client Originated (CO) 201
6.1.18 On-network / Short Data Service (SDS) / Standalone SDS Using Media Plane / Group Standalone SDS / Pre-established session / Client Terminated (CT) 211
6.1.19 On-network / Short Data Service (SDS) / SDS Session / Group SDS Session / Pre-established session / Client Originated (CO) 220
6.1.20 On-network / Short Data Service (SDS) / SDS Session / Group SDS Session / Pre-established session / Client Terminated (CT) 228
6.1.21 On-network / Short Data Service (SDS) / Standalone SDS using signalling control plane / One-to-one Standalone SDS / Active functional alias / Client Originated (CO) 236
6.1.22 On-network / Short Data Service (SDS) / Standalone SDS Using Media Plane / One-to-one Standalone SDS / Active functional alias / Client Originated (CO) 242
6.1.23 On-network / Short Data Service (SDS) / SDS Session / Group SDS Session / Pre-established session / Preconfigured Group Use Only 251
6.2 File Distribution 255
6.2.1 On-network / File Distribution (FD) / FD Using HTTP / One-to-one Standalone FD / Non-Mandatory Download / FILE DOWNLOAD REQUEST ACCEPTED / FILE DOWNLOAD COMPLETED / FILE DOWNLOAD REQUEST REJECTED / FILE DOWNLOAD DEFERRED / Client Originated (CO) 255
6.2.2 On-network / File Distribution (FD) / FD Using HTTP / One-to-one Standalone FD / Non-Mandatory Download / Before TDU2 Timers Expires / FILE DOWNLOAD REQUEST ACCEPTED / FILE DOWNLOAD COMPLETED / FILE DOWNLOAD REQUEST REJECTED / FILE DOWNLOAD DEFERRED / FD Client Terminated (CT) 264
6.2.3 On-network / File Distribution (FD) / FD Using HTTP / Group Standalone FD / Non-Mandatory Download / FILE DOWNLOAD REQUEST ACCEPTED / FILE DOWNLOAD COMPLETED / FILE DOWNLOAD REQUEST REJECTED / Client Originated (CO) 274
6.2.4 On-network / File Distribution (FD) / FD Using HTTP / Group Standalone FD / Non-Mandatory Download / After TDU2 Timers Expires / FILE DOWNLOAD REQUEST ACCEPTED / FILE DOWNLOAD COMPLETED / FILE DOWNLOAD REQUEST REJECTED / Client Terminated (CT) 283
6.2.5 On-network / File Distribution (FD) / FD Using HTTP / One-to-one Standalone FD / Mandatory Download / With Disposition Request / Client Originated (CO) 290
6.2.6 On-network / File Distribution (FD) / FD Using HTTP / One-to-one Standalone FD / Mandatory Download / With Disposition Request / Client Terminated (CT) 296
6.2.7 On-network / File Distribution (FD) / FD Using HTTP / Group Standalone FD / Mandatory Download / Without Disposition Request / Client Originated (CO) 302
6.2.8 On-network / File Distribution (FD) / FD Using HTTP / Group Standalone FD / Mandatory Download / Without Disposition Request / Client Terminated (CT) 308
6.2.9 On-network / File Distribution (FD) / FD Using Media Plane / One-to-one Standalone FD / Client Originated (CO) 314
6.2.10 On-network / File Distribution (FD) / FD Using Media Plane / One-to-one Standalone FD / Client Terminated (CT) 323
6.2.11 On-network / File Distribution (FD) / FD Using Media Plane / Group Standalone FD / Client Originated (CO) 329
6.2.12 On-network / File Distribution (FD) / FD Using Media Plane / Group Standalone FD / Client Terminated (CT) 338
6.2.13 On-network / File Distribution (FD) / Accessing list of deferred data group communications / Client Originated (CO) 345
6.2.14 On-network / File Distribution (FD) / FD Using HTTP / One-to-one Standalone FD / Non-Mandatory Download / Active functional alias / Client Originated (CO) 353

6.2.15 On-network / File Distribution (FD) / FD Using Media Plane / One-to-one Standalone FD / Active Functional Alias / Client Originated (CO) 360
6.2.16 On-network / File Distribution (FD) / FD Using HTTP / Group Standalone FD / Preconfigured Group Use Only 367
6.2.17 On-network / File Distribution (FD) / FD Using Media Plane / Group Standalone FD / Preconfigured Group Use Only 370
6.3 Enhanced Status (ES) 375
6.3.1 On-network / Enhanced Status (ES) / Client Originated (CO) 375
6.3.2 On-network / Enhanced Status (ES) / Client Terminated (CT) 381
6.4 Emergency Alert 387
6.4.1 On-network / Emergency Alert / Cancel Emergency Alert / Client Originated (CO) 387
6.4.2 On-network / Emergency Alert / Client Terminated (CT) 393
6.4.3 On-network / Emergency Alert / Group geographic area 396
6.4.4 On-network / Emergency Alert / Emergency alert area 397
6.5 Location 400
6.6 MBMS 420
6.6.1 On-network / MBMS / MBMS Bearer Announcement / MBMS Bearer Listening Status / Transition to MBMS from Unicast 420
6.7 IP Connectivity 441
6.7.1 On-network / IP Connectivity / Client Originated (CO) 441
6.7.2 On-network / IP Connectivity / Client Terminated (CT) 447
6.8 MCData Message Store 453
6.8.1 On-network / MCData Message Store / Objects / Object upload / Object search / Update Object / Object retrieval / Delete stored object 453
6.8.2 On-network / MCData Message Store / Folders / Discover a folder / Create a folder / Object and folder copy / Search a folder / Move a folder / Delete a folder 462
6.8.3 On-network / MCData Message Store / Subscription / Create a subscription to notifications / Update a subscription to notifications / Delete a subscription to notifications 478
6.8.4 On-network / MCData Message Store / Synchronization / Synchronization notifications / Search-based synchronization 483
6.8.5 On-network / MCData Message Store / Notification Channel / Create / Open / Update / Delete 490
6.9 Regroup using a preconfigured group 497
6.9.1 On-network / Regroup using a preconfigured group / Requesting a group regroup using a preconfigured group / Removing a regroup using preconfigured group / Client Originated (CO) 497
6.9.2 On-network / Regroup using a preconfigured group / Receiving a notification of creation of a regroup using preconfigured group / Receiving notification of removal of a regroup using preconfigured group / Client Terminated (CT) 503
6.9.3 On-network / Regroup using a preconfigured group / Requesting a user regroup using a preconfigured group / Removing a regroup using preconfigured group / Client Originated (CO) 509
6.9.4 On-network / Regroup using a preconfigured group / Creating a user regroup using preconfigured group / Removing a user regroup using preconfigured group / Client Terminated (CT) 515

7 Off-Network Test Scenarios 521
7.1 Short Data Service (SDS) 521
7.1.1 Off-network / Short Data Service (SDS) / Standalone SDS using signalling control plane / One-to-one SDS message / Client Originated (CO) 521
7.1.2 Off-network / Short Data Service (SDS) / Standalone SDS using signalling control plane / One-to-one SDS message / Client Terminated (CT) 530
7.1.3 Off-network / Short Data Service (SDS) / Standalone SDS using signalling control plane / Group SDS message / Client Originated (CO) 540
7.1.4 Off-network / Short Data Service (SDS) / Standalone SDS using signalling control plane / Group SDS message / Client Terminated (CT) 549
7.2 Enhanced Status (ES) 559
7.2.1 Off-network / Enhanced Status (ES) / Client Originated (CO) 559
7.2.2 Off-network / Enhanced Status (ES) / Client Terminated (CT) 566
7.3 Emergency Alert 571
7.3.1 Off-network / Group Call / Emergency Alert / Emergency Alert Retransmission / Cancel Emergency Alert / Client Originated (CO) 571
7.3.2 Off-network / Group Call / Emergency Alert / Emergency Alert Retransmission / Cancel Emergency Alert / Client Terminated (CT) 576

Annex A (normative): Test Files 582

A.1 Introduction 582
A.2 Test files for client originated file distribution 582
A.2.1 Test File 1 for CO FD 582
A.2.2 Test File 2 for CO FD 582
A.3 Test files for client terminated file distribution 582
A.3.1 Test File 1 for CT FD 582
A.3.2 Test File 2 for CT FD 582
Annex B (informative): Change history 583
History 587

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

x the first digit:

1 presented to TSG for information;

2 presented to TSG for approval;

3 or greater indicates TSG approved document under change control.

y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.

z the third digit is incremented when editorial only changes have been incorporated in the document.

The present document is part 1 of a multi-part deliverable covering conformance test specification for Mission Critical Services consisting of:

3GPP TS 37.579-1 [2]: "Mission Critical (MC) services; Part 1: Common test environment" (the present document)

3GPP TS 37.579-2 [24]: "Mission Critical (MC) services; Part 2: Mission Critical Push To Talk (MCPTT) User Equipment (UE) Protocol conformance specification"

3GPP TS 37.579-4 [4]: "Mission Critical (MC) services; Part 4: Test Applicability and Implementation Conformance Statement (ICS)"

3GPP TS 37.579-5 [5]: "Mission Critical (MC) services; Part 5: Abstract test suite (ATS)"

3GPP TS 37.579-6 [25]: "Mission Critical (MC) services: Mission Critical Video (MCVideo) User Equipment (UE) Protocol conformance specification"

3GPP TS 37.579-7: "Mission Critical (MC) services; Part 7: Mission Critical Data (MCData) User Equipment (UE) Protocol conformance specification"

In the present document, modal verbs have the following meanings:

shall indicates a mandatory requirement to do something

shall not indicates an interdiction (prohibition) to do something

The constructions "shall" and "shall not" are confined to the context of normative provisions, and do not appear in Technical Reports.

The constructions "must" and "must not" are not used as substitutes for "shall" and "shall not". Their use is avoided insofar as possible, and they are not used in a normative context except in a direct citation from an external, referenced, non-3GPP document, or so as to maintain continuity of style when extending or modifying the provisions of such a referenced document.

should indicates a recommendation to do something

should not indicates a recommendation not to do something

may indicates permission to do something

need not indicates permission not to do something

The construction "may not" is ambiguous and is not used in normative elements. The unambiguous constructions "might not" or "shall not" are used instead, depending upon the meaning intended.

can indicates that something is possible

cannot indicates that something is impossible

The constructions "can" and "cannot" are not substitutes for "may" and "need not".

will indicates that something is certain or expected to happen as a result of action taken by an agency the behaviour of which is outside the scope of the present document

will not indicates that something is certain or expected not to happen as a result of action taken by an agency the behaviour of which is outside the scope of the present document

might indicates a likelihood that something will happen as a result of action taken by some agency the behaviour of which is outside the scope of the present document

might not indicates a likelihood that something will not happen as a result of action taken by some agency the behaviour of which is outside the scope of the present document

In addition:

is (or any other verb in the indicative mood) indicates a statement of fact

is not (or any other negative verb in the indicative mood) indicates a statement of fact

The constructions "is" and "is not" do not indicate requirements.

1 Scope

The present document specifies the protocol conformance testing for testing a MCData Client for compliance to the Mission Critical Data (MCData) protocol requirements defined by 3GPP.

In particular the present document contains:

- the overall test structure;
- the test configurations;
- the conformance requirement and reference to the core specifications;
- the test purposes; and
- a brief description of the test procedure, the specific test requirements and short message exchange table.

The present document is valid for MCData Clients implemented according to 3GPP releases starting from Release 13 up to the Release indicated on the cover page of the present document.

The following information relevant to testing specified in the present document could be found in accompanying specifications:

- default setting of the test parameters TS 37.579-1 [2];
- Implementation Conformance Statement (ICS) TS 37.579-4 [4] and Implementation eXtra Information for Testing (IXIT) TS 37.579-5 [5];
- the applicability of each test case TS 37.579-4 [4].

The test cases are expected to be executed through the 3GPP radio interface. The present document does not specify the protocol conformance testing for the 3GPP bearers which carry the MCData data sent or received by the MCData Client and which are required to be supported by the UE in which the MCData Client is installed. This is defined in TS 36.523-1 [6] for EPS (LTE) or TS 38.523-1 [45] for NR/5GC.

According to 3GPP drafting rules, the references clause shall list only documents that are explicitly mentioned in the deliverable. This reference is not used within the document and thus shall be removed from references clause.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

[1] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".

[2] 3GPP TS 37.579-1: "Mission Critical (MC) services; Part 1: Common test environment".

[3] Void.

[4] 3GPP TS 37.579-4: " Mission Critical (MC) services; Part 4: Test Applicability and Implementation Conformance Statement (ICS).

[5] 3GPP TS 37.579-5: "Mission Critical (MC) services; Part 5: Abstract test suite (ATS)".

[6] 3GPP TS 36.523-1: "Evolved Universal Terrestrial Radio Access (E-UTRA) and Evolved Packet Core (EPC); User Equipment (UE) conformance specification; Part 1: Protocol conformance specification".

[7] Void

[8] Void

[9] 3GPP TS 24.379: "Mission Critical Push To Talk (MCPTT) call control; Protocol specification".

[10] Void

[11] 3GPP TS 24.481: "Mission Critical Services (MCS) group management; Protocol specification".

[12] 3GPP TS 24.482: "Mission Critical Services (MCS) identity management; Protocol specification".

[13] 3GPP TS 24.483: "Mission Critical Services (MCS) Management Object (MO)".

[14] 3GPP TS 24.484: "Mission Critical Services (MCS) configuration management; Protocol specification".

[15] 3GPP TS 33.179: " Security of Mission Critical Push To Talk (MCPTT) over LTE ".

[16] 3GPP TS 24.229: "IP multimedia call control protocol based on Session Initiation Protocol (SIP) and Session Description Protocol (SDP); Stage 3".

[17] 3GPP TS 24.301: "Non-Access-Stratum (NAS) protocol for Evolved Packet System (EPS); Stage 3".

[18] Void

[19] 3GPP TS 36.509: "Evolved Universal Terrestrial Radio Access (E-UTRA) and Evolved Universal Terrestrial Radio Access Network (E-UTRAN); Special conformance testing functions for User Equipment (UE)".

[20] 3GPP TS 36.508: "Evolved Universal Terrestrial Radio Access (E-UTRA) and Evolved Universal Terrestrial Radio Access (E-UTRAN); Common Test Environments for User Equipment (UE) Conformance Testing".

[21] OpenID Connect 1.0: "OpenID Connect Core 1.0 incorporating errata set 1", http://openid.net/specs/openid-connect-core-1_0.html.

[22] 3GPP TS 33.310: "Network Domain Security (NDS); Authentication Framework (AF)".

[23] Void

[24] 3GPP TS 37.579-2: "Mission Critical (MC) services; Part 2: Mission Critical Push To Talk (MCPTT) User Equipment (UE) Protocol conformance specification".

[25] 3GPP TS 37.579-6: "Mission Critical (MC) services; Part 6: Mission Critical Video (MCVideo) User Equipment (UE) Protocol conformance specification ".

[26] Void

[27] Void

[28] Void

[29] Void

[30] 3GPP TS 33.180: "Security of the mission critical service".

[31] 3GPP TS 24.282: "Mission Critical Data (MCData) signalling control; Protocol specification".

[32] 3GPP TS 24.582: "Mission Critical Data (MCData) media plane control; Protocol specification".

[33] 3GPP TS 23.282: "Functional architecture and information flows to support Mission Critical Data (MCData); Stage 2".

[34] 3GPP TS 22.282: "Mission Critical Data over LTE. Status: Under change control".

[35] Void

[36] IETF RFC 4826 (May 2007): "Extensible Markup Language (XML) Formats for Representing Resource Lists".

[37] IETF RFC 4122 (July 2005): "A Universally Unique IDentifier (UUID) URN Namespace".

[38] IETF RFC 2046: "Multipurpose Internet Mail Extensions (MIME) Part Two: Media Types".

[39] 3GPP TS 23.032: "Universal Geographical Area Description (GAD)".

[40] OMA-TS-REST_NetAPI_NMS-V1_0-20190528-C: "RESTful Network API for Network Message Storage".

[41] IETF RFC 4567: "Key Management Extensions for Session Description Protocol (SDP) and Real Time Streaming Protocol (RTSP)"

[42] OMA-TS-REST_NetAPI_Common-V1_0-20180116-A: "Common definitions for RESTful Network APIs"

[43] IETF RFC 2388: "Returning Values from Forms: multipart/form-data".

[44] IETF RFC 2616: "Hypertext Transfer Protocol -- HTTP/1.1".

[45] 3GPP TS 38.523-1: " 5GS; User Equipment (UE) conformance specification;Part 1: Protocol"

[46] OMA-TS-REST_NetAPI_NotificationChannel-V1_0-20200319-C: “RESTful Network API for Notification Channel”.

[47] OMA-SUP-XSD_rest_netapi_notificationchannel-V1_0: “XML data type definitions for the RESTful Network API for Notification Channel”, https://www.openmobilealliance.org/tech/profiles/rest_netapi_notificationchannel-v1_0.xsd

[48] OMA-SUP-XSD_rest_netapi_nms-V1_0: “XML data type definitions for the RESTful Network API for Network Message Storage (NMS)”, http://www.openmobilealliance.org/tech/profiles/rest_netapi_nms-v1_0.xsd

3 Definitions of terms, symbols and abbreviations

3.1 Terms

For the purposes of the present document, the terms given in TR 21.905 [1] and the following apply. A term defined in the present document takes precedence over the definition of the same term, if any, in TR 21.905 [1].

For the purpose of the present document, the following terms given in TS 23.282 [33] apply:

Auto-receive
Conversation identifier
Data stream
FD disposition
MCData client
MCData group
MCData group affiliation
MCData group communication
MCData group de-affiliation
MCData ID
MCData server

MCData service
MCData UE
MCData user
Reception control
Reply identifier
SDS data
SDS disposition
Standalone communication
Transaction identifier
Transmission control

For the purpose of the present document, the following terms given in TS 22.282 [34] apply:

Conversation
Conversation ID
MCData Conversation Hang Time
MCData System

For the purpose of the present document, the following terms given in 3GPP TS 33.180 [30] apply:

Client Server Key (CSK)
Private Call Key (PCK)
Signalling Protection Key (SPK)
XML Protection Key (XPK)

3.2 Symbols

Void.

3.3 Abbreviations

For the purposes of the present document, the abbreviations given in TR 21.905 [1] and the following apply. An abbreviation defined in the present document takes precedence over the definition of the same abbreviation, if any, in TR 21.905 [1].

CSK	Client-Server Key
DS	Data Streaming
ECGI	E-UTRAN Cell Global Identification
FD	File Distribution
FFS	For Further Study
ICS	Implementation Conformance Statement
IOPS	Isolated E-UTRAN Operation for Public Safety
IUT	Implementation Under Test
IXIT	Implementation eXtra Information for Testing
MBMS	Multimedia Broadcast and Multicast Service
MBSFN	Multimedia Broadcast multicast service Single Frequency Network
MC	Mission Critical
MCData	Mission Critical Data
MCData group ID	MCData group Identity
MCPTT	Mission Critical Push To Talk
MCS	Mission Critical Service
MCVideo	Mission Critical Video
MDEA	MCData Emergency Alert
MIME	Multipurpose Internet Mail Extensions
MONP	MC service Off-Network Protocol
NAT	Network Address Translation
PCC	Policy and Charging Control
PCCB	Private Call Call-Back
PCRF	Policy and Charging Rules Function
PLMN	Public Land Mobile Network

QCI	QoS Class Identifier
RTP	Real-time Transport Protocol
SAI	Service Area Identifier
SDP	Session Description Protocol
SDS	Short Data Service
SIP	Session Initiation Protocol
SPK	Signalling Protection Key
SS	System Simulator
SSRC	Synchronization SouRCe
TGI	Temporary MCVideo Group Identity
TMGI	Temporary Mobile Group Identity
TP	Transmission Point
TP	Test Purpose
UE	User Equipment
UM	Unacknowledged Mode
URI	Uniform Resource Identifier
XPK	XML Protection Key

4 General

4.1 Test methodology

4.1.1 Testing of optional functions and procedures

Any function or procedure which is optional, may be subject to a conformance test if it is implemented in the MCData Client.

A declaration by the MCData Client supplier (to use the Implementation Conformance Statement (ICS) proforma specified in TS 37.579-4 [4]) is used to determine whether an optional function/procedure has been implemented.

4.1.2 Test interfaces and facilities

Detailed descriptions of the MCData

Client test interfaces and special facilities for testing are provided in 3GPP TS 36.509 [19].

4.2 Implicit testing

For some 3GPP MCData protocol features conformance is not verified explicitly in the present document. This does not imply that correct functioning of these features is not essential, but that these are implicitly tested to a sufficient degree in tests which are not explicitly dedicated to test the feature.

4.3 Repetition of tests

As a general rule, the test cases specified in the present document are highly reproducible and do not need to be repeated unless otherwise stated.

4.4 Handling of differences between conformance requirements in different releases of cores specifications

The conformance requirements which determine the scope of each test case are explicitly copy-pasted from relevant core specifications in the especially dedicated for this clause of each test with the title 'Conformance requirements'.

NOTE: When in the copy/pasted text there are references to other specifications the reference numbers will not match the reference numbers used in the present document. This approach has been taken in order to allow easy copy and then search for conformance requirements in those specifications.

When differences between conformance requirements in different releases of the cores specifications have impact on the Pre-test conditions, Test procedure sequence or/and the Specific message contents, the Conformance requirements related to different releases are specified separately with clear indication of the Release of the spec from which they were copied.

When there is no Release indicated for a conformance requirement text, this should be understood either as the Conformance requirements in the latest version of the spec with release = the TC Applicability release (which can be found in TS 37.579-4 [4], Table 4-1: Applicability of tests and additional information for testing, column 'Release'), or, as the Conformance requirements in the latest version of the spec of the release when the feature was introduced to the core specs.

4.5 Reference conditions

The reference environments used by all signalling and protocol tests is specified in TS 37.579-1 [2]. Where a test requires an environment that is different, this will be specified in the test itself.

For all test cases in this document unless specified otherwise the condition MCDATA applies for all message contents.

4.6 Generic setup procedures

A set of basic generic procedures for MCData Client-Server communication are described in TS 37.579-1 [2]. These procedures will be used in numerous test cases throughout the present document.

5 MCData Client Configuration

5.1 Configuration / Authentication / User Authorization / UE Configuration / User Profile / Key Generation

5.1.1 Test Purpose (TP)

(1)

```
with { UE (MCDATA Client) attached to EPS or 5GS services }
ensure that {
  when { the MCData User activates an MCData application and requests MCData initialisation }
    then { UE (MCDATA Client) performs MCData User Authentication }
            }
```

(2)

```
with { UE (MCDATA Client) user authenticated }
ensure that {
  when { the UE (MCDATA Client) has established a secure HTPP tunnel }
    then { UE (MCDATA Client) performs key management authorization and obtains identity management
key material }
            }
```

(3)

```
with { UE (MCDATA Client) has obtained identity management key material }
ensure that {
  when { the UE (MCDATA Client) requests user service authorization }
    then { UE (MCDATA Client) sends a user authorization request to the MCData Server }
            }
```

(4)

```
with { UE (MCDATA Client) authorized for user services }
ensure that {
  when { the UE (MCDATA Client) requests configuration management authorization}
    then { UE (MCDATA Client) requests subscription to multiple documents simultaneously and request
the retrieval of the MCData UE Configuration document, the MCData User Profile Configuration
Document and the MCData Service Configuration Document }
            }
```

(5)

```
with { UE (MCDATA Client) having obtained user configuration data }
ensure that {
  when { the UE (MCDATA Client) requests group management authorization }
    then { UE (MCDATA Client) receives the group profile including group traffic keys }
            }
```

(6)

```
with { UE (MCDATA Client) having obtained all required configuration data }
ensure that {
  when { the UE (MCDATA Client) requires to refresh its service settings }
    then { UE (MCDATA Client) sends a SIP PUBLISH request }
            }
```

5.1.2 Conformance requirements

References: The conformance requirements covered in the present TC are specified in: TS 24.482 clause 6.2.1 and Annex A.2.1.2, TS 24.484 clauses 4.2.1, 4.2.2.1, 6.2.2, 6.3.1.1, 6.3.2.1, 6.3.2.2, 6.3.3.2.1, 6.3.3.2.2, 6.3.13.2.1 and 6.3.13.2.2, TS 24.481 clauses 6.2.2.2, 6.2.3, 6.3.3.2.1, 6.3.3.2.2 and 6.3.13.2.1, TS 24.282 clauses 7.2.1, 7.2.1A, 7.2.2 and 7.2.3, TS 33.180 clauses 5.1.3.1, 5.3.3, 6.1.2, and Annex D. The following represents a copy/paste extraction of the requirements relevant to the test purpose; any references within the copy/paste text should be understood within the scope of the core spec they have been copied from. Unless otherwise stated these are Rel-14 requirements.

[TS 24.482, clause 6.2.1]

Upon an indication from the MC service client to initiate MC service user authentication, the IdM client shall perform the user authentication procedure according to 3GPP TS 33.180 [17] with the following clarifications:

1) shall establish a TLS tunnel to the authorisation endpoint of the IdM server as specified in 3GPP TS 33.180 [17] using the configured URL of the authorisation endpoint of the IdM server as specified in the "/<x>/OnNetwork/AppServerInfo/IDMSAuthEndpoint" leaf node defined in 3GPP TS 24.483 [11] and the clarifications in annex A;

2) shall generate an OIDC Authentication Request message as specified in the OpenID Connect 1.0 [6] and IETF RFC 6749 [5] with the following clarifications:

   a) shall generate an HTTP GET request method according to IETF RFC 2616 [4];

   b) shall include the configured parameter IdM client id as the client_id parameter specified in 3GPP TS 33.180 [17] in the query component of the authorization endpoint's URI using the "application/x-www-form-urlencoded" format as specified in W3C.REC-html401-19991224 [7]; and

   NOTE 1: The configuration of client_id is specified in 3GPP TS 24.483 [11].

   c) shall include the remaining required parameters as specified in 3GPP TS 33.180 [17] in the query component of the authorization endpoint's URI using the "application/x-www-form-urlencoded" format as specified in W3C.REC-html401-19991224 [7]; and

3) shall send the HTTP GET request method towards the IdM server.

NOTE 2: The OpenID Connect 1.0 [6] specification allows for an alternative mechanism for sending the OIDC Authentication request message using an HTTP POST request method which can be used in place of steps 1, 2, and 3 above.

Upon receipt of an HTTP 200 (OK) response from the IdM server, the IdM client:

1) shall prompt the MC service user for their username and password;

NOTE 3: Other types of authentication are supported and are not defined by the OIDC specifications. 3GPP TS 33.180 [17] has defined username and password as a mandatory authentication method to be supported, hence a procedure to realize that method is included here.

2) shall generate an HTTP POST request method containing the MC service user's username and password; and

3) shall send the HTTP POST request method towards the IdM server.

Upon receipt of an OIDC Authentication Response message, the IdM client:

1) shall establish a TLS tunnel to the token endpoint of the IdM server as specified in 3GPP TS 33.180 [17] using the configured URL of the token endpoint of the IdM server as specified in the "/<x>/OnNetwork/AppServerInfo/IDMSTokenEndpoint" leaf node defined in 3GPP TS 24.483 [11] and the clarifications in annex A;

2) shall generate an OIDC Token Request message as specified in OpenID Connect 1.0 [6] and IETF RFC 6749 [5] with the following clarifications:

   a) shall generate an HTTP POST request method according to IETF RFC 2616 [4]; and

   b) shall include the grant_type parameter set to a value of "authorization_code" and the other required parameters in the entity body of the HTTP POST request method using the using the "application/x-www-form-urlencoded" format as specified in 3GPP TS 33.180 [17]; and

3) shall send the HTTP POST request method towards the IdM server.

Upon receipt of an OIDC Token Response message, the IdM client:

1) shall validate the id_token, access_token and refresh token in the received OIDC Token Response message as specified in the OpenID Connect 1.0 [6] specification; and

2) shall provide the id_token and access_token in the received OIDC Token Response message to the MC service client.

NOTE 4: The method in which the IdM client provides the id_token and access_token to the MC service client is implementation specific.

The MC UE may repeat the entire procedure in this clause as needed to obtain the necessary authorisation tokens for the MC service clients, depending on the scope parameter in the Authentication Request message as specified in 3GPP TS 33.180 [17].

[TS 24.482, Annex A.2.1.2]

The HTTP client in the UE shall support the client role defined in IETF RFC 2818 [10].

The HTTP client in the UE shall support transport layer security (TLS) as specified in 3GPP TS 33.180 [17].

The HTTP client in the UE is configured with the following parameters:

1) a home HTTP proxy FQDN;

2) a home HTTP proxy port;

3) a TLS tunnel authentication method. The TLS tunnel authentication method parameter is set to one of the following:

   a) one-way authentication of the HTTP proxy based on the server certificate;

   b) mutual authentication based on certificates; and

   c) mutual authentication based on pre-shared key;

   as specified in 3GPP TS 33.180 [17];

4) if the TLS tunnel authentication method is the mutual authentication based on certificates:

a) TLS tunnel authentication X.509 certificate; and

5) if the TLS tunnel authentication method is the mutual authentication based on pre-shared key;

a) TLS tunnel authentication pre-shared key.

The HTTP client in the UE shall establish a TCP connection towards the home HTTP proxy FQDN and the home HTTP proxy port, unless the specific TCP connection is to be used for the IdM client to IdM server procedures described in clause 6.2 and subclause 6.3 in the present document, in which case the HTTP client shall establish a TCP connection towards the IdM server.

The HTTP client in the UE shall establish a TLS tunnel via the TCP connection as specified in 3GPP TS 33.180 [17]. When establishing the TLS tunnel, the HTTP client in the UE shall act as a TLS client and the UE shall perform the TLS tunnel authentication using the TLS authentication method indicated by the TLS tunnel authentication method parameter according to 3GPP TS 33.180 [17]. The UE shall use the configured TLS tunnel authentication X.509 certificate and the configured TLS tunnel authentication pre-shared key when applicable for the used TLS authentication method. In order to prevent man-in-the-middle attacks, the HTTP client in the UE shall check the home HTTP proxy FQDN against the server's identity as presented in the received server's certificate message if the TCP connection terminates on the HTTP proxy. The HTTP client in the UE shall not check the portion of dereferenced HTTP URL against the server's identity as presented in the received server's certificate message if the TCP connection terminates on the HTTP proxy, but shall do so if the TCP connection terminates on the IdM server.

NOTE: The TLS tunnel can be terminated in the HTTP proxy (rather than in the HTTP server providing the dereferenced HTTP URL).

The HTTP client in the UE shall send and receive all HTTP messages via the TLS tunnel.

If the HTTP client in the UE has an access token of the "bearer" token type as specified in IETF RFC 6750 [14], the HTTP client in the UE shall include an Authorization header field with the "Bearer" authentication scheme as specified in IETF RFC 6750 [14] in HTTP requests.

[TS 33.180, Annex D.1]

This annex specifies the key management procedures between the KMS and the key management client that allows keys to be provisioned to the key management client based on an identity. It describes the requests and responses for the authorization following provisioning messages:

- KMS Initialize.
- KMS KeyProvision.
- KMS CertCache.

All KMS communications are made via HTTPS. The key management client is provisioned via XML content in the KMS's response. The XML content is designed to be extendable to allow KMS/client providers to add further information in the XML. Where the interface is extended, a different XML namespace should be used (so that may be ignored by non-compatible clients).

It is assumed that transmissions between the KMS and the key management client are secure and that the KMS has authenticated the identity of the key management client.

Additionally, to allow the transmission of key material securely between a secure element within the KMS and a secure element within the key management client, a security extension is defined which allows messages to be signed and key material to be encrypted using a shared Transport Key (TrK).

[TS 33.180, clause 5.1.3.1]

This clause expands on the MCX user service authorization step shown in figure 5.1.1-1 step C.

MCX User Service Authorization is the function that validates whether or not a MCX user has the authority to access certain MCX services. In order to gain access to MCX services, the MCX client in the UE presents an access token (acquired during user authentication as described in subclause 5.1.2) to each service of interest (i.e. Key Management, MCX server, Configuration Management, Group Management, etc.). If the access token is valid, then the user is granted the use of that service. Figure 5.1.3.1-1 shows the flow for user authorization which covers key management authorization, MCX user service authorization, configuration management authorization, and group management authorization.

NOTE: All HTTP traffic between the UE and HTTP proxy, and all HTTP traffic between the UE and KMS (if not going through the HTTP proxy) is protected using HTTPS.

For key management authorization, the KM client in the UE presents an access token to the KMS over HTTP. The KMS validates the access token and if successful, provides one or more sets of user specific key material back to the UE KM client based on the MC service ID(s) present in the access token (MCPTT ID, MCVideo ID and/or MCData ID). User specific key material includes identity based key information for media and signalling protection. This key management authorisation may be repeated for each KM service the user is authorised to use (MCPTT, MCVideo, MCData).

For MCPTT user service authorization, the MCPTT client in the UE presents an access token to the MCPTT server over SIP. The MCPTT server validates the access token and if successful, authorizes the user for full MCPTT services and sends an acknowledgement back to the MCPTT client. The MCPTT server then maps and maintains the IMPU to MCPTT ID association. The MCPTT ID to IMPU association shall only be known to the application layer. The SIP message used to convey the access token from the MCPTT client to the MCPTT server may be either a SIP REGISTER or SIP PUBLISH message.

For MCVideo service authorization, the MCVideo client in the UE presents an access token to the MCVideo server over SIP. The MCVideo server validates the access token and if successful, authorizes the user for full MCVideo services and sends an acknowledgement back to the MCVideo client. The MCVideo server then maps and maintains the IMPU to MCVideo ID association. The MCVideo ID to IMPU association shall only be known to the application layer. The SIP message used to convey the access token from the MCVideo client to the MCVideo server may be either a SIP REGISTER or SIP PUBLISH message.

For MCData user service authorization, the MCData client in the UE presents an access token to the MCData server over SIP. The MCData server validates the access token and if successful, authorizes the user for full MCData services and sends an acknowledgement back to the MCData client. The MCData server then maps and maintains the IMPU to MCData ID association. The MCData ID to IMPU association shall only be known to the application layer. The SIP message used to convey the access token from the MCData client to the MCData server may be either a SIP REGISTER or SIP PUBLISH message.

The UE can now perform configuration management authorization and download the user profile for the service(s) (MCPTT, MCVideo, MCData). Following the flow described in subclause 10.1.4.3 of 3GPP TS 23.280 [36] " MC service user obtains the MC service user profile(s) from the network ", the Configuration Management (CM) client in the UE sends an access token in the user profile query to the Configuration Management server over HTTP. The CM server receives the request and validates the access token, and if valid, the CM server uses the identity from the access token (MCPTT ID, MCVideo ID, MCData ID) to obtain the user profile from the MCX user database. The CM server then sends the user profile back to the CM client over HTTP. This configuration management authorisation may be repeated for each CM service the user is authorised to use (MCPTT, MCVideo, MCData).

Upon receiving each user profile, the Group Management (GM) client in the UE can now perform group management authorization. The GM client obtains the user's group membership information from the user profile, and following the flow shown in clause 10.1.5.2 of 3GPP TS 23.280 [36] "Retrieve group configurations at the group management client", the Group Management (GM) client in the UE sends an access token in the Get group configuration request to the host GM server of the group membership over HTTP. The GM server validates the access token, and if valid, completes the flow. As part of group management authorization, group key information is provided as per subclause 5.7 of the present document. This group management authorisation may be repeated for each GM service the user is authorised to use (MCPTT, MCVideo, MCData).




Figure 5.1.3.1-1: MCX user service authorization

The user authorization procedure in Step C of Figure 5.1.1-1 is further detailed into 5 sub steps that comprise the MCX user service authorization process:

Step C-1: If not already done, establish a secure HTTP tunnel using HTTPS between the MCX UE and MCX proxy server. Subsequent HTTP messaging makes use of this tunnel (with the possible exception of the KMS client to KMS server interface).

Step C-2: The KMS client in the UE presents an access token to the KMS over HTTP. The KMS authorizes the user for key management services based upon the MC service ID(s) provided and replies to the client with identity specific key information. This step may be repeated to authorise the user with additional KM services (MCPTT, MCVideo, MCData) as necessary.

Step C-3: The MCX client in the UE presents an access token to the MCX server over SIP as defined in clause 5.1.3.2 of the present document. This step may be repeated to authorise the user with additional MCX services (MCPTT, MCVideo, MCData) as necessary.

Step C-4: The CM client in the UE follows the "MCX user obtains the user profile (UE initiated)" flow from clause 10.1.4.3 of 3GPP TS 23.280 [36], presenting an access token in the Get MCX user profile request over HTTP. If the token is valid, then the CM server authorizes the user for configuration management services. Completion of this step results in the CM server providing the user's profile to the CM client. This step may be repeated as necessary to obtain the user profile for additional services (MCPTT, MCVideo, or MCData).

Step C-5: The GM client in the UE follows the "Retrieve group configurations at the group management client" flow as shown in clause 10.1.5.2 of 3GPP TS 23.280 [36], presenting an access token in the Get group configuration request over HTTP. If the token is valid, the GMS authorizes the user for group management services. Completion of this step results in the GMS sending the user's group policy information and group key information to the GM client. This step may be repeated to authorise the user for additional group services (MCPTT, MCVideo, MCData) as necessary.

[TS 33.180, clause 5.3.3]

The procedure for the provision of identity-specific key material when the HTTP proxy is supported between the KMS and the KMS client is described in figure 5.3.3-1. The procedure is the same whether the key management client in the MC UE, an MCX Server or a Group Management Server is making the request.




Figure 5.3.3-1: Provisioning of key material via the HTTP proxy

The procedure in figure 5.3.3-1 is now described step-by-step.

0) The key management client establishes a connection to the KMS. As with other elements in the Common Services Core, the connection is routed via, and secured by, the HTTP Proxy. The message flow below is within this secure connection.

NOTE: Additionally, the connection between the KMS and the HTTP Proxy is secured according to clause 6.1.

1) The key management client makes a request for user key material from the KMS. The request contains an access token to authenticate the user as defined in clause 5.1. There are three types of request (as defined in Annex D):

   a) KMSInit Request. This request is the first request sent to the KMS to setup the user.

   b) KMSKeyProv Request: This request is to obtain new key material from the KMS. The request may contain details of a specific identity (e.g. MCPTT ID) required for key management, and may contain a specific time for which the key material is required.

   c) KMSCertCache Request: This request is to obtain external KMS certificates associated with external security domains (managed by another KMS). The request may contain details of the latest version of the cache received by the client.

2) The KMS provides a response based upon the authenticated user and the user's request. For public safety use, the key material itself shall be encrypted using a 256-bit transport key (TrK). The response may also be signed by the TrK or the InK. The TrK and InK are initially distributed via an out-of-band mechanism along with their 32-bit identifiers, the TrK-ID and InK-ID, respectively. The responses are:

   a) KMSInit Response. This response contains domain parameters and optionally, a new TrK and/or a new InK.

   b) KMSKeyProv Response: This response provides new key material to the user and optionally, a new TrK.

   c) KMSCertCache Response: This response contains new or updated home KMS certificates and/or external KMS certificates required by the user for communications with external security domains.

The procedure for the provisioning of identity-specific key material when the HTTP proxy is not used between the KMS and the KMS client is as described in Figure 5.3.3-2.




Figure 5.3.3-2: Provisioning of key material without a proxy

The procedure in Figure 5.3.3-2 is now described step-by-step:

0) The key management client establishes a direct HTTPS connection to the KMS. The following message flow is within this secure connection.

1) The key management client makes a request to the KMS. The same requests can be made as defined above with a proxy.

2) The KMS provides a response based upon the authenticated user and the user's request. Optionally, the key material itself may also be encrypted using a 256-bit transport key (TrK). The response may also be signed using the TrK or the InK. The TrK and InK are initially distributed via an out-of-band mechanism along with their 32-bit identifiers (TrK-ID and InK-ID respectively).

As a result of this procedure, the key management client has securely obtained key material for use within the MC system.

[TS 24.484, clause 4.2.1]

Upon start up the MC UE bootstraps the required information (e.g. FQDN or IP address) to locate the configuration management server for configuration of the MCS UE initial configuration management object (MO) and the default MCPTT user profile configuration management object (MO).

In order to obtain access to MC services the UE needs to obtain configuration data either online via the network or offline using some external device (e.g. a laptop). As part of the bootstrap process the MC UE needs to discover either:

1. the online configuration management server in the network that configures the MCS UE initial configuration MO and the default MCS user profile configuration MO(s), then the MC UE:

   a) using the URI of the configuration management server obtained from the MCS UE initial configuration MO, obtains for each MCS that is enabled:

      - the appropriateMCS UE configuration document;

      - the appropriateMCS user profile configuration document; and

      - the appropriateMC service configuration document; and

   b) using the URI of the group management server obtained from the MCS UE initial configuration MO obtain the MCS group document; or

2. the:

   a) offline configuration management server on the external device that configures the MC UE with the:

      - MCS UE initial configuration MO;

      - appropriate MCS UE configuration MO(s);

      - appropriate MCS user profile MO(s); and

- appropriate MCS service configuration MO(s); and

b) offline group management server on the external device that configures the MC UE with the MCS group MO.

The mechanism to discover the online or offline configuration management server is dependent on the protocol used to manage and configure the MO and is out of scope of the present document.

[TS 24.484, clause 4.2.2.1]

The format of the MCS UE initial configuration MO downloaded to the MC UE during online configuration is defined in 3GPP TS 24.483 [4].

The format of the MCS group document downloaded to the MC UE during online configuration is defined in 3GPP TS 24.481 [5].

Figure 4.2.2-1 shows the MCPTT UE online configuration time sequence.




Figure 4.2.2-1 MC UE online configuration time sequence

If the MCS UE initial configuration MO has changed from the version stored in the MC UE, the updated MC UE initial configuration MO is downloaded to the MCPTT UE.

If the MCS UE initial configuration MO contains a <default-user-profile> element and the identified default MCS user profile configuration MO(s) have changed from the version stored in the MC UE, the updated default MCS user profile configuration MO(s) are downloaded to the MC UE.

NOTE 1: The default MCS user profile configuration MO(s) define the default identity(s) for the enabled mission critical service(s) and the profile of services available to the user (e.g. emergency MCPTT services) prior to user authentication.

The MC UE contacts the identity management server using the HTTPS URI stored in the MCS UE initial configuration MO and performs MC User authentication as specified in 3GPP TS 24.482 [6].

The MC UE, using the identities obtained during MC user authentication, subscribes to the MCS UE configuration document, the MCS user profile configuration document and the MCS service configuration document for each enabled MCS using the procedure for subscribing to multiple documents simultaneously using the subscription proxy function

specified in subclause 6.3.13.2.2(i.e., the CMS acts as a Subscription Proxy) and subscribes to the MCS group document using the procedure specified in 3GPP TS 24.481 [5]. If these documents have been updated since the current version stored in the MC UE, then the MC UE will receive a SIP NOTIFY request with an XCAP Diff document (see IETF RFC 5875 [11]), in which case the CMC updates its local document copies . Retrieval by the MC UE using the notified HTTPS URI of the MCS group document is performed as specified in 3GPP TS 24.481 [5].

NOTE 2: The MC UE can be notified of changes to an configuration documents at any time while using the MCS.

[TS 24.484, clause 6.2.2]

The CMC shall send the HTTP request over TLS connection as specified for the HTTP client in the UE in annex A of 3GPP TS 24.482 [6].

[TS 24.484, clause 6.3.1.1]

A CMC shall support subclause 6.1.1 "*Document Management*" of OMA OMA-TS-XDM_Core-V2_1 [2] and subclause 6.3.13.2.2 for subscribing to configuration management documents.

[TS 24.484, clause 6.3.3.2.1]

In order to retrieve a configuration management document, a GC shall send an HTTP GET request with the Request URI that references the document to be updated to the network according to procedures specified in IETF RFC 4825 [14] "*Retrieve a Document*".

[TS 24.484, clause 6.3.3.2.2]

In order to retrieve a configuration management document, a CMC shall perform the procedures in subclause 6.3.3.2.1 specified for GC. The CMC shall set the Request-URI of the HTTP GET request to the "CMSXCAPRootURI" configured as per 3GPP TS 24.483 [4] and include the "auid" as per the appropriate application usage in clause 7.

Subclause 7.5 specifies which configuration management documents can be retrieved from the CMS over the CSC-4 reference point.

[TS 24.484, clause 6.3.13.2.1]

This procedure enables the CMC to subscribe to notification of changes of one or more configuration management documents defined.

This procedure enables the MCS server to subscribe to notification of changes of the MCPTT service configuration document.

[TS 24.484, clause 6.3.13.2.2]

In order to subscribe to Configuration management document, a CMC shall send an initial SIP SUBSCRIBE request to the network according to the UE originating procedures specified in 3GPP TS 24.229 [22] and IETF RFC 5875 [11]. In the initial SIP SUBSCRIBE request, the CMC:

…

b) if subscription to multiple documents simultaneously using the subscription proxy function is used:

   1) shall include an application/resource-lists+xml MIME body. In the application/resource-lists+xml MIME body, the CMC shall include one <entry> element for each document or element to be subscribed to, such that the "uri" attribute of the <entry> element contains a relative path reference:

      A) with the base URI being equal to the "CMSXCAPRootURI" configured in the CMC as per 3GPP TS 24.483 [4]; and

      B) with the "auid" parameter set to the appropriate application usage identifying a configuration management document;

   2) shall set the Request-URI to the configured public service identity for performing subscription proxy function of the CMS;

c) shall include an application/vnd.3gpp.mcptt-info+xml MIME body with the <mcptt-access-token> element set to the value of the access token received during authentication procedure as described in 3GPP TS 24.482 [6];

d) if identity hiding is required:

1) shall perform the confidentiality protection procedures and integrity protection procedures defined in 3GPP TS 24.379 [9] for MCPTT client on the application/vnd.3gpp.mcptt-info+xml MIME body and on the application/resource-lists+xml MIME body; and

2) shall include an application/mikey MIME body with the CSK as specified in 3GPP TS 24.379 [9];

e) shall include the ICSI value "urn:urn-7:3gpp-service.ims.icsi.mcptt" (coded as specified in 3GPP TS 24.229 [22]), in a P-Preferred-Service header field according to IETF RFC 6050 [23]; and

f) shall include the g.3gpp.icsi-ref media feature tag containing the value of "urn:urn-7:3gpp-service.ims.icsi.mcptt" in the Contact header field.

Upon receiving a SIP NOTIFY request associated with a subscription created as result of the sent initial SIP SUBSCRIBE request:

1) if identity hiding is required, the CMC shall perform the confidentiality protection procedures and integrity protection procedures defined in 3GPP TS 24.379 [9] for MC client; and

2) shall handle the SIP NOTIFY request according to IETF RFC 5875 [11].

In order to re-subscribe to notification of changes of a modified list of one or more configuration management documents; a CMC shall send a SIP re-SUBSCRIBE request to the network according to the UE originating procedures specified in 3GPP TS 24.229 [22] and IETF RFC 5875 [11]. In the SIP re-SUBSCRIBE request, the CMC:

a) if direct subscription is used, shall set the Request URI to a SIP URI containing:

1) the base URI being equal to the "CMSXCAPRootURI" configured in the CMC as per 3GPP TS 24.483 [4]; and

2) the "auid" parameter set to the appropriate application usage identifying a configuration management document as described in clause 7;

b) if subscription to multiple documents simultaneously using the subscription proxy function is used:

1) shall include an application/resource-lists+xml MIME body. In the application/resource-lists+xml MIME body, the CMC shall include one <entry> element for each document or element to be subscribed to, such that the "uri" attribute of the <entry> element contains a relative path reference:

A) with the base URI being equal to the "CMSXCAPRootURI" configured in the CMC as per 3GPP TS 24.483 [4]; and

B) with the "auid" parameter set to the appropriate application usage identifying a configuration management document as described in clause 7;

c) if identity hiding is required, shall perform the confidentiality protection procedures and integrity protection procedures defined in 3GPP TS 24.379 [9] for MC client on the application/vnd.3gpp.mcptt-info+xml MIME body and on the application/resource-lists+xml MIME body using the CSK included in the initial SIP SUBSCRIBE request; and

d) shall include the g.3gpp.icsi-ref media feature tag containing the value of "urn:urn-7:3gpp-service.ims.icsi.mcptt" in the Contact header field.

[TS 24.481, clauses 6.2.2.2]

In order to address an existing group document defining a group ID known by GC, the GC shall set the Request-URI of an HTTP request to a XCAP URI identifying a group document addressed by a group ID as described in subclause 7.2.10.2, where the group ID is set to the group ID known by GC and where the XCAP root URI is the XCAP root URI configured in the GC.

[TS 24.481, clauses 6.2.3]

The GMC shall send the HTTP request over a TLS connection as specified for the HTTP client in the UE in annex A of 3GPP TS 24.482 [10].

The GMC shall perform the procedures in subclause 6.2.2 specified for GC.

[TS 24.481, clauses 6.3.3.2.1]

In order to retrieve a group document, a GC shall send an HTTP GET request with the Request URI that references the document to be retrieved to the network according to procedures specified in IETF RFC 4825 [22] "*Fetch a Document*".

[TS 24.481, clauses 6.3.3.2.2]

In order to retrieve a group document, a GMC shall perform the procedures in subclause 6.3.3.2.1 specified for GC.

[TS 24.481, clauses 6.3.13.2.1]

In order to subscribe to notification of changes of:

a) one or more MCData group documents of MCData groups identified by MCData group IDs;

…

a GMC shall send an initial SIP SUBSCRIBE request to the network according to the UE originating procedures specified in 3GPP TS 24.229 [12] and IETF RFC 5875 [13]. In the initial SIP SUBSCRIBE request, the GMC:

a) shall include an application/resource-lists+xml MIME body. In the application/resource-lists+xml MIME body, the GMC shall include one <entry> element for each document or element to be subscribed to, such that the "uri" attribute of the <entry> element:

   1) contains a relative path reference:

      A) with the base URI being equal to the XCAP root URI configured in the GMC; and

      B) identifying a group document addressed by a group ID as described in subclause 7.2.10.2 where the group ID is set to the MCData group ID; or

   ...

b) shall set the Request-URI to the configured public service identity for performing subscription proxy function of the GMS;

c) shall include an application/vnd.3gpp.mcptt-info+xml MIME body with the <mcptt-access-token> element set to the value of the access token received during authentication procedure as described in 3GPP TS 24.482 [49];

d) if identity hiding is required:

   1) shall perform the confidentiality protection procedures and integrity protection procedures defined in 3GPP TS 24.379 [5] for MCPTT client on the application/vnd.3gpp.mcptt-info+xml MIME body and on the application/resource-lists+xml MIME body; and

   2) shall include an application/mikey MIME body with the CSK as specified in 3GPP TS 24.379 [5];

e) shall include the ICSI value "urn:urn-7:3gpp-service.ims.icsi.mcptt" (coded as specified in 3GPP TS 24.229 [12]), in a P-Preferred-Service header field according to IETF RFC 6050 [14]; and

f) shall include the g.3gpp.icsi-ref media feature tag containing the value of "urn:urn-7:3gpp-service.ims.icsi.mcptt" in the Contact header field.

Upon receiving a SIP NOTIFY request associated with a subscription created as result of the sent initial SIP SUBSCRIBE request:

1) if identity hiding is required, the GMC shall perform the confidentiality protection procedures and integrity protection procedures defined in 3GPP TS 24.379 [5] for MCPTT client; and

2) shall handle the SIP NOTIFY request according to IETF RFC 5875 [13].

[TS 24.282, clause 7.2.1]

When the MCData client performs SIP registration for service authorisation the MCData client shall perform the registration procedures as specified in 3GPP TS 24.229 [5].

The MCData client shall include the following media feature tags in the Contact header field of the SIP REGISTER request:

1) the g.3gpp.icsi-ref media feature tag containing the value of "urn:urn-7:3gpp-service.ims.icsi.mcdata";

2) if SDS is supported then:

   a) the g.3gpp.mcdata.sds media feature tag; and

   b) the g.3gpp.icsi-ref media feature tag containing the value of "urn:urn-7:3gpp-service.ims.icsi.mcdata.sds"; and

3) if FD service is supported then:

   a) the g.3gpp.mcdata.fd media feature tag; and

   b) the g.3gpp.icsi-ref media feature tag containing the value of "urn:urn-7:3gpp-service.ims.icsi.mcdata.fd".

NOTE 1: If the MCData client logs off from the MCData service but the MCData UE remains registered the MCData UE performs a re-registration as specified in 3GPP TS 24.229 [5] without the supported g.3gpp.mcdata media feature tags and the g.3gpp.icsi-ref media feature tag containing the supported MCData service ICSIs in the Contact header field of the SIP REGISTER request.

If the MCData client, upon performing SIP registration:

1) has successfully finished the user authentication procedure as described in 3GPP TS 24.482 [24];

2) has available an access-token;

3) based on implementation decides to use SIP REGISTER for service authorization;

4) confidentiality protection is disabled as specified in subclause 6.5.2.3.1; and

5) integrity protection is disabled as specified in subclause 6.5.3.3.1;

then the MCData client shall include an application/vnd.3gpp.mcdata-info+xml MIME body as defined in Annex F.1 with the <mcdata-access-token> element set to the value of the access token received during the user authentication procedures, in the SIP REGISTER request.

NOTE 2: the access-token contains the MCData ID of the user.

If the MCData client, upon performing SIP registration:

1) has successfully finished the user authentication procedure as described in 3GPP TS 24.482 [24];

2) has an available access-token;

3) based on implementation decides to use SIP REGISTER for service authorization; and

4) either confidentiality protection is enabled as specified in subclause 6.5.2.3.1 or integrity protection is enabled as specified in subclause 6.5.3.3.1;

then the MCData client:

1) shall include an application/mikey MIME body with the CSK as MIKEY-SAKKE I_MESSAGE as specified in 3GPP TS 33.180 [26] in the body of the SIP REGISTER request;

2) if confidentiality protection is enabled as specified in subclause 6.5.2.3.1, shall encrypt the received access-token using the CSK and shall include in the body of the SIP REGISTER request, an application/vnd.3gpp.mcdata-info+xml MIME body with the <mcdata-access-token> element set to the encrypted access-token, as specified in subclause 6.5.3.3.1;

3) if confidentiality protection is disabled as specified in subclause 6.5.2.3.1, shall include an application/vnd.3gpp.mcdata-info+xml MIME body as defined in Annex F.1 with the <mcdata-access-token> element set to the value of the access token received during the user authentication procedures; and

4) if integrity protection is enabled as specified in subclause 6.5.3.3.1, shall use the CSK to integrity protect the application/vnd.3gpp.mcdata-info+xml MIME body by following the procedures in subclause 6.6.3.3.3.

[TS 24.282, clause 7.2.1A]

This procedure is only referenced from other procedures.

When populating the SIP PUBLISH request, the MCData client shall:

1) shall set the Request-URI to the public service identity identifying the participating MCData function serving the MCData user;

2) shall include the ICSI value "urn:urn-7:3gpp-service.ims.icsi.mcdata" (coded as specified in 3GPP TS 24.229 [5]), in a P-Preferred-Service header field according to IETF RFC 6050 [7];

3) shall set the Event header field to the "poc-settings" value; and

4) shall set the Expires header field according to IETF RFC 3903 [34], to 4294967295, if the MCData user is not removing the MCData service settings, otherwise to remove the MCData service settings the MCData client shall set the Expires header field to zero.

NOTE 1: 4294967295, which is equal to 2^{32}-1, is the highest value defined for Expires header field in IETF RFC 3261 [4].

NOTE 2: The expiration timer of the MCData client service settings is only applicable for the MCData client service settings from the MCData client that matches the Instance Identifier URN. The expiration timer of MCData user service settings is also updated in the MCData server if expiration timer of MCData client service settings is updated in the MCData server.

NOTE 3: Removing the MCData service settings by setting the Expires header field to zero, logs off the MCData client from the MCData service.

[TS 24.282, clause 7.2.2]

If based on implementation the MCData client decides to use SIP PUBLISH for MCData server settings to also perform service authorization and

1) has successfully finished the user authentication procedure as described in 3GPP TS 24.482 [24]; and

2) has available an access-token;

then the MCData client:

1) shall perform the procedures in subclause 7.2.1A;

2) if confidentiality protection is disabled as specified in subclause 6.5.2.3.1 and integrity protection is disabled, shall include in the body of the SIP PUBLISH request, an application/vnd.3gpp.mcdata-info+xml MIME body as specified in Annex F.1 with the <mcdata-access-token> element set to the value of the access token received during the user authentication procedures;

3) if either confidentiality protection is enabled as specified in subclause 6.5.2.3.1 or integrity protection is enabled as specified in subclause 6.5.3.3.1 shall include an application/mikey MIME body with the CSK as MIKEY-SAKKE I_MESSAGE as specified in 3GPP TS 33.180 [26] in the body of the SIP PUBLISH request;

4) if confidentiality protection is enabled as specified in subclause 6.5.2.3.1, shall include in the body of the SIP PUBLISH request an application/vnd.3gpp.mcdata-info+xml MIME body with:

   a) the <mcdata-access-token> element set to the received access-token encrypted using the CSK, as specified in subclause 6.5.2.3.3; and

   b) the <mcdata-client-id> element set to the encrypted MCData client ID of the originating MCData client, as specified in subclause 6.5.2.3.3;

5) if confidentiality protection is disabled as specified in subclause 6.5.2.3.1, shall include in the body of the SIP PUBLISH request, an application/vnd.3gpp.mcdata-info+xml MIME body as specified in Annex F.1 with:

a) the <mcdata-access-token> element set to the value of the access token received during the user authentication procedures in the body of the SIP PUBLISH request; and

b) the <mcdata-client-id> element set to the value of the MCData client ID of the originating MCData client;

6) shall include an application/poc-settings+xml MIME body as defined in 3GPP TS 24.379 [10] containing:

a) the <selected-user-profile-index> element set to the value contained in the "user-profile-index" attribute of the selected MCData user profile as defined in 3GPP TS 24.484 [12]; and

7) if integrity protection is enabled as specified in subclause 6.5.3.3.1, shall use the CSK to integrity protect the application/vnd.3gpp.mcdata-info+xml MIME body and application/poc-settings+xml MIME body by following the procedures in subclause 6.5.3.3.3.

The MCData client shall send the SIP PUBLISH request according to 3GPP TS 24.229 [5].

[TS 24.282, clause 7.2.3]

To set, update, remove or refresh the MCData service settings, the MCData client shall generate a SIP PUBLISH request according 3GPP TS 24.229 [5], IETF RFC 3903 [34] and IETF RFC 4354 [35]. In the SIP PUBLISH request, the MCData client:

1) shall perform the procedures in subclause 7.2.1A;

2) if confidentiality protection is enabled as specified in subclause 6.5.2.3.1, shall include in the body of the SIP PUBLISH request, an application/vnd.3gpp.mcdata-info+xml MIME body with:

a) the <mcdata-request-uri> element set to the targeted MCData ID encrypted using the CSK, as specified in subclause 6.5.2.3.3; and

b) the <mcdata-client-id> element set to the encrypted MCData client ID of the originating MCData client, as specified in subclause 6.5.2.3.3;

3) if confidentiality protection is disabled as specified in subclause 6.5.2.3.1, shall include an application/vnd.3gpp.mcdata-info+xml MIME body as specified in Annex F.1 with:

a) the <mcdata-request-uri> set to the cleartext targeted MCData ID; and

b) the <mcdata-client-id> element set to the value of the MCData client ID of the originating MCData client;

4) shall include an application/poc-settings+xml MIME body as defined in 3GPP TS 24.379 [10] containing:

a) the <selected-user-profile-index> element set to the value contained in the "user-profile-index" attribute of the selected MCData user profile as defined in 3GPP TS 24.484 [12]; and

5) if integrity protection is enabled as specified in subclause 6.5.3.3.1, shall use the CSK to integrity protect the application/vnd.3gpp.mcdata-info+xml MIME body and application/poc-settings+xml MIME body by following the procedures in subclause 6.5.3.3.3.

The MCData client shall send the SIP PUBLISH request according to 3GPP TS 24.229 [5].

On receiving the SIP 200 (OK) response to the SIP PUBLISH request the MCData client may indicate to the MCData User the successful communication of the MCData service settings to the MCData server.

[TS 33.180, clause 6.1.2]

The support of Transport Layer Security (TLS) on HTTP-1 is mandatory. The profile for TLS implementation and usage shall follow the provisions given in 3GPP TS 33.310 [5], annex E.

If the PSK TLS based authentication mechanism is supported, the HTTP client in the MC UE and the HTTP Proxy shall support the TLS version, PSK ciphersuites and TLS Extensions as specified in the TLS profile given in 3GPP TS 33.310 [5], annex E. The usage of pre-shared key ciphersuites for TLS is specified in the TLS profile given in 3GPP TS 33.310 [5], annex E.

5.1.3 Test description

5.1.3.1 Pre-test conditions

Same pre-test conditions as for MCPTT test case 5.1 (TS 37.579-2 [24]) with the following exception(s):

- The term "MCPTT" is replaced with "MCData".

5.1.3.2 Test procedure sequence

Same test procedure sequence as for MCPTT test case 5.1 (TS 37.579-2 [24]) with the following exception(s):

- The term "MCPTT" is replaced with "MCData".

5.1.3.3 Specific message contents

Same specific message contents as for MCPTT test case 5.1 (TS 37.579-2 [24]) with the following exception(s):

- The term "MCPTT" is replaced with "MCData".
- Condition MCDATA is used for all messages.

5.2 Configuration / Group Creation / Group ReGroup Creation / Group ReGroup Teardown

5.2.1 Test Purpose (TP)

(1)

```
with { UE (MCData Client) attached to EPS or 5GS services }
ensure that {
  when { the UE (MCData Client) requests formation of a new MCData group }
    then { on successful group creation the UE (MCData Client) has access to the new group }
           }
```

(2)

```
with { UE (MCData Client) having access to at least two MCData groups }
ensure that {
  when { the UE (MCData Client) requests the groups to be combined }
    then { on successful group regrouping the UE (MCData Client) has access to the temporary group }
           }
```

(3)

```
with { UE (MCData Client) having access to a temporary group }
ensure that {
  when { the UE (MCData Client) requests temporary group tear down }
    then { on successful group tear down the UE (MCData Client) removes the temporary group }
           }
```

5.2.2 Conformance requirements

References: The conformance requirements covered in the present TC are specified in: TS 24.481 clauses 6.3.2.2.1, 6.3.2.2.2, 6.3.14.1, 6.3.14.2, 6.3.15.1 and 6.3.15.2; TS 33.180, clause 7.3.2. The following represents a copy/paste extraction of the requirements relevant to the test purpose; any references within the copy/paste text should be understood within the scope of the core spec they have been copied from. Unless otherwise stated these are Rel-14 requirements.

[TS 24.481, clause 6.3.2.2.1]

In order to create a group document, a GC shall create an XML document of the application usage specified in subclause 7.2.1 and shall send the XML document to the network according to procedures specified in

IETF RFC 4825 [22] "*Create or Replace a Document*". The GC shall set the Request-URI of the HTTP PUT request to an XCAP URI in users tree where the XUI is set to a group creation XUI configuration parameter.

[TS 24.481, clause 6.3.2.2.2]

In order to create a group document, a GMC shall perform the procedures in subclause 6.3.2.2.1 specified for GC.

[TS 24.481, clause 6.3.14.1]

This procedure enables a GMC to initiate creation of a temporary MCS group by combining MCS groups.

NOTE: The temporary MCS group formation procedure does not ensure that the MCSs of the temporary MCS group are the same as MCSs of each constituent MCS group of the temporary MCS group.

[TS 24.481, clause 6.3.14.2]

In order to form a temporary MCS group, a GMC shall send a HTTP POST request according to procedures specified in IETF RFC 2616 [21] and subclause 6.2.3. In the HTTP POST request, the GMC:

a) shall set the Request-URI to an XCAP URI:

   1) in users tree where the XUI is set to a group creation XUI configuration parameter; and

   2) with the document selector identifying the temporary MCS group to be created; and

b) shall include an application/vnd.3gpp.GMOP+xml MIME body containing a GMOP document requesting group regroup creation specified in subclause 7.3.4.3, with a <group> element containing a group document for an MCS group. In the group document, the GMC shall include the <on-network-temporary> element according to subclause 7.2. In the <on-network-temporary> element, the GMC shall include <constituent-MCPTT-group-IDs> element according to subclause 7.2. In the <constituent-MCPTT-group-IDs> element, the GMC shall include one <constituent-MCPTT-group-ID> element according to subclause 7.2 for each MCS group to be combined.

Upon reception of an HTTP 2xx response to the sent HTTP POST request, the GMC shall consider the temporary MCS group formation as successful.

Upon reception of an HTTP 409 (Conflict) response with at least one <alt-value> element in the <uniqueness-failure> error element, the GMC may repeat procedures of the present subclause and identify the temporary MCS group being formed with an MCS Group ID indicated in an <alt-value> element.

[TS 24.481, clause 6.3.15.1]

This procedure enables a GMC to initiate tear down of a temporary MCS group.

[TS 24.481, clause 6.3.15.2]

In order to tear down a temporary MCS group, the GMC shall send an HTTP DELETE request with Request-URI with an XCAP URI identifying a group document of the temporary MCS group according to procedures specified in IETF RFC 4825 [22] "*Delete an Element*".

[TS 33.180, clause 7.3.2]

The group creation procedure is described in clause 10.2.3 of 3GPP TS 23.280 [36] and applies to the MCPTT scenario of normal group creation by an MC administrator and user regrouping operations by an authorized user/dispatcher. To establish the security context for the group, the GMS follows the procedures in clause 5.7 to create a new GMK and GMK-ID.

The encapsulated GMK and GUK-ID is sent to group members by the GMS within a notification message (step 4 in clause 10.2.3 of 3GPP TS 23.280 [36]). The procedure is equivalent to that described in clause 5.7 of this specification.

5.2.3 Test description

5.2.3.1 Pre-test conditions

Same pre-test conditions as for MCPTT test case 5.2 (TS 37.579-2 [24]) with the following exception(s):

- The term "MCPTT" is replaced with "MCData"

5.2.3.2 Test procedure sequence

Same test procedure sequence as for MCPTT test case 5.2 (TS 37.579-2 [24]) with the following exception(s):

- The term "MCPTT" is replaced with "MCData"

5.2.3.3 Specific message contents

Same specific message contents as for MCPTT test case 5.2 (TS 37.579-2 [24]) with the following exception(s):

- The term "MCPTT" is replaced with "MCData"
- Condition MCDATA is used for all messages.

5.3 Configuration / Group Affiliation / Remote change / De-affiliation / Home MCData system

5.3.1 Test Purpose (TP)

(1)

```
with { UE (MCData Client) already provisioned with the group information or a pointer to the group
information, that the UE (MCData Client) is allowed to be affiliated }
ensure that {
  when { MCData User requests for current affiliation status and to subscribe to affiliation status
changes for the MCData User }
    then { UE (MCData Client) requests to subscribe to affiliation status changes for the MCData
User by sending the SS (MCData Server) a SIP SUBSCRIBE message and starts informing the MCData User
of any affiliation status changes for the MCData User after the subscription is accepted }
            }
```

(2)

```
with { UE (MCData Client) already provisioned with the group information or a pointer to the group
information, that the UE (MCData Client) is allowed to be affiliated }
ensure that {
  when { MCData User requests to affiliate to an MCData group }
    then { UE (MCData Client) requests to affiliate to a MCData group by sending the SS (MCData
Server) a SIP PUBLISH message }
            }
```

(3)

```
with { UE (MCData Client) already provisioned with the group information or a pointer to the group
information, that the UE (MCData Client) is allowed to be affiliated }
ensure that {
  when { MCData User requests for current affiliation status and to subscribe to affiliation status
changes for a target user }
    then { UE (MCData Client) requests to subscribe to affiliation status changes for the target
user by sending the SS (MCData Server) a SIP SUBSCRIBE message and starts informing the MCData User
of any affiliation status changes for the target user after the subscription is accepted }
            }
```

(4)

```
with { UE (MCData Client) already provisioned with the group information or a pointer to the group
information that the UE (MCData Client) is allowed to make affiliation changes for another user }
ensure that {
  when { MCData User requests that a target user be affiliated to an MCData group via mandatory mode
}
    then { UE (MCData Client) requests that a target user be affiliated to an MCData group via
mandatory mode by sending the SS (MCData Server) a SIP PUBLISH message }
            }
```

(5)

```
with { UE (MCData Client) already provisioned with the group information or a pointer to the group
information that the UE (MCData Client) is allowed to make affiliation changes for another user }
ensure that {
  when { MCData User requests that a target user be de-affiliated to an MCData group via mandatory
mode }
    then { UE (MCData Client) requests that a target user be de-affiliated to an MCData group via
mandatory mode by sending the SS (MCData Server) a SIP PUBLISH message }
            }
```

(6)

```
with { UE (MCData Client) already provisioned with the group information or a pointer to the group
information that the UE (MCData Client) is allowed to make affiliation changes for another user }
ensure that {
  when { MCData User requests that a target user be affiliated to an MCData group via negotiated
mode }
    then { UE (MCData Client) requests that a target user be affiliated to an MCData group via
negotiated mode by sending the SS (MCData Server) a SIP MESSAGE message }
            }
```

(7)

```
with { UE (MCData Client) already provisioned with the group information or a pointer to the group
information, that the UE (MCData Client) is allowed to be affiliated }
ensure that {
  when { MCData User requests to de-subscribe to affiliation status changes for a target user }
    then { UE (MCData Client) requests to de-subscribe to affiliation status changes for a target
user by sending the SS (MCData Server) a SIP SUBSCRIBE message }
            }
```

(8)

```
with { UE (MCData Client) already affiliated with a MCData group }
ensure that {
  when { MCData User requests to de-affiliate from an MCData group }
    then { UE (MCData Client) requests to de-affiliate from an MCData group by sending the SS
(MCData Server) a SIP PUBLISH message }
            }
```

(9)

```
with { UE (MCData Client) already provisioned with the group information or a pointer to the group
information, that the UE (MCData Client) is allowed to be affiliated }
ensure that {
  when { MCData Server requests that the MCData User choose to affiliate to an MCData group via
negotiated mode by sending a SIP MESSAGE message }
    then { UE (MCData Client) accepts to affiliate to a MCData group by sending the SS (MCData
Server) a SIP PUBLISH message }
            }
```

5.3.2 Conformance requirements

References: The conformance requirements covered in the current TC are specified in: TS 24.282, clauses 8.2.2, 8.2.3, 8.2.4, and 8.2.5. The following represents a copy/paste extraction of the requirements relevant to the test purpose; any references within the copy/paste text should be understood within the scope of the core spec they have been copied from. Unless otherwise stated, these are Rel-14 requirements.

[TS 24.282, clause 8.2.2]

In order:

- to indicate that an MCData user is interested in one or more MCData group(s) at an MCData client;
- to indicate that the MCData user is no longer interested in one or more MCData group(s) at the MCData client;
- to refresh indication of an MCData user interest in one or more MCData group(s) at an MCData client due to near expiration of the expiration time of an MCData group with the affiliation status set to the "affiliated" state received in a SIP NOTIFY request in subclause 8.2.3;

- to send an affiliation status change request in mandatory mode to another MCData user; or
- any combination of the above;

the MCData client shall generate a SIP PUBLISH request according to 3GPP TS 24.229 [5], IETF RFC 3903 [34], and IETF RFC 3856 [39].

In the SIP PUBLISH request, the MCData client:

1) shall set the Request-URI to the public service identity identifying the originating participating MCData function serving the MCData user;
2) shall include an application/vnd.3gpp.mcdata-info+xml MIME body. In the application/vnd.3gpp.mcdata-info+xml MIME body, the MCData client shall include the <mcdata-request-uri> element set to the MCData ID of the MCData user;
3) shall include the ICSI value "urn:urn-7:3gpp-service.ims.icsi.mcdata" (coded as specified in 3GPP TS 24.229 [5]), in a P-Preferred-Service header field according to IETF RFC 6050 [7];
4) if the targeted MCData user is interested in at least one MCData group at the targeted MCData client, shall set the Expires header field according to IETF RFC 3903 [34], to 4294967295;

NOTE 1: 4294967295, which is equal to 2^{32}-1, is the highest value defined for Expires header field in IETF RFC 3261 [4].

5) if the targeted MCData user is no longer interested in any MCData group at the targeted MCData client, shall set the Expires header field according to IETF RFC 3903 [34], to zero; and
6) shall include an application/pidf+xml MIME body indicating per-user affiliation information according to subclause 8.4.1. In the MIME body, the MCData client:
   a) shall include all MCData groups where the targeted MCData user indicates its interest at the targeted MCData client;
   b) shall include the MCData client ID of the targeted MCData client;
   c) shall not include the "status" attribute and the "expires" attribute in the <affiliation> element; and
   d) shall set the <p-id> child element of the <presence> root element to a globally unique value.

The MCData client shall send the SIP PUBLISH request according to 3GPP TS 24.229 [5].

[TS 24.282, clause 8.2.3]

NOTE 1: The MCData UE also uses this procedure to determine which MCData groups the MCData user successfully affiliated to.

In order to discover MCData groups:

1) which the MCData user at an MCData client is affiliated to; or
2) which another MCData user is affiliated to;

the MCData client shall generate an initial SIP SUBSCRIBE request according to 3GPP TS 24.229 [5], IETF RFC 3856 [39], and IETF RFC 6665 [36].

In the SIP SUBSCRIBE request, the MCData client:

1) shall set the Request-URI to the public service identity identifying the originating participating MCData function serving the MCData user;
2) shall include an application/vnd.3gpp.mcdata-info+xml MIME body. In the application/vnd.3gpp.mcdata-info+xml MIME body, the MCData client shall include the <mcdata-request-uri> element set to the MCData ID of the targeted MCData user;
3) shall include the ICSI value "urn:urn-7:3gpp-service.ims.icsi.mcdata" (coded as specified in 3GPP TS 24.229 [5]), in a P-Preferred-Service header field according to IETF RFC 6050 [7];

4) if the MCData client wants to receive the current status and later notification, shall set the Expires header field according to IETF RFC 6665 [36], to 4294967295;

NOTE 2: 4294967295, which is equal to 2^{32}-1, is the highest value defined for Expires header field in IETF RFC 3261 [4].

5) if the MCData client wants to fetch the current state only, shall set the Expires header field according to IETF RFC 6665 [36], to zero; and

6) shall include an Accept header field containing the application/pidf+xml MIME type; and

7) if requesting MCData groups where the MCData user is affiliated to at the MCData client, shall include an application/simple-filter+xml MIME body indicating per-client restrictions of presence event package notification information according to subclause 8.4.2, indicating the MCData client ID of the MCData client.

In order to re-subscribe or de-subscribe, the MCData client shall generate an in-dialog SIP SUBSCRIBE request according to 3GPP TS 24.229 [5], IETF RFC 3856 [39], and IETF RFC 6665 [36]. In the SIP SUBSCRIBE request, the MCData client:

1) if the MCData client wants to receive the current status and later notification, shall set the Expires header field according to IETF RFC 6665 [36], to 4294967295;

NOTE 3: 4294967295, which is equal to 2^{32}-1, is the highest value defined for Expires header field in IETF RFC 3261 [4].

2) if the MCData client wants to de-subscribe, shall set the Expires header field according to IETF RFC 6665 [36], to zero; and

3) shall include an Accept header field containing the application/pidf+xml MIME type.

Upon receiving a SIP NOTIFY request according to 3GPP TS 24.229 [5], IETF RFC 3856 [39], and IETF RFC 6665 [36], if SIP NOTIFY request contains an application/pidf+xml MIME body indicating per-user affiliation information constructed according to subclause 8.4.1, then the MCData client shall determine affiliation status of the MCData user for each MCData group at the MCData client(s) in the MIME body. If the <p-id> child element of the <presence> root element of the application/pidf+xml MIME body of the SIP NOTIFY request is included, the <p-id> element value indicates the SIP PUBLISH request which triggered sending of the SIP NOTIFY request.

[TS 24.282, clause 8.2.4]

NOTE: Procedure for sending affiliation status change request in negotiated mode to several target MCData users is not supported in this version of the specification.

Upon receiving a request from the MCData user to send an affiliation status change request in negotiated mode to a target MCData user, the MCData client shall generate a SIP MESSAGE request in accordance with 3GPP TS 24.229 [5] and IETF RFC 3428 [6]. In the SIP MESSAGE request, the MCData client:

1) shall set the Request-URI to the public service identity identifying the originating participating MCData function serving the MCData user;

2) shall include an application/vnd.3gpp.mcdata-info+xml MIME body. In the application/vnd.3gpp.mcdata-info+xml MIME body, the MCData client shall include the <mcdata-request-uri> element set to the MCData ID of the target MCData user;

3) shall include the ICSI value "urn:urn-7:3gpp-service.ims.icsi.mcdata" (coded as specified in 3GPP TS 24.229 [5]), in a P-Preferred-Service header field according to IETF RFC 6050 [7] in the SIP MESSAGE request;

4) shall include an application/vnd.3gpp.mcdata-affiliation-command+xml MIME body as specified in Annex D.3; and

5) shall send the SIP MESSAGE request according to rules and procedures of 3GPP TS 24.229 [5].

On receiving a SIP 2xx response to the SIP MESSAGE request, the MCData client shall indicate to the user that the request has been delivered to an MCData client of the target MCData user.

[TS 24.282, clause 8.2.5]

Upon receiving a SIP MESSAGE request containing:

1) the ICSI value "urn:urn-7:3gpp-service.ims.icsi.mcdata" (coded as specified in 3GPP TS 24.229 [5]), in a P-Asserted-Service header field according to IETF RFC 6050 [7]; and

2) an application/vnd.3gpp.mcdata-affiliation-command+xml MIME body with a list of MCData groups for affiliation under the <affiliate> element and a list of MCData groups for de-affiliation under the <de-affiliate> element;

then the MCData client:

1) shall send a 200 (OK) response to the SIP MESSAGE request;

2) shall seek confirmation of the list of MCData groups for affiliation and the list of MCData groups for de-affiliation, resulting in an accepted list of MCData groups for affiliation and an accepted list of MCData groups for de-affiliation; and

3) if the user accepts the request:

   a) shall perform affiliation for each entry in the accepted list of MCData groups for affiliation for which the MCData client is not affiliated, as specified in subclause 8.2.2; and

   b) shall perform de-affiliation for each entry in the accepted list of MCData groups for de-affiliation for which the MCData client is affiliated, as specified in subclause 8.2.2.

5.3.3 Test description

5.3.3.1 Pre-test conditions

Same pre-test conditions as for MCPTT test case 5.3 (TS 37.579-2 [24]) with the following exception(s):

- The term "MCPTT" is replaced with "MCData"

5.3.3.2 Test procedure sequence

Same test procedure sequence as for MCPTT test case 5.3 (TS 37.579-2 [24]) with the following exception(s):

- The term "MCPTT" is replaced with "MCData"

5.3.3.3 Specific message contents

Same specific message contents as for MCPTT test case 5.3 (TS 37.579-2 [24]) with the following exception(s):

- The term "MCPTT" is replaced with "MCData"
- Condition MCDATA is used for all messages.

5.4 Configuration / Determination of MCData Service Settings / Current Active MCData Settings / De-subscribe

5.4.1 Test Purpose (TP)

(1)

```
with { UE (MCDATA Client) registered and authorised for MCDATA Service }
ensure that {
  when { MCData User requests to verify the currently active MCData service settings or to discover
MCData service settings }
    then { UE (MCData Client) sends a SIP SUBSCRIBE message to find the MCData service settings and
responds to the SIP NOTIFY message with a SIP 200 (OK) message }
            }
```

(2)

```
with { UE (MCDATA Client) having already subscribed to find the MCData service settings }
ensure that {
  when { MCData User requests to re-subscribe for MCData service settings }
    then { UE (MCData Client) sends a SIP SUBSCRIBE message to re-subscribe for the MCData service
settings and responds to the SIP NOTIFY message with a SIP 200 (OK) message }
           }
```

(3)

```
with { UE (MCDATA Client) having already subscribed to find the MCData service settings }
ensure that {
  when { MCData User requests to de-subscribe for MCData service settings }
    then { UE (MCData Client) sends a SIP SUBSCRIBE message to de-subscribe for the MCData service
settings and responds to the SIP NOTIFY message with a SIP 200 (OK) message }
           }
```

5.4.2 Conformance requirements

References: The conformance requirements covered in the present TC are specified in: TS 24.282 clause 7.2.4. The following represents a copy/paste extraction of the requirements relevant to the test purpose; any references within the copy/paste text should be understood within the scope of the core spec they have been copied from. Unless otherwise stated these are Rel-14 requirements.

[TS 24.282, clause 7.2.4]

In order to discover MCData service settings of another MCData client of the same MCData user or to verify the currently active MCData service settings of this MCData client, the MCData client shall generate an initial SIP SUBSCRIBE request according to 3GPP TS 24.229 [5], IETF RFC 6665 [36], and IETF RFC 4354 [35].

In the SIP SUBSCRIBE request, the MCData client:

1) shall set the Request-URI to the public service identity identifying the originating participating MCData function serving the MCData user;

2) shall include an application/vnd.3gpp.mcdata-info+xml MIME body. In the application/vnd.3gpp.mcdata-info+xml MIME body, the MCData client shall include the <mcdata-request-uri> element set to the MCData ID of the MCData user;

3) shall include the ICSI value "urn:urn-7:3gpp-service.ims.icsi.mcdata" (coded as specified in 3GPP TS 24.229 [5]), in a P-Preferred-Service header field according to IETF RFC 6050 [7];

4) shall set the Event header field to the 'poc-settings' value;

5) shall include an Accept header field containing the "application/poc-settings+xml" MIME type;

6) if the MCData client wants to receive the current status and later notification, shall set the Expires header field according to IETF RFC 6665 [36], to 4294967295; and

NOTE 1: 4294967295, which is equal to 2^{32}-1, is the highest value defined for Expires header field in IETF RFC 3261 [4].

7) if the MCData client wants to fetch the current state only, shall set the Expires header field according to IETF RFC 6665 [36], to zero.

In order to re-subscribe or de-subscribe, the MCData client shall generate an in-dialog SIP SUBSCRIBE request according to 3GPP TS 24.229 [5], IETF RFC 6665 [36], IETF RFC 4354 [35]. In the SIP SUBSCRIBE request, the MCData client:

1) shall set the Event header field to the 'poc-settings' value;

2) shall include an Accept header field containing the "application/poc-settings+xml" MIME type;

3) if the MCData client wants to receive the current status and later notification, shall set the Expires header field according to IETF RFC 6665 [36], to 4294967295; and

NOTE 2: 4294967295, which is equal to 2^{32}-1, is the highest value defined for Expires header field in IETF RFC 3261 [4].

4) if the MCData client wants to de-subscribe, shall set the Expires header field according to IETF RFC 6665 [36], to zero.

Upon receiving a SIP NOTIFY request according to 3GPP TS 24.229 [5], IETF RFC 6665 [36] and IETF RFC 4354 [35], that contains an application/poc-settings+xml MIME body the MCData client shall cache:

1) the <am-settings> element of the poc-settings+xml MIME body for each MCData client identified by the "id" attribute according to IETF RFC 4354 [35] as the current Answer-mode indication of that MPCTT client; and

2) the <selected-user-profile-index> element of the poc-settings+xml MIME body for each MCData client identified by the "id" attribute according to IETF RFC 4354 [35] as the active MCData user profile of that MCData client.

5.4.3 Test description

5.4.3.1 Pre-test conditions

Same pre-test conditions as for MCPTT test case 5.5 (TS 37.579-2 [24]) with the following exception(s):

- The term "MCPTT" is replaced with "MCData"

5.4.3.2 Test procedure sequence

Same test procedure sequence as for MCPTT test case 5.5 (TS 37.579-2 [24]) with the following exception(s):

- The term "MCPTT" is replaced with "MCData"

5.4.3.3 Specific message contents

Same specific message contents as for MCPTT test case 5.5 (TS 37.579-2 [24]) with the following exception(s):

- The term "MCPTT" is replaced with "MCData"
- Condition MCDATA is used for all messages.

5.5 Configuration / Pre-established Session Establishment / Pre-established Session Release

5.5.5 Test Purpose (TP)

(1)

```
with { UE (MCData client) registered and authorized for MCData Service }
ensure that {
  when { MCData User requests the creation of a pre-established session }
    then { UE (MCData client) requests the creation of a pre-establish session by sending a SIP
INVITE message }
            }
```

(2)

```
with { the MCData client already having a pre-stablished session created }
ensure that {
  when { MCData User requests the release of a pre-established session }
    then { UE (MCData client) requests the release of a pre-establish session by sending a SIP BYE
message }
            }
```

(3)

```
with { the MCData client already having a pre-stablished session created }
ensure that {
  when { MCData Server requests the release of a pre-established session by sending a SIP BYE
message }
    then { UE (MCData client) responds to the pre-established session release request by sending a
SIP 200 (OK) message }
            }
```

5.5.2 Conformance requirements

References: The conformance requirements covered in the current TC are specified in: TS 24.282, clauses 18.3.2.1, 18.3.3.1.1, 18.3.3.1.2. Unless otherwise stated, these are Rel-13 requirements.

[TS 24.282, clause 18.3.2.1]

When the MCData client initiates a pre-established session the MCData client shall:

1) gather ICE candidates according to IETF RFC 5245 [50]; and

NOTE: ICE candidates are only gathered on interfaces that the MCData UE uses to obtain MCData service.

2) generate an initial SIP INVITE request by following the UE originating session procedures specified in 3GPP TS 24.229 [5], with the clarifications given below.

The MCData client:

1) shall set the Request-URI of the SIP INVITE request to the public service identity of the participating MCData function serving the MCData user;

2) may include a P-Preferred-Identity header field in the SIP INVITE request containing a public user identity as specified in 3GPP TS 24.229 [5];

3) shall include the g.3gpp.mcdata.sds media feature tag in the Contact header field of the SIP INVITE request according to IETF RFC 3840 [16];

4) shall include an Accept-Contact header field with the media feature tag g.3gpp.mcdata.sds along with parameters "require" and "explicit" according to IETF RFC 3841 [8];

5) shall include the ICSI value "urn:urn-7:3gpp-service.ims.icsi.mcdata.sds" (coded as specified in 3GPP TS 24.229 [5]), in a P-Preferred-Service header field according to IETF RFC 6050 [7] in the SIP INVITE request;

6) shall include an Accept-Contact header field with the media feature tag g.3gpp.icsi-ref set to the value "urn:urn-7:3gpp-service.ims.icsi.mcdata.sds" along with parameters "require" and "explicit" according to IETF RFC 3841 [8];

7) shall include the "timer" option tag in the Supported header field;

8) should include the Session-Expires header field according to IETF RFC 4028 [38] and should not include the "refresher" header field. The "refresher" header field parameter shall be set to "uac" if included;

9) shall include in the application/vnd.3gpp.mcdata-info+xml MIME body with the <mcdataInfo> element containing the <mcdata-Params> element with the <anyExt> element an <pre-established-session-ind> element set to a value of "true";

10) shall include an SDP offer according to 3GPP TS 24.229 [5] with the clarifications given in subclause 18.3.1.1, and include ICE candidates in the SDP offer as per IETF RFC 5245 [50]; and

11) shall send the SIP INVITE request according to 3GPP TS 24.229 [5].

Upon receiving a SIP 2xx response to the SIP INVITE request the MCData client:

1) shall interact with the media plane as specified in 3GPP TS 24.582 [15].

[TS 24.282, clause 18.3.3.1.1]

NOTE: The MCData client needs to be prepared to release the pre-established session when receiving a SIP BYE request generated by the SIP core (e.g. due to network release of media plane resources).

When a MCData client needs to release a pre-established session as created in subclause 18.3.2, the MCData client shall perform the procedure as described in subclause 13.2.2.2.2.1.

[TS 24.282, clause 18.3.3.1.2

Upon receiving a SIP BYE request from the participating MCData function within a pre-established session the MCData client shall check whether there are any MCData sessions using the pre-established session, and:

1) if there is an established MCData session then the MCData client shall remove the MCData client from the MCData session by performing the procedures for session release for each MCData session as specified in 3GPP TS 24.582 [15]; and

2) if there is no MCData session using the pre-established session, then the MCData client shall follow the procedure described in subclause 13.2.3.2.2.

5.5.3 Test description

5.5.3.1 Pre-test conditions

Test configuration:

- Single cell configuration according to TS 37.579-1 [2] clause 5.2.2.2.1.

Preamble:

- The UE has performed procedure 'Initial registration' as described in TS 37.579-1 [2] clause 5.4.2.
- UE States at the end of the preamble:
  - The UE is in RRC_IDLE state.
  - The client is registered for MCData.

5.5.3.2 Test procedure sequence

Table 5.5.3.2-1: Main Behaviour

St	Procedure	Message Sequence		TP	Verdict
		U - S	Message		
1	Make the UE (MCData client) initiate establishment of a pre-established session for MCData SDS communication. (NOTE 1)	-	-	-	-
2	Check: Does the UE (MCData client) correctly perform procedure 'MCX pre-established session establishment' as described in TS 37.579-1 [2] Table 5.3.3.3-1 to create a pre-established session?	-	-	1	P
3	Make the UE (MCData client) release the pre-established session. (NOTE 1)	-	-	-	-
4	Check: Does the UE (MCData client) correctly perform procedure 'MCX CO call release' as described in TS 37.579-1 [2] Table 5.3.10.3-1 to release the pre-established session?	-	-	2	P
5	Make the UE (MCData client) initiate establishment of a pre-established session for MCData SDS communication. (NOTE 1)	-	-	-	-
6	Procedure 'MCX pre-established session establishment' as described in TS 37.579-1 [2] Table 5.3.3.3-1 is performed to create a pre-established session.	-	-	-	-
7	Check: Does the UE (MCData client) correctly perform procedure 'MCX CT call release' as described in TS 37.579-1 [2] Table 5.3.12.3-1 to release the pre-established session?	-	-	3	P
NOTE 1: This is expected to be done via a suitable implementation dependent MMI.					

5.5.3.3 Specific message contents

Table 5.5.3.3-1: SIP BYE from the UE (step 4, Table 5.5.3.2-1; step 1, TS 37.579-1 [2] Table 5.3.10.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.2.1-1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Request-Line				
Request-URI	tsc_MCX_SessionID_B	The URI that identifies the pre-established session		

Table 5.5.3.3-2: SIP BYE from the SS (step 7, Table 5.5.3.2-1; step 1, TS 37.579-1 [2] Table 5.3.12.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.2.2-1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Request-Line				
Request-URI	tsc_MCX_SessionID_B	The URI that identifies the pre-established session		

5.6 Configuration / Download CSK

5.6.1 Test Purpose (TP)

(1)

```
with { UE (MCData Client) registered and authorised for MCData Service }
ensure that {
  when { MCData Client receives a CSK key download message via a SIP MESSAGE message }
    then { UE (MCData Client) responds with a SIP 200 (OK) message and replaces the existing CSK and
CSK-ID associated with the participating MCData function and uses the new CSK information with a SIP
MESSAGE message when prompted to initiate a call }
            }
```

(2)

```
with { UE (MCDATA Client) having sent a standalone one-to-one SDS message }
ensure that {
  when { UE (MCDATA Client receives a disposition response via a SIP MESSAGE message from the SS
(MCDATA Server) }
    then { UE (MCDATA Client) responds to the SIP MESSAGE message by sending a SIP 200 (OK) message
and delivers the notification to the MCDATA User }
            }
```

5.6.2 Conformance requirements

References: The conformance requirements covered in the present TC are specified in: TS 24.282 clause 7.2.5, TS 33.180 clause 9.2.1.4, TS 24.582 clause 10.1. Unless otherwise stated these are Rel-16 requirements.

[TS 24.282, clause 7.2.5]

When the MCData client receives a SIP MESSAGE request containing:

1) a P-Asserted-Service header field containing the "urn:urn-7:3gpp-service.ims.icsi.mcdata"; and

2) an application/mikey MIME body;

Then, if the key identifier within the CSB-ID of the MIKEY payload is a CSK-ID (4 most-significant bits have the value '2'), the MCData client:

1) shall follow the security procedures in subclause 9.2.1 of 3GPP TS 33.180 [26] to extract the CSK. The client:

   a) if the initiator field (IDRi) has type 'URI' (identity hiding is not used), the client:

      i) shall extract the initiator URI from the initiator field (IDRi) of the I_MESSAGE as described in 3GPP TS 33.180 [26]. If the initiator URI deviates from the public service identity of the participating MCData function serving the MCData user, shall reject the SIP MESSAGE request with a SIP 488 (Not Acceptable Here) response as specified in IETF RFC 4567 [45], and include warning text set to "136 authentication of the MIKEY-SAKKE I_MESSAGE failed" in a Warning header field as specified in subclause 4.9.2 and shall not continue with the rest of the steps; and

      ii) shall convert the initiator URI to a UID as described in 3GPP TS 33.180 [26];

   b) if the initiator field (IDRi) has type 'UID' (identity hiding in use), the client:

      i) shall convert the public service identity of participating MCData function serving the MCData user to a UID as described in 3GPP TS 33.180 [26]; and

      ii) shall compare the generated UID with the UID in the initiator field (IDRi) of the I_MESSAGE as described in 3GPP TS 33.180 [26]. If the two initiator UIDs deviate from each other, shall reject the SIP MESSAGE request with a SIP 488 (Not Acceptable Here) response as specified in IETF RFC 4567 [45], and include warning text set to "136 authentication of the MIKEY-SAKKE I_MESSAGE failed" in a Warning header field as specified in subclause 4.9.2 and shall not continue with the rest of the steps;

   c) shall use the UID to validate the signature of the I_MESSAGE as described in 3GPP TS 33.180 [26];

d) if authentication verification of the I_MESSAGE fails, shall reject the SIP MESSAGE request with a SIP 488 (Not Acceptable Here) response as specified in IETF RFC 4567 [45], and include warning text set to "136 authentication of the MIKEY-SAKKE I_MESSAGE failed" in a Warning header field as specified in subclause 4.4 and shall not continue with the rest of the steps;

e) shall extract and decrypt the encapsulated CSK using the participating MCData function's (KMS provisioned) UID key as described in 3GPP TS 33.180 [26];

f) shall extract and store the algorithm to be used to protect the MCData signalling fields; and

g) shall extract the CSK-ID, from the payload as specified in 3GPP TS 33.180 [26]; and

2) Upon successful extraction, the client shall replace the existing CSK and CSK-ID associated with the participating MCData function, with the extracted CSK and CSK-ID in the 'key download' message.

[TS 33.180, clause 9.2.1.4]

The MCX Server may decide to update an existing CSK at any time. This may be due to CSK revocation or expiry.

The CSK shall be updated by the MCX Server using the 'key download' procedure, defined in clause 5.8. Upon receipt of a CSK via a 'key download' procedure, the MC client shall identify the type of key as a CSK via the 4 most significant bits of the CSK-ID. The MC client shall:

- discard any previous CSKs associated with the MC Server FQDN, and
- use the new CSK for uplink signalling with the MC Server.

[TS 24.582, clause 10.1]

Media plane security provides integrity and confidentiality protection for the MCData media information and media plane control information transmitted using media plane. Media plane security also provides the authentication of MCData media information.

The media plane security is based on 3GPP MCData security solution including key management as defined in 3GPP TS 33.180 [15].

NOTE: In 3GPP TS 33.180 [15] media information is denoted as MCData Data Payload and media plane control information is denoted as MCData Data signalling Payload.

Various keys and associated key identifiers protect the media information and media plane control information carried in the body of an MSRP SEND message.

The media plane control information may be:

1. SDS SIGNALLING PAYLOAD; or
2. SDS NOTIFICATION.

The media information may be:

1. DATA PAYLOAD; or
2. File or file portion.

In an on-network MCData communication for an MCData group, if protection of media is negotiated, the GMK and the GMK-ID of the MCData group shall be used for protecting the media sent and received by MCData clients.

In an on-network one-to-one MCData communication, if protection of media is negotiated, the PCK and the PCK-ID shall be used for protecting the media sent and received by MCData clients.

If protection of media control information sent using unicast between the MCData client and the participating MCData function serving the MCData client is negotiated, the CSK and the CSK-ID shall be used for protecting the media control information sent and received using unicast by the MCData client and by a participating MCData function.

If protection of media control information between the participating MCData function and the controlling MCData function is configured, the SPK and the SPK-ID shall be used for protecting the media control information sent and received between the participating MCData function and the controlling MCData function.

The GMK and the GMK-ID are distributed to the MCData clients using the group document subscription and notification procedure specified in 3GPP TS 24.481 [4].

The PCK and the PCK-ID are generated by the MCData client initiating the standalone one-to-one SDS using media plane or one-to-one SDS session or one-to-one FD using media plane and provided to the MCData client receiving the SIP signalling according to 3GPP TS 24.282 [8].

The CSK and the CSK-ID are generated by the MCData client and provided to the participating MCData function serving the MCData client using SIP signalling according to 3GPP TS 24.282 [8].

The SPK and the SPK-ID are configured in the participating MCData function and the controlling MCData function.

The key material for creating and verifying the authentication signature (SSK, PVT and KPAK) is provisioned to the MCData clients by the KMS as specified in 3GPP TS 33.180 [15].

5.6.3 Test description

5.6.3.1 Pre-test conditions

Test configuration:

- Single cell configuration according to TS 37.579-1 [2] clause 5.2.2.2.1.

Preamble:

- The UE has performed procedure 'Initial registration' as described in TS 37.579-1 [2] clause 5.4.2.
- UE States at the end of the preamble:
  - The UE is in RRC_IDLE state.
  - The client is registered for MCData.

5.6.3.2 Test procedure sequence

Table 5.6.3.2-1: Main Behaviour

St	Procedure	Message Sequence		TP	Verdict
		U - S	Message		
1	Check: Does the UE (MCData client) correctly perform procedure 'MCX SIP MESSAGE CT' as described in TS 37.579-1 [2] Table 5.3.33.3-1 requesting to update the existing CSK?.	-	-	1	P
2	Make the UE (MCData client) send a standalone one-to-one SDS message with disposition request "DELIVERY". (NOTE 1)	-	-	-	-
3-5	Check: Does the UE (MCData client) correctly perform steps 1a1-3 of procedure 'CO SDS or FD message transfer using signalling plane' as described in TS 37.579-1 [2] Table 5.3C.1.3-1 to send a standalone one-to-one SDS message with disposition request "DELIVERY"? (NOTE 2)	-	-	1	P
6	Check: Does the UE (MCData client) correctly perform procedure 'MCX SIP MESSAGE CT' as described in TS 37.579-1 [2] Table 5.3.33.3-1 to receive the disposition notification for the SDS message sent at step 4?	-	-	2	P
7	Check: Does the UE (MCData client) provide the disposition notification to the user? (NOTE 1)	-	-	2	P
NOTE 1: This is expected to be done via a suitable implementation dependent MMI. NOTE 2: The RRC connection is not released at the end of the procedure.					

5.6.3.3 Specific message contents

Table 5.6.3.3-1: SIP MESSAGE from the SS (step 1, Table 5.6.3.2-1; step 2, TS 37.579-1 [2] Table 5.3.33.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.7.2-2				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
P-Asserted-Service			TS 24.282 [31] clause 7.3.7	
Service-ID	"urn:urn-7:3gpp-service.ims.icsi.mcdata"			
Content-Type				
media-type	"application/mikey"			
Message-body				
MIKEY message	base64 encoded MIKEY message as described in TS 37.579-1 [2], Table 5.5.9.1-1A	MIKEY message, containing the updated CSK		

Table 5.6.3.3-2: SIP MESSAGE from the UE (step 4, Table 5.6.3.2-1; step 2, TS 37.579-1 [2] Table 5.3C.1.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.7.1-1, condition MCDATA_SDS, RESOURCE_LISTS, MIKEY, MCDATA_SIGNALLING, MCDATA_PAYLOAD				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part		**MCData-Info**		
MIME-part-body	MCData-Info as described in Table 5.6.3.3-3			
MIME body part		**MCData Data signalling message**		
MIME-part-body	MCData Protected Payload Message containing SDS SIGNALLING PAYLOAD as described in Table 5.6.3.3-4			
MIME body part		**MCData Data message**		
MIME-part-body	DATA PAYLOAD as described in Table 5.6.3.3-5			

Table 5.6.3.3-3: MCData-Info (Table 5.6.3.3-2)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.2.1-3, condition MCD_1to1

Table 5.6.3.3-4: SDS SIGNALLING PAYLOAD (Table 5.6.3.3-2)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.1-1, condition DELIVERED

Table 5.6.3.3-5: DATA PAYLOAD (Table 5.6.3.3-2)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.9.2-1

Table 5.6.3.3-6: SIP MESSAGE from the SS (step 6, Table 5.6.3.2-1; step 2, TS 37.579-1 [2] Table 5.3.33.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.7.2-1, condition MCDATA_SDS, MCDATA_SIGNALLING				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part		**MCData Data signalling message**		
MIME-part-body	MCData Protected Payload Message containing SDS NOTIFICATION as described in Table 5.6.3.3-7			

Table 5.6.3.3-7: SDS NOTIFICATION (Table 5.6.3.3-6)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.4-1, condition DELIVERED

5.7 Configuration / Functional Alias / Functional alias status determination / Activate functional alias / Deactivate functional alias

5.7.1 Test Purpose (TP)

(1)

```
with { UE (MCData Client) registered and authorised for MCData Service }
ensure that {
  when { MCData User requests to determine the current status of a functional alias and later
notification of status changes of a functional alias }
    then { UE (MCData Client) sends a SIP SUBSCRIBE message to determine the current status of a
functional alias and later notification of status changes of a functional alias and responds to the
SIP NOTIFY message with a SIP 200 (OK) message }
            }
```

(2)

```
with { UE (MCData Client) having already subscribed to determine the status of a functional alias }
ensure that {
  when { MCData User requests to activate a functional alias }
    then { UE (MCData Client) sends a SIP PUBLISH message to activate a functional alias and
responds to the SIP NOTIFY message with a SIP 200 (OK) message }
            }
```

(3)

```
with { UE (MCData Client) having already subscribed to determine the status of a functional alias }
ensure that {
  when { MCData User requests to deactivate a functional alias }
    then { UE (MCData Client) sends a SIP PUBLISH message to deactivate a functional alias and
responds to the SIP NOTIFY message with a SIP 200 (OK) message }
            }
```

(4)

```
with { UE (MCData Client) having already subscribed to determine the status of a functional alias }
ensure that {
  when { MCData User requests to de-subscribe from determining the status of a functional alias }
    then { UE (MCData Client) sends a SIP SUBSCRIBE message to de-subscribe from determining the
status of a functional alias and responds to the SIP NOTIFY message with a SIP 200 (OK) message }
            }
```

5.7.2 Conformance requirements

References: The conformance requirements covered in the present TC are specified in: TS 24.282 clause 22.2.1.2, 22.2.1.3. Unless otherwise stated these are Rel-16 requirements.

[TS 24.282, clause 22.2.1.2]

In order:

- to indicate that an MCData user requests to activate one or more functional aliases;
- to indicate that the MCData user requests to deactivate one or more functional aliases;
- to refresh indication of an MCData user interest in one or more functional aliases due to near expiration of the expiration time of a functional alias with the status set to the "activated" state received in a SIP NOTIFY request in subclause 22.2.1.3;
- to indicate that the MCData client entering into or exiting from a location area triggers one or more functional aliases to be activated;
- to indicate that the MCData client entering into or exiting from a location area triggers one or more functional aliases to be deactivated; or

- any combination of the above;

the MCData client shall generate a SIP PUBLISH request according to TS 24.229 [5], IETF RFC 3903 [34], and IETF RFC 3856 [39].

When the MCData user requests to deactivate a functional alias, the MCData client shall first check the <manual-deactivation-not-allowed-if-location-criteria-met> element within the <anyExt> element of the <entry> element corresponding to the functional alias within the <FunctionalAliasList> list element of the <anyExt> element of the <OnNetwork> element of the MCData user profile document (see the MCData user profile document in TS 24.484 [12]). If the functional alias has been activated due to a location area trigger and the <manual-deactivation-not-allowed-if-location-criteria-met> element is set to a value of "true", the MCData client shall suppress the MCData user's request.

NOTE 1: If the request is suppressed, a notification message can be displayed to the user.

In the SIP PUBLISH request, the MCData client:

1) shall set the Request-URI to the public service identity identifying the originating participating MCData function serving the MCData user;

2) shall include an application/vnd.3gpp.mcdata-info+xml MIME body. In the application/vnd.3gpp.mcdata-info+xml MIME body, the MCData client shall include the <mcdata-request-uri> element set to the MCData ID of the MCData user;

3) shall include the ICSI value "urn:urn-7:3gpp-service.ims.icsi.mcdata" (coded as specified in TS 24.229 [5]), in a P-Preferred-Service header field according to IETF RFC 6050 [7];

4) if the MCData client requests to activate one or more functional aliases, shall set the Expires header field according to IETF RFC 3903 [34], to 4294967295;

NOTE 2: 4294967295, which is equal to 2^{32}-1, is the highest value defined for Expires header field in IETF RFC 3261 [4].

5) if the MCData client requests to deactivate one or more functional aliases, shall set the Expires header field according to IETF RFC 3903 [34], to zero; and

NOTE 3: Activation and deactivation of functional alias cannot be performed with the same PUBLISH request.

6) shall include an application/pidf+xml MIME body indicating per-user functional alias information according to subclause 22.3.1. In the MIME body, the MCData client:

   a) shall include all functional aliases where the MCData user requests activation for the MCData ID;

   b) shall include the MCData client ID of the targeted MCData client;

   c) shall not include the "status" attribute and the "expires" attribute in the <functionalalias> element;

   d) if the MCData client has received an indication that take over of a functional alias is possible and intends to take over a functional alias, shall include a <take-over> child element set to "true"; and

   e) shall set the <p-id-fa> child element of the <presence> root element to a globally unique value.

The MCData client shall send the SIP PUBLISH request according to TS 24.229 [5].

[TS 24.282, clause 22.2.1.3]

NOTE 1: The MCData UE also uses this procedure to determine which functional alias have been successfully activated for the MCData ID.

In order to discover functional aliases:

1) which are activated for the MCData user; or

2) which another MCData user has activated;

the MCData client shall generate an initial SIP SUBSCRIBE request according to TS 24.229 [5], IETF RFC 3856 [39], and IETF RFC 6665 [36].

In the SIP SUBSCRIBE request, the MCData client:

1) shall set the Request-URI to the public service identity identifying the originating participating MCData function serving the MCData user;

2) shall include an application/vnd.3gpp.mcdata-info+xml MIME body. In the application/vnd.3gpp.mcdata-info+xml MIME body, the MCData client shall include:

   a) the <mcdata-request-uri> element set to the MCData ID of the targeted MCData user; and

   b) the <request-type> element in the <mcdata-Params> element of the <mcdatainfo> element set to the value "functional-alias-status-determination";

3) shall include the ICSI value "urn:urn-7:3gpp-service.ims.icsi.mcdata" (coded as specified in TS 24.229 [5]), in a P-Preferred-Service header field according to IETF RFC 6050 [7];

4) if the MCData client wants to receive the current status and later notification, shall set the Expires header field according to IETF RFC 6665 [36], to 4294967295;

NOTE 2: 4294967295, which is equal to 2^{32}-1, is the highest value defined for Expires header field in IETF RFC 3261 [4].

5) if the MCData client wants to fetch the current state only, shall set the Expires header field according to IETF RFC 6665 [36], to zero;

6) shall include an Events header field set to "presence"; and

7) shall include an Accept header field containing the application/pidf+xml MIME type.

In order to re-subscribe or de-subscribe, the MCData client shall generate an in-dialog SIP SUBSCRIBE request according to TS 24.229 [5], IETF RFC 3856 [39], and IETF RFC 6665 [36]. In the SIP SUBSCRIBE request, the MCData client:

1) if the MCData client wants to receive the current status and later notification, shall set the Expires header field according to IETF RFC 6665 [36], to 4294967295;

NOTE 3: 4294967295, which is equal to 2^{32}-1, is the highest value defined for Expires header field in IETF RFC 3261 [4].

2) if the MCData client wants to de-subscribe, shall set the Expires header field according to IETF RFC 6665 [36], to zero;

3) shall include an Events header field set to "presence"; and

4) shall include an Accept header field containing the application/pidf+xml MIME type.

Upon receiving a SIP NOTIFY request according to TS 24.229 [5], IETF RFC 3856 [39], and IETF RFC 6665 [36], if SIP NOTIFY request contains an application/pidf+xml MIME body indicating per-user functional alias information constructed according to subclause 22.3.1, then the MCData client shall determine the status of the MCData user for each functional alias in the MIME body. If the <p-id-fa> child element of the <presence> root element of the application/pidf+xml MIME body of the SIP NOTIFY request is included, the <p-id-fa> element value indicates the SIP PUBLISH request which triggered sending of the SIP NOTIFY request.

If the MCData client detected a functional alias activation or deactivation, it shall perform the procedure specified in subclause 8.2.6.

5.7.3 Test description

5.7.3.1 Pre-test conditions

Same pre-test conditions as for MCPTT test case 5.8 (TS 37.579-2 [24]) with the following exception(s):

- The term "MCPTT" is replaced with "MCData"

5.7.3.2 Test procedure sequence

Same test procedure sequence as for MCPTT test case 5.8 (TS 37.579-2 [24]) with the following exception(s):

- The term "MCPTT" is replaced with "MCData"

5.7.3.3 Specific message contents

Same specific message contents as for MCPTT test case 5.8 (TS 37.579-2 [24]) with the following exception(s):

- The term "MCPTT" is replaced with "MCData"
- Condition MCDATA is used for all messages.

5.8 Configuration / Rules based affiliation status change

5.8.1 Test Purpose (TP)

(1)

```
with { UE (MCData Client) registered and authorised for MCData Service }
ensure that {
  when { UE enters into or exits from a location area that triggers a group de-affiliation }
    then { UE (MCData Client) sends a SIP PUBLISH message to de-affiliate from a group }
           }
```

(2)

```
with { UE (MCData Client) registered and authorised for MCData Service }
ensure that {
  when { UE enters into or exits from a location area that triggers a group affiliation }
    then { UE (MCData Client) sends a SIP PUBLISH message to affiliate to a group }
           }
```

5.8.2 Conformance requirements

References: The conformance requirements covered in the present TC are specified in: TS 24.282 clause 8.2.6, 8.2.2. Unless otherwise stated these are Rel-16 requirements.

[TS 24.282, clause 8.2.6]

Rules based affiliation is controlled by the elements <RulesForAffiliation> or <RulesForDeaffiliation> of the MCData user profile document identified by the MCData ID of the MCData user (see the MCData user profile document specified in 3GPP TS 24.484 [50]). The rules can be composed of location criteria (including heading and speed) or functional alias based criteria. A rule is fulfilled if any of the location criteria and any of the functional alias based criteria are met. These rules are evaluated whenever a change of location occurs and whenever a functional alias is activated or deactivated. If any defined rule is fulfilled, the MCData client shall initiate the affiliation status change procedure as specified in subclause 8.2.2.

NOTE: Hysteresis can be applied to location changes to avoid too frequent affiliation changes. In addition, the definition of area entry and exit criteria can be specified to provide a buffer space to minimize ping-ponging into and out of an area.

[TS 24.282, clause 8.2.2]

In order:

- to indicate that an MCData user is interested in one or more MCData group(s) at an MCData client;
- to indicate that the MCData user is no longer interested in one or more MCData group(s) at the MCData client;
- to refresh indication of an MCData user interest in one or more MCData group(s) at an MCData client due to near expiration of the expiration time of an MCData group with the affiliation status set to the "affiliated" state received in a SIP NOTIFY request in subclause 8.2.3;

- to send an affiliation status change request in mandatory mode to another MCData user;
- to indicate that an MCData user is interested in one or more MCData group(s) at an MCData client triggered by a location or functional alias activation criteria;
- to indicate that the MCData user is no longer interested in one or more MCData group(s) at the MCData client client triggered by location or functional alias deactivation criteria; or
- any combination of the above;

the MCData client shall generate a SIP PUBLISH request according to 3GPP TS 24.229 [5], IETF RFC 3903 [34], and IETF RFC 3856 [39].

When the MCData user indicates that he is no longer interested in one or more MCData group(s) at the MCData client, the MCData client shall first check value of the <manual-deaffiliation-not-allowed-if-affiliation-rules-are-met> element if present within the MCData user profile document (see the MCData user profile document specified in 3GPP TS 24.484 [50]). If the affiliation to the group has been activated due to a rule being fulfilled and the <manual-deaffiliation-not-allowed-if-affiliation-rules-are-met> element is present and is set to a value of "true", the MCData client shall suppress the MCData user's request.

NOTE 0: If the request is suppressed, a notification message can be displayed to the user.

In the SIP PUBLISH request, the MCData client:

1) shall set the Request-URI to the public service identity identifying the originating participating MCData function serving the MCData user;
2) shall include an application/vnd.3gpp.mcdata-info+xml MIME body. In the application/vnd.3gpp.mcdata-info+xml MIME body, the MCData client shall include the <mcdata-request-uri> element set to the MCData ID of the MCData user;
3) shall include the ICSI value "urn:urn-7:3gpp-service.ims.icsi.mcdata" (coded as specified in 3GPP TS 24.229 [5]), in a P-Preferred-Service header field according to IETF RFC 6050 [7];
4) if the targeted MCData user is interested in at least one MCData group at the targeted MCData client, shall set the Expires header field according to IETF RFC 3903 [34], to 4294967295;

NOTE 1: 4294967295, which is equal to 2^{32}-1, is the highest value defined for Expires header field in IETF RFC 3261 [4].

5) if the targeted MCData user is no longer interested in any MCData group at the targeted MCData client, shall set the Expires header field according to IETF RFC 3903 [34], to zero; and
6) shall include an application/pidf+xml MIME body indicating per-user affiliation information according to subclause 8.4.1. In the MIME body, the MCData client:
   a) shall include all MCData groups where the targeted MCData user indicates its interest at the targeted MCData client;
   b) shall include the MCData client ID of the targeted MCData client;
   c) shall not include the "status" attribute and the "expires" attribute in the <affiliation> element; and
   d) shall set the <p-id> child element of the <presence> root element to a globally unique value.

The MCData client shall send the SIP PUBLISH request according to 3GPP TS 24.229 [5].

5.8.3 Test description

5.8.3.1 Pre-test conditions

Test configuration:

- Single cell configuration according to TS 37.579-1 [2] clause 5.2.2.2.1.

- GNSS simulator to simulate a location.

Preamble:

- The UE has performed procedure 'Initial registration' as described in TS 37.579-1 [2] clause 5.4.2.
- The GNSS simulator is configured to simulate a location in the centre of Geographical area #1 to provide a location, as defined in TS 36.508 [24] Table 4.11.2-2, step 1 of scenario #4.
- UE States at the end of the preamble:
  - The UE is in RRC_IDLE state.
  - The client is registered for MCData.

5.8.3.2 Test procedure sequence

Table 5.8.3.2-1: Main Behaviour

St	Procedure	Message Sequence		TP	Verdict
		U - S	Message		
1	Trigger the UE to reset UTC time and location. NOTE: The UTC time and location reset may be performed by MMI or AT command (+CUTCR).	-	-	-	-
2	Trigger the GNSS simulator to start step 2 of Scenario #4 to simulate the UE moving to location #7 inside Geographical area #1 as defined in TS 36.508 [24] Table 4.11.2-2.	-	-	-	-
3	Wait 10 sec to allow the simulated location to move approximately 100 m from the original location to location #7.	-	-	-	-
4-6	Check: Check: Does the UE (MCData Client) correctly perform steps 1a1-3 of procedure 'MCX Group Affiliation status change' as described in TS 37.579-1 [2] Table 5.3.34.3-1 to de-affiliate with group A? NOTE: The UE (MCData Client) sends a SIP PUBLISH message and the SS responds with a SIP 200(OK) message.	-	-	1	P
7	The procedure 'MCX communication release' as described in TS 37.579-1 [2] clause 5.4.14 is performed to release the RRC connection.	-	-	-	-
8	Trigger the GNSS simulator to start step 4 of Scenario #4 to simulate the UE moving to location #8 inside Geographical area #1 as defined in TS 36.508 [24] Table 4.11.2-2.	-	-	-	-
9	Wait 10 sec to allow the simulated location to move approximately 100 m from the original location to location #8.	-	-	-	-
10-12	Check: Check: Does the UE (MCData Client) correctly perform steps 1a1-3 of procedure 'MCX Group Affiliation status change' as described in TS 37.579-1 [2] Table 5.3.34.3-1 to affiliate with group A? NOTE: The UE (MCData Client) sends a SIP PUBLISH message and the SS responds with a SIP 200(OK) message.	-	-	2	P
13	The procedure 'MCX communication release' as described in TS 37.579-1 [2] clause 5.4.14 is performed to release the RRC connection.	-	-	-	-

5.8.3.3 Specific message contents

Table 5.8.3.3-1: SIP PUBLISH from the UE (step 5, Table 5.8.3.2-1; step 2, TS 37.579-1 [2] Table 5.3.34.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.11-1, condition PRESENCE-EVENT				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Expires				
delta-seconds	"0"			
Message-body				
MIME body part		**MCData-Info**		
MIME-part-body	MCData-Info as described in Table 5.8.3.3-2			
MIME body part		**PIDF**		
MIME-part-body	PIDF as described in Table 5.8.3.3-3			

Table 5.8.3.3-2: MCData-Info in SIP PUBLISH (Table 5.8.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.2.1-3				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
mcdata-info				
mcdata-Params				
mcdata-request-uri	px_MCData_ID_User_A			

Table 5.8.3.3-3: PIDF in SIP PUBLISH (Table 5.8.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.5.1-3, condition AFFILIATION				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
presence				
tuple				
status	present but empty	status shall be present but empty acc. to TS 24.282 [31] clause 8.2.2, 8.4.1.2		
..p-id	any allowed value		TS 24.282 [31] clause 8.2.2	

Table 5.8.3.3-4: SIP PUBLISH from the UE (step 11, Table 5.3.3.2-1; step 2, TS 37.579-1 [2] Table 5.3.34.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.11-1, condition PRESENCE-EVENT				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part		**MCData-Info**		
MIME-part-body	MCData-Info as described in Table 5.8.3.3-2			
MIME body part		**PIDF**		
MIME-part-body	PIDF as described in Table 5.8.3.3-5			

Table 5.8.3.3-5: PIDF in SIP PUBLISH (Table 5.8.3.3-4

Derivation Path: TS 37.579-1 [2], Table 5.5.3.5.1-3, condition AFFILIATION				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
presence				
..p-id	any allowed value		TS 24.282 [31] clause 8.2.2	

5.9 Configuration / Functional Alias / Location based functional alias status change

5.9.1 Test Purpose (TP)

(1)

```
with { UE (MCData Client) registered and authorised for MCData Service }
ensure that {
  when { UE enters into or exits from a location area that triggers one or more functional aliases
to be activated according to the MCData user profile document }
    then { UE (MCData Client) sends a SIP PUBLISH message to activate a functional alias }
            }
```

(2)

```
with { UE (MCData Client) registered and authorised for MCData Service and having already activated
a functional alias }
ensure that {
  when { UE enters into or exits from a location area that triggers one or more functional aliases
to be deactivated according to the MCData user profile document }
    then { UE (MCData Client) sends a SIP PUBLISH message to deactivate a functional alias }
            }
```

5.9.2 Conformance requirements

References: The conformance requirements covered in the present TC are specified in: TS 24.282clause 22.2.1.4, 22.2.1.2. Unless otherwise stated these are Rel-16 requirements.

[TS 24.282, clause 22.2.1.4]

If a location criterion for functional alias activation or de-activation is met, the MCData client shall initiate the functional alias status change procedure as specified in subclause 22.2.1.2.

[TS 24.282, clause 22.2.1.2]

In order:

- to indicate that an MCData user requests to activate one or more functional aliases;
- to indicate that the MCData user requests to deactivate one or more functional aliases;
- to refresh indication of an MCData user interest in one or more functional aliases due to near expiration of the expiration time of a functional alias with the status set to the "activated" state received in a SIP NOTIFY request in subclause 22.2.1.3;
- to indicate that the MCData client entering into or exiting from a location area triggers one or more functional aliases to be activated;
- to indicate that the MCData client entering into or exiting from a location area triggers one or more functional aliases to be deactivated; or
- any combination of the above;

the MCData client shall generate a SIP PUBLISH request according to TS 24.229 [5], IETF RFC 3903 [34], and IETF RFC 3856 [39].

When the MCData user requests to deactivate a functional alias, the MCData client shall first check the <manual-deactivation-not-allowed-if-location-criteria-met> element within the <anyExt> element of the <entry> element corresponding to the functional alias within the <FunctionalAliasList> list element of the <anyExt> element of the <OnNetwork> element of the MCData user profile document (see the MCData user profile document in TS 24.484 [12]). If the functional alias has been activated due to a location area trigger and the <manual-deactivation-not-allowed-if-location-criteria-met> element is set to a value of "true", the MCData client shall suppress the MCData user's request.

NOTE 1: If the request is suppressed, a notification message can be displayed to the user.

In the SIP PUBLISH request, the MCData client:

1) shall set the Request-URI to the public service identity identifying the originating participating MCData function serving the MCData user;

2) shall include an application/vnd.3gpp.mcdata-info+xml MIME body. In the application/vnd.3gpp.mcdata-info+xml MIME body, the MCData client shall include the <mcdata-request-uri> element set to the MCData ID of the MCData user;

3) shall include the ICSI value "urn:urn-7:3gpp-service.ims.icsi.mcdata" (coded as specified in TS 24.229 [5]), in a P-Preferred-Service header field according to IETF RFC 6050 [7];

4) if the MCData client requests to activate one or more functional aliases, shall set the Expires header field according to IETF RFC 3903 [34], to 4294967295;

NOTE 2: 4294967295, which is equal to 2^{32}-1, is the highest value defined for Expires header field in IETF RFC 3261 [4].

5) if the MCData client requests to deactivate one or more functional aliases, shall set the Expires header field according to IETF RFC 3903 [34], to zero; and

NOTE 3: Activation and deactivation of functional alias cannot be performed with the same PUBLISH request.

6) shall include an application/pidf+xml MIME body indicating per-user functional alias information according to subclause 22.3.1. In the MIME body, the MCData client:

   a) shall include all functional aliases where the MCData user requests activation for the MCData ID;

   b) shall include the MCData client ID of the targeted MCData client;

   c) shall not include the "status" attribute and the "expires" attribute in the <functionalalias> element;

   d) if the MCData client has received an indication that take over of a functional alias is possible and intends to take over a functional alias, shall include a <take-over> child element set to "true"; and

   e) shall set the <p-id-fa> child element of the <presence> root element to a globally unique value.

The MCData client shall send the SIP PUBLISH request according to TS 24.229 [5].

5.9.3 Test description

5.9.3.1 Pre-test conditions

Test configuration:

- Single cell configuration according to TS 37.579-1 [2] clause 5.2.2.2.1.
- GNSS simulator to simulate a location.

Preamble:

- The UE has performed procedure 'Initial registration' as described in TS 37.579-1 [2] clause 5.4.2.
- The GNSS simulator is configured to simulate a location in the centre of Geographical area #1 to provide a location, as defined in TS 36.508 [24] Table 4.11.2-2, step 1 of scenario #4.

- UE States at the end of the preamble:
  - The UE is in RRC_IDLE state.
  - The client is registered for MCData.

5.9.3.2 Test procedure sequence

Table 5.9.3.2-1: Main Behaviour

St	Procedure	Message Sequence		TP	Verdict
		U - S	Message		
1	Trigger the UE to reset UTC time and location. NOTE: The UTC time and location reset may be performed by MMI or AT command (+CUTCR).	-	-	-	-
2	Trigger the GNSS simulator to start step 2 of Scenario #4 to simulate the UE moving to location #7 inside Geographical area #1 as defined in TS 36.508 [24] Table 4.11.2-2.	-	-	-	-
3	Wait 10 sec to allow the simulated location to move approximately 100 m from the original location to location #7.	-	-	-	-
4-6	Check: Does the UE (MCData Client) correctly perform steps 2a1-4 of procedure 'UE initiated MCX functional alias status change' as described in TS 37.579-1 [2] Table 5.3.37.3-1 to change the status of a functional alias to "activated"? NOTE: The UE (MCData Client) sends a SIP PUBLISH message and the SS responds with a SIP 200(OK) message and then the RRC connection is released.	-	-	1	P
7	The procedure 'MCX communication release' as described in TS 37.579-1 [2] clause 5.4.14 is performed to release the RRC connection.	-	-	-	-
8	Trigger the GNSS simulator to start step 4 of Scenario #4 to simulate the UE moving to location #8 inside Geographical area #1 as defined in TS 36.508 [24] Table 4.11.2-2.	-	-	-	-
9	Wait 10 sec to allow the simulated location to move approximately 100 m from the original location to location #8.	-	-	-	-
10-12	Check: Does the UE (MCData Client) correctly perform steps 2a1-4 of procedure 'UE initiated MCX functional alias status change' as described in TS 37.579-1 [2] Table 5.3.37.3-1 to change the status of a functional alias to "not activated"? NOTE: The UE (MCData Client) sends a SIP PUBLISH message and the SS responds with a SIP 200(OK) message and then the RRC connection is released.	-	-	2	P
13	The procedure 'MCX communication release' as described in TS 37.579-1 [2] clause 5.4.14 is performed to release the RRC connection.	-	-	-	-

5.9.3.3 Specific message contents

Table 5.9.3.3-1: SIP PUBLISH from the UE (step 11, Table 5.9.3.2-1; step 3, TS 37.579-1 [2] Table 5.3.37.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.3.37.4-1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Expires			TS 24.282 [31] clause 22.2.1.2	
value	"0"			

6 On-Network Test Scenarios

6.1 Short Data Service

6.1.1 On-network / Short Data Service (SDS) / Standalone SDS Using Signalling Control Plane / One-to-one Standalone SDS / Client Originated (CO)

6.1.1.1 Test Purpose (TP)

(1)

```
with { UE (MCDATA Client) registered and authorised for MCDATA Service }
ensure that {
  when { the MCDATA User requests to send a standalone one-to-one SDS message with a disposition of
only Delivery }
    then { UE (MCDATA Client) sends a standalone one-to-one SDS message with a disposition of only
Delivery via a SIP MESSAGE message }
            }
```

(2)

```
with { UE (MCDATA Client) having sent a standalone one-to-one SDS message }
ensure that {
  when { UE (MCDATA Client receives a disposition response via a SIP MESSAGE message from the SS
(MCDATA Server) }
    then { UE (MCDATA Client) responds to the SIP MESSAGE message by sending a SIP 200 (OK) message
and delivers the notification to the MCDATA User }
            }
```

(3)

```
with { UE (MCDATA Client) registered and authorised for MCDATA Service }
ensure that {
  when { the MCDATA User requests to send a standalone one-to-one SDS message with a disposition of
only Read }
    then { UE (MCDATA Client) sends a standalone one-to-one SDS message with a disposition of only
Read via a SIP MESSAGE message }
            }
```

(4)

```
with { UE (MCDATA Client) registered and authorised for MCDATA Service }
ensure that {
  when { the MCDATA User requests to send a standalone one-to-one SDS message with a disposition of
both Read and Delivery }
    then { UE (MCDATA Client) sends a standalone one-to-one SDS message with a disposition of both
Read and Delivery via a SIP MESSAGE message }
            }
```

6.1.1.2 Conformance requirements

References: The conformance requirements covered in the current TC are specified in: TS 24.282, clauses 9.2.2.2.1, 6.2.2.1, 6.2.4.1, 12.2.1.2. The following represents a copy/paste extraction of the requirements relevant to the test purpose; any references within the copy/paste text should be understood within the scope of the core spec they have been copied from. Unless otherwise stated, these are Rel-14 requirements.

[TS 24.282, clause 9.2.2.2.1]

The MCData client shall generate a SIP MESSAGE request in accordance with 3GPP TS 24.229 [5] and IETF RFC 3428 [6] with the clarifications given below.

The MCData client:

1) shall build the SIP MESSAGE request as specified in subclause 6.2.4.1;

2) if a one-to-one standalone SDS message is to be sent, shall insert in the SIP MESSAGE request:

   a) an application/resource-lists+xml MIME body with the MCData ID of the target MCData user, according to rules and procedures of IETF RFC 4826 [9];

   b) an application/vnd.3gpp.mcdata-info+xml MIME body with a <request-type> element set to a value of "one-to-one-sds"; and

   c) if end-to-end security is required and the security context does not exist or if the existing security context has expired, an application/mikey MIME body with the MIKEY-SAKKE I_MESSAGE as specified in 3GPP TS 33.180 [26]. The MCData client:

      i) if necessary, shall instruct the key management client to request keying material from the key management server as described in 3GPP TS 33.180 [26];

      ii) shall use the keying material to generate a PCK as described in 3GPP TS 33.180 [26];

      iii) shall use the PCK to generate a PCK-ID with the four most significant bits set to "0001" to indicate that the purpose of the PCK is to protect one-to-one communications and with the remaining twenty eight bits being randomly generated as described in 3GPP TS 33.180 [26];

      iv) shall encrypt the PCK to a UID associated to the MCData client using the MCData ID of the invited user and a time related parameter as described in 3GPP TS 33.180 [26];

      v) shall generate a MIKEY-SAKKE I_MESSAGE using the encapsulated PCK and PCK-ID as specified in 3GPP TS 33.180 [26]; and

      vi) shall add the MCData ID of the originating MCData to the initiator field (IDRi) of the I_MESSAGE as described in 3GPP TS 33.180 [26];

      vii) shall sign the MIKEY-SAKKE I_MESSAGE using the originating MCData user's signing key provided in the keying material together with a time related parameter; and

      viii) shall include the MIKEY-SAKKE I_MESSAGE in an application/mikey MIME body as specified in 3GPP TS 33.180 [26];

      …

4) shall generate a standalone SDS message as specified in subclause 6.2.2.1; and

5) shall send the SIP MESSAGE request according to rules and procedures of 3GPP TS 24.229 [5].

[TS 24.282, clause 6.2.2.1]

In order to generate an SDS message, the MCData client:

1) shall generate an SDS SIGNALLING PAYLOAD message as specified in subclause 15.1.2;

2) shall generate a DATA PAYLOAD message as specified in subclause 15.1.4;

3) shall include in the SIP request, the SDS SIGNALLING PAYLOAD message in an application/vnd.3gpp.mcdata-signalling MIME body as specified in subclause E.1; and

4) shall include in the SIP request, the DATA PAYLOAD message in an application/vnd.3gpp.mcdata-payload MIME body as specified in subclause E.2.

When generating an SDS SIGNALLING PAYLOAD message as specified in subclause 15.1.2, the MCData client:

1) shall set the Date and time IE to the current time as specified in subclause 15.2.8;

2) if the SDS message starts a new conversation, shall set the Conversation ID IE to a newly generated Conversation ID value as specified in subclause 15.2.9;

3) if the SDS message continues an existing unfinished conversation, shall set the Conversation ID IE to the Conversation ID value of the existing conversation as specified in subclause 15.2.9;

4) shall set the Message ID IE to a newly generated Message ID value as specified in subclause 15.2.10;

5) if the SDS message is in reply to a previously received SDS message, shall include the InReplyTo message ID IE with the Message ID value in the previously received SDS message;

6) if the SDS message is for user consumption, shall not include an Application ID IE as specified in subclause 15.2.7;

7) if the SDS message is intended for an application on the terminating MCData client, shall include an Application ID IE with an Application ID value representing the intended application as specified in subclause 15.2.7;

NOTE: The value chosen for the Application ID value is decided by the mission critical organisation.

8) if only a delivery disposition notification is required shall include a SDS disposition request type IE set to "DELIVERY" as specified in subclause 15.2.3;

9) if only a read disposition notification is required shall include a SDS disposition request type IE set to "READ" as specified in subclause 15.2.3; and

10) if both a delivery and read disposition notification is required shall include a SDS disposition request type IE set to "DELIVERY AND READ" as specified in subclause 15.2.3.

When generating an DATA PAYLOAD message for SDS as specified in subclause 15.1.4, the MCData client:

1) shall set the Number of payloads IE to the number of Payload IEs that needs to be encoded, as specified in subclause 15.2.12;

2) if end-to-end security is required for a one-to-one communication, shall include the Security parameters and Payload IE with security parameters as described in 3GPP TS 33.180 [26]. Otherwise, if end-to-end security is not required for a one-to-one communication, shall include the Payload IE as specified in subclause 15.1.4; and

3) for each Payload IE included:

   a) if the payload is text, shall set the Payload content type as "TEXT" as specified in subclause 15.2.13;

   b) if the payload is binary data, shall set the Payload content type as "BINARY" as specified in subclause 15.2.13;

   c) if the payload is hyperlinks, shall set the Payload content type as "HYPERLINKS" as specified in subclause 15.2.13;

   d) if the payload is location, shall set the Payload content type as "LOCATION" as specified in subclause 15.2.13; and

   e) shall include the data to be sent in the Payload data.

[TS 24.282, clause 6.2.4.1]

This subclause is referenced from other procedures.

In a SIP MESSAGE request, the MCData client:

1) when sending SDS messages or SDS disposition notifications:

   a) shall include an Accept-Contact header field containing the g.3gpp.mcdata.sds media feature tag along with the "require" and "explicit" header field parameters according to IETF RFC 3841 [8];

   b) shall include an Accept-Contact header field with the media feature tag g.3gpp.icsi-ref containing the value of "urn:urn-7:3gpp-service.ims.icsi.mcdata.sds" along with the "require" and "explicit" header field parameters according to IETF RFC 3841 [8]; and

   c) shall include the ICSI value "urn:urn-7:3gpp-service.ims.icsi.mcdata.sds" (coded as specified in 3GPP TS 24.229 [5]), in a P-Preferred-Service header field according to IETF RFC 6050 [7] in the SIP MESSAGE request;

   …

3) may include a P-Preferred-Identity header field in the SIP MESSAGE request containing a public user identity as specified in 3GPP TS 24.229 [5]; and

4) shall set the Request-URI to the public service identity identifying the participating MCData function serving the MCData user.

[TS 24.282, clause 12.2.1.2]

Upon receipt of a:

"SIP MESSAGE request for SDS disposition notification for terminating MCData client"; or

"SIP MESSAGE request for FD disposition notification for terminating MCData client";

the MCData client:

1) shall decode the contents of the application/vnd.3gpp.mcdata-signalling MIME body; and

2) shall deliver the notification to the user or application.

6.1.1.3 Test description

6.1.1.3.1 Pre-test conditions

Test configuration:

- Single cell configuration according to TS 37.579-1 [2] clause 5.2.2.2.1.

Preamble:

- The UE has performed procedure 'Initial registration' as described in TS 37.579-1 [2] clause 5.4.2 with the following clarifications:

  - The <max-payload-size-sds-cplane-bytes> element shall not be present in the MCData Service Configuration document so that according to TS 24.484 [24] there is no size limit imposed for the use of C-plane procedures for the SDS message.

- UE States at the end of the preamble:

  - The UE is in RRC_IDLE state.

  - The client is registered for MCData.

6.1.1.3.2 Test procedure sequence

Table 6.1.1.3.2-1: Main Behaviour

St	Procedure	Message Sequence		TP	Verdict
		U - S	Message		
1	Make the UE (MCData client) send a standalone one-to-one SDS message with disposition request "**DELIVERY**". (NOTE 1)	-	-	-	-
2-2B	Check: Does the UE (MCData client) correctly perform steps 1a1-3 of procedure '**CO SDS or FD message transfer** using signalling plane' as described in TS 37.579-1 [2] Table 5.3C.1.3-1 **to send a standalone one-to-one SDS message with disposition request "DELIVERY"**? (NOTE 2)	-	-	1	P
3	Void	-	-	-	-
4	Check: Does the UE (MCData client) correctly perform procedure '**MCX SIP MESSAGE CT**' as described in TS 37.579-1 [2] Table 5.3.33.3-1 **to receive the disposition notification** for the SDS message sent at step 2A?	-	-	2	P
5	Void	-	-	-	-
6	Check: Does the UE (MCData client) provide the disposition notification to the user? (NOTE 1)	-	-	2	P
7	Make the UE (MCData client) send a standalone one-to-one SDS message with disposition request "**READ**". (NOTE 1)	-	-	-	-
8	Check: Does the UE (MCData client) correctly perform procedure '**CO SDS or FD message transfer** using signalling plane' as described in TS 37.579-1 [2] Table 5.3C.1.3-1 **to send a standalone one-to-one SDS message with disposition request "READ"**?	-	-	3	P
9	Void	-	-	-	-
10	Check: Does the UE (MCData client) correctly perform procedure '**MCX SIP MESSAGE CT**' as described in TS 37.579-1 [2] Table 5.3.33.3-1 **to receive the disposition notification** for the SDS message sent at step 8?	-	-	2	P
11	Void	-	-	-	-
12	Check: Does the UE (MCData client) provide the disposition notification to the user? (NOTE 1)	-	-	2	P
13	Make the UE (MCData client) send a standalone one-to-one SDS message with disposition request "**DELIVERY AND READ**". (NOTE 1)	-	-	-	-
14	Check: Does the UE (MCData client) correctly perform procedure '**CO SDS or FD message transfer** using signalling plane' as described in TS 37.579-1 [2] Table 5.3C.1.3-1 **to send a standalone one-to-one SDS message with disposition request "DELIVERY AND READ"**?	-	-	4	P
15	Void	-	-	-	-
16	Check: Does the UE (MCData client) correctly perform procedure '**MCX SIP MESSAGE CT**' as described in TS 37.579-1 [2] Table 5.3.33.3-1 **to receive the disposition notification** for the SDS message sent at step 14?	-	-	2	P
17	Void	-	-	-	-
18	Check: Does the UE (MCData client) provide the disposition notification to the user? (NOTE 1)	-	-	2	P

NOTE 1: This is expected to be done via a suitable implementation dependent MMI.
NOTE 2: The RRC connection is not released at the end of the procedure.

6.1.1.3.3 Specific message contents

Table 6.1.1.3.3-1: SIP MESSAGE from the UE (step 2A, Table 6.1.1.3.2-1; step 2, TS 37.579-1 [2] Table 5.3C.1.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.7.1-1, condition MCDATA_SDS, RESOURCE_LISTS, MIKEY, MCDATA_SIGNALLING, MCDATA_PAYLOAD				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part		**MCData-Info**		
MIME-part-body	MCData-Info as described in Table 6.1.1.3.3-2			
MIME body part		**MCData Data signalling message**		
MIME-part-body	MCData Protected Payload Message containing SDS SIGNALLING PAYLOAD as described in Table 6.1.1.3.3-3			
MIME body part		**MCData Data message**		
MIME-part-body	DATA PAYLOAD as described in Table 6.1.1.3.3-4			

Table 6.1.1.3.3-2: MCData-Info (Table 6.1.1.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.2.1-3, condition MCD_1to1

Table 6.1.1.3.3-3: SDS SIGNALLING PAYLOAD (Table 6.1.1.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.1-1, condition DELIVERED

Table 6.1.1.3.3-4: DATA PAYLOAD (Table 6.1.1.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.9.2-1

Table 6.1.1.3.3-5: SIP MESSAGE from the SS (step 4, Table 6.1.1.3.2-1; step 2, TS 37.579-1 [2] Table 5.3.33.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.7.2-1, condition MCDATA_SDS, MCDATA_SIGNALLING				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part		**MCData Data signalling message**		
MIME-part-body	MCData Protected Payload Message containing SDS NOTIFICATION as described in Table 6.1.1.3.3-7			

Table 6.1.1.3.3-6: Void

Table 6.1.1.3.3-7: SDS NOTIFICATION (Table 6.1.1.3.3-5)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.4-1, condition DELIVERED

Table 6.1.1.3.3-8: Void

Table 6.1.1.3.3-9: SIP MESSAGE from the UE (step 8, Table 6.1.1.3.2-1; step 2, TS 37.579-1 [2] Table 5.3C.1.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.7.1-1, condition MCDATA_SDS, RESOURCE_LISTS, MIKEY, MCDATA_SIGNALLING, MCDATA_PAYLOAD				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part		**MCData-Info**		
MIME-part-body	As described in Table 6.1.1.3.3-2			
MIME body part		**MCData Data signalling message**		
MIME-part-body	MCData Protected Payload Message containing SDS SIGNALLING PAYLOAD as described in Table 6.1.1.3.3-10			
MIME body part		**MCData Data message**		
MIME-part-body	DATA PAYLOAD as described in Table 6.1.1.3.3-4			

Table 6.1.1.3.3-10: SDS SIGNALLING PAYLOAD (Table 6.1.1.3.3-9)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.1-1. condition READ

Table 6.1.1.3.3-11: SIP MESSAGE from the SS (step 10, Table 6.1.1.3.2-1; step 2, TS 37.579-1 [2] Table 5.3.33.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.7.2-1, condition MCDATA_SDS, MCDATA_SIGNALLING				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part		**MCData Data signalling message**		
MIME-part-body	MCData Protected Payload Message containing SDS NOTIFICATION as described in Table 6.1.1.3.3-12			

Table 6.1.1.3.3-12: SDS NOTIFICATION (Table 6.1.1.3.3-11)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.4-1, condition READ

Table 6.1.1.3.3-13: SIP MESSAGE from the UE (step 14, Table 6.1.1.3.2-1; step 2, TS 37.579-1 [2] Table 5.3C.1.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.7.1-1, condition MCDATA_SDS, RESOURCE_LISTS, MIKEY, MCDATA_SIGNALLING, MCDATA_PAYLOAD				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part		**MCData-Info**		
MIME-part-body	MCData-Info as described in Table 6.1.1.3.3-2			
MIME body part		**MCData Data signalling message**		
MIME-part-body	MCData Protected Payload Message containing SDS SIGNALLING PAYLOAD as described in Table 6.1.1.3.3-14			
MIME body part		**MCData Data message**		
MIME-part-body	DATA PAYLOAD as described in Table 6.1.1.3.3-4			

Table 6.1.1.3.3-14: SDS SIGNALLING PAYLOAD (Table 6.1.1.3.3-13)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.1-1, condition DELIVERED_READ

Table 6.1.1.3.3-15: SIP MESSAGE from the SS (step 16, Table 6.1.1.3.2-1; step 2, TS 37.579-1 [2] Table 5.3.33.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.7.2-1, condition MCDATA_SDS, MCDATA_SIGNALLING				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part		**MCData Data signalling message**		
MIME-part-body	MCData Protected Payload Message containing SDS NOTIFICATION described in Table 6.1.1.3.3-16			

Table 6.1.1.3.3-16: SDS NOTIFICATION (Table 6.1.1.3.3-15)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.4-1, condition DELIVERED_READ

6.1.2 On-network / Short Data Service (SDS) / Standalone SDS Using Signalling Control Plane / One-to-one Standalone SDS / Client Terminated (CT)

6.1.2.1 Test Purpose (TP)

(1)

```
with { UE (MCDATA Client) registered and authorised for MCDATA Service }
ensure that {
```

```
  when { the MCDATA User receives a standalone one-to-one SDS message with a disposition request of
"DELIVERY" }
    then { UE (MCDATA Client) confirms the reception of the SDS message by sending a SIP 200 (OK)
message, followed by a SIP MESSAGE with a disposition notification of "DELIVERED" and renders the
contents of the Payload IE to the MCDATA User }
            }
```

(2)

```
with { UE (MCDATA Client) registered and authorised for MCDATA Service }
ensure that {
  when { the MCDATA User receives a standalone one-to-one SDS message with a disposition request of
"READ" }
    then { UE (MCDATA Client) confirms the reception of the SDS message by sending a SIP 200 (OK)
message, and, renders the contents of the Payload IE to the MCDATA User, and, then sends a SIP
MESSAGE message with a disposition notification of "READ" }
            }
```

(3)

```
with { UE (MCDATA Client) registered and authorised for MCDATA Service }
ensure that {
  when { the MCDATA User receives a standalone one-to-one SDS message with a disposition request of
"DELIVERY AND READ" with pre-set timer TDU1 (delivery and read) }
    then { UE (MCDATA Client) sends a delivered and read notification after the message is rendered
to the user if the timer TDU1 (delivery and read) has not expired at this time, or, if the timer
TDU1 (delivery and read) expires before the message is rendered to the user sends first a delivered
notification and after the message is rendered to the user a read notification }
            }
```

6.1.2.2 Conformance requirements

References: The conformance requirements covered in the current TC are specified in: TS 24.282, clauses 9.2.2.2.2, 9.2.1.2, 9.2.1.3, 12.2.1.1, 6.2.3.1, 6.2.4.1. The following represents a copy/paste extraction of the requirements relevant to the test purpose; any references within the copy/paste text should be understood within the scope of the core spec they have been copied from. Unless otherwise stated, these are Rel-14 requirements.

[TS 24.282, clause 9.2.2.2.2]

Upon receipt of a "SIP MESSAGE request for standalone SDS for terminating MCData client", the MCData client:

1) may reject the SIP MESSAGE request if there are not enough resources to handle the SIP MESSAGE request;

2) if the SIP MESSAGE request is rejected in step 1), shall respond toward participating MCData function with a SIP 480 (Temporarily unavailable) response and skip the rest of the steps of this subclause;

3) if the SIP MESSAGE request contains an application/mikey MIME body containing a MIKEY-SAKKE I_MESSAGE:

   a) shall extract the MCData ID of the originating MCData user from the initiator field (IDRi) of the I_MESSAGE as described in 3GPP TS 33.180 [26];

   b) shall convert the MCData ID to a UID as described in 3GPP TS 33.180 [26];

   c) shall use the UID to validate the signature of the MIKEY-SAKKE I_MESSAGE as described in 3GPP TS 33.180 [26];

   d) if authentication verification of the MIKEY-SAKKE I_MESSAGE fails, shall reject the SIP MESSAGE request with a SIP 606 (Not Acceptable) response, and include warning text set to "136 authentication of the MIKEY-SAKKE I_MESSAGE failed" in a Warning header field as specified in subclause 4.9 and not continue with rest of the steps in this subclause; and

   e) if the signature of the MIKEY-SAKKE I_MESSAGE was successfully validated:

      i) shall extract and decrypt the encapsulated PCK using the terminating user's (KMS provisioned) UID key as described in 3GPP TS 33.180 [26]; and

      ii) shall extract the PCK-ID, from the payload as specified in 3GPP TS 33.180 [26];

NOTE: With the PCK successfully shared between the originating MCData client and the terminating MCData client, both clients are able to exchange end-to-end secure message.

4) shall generate a SIP 200 (OK) response according to rules and procedures of 3GPP TS 24.229 [5];

5) shall send the SIP 200 (OK) response towards the MCData server according to rules and procedures of 3GPP TS 24.229 [5]; and

6) shall handle the received message as specified in subclause 9.2.1.2.

[TS 24.282, clause 9.2.1.2]

When a MCData client has received a SIP request containing:

- an application/vnd.3gpp.mcdata-signalling MIME body as specified in subclause E.1; and
- an application/vnd.3gpp.mcdata-payload MIME body as specified in subclause E.2;

the MCData Client:

1) shall decode the contents of the application/vnd.3gpp.mcdata-signalling MIME body;

2) shall decode the contents of the application/vnd.3gpp.mcdata-payload MIME body;

3) if the SDS SIGNALLING PAYLOAD message contains a new Conversation ID, shall instantiate a new conversation with the Message ID in the SDS SIGNALLING PAYLOAD identifying the first message in the conversation thread;

4) if the SDS SIGNALLING PAYLOAD message contains an existing Conversation ID and:

   a) if the SDS SIGNALLING PAYLOAD message does not contain an InReplyTo message ID, shall use the Message ID in the SDS SIGNALLING PAYLOAD to identify a new message in the existing conversation thread; and

   b) if the SDS SIGNALLING PAYLOAD message contains an InReplyTo message ID, shall associate the message to an existing message in the conversation thread as identified by the InReplyTo message ID in the SDS SIGNALLING PAYLOAD, and use the Message ID in the SDS SIGNALLING PAYLOAD to identify the new message;

5) shall identify the number of Payload IEs in the DATA PAYLOAD message from the Number of payloads IE in the DATA PAYLOAD message;

6) if the SDS SIGNALLING PAYLOAD message does not contain an Application ID IE:

   a) shall determine that the payload contained in the DATA PAYLOAD message is for user consumption

   b) may notify the MCData user; and

   c) shall render the contents of the Payload IE(s) to the MCData user;

7) if the SDS SIGNALLING PAYLOAD message contains an Application ID IE:

   a) shall determine that the payload contained in the DATA PAYLOAD message is not for user consumption,

   b) shall not notify the MCData user;

   c) if the Application ID value is unknown, shall discard the SDS message; and

   d) if the Application ID value is known, shall deliver the contents of the Payload IE(s) to the identified application;

NOTE 1: If required, the MCData client decrypts the Payload IEs before rendering the SDS message to the user or delivering the SDS message to the application.

NOTE 2: The actions taken when the payload contains application data not meant for user consumption or command instructions are based upon the contents of the payload. If the payload content is addressed to a non-MCData application that is not running, the MCData client starts the local non-MCData application and delivers the payload to that application.

NOTE 3: User consent is not required before accepting the data.

8) may store the message payload in local storage along with the Conversation ID, Message ID, InReplyTo message ID and Date and time; and

9) if the received SDS SIGNALLING PAYLOAD message contains an SDS disposition request type IE shall follow the procedures in subclause 9.2.1.3.

[TS 24.282, clause 9.2.1.3]

To handle the disposition requests, the MCData client:

1) If the SDS disposition request type IE is set to:

   a) "DELIVERY" then, shall send a delivered notification as described in subclause 12.2.1.1;

   b) "READ", shall send a read notification as described in subclause 12.2.1.1, when a display indication is received; or

   c) "DELIVERY AND READ" then, shall start timer TDU1 (delivery and read).

Upon receiving a display indication before timer TDU1 (delivery and read) expires, the MCData client:

1) shall stop timer TDU1 (delivery and read); and

2) shall send a delivered and read notification as described in subclause 12.2.1.1.

Upon expiry of timer TDU1 (delivery and read), the MCData client:

1) shall send a delivered notification as described in subclause 12.2.1.1; and

2) upon receiving a display indication, send a read notification as described in subclause 12.2.1.1.

[TS 24.282, clause 12.2.1.1]

The MCData client shall follow the procedures in this subclause to:

- indicate to an MCData client that an SDS message was delivered, read or delivered and read when the originating client requested a delivery, read or delivery and read report;

- indicate to the participating MCData function serving the MCData user that an SDS message was undelivered. The participating MCData function can store the message for later re-delivery;

- indicate to an MCData client that a request for FD was accepted, deferred or rejected; or

- indicate to an MCData client that a file download has been completed;

Before sending a disposition notification the MCData client needs to determine:

- the controlling MCData function that sent the SDS or FD message request. The MCData client determines the controlling MCData function from the contents of the <mcdata-controller-psi> element contained in the application/vnd.3gpp.mcdata-info+xml MIME body of the incoming SDS or FD message request;

- the group identity related to an SDS or FD message request received as part of a group communication. The MCData client determines the group identity from the contents of the <mcdata-calling-group-id> element contained in the application/vnd.3gpp.mcdata-info+xml MIME body of the incoming SDS or FD message request; and

- the MCData user targeted for the disposition notification. The MCData client determines the targeted MCData user from the contents of the <mcdata-calling-user-id> element contained in the application/vnd.3gpp.mcdata-info+xml MIME body of the incoming SDS or FD message request.

The MCData client shall generate a SIP MESSAGE request in accordance with 3GPP TS 24.229 [5] and IETF RFC 3428 [6] with the clarifications given below.

The MCData client:

1) shall build the SIP MESSAGE request as specified in subclause 6.2.4.1;

2) shall follow the rules specified in subclause 6.4 for the handling of MIME bodies in a SIP message when processing the remaining steps in this subclause;

3) shall insert in the SIP MESSAGE request an application/resource-lists+xml MIME body containing the MCData ID of the targeted MCData user, according to rules and procedures of IETF RFC 5366 [18];

4) shall insert in the SIP MESSAGE request an application/vnd.3gpp.mcdata-info+xml MIME body with an <mcdata-controller-psi> element containing the PSI of the controlling MCData function;

5) if sending a disposition notification in response to an MCData group data request, shall include an <mcdata-calling-group-id> element set to the MCData group identity in the application/vnd.3gpp.mcdata-info+xml MIME body;

6) if requiring to send an SDS notification, shall generate an SDS NOTIFICATION message and include it in the SIP MESSAGE request as specified in subclause 6.2.3.1;

7) if requiring to send an FD notification, shall generate an FD NOTIFICATION message and include it in the SIP MESSAGE request as specified in subclause 6.2.3.2; and

8) shall send the SIP MESSAGE request according to rules and procedures of 3GPP TS 24.229 [5].

[TS 24.282, clause 6.2.3.1]

In order to generate an SDS notification, the MCData client:

1) shall generate an SDS NOTIFICATION message as specified in subclause 15.1.5; and

2) shall include in the SIP request, the SDS NOTIFICATION message in an application/vnd.3gpp.mcdata-signalling MIME body as specified in subclause E.1.

When generating an SDS NOTIFICATION message as specified in subclause 15.1.5, the MCData client:

1) if sending a delivered notification, shall set the SDS disposition notification type IE as "DELIVERED" as specified in subclause 15.2.5;

2) if sending a read notification, shall set the SDS disposition notification type IE as "READ" as specified in subclause 15.2.5;

3) if sending a delivered and read notification, shall set the SDS disposition notification type IE as "DELIVERED AND READ" as specified in subclause 15.2.5;

4) if the SDS message could not be delivered to the user or application (e.g. due to lack of storage), shall set the SDS disposition notification type IE as "UNDELIVERED" as specified in subclause 15.2.5;

5) shall set the Date and time IE to the current time to as specified in subclause 15.2.8;

6) shall set the Conversation ID to the value of the Conversation ID that was received in the SDS message as specified in subclause 15.2.9;

7) shall set the Message ID to the value of the Message ID that was received in the SDS message as specified in subclause 15.2.10;

8) if the SDS message was destined for the user, shall not include an Application ID IE as specified in subclause 15.2.7; and

9) if the SDS message was destined for an application, shall include an Application ID IE set to the value of the Application ID that was included in the SDS message as specified in subclause 15.2.3.

[TS 24.282, clause 6.2.4.1]

This subclause is referenced from other procedures.

In a SIP MESSAGE request, the MCData client:

1) when sending SDS messages or SDS disposition notifications:

   a) shall include an Accept-Contact header field containing the g.3gpp.mcdata.sds media feature tag along with the "require" and "explicit" header field parameters according to IETF RFC 3841 [8];

   b) shall include an Accept-Contact header field with the media feature tag g.3gpp.icsi-ref containing the value of "urn:urn-7:3gpp-service.ims.icsi.mcdata.sds" along with the "require" and "explicit" header field parameters according to IETF RFC 3841 [8]; and

   c) shall include the ICSI value "urn:urn-7:3gpp-service.ims.icsi.mcdata.sds" (coded as specified in 3GPP TS 24.229 [5]), in a P-Preferred-Service header field according to IETF RFC 6050 [7] in the SIP MESSAGE request;

…

3) may include a P-Preferred-Identity header field in the SIP MESSAGE request containing a public user identity as specified in 3GPP TS 24.229 [5]; and

4) shall set the Request-URI to the public service identity identifying the participating MCData function serving the MCData user.

6.1.2.3 Test description

6.1.2.3.1 Pre-test conditions

Test configuration:

- Single cell configuration according to TS 37.579-1 [2] clause 5.2.2.2.1.

Preamble:

- The UE has performed procedure 'Initial registration' as described in TS 37.579-1 [2] clause 5.4.2 with the following clarifications:

  - The <max-payload-size-sds-cplane-bytes> element shall not be present in the MCData Service Configuration document so that according to TS 24.484 [24] there is no size limit imposed for the use of C-plane procedures for the SDS message.

- UE States at the end of the preamble:

  - The UE is in RRC_IDLE state.

  - The client is registered for MCData.

6.1.2.3.2 Test procedure sequence

Table 6.1.2.3.2-1: Main Behaviour

St	Procedure	Message Sequence		TP	Verdict
		U - S	Message		
1-1B	Check: Does the UE (MCData client) correctly perform steps 1a1-3 of procedure '**MCX SIP MESSAGE CT**' as described in TS 37.579-1 [2] Table 5.3.33.3-1 **to receive a standalone one-to-one SDS message with disposition request "DELIVERY"**? (NOTE 3)	-	-	1	P
2	Void	-	-	-	-
3	Check: Does the UE (MCData client) correctly perform procedure '**CO SDS or FD message transfer using signalling plane**' as described in TS 37.579-1 [2] Table 5.3C.1.3-1 **to send a disposition notification of "DELIVERED"**?	-	-	1	P
4	Void	-	-	-	-
5	Check: Does the UE (MCData client) provide the contents of the Payload IE to the user? (NOTE 2) The exact expected content is' as described in TS 37.579-1 [2], Table 5.5.3.10-2	-	-	1	P
6	Make the UE (MCData client) close the message application. (NOTE 2, NOTE 5)	-	-	-	-
7-7B	Check: Does the UE (MCData client) correctly perform steps 1a1-3 of procedure '**MCX SIP MESSAGE CT**' as described in TS 37.579-1 [2] Table 5.3.33.3-1 **to receive a standalone one-to-one SDS message with disposition request "READ"**? (NOTE 3)	-	-	2	P
8	Void	-	-	-	-
-	EXCEPTION: In parallel to the event described in step 9 the events described in Table 6.1.2.3.2-2 take place. (NOTE 1)	-	-	-	-
9	Check: Does the UE (MCData client) provide the contents of the Payload IE to the user? (NOTE 2) The exact expected content is' as described in TS 37.579-1 [2], Table 5.5.3.10-2.	-	-	2	P
10	Make the UE (MCData client) close the message application. (NOTE 2, NOTE 5)	-	-	-	-
11-11B	Check: Does the UE (MCData client) correctly perform steps 1a1-3 of procedure '**MCX SIP MESSAGE CT**' as described in TS 37.579-1 [2] Table 5.3.33.3-1 **to receive a standalone one-to-one SDS message with disposition request "DELIVERY AND READ"**? (NOTE 3, 4)	-	-	2	P
12	Void	-	-	-	-
-	EXCEPTION: In parallel to the event described in step 13 the events described in Table 6.1.2.3.2-3 take place. (NOTE 1)	-	-	-	-
13	Check: Does the UE (MCData client) provide the contents of the Payload IE to the user before expiry of timer TDU1 (delivery and read)? (NOTE 2) The exact expected content is' as described in TS 37.579-1 [2], Table 5.5.3.10-2.	-	-	4	P
14	Make the UE (MCData client) close the message application. (NOTE 2, NOTE 5)	-	-	-	-

NOTE 1: The behaviour is handled through parallel actions to allow for implementations which first indicate to the user that there is a message available, but render the message to the user only after the user takes an action to open the message.
NOTE 2: This is expected to be done via a suitable implementation dependent MMI.
NOTE 3: The RRC connection is not released at the end of the procedure.
NOTE 4: Timer TDU1 (delivery and read) is started upon receipt of the SIP MESSAGE message that contains a "DELIVERY AND READ" disposition request. Timer TDU1 (delivery and read)=120ms according to the default value defined in TS 24.282 [31].
NOTE 5; The message application shall be closed to avoid unexpected behaviour at the UE when receiving a next message.

Table 6.1.2.3.2-2: Parallel Behaviour

St	Procedure	Message Sequence		TP	Verdict
		U - S	Message		
1	Check: Does the UE (MCData client) correctly perform procedure '**CO SDS or FD message transfer using signalling plane**' as described in TS 37.579-1 [2] Table 5.3C.1.3-1 **to send a disposition notification of "READ"**?	-	-	2	P

Table 6.1.2.3.2-3: Parallel Behaviour

St	Procedure	Message Sequence		TP	Verdict
		U - S	Message		
-	EXCEPTION: Steps 1a1-1b1 describe behaviour that depends on the UE implementation in regard to how quick the UE (MCData client) will render the contents of the Payload IE to the MCData user and the value of Timer TDU1.	-	-	-	-
1a1-1a2	Check: Does the UE (MCData client) correctly perform steps 2-3 of procedure '**CO SDS or FD message transfer using signalling** plane' as described in TS 37.579-1 [2] Table 5.3C.1.3-1 **to send a disposition notification of "DELIVERED"**?	-	-	3	P
1a3	Check: Does the UE (MCData client) correctly perform procedure '**CO SDS or FD message transfer using signalling plane**' as described in TS 37.579-1 [2] Table 5.3C.1.3-1 **to send a disposition notification of "READ"**?	-	-	3	P
1b1	Check: Does the UE (MCData client) correctly perform procedure '**CO SDS or FD message transfer using signalling plane**' as described in TS 37.579-1 [2] Table 5.3C.1.3-1 **to send a disposition notification of "DELIVERED AND READ"**?	-	-	3	P

6.1.2.3.3 Specific message contents

Table 6.1.2.3.3-1: SIP MESSAGE from the SS (step 1A, Table 6.1.2.3.2-1; step 2, TS 37.579-1 [2] Table 5.3.33.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.7.2-1, condition MCDATA_SDS, MIKEY, MCDATA_SIGNALLING, MCDATA_PAYLOAD				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part		**MCData-Info**		
MIME-part-body	MCData-Info as described in Table 6.1.2.3.3-2			
MIME body part		**MCData Data signalling message**		
MIME-part-body	MCData Protected Payload Message containing SDS SIGNALLING PAYLOAD as described in Table 6.1.2.3.3-3			
MIME body part		**MCData Data message**		
MIME-part-body	DATA PAYLOAD as described in Table 6.1.2.3.3-4			

Table 6.1.2.3.3-2: MCData-Info (Table 6.1.2.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.2.2-3, condition MCD_1to1

Table 6.1.2.3.3-3: SDS SIGNALLING PAYLOAD (Table 6.1.2.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.2-1, condition DELIVERED

Table 6.1.2.3.3-4: DATA PAYLOAD (Table 6.1.2.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.9.2-2

Table 6.1.2.3.3-5: Void

Table 6.1.2.3.3-6: SIP MESSAGE from the UE (step 3, Table 6.1.2.3.2-1, step 1a1, Table 6.1.2.3.2-3; step 2, TS 37.579-1 [2] Table 5.3C.1.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.7.1-1, condition MCDATA_SDS, RESOURCE_LISTS, MCDATA_SIGNALLING				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part	not present	**MCData-Info**		
MIME body part		**MCData Data signalling message**		
MIME-part-body	MCData Protected Payload Message containing SDS NOTIFICATION as described in Table 6.1.2.3.3-7			

Table 6.1.2.3.3-7: SDS NOTIFICATION (Table 6.1.2.3.3-6)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.3-1, condition DELIVERED

Table 6.1.2.3.3-8: SIP MESSAGE from the SS (step 7A, Table 6.1.2.3.2-1; step 2, TS 37.579-1 [2] Table 5.3.33.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.7.2-1, condition MCDATA_SDS, MIKEY, MCDATA_SIGNALLING, MCDATA_PAYLOAD				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part		**MCData-Info**		
MIME-part-body	MCData-Info as described in Table 6.1.2.3.3-2			
MIME body part		**MCData Data signalling message**		
MIME-part-body	MCData Protected Payload Message containing SDS SIGNALLING PAYLOAD as described in Table 6.1.2.3.3-9			
MIME body part		**MCData Data message**		
MIME-part-body	DATA PAYLOAD as described in Table 6.1.2.3.3-4			

Table 6.1.2.3.3-9: SDS SIGNALLING PAYLOAD (Table 6.1.2.3.3-8)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.2-1. condition READ

Table 6.1.2.3.3-10: SIP MESSAGE from the UE (step 1, Table 6.1.2.3.2-2, step 1a3, Table 6.1.2.3.2-3; step 2, TS 37.579-1 [2] Table 5.3C.1.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.7.1-1, condition MCDATA_SDS, RESOURCE_LISTS, MCDATA_SIGNALLING				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part	not present	**MCData-Info**		
MIME body part		**MCData Data signalling message**		
MIME-part-body	MCData Protected Payload Message containing SDS NOTIFICATION as described in Table 6.1.2.3.3-11			

Table 6.1.2.3.3-11: SDS NOTIFICATION (Table 6.1.2.3.3-10)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.3-1, condition READ

Table 6.1.2.3.3-12: SIP MESSAGE from the SS (step 11A, Table 6.1.2.3.2-1; step 2, TS 37.579-1 [2] Table 5.3.33.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.7.2-1, condition MCDATA_SDS, MIKEY, MCDATA_SIGNALLING, MCDATA_PAYLOAD				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part		**MCData-Info**		
MIME-part-body	MCData-Info as described in Table 6.1.2.3.3-2			
MIME body part		**MCData Data signalling messag**		
MIME-part-body	MCData Protected Payload Message containing SDS SIGNALLING PAYLOAD as described in Table 6.1.2.3.3-13			
MIME body part		**MCData Data message**		
MIME-part-body	DATA PAYLOAD as described in Table 6.1.2.3.3-4			

Table 6.1.2.3.3-13: SDS SIGNALLING PAYLOAD (Table 6.1.2.3.3-12)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.2-1, condition DELIVERED_READ

Table 6.1.2.3.3-14: SIP MESSAGE from the UE (step 1b1, Table 6.1.2.3.2-2; step 2, TS 37.579-1 [2] Table 5.3C.1.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.7.1-1, condition MCDATA_SDS, RESOURCE_LISTS, MCDATA_SIGNALLING				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part	not present	**MCData-Info**		
MIME body part		**MCData Data signalling message**		
MIME-part-body	MCData Protected Payload Message containing SDS NOTIFICATION as described in Table 6.1.2.3.3-15			

Table 6.1.2.3.3-15: SDS NOTIFICATION (Table 6.1.2.3.3-14)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.3-1, condition DELIVERED_READ

6.1.3 On-network / Short Data Service (SDS) / Standalone SDS Using Signalling Control Plane / Group Standalone SDS / Client Originated (CO)

6.1.3.1 Test Purpose (TP)

(1)

```
with { UE (MCDATA Client) registered and authorised for MCDATA Service }
ensure that {
  when { the MCDATA User requests to send a group standalone SDS message with a disposition of only
Delivery }
    then { UE (MCDATA Client) sends a group standalone SDS message with a disposition of only
Delivery via s SIP MESSAGE message }
            }
```

(2)

```
with { UE (MCDATA Client) having sent a group standalone SDS message }
ensure that {
  when { the UE (MCDATA Client) receives a disposition response via a SIP MESSAGE message from the
SS (MCDATA Server) }
    then { UE (MCData Client) responds to the SIP MESSAGE message by sending a SIP 200 (OK) message
and delivers the notification to the MCDATA User }
            }
```

6.1.3.2 Conformance requirements

References: The conformance requirements covered in the current TC are specified in: TS 24.282, clauses 9.2.2.2.1, 6.2.2.1, 6.2.4.1, 12.2.1.2. The following represents a copy/paste extraction of the requirements relevant to the test purpose; any references within the copy/paste text should be understood within the scope of the core spec they have been copied from. Unless otherwise stated, these are Rel-14 requirements.

[TS 24.282, clause 9.2.2.2.1]

The MCData client shall generate a SIP MESSAGE request in accordance with 3GPP TS 24.229 [5] and IETF RFC 3428 [6] with the clarifications given below.

The MCData client:

1) shall build the SIP MESSAGE request as specified in subclause 6.2.4.1;

...

3) if a group standalone SDS message is to be sent:

   a) if the "/<*x*>/<x>/Common/MCData/AllowedSDS" leaf node present in the group document of the requested MCData group, configured on the group management client as specified in 3GPP TS 24.483 [42] is set to "false", shall reject the request to send SDS and not continue with the rest of the steps in this subclause; and

   b) shall insert in the SIP MESSAGE request an application/vnd.3gpp.mcdata-info+xml MIME body with:

      i) the <request-type> element set to a value of "group-sds";

      ii) the <mcdata-request-uri> element set to the MCData group identity; and

      iii) the <mcdata-client-id> element set to the MCData client ID of the originating MCData client;

4) shall generate a standalone SDS message as specified in subclause 6.2.2.1; and

5) shall send the SIP MESSAGE request according to rules and procedures of 3GPP TS 24.229 [5].

[TS 24.282, clause 6.2.2.1]

In order to generate an SDS message, the MCData client:

1) shall generate an SDS SIGNALLING PAYLOAD message as specified in subclause 15.1.2;

2) shall generate a DATA PAYLOAD message as specified in subclause 15.1.4;

3) shall include in the SIP request, the SDS SIGNALLING PAYLOAD message in an application/vnd.3gpp.mcdata-signalling MIME body as specified in subclause E.1; and

4) shall include in the SIP request, the DATA PAYLOAD message in an application/vnd.3gpp.mcdata-payload MIME body as specified in subclause E.2.

When generating an SDS SIGNALLING PAYLOAD message as specified in subclause 15.1.2, the MCData client:

1) shall set the Date and time IE to the current time as specified in subclause 15.2.8;

2) if the SDS message starts a new conversation, shall set the Conversation ID IE to a newly generated Conversation ID value as specified in subclause 15.2.9;

3) if the SDS message continues an existing unfinished conversation, shall set the Conversation ID IE to the Conversation ID value of the existing conversation as specified in subclause 15.2.9;

4) shall set the Message ID IE to a newly generated Message ID value as specified in subclause 15.2.10;

5) if the SDS message is in reply to a previously received SDS message, shall include the InReplyTo message ID IE with the Message ID value in the previously received SDS message;

6) if the SDS message is for user consumption, shall not include an Application ID IE as specified in subclause 15.2.7;

7) if the SDS message is intended for an application on the terminating MCData client, shall include an Application ID IE with an Application ID value representing the intended application as specified in subclause 15.2.7;

NOTE: The value chosen for the Application ID value is decided by the mission critical organisation.

8) if only a delivery disposition notification is required shall include a SDS disposition request type IE set to "DELIVERY" as specified in subclause 15.2.3;

9) if only a read disposition notification is required shall include a SDS disposition request type IE set to "READ" as specified in subclause 15.2.3; and

10) if both a delivery and read disposition notification is required shall include a SDS disposition request type IE set to "DELIVERY AND READ" as specified in subclause 15.2.3.

When generating an DATA PAYLOAD message for SDS as specified in subclause 15.1.4, the MCData client:

1) shall set the Number of payloads IE to the number of Payload IEs that needs to be encoded, as specified in subclause 15.2.12;

2) if end-to-end security is required for a one-to-one communication, shall include the Security parameters and Payload IE with security parameters as described in 3GPP TS 33.180 [26]. Otherwise, if end-to-end security is not required for a one-to-one communication, shall include the Payload IE as specified in subclause 15.1.4; and

3) for each Payload IE included:

   a) if the payload is text, shall set the Payload content type as "TEXT" as specified in subclause 15.2.13;

   b) if the payload is binary data, shall set the Payload content type as "BINARY" as specified in subclause 15.2.13;

   c) if the payload is hyperlinks, shall set the Payload content type as "HYPERLINKS" as specified in subclause 15.2.13;

   d) if the payload is location, shall set the Payload content type as "LOCATION" as specified in subclause 15.2.13; and

   e) shall include the data to be sent in the Payload data.

[TS 24.282, clause 6.2.4.1]

This subclause is referenced from other procedures.

In a SIP MESSAGE request, the MCData client:

1) when sending SDS messages or SDS disposition notifications:

   a) shall include an Accept-Contact header field containing the g.3gpp.mcdata.sds media feature tag along with the "require" and "explicit" header field parameters according to IETF RFC 3841 [8];

   b) shall include an Accept-Contact header field with the media feature tag g.3gpp.icsi-ref containing the value of "urn:urn-7:3gpp-service.ims.icsi.mcdata.sds" along with the "require" and "explicit" header field parameters according to IETF RFC 3841 [8]; and

   c) shall include the ICSI value "urn:urn-7:3gpp-service.ims.icsi.mcdata.sds" (coded as specified in 3GPP TS 24.229 [5]), in a P-Preferred-Service header field according to IETF RFC 6050 [7] in the SIP MESSAGE request;

   …

3) may include a P-Preferred-Identity header field in the SIP MESSAGE request containing a public user identity as specified in 3GPP TS 24.229 [5]; and

4) shall set the Request-URI to the public service identity identifying the participating MCData function serving the MCData user.

[TS 24.282, clause 12.2.1.2]

Upon receipt of a:

"SIP MESSAGE request for SDS disposition notification for terminating MCData client"; or

"SIP MESSAGE request for FD disposition notification for terminating MCData client";

the MCData client:

1) shall decode the contents of the application/vnd.3gpp.mcdata-signalling MIME body; and

2) shall deliver the notification to the user or application.

6.1.3.3 Test description

6.1.3.3.1 Pre-test conditions

Test configuration:

- Single cell configuration according to TS 37.579-1 [2] clause 5.2.2.2.1.

Preamble:

- The UE has performed procedure 'Initial registration' as described in TS 37.579-1 [2] clause 5.4.2 with the following clarifications:

  - The <max-payload-size-sds-cplane-bytes> element shall not be present in the MCData Service Configuration document so that according to TS 24.484 [24] there is no size limit imposed for the use of C-plane procedures for the SDS message.

- UE States at the end of the preamble:

  - The UE is in RRC_IDLE state.

  - The client is registered for MCData.

6.1.3.3.2 Test procedure sequence

Table 6.1.3.3.2-1: Main Behaviour

St	Procedure	Message Sequence		TP	Verdict
		U - S	Message		
1	Make the UE (MCData client) send a group standalone SDS message with disposition request "DELIVERY". (NOTE 1)	-	-	-	-
2-2B	Check: Does the UE (MCData client) correctly perform steps 1a1-3 of procedure '**CO SDS or FD message transfer using signalling plane**' as described in TS 37.579-1 [2] Table 5.3C.1.3-1 **to send a standalone group SDS message with disposition request "DELIVERY"**? (NOTE 2)	-	-	1	P
3	Void	-	-	-	-
4	Check: Does the UE (MCData client) correctly perform procedure '**MCX SIP MESSAGE CT**' as described in TS 37.579-1 [2] Table 5.3.33.3-1 **to receive the disposition notification** for the SDS message sent at step 2A?	-	-	2	P
5	Void	-	-	-	-
6	Check: Does the UE (MCData client) provide the disposition notification to the user? (NOTE 1)	-	-	2	P
NOTE 1: This is expected to be done via a suitable implementation dependent MMI. NOTE 2: The RRC connection is not released at the end of the procedure.					

6.1.3.3.3 Specific message contents

Table 6.1.3.3.3-1: SIP MESSAGE from the UE (step 2A, Table 6.1.3.3.2-1; step 2, TS 37.579-1 [2] Table 5.3C.1.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.7.1-1, condition MCDATA_SDS, MCDATA_SIGNALLING, MCDATA_PAYLOAD				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part		**MCData-Info**		
MIME-part-body	MCData-Info as described in Table 6.1.3.3.3-2			
MIME body part		**MCData Data signalling message**		
MIME-part-body	MCData Protected Payload Message containing SDS SIGNALLING PAYLOAD as described in Table 6.1.3.3.3-2A			
MIME body part		**MCData Data message**		
MIME-part-body	MCData Protected Payload Message containing DATA PAYLOAD as described in Table 6.1.3.3.3-3			

Table 6.1.3.3.3-2: MCData-Info (Table 6.1.3.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.2.1-3, condition MCD_grp

Table 6.1.3.3.3-2A: SDS SIGNALLING PAYLOAD (Table 6.1.3.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.1-1, condition DELIVERED

Table 6.1.3.3.3-3: DATA PAYLOAD (Table 6.1.3.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.9.1-1

Table 6.1.3.3.3-4: SIP MESSAGE from the SS (step 4, Table 6.1.3.3.2-1; step 2, TS 37.579-1 [2] Table 5.3.33.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.7.2-1, condition MCDATA_SDS, MCDATA_SIGNALLING				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part		**MCData-Info**		
MIME-part-body	As described in Table 6.1.3.3.3-5			
MIME body part		**MCData Data signalling message**		
MIME-part-body	MCData Protected Payload Message containing SDS NOTIFICATION as described in Table 6.1.3.3.3-6			

Table 6.1.3.3.3-5: MCData-Info (Table 6.1.3.3.3-4)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.2.2-3				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
mcdata-info				
mcdata-Params				
mcdata-calling-group-id	Encrypted <mcdata-calling-group-id> with mcdataURI set to px_MCData_Group_A_ID	Encrypted according to TS 37.579-1 [2] Table 5.5.3.2.2-3A		

Table 6.1.3.3.3-6: SDS NOTIFICATION (Table 6.1.3.3.3-4)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.4-1, condition DELIVERED

Table 6.1.3.3.3-7: Void

6.1.4 On-network / Short Data Service (SDS) / Standalone SDS Using Signalling Control Plane / Group Standalone SDS / Client Terminated (CT)

6.1.4.1 Test Purpose (TP)

(1)

```
with { UE (MCDATA Client) registered and authorised for MCDATA Service }
ensure that {
  when { the MCDATA User receives a standalone group SDS message with a disposition request of
"DELIVERY" }
    then { UE (MCDATA Client) responds by sending a SIP 200 (OK) message and sends a SIP MESSAGE
message with a disposition notification of "DELIVERED" and renders the contents of the Payload IE to
the MCDATA User }
            }
```

6.1.4.2 Conformance requirements

References: The conformance requirements covered in the current TC are specified in: TS 24.282, clauses 9.2.2.2.2, 9.2.1.2, 9.2.1.3, 12.2.1.1, 6.2.3.1, 6.2.4.1. The following represents a copy/paste extraction of the requirements relevant to the test purpose; any references within the copy/paste text should be understood within the scope of the core spec they have been copied from. Unless otherwise stated, these are Rel-14 requirements.

[TS 24.282, clause 9.2.2.2.2]

Upon receipt of a "SIP MESSAGE request for standalone SDS for terminating MCData client", the MCData client:

…

3) if the SIP MESSAGE request contains an application/mikey MIME body containing a MIKEY-SAKKE I_MESSAGE:

   a) shall extract the MCData ID of the originating MCData user from the initiator field (IDRi) of the I_MESSAGE as described in 3GPP TS 33.180 [26];

   b) shall convert the MCData ID to a UID as described in 3GPP TS 33.180 [26];

   c) shall use the UID to validate the signature of the MIKEY-SAKKE I_MESSAGE as described in 3GPP TS 33.180 [26];

   d) if authentication verification of the MIKEY-SAKKE I_MESSAGE fails, shall reject the SIP MESSAGE request with a SIP 606 (Not Acceptable) response, and include warning text set to "136 authentication of the MIKEY-SAKKE I_MESSAGE failed" in a Warning header field as specified in subclause 4.9 and not continue with rest of the steps in this subclause; and

   e) if the signature of the MIKEY-SAKKE I_MESSAGE was successfully validated:

      i) shall extract and decrypt the encapsulated PCK using the terminating user's (KMS provisioned) UID key as described in 3GPP TS 33.180 [26]; and

      ii) shall extract the PCK-ID, from the payload as specified in 3GPP TS 33.180 [26];

NOTE: With the PCK successfully shared between the originating MCData client and the terminating MCData client, both clients are able to exchange end-to-end secure message.

4) shall generate a SIP 200 (OK) response according to rules and procedures of 3GPP TS 24.229 [5];

5) shall send the SIP 200 (OK) response towards the MCData server according to rules and procedures of 3GPP TS 24.229 [5]; and

6) shall handle the received message as specified in subclause 9.2.1.2.

[TS 24.282, clause 9.2.1.2]

When a MCData client has received a SIP request containing:

- an application/vnd.3gpp.mcdata-signalling MIME body as specified in subclause E.1; and
- an application/vnd.3gpp.mcdata-payload MIME body as specified in subclause E.2;

the MCData Client:

1) shall decode the contents of the application/vnd.3gpp.mcdata-signalling MIME body;
2) shall decode the contents of the application/vnd.3gpp.mcdata-payload MIME body;

…

5) shall identify the number of Payload IEs in the DATA PAYLOAD message from the Number of payloads IE in the DATA PAYLOAD message;
6) if the SDS SIGNALLING PAYLOAD message does not contain an Application ID IE:
   a) shall determine that the payload contained in the DATA PAYLOAD message is for user consumption
   b) may notify the MCData user; and
   c) shall render the contents of the Payload IE(s) to the MCData user;
7) if the SDS SIGNALLING PAYLOAD message contains an Application ID IE:
   a) shall determine that the payload contained in the DATA PAYLOAD message is not for user consumption,
   b) shall not notify the MCData user;
   c) if the Application ID value is unknown, shall discard the SDS message; and
   d) if the Application ID value is known, shall deliver the contents of the Payload IE(s) to the identified application;

NOTE 1: If required, the MCData client decrypts the Payload IEs before rendering the SDS message to the user or delivering the SDS message to the application.

…

NOTE 3: User consent is not required before accepting the data.

8) may store the message payload in local storage along with the Conversation ID, Message ID, InReplyTo message ID and Date and time; and
9) if the received SDS SIGNALLING PAYLOAD message contains an SDS disposition request type IE shall follow the procedures in subclause 9.2.1.3.

[TS 24.282, clause 9.2.1.3]

To handle the disposition requests, the MCData client:

1) If the SDS disposition request type IE is set to:
   a) "DELIVERY" then, shall send a delivered notification as described in subclause 12.2.1.1;
   b) "READ", shall send a read notification as described in subclause 12.2.1.1, when a display indication is received; or
   c) "DELIVERY AND READ" then, shall start timer TDU1 (delivery and read).

[TS 24.282, clause 12.2.1.1]

The MCData client shall follow the procedures in this subclause to:

- indicate to an MCData client that an SDS message was delivered, read or delivered and read when the originating client requested a delivery, read or delivery and read report;

- indicate to the participating MCData function serving the MCData user that an SDS message was undelivered. The participating MCData function can store the message for later re-delivery;

- indicate to an MCData client that a request for FD was accepted, deferred or rejected; or

- indicate to an MCData client that a file download has been completed;

Before sending a disposition notification the MCData client needs to determine:

- the controlling MCData function that sent the SDS or FD message request. The MCData client determines the controlling MCData function from the contents of the <mcdata-controller-psi> element contained in the application/vnd.3gpp.mcdata-info+xml MIME body of the incoming SDS or FD message request;

- the group identity related to an SDS or FD message request received as part of a group communication. The MCData client determines the group identity from the contents of the <mcdata-calling-group-id> element contained in the application/vnd.3gpp.mcdata-info+xml MIME body of the incoming SDS or FD message request; and

- the MCData user targeted for the disposition notification. The MCData client determines the targeted MCData user from the contents of the <mcdata-calling-user-id> element contained in the application/vnd.3gpp.mcdata-info+xml MIME body of the incoming SDS or FD message request.

The MCData client shall generate a SIP MESSAGE request in accordance with 3GPP TS 24.229 [5] and IETF RFC 3428 [6] with the clarifications given below.

The MCData client:

1) shall build the SIP MESSAGE request as specified in subclause 6.2.4.1;

2) shall follow the rules specified in subclause 6.4 for the handling of MIME bodies in a SIP message when processing the remaining steps in this subclause;

3) shall insert in the SIP MESSAGE request an application/resource-lists+xml MIME body containing the MCData ID of the targeted MCData user, according to rules and procedures of IETF RFC 5366 [18];

4) shall insert in the SIP MESSAGE request an application/vnd.3gpp.mcdata-info+xml MIME body with an <mcdata-controller-psi> element containing the PSI of the controlling MCData function;

5) if sending a disposition notification in response to an MCData group data request, shall include an <mcdata-calling-group-id> element set to the MCData group identity in the application/vnd.3gpp.mcdata-info+xml MIME body;

6) if requiring to send an SDS notification, shall generate an SDS NOTIFICATION message and include it in the SIP MESSAGE request as specified in subclause 6.2.3.1;

…

8) shall send the SIP MESSAGE request according to rules and procedures of 3GPP TS 24.229 [5].

[TS 24.282, clause 6.2.3.1]

In order to generate an SDS notification, the MCData client:

1) shall generate an SDS NOTIFICATION message as specified in subclause 15.1.5; and

2) shall include in the SIP request, the SDS NOTIFICATION message in an application/vnd.3gpp.mcdata-signalling MIME body as specified in subclause E.1.

When generating an SDS NOTIFICATION message as specified in subclause 15.1.5, the MCData client:

1) if sending a delivered notification, shall set the SDS disposition notification type IE as "DELIVERED" as specified in subclause 15.2.5;

…

5) shall set the Date and time IE to the current time to as specified in subclause 15.2.8;

6) shall set the Conversation ID to the value of the Conversation ID that was received in the SDS message as specified in subclause 15.2.9;

7) shall set the Message ID to the value of the Message ID that was received in the SDS message as specified in subclause 15.2.10;

8) if the SDS message was destined for the user, shall not include an Application ID IE as specified in subclause 15.2.7; and

[TS 24.282, clause 6.2.4.1]

This subclause is referenced from other procedures.

In a SIP MESSAGE request, the MCData client:

1) when sending SDS messages or SDS disposition notifications:

   a) shall include an Accept-Contact header field containing the g.3gpp.mcdata.sds media feature tag along with the "require" and "explicit" header field parameters according to IETF RFC 3841 [8];

   b) shall include an Accept-Contact header field with the media feature tag g.3gpp.icsi-ref containing the value of "urn:urn-7:3gpp-service.ims.icsi.mcdata.sds" along with the "require" and "explicit" header field parameters according to IETF RFC 3841 [8]; and

   c) shall include the ICSI value "urn:urn-7:3gpp-service.ims.icsi.mcdata.sds" (coded as specified in 3GPP TS 24.229 [5]), in a P-Preferred-Service header field according to IETF RFC 6050 [7] in the SIP MESSAGE request;

…

3) may include a P-Preferred-Identity header field in the SIP MESSAGE request containing a public user identity as specified in 3GPP TS 24.229 [5]; and

4) shall set the Request-URI to the public service identity identifying the participating MCData function serving the MCData user.

6.1.4.3 Test description

6.1.4.3.1 Pre-test conditions

Test configuration:

- Single cell configuration according to TS 37.579-1 [2] clause 5.2.2.2.1.

Preamble:

- The UE has performed procedure 'Initial registration' as described in TS 37.579-1 [2] clause 5.4.2 with the following clarifications:

  - The <max-payload-size-sds-cplane-bytes> element shall not be present in the MCData Service Configuration document so that according to TS 24.484 [24] there is no size limit imposed for the use of C-plane procedures for the SDS message.

- UE States at the end of the preamble:

  - The UE is in RRC_IDLE state.

  - The client is registered for MCData.

6.1.4.3.2 Test procedure sequence

Table 6.1.4.3.2-1: Main Behaviour

St	Procedure	Message Sequence		TP	Verdict
		U - S	Message		
1-1B	Check: Does the UE (MCData client) correctly perform steps 1a1-3 of procedure '**MCX SIP MESSAGE CT**' as described in TS 37.579-1 [2] Table 5.3.33.3-1 **to receive a standalone group SDS message with disposition request "DELIVERY"**? (NOTE 2)	-	-	1	P
2	Void	-	-	-	-
3	Check: Does the UE (MCData client) correctly perform procedure '**CO SDS or FD message transfer using signalling plane**' as described in TS 37.579-1 [2] Table 5.3C.1.3-1 **to send a disposition notification of "DELIVERED"**?	-	-	1	P
4	Void	-	-	-	-
5	Check: Does the UE (MCData client) provide the contents of the Payload IE to the user? (NOTE 1)	-	-	1	P
NOTE 1: This is expected to be done via a suitable implementation dependent MMI. NOTE 2: The RRC connection is not released at the end of the procedure.					

6.1.4.3.3 Specific message contents

Table 6.1.4.3.3-1: SIP MESSAGE from the SS (step 1A, Table 6.1.4.3.2-1; step 2, TS 37.579-1 [2] Table 5.3.33.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.7.2-1, condition MCDATA_SDS, MCDATA_SIGNALLING, MCDATA_PAYLOAD				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part		**MCData-Info**		
MIME-part-body	MCData-Info as described in Table 6.1.4.3.3-2			
MIME body part		**MCData Data signalling message**		
MIME-part-body	MCData Protected Payload Message containing SDS SIGNALLING PAYLOAD as described in Table 6.1.4.3.3-3			
MIME body part		**MCData Data message**		
MIME-part-body	MCData Protected Payload Message containing DATA PAYLOAD as described in Table 6.1.4.3.3-3			

Table 6.1.4.3.3-2: MCData-Info (Table 6.1.4.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.2.2-3, condition MCD_grp

Table 6.1.4.3.3-3: SDS SIGNALLING PAYLOAD (Table 6.1.4.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.2-1, condition DELIVERED

Table 6.1.4.3.3-4: DATA PAYLOAD (Table 6.1.4.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.9.1-2

Table 6.1.4.3.3-5: Void

Table 6.1.4.3.3-6: SIP MESSAGE from the UE (step 3, Table 6.1.4.3.2-1; step 2, TS 37.579-1 [2] Table 5.3C.1.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.7.1-1, condition MCDATA_SDS, RESOURCE_LISTS, MCDATA_SIGNALLING				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part		**MCData-Info**		
MIME-part-headers	MCData-Info as described in Table 6.1.4.3.3-7			
MIME body part		**MCData Data signalling message**		
MIME-part-body	MCData Protected Payload Message containing SDS NOTIFICATION as described in Table 6.1.4.3.3-8			

Table 6.1.4.3.3-7: MCData-Info (Table 6.1.4.3.3-6)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.2.1-3				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
mcdata-info				
mcdata-Params				
mcdata-calling-group-id	Encrypted <mcdata-request-uri> with mcdataURI set to px_MCData_Group_A_ID	Encrypted according to TS 37.579-1 [2] Table 5.5.3.2.1-3A		

Table 6.1.4.3.3-8: SDS NOTIFICATION (Table 6.1.4.3.3-6)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.3-1, condition DELIVERED

6.1.5 On-network / Short Data Service (SDS) / Standalone SDS Using Media Plane / One-to-one Standalone SDS / Client Originated (CO)

6.1.5.1 Test Purpose (TP)

(1)

```
with { UE (MCDATA Client) registered and authorised for MCDATA Service }
ensure that {
  when { the MCDATA User requests to send a one-to-one standalone SDS message using the media plane}
    then { UE (MCDATA Client) sends a request to establish an MSRP connection via a SIP INVITE
message and then responds to the SIP 200 (OK) message with a SIP ACK message }
           }
```

(2)

```
with { UE (MCDATA Client) having requested the establishment of a MSRP connection }
ensure that {
  when { UE (MCDATA Client) receives a SIP 200 (OK) message with the a=setup attribute set to
"passive"  from the SS (MCDATA server) }
    then { UE (MCDATA Client) sends a blank MSRP SEND message to bind the MSRP connection and then
sends the one-to-one standalone SDS message via a MSRP SEND message with a disposition of "DELIVERY"
}
            }
```

(3)

```
with { UE (MCDATA Client) having sent a one-to-one standalone SDS message using the media plane }
ensure that {
  when { UE (MCDATA Client receives a MSRP 200 (OK) message in response to the last MSRP SEND
message indicating that the standalone SDS message has been successfully transferred }
    then { UE (MCDATA Client) sends a SIP BYE message }
            }
```

(4)

```
with { UE (MCDATA Client) having sent a one-to-one standalone SDS message using the media plane with
a disposition of "DELIVERY" }
ensure that {
  when { UE (MCDATA Client receives a disposition response via a SIP MESSAGE message from the SS
(MCDATA Server }
    then { UE (MCDATA Client) responds to the SIP MESSAGE message by sending a SIP 200 (OK) message
and delivers the notification to the MCDATA User }
            }
```

6.1.5.2 Conformance requirements

References: The conformance requirements covered in the current TC are specified in: TS 24.282, clauses 9.2.3.2.3, 9.2.3.2.1, 13.2.2.2.2.1, 12.2.1.2, TS 24.582 clauses 6.1.1.2.1, 6.1.1.2.2, 6.1.1.2.3, 6.1.1.2.4. The following represents a copy/paste extraction of the requirements relevant to the test purpose; any references within the copy/paste text should be understood within the scope of the core spec they have been copied from. Unless otherwise stated, these are Rel-14 requirements.

[TS 24.282, clause 9.2.3.2.3]

The MCData client shall generate a SIP INVITE request in accordance with 3GPP TS 24.229 [5] with the clarifications given below.

The MCData client:

1) shall include the g.3gpp.mcdata.sds media feature tag and the g.3gpp.icsi-ref media feature tag with the value of "urn:urn-7:3gpp-service.ims.icsi.mcdata.sds" in the Contact header field of the SIP INVITE request according to IETF RFC 3840 [16];

2) shall include an Accept-Contact header field containing the g.3gpp.mcdata.sds media feature tag along with the "require" and "explicit" header field parameters according to IETF RFC 3841 [8];

3) shall include an Accept-Contact header field with the g.3gpp.icsi-ref media feature tag containing the value of "urn:urn-7:3gpp-service.ims.icsi.mcdata.sds" along with the "require" and "explicit" header field parameters according to IETF RFC 3841 [8];

4) shall include the ICSI value "urn:urn-7:3gpp-service.ims.icsi.mcdata.sds" (coded as specified in 3GPP TS 24.229 [5]), in a P-Preferred-Service header field according to IETF RFC 6050 [7] in the SIP INVITE request;

5) should include the "timer" option tag in the Supported header field;

6) should include the Session-Expires header field according to IETF RFC 4028 [38]. It is recommended that the "refresher" header field parameter is omitted. If included, the "refresher" header field parameter shall be set to "uac";

7) if a one-to-one standalone SDS message is to be sent:

   a) shall insert in the SIP INVITE request a MIME resource-lists body with the MCData ID of the invited MCData user, according to rules and procedures of IETF RFC 5366 [18];

   b) shall contain an application/vnd.3gpp.mcdata-info+xml MIME body with the <mcdatainfo> element containing the <mcdata-Params> element with:

      i) the <request-type> element set to a value of "one-to-one-sds"; and

   c) if an end-to-end security context needs to be established and the security context does not exist or if the existing security context has expired, then:

      i) if necessary, shall instruct the key management client to request keying material from the key management server as described in 3GPP TS 33.180 [26];

      ii) shall use the keying material to generate a PCK as described in 3GPP TS 33.180 [26];

      iii) shall use the PCK to generate a PCK-ID with the four most significant bits set to "0001" to indicate that the purpose of the PCK is to protect one-to-one communications and with the remaining twenty eight bits being randomly generated as described in 3GPP TS 33.180 [26];

      iv) shall encrypt the PCK to a UID associated to the MCData client using the MCData ID of the invited user and a time related parameter as described in 3GPP TS 33.180 [26];

      v) shall generate a MIKEY-SAKKE I_MESSAGE using the encapsulated PCK and PCK-ID as specified in 3GPP TS 33.180 [26];

      vi) shall add the MCData ID of the originating MCData to the initiator field (IDRi) of the I_MESSAGE as described in 3GPP TS 33.180 [26]; and

      vii) shall sign the MIKEY-SAKKE I_MESSAGE using the originating MCData user's signing key provided in the keying material together with a time related parameter, and add this to the MIKEY-SAKKE payload, as described in 3GPP TS 33.180 [26];

…

9) shall set the Request-URI of the SIP INVITE request to the public service identity identifying the participating MCData function serving the MCData user;

NOTE 2: The MCData client is configured with public service identity identifying the participating MCData function serving the MCData user.

10) may include a P-Preferred-Identity header field in the SIP INVITE request containing a public user identity as specified in 3GPP TS 24.229 [5];

11) shall include an SDP offer according to 3GPP TS 24.229 [5] with the clarifications given in subclause 9.2.3.2.1; and

12) shall send the SIP INVITE request towards the MCData server according to 3GPP TS 24.229 [5].

On receipt of a SIP 2xx response to the SIP INVITE request, the MCData client:

1) shall send a SIP ACK request as specified in 3GPP TS 24.229 [5];

2) shall start the SIP Session timer according to rules and procedures of IETF RFC 4028 [38]; and

3) shall interact with the media plane as specified in 3GPP TS 24.582 [15] subclause 6.1.1.2.

…

On receipt of an indication from the media plane indicating that the standalone SDS message has been successfully transferred, the MCData client shall:

1) shall generate a SIP BYE request according to 3GPP TS 24.229 [5] with:

   a) Reason code set to "SIP";

b) cause set to "200"; and

c) text set to "transmission succeeded";

2) shall set the Request-URI to the MCData session identity to release; and

3) shall send a SIP BYE request towards MCData server according to 3GPP TS 24.229 [5].

Upon receiving a SIP 200 (OK) response to the SIP BYE request, the MCData client shall interact with the media plane and indicate to terminate the session, as specified in 3GPP TS 24.582 [15].

[TS 24.282, clause 9.2.3.2.1]

When composing an SDP offer according to 3GPP TS 24.229 [5], IETF RFC 4975 [17], IETF RFC 6135 [19] and IETF RFC 6714 [20] the MCData client:

1) shall include an "m=message" media-level section for the MCData media stream consisting of:

a) the IP address and the port number;

b) a protocol field value of "TCP/MSRP", or "TCP/TLS/MSRP" for TLS;

c) a format list field set to '*';

d) an "a=sendonly" attribute;

e) an "a=path" attribute containing its own MSRP URI;

f) set the content type as "a=accept-types:application/vnd.3gpp.mcdata-signalling application/vnd.3gpp.mcdata-payload"; and

g) set the a=setup attribute as "actpass"; and

2) if end-to-end security is required for a one-to-one communication and the security context does not exist or if the existing security context has expired, shall include the MIKEY-SAKKE I_MESSAGE in an "a=key-mgmt" attribute as a "mikey" attribute value in the SDP offer as specified in IETF RFC 4567 [45].

[TS 24.282, clause 13.2.2.2.2.1]

When the MCData client wants to release a MCData communication established over the media plane, the MCData client:

1) shall generate a SIP BYE request according to 3GPP TS 24.229 [5];

2) shall set the Request-URI to the MCData session identity to be released; and

3) shall send the SIP BYE request towards MCData server according to 3GPP TS 24.229 [5].

Upon receiving a SIP 200 (OK) response to the SIP BYE request, the MCData client shall release all media plane resources corresponding to the MCData communication being released.

[TS 24.282, clause 12.2.1.2]

Upon receipt of a:

"SIP MESSAGE request for SDS disposition notification for terminating MCData client"; or

"SIP MESSAGE request for FD disposition notification for terminating MCData client";

the MCData client:

1) shall decode the contents of the application/vnd.3gpp.mcdata-signalling MIME body; and

2) shall deliver the notification to the user or application.

[TS 24.582, clause 6.1.1.2.1]

Upon receiving an indication to establish MSRP connection for standalone SDS using media plane as the originating client, the MCData client:

1. shall act as an MSRP client according to IETF RFC 6135 [12];
2. shall act according to IETF RFC 6135 [12], as:
   a. an "active" endpoint, if a=setup attribute in the received SDP answer is set to "passive"; and
   b. an "passive" endpoint, if a=setup attribute in the received SDP answer is set to "active";
3. shall establish the MSRP connection according to the MSRP connection parameters in the SDP answer received in the SIP 200 (OK) response according to IETF RFC 4975 [11]; and
4. if acting as an "active" endpoint, shall send an empty MSRP SEND request to bind the MSRP connection to the MSRP session from the perspective of the passive endpoint according to the rules and procedures of IETF RFC 4975 [11] and IETF RFC 6135 [12].

On receiving MSRP 200 (OK) response to the first MSRP SEND request, the MCData client:

1. shall generate a SDS SIGNALLING PAYLOAD as specified in subclause 6.1.1.2.2;
2. shall generate a SDS DATA PAYLOAD as specified in subclause 6.1.1.2.3;
3. shall include the SDS SIGNALLING PAYLOAD and SDS DATA PAYLOAD in an MSRP SEND request as specified in subclause 6.1.1.2.4; and
4. shall send the MSRP SEND request on the established MSRP connection.

NOTE: MSRP chunking, if needed, may affect the number of "Content Type" lines in each MSRP SEND message conveying a chunk, as also specified in subclause 6.1.1.2.4.

If MSRP chunking is not used then on receipt of a 200 (OK) response, the MCData client shall terminate the SIP session as specified in 3GPP TS 24.282 [8].

If MSRP chunking is used, the MCData client:

1. shall send further MSRP SEND requests as necessary;
2. shall wait for a 200 (OK) response to each MSRP SEND request sent; and
3. on receipt of the last 200 (OK) response shall terminate the SIP session as specified in 3GPP TS 24.282 [8].

On receiving a non-200 MSRP response to the MSRP SEND request the MCData client shall handle the error as specified in IETF RFC 4975 [11]. To terminate the MSRP session, the MCData client:

1. if there are further MSRP chunks to send, shall abort transmission of these further MSRP chunks;
2. shall indicate to MCData user that the SDS message could not be sent; and
3. shall terminate the SIP session as specified in 3GPP TS 24.282 [8].

On receiving an indication to terminate the session from the signalling plane, the MCData client:

1. if there are further MSRP chunks to send, shall abort transmission of these further MSRP chunks and may indicate to MCData user that the SDS message could not be sent.

[TS 24.582, clause 6.1.1.2.2]

In order to generate an SDS signalling payload, the MCData client:

1. shall generate an SDS SIGNALLING PAYLOAD message as specified in 3GPP TS 24.282 [8]; and
2. shall include the SDS SIGNALLING PAYLOAD message in an application/vnd.3gpp.mcdata-signalling MIME body as specified in 3GPP TS 24.282 [8]; and

When generating a an SDS SIGNALLING PAYLOAD message, the MCData client:

1. shall generate a SDS SIGNALLING PAYLOAD message as defined in 3GPP TS 24.282 [8]. In the SDS SIGNALLING PAYLOAD message, the MCData client:

    a. may include and set the Disposition request type IE to:

        i. "DELIVERY", if only delivery disposition is requested;

        ii. "READ", if only read disposition is requested; or

        iii. "DELIVERY AND READ", if both delivery and read dispositions are requested;

    b. shall set Date and time IE to current UTC time;

    c. shall set Conversation ID IE to a universally unique message ID generated as per IETF RFC 4122 [10];

    d. shall set Message ID IE to a universally unique message ID generated as per IETF RFC 4122 [10];

    e. if indicated that the SDS message is in reply to another SDS message then, shall include the Reply ID IE set to the message identifier of the indicated SDS message; and

    f. if indicated that the target recipient of the SDS message is an application then, shall set Application Identifier IE to the application identifier.

[TS 24.582, clause 6.1.1.2.3]

In order to generate SDS data payload, the MCData client:

1. shall generate a DATA PAYLOAD message as specified in 3GPP TS 24.282 [8]; and

2. shall include the DATA PAYLOAD message in an application/vnd.3gpp.mcdata-payload MIME body as specified in 3GPP TS 24.282 [8].

When generating a DATA PAYLOAD message, the MCData client:

1. shall generate a SDS DATA PAYLOAD message as defined in 3GPP TS 24.282 [8]. In the SDS DATA PAYLOAD message, the MCData client:

    a. shall set Number of payloads IE to the total number of payloads being sent; and

    b. for each payload, shall include Payload IE. In the Payload IE:

        i. shall set Payload content type to "TEXT", or "BINARY", or "HYPERLINKS", or "LOCATION" according to the payload type; and

        ii. shall set Payload data IE to actual payload.

[TS 24.582, clause 6.1.1.2.4]

The MCData client shall take the procedures in subclause 6.4.1 into consideration when generating MSRP SEND messages.

The MCData client shall generate MSRP SEND for SDS message requests according to IETF RFC 4975 [11].

When generating an MSRP SEND for SDS message request containing an SDS SIGNALLING PAYLOAD message and an SDS DATA PAYLOAD message, the MCData client

1. shall set To-Path header according to the MSRP URI(s) received in the answer SDP;

2. shall set the first content type as Content-Type = "application/vnd.3gpp.mcdata-signalling";

3. shall set the first body of the MSRP SEND request to the generated SDS SIGNALLING PAYLOAD message;

4. shall set the second Content-Type as "application/vnd.3gpp.mcdata-payload"; and

5. shall set the second body of the MSRP SEND request to the generated SDS DATA PAYLOAD message.

When generating an MSRP SEND for SDS message request containing only an SDS DATA PAYLOAD message, the MCData client:

1. shall set To-Path header according to the MSRP URI(s) received in the answer SDP;
2. shall set the Content-Type as "application/vnd.3gpp.mcdata-payload"; and
3. shall set the body of the MSRP SEND request to the generated SDS DATA PAYLOAD message.

When generating an MSRP SEND for SDS message request containing only an SDS SIGNALLING PAYLOAD, the MCData client.

1. shall set To-Path header according to the MSRP URI(s) received in the answer SDP;
2. shall set the Content-Type as "application/vnd.3gpp.mcdata-signalling"; and
3. shall set the body of the MSRP SEND request to the generated SDS SIGNALLING PAYLOAD message.

6.1.5.3 Test description

6.1.5.3.1 Pre-test conditions

Test configuration:

- Single cell configuration according to TS 37.579-1 [2] clause 5.2.2.2.1.

Preamble:

- The UE has performed procedure 'Initial registration' as described in TS 37.579-1 [2] clause 5.4.2 with the following clarifications:
  - The <max-payload-size-sds-cplane-bytes> element of the MCData Service Configuration document shall be set to 0 to force the MCData client to send the data using the media plane.
- UE States at the end of the preamble:
  - The UE is in RRC_IDLE state.
  - The client is registered for MCData.

6.1.5.3.2 Test procedure sequence

Table 6.1.5.3.2-1: Main Behaviour

St	Procedure	Message Sequence		TP	Verdict
		U - S	Message		
1	Make the UE (MCData client) send a one-to-one standalone SDS message with disposition request "**DELIVERY**". (NOTE 1)	-	-	-	-
2	Check: Does the UE (MCData client) correctly perform procedure '**CO MCData Call Establishment**' as described in TS 37.579-1 [2] Table 5.3C.2.3-1?	-	-	1,2	P
3-6	Void	-	-	-	-
7	Check: Does the UE (MCData client) correctly perform procedure 'CO MSRP message transfer' as described in TS 37.579-1 [2] Table 5.3C.4.3-1 to **send an SDS message with disposition request "DELIVERY"**?	-	-	2	P
8	Check: Does the UE (MCData client) correctly perform procedure '**CO MCData call release**' as described in TS 37.579-1 [2] Table 5.3C.6.3-1? (NOTE 2)	-	-	3	P
9	Void	-	-	-	-
10	Check: Does the UE (MCData client) correctly perform procedure 'MCX SIP MESSAGE CT' as described in TS 37.579-1 [2] Table 5.3.33.3-1 to **receive the disposition notification** for the SDS message sent at step 7?	-	-	-	-
11	Void	-	-	-	-
12	Check: Does the UE (MCData client) provide the disposition notification to the user? (NOTE 1)	-	-	4	P
NOTE 1: This is expected to be done via a suitable implementation dependent MMI. NOTE 2: The procedure does not release the RRC connection.					

6.1.5.3.3 Specific message contents

Table 6.1.5.3.3-1: SIP INVITE from the UE (step 2, Table 6.1.5.3.2-1; step 2, TS 37.579-1 [2] Table 5.3C.2.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.5.1-1, condition MCDATA_SDS, MCD_1to1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part		**SDP message**		
MIME-part-body	As described in Table 6.1.5.3.3-2			
MIME body part		**MCData-Info**		
MIME-part-body	MCData-Info as described in Table 6.1.5.3.3-3			

Table 6.1.5.3.3-2: SDP for SIP INVITE (Table 6.1.5.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.1.1-3, condition MCDATA_SDS, SDP_OFFER, MCD_1to1

Table 6.1.5.3.3-3: MCData-Info (Table 6.1.5.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.2.1-3, condition MCD_1to1

Table 6.1.5.3.3-4: SIP 200 (OK) from the SS (step 2, Table 6.1.5.3.2-1; step 4, TS 37.579-1 [2] Table 5.3C.2.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.17.1.2-1, condition INVITE-RSP				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
SDP message	As described in Table 6.1.5.3.3-5			

Table 6.1.5.3.3-5: SDP for SIP 200 (OK) (Table 6.1.5.3.3-4)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.1.2-3, condition MCDATA_SDS, SDP_ANSWER

Table 6.1.5.3.3-6: MSRP SEND from the UE (step 7, Table 6.1.5.3.2-1; step 1, TS 37.579-1 [2] Table 5.3C.4.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.12.1.1-1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Content-Type				
media-type	"multipart/mixed"			
data	Message or chunk of message as specified in table 6.1.5.3.3-6A			

Table 6.1.5.3.3-6A: MIME Message (step 7, Table 6.1.5.3.2-1; step 3, TS 37.579-1 [2] Table 5.3C.4.3-1)

Derivation Path: RFC 2046 [38]				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
MIME body part		**MCData Data signalling message**		
MIME-part-headers				
Content-Type	"application/vnd.3gpp. mcdata-signalling"			
MIME-part-body	MCData Protected Payload Message containing SDS SIGNALLING PAYLOAD as described in table 6.1.5.3.3-6B			
MIME body part		**MCData Data message**		
MIME-part-headers				
Content-Type	"application/vnd.3gpp. mcdata-payload"			
MIME-part-body	DATA PAYLOAD as described in Table 6.1.5.3.3-7			

Table 6.1.5.3.3-6B: SDS SIGNALLING PAYLOAD (Table 6.1.5.3.3-6A)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.1-1, condition DELIVERED

Table 6.1.5.3.3-7: Data Payload (Table 6.1.5.3.3-6A)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.9.2-1

Table 6.1.5.3.3-8..9: Void

Table 6.1.5.3.3-10: SIP BYE from the UE (step 8, Table 6.1.5.3.2-1; step 1, TS 37.579-1 [2] Table 5.3C.6.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.2.1-1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Reason			RFC 3326 [125]	
reason-value	"SIP"			
protocol-cause	"cause="200""			
reason-text	"text="transmission succeeded""			

Table 6.1.5.3.3-11: Void

Table 6.1.5.3.3-12: SIP MESSAGE from the SS (step 10, Table 6.1.5.3.2-1; step 2, TS 37.579-1 [2] Table 5.3.33.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.7.2-1, condition MCDATA_SDS, MCDATA_SIGNALLING				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part		**MCData Data signalling message**		
MIME-part-body	MCData Protected Payload Message containing SDS NOTIFICATION as described in Table 6.1.5.3.3-14			

Table 6.1.5.3.3-13: Void

Table 6.1.5.3.3-14: SDS NOTIFICATION (Table 6.1.5.3.3-12)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.4-1, condition DELIVERED

Table 6.1.5.3.3-15: Void

6.1.6 On-network / Short Data Service (SDS) / Standalone SDS Using Media Plane / One-to-one Standalone SDS / Client Terminated (CT)

6.1.6.1 Test Purpose (TP)

(1)

```
with { UE (MCDATA Client) registered and authorised for MCDATA Service }
ensure that {
  when { the MCDATA User receives a SIP INVITE to initiate a standalone one-to-one SDS message using
the media plane }
    then { UE (MCDATA Client) responds by sending a SIP 200 (OK) message }
            }
```

(2)

```
with { UE (MCDATA Client) having responded to the SIP INVITE message that initiated a standalone
one-to-one SDS message using the media plane }
ensure that {
  when { UE (MCDATA Client) receives an MSRP SEND message from the SS (MCDATA Server) }
```

```
    then { UE (MCDATA Client) responds with an MSRP 200 (OK) message and if the MSRP SEND message is
not blank, renders the contents of the Payload IE to the MCDATA User and sends a SIP MESSAGE message
with a disposition notification of "DELIVERED" }
            }
```

(3)

```
with { UE (MCDATA Client) having responded to the MSRP SEND message from the SS (MCDATA server) }
ensure that {
  when { UE (MCDATA Client) receives a SIP BYE message to release communications }
    then { UE (MCDATA Client) responds with a SIP 200 (OK) message }
            }
```

6.1.6.2 Conformance requirements

References: The conformance requirements covered in the current TC are specified in: TS 24.282, clauses 9.2.3.2.4, 9.2.3.2.2, 13.2.2.2.2.2, 9.2.1.3, 12.2.1.1, 6.2.4.1, 6.2.3.1, TS 24.582 clauses 6.1.1.3.1, 6.1.1.3.2. The following represents a copy/paste extraction of the requirements relevant to the test purpose; any references within the copy/paste text should be understood within the scope of the core spec they have been copied from. Unless otherwise stated, these are Rel-14 requirements.

[TS 24.282, clause 9.2.3.2.4]

Upon receipt of an initial SIP INVITE request, the MCData client shall follow the procedures for termination of multimedia sessions in the IM CN subsystem as specified in 3GPP TS 24.229 [5] with the clarifications below.

The MCData client:

1) may reject the SIP INVITE request if either of the following conditions are met:

   a) MCData client does not have enough resources to handle the call; or

   b) any other reason outside the scope of this specification;

   and skip the rest of the steps after step 2;

2) if the SIP INVITE request is rejected in step 1), shall respond toward participating MCData function either with appropriate reject code as specified in 3GPP TS 24.229 [5] and warning texts as specified in subclause 4.9 or with SIP 480 (Temporarily unavailable) response not including warning texts if the user is authorised to restrict the reason for failure and skip the rest of the steps of this subclause;

3) if the SDP offer of the SIP INVITE request contains an "a=key-mgmt" attribute field with a "mikey" attribute value containing a MIKEY-SAKKE I_MESSAGE:

   a) shall extract the MCData ID of the originating MCData user from the initiator field (IDRi) of the I_MESSAGE as described in 3GPP TS 33.180 [26];

   b) shall convert the MCData ID to a UID as described in 3GPP TS 33.180 [26];

   c) shall use the UID to validate the signature of the MIKEY-SAKKE I_MESSAGE as described in 3GPP TS 33.180 [26];

   d) if authentication verification of the MIKEY-SAKKE I_MESSAGE fails, shall reject the SIP INVITE request with a SIP 488 (Not Acceptable Here) response as specified in IETF RFC 4567 [45], and include warning text set to "136 authentication of the MIKEY-SAKKE I_MESSAGE failed" in a Warning header field as specified in subclause 4.9 and not continue with rest of the steps in this subclause; and

   e) if the signature of the MIKEY-SAKKE I_MESSAGE was successfully validated:

      i) shall extract and decrypt the encapsulated PCK using the terminating user's (KMS provisioned) UID key as described in 3GPP TS 33.180 [26]; and

      ii) shall extract the PCK-ID, from the payload as specified in 3GPP TS 33.180 [26];

NOTE: With the PCK successfully shared between the originating MCData client and the terminating MCData client, both clients are able to create an end-to-end secure session.

3) may display to the MCData user the MCData ID of the inviting MCData user and the type of SDS request;

4) shall accept the SIP INVITE request and generate a SIP 200 (OK) response according to rules and procedures of 3GPP TS 24.229 [5];

5) shall include the option tag "timer" in a Require header field of the SIP 200 (OK) response;

6) shall include the Session-Expires header field in the SIP 200 (OK) response and start the SIP session timer according to IETF RFC 4028 [38]. The "refresher" parameter in the Session-Expires header field shall be set to "uas";

7) shall include the g.3gpp.mcdata.sds media feature tag in the Contact header field of the SIP 200 (OK) response;

8) shall include the g.3gpp.icsi-ref media feature tag containing the value of "urn:urn-7:3gpp-service.ims.icsi.mcdata.sds" in the Contact header field of the SIP 200 (OK) response;

9) shall include an SDP answer in the SIP 200 (OK) response to the SDP offer in the incoming SIP INVITE request according to 3GPP TS 24.229 [5] with the clarifications given in subclause 9.2.3.2.2; and

10) shall send the SIP 200 (OK) response towards the MCData server according to rules and procedures of 3GPP TS 24.229 [5].

On receipt of an SIP ACK message to the sent SIP 200 (OK) message, the MCData client shall:

1) shall interact with the media plane as specified in 3GPP TS 24.582 [15] subclause 6.1.1.3.

[TS 24.282, clause 9.2.3.2.2]

When the MCData client receives an initial SDP offer for an MCData standalone SDS, the MCData client shall process the SDP offer and shall compose an SDP answer according to 3GPP TS 24.229 [5] and IETF RFC 4975 [17].

When composing an SDP answer, the MCData client:

1) shall include an "m=message" media-level section for the accepted MCData media stream consisting of:

   a) the port number;

   b) a protocol field value of "TCP/MSRP", or "TCP/TLS/MSRP" for TLS according to the received SDP offer;

   c) a format list field set to '*';

   d) an "a=recvonly" attribute;

   e) an "a=path" attribute containing its own MSRP URI;

   f) set the content type as a=accept-types: application/vnd.3gpp.mcdata-signalling application/vnd.3gpp.mcdata-payload; and

   g) set the a=setup attribute according to IETF RFC 6135 [19].

[TS 24.282, clause 13.2.2.2.2.2]

Upon receiving a SIP BYE request, the MCData client:

1) shall send SIP 200 (OK) response towards MCData server according to 3GPP TS 24.229 [5]; and

2) shall release all media plane resources corresponding to the MCData communication being released.

NOTE: Partially received data can be stored and processed.

[TS 24.282, clause 9.2.1.3]

To handle the disposition requests, the MCData client:

1) If the SDS disposition request type IE is set to:

   a) "DELIVERY" then, shall send a delivered notification as described in subclause 12.2.1.1;

b) "READ", shall send a read notification as described in subclause 12.2.1.1, when a display indication is received; or

c) "DELIVERY AND READ" then, shall start timer TDU1 (delivery and read).

Upon receiving a display indication before timer TDU1 (delivery and read) expires, the MCData client:

1) shall stop timer TDU1 (delivery and read); and

2) shall send a delivered and read notification as described in subclause 12.2.1.1.

Upon expiry of timer TDU1 (delivery and read), the MCData client:

1) shall send a delivered notification as described in subclause 12.2.1.1; and

2) upon receiving a display indication, send a read notification as described in subclause 12.2.1.1.

[TS 24.282, clause 12.2.1.1]

The MCData client shall follow the procedures in this subclause to:

- indicate to an MCData client that an SDS message was delivered, read or delivered and read when the originating client requested a delivery, read or delivery and read report;

- indicate to the participating MCData function serving the MCData user that an SDS message was undelivered. The participating MCData function can store the message for later re-delivery;

- indicate to an MCData client that a request for FD was accepted, deferred or rejected; or

- indicate to an MCData client that a file download has been completed;

Before sending a disposition notification the MCData client needs to determine:

- the controlling MCData function that sent the SDS or FD message request. The MCData client determines the controlling MCData function from the contents of the <mcdata-controller-psi> element contained in the application/vnd.3gpp.mcdata-info+xml MIME body of the incoming SDS or FD message request;

- the group identity related to an SDS or FD message request received as part of a group communication. The MCData client determines the group identity from the contents of the <mcdata-calling-group-id> element contained in the application/vnd.3gpp.mcdata-info+xml MIME body of the incoming SDS or FD message request; and

- the MCData user targeted for the disposition notification. The MCData client determines the targeted MCData user from the contents of the <mcdata-calling-user-id> element contained in the application/vnd.3gpp.mcdata-info+xml MIME body of the incoming SDS or FD message request.

The MCData client shall generate a SIP MESSAGE request in accordance with 3GPP TS 24.229 [5] and IETF RFC 3428 [6] with the clarifications given below.

The MCData client:

1) shall build the SIP MESSAGE request as specified in subclause 6.2.4.1;

2) shall follow the rules specified in subclause 6.4 for the handling of MIME bodies in a SIP message when processing the remaining steps in this subclause;

3) shall insert in the SIP MESSAGE request an application/resource-lists+xml MIME body containing the MCData ID of the targeted MCData user, according to rules and procedures of IETF RFC 5366 [18];

4) shall insert in the SIP MESSAGE request an application/vnd.3gpp.mcdata-info+xml MIME body with an <mcdata-controller-psi> element containing the PSI of the controlling MCData function;

5) if sending a disposition notification in response to an MCData group data request, shall include an <mcdata-calling-group-id> element set to the MCData group identity in the application/vnd.3gpp.mcdata-info+xml MIME body;

6) if requiring to send an SDS notification, shall generate an SDS NOTIFICATION message and include it in the SIP MESSAGE request as specified in subclause 6.2.3.1;

7) if requiring to send an FD notification, shall generate an FD NOTIFICATION message and include it in the SIP MESSAGE request as specified in subclause 6.2.3.2; and

8) shall send the SIP MESSAGE request according to rules and procedures of 3GPP TS 24.229 [5].

[TS 24.282, clause 6.2.4.1]

This subclause is referenced from other procedures.

In a SIP MESSAGE request, the MCData client:

1) when sending SDS messages or SDS disposition notifications:

   a) shall include an Accept-Contact header field containing the g.3gpp.mcdata.sds media feature tag along with the "require" and "explicit" header field parameters according to IETF RFC 3841 [8];

   b) shall include an Accept-Contact header field with the media feature tag g.3gpp.icsi-ref containing the value of "urn:urn-7:3gpp-service.ims.icsi.mcdata.sds" along with the "require" and "explicit" header field parameters according to IETF RFC 3841 [8]; and

   c) shall include the ICSI value "urn:urn-7:3gpp-service.ims.icsi.mcdata.sds" (coded as specified in 3GPP TS 24.229 [5]), in a P-Preferred-Service header field according to IETF RFC 6050 [7] in the SIP MESSAGE request;

2) when sending FD messages, FD disposition notifications or FD media storage function discovery messages:

   a) shall include an Accept-Contact header field containing the g.3gpp.mcdata.fd media feature tag along with the "require" and "explicit" header field parameters according to IETF RFC 3841 [8];

   b) shall include an Accept-Contact header field with the media feature tag g.3gpp.icsi-ref containing the value of "urn:urn-7:3gpp-service.ims.icsi.mcdata.fd" along with the "require" and "explicit" header field parameters according to IETF RFC 3841 [8]; and

   c) shall include the ICSI value "urn:urn-7:3gpp-service.ims.icsi.mcdata.fd" (coded as specified in 3GPP TS 24.229 [5]), in a P-Preferred-Service header field according to IETF RFC 6050 [7] in the SIP MESSAGE request;

3) may include a P-Preferred-Identity header field in the SIP MESSAGE request containing a public user identity as specified in 3GPP TS 24.229 [5]; and

4) shall set the Request-URI to the public service identity identifying the participating MCData function serving the MCData user.

[TS 24.282, clause 6.2.3.1]

In order to generate an SDS notification, the MCData client:

1) shall generate an SDS NOTIFICATION message as specified in subclause 15.1.5; and

2) shall include in the SIP request, the SDS NOTIFICATION message in an application/vnd.3gpp.mcdata-signalling MIME body as specified in subclause E.1.

When generating an SDS NOTIFICATION message as specified in subclause 15.1.5, the MCData client:

1) if sending a delivered notification, shall set the SDS disposition notification type IE as "DELIVERED" as specified in subclause 15.2.5;

2) if sending a read notification, shall set the SDS disposition notification type IE as "READ" as specified in subclause 15.2.5;

3) if sending a delivered and read notification, shall set the SDS disposition notification type IE as "DELIVERED AND READ" as specified in subclause 15.2.5;

4) if the SDS message could not be delivered to the user or application (e.g. due to lack of storage), shall set the SDS disposition notification type IE as "UNDELIVERED" as specified in subclause 15.2.5;

5) shall set the Date and time IE to the current time to as specified in subclause 15.2.8;

6) shall set the Conversation ID to the value of the Conversation ID that was received in the SDS message as specified in subclause 15.2.9;

7) shall set the Message ID to the value of the Message ID that was received in the SDS message as specified in subclause 15.2.10;

8) if the SDS message was destined for the user, shall not include an Application ID IE as specified in subclause 15.2.7; and

9) if the SDS message was destined for an application, shall include an Application ID IE set to the value of the Application ID that was included in the SDS message as specified in subclause 15.2.3.

[TS 24.582, clause 6.1.1.3.1]

Upon receiving an indication to establish MSRP connection for standalone SDS using media plane as the terminating client, the MCData client:

1. shall act as an MSRP client according to IETF RFC 6135 [12];

2. shall act either as an active endpoint or as an passive endpoint to open the transport connection, according to IETF RFC 6135 [12];

3. shall establish the MSRP connection according to the MSRP connection parameters in the SDP offer received in the SIP INVITE request according to IETF RFC 4975 [11];

4. if acting as an "active" endpoint, shall send an empty MSRP SEND request to bind the MSRP connection to the MSRP session from the perspective of the passive endpoint according to the rules and procedures of IETF RFC 4975 [11] and IETF RFC 6135 [12];

Once the MSRP connection is established, the MCData client:

1. on receipt of an MSRP request in an MSRP session, shall follow the rules and procedures defined in IETF RFC 4975 [11] and in IETF RFC 6714 [13];

2. If an MSRP SEND request indicates the use of chunking, shall wait until all further MSRP SEND requests for the remaining chunks have been received and shall reassemble the entire set of MSRP requests into the MCData standalone message before delivering the content to the application; and

3. shall handle the received content as described in subclause 6.1.1.3.2.

[TS 24.582, clause 6.1.1.3.2]

The MCData client:

1. shall decode the contents of the application/vnd.3gpp.mcdata-signalling MIME body;

2. shall decode the contents of the application/vnd.3gpp.mcdata-payload MIME body;

3. if the SDS SIGNALLING PAYLOAD message contains a new Conversation ID, shall instantiate a new conversation with the Message ID in the SDS SIGNALLING PAYLOAD identifying the first message in the conversation thread;

4. if the SDS SIGNALLING PAYLOAD message contains an existing Conversation ID and:

   a. if the SDS SIGNALLING PAYLOAD message does not contain an InReplyTo Message ID, shall use the Message ID in the SDS SIGNALLING PAYLOAD to identify a new message in the existing conversation thread; and

   b. if the SDS SIGNALLING PAYLOAD message contains an InReplyTo Message ID, shall associate the message to an existing message in the conversation thread as identified by the InReplyTo Message ID in the SDS SIGNALLING PAYLOAD and use the Message ID in the SDS SIGNALLING PAYLOAD to identify the new message;

5. shall identify the number of Payload IEs in the DATA PAYLOAD message from the Number of Payloads IE in the DATA PAYLOAD message;
6. if the SDS SIGNALLING PAYLOAD message does not contain an Application identifier IE:
   a. shall determine that the payload contained in the DATA PAYLOAD message is for user consumption;
   b. may notify the MCData user; and
   c. shall render the contents of the Payload IE(s) to the MCData user;
7. if the SDS SIGNALLING PAYLOAD message contains an Application identifier IE:
   a. shall determine that the payload contained in the DATA PAYLOAD message is not for user consumption;
   b. shall not notify the MCData user;
   c. if the Application identifier value is unknown, shall discard the SDS message; and
   d. if the Application identifier value is known, shall deliver the contents of the Payload IE(s) to the identified application; and
8. if SDS Disposition request type IE is present in the SDS SIGNALLING PAYLOAD message received in subclause 6.1.1.3.1 then, shall send a disposition notification as described in 3GPP TS 24.282 [8] subclause 9.2.1.3.

6.1.6.3 Test description

6.1.6.3.1 Pre-test conditions

Test configuration:

- Single cell configuration according to TS 37.579-1 [2] clause 5.2.2.2.1.

Preamble:

- The UE has performed procedure 'Initial registration' as described in TS 37.579-1 [2] clause 5.4.2 with the following clarifications:
  - The <max-payload-size-sds-cplane-bytes> element of the MCData Service Configuration document shall be set to 0 to force the MCData client to send the data using the media plane.
- UE States at the end of the preamble:
  - The UE is in RRC_IDLE state.
  - The client is registered for MCData.

6.1.6.3.2 Test procedure sequence

Table 6.1.6.3.2-1: Main Behaviour

St	Procedure	Message Sequence		TP	Verdict
		U - S	Message		
1	Check: Does the UE (MCData client) correctly perform procedure '**CT MCData Call Establishment**' as described in TS 37.579-1 [2] Table 5.3C.3.3-1?	-	-	1,2	P
2-5	Void	-	-	-	-
6	Check: Does the UE (MCData client) correctly perform procedure 'CT MSRP message transfer' as described in TS 37.579-1 [2] Table 5.3C.5.3-1 to **receive an SDS message with disposition request "DELIVERY"**?	-	-	2	P
7	Void	-	-	-	-
8	Check: Does the UE (MCData client) correctly perform procedure '**CT MCData call release**' as described in TS 37.579-1 [2] Table 5.3C.7.3-1? (NOTE 2)	-	-	3	P
9-10	Void	-	-	-	-
11	Check: Does the UE (MCData client) correctly perform procedure '**CO SDS or FD message transfer** using signalling plane' as described in TS 37.579-1 [2] Table 5.3C.1.3-1 to **send a disposition notification of "DELIVERED"**?	-	-	2	P
12	Check: Does the UE (MCData client) provide the contents of the Payload IE to the user? (NOTE 1)	-	-	2	P
NOTE 1: This is expected to be done via a suitable implementation dependent MMI. NOTE 2: The procedure does not release the RRC connection.					

6.1.6.3.3 Specific message contents

Table 6.1.6.3.3-1: SIP INVITE from the SS (step 1, Table 6.1.6.3.2-1; step 2, TS 37.579-1 [2] Table 5.3C.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.5.2-1, condition MCDATA_SDS				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part		**SDP message**		
MIME-part-body	SDP message as described in Table 6.1.6.3.3-2			
MIME body part		**MCData-Info**		
MIME-part-body	MCData-Info as described in Table 6.1.6.3.3-3			

Table 6.1.6.3.3-2: SDP for SIP INVITE (Table 6.1.6.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.1.2-3, condition MCDATA_SDS, SDP_OFFER, MCD_1to1

Table 6.1.6.3.3-3: MCData-Info (Table 6.1.6.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.2.2-3, condition MCD_1to1

Table 6.1.6.3.3-4: SIP 200 (OK) from the UE (step 1, Table 6.1.6.3.2-1; step 4, TS 37.579-1 [2] Table 5.3C.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.17.1.1-1, condition INVITE-RSP, MCDATA_SDS				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Content-Type				
value	"application/sdp"			
Message-body				
SDP message	As described in Table 6.1.6.3.3-5			

Table 6.1.6.3.3-5: SDP for SIP 200 (OK) (Table 6.1.6.3.3-4)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.1.1-3, condition MCDATA_SDS, SDP_ANSWER

Table 6.1.6.3.3-6: MSRP SEND from the SS (step 6, Table 6.1.6.3.2-1; step 1, TS 37.579-1 [2] Table 5.3C.5.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.12.1.2-1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Content-Type				
media-type	"multipart/mixed"			
data	Message as specified in table 6.1.6.3.3-6A			

Table 6.1.6.3.3-6A: MIME Message (step 6, Table 6.1.6.3.2-1; step 1, TS 37.579-1 [2] Table 5.3C.5.3-1)

Derivation Path: RFC 2046 [38]				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
MIME body part		**MCData Data signalling message**		
MIME-part-headers				
Content-Type	"application/vnd.3gpp. mcdata-signalling"			
MIME-part-body	MCData Protected Payload Message containing SDS SIGNALLING PAYLOAD as described in table 6.1.6.3.3-6B			
MIME body part		**MCData Data message**		
MIME-part-headers				
Content-Type	"application/vnd.3gpp. mcdata-payload"			
MIME-part-body	DATA PAYLOAD as described in Table 6.1.6.3.3-7			

Table 6.1.6.3.3-6B: SDS SIGNALLING PAYLOAD (Table 6.1.6.3.3-6A)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.2-1, condition DELIVERED

Table 6.1.6.3.3-7: Data Payload (Table 6.1.6.3.3-6A)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.9.2-2

Table 6.1.6.3.3-8: SIP BYE from the SS (step 8, Table 6.1.6.3.2-1; step 1, TS 37.579-1 [2] Table 5.3C.7.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.2.2-1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Reason			RFC 3326 [125]	
reason-value	"SIP"			
protocol-cause	"cause="200""			
reason-text	"text="transmission succeeded""			

Table 6.1.6.3.3-9: Void

Table 6.1.6.3.3-10: SIP MESSAGE from the UE (step 11, Table 6.1.6.3.2-1; step 2, TS 37.579-1 [2] Table 5.3C.1.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.7.1-1, condition MCDATA_SDS, RESOURCE_LISTS, MCDATA_SIGNALLING				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part	not present	**MCData-Info**		
MIME body part		**MCData Data signalling message**		
MIME-part-body	MCData Protected Payload Message containing SDS NOTIFICATION as described in Table 6.1.6.3.3-11			

Table 6.1.6.3.3-11: SDS NOTIFICATION (Table 6.1.6.3.3-10)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.3-1, condition DELIVERED

6.1.7 On-network / Short Data Service (SDS) / Standalone SDS Using Media Plane / Group Standalone SDS / Client Originated (CO)

6.1.7.1 Test Purpose (TP)

(1)

```
with { UE (MCDATA Client) registered and authorised for MCDATA Service }
ensure that {
  when { the MCDATA User requests to send a group standalone SDS message using the media plane}
    then { UE (MCDATA Client) sends a request to establish an MSRP connection via a SIP INVITE
message and then responds to the SIP 200 (OK) message with a SIP ACK message }
            }
```

(2)

```
with { UE (MCDATA Client) having requested the establishment of a MSRP connection }
ensure that {
  when { UE (MCDATA Client) receives a SIP 200 (OK) message with the a=setup attribute set to
"passive" }
    then { UE (MCDATA Client) sends a blank MSRP SEND message to bind the MSRP connection and then
sends the group standalone SDS message via a MSRP SEND message with a disposition of "DELIVERY" }
            }
```

(3)

```
with { UE (MCDATA Client) having sent a group standalone SDS message using the media plane }
```

```
ensure that {
  when { UE (MCDATA Client) receives a MSRP 200 (OK) message in response to the last MSRP SEND
message indicating that the standalone SDS message has been successfully transferred }
    then { UE (MCDATA Client) sends a SIP BYE message }
            }
```

(4)

```
with { UE (MCDATA Client) having sent a group standalone SDS message using the media plane with a
disposition of "DELIVERY" }
ensure that {
  when { UE (MCDATA Client) receives a disposition response via a SIP MESSAGE message }
    then { UE (MCDATA Client) responds to the SIP MESSAGE message by sending a SIP 200 (OK) message
and delivers the notification to the MCDATA User }
            }
```

6.1.7.2 Conformance requirements

References: The conformance requirements covered in the current TC are specified in: TS 24.282, clauses 9.2.3.2.3, 9.2.3.2.1, 13.2.2.2.2.1, 12.2.1.2, TS 24.582 clauses 6.1.1.2.1, 6.1.1.2.2, 6.1.1.2.3, 6.1.1.2.4. The following represents a copy/paste extraction of the requirements relevant to the test purpose; any references within the copy/paste text should be understood within the scope of the core spec they have been copied from. Unless otherwise stated, these are Rel-14 requirements.

[TS 24.282, clause 9.2.3.2.3]

The MCData client shall generate a SIP INVITE request in accordance with 3GPP TS 24.229 [5] with the clarifications given below.

The MCData client:

1) shall include the g.3gpp.mcdata.sds media feature tag and the g.3gpp.icsi-ref media feature tag with the value of "urn:urn-7:3gpp-service.ims.icsi.mcdata.sds" in the Contact header field of the SIP INVITE request according to IETF RFC 3840 [16];

2) shall include an Accept-Contact header field containing the g.3gpp.mcdata.sds media feature tag along with the "require" and "explicit" header field parameters according to IETF RFC 3841 [8];

3) shall include an Accept-Contact header field with the g.3gpp.icsi-ref media feature tag containing the value of "urn:urn-7:3gpp-service.ims.icsi.mcdata.sds" along with the "require" and "explicit" header field parameters according to IETF RFC 3841 [8];

4) shall include the ICSI value "urn:urn-7:3gpp-service.ims.icsi.mcdata.sds" (coded as specified in 3GPP TS 24.229 [5]), in a P-Preferred-Service header field according to IETF RFC 6050 [7] in the SIP INVITE request;

5) should include the "timer" option tag in the Supported header field;

6) should include the Session-Expires header field according to IETF RFC 4028 [38]. It is recommended that the "refresher" header field parameter is omitted. If included, the "refresher" header field parameter shall be set to "uac";

7) if a one-to-one standalone SDS message is to be sent:

   a) shall insert in the SIP INVITE request a MIME resource-lists body with the MCData ID of the invited MCData user, according to rules and procedures of IETF RFC 5366 [18];

   b) shall contain an application/vnd.3gpp.mcdata-info+xml MIME body with the <mcdatainfo> element containing the <mcdata-Params> element with:

      i) the <request-type> element set to a value of "one-to-one-sds"; and

   c) if an end-to-end security context needs to be established and the security context does not exist or if the existing security context has expired, then:

      i) if necessary, shall instruct the key management client to request keying material from the key management server as described in 3GPP TS 33.180 [26];

ii) shall use the keying material to generate a PCK as described in 3GPP TS 33.180 [26];

iii) shall use the PCK to generate a PCK-ID with the four most significant bits set to "0001" to indicate that the purpose of the PCK is to protect one-to-one communications and with the remaining twenty eight bits being randomly generated as described in 3GPP TS 33.180 [26];

iv) shall encrypt the PCK to a UID associated to the MCData client using the MCData ID of the invited user and a time related parameter as described in 3GPP TS 33.180 [26];

v) shall generate a MIKEY-SAKKE I_MESSAGE using the encapsulated PCK and PCK-ID as specified in 3GPP TS 33.180 [26];

vi) shall add the MCData ID of the originating MCData to the initiator field (IDRi) of the I_MESSAGE as described in 3GPP TS 33.180 [26]; and

vii) shall sign the MIKEY-SAKKE I_MESSAGE using the originating MCData user's signing key provided in the keying material together with a time related parameter, and add this to the MIKEY-SAKKE payload, as described in 3GPP TS 33.180 [26];

…

9) shall set the Request-URI of the SIP INVITE request to the public service identity identifying the participating MCData function serving the MCData user;

NOTE 2: The MCData client is configured with public service identity identifying the participating MCData function serving the MCData user.

10) may include a P-Preferred-Identity header field in the SIP INVITE request containing a public user identity as specified in 3GPP TS 24.229 [5];

11) shall include an SDP offer according to 3GPP TS 24.229 [5] with the clarifications given in subclause 9.2.3.2.1; and

12) shall send the SIP INVITE request towards the MCData server according to 3GPP TS 24.229 [5].

On receipt of a SIP 2xx response to the SIP INVITE request, the MCData client:

1) shall send a SIP ACK request as specified in 3GPP TS 24.229 [5];

2) shall start the SIP Session timer according to rules and procedures of IETF RFC 4028 [38]; and

3) shall interact with the media plane as specified in 3GPP TS 24.582 [15] subclause 6.1.1.2.

…

On receipt of an indication from the media plane indicating that the standalone SDS message has been successfully transferred, the MCData client shall:

1) shall generate a SIP BYE request according to 3GPP TS 24.229 [5] with:

   a) Reason code set to "SIP";

   b) cause set to "200"; and

   c) text set to "transmission succeeded";

2) shall set the Request-URI to the MCData session identity to release; and

3) shall send a SIP BYE request towards MCData server according to 3GPP TS 24.229 [5].

Upon receiving a SIP 200 (OK) response to the SIP BYE request, the MCData client shall interact with the media plane and indicate to terminate the session, as specified in 3GPP TS 24.582 [15].

[TS 24.282, clause 9.2.3.2.1]

When composing an SDP offer according to 3GPP TS 24.229 [5], IETF RFC 4975 [17], IETF RFC 6135 [19] and IETF RFC 6714 [20] the MCData client:

1) shall include an "m=message" media-level section for the MCData media stream consisting of:

   a) the IP address and the port number;

   b) a protocol field value of "TCP/MSRP", or "TCP/TLS/MSRP" for TLS;

   c) a format list field set to '*';

   d) an "a=sendonly" attribute;

   e) an "a=path" attribute containing its own MSRP URI;

   f) set the content type as "a=accept-types:application/vnd.3gpp.mcdata-signalling application/vnd.3gpp.mcdata-payload"; and

   g) set the a=setup attribute as "actpass"; and

2) if end-to-end security is required for a one-to-one communication and the security context does not exist or if the existing security context has expired, shall include the MIKEY-SAKKE I_MESSAGE in an "a=key-mgmt" attribute as a "mikey" attribute value in the SDP offer as specified in IETF RFC 4567 [45].

[TS 24.282, clause 13.2.2.2.2.1]

When the MCData client wants to release a MCData communication established over the media plane, the MCData client:

1) shall generate a SIP BYE request according to 3GPP TS 24.229 [5];

2) shall set the Request-URI to the MCData session identity to be released; and

3) shall send the SIP BYE request towards MCData server according to 3GPP TS 24.229 [5].

Upon receiving a SIP 200 (OK) response to the SIP BYE request, the MCData client shall release all media plane resources corresponding to the MCData communication being released.

[TS 24.282, clause 12.2.1.2]

Upon receipt of a:

"SIP MESSAGE request for SDS disposition notification for terminating MCData client"; or

"SIP MESSAGE request for FD disposition notification for terminating MCData client";

the MCData client:

1) shall decode the contents of the application/vnd.3gpp.mcdata-signalling MIME body; and

2) shall deliver the notification to the user or application.

[TS 24.582, clause 6.1.1.2.1]

Upon receiving an indication to establish MSRP connection for standalone SDS using media plane as the originating client, the MCData client:

1. shall act as an MSRP client according to IETF RFC 6135 [12];

2. shall act according to IETF RFC 6135 [12], as:

   a. an "active" endpoint, if a=setup attribute in the received SDP answer is set to "passive"; and

   b. an "passive" endpoint, if a=setup attribute in the received SDP answer is set to "active";

3. shall establish the MSRP connection according to the MSRP connection parameters in the SDP answer received in the SIP 200 (OK) response according to IETF RFC 4975 [11]; and

4. if acting as an "active" endpoint, shall send an empty MSRP SEND request to bind the MSRP connection to the MSRP session from the perspective of the passive endpoint according to the rules and procedures of IETF RFC 4975 [11] and IETF RFC 6135 [12].

On receiving MSRP 200 (OK) response to the first MSRP SEND request, the MCData client:

1. shall generate a SDS SIGNALLING PAYLOAD as specified in subclause 6.1.1.2.2;
2. shall generate a SDS DATA PAYLOAD as specified in subclause 6.1.1.2.3;
3. shall include the SDS SIGNALLING PAYLOAD and SDS DATA PAYLOAD in an MSRP SEND request as specified in subclause 6.1.1.2.4; and
4. shall send the MSRP SEND request on the established MSRP connection.

NOTE: MSRP chunking, if needed, may affect the number of "Content Type" lines in each MSRP SEND message conveying a chunk, as also specified in subclause 6.1.1.2.4.

If MSRP chunking is not used then on receipt of a 200 (OK) response, the MCData client shall terminate the SIP session as specified in 3GPP TS 24.282 [8].

If MSRP chunking is used, the MCData client:

1. shall send further MSRP SEND requests as necessary;
2. shall wait for a 200 (OK) response to each MSRP SEND request sent; and
3. on receipt of the last 200 (OK) response shall terminate the SIP session as specified in 3GPP TS 24.282 [8].

On receiving a non-200 MSRP response to the MSRP SEND request the MCData client shall handle the error as specified in IETF RFC 4975 [11]. To terminate the MSRP session, the MCData client:

1. if there are further MSRP chunks to send, shall abort transmission of these further MSRP chunks;
2. shall indicate to MCData user that the SDS message could not be sent; and
3. shall terminate the SIP session as specified in 3GPP TS 24.282 [8].

On receiving an indication to terminate the session from the signalling plane, the MCData client:

1. if there are further MSRP chunks to send, shall abort transmission of these further MSRP chunks and may indicate to MCData user that the SDS message could not be sent.

[TS 24.582, clause 6.1.1.2.2]

In order to generate an SDS signalling payload, the MCData client:

1. shall generate an SDS SIGNALLING PAYLOAD message as specified in 3GPP TS 24.282 [8]; and
2. shall include the SDS SIGNALLING PAYLOAD message in an application/vnd.3gpp.mcdata-signalling MIME body as specified in 3GPP TS 24.282 [8]; and

When generating a an SDS SIGNALLING PAYLOAD message, the MCData client:

1. shall generate a SDS SIGNALLING PAYLOAD message as defined in 3GPP TS 24.282 [8]. In the SDS SIGNALLING PAYLOAD message, the MCData client:
    a. may include and set the Disposition request type IE to:
        i. "DELIVERY", if only delivery disposition is requested;
        ii. "READ", if only read disposition is requested; or
        iii. "DELIVERY AND READ", if both delivery and read dispositions are requested;
    b. shall set Date and time IE to current UTC time;
    c. shall set Conversation ID IE to a universally unique message ID generated as per IETF RFC 4122 [10];
    d. shall set Message ID IE to a universally unique message ID generated as per IETF RFC 4122 [10];

e. if indicated that the SDS message is in reply to another SDS message then, shall include the Reply ID IE set to the message identifier of the indicated SDS message; and

f. if indicated that the target recipient of the SDS message is an application then, shall set Application Identifier IE to the application identifier.

[TS 24.582, clause 6.1.1.2.3]

In order to generate SDS data payload, the MCData client:

1. shall generate a DATA PAYLOAD message as specified in 3GPP TS 24.282 [8]; and
2. shall include the DATA PAYLOAD message in an application/vnd.3gpp.mcdata-payload MIME body as specified in 3GPP TS 24.282 [8].

When generating a DATA PAYLOAD message, the MCData client:

1. shall generate a SDS DATA PAYLOAD message as defined in 3GPP TS 24.282 [8]. In the SDS DATA PAYLOAD message, the MCData client:
   a. shall set Number of payloads IE to the total number of payloads being sent; and
   b. for each payload, shall include Payload IE. In the Payload IE:
      i. shall set Payload content type to "TEXT", or "BINARY", or "HYPERLINKS", or "LOCATION" according to the payload type; and
      ii. shall set Payload data IE to actual payload.

[TS 24.582, clause 6.1.1.2.4]

The MCData client shall take the procedures in subclause 6.4.1 into consideration when generating MSRP SEND messages.

The MCData client shall generate MSRP SEND for SDS message requests according to IETF RFC 4975 [11].

When generating an MSRP SEND for SDS message request containing an SDS SIGNALLING PAYLOAD message and an SDS DATA PAYLOAD message, the MCData client

1. shall set To-Path header according to the MSRP URI(s) received in the answer SDP;
2. shall set the first content type as Content-Type = "application/vnd.3gpp.mcdata-signalling";
3. shall set the first body of the MSRP SEND request to the generated SDS SIGNALLING PAYLOAD message;
4. shall set the second Content-Type as "application/vnd.3gpp.mcdata-payload"; and
5. shall set the second body of the MSRP SEND request to the generated SDS DATA PAYLOAD message.

When generating an MSRP SEND for SDS message request containing only an SDS DATA PAYLOAD message, the MCData client:

1. shall set To-Path header according to the MSRP URI(s) received in the answer SDP;
2. shall set the Content-Type as "application/vnd.3gpp.mcdata-payload"; and
3. shall set the body of the MSRP SEND request to the generated SDS DATA PAYLOAD message.

When generating an MSRP SEND for SDS message request containing only an SDS SIGNALLING PAYLOAD, the MCData client.

1. shall set To-Path header according to the MSRP URI(s) received in the answer SDP;
2. shall set the Content-Type as "application/vnd.3gpp.mcdata-signalling"; and
3. shall set the body of the MSRP SEND request to the generated SDS SIGNALLING PAYLOAD message.

6.1.7.3 Test description

6.1.7.3.1 Pre-test conditions

Test configuration:

- Single cell configuration according to TS 37.579-1 [2] clause 5.2.2.2.1.

Preamble:

- The UE has performed procedure 'Initial registration' as described in TS 37.579-1 [2] clause 5.4.2 with the following clarifications:
  - The <max-payload-size-sds-cplane-bytes> element of the MCData Service Configuration document shall be set to 0 to force the MCData client to send the data using the media plane.
- UE States at the end of the preamble:
  - The UE is in RRC_IDLE state.
  - The client is registered for MCData.

6.1.7.3.2 Test procedure sequence

Table 6.1.7.3.2-1: Main Behaviour

St	Procedure	Message Sequence		TP	Verdict
		U - S	Message		
1	Make the UE (MCData client) send a group standalone SDS message with disposition request "**DELIVERY**". (NOTE 1)	-	-	-	-
2	Check: Does the UE (MCData client) correctly perform procedure '**CO MCData Call Establishment**' as described in TS 37.579-1 [2] Table 5.3C.2.3-1?	-	-	1,2	P
3-6	Void	-	-	-	-
7	Check: Does the UE (MCData client) correctly perform procedure '**CO MSRP message transfer**' as described in TS 37.579-1 [2] Table 5.3C.4.3-1 **to send an SDS message with disposition request "DELIVERY"**?	-	-	2	P
8	Check: Does the UE (MCData client) correctly perform procedure '**CO MCData call release**' as described in TS 37.579-1 [2] Table 5.3C.6.3-1? (NOTE 2)	-	-	3	P
9	Void	-	-	-	-
10	Check: Does the UE (MCData client) correctly perform procedure '**MCX SIP MESSAGE CT**' as described in TS 37.579-1 [2] Table 5.3.33.3-1 **to receive the disposition notification** for the SDS message sent at step 7?	-	-	4	P
11	Void	-	-	-	-
12	Check: Does the UE (MCData client) provide the disposition notification to the user? (NOTE 1)	-	-	4	P
NOTE 1: This is expected to be done via a suitable implementation dependent MMI. NOTE 2: The procedure does not release the RRC connection.					

6.1.7.3.3 Specific message contents

Table 6.1.7.3.3-1: SIP INVITE from the UE (step 2, Table 6.1.7.3.2-1; step 2, TS 37.579-1 [2] Table 5.3C.2.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.5.1-1, condition MCDATA_SDS				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part		**SDP message**		
MIME-part-body	As described in Table 6.1.7.3.3-1A			
MIME body part		**MCData-Info**		
MIME-part-body	MCData-Info as described in Table 6.1.7.3.3-2			

Table 6.1.7.3.3-1A: SDP for SIP INVITE (Table 6.1.7.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.1.1-3, condition MCDATA_SDS, SDP_OFFER

Table 6.1.7.3.3-2: MCData-Info (Table 6.1.7.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.2.1-3, condition MCD_grp

Table 6.1.7.3.3-3: SIP 200 (OK) from the SS (step 2, Table 6.1.7.3.2-1; step 4, TS 37.579-1 [2] Table 5.3C.2.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.17.1.2-1, condition INVITE-RSP				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
SDP message	As described in Table 6.1.7.3.3-4			

Table 6.1.7.3.3-4: SDP for SIP 200 (OK) (Table 6.1.7.3.3-3)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.1.2-3, condition MCDATA_SDS, SDP_ANSWER

Table 6.1.7.3.3-5: MSRP SEND from the UE (step 7, Table 6.1.7.3.2-1; step 1, TS 37.579-1 [2] Table 5.3C.4.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.12.1.1-1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Content-Type				
media-type	"multipart/mixed"			
data	Message or chunk of message as specified in table 6.1.7.3.3-5A			

Table 6.1.7.3.3-5A: MIME Message (step 7, Table 6.1.7.3.2-1; step 3, TS 37.579-1 [2] Table 5.3C.4.3-1)

Derivation Path: RFC 2046 [38]				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
MIME body part		**MCData Data signalling message**		
MIME-part-headers				
Content-Type	"application/vnd.3gpp.mcdata-signalling"			
MIME-part-body	MCData Protected Payload Message containing SDS SIGNALLING PAYLOAD as described in table 6.1.7.3.3-5B			
MIME body part		**MCData Data message**		
MIME-part-headers				
Content-Type	"application/vnd.3gpp.mcdata-payload"			
MIME-part-body	MCData Protected Payload Message containing DATA PAYLOAD as described in Table 6.1.7.3.3-6			

Table 6.1.7.3.3-5B: SDS SIGNALLING PAYLOAD (Table 6.1.7.3.3-5A)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.1-1, condition DELIVERED

Table 6.1.7.3.3-6: Data Payload (Table 6.1.7.3.3-5A)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.9.1-1

Table 6.1.7.3.3-7..8: Void

Table 6.1.7.3.3-9: SIP BYE from the UE (step 8, Table 6.1.7.3.2-1; step 1, TS 37.579-1 [2] Table 5.3C.6.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.2.1-1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Reason			RFC 3326 [125]	
reason-value	"SIP"			
protocol-cause	"cause="200""			
reason-text	"text="transmission succeeded""			

Table 6.1.7.3.3-10: Void

Table 6.1.7.3.3-11: SIP MESSAGE from the SS (step 10, Table 6.1.7.3.2-1; step 2, TS 37.579-1 [2] Table 5.3.33.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.7.2-1, condition MCDATA_SDS, MCDATA_SIGNALLING				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part		**MCData-Info**		
MIME-part-body	As described in Table 6.1.7.3.3-12			
MIME body part		**MCData Data signalling message**		
MIME-part-body	MCData Protected Payload Message containing SDS NOTIFICATION as described in Table 6.1.7.3.3-13			

Table 6.1.7.3.3-12: MCData-Info (Table 6.1.7.3.3-11)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.2.2-3				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
mcdata-info				
mcdata-Params				
mcdata-calling-group-id	Encrypted <mcdata-calling-group-id> with mcdataURI set to px_MCData_Group_A_ID	Encrypted according to TS 37.579-1 [2] Table 5.5.3.2.2-3A		

Table 6.1.7.3.3-13: SDS NOTIFICATION (Table 6.1.7.3.3-11)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.4-1, condition DELIVERED

Table 6.1.7.3.3-14: Void

6.1.8 On-network / Short Data Service (SDS) / Standalone SDS Using Media Plane / Group Standalone SDS / Client Terminated (CT)

6.1.8.1 Test Purpose (TP)

(1)

```
with { UE (MCDATA Client) registered and authorised for MCDATA Service }
ensure that {
  when { the MCDATA User receives a SIP INVITE to initiate a standalone group SDS message using the
media plane }
    then { UE (MCDATA Client) responds by sending a SIP 200 (OK) message }
            }
```

(2)

```
with { UE (MCDATA Client) having responded to the SIP INVITE message that initiated a standalone
group SDS message using the media plane }
ensure that {
  when { UE (MCDATA Client) receives an MSRP SEND message }
    then { UE (MCDATA Client) responds with an MSRP 200 (OK) message and if the MSRP SEND message is
not blank, renders the contents of the Payload IE to the MCDATA User and sends a SIP MESSAGE message
with a disposition notification of "DELIVERED" }
            }
```

(3)

```
with { UE (MCDATA Client) having responded to the MSRP SEND message from the SS (MCDATA server) }
ensure that {
  when { UE (MCDATA Client) receives a SIP BYE message to release communications }
    then { UE (MCDATA Client) sends a SIP 200 (OK) message }
           }
```

6.1.8.2 Conformance requirements

References: The conformance requirements covered in the current TC are specified in: TS 24.282, clauses 9.2.3.2.4, 9.2.3.2.2, 13.2.2.2.2.2, 9.2.1.3, 12.2.1.1, 6.2.4.1, 6.2.3.1, TS 24.582 clauses 6.1.1.3.1, 6.1.1.3.2. The following represents a copy/paste extraction of the requirements relevant to the test purpose; any references within the copy/paste text should be understood within the scope of the core spec they have been copied from. Unless otherwise stated, these are Rel-14 requirements.

[TS 24.282, clause 9.2.3.2.4]

Upon receipt of an initial SIP INVITE request, the MCData client shall follow the procedures for termination of multimedia sessions in the IM CN subsystem as specified in 3GPP TS 24.229 [5] with the clarifications below.

The MCData client:

1) may reject the SIP INVITE request if either of the following conditions are met:

   a) MCData client does not have enough resources to handle the call; or

   b) any other reason outside the scope of this specification;

   and skip the rest of the steps after step 2;

2) if the SIP INVITE request is rejected in step 1), shall respond toward participating MCData function either with appropriate reject code as specified in 3GPP TS 24.229 [5] and warning texts as specified in subclause 4.9 or with SIP 480 (Temporarily unavailable) response not including warning texts if the user is authorised to restrict the reason for failure and skip the rest of the steps of this subclause;

3) if the SDP offer of the SIP INVITE request contains an "a=key-mgmt" attribute field with a "mikey" attribute value containing a MIKEY-SAKKE I_MESSAGE:

   a) shall extract the MCData ID of the originating MCData user from the initiator field (IDRi) of the I_MESSAGE as described in 3GPP TS 33.180 [26];

   b) shall convert the MCData ID to a UID as described in 3GPP TS 33.180 [26];

   c) shall use the UID to validate the signature of the MIKEY-SAKKE I_MESSAGE as described in 3GPP TS 33.180 [26];

   d) if authentication verification of the MIKEY-SAKKE I_MESSAGE fails, shall reject the SIP INVITE request with a SIP 488 (Not Acceptable Here) response as specified in IETF RFC 4567 [45], and include warning text set to "136 authentication of the MIKEY-SAKKE I_MESSAGE failed" in a Warning header field as specified in subclause 4.9 and not continue with rest of the steps in this subclause; and

   e) if the signature of the MIKEY-SAKKE I_MESSAGE was successfully validated:

      i) shall extract and decrypt the encapsulated PCK using the terminating user's (KMS provisioned) UID key as described in 3GPP TS 33.180 [26]; and

      ii) shall extract the PCK-ID, from the payload as specified in 3GPP TS 33.180 [26];

NOTE: With the PCK successfully shared between the originating MCData client and the terminating MCData client, both clients are able to create an end-to-end secure session.

3) may display to the MCData user the MCData ID of the inviting MCData user and the type of SDS request;

4) shall accept the SIP INVITE request and generate a SIP 200 (OK) response according to rules and procedures of 3GPP TS 24.229 [5];

5) shall include the option tag "timer" in a Require header field of the SIP 200 (OK) response;

6) shall include the Session-Expires header field in the SIP 200 (OK) response and start the SIP session timer according to IETF RFC 4028 [38]. The "refresher" parameter in the Session-Expires header field shall be set to "uas";

7) shall include the g.3gpp.mcdata.sds media feature tag in the Contact header field of the SIP 200 (OK) response;

8) shall include the g.3gpp.icsi-ref media feature tag containing the value of "urn:urn-7:3gpp-service.ims.icsi.mcdata.sds" in the Contact header field of the SIP 200 (OK) response;

9) shall include an SDP answer in the SIP 200 (OK) response to the SDP offer in the incoming SIP INVITE request according to 3GPP TS 24.229 [5] with the clarifications given in subclause 9.2.3.2.2; and

10) shall send the SIP 200 (OK) response towards the MCData server according to rules and procedures of 3GPP TS 24.229 [5].

On receipt of an SIP ACK message to the sent SIP 200 (OK) message, the MCData client shall:

1) shall interact with the media plane as specified in 3GPP TS 24.582 [15] subclause 6.1.1.3.

[TS 24.282, clause 9.2.3.2.2]

When the MCData client receives an initial SDP offer for an MCData standalone SDS, the MCData client shall process the SDP offer and shall compose an SDP answer according to 3GPP TS 24.229 [5] and IETF RFC 4975 [17].

When composing an SDP answer, the MCData client:

1) shall include an "m=message" media-level section for the accepted MCData media stream consisting of:

   a) the port number;

   b) a protocol field value of "TCP/MSRP", or "TCP/TLS/MSRP" for TLS according to the received SDP offer;

   c) a format list field set to '*';

   d) an "a=recvonly" attribute;

   e) an "a=path" attribute containing its own MSRP URI;

   f) set the content type as a=accept-types: application/vnd.3gpp.mcdata-signalling application/vnd.3gpp.mcdata-payload; and

   g) set the a=setup attribute according to IETF RFC 6135 [19].

[TS 24.282, clause 13.2.2.2.2.2]

Upon receiving a SIP BYE request, the MCData client:

1) shall send SIP 200 (OK) response towards MCData server according to 3GPP TS 24.229 [5]; and

2) shall release all media plane resources corresponding to the MCData communication being released.

NOTE: Partially received data can be stored and processed.

[TS 24.282, clause 9.2.1.3]

To handle the disposition requests, the MCData client:

1) If the SDS disposition request type IE is set to:

   a) "DELIVERY" then, shall send a delivered notification as described in subclause 12.2.1.1;

   b) "READ", shall send a read notification as described in subclause 12.2.1.1, when a display indication is received; or

   c) "DELIVERY AND READ" then, shall start timer TDU1 (delivery and read).

Upon receiving a display indication before timer TDU1 (delivery and read) expires, the MCData client:

1) shall stop timer TDU1 (delivery and read); and

2) shall send a delivered and read notification as described in subclause 12.2.1.1.

Upon expiry of timer TDU1 (delivery and read), the MCData client:

1) shall send a delivered notification as described in subclause 12.2.1.1; and

2) upon receiving a display indication, send a read notification as described in subclause 12.2.1.1.

[TS 24.282, clause 12.2.1.1]

The MCData client shall follow the procedures in this subclause to:

- indicate to an MCData client that an SDS message was delivered, read or delivered and read when the originating client requested a delivery, read or delivery and read report;

- indicate to the participating MCData function serving the MCData user that an SDS message was undelivered. The participating MCData function can store the message for later re-delivery;

- indicate to an MCData client that a request for FD was accepted, deferred or rejected; or

- indicate to an MCData client that a file download has been completed;

Before sending a disposition notification the MCData client needs to determine:

- the controlling MCData function that sent the SDS or FD message request. The MCData client determines the controlling MCData function from the contents of the <mcdata-controller-psi> element contained in the application/vnd.3gpp.mcdata-info+xml MIME body of the incoming SDS or FD message request;

- the group identity related to an SDS or FD message request received as part of a group communication. The MCData client determines the group identity from the contents of the <mcdata-calling-group-id> element contained in the application/vnd.3gpp.mcdata-info+xml MIME body of the incoming SDS or FD message request; and

- the MCData user targeted for the disposition notification. The MCData client determines the targeted MCData user from the contents of the <mcdata-calling-user-id> element contained in the application/vnd.3gpp.mcdata-info+xml MIME body of the incoming SDS or FD message request.

The MCData client shall generate a SIP MESSAGE request in accordance with 3GPP TS 24.229 [5] and IETF RFC 3428 [6] with the clarifications given below.

The MCData client:

1) shall build the SIP MESSAGE request as specified in subclause 6.2.4.1;

2) shall follow the rules specified in subclause 6.4 for the handling of MIME bodies in a SIP message when processing the remaining steps in this subclause;

3) shall insert in the SIP MESSAGE request an application/resource-lists+xml MIME body containing the MCData ID of the targeted MCData user, according to rules and procedures of IETF RFC 5366 [18];

4) shall insert in the SIP MESSAGE request an application/vnd.3gpp.mcdata-info+xml MIME body with an <mcdata-controller-psi> element containing the PSI of the controlling MCData function;

5) if sending a disposition notification in response to an MCData group data request, shall include an <mcdata-calling-group-id> element set to the MCData group identity in the application/vnd.3gpp.mcdata-info+xml MIME body;

6) if requiring to send an SDS notification, shall generate an SDS NOTIFICATION message and include it in the SIP MESSAGE request as specified in subclause 6.2.3.1;

7) if requiring to send an FD notification, shall generate an FD NOTIFICATION message and include it in the SIP MESSAGE request as specified in subclause 6.2.3.2; and

8) shall send the SIP MESSAGE request according to rules and procedures of 3GPP TS 24.229 [5].

[TS 24.282, clause 6.2.4.1]

This subclause is referenced from other procedures.

In a SIP MESSAGE request, the MCData client:

1) when sending SDS messages or SDS disposition notifications:

   a) shall include an Accept-Contact header field containing the g.3gpp.mcdata.sds media feature tag along with the "require" and "explicit" header field parameters according to IETF RFC 3841 [8];

   b) shall include an Accept-Contact header field with the media feature tag g.3gpp.icsi-ref containing the value of "urn:urn-7:3gpp-service.ims.icsi.mcdata.sds" along with the "require" and "explicit" header field parameters according to IETF RFC 3841 [8]; and

   c) shall include the ICSI value "urn:urn-7:3gpp-service.ims.icsi.mcdata.sds" (coded as specified in 3GPP TS 24.229 [5]), in a P-Preferred-Service header field according to IETF RFC 6050 [7] in the SIP MESSAGE request;

2) when sending FD messages, FD disposition notifications or FD media storage function discovery messages:

   a) shall include an Accept-Contact header field containing the g.3gpp.mcdata.fd media feature tag along with the "require" and "explicit" header field parameters according to IETF RFC 3841 [8];

   b) shall include an Accept-Contact header field with the media feature tag g.3gpp.icsi-ref containing the value of "urn:urn-7:3gpp-service.ims.icsi.mcdata.fd" along with the "require" and "explicit" header field parameters according to IETF RFC 3841 [8]; and

   c) shall include the ICSI value "urn:urn-7:3gpp-service.ims.icsi.mcdata.fd" (coded as specified in 3GPP TS 24.229 [5]), in a P-Preferred-Service header field according to IETF RFC 6050 [7] in the SIP MESSAGE request;

3) may include a P-Preferred-Identity header field in the SIP MESSAGE request containing a public user identity as specified in 3GPP TS 24.229 [5]; and

4) shall set the Request-URI to the public service identity identifying the participating MCData function serving the MCData user.

[TS 24.282, clause 6.2.3.1]

In order to generate an SDS notification, the MCData client:

1) shall generate an SDS NOTIFICATION message as specified in subclause 15.1.5; and

2) shall include in the SIP request, the SDS NOTIFICATION message in an application/vnd.3gpp.mcdata-signalling MIME body as specified in subclause E.1.

When generating an SDS NOTIFICATION message as specified in subclause 15.1.5, the MCData client:

1) if sending a delivered notification, shall set the SDS disposition notification type IE as "DELIVERED" as specified in subclause 15.2.5;

2) if sending a read notification, shall set the SDS disposition notification type IE as "READ" as specified in subclause 15.2.5;

3) if sending a delivered and read notification, shall set the SDS disposition notification type IE as "DELIVERED AND READ" as specified in subclause 15.2.5;

4) if the SDS message could not be delivered to the user or application (e.g. due to lack of storage), shall set the SDS disposition notification type IE as "UNDELIVERED" as specified in subclause 15.2.5;

5) shall set the Date and time IE to the current time to as specified in subclause 15.2.8;

6) shall set the Conversation ID to the value of the Conversation ID that was received in the SDS message as specified in subclause 15.2.9;

7) shall set the Message ID to the value of the Message ID that was received in the SDS message as specified in subclause 15.2.10;

8) if the SDS message was destined for the user, shall not include an Application ID IE as specified in subclause 15.2.7; and

9) if the SDS message was destined for an application, shall include an Application ID IE set to the value of the Application ID that was included in the SDS message as specified in subclause 15.2.3.

[TS 24.582, clause 6.1.1.3.1]

Upon receiving an indication to establish MSRP connection for standalone SDS using media plane as the terminating client, the MCData client:

1. shall act as an MSRP client according to IETF RFC 6135 [12];

2. shall act either as an active endpoint or as an passive endpoint to open the transport connection, according to IETF RFC 6135 [12];

3. shall establish the MSRP connection according to the MSRP connection parameters in the SDP offer received in the SIP INVITE request according to IETF RFC 4975 [11];

4. if acting as an "active" endpoint, shall send an empty MSRP SEND request to bind the MSRP connection to the MSRP session from the perspective of the passive endpoint according to the rules and procedures of IETF RFC 4975 [11] and IETF RFC 6135 [12];

Once the MSRP connection is established, the MCData client:

1. on receipt of an MSRP request in an MSRP session, shall follow the rules and procedures defined in IETF RFC 4975 [11] and in IETF RFC 6714 [13];

2. If an MSRP SEND request indicates the use of chunking, shall wait until all further MSRP SEND requests for the remaining chunks have been received and shall reassemble the entire set of MSRP requests into the MCData standalone message before delivering the content to the application; and

3. shall handle the received content as described in subclause 6.1.1.3.2.

[TS 24.582, clause 6.1.1.3.2]

The MCData client:

1. shall decode the contents of the application/vnd.3gpp.mcdata-signalling MIME body;

2. shall decode the contents of the application/vnd.3gpp.mcdata-payload MIME body;

3. if the SDS SIGNALLING PAYLOAD message contains a new Conversation ID, shall instantiate a new conversation with the Message ID in the SDS SIGNALLING PAYLOAD identifying the first message in the conversation thread;

4. if the SDS SIGNALLING PAYLOAD message contains an existing Conversation ID and:

   a. if the SDS SIGNALLING PAYLOAD message does not contain an InReplyTo Message ID, shall use the Message ID in the SDS SIGNALLING PAYLOAD to identify a new message in the existing conversation thread; and

   b. if the SDS SIGNALLING PAYLOAD message contains an InReplyTo Message ID, shall associate the message to an existing message in the conversation thread as identified by the InReplyTo Message ID in the SDS SIGNALLING PAYLOAD and use the Message ID in the SDS SIGNALLING PAYLOAD to identify the new message;

5. shall identify the number of Payload IEs in the DATA PAYLOAD message from the Number of Payloads IE in the DATA PAYLOAD message;

6. if the SDS SIGNALLING PAYLOAD message does not contain an Application identifier IE:

   a. shall determine that the payload contained in the DATA PAYLOAD message is for user consumption;

b. may notify the MCData user; and

c. shall render the contents of the Payload IE(s) to the MCData user;

7. if the SDS SIGNALLING PAYLOAD message contains an Application identifier IE:

   a. shall determine that the payload contained in the DATA PAYLOAD message is not for user consumption;

   b. shall not notify the MCData user;

   c. if the Application identifier value is unknown, shall discard the SDS message; and

   d. if the Application identifier value is known, shall deliver the contents of the Payload IE(s) to the identified application; and

8. if SDS Disposition request type IE is present in the SDS SIGNALLING PAYLOAD message received in subclause 6.1.1.3.1 then, shall send a disposition notification as described in 3GPP TS 24.282 [8] subclause 9.2.1.3.

6.1.8.3 Test description

6.1.8.3.1 Pre-test conditions

Test configuration:

- Single cell configuration according to TS 37.579-1 [2] clause 5.2.2.2.1.

Preamble:

- The UE has performed procedure 'Initial registration' as described in TS 37.579-1 [2] clause 5.4.2 with the following clarifications:

  - The <max-payload-size-sds-cplane-bytes> element of the MCData Service Configuration document shall be set to 0 to force the MCData client to send the data using the media plane.

- UE States at the end of the preamble:

  - The UE is in RRC_IDLE state.

  - The client is registered for MCData.

6.1.8.3.2 Test procedure sequence

Table 6.1.8.3.2-1: Main Behaviour

St	Procedure	Message Sequence		TP	Verdict
		U - S	Message		
1	Check: Does the UE (MCData client) correctly perform procedure '**CT MCData Call Establishment**' as described in TS 37.579-1 [2] Table 5.3C.3.3-1?	-	-	1,2	P
2-5	Void	-	-	-	-
6	Check: Does the UE (MCData client) correctly perform procedure '**CT MSRP message transfer**' as described in TS 37.579-1 [2] Table 5.3C.5.3-1 to **receive an SDS message with disposition request "DELIVERY"**?	-	-	2	P
7	Void	-	-	-	-
8	Check: Does the UE (MCData client) correctly perform procedure '**CT MCData call release**' as described in TS 37.579-1 [2] Table 5.3C.7.3-1? (NOTE 2)	-	-	3	P
9-10	Void	-	-	-	-
11	Check: Does the UE (MCData client) correctly perform procedure '**CO SDS or FD message transfer using signalling plane**' as described in TS 37.579-1 [2] Table 5.3C.1.3-1 to **send a disposition notification of "DELIVERED"**?	-	-	2	P
12	Check: Does the UE (MCData client) provide the contents of the Payload IE to the user? (NOTE 1)	-	-	2	P
NOTE 1: This is expected to be done via a suitable implementation dependent MMI. NOTE 2: The procedure does not release the RRC connection.					

6.1.8.3.3 Specific message contents

Table 6.1.8.3.3-1: SIP INVITE from the SS (step 1, Table 6.1.8.3.2-1; step 2, TS 37.579-1 [2] Table 5.3C.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.5.2-1, condition MCDATA_SDS				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part		**SDP message**		
MIME-part-body	SDP message as described in Table 6.1.8.3.3-1A			
MIME body part		**MCData-Info**		
MIME-part-body	MCData-Info as described in Table 6.1.8.3.3-2			

Table 6.1.8.3.3-1A: SDP for SIP INVITE (Table 6.1.8.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.1.2-3, condition MCDATA_SDS, SDP_OFFER

Table 6.1.8.3.3-2: MCData-Info (Table 6.1.8.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.2.2-3, condition MCD_grp

Table 6.1.8.3.3-3: SIP 200 (OK) from the UE (step 1, Table 6.1.8.3.2-1; step 4, TS 37.579-1 [2] Table 5.3C.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.17.1.1-1, condition INVITE-RSP, MCDATA_SDS				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Content-Type				
value	"application/sdp"			
Message-body				
SDP message	As described in Table 6.1.8.3.3-4			

Table 6.1.8.3.3-4: SDP for SIP 200 (OK) (Table 6.1.8.3.3-3)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.1.1-3, condition MCDATA_SDS, SDP_ANSWER

Table 6.1.8.3.3-5: MSRP SEND from the SS (step 6, Table 6.1.8.3.2-1; step 1, TS 37.579-1 [2] Table 5.3C.5.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.12.1.2-1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Content-Type				
media-type	"multipart/mixed"			
data	Message as specified in table 6.1.8.3.3-5A			

Table 6.1.8.3.3-5A: MIME Message (step 6, Table 6.1.8.3.2-1; step 1, TS 37.579-1 [2] Table 5.3C.5.3-1)

Derivation Path: RFC 2046 [38]				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
MIME body part		**MCData Data signalling message**		
MIME-part-headers				
Content-Type	"application/vnd.3gpp. mcdata-signalling"			
MIME-part-body	MCData Protected Payload Message containing SDS SIGNALLING PAYLOAD as described in table 6.1.8.3.3-5B			
MIME body part		**MCData Data message**		
MIME-part-headers				
Content-Type	"application/vnd.3gpp. mcdata-payload"			
MIME-part-body	MCData Protected Payload Message containing DATA PAYLOAD as described in Table 6.1.8.3.3-6			

Table 6.1.8.3.3-5B: SDS SIGNALLING PAYLOAD (Table 6.1.8.3.3-5A)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.2-1, condition DELIVERED

Table 6.1.8.3.3-6: Data Payload (Table 6.1.8.3.3-5A)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.9.1-2

Table 6.1.8.3.3-7: SIP BYE from the SS (step 8, Table 6.1.8.3.2-1; step 1, TS 37.579-1 [2] Table 5.3C.7.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.2.2-1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Reason			RFC 3326 [125]	
reason-value	"SIP"			
protocol-cause	"cause="200""			
reason-text	"text="transmission succeeded""			

Table 6.1.8.3.3-8: Void

Table 6.1.8.3.3-9: SIP MESSAGE from the UE (step 11, Table 6.1.8.3.2-1; step 2, TS 37.579-1 [2] Table 5.3C.1.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.7.1-1, condition MCDATA_SDS, RESOURCE_LISTS, MCDATA_SIGNALLING				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part		**MCData-Info**		
MIME-part-body	MCData-Info as described in Table 6.1.8.3.3-10			
MIME body part		**MCData Data signalling message**		
MIME-part-body	MCData Protected Payload Message containing SDS NOTIFICATION as described in Table 6.1.6.3.3-11			

Table 6.1.8.3.3-10: MCData-Info (Table 6.1.8.3.3-9)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.2.1-3				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
mcdata-info				
mcdata-Params				
mcdata-calling-group-id	Encrypted <mcdata-request-uri> with mcdataURI set to px_MCData_Group_A_ID	Encrypted according to TS 37.579-1 [2] Table 5.5.3.2.1-3A		

Table 6.1.8.3.3-11: SDS NOTIFICATION (Table 6.1.8.3.3-9)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.3-1, condition DELIVERED

6.1.9 On-network / Short Data Service (SDS) / SDS Session / One-to-one SDS Session / Client Originated (CO)

6.1.9.1 Test Purpose (TP)

(1)

```
with { UE (MCDATA Client) registered and authorised for MCDATA Service }
ensure that {
  when { the MCDATA User requests to initiate a one-to-one SDS session using the media plane}
    then { UE (MCDATA Client) sends a request to establish a one-to-one SDS session and a MSRP
connection via a SIP INVITE message and then responds to the SIP 200 (OK) message with a SIP ACK
message }
            }
```

(2)

```
with { UE (MCDATA Client) having received a SIP 200 (OK) message with the a=setup attribute set to
"passive" in response to a SIP INVITE message}
ensure that {
  when { UE (MCDATA Client) responds to the SIP 200 (OK) message with a SIP ACK message }
    then { UE (MCData Client) sends a blank MSRP SEND message to bind the MSRP connection and then
sends the one-to-one session SDS message via a MSRP SEND message with a disposition of "DELIVERY" }
            }
```

(3)

```
with { UE (MCDATA Client) having sent a one-to-one session SDS message using the media plane with a
disposition of "DELIVERY" }
ensure that {
  when { UE (MCDATA Client) receives a disposition response via a MSRP SEND message }
    then { UE (MCDATA Client) responds to the MSRP SEND message by sending a MSRP 200 (OK) message
and delivers the notification to the MCDATA User }
            }
```

(4)

```
with { UE (MCDATA Client) having established a one-to-one SDS session and a MSRP connection }
ensure that {
  when { UE (MCDATA Client) receives an MSRP SEND message with a disposition of "READ" }
    then { UE (MCDATA Client) responds with a MSRP 200 (OK) message and then renders the contents of
the Payload IE to the MCDATA User and then sends a MSRP SEND message with a disposition notification
of "READ" }
            }
```

(5)

```
with { UE (MCDATA Client) having established a one-to-one SDS session }
ensure that {
  when { the MCDATA User requests to release the one-to-one SDS session }
    then { UE (MCDATA Client) sends a SIP BYE message }
            }
```

6.1.9.2 Conformance requirements

References: The conformance requirements covered in the current TC are specified in: TS 24.282, clauses 9.2.4.2.3, 9.2.4.2.1, 13.2.2.2.2.1, TS 24.582 clauses 6.1.2.2.1, 6.1.2.4, 6.1.2.5.1, 6.1.2.5.2, 6.1.2.5.3, 6.1.2.6. The following represents a copy/paste extraction of the requirements relevant to the test purpose; any references within the copy/paste text should be understood within the scope of the core spec they have been copied from. Unless otherwise stated, these are Rel-14 requirements.

[TS 24.282, clause 9.2.4.2.3]

The MCData client shall generate a SIP INVITE request in accordance with 3GPP TS 24.229 [5] with the clarifications given below.

The MCData client:

1) shall include the g.3gpp.mcdata.sds media feature tag and the g.3gpp.icsi-ref media feature tag with the value of "urn:urn-7:3gpp-service.ims.icsi.mcdata.sds" in the Contact header field of the SIP INVITE request according to IETF RFC 3840 [16];

2) shall include an Accept-Contact header field containing the g.3gpp.mcdata.sds media feature tag along with the "require" and "explicit" header field parameters according to IETF RFC 3841 [8];

3) shall include an Accept-Contact header field with the g.3gpp.icsi-ref media feature tag containing the value of "urn:urn-7:3gpp-service.ims.icsi.mcdata.sds" along with the "require" and "explicit" header field parameters according to IETF RFC 3841 [8];

4) shall include the ICSI value "urn:urn-7:3gpp-service.ims.icsi.mcdata.sds" (coded as specified in 3GPP TS 24.229 [5]), in a P-Preferred-Service header field according to IETF RFC 6050 [7] in the SIP INVITE request;

5) should include the "timer" option tag in the Supported header field;

6) should include the Session-Expires header field according to IETF RFC 4028 [38]. It is recommended that the "refresher" header field parameter is omitted. If included, the "refresher" header field parameter shall be set to "uac";

7) if a one-to-one SDS session is requested:

   a) shall insert in the SIP INVITE request a MIME resource-lists body with the MCData ID of the invited MCData user, according to rules and procedures of IETF RFC 5366 [18];

   b) shall contain an application/vnd.3gpp.mcdata-info+xml MIME body with the <mcdatainfo> element containing the <mcdata-Params> element with:

      i) the <request-type> element set to a value of "one-to-one-sds-session"; and

   c) if an end-to-end security context needs to be established and the security context does not exist or if the existing security context has expired, then:

      i) if necessary, shall instruct the key management client to request keying material from the key management server as described in 3GPP TS 33.180 [26];

      ii) shall use the keying material to generate a PCK as described in 3GPP TS 33.180 [26];

      iii) shall use the PCK to generate a PCK-ID with the four most significant bits set to "0001" to indicate that the purpose of the PCK is to protect one-to-one communications and with the remaining twenty eight bits being randomly generated as described in 3GPP TS 33.180 [26];

      iv) shall encrypt the PCK to a UID associated to the MCData client using the MCData ID of the invited user and a time related parameter as described in 3GPP TS 33.180 [26];

      v) shall generate a MIKEY-SAKKE I_MESSAGE using the encapsulated PCK and PCK-ID as specified in 3GPP TS 33.180 [26];

      vi) shall add the MCData ID of the originating MCData to the initiator field (IDRi) of the I_MESSAGE as described in 3GPP TS 33.180 [26]; and

      vii) shall sign the MIKEY-SAKKE I_MESSAGE using the originating MCData user's signing key provided in the keying material together with a time related parameter, and add this to the MIKEY-SAKKE payload, as described in 3GPP TS 33.180 [26];

…

9) shall set the Request-URI of the SIP INVITE request to the public service identity identifying the participating MCData function serving the MCData user;

NOTE 2: The MCData client is configured with public service identity identifying the participating MCData function serving the MCData user.

10) may include a P-Preferred-Identity header field in the SIP INVITE request containing a public user identity as specified in 3GPP TS 24.229 [5];

11) shall include an SDP offer according to 3GPP TS 24.229 [5] with the clarifications given in subclause 9.2.4.2.1; and

12) shall send the SIP INVITE request towards the MCData server according to 3GPP TS 24.229 [5].

On receipt of a SIP 2xx response to the SIP INVITE request, the MCData client:

1) shall send a SIP ACK request as specified in 3GPP TS 24.229 [5];

2) shall start the SIP Session timer according to rules and procedures of IETF RFC 4028 [38]; and

3) shall interact with the media plane as specified in 3GPP TS 24.582 [15] subclause 6.1.2.2.

[TS 24.282, clause 9.2.4.2.1]

When composing an SDP offer according to 3GPP TS 24.229 [5], IETF RFC 4975 [17], IETF RFC 6135 [19] and IETF RFC 6714 [20] the MCData client:

1) shall include an "m=message" media-level section for the MCData media stream consisting of:

   a) the port number;

   b) a protocol field value of "TCP/MSRP" or "TCP/TLS/MSRP" for TLS;

   c) an "a=sendrecv" attribute;

   d) an "a=path" attribute containing its own MSRP URI;

   e) set the content type as "a=accept-types:application/vnd.3gpp.mcdata-signalling application/vnd.3gpp.mcdata-payload"; and

   f) set the a=setup attribute as "actpass"; and

2) if end-to-end security is required for a one-to-one communication and the security context does not exist or if the existing security context has expired, shall include the MIKEY-SAKKE I_MESSAGE in an "a=key-mgmt" attribute as a "mikey" attribute value in the SDP offer as specified in IETF RFC 4567 [45].

[TS 24.282, clause 13.2.2.2.2.1]

When the MCData client wants to release a MCData communication established over the media plane, the MCData client:

1) shall generate a SIP BYE request according to 3GPP TS 24.229 [5];

2) shall set the Request-URI to the MCData session identity to be released; and

3) shall send the SIP BYE request towards MCData server according to 3GPP TS 24.229 [5].

Upon receiving a SIP 200 (OK) response to the SIP BYE request, the MCData client shall release all media plane resources corresponding to the MCData communication being released.

[TS 24.582, clause 6.1.2.2.1]

Upon receiving an indication to establish MSRP connection for SDS session as the originating MCData client, the MCData client:

1. shall act as an MSRP client according to IETF RFC 6135 [12];

2. shall act according to IETF RFC 6135 [12], as:

   a. an "active" endpoint, if a=setup attribute in the received SDP answer is set to "passive"; and

   b. an "passive" endpoint, if a=setup attribute in the received SDP answer is set to "active";

3. shall establish the MSRP connection according to the MSRP connection parameters in the SDP answer received in the SIP 200 (OK) response according to IETF RFC 4975 [11];

4. if acting as an "active" endpoint, shall send an empty MSRP SEND request to bind the MSRP connection to the MSRP session from the perspective of the passive endpoint according to the rules and procedures of IETF RFC 4975 [11] and IETF RFC 6135 [12];

Once the MSRP session is established, the MCData client:

1. on receipt of an MSRP request in the MSRP session, shall follow the rules and procedures defined in IETF RFC 4975 [11] and in IETF RFC 6714 [13];

2. If an MSRP SEND request indicates the use of chunking, shall wait until all further MSRP SEND requests for the remaining chunks have been received and shall reassemble the entire set of MSRP requests into the MCData SDS message before delivering the content to the application; and

3. shall handle the received content as described in subclause 6.1.2.6.

On receiving MSRP 200 (OK) response to the first MSRP SEND request, the MCData client can generate and send an SDS message as specified in subclause 6.1.2.4, or can generate and send an SDS disposition notification for a received SDS message as specified in subclause 6.1.2.5, if requested.

Received content and disposition requests shall be handled as specified in subclause 6.1.2.6.

[TS 24.582, clause 6.1.2.4]

An MCData client is allowed to send an one-to-one SDS message only if

1. the <allow-transmit-data> element of an <actions> element is present with a value "true" (see the MCData user profile document in 3GPP TS 24.484 [7]);

2. the size of the SDS message is less than or equal to the value of the <max-data-size-sds-bytes> element in the MCData service configuration document as specified in 3GPP TS 24.484 [7]; and

3. the size of the SDS message is less than or equal to the value of <MaxData1To1> element of the MCData user profile document (see the MCData user profile document in 3GPP TS 24.484 [7]).

An MCData client is allowed to send a group SDS message only if

1. the <mcdata-allow-transmit-data-in-this-group> element of an <action> element is present with a value "true" as defined in the MCData group document for this MCData group as specified in 3GPP TS 24.481 [4];

2. the size of the SDS message is less than or equal to the value contained in the <mcdata-on-network-max-data-size-for-SDS> as defined in the MCData group document for this MCData group as specified in 3GPP TS 24.481 [4]; and

3. the size of the SDS message is less than or equal to the value contained in the <mcdata-max-data-in-single-request> element of the <entry> element of the MCData group document for this MCData group as specified in 3GPP TS 24.481 [11].

If the above mentioned conditions satisfy, the MCData client:

1. shall generate a SDS SIGNALLING PAYLOAD as specified in subclause 6.1.1.2.2;

2. shall generate a SDS DATA PAYLOAD as specified in subclause 6.1.1.2.3;

3. shall include the SDS SIGNALLING PAYLOAD and SDS DATA PAYLOAD in an MSRP SEND request as specified in subclause 6.1.1.2.4, with the following clarification;

   a. shall set To-Path header according to the MSRP URI in the received SDP; and

4. shall send the MSRP SEND request on the established MSRP connection.

NOTE: MSRP chunking, if needed, may affect the number of "Content Type" lines in each MSRP SEND message conveying a chunk, as also specified in subclause 6.1.1.2.4.

[TS 24.582, clause 6.1.2.5.1]

To send an SDS disposition notification, the MCData client:

1. shall generate a SDS NOTIFICATION as specified in subclause 6.1.2.5.2;
2. shall include the SDS NOTIFICATION in an MSRP SEND request as specified in subclause 6.1.2.5.3, with the following clarification;
    a. shall set To-Path header according to the MSRP URI in the received SDP; and
3. shall send the MSRP SEND request on the established MSRP connection.

If MSRP chunking is used, the MCData client:

1. shall send further MSRP SEND requests as necessary.

On receiving a non-200 MSRP response to the MSRP SEND request the MCData client shall handle the error as specified in IETF RFC 4975 [11]. To terminate the MSRP session, the MCData client:

1. if there are further MSRP chunks to send, shall abort transmission of these further MSRP chunks; and
2. shall indicate to MCData user that the SDS message or the SDS disposition notification could not be sent.

[TS 24.582, clause 6.1.2.5.2]

In order to generate an SDS notification, the MCData client:

1. shall generate an SDS NOTIFICATION message as specified in 3GPP TS 24.282 [8]; and
2. shall include the SDS NOTIFICATION message in an application/vnd.3gpp.mcdata-signalling MIME body as specified in 3GPP TS 24.282 [8].

When generating an SDS NOTIFICATION message, the MCData client:

1. if sending a delivered notification, shall set the SDS disposition notification type IE as "DELIVERED";
2. if sending a read notification, shall set the SDS disposition notification type IE as "READ";
3. if sending a delivered and read notification, shall set the SDS disposition notification type IE as "DELIVERED AND READ";
4. if the SDS message could not be delivered to the user or application (e.g. due to lack of storage), shall set the SDS disposition notification type IE as "UNDELIVERED";
5. shall set the Date and time IE to the current time;
6. shall set the Conversation ID to the value of the Conversation ID that was received in the SDS message;
7. shall set the Message ID to the value of the Message ID that was received in the SDS message;
8. if the SDS message was destined for the user, shall not include an Application ID IE; and
9. if the SDS message was destined for an application, shall include an Application ID IE set to the value of the Application ID that was included in the SDS message.

[TS 24.582, clause 6.1.2.5.3]

The MCData client shall generate MSRP SEND requests for SDS disposition notification according to IETF RFC 4975 [11].

When generating an MSRP SEND request for SDS disposition notification containing an SDS NOTIFICATION message, the MCData client

1. shall set To-Path header according to the MSRP URI(s) received in the answer SDP;
2. shall set the content type as Content-Type = "application/vnd.3gpp.mcdata-signalling"; and
3. shall set the body of the MSRP SEND request to the generated SDS NOTIFICATION message.

[TS 24.582, clause 6.1.2.6]

Upon receiving an SDS message, the MCData client:

1. shall follow the procedure defined in subclause 6.1.1.3.2, with the following clarification:

   a. if SDS Disposition request type IE is present in the received SDS SIGNALLING PAYLOAD message then, shall send an SDS disposition notification as described in subclause 6.1.2.5.

Upon receiving an SDS disposition notification, the MCData client:

1. shall decode the contents of the application/vnd.3gpp.mcdata-signalling MIME body; and
2. shall deliver the notification to the user or application.

6.1.9.3 Test description

6.1.9.3.1 Pre-test conditions

Test configuration:

- Single cell configuration according to TS 37.579-1 [2] clause 5.2.2.2.1.

Preamble:

- The UE has performed procedure 'Initial registration' as described in TS 37.579-1 [2] clause 5.4.2.
- UE States at the end of the preamble:
  - The UE is in RRC_IDLE state.
  - The client is registered for MCData.

6.1.9.3.2 Test procedure sequence

Table 6.1.9.3.2-1: Main Behaviour

St	Procedure	Message Sequence		TP	Verdict
		U - S	Message		
1	Make the UE (MCData client) send a one-to-one session SDS message with disposition request "**DELIVERY**". (NOTE 1)	-	-	-	-
2	Check: Does the UE (MCData client) correctly perform procedure '**CO MCData Call Establishment**' as described in TS 37.579-1 [2] Table 5.3C.2.3-1?	-	-	1,2	P
3-6	Void	-	-	-	-
7	Check: Does the UE (MCData client) correctly perform procedure '**CO MSRP message transfer**' as described in TS 37.579-1 [2] Table 5.3C.4.3-1 **to send an SDS message with disposition request "DELIVERY"**?	-	-	2	P
8	Check: Does the UE (MCData client) correctly perform procedure '**CT MSRP message transfer**' as described in TS 37.579-1 [2] Table 5.3C.5.3-1 **to receive the disposition notification** for the SDS message sent at step 7?	-	-	3	P
9	Void	-	-	-	-
10	Check: Does the UE (MCData client) provide the disposition notification to the user? (NOTE 1)	-	-	3	P
11	Check: Does the UE (MCData client) correctly perform procedure '**CT MSRP message transfer**' as described in TS 37.579-1 [2] Table 5.3C.5.3-1 **to receive an SDS message with disposition request "READ"**?	-	-	4	P
12	Void	-	-	-	-
-	EXCEPTION: In parallel to the event described in step 13 the events described in Table 6.1.9.3.2-2 take place. (NOTE 2)	-	-	-	-
13	Check: Does the UE (MCData client) provide the contents of the Payload IE to the user? (NOTE 1)	-	-	4	P
14-15	Void	-	-	-	-
16	Make the UE (MCData client) release the one-to-one session. (NOTE 1)	-	-	-	-
17	Check: Does the UE (MCData client) correctly perform procedure '**CO MCData call release**' as described in TS 37.579-1 [2] Table 5.3C.6.3-1? (NOTE 3)	-	-	3	P
18	The procedure 'MCX communication release' as described in TS 37.579-1 [2] clause 5.4.14 is performed to release the RRC connection.	-	-	-	-

NOTE 1: This is expected to be done via a suitable implementation dependent MMI.
NOTE 2: The behaviour is handled through parallel actions to allow for implementations which first indicate to the user that there is a message available, but render the message to the user only after the user takes an action to open the message.
NOTE 3: The procedure does not release the RRC connection.

Table 6.1.9.3.2-2: Parallel Behaviour

St	Procedure	Message Sequence		TP	Verdict
		U - S	Message		
1	Check: Does the UE (MCData client) correctly perform procedure '**CO MSRP message transfer**' as described in TS 37.579-1 [2] Table 5.3C.4.3-1 **to send a disposition notification of "READ"**?	-	-	2	P

6.1.9.3.3 Specific message contents

Table 6.1.9.3.3-1: SIP INVITE from the UE (step 2, Table 6.1.9.3.2-1; step 2, TS 37.579-1 [2] Table 5.3C.2.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.5.1-1, condition MCDATA_SDS, MCD_1to1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part		**SDP message**		
MIME-part-body	As described in Table 6.1.9.3.3-2			
MIME body part		**MCData-Info**		
MIME-part-body	MCData-Info as described in Table 6.1.9.3.3-3			

Table 6.1.9.3.3-2: SDP for SIP INVITE (Table 6.1.9.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.1.1-3, condition MCDATA_SDS, SDP_OFFER, SDS_SESSION, MCD_1to1

Table 6.1.9.3.3-3: MCData-Info (Table 6.1.9.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.2.1-3, condition MCD_1to1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
mcdata-info				
mcdata-Params				
request-type	"one-to-one-sds-session"			

Table 6.1.9.3.3-4: SIP 200 (OK) from the SS (step 2, Table 6.1.9.3.2-1; step 4, TS 37.579-1 [2] Table 5.3C.2.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.17.1.2-1, condition INVITE-RSP				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
SDP message	As described in Table 6.1.5.9.3-5			

Table 6.1.9.3.3-5: SDP for SIP 200 (OK) (Table 6.1.9.3.3-4)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.1.2-3, condition MCDATA_SDS, SDP_ANSWER, SDS_SESSION

Table 6.1.9.3.3-6: MSRP SEND from the UE (step 7, Table 6.1.9.3.2-1; step 1, TS 37.579-1 [2] Table 5.3C.4.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.12.1.1-1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Content-Type				
media-type	"multipart/mixed"			
data	Message or chunk of message as specified in table 6.1.9.3.3-6A			

Table 6.1.9.3.3-6A: MIME Message (step 7, Table 6.1.9.3.2-1; step 3, TS 37.579-1 [2] Table 5.3C.4.3-1)

Derivation Path: RFC 2046 [38]				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
MIME body part		**MCData Data signalling message**		
MIME-part-headers				
Content-Type	"application/vnd.3gpp. mcdata-signalling"			
MIME-part-body	MCData Protected Payload Message containing SDS SIGNALLING PAYLOAD as described in table 6.1.9.3.3-6B			
MIME body part		**MCData Data message**		
MIME-part-headers				
Content-Type	"application/vnd.3gpp. mcdata-payload"			
MIME-part-body	DATA PAYLOAD as described in Table 6.1.9.3.3-7			

Table 6.1.9.3.3-6B: SDS SIGNALLING PAYLOAD (Table 6.1.9.3.3-6A)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.1-1, condition DELIVERED

Table 6.1.9.3.3-7: Data Payload (Table 6.1.9.3.3-6A)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.9.2-1

Table 6.1.9.3.3-8..9: Void

Table 6.1.9.3.3-10: MSRP SEND from the SS (step 8, Table 6.1.9.3.2-1; step 1, TS 37.579-1 [2] Table 5.3C.5.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.12.1.2-1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Content-Type				
media-type	"application/vnd.3gpp. mcdata-signalling"			
data	MCData Protected Payload Message containing SDS NOTIFICATION as specified in table 6.1.9.3.3-11			

Table 6.1.9.3.3-11: SDS NOTIFICATION (Table 6.1.9.3.3-10)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.4-1, condition DELIVERED

Table 6.1.9.3.3-12: MSRP SEND from the SS (step 11, Table 6.1.9.3.2-1; step 1, TS 37.579-1 [2] Table 5.3C.5.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.12.1.2-1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Content-Type				
media-type	"multipart/mixed"			
data	Message as specified in table 6.1.9.3.3-12A			

Table 6.1.9.3.3-12A: MIME Message (step 11, Table 6.1.9.3.2-1; step 1, TS 37.579-1 [2] Table 5.3C.5.3-1)

Derivation Path: RFC 2046 [38]				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
MIME body part		**MCData Data signalling message**		
MIME-part-headers				
Content-Type	"application/vnd.3gpp. mcdata-signalling"			
MIME-part-body	MCData Protected Payload Message containing SDS SIGNALLING PAYLOAD as described in table 6.1.9.3.3-13			
MIME body part		**MCData Data message**		
MIME-part-headers				
Content-Type	"application/vnd.3gpp. mcdata-payload"			
MIME-part-body	DATA PAYLOAD as described in Table 6.1.9.3.3-13A			

Table 6.1.9.3.3-13: SDS SIGNALLING PAYLOAD (Table 6.1.9.3.3-12A)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.2-1, condition READ

Table 6.1.9.3.3-13A: Data Payload (Table 6.1.9.3.3-12A)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.9.2-2

Table 6.1.9.3.3-14: MSRP SEND from the UE (step 1, Table 6.1.9.3.2-2; step 3, TS 37.579-1 [2] Table 5.3C.4.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.12.1.1-1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Content-Type				
media-type	"application/vnd.3gpp.mcdata-signalling"			
data	MCData Protected Payload Message containing SDS NOTIFICATION as specified in table 6.1.9.3.3-15			

Table 6.1.9.3.3-15: SDS NOTIFICATION (Table 6.1.9.3.3-14)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.3-1, condition READ

Table 6.1.9.3.3-16..17: Void

6.1.10 On-network / Short Data Service (SDS) / SDS Session / One-to-one SDS Session / Client Terminated (CT)

6.1.10.1 Test Purpose (TP)

(1)

```
with { UE (MCDATA Client) registered and authorised for MCDATA Service }
ensure that {
  when { the MCDATA User receives a SIP INVITE to initiate a one-to-one SDS session using the media
plane }
    then { UE (MCDATA Client) responds by sending a SIP 200 (OK) message }
            }
```

(2)

```
with { UE (MCDATA Client) having responded to the SIP INVITE message that initiated a one-to-one SDS
session using the media plane }
ensure that {
  when { UE (MCDATA Client) receives an MSRP SEND message }
    then { UE (MCDATA Client) responds with an MSRP 200 (OK) message and if the MSRP SEND message is
not blank, renders the contents of the Payload IE to the MCDATA User and sends a SIP MESSAGE message
with a disposition notification of "DELIVERED" }
            }
```

(3)

```
with { UE (MCDATA Client) being in a one-to-one SDS session initiated by the SS (MCDATA server) }
ensure that {
  when { the MCDATA User requests to send a one-to-one SDS Session message with a disposition of
"READ" }
    then { UE (MCDATA Client) sends a one-to-one session SDS message via a MSRP SEND message with a
disposition of "DELIVERY" }
            }
```

(4)

```
with { UE (MCDATA Client) having sent a one-to-one SDS session message using the media plane with a
disposition of "READ" }
ensure that {
  when { UE (MCDATA Client) receives a disposition response via a MSRP SEND message }
```

```
    then { UE (MCDATA Client) responds to the MSRP SEND message by sending a MSRP 200 (OK) message
and delivers the notification to the MCDATA User }
            }
```

(5)

```
with { UE (MCDATA Client) being in a one-to-one SDS session initiated by the SS (MCDATA server) }
ensure that {
  when { UE (MCDATA Client) receives a SIP BYE message }
    then { UE (MCDATA Client) responds by sending a SIP 200 (OK) message }
            }
```

6.1.10.2 Conformance requirements

References: The conformance requirements covered in the current TC are specified in: TS 24.282, clauses 9.2.4.2.4, 9.2.4.2.2, 13.2.2.2.2.2, TS 24.582 clauses 6.1.2.3.1, 6.1.2.3.1, 6.1.2.4, 6.1.2.5.1, 6.1.2.5.2, 6.1.2.5.3, 6.1.2.6. The following represents a copy/paste extraction of the requirements relevant to the test purpose; any references within the copy/paste text should be understood within the scope of the core spec they have been copied from. Unless otherwise stated, these are Rel-14 requirements.

[TS 24.282, clause 9.2.4.2.4]

Upon receipt of an initial SIP INVITE request, the MCData client shall follow the procedures for termination of multimedia sessions in the IM CN subsystem as specified in 3GPP TS 24.229 [5] with the clarifications below.

The MCData client:

1) may reject the SIP INVITE request if either of the following conditions are met:

   a) MCData client does not have enough resources to handle the call; or

   b) any other reason outside the scope of this specification;

   and skip the rest of the steps after step 2;

2) if the SIP INVITE request is rejected in step 1), shall respond toward participating MCData function either with appropriate reject code as specified in 3GPP TS 24.229 [5] and warning texts as specified in subclause 4.9 or with SIP 480 (Temporarily unavailable) response not including warning texts if the user is authorised to restrict the reason for failure and skip the rest of the steps of this subclause;

3) if the SDP offer of the SIP INVITE request contains an "a=key-mgmt" attribute field with a "mikey" attribute value containing a MIKEY-SAKKE I_MESSAGE:

   a) shall extract the MCData ID of the originating MCData user from the initiator field (IDRi) of the I_MESSAGE as described in 3GPP TS 33.180 [26];

   b) shall convert the MCData ID to a UID as described in 3GPP TS 33.180 [26];

   c) shall use the UID to validate the signature of the MIKEY-SAKKE I_MESSAGE as described in 3GPP TS 33.180 [26];

   d) if authentication verification of the MIKEY-SAKKE I_MESSAGE fails, shall reject the SIP INVITE request with a SIP 488 (Not Acceptable Here) response as specified in IETF RFC 4567 [45], and include warning text set to "136 authentication of the MIKEY-SAKKE I_MESSAGE failed" in a Warning header field as specified in subclause 4.9 and not continue with rest of the steps in this subclause; and

   e) if the signature of the MIKEY-SAKKE I_MESSAGE was successfully validated:

      i) shall extract and decrypt the encapsulated PCK using the terminating user's (KMS provisioned) UID key as described in 3GPP TS 33.180 [26]; and

      ii) shall extract the PCK-ID, from the payload as specified in 3GPP TS 33.180 [26];

NOTE: With the PCK successfully shared between the originating MCData client and the terminating MCData client, both clients are able to create an end-to-end secure session.

4) may display to the MCData user the MCData ID of the inviting MCData user and the type of SDS request;

5) shall accept the SIP INVITE request and generate a SIP 200 (OK) response according to rules and procedures of 3GPP TS 24.229 [5];

6) shall include the option tag "timer" in a Require header field of the SIP 200 (OK) response;

7) shall include the Session-Expires header field in the SIP 200 (OK) response and start the SIP session timer according to IETF RFC 4028 [38]. The "refresher" parameter in the Session-Expires header field shall be set to "uas";

8) shall include the g.3gpp.mcdata.sds media feature tag in the Contact header field of the SIP 200 (OK) response;

9) shall include the g.3gpp.icsi-ref media feature tag containing the value of "urn:urn-7:3gpp-service.ims.icsi.mcdata.sds" in the Contact header field of the SIP 200 (OK) response;

10) shall include an SDP answer in the SIP 200 (OK) response to the SDP offer in the incoming SIP INVITE request according to 3GPP TS 24.229 [5] with the clarifications given in subclause 9.2.4.2.2; and

11) shall send the SIP 200 (OK) response towards the MCData server according to rules and procedures of 3GPP TS 24.229 [5].

On receipt of an SIP ACK message to the sent SIP 200 (OK) message, the MCData client shall:

1) shall interact with the media plane as specified in 3GPP TS 24.582 [15] subclause 6.1.2.3.

To send a disposition notification after the media plane is released, the MCData client:

1) shall follow the procedures described in subclause 12.2.1.1.

[TS 24.282, clause 9.2.4.2.2]

When the MCData client receives an initial SDP offer for an MCData SDS session, the MCData client shall process the SDP offer and shall compose an SDP answer according to 3GPP TS 24.229 [5] and IETF RFC 4975 [17].

When composing an SDP answer, the MCData client:

1) shall include an "m=message" media-level section for the accepted MCData media stream consisting of:

   a) the port number;

   b) a protocol field value of "TCP/MSRP" or "TCP/TLS/MSRP" for TLS according to the received SDP offer;

   c) an "a=sendrecv" attribute;

   d) an "a=path" attribute containing its own MSRP URI;

   e) set the content type as a=accept-types: application/vnd.3gpp.mcdata-signalling application/vnd.3gpp.mcdata-payload; and

   f) set the a=setup attribute according to IETF RFC 6135 [19].

[TS 24.282, clause 13.2.2.2.2.2]

Upon receiving a SIP BYE request, the MCData client:

1) shall send SIP 200 (OK) response towards MCData server according to 3GPP TS 24.229 [5]; and

2) shall release all media plane resources corresponding to the MCData communication being released.

NOTE: Partially received data can be stored and processed.

[TS 24.582, clause 6.1.2.3.1]

Upon receiving an indication to establish MSRP connection for SDS session as the terminating MCData client, the MCData client:

1. shall act as an MSRP client according to IETF RFC 6135 [12];

2. shall act either as an active endpoint or as an passive endpoint to open the transport connection, according to IETF RFC 6135 [12];

3. shall establish the MSRP connection according to the MSRP connection parameters in the SDP offer received in the SIP INVITE request according to IETF RFC 4975 [11];

4. if acting as an "active" endpoint, shall send an empty MSRP SEND request to bind the MSRP connection to the MSRP session from the perspective of the passive endpoint according to the rules and procedures of IETF RFC 4975 [11] and IETF RFC 6135 [12];

Once the MSRP session is established, the MCData client:

1. on receipt of an MSRP request in the MSRP session, shall follow the rules and procedures defined in IETF RFC 4975 [11] and in IETF RFC 6714 [13];

2. If an MSRP SEND request indicates the use of chunking, shall wait until all further MSRP SEND requests for the remaining chunks have been received and shall reassemble the entire set of MSRP requests into the MCData SDS message before delivering the content to the application; and

3. shall handle the received content as described in subclause 6.1.2.6.

On receiving MSRP 200 (OK) response to the first MSRP SEND request sent as "active" endpoint, or after sending MSRP 200 (OK) response to the first MSRP SEND request received as "passive" endpoint, the MCData client can generate and send an SDS message as specified in subclause 6.1.2.4, or can generate and send an SDS disposition notification for a received SDS message as specified in subclause 6.1.2.5, if requested.

Received content and disposition requests shall be handled as specified in subclause 6.1.2.6.

[TS 24.582, clause 6.1.2.4]

An MCData client is allowed to send an one-to-one SDS message only if

1. the <allow-transmit-data> element of an <actions> element is present with a value "true" (see the MCData user profile document in 3GPP TS 24.484 [7]);

2. the size of the SDS message is less than or equal to the value of the <max-data-size-sds-bytes> element in the MCData service configuration document as specified in 3GPP TS 24.484 [7]; and

3. the size of the SDS message is less than or equal to the value of <MaxData1To1> element of the MCData user profile document (see the MCData user profile document in 3GPP TS 24.484 [7]).

An MCData client is allowed to send a group SDS message only if

1. the <mcdata-allow-transmit-data-in-this-group> element of an <action> element is present with a value "true" as defined in the MCData group document for this MCData group as specified in 3GPP TS 24.481 [4];

2. the size of the SDS message is less than or equal to the value contained in the <mcdata-on-network-max-data-size-for-SDS> as defined in the MCData group document for this MCData group as specified in 3GPP TS 24.481 [4]; and

3. the size of the SDS message is less than or equal to the value contained in the <mcdata-max-data-in-single-request> element of the <entry> element of the MCData group document for this MCData group as specified in 3GPP TS 24.481 [11].

If the above mentioned conditions satisfy, the MCData client:

1. shall generate a SDS SIGNALLING PAYLOAD as specified in subclause 6.1.1.2.2;

2. shall generate a SDS DATA PAYLOAD as specified in subclause 6.1.1.2.3;

3. shall include the SDS SIGNALLING PAYLOAD and SDS DATA PAYLOAD in an MSRP SEND request as specified in subclause 6.1.1.2.4, with the following clarification;

   a. shall set To-Path header according to the MSRP URI in the received SDP; and

4. shall send the MSRP SEND request on the established MSRP connection.

NOTE: MSRP chunking, if needed, may affect the number of "Content Type" lines in each MSRP SEND message conveying a chunk, as also specified in subclause 6.1.1.2.4.

[TS 24.582, clause 6.1.2.5.1]

To send an SDS disposition notification, the MCData client:

1. shall generate a SDS NOTIFICATION as specified in subclause 6.1.2.5.2;
2. shall include the SDS NOTIFICATION in an MSRP SEND request as specified in subclause 6.1.2.5.3, with the following clarification;
   a. shall set To-Path header according to the MSRP URI in the received SDP; and
3. shall send the MSRP SEND request on the established MSRP connection.

If MSRP chunking is used, the MCData client:

1. shall send further MSRP SEND requests as necessary.

On receiving a non-200 MSRP response to the MSRP SEND request the MCData client shall handle the error as specified in IETF RFC 4975 [11]. To terminate the MSRP session, the MCData client:

1. if there are further MSRP chunks to send, shall abort transmission of these further MSRP chunks; and
2. shall indicate to MCData user that the SDS message or the SDS disposition notification could not be sent.

[TS 24.582, clause 6.1.2.5.2]

In order to generate an SDS notification, the MCData client:

1. shall generate an SDS NOTIFICATION message as specified in 3GPP TS 24.282 [8]; and
2. shall include the SDS NOTIFICATION message in an application/vnd.3gpp.mcdata-signalling MIME body as specified in 3GPP TS 24.282 [8].

When generating an SDS NOTIFICATION message, the MCData client:

1. if sending a delivered notification, shall set the SDS disposition notification type IE as "DELIVERED";
2. if sending a read notification, shall set the SDS disposition notification type IE as "READ";
3. if sending a delivered and read notification, shall set the SDS disposition notification type IE as "DELIVERED AND READ";
4. if the SDS message could not be delivered to the user or application (e.g. due to lack of storage), shall set the SDS disposition notification type IE as "UNDELIVERED";
5. shall set the Date and time IE to the current time;
6. shall set the Conversation ID to the value of the Conversation ID that was received in the SDS message;
7. shall set the Message ID to the value of the Message ID that was received in the SDS message;
8. if the SDS message was destined for the user, shall not include an Application ID IE; and
9. if the SDS message was destined for an application, shall include an Application ID IE set to the value of the Application ID that was included in the SDS message.

[TS 24.582, clause 6.1.2.5.3]

The MCData client shall generate MSRP SEND requests for SDS disposition notification according to IETF RFC 4975 [11].

When generating an MSRP SEND request for SDS disposition notification containing an SDS NOTIFICATION message, the MCData client

1. shall set To-Path header according to the MSRP URI(s) received in the answer SDP;

2. shall set the content type as Content-Type = "application/vnd.3gpp.mcdata-signalling"; and
3. shall set the body of the MSRP SEND request to the generated SDS NOTIFICATION message.

[TS 24.582, clause 6.1.2.6]

Upon receiving an SDS message, the MCData client:

1. shall follow the procedure defined in subclause 6.1.1.3.2, with the following clarification:
   a. if SDS Disposition request type IE is present in the received SDS SIGNALLING PAYLOAD message then, shall send an SDS disposition notification as described in subclause 6.1.2.5.

Upon receiving an SDS disposition notification, the MCData client:

1. shall decode the contents of the application/vnd.3gpp.mcdata-signalling MIME body; and
2. shall deliver the notification to the user or application.

6.1.10.3 Test description

6.1.10.3.1 Pre-test conditions

Test configuration:

- Single cell configuration according to TS 37.579-1 [2] clause 5.2.2.2.1.

Preamble:

- The UE has performed procedure 'Initial registration' as described in TS 37.579-1 [2] clause 5.4.2.
- UE States at the end of the preamble:
  - The UE is in RRC_IDLE state.
  - The client is registered for MCData.

6.1.10.3.2 Test procedure sequence

Table 6.1.10.3.2-1: Main Behaviour

St	Procedure	Message Sequence		TP	Verdict
		U - S	Message		
1	Check: Does the UE (MCData client) correctly perform procedure '**CT MCData Call Establishment**' as described in TS 37.579-1 [2] Table 5.3C.3.3-1?	-	-	1,2	P
2-5	Void	-	-	-	-
6	Check: Does the UE (MCData client) correctly perform procedure '**CT MSRP message transfer**' as described in TS 37.579-1 [2] Table 5.3C.5.3-1 **to receive an SDS message with disposition request "DELIVERY"**?	-	-	2	P
7	Void	-	-	-	-
8	Check: Does the UE (MCData client) correctly perform procedure '**CO MSRP message transfer**' as described in TS 37.579-1 [2] Table 5.3C.4.3-1 **to send a disposition notification of "DELIVERED"**?	-	-	2	P
9	Void	-	-	-	-
10	Check: Does the UE (MCData client) provide the contents of the Payload IE to the user? (NOTE 1)	-	-	2	P
11	Make the UE (MCData client) send a one-to-one session SDS message over the media plane with disposition request "READ". (NOTE 1)	-	-	-	-
12	Check: Does the UE (MCData client) correctly perform procedure '**CO MSRP message transfer**' as described in TS 37.579-1 [2] Table 5.3C.4.3-1 **to send an SDS message with disposition request "READ"**?	-	-	3	P
13	Check: Does the UE (MCData client) correctly perform procedure '**CT MSRP message transfer**' as described in TS 37.579-1 [2] Table 5.3C.5.3-1 **to receive the disposition notification** for the SDS message sent at step 12?	-	-	4	P
14	Void	-	-	-	-
15	Check: Does the UE (MCData client) provide the disposition notification to the user? (NOTE 1)	-	-	4	P
16	Check: Does the UE (MCData client) correctly perform procedure '**CT MCData call release**' as described in TS 37.579-1 [2] Table 5.3C.7.3-1? (NOTE 2)	-	-	5	P
17	The procedure 'MCX communication release' as described in TS 37.579-1 [2] clause 5.4.14 is performed to release the RRC connection.	-	-	-	-
NOTE 1: This is expected to be done via a suitable implementation dependent MMI. NOTE 2: The procedure does not release the RRC connection.					

6.1.10.3.3 Specific message contents

Table 6.1.10.3.3-1: SIP INVITE from the SS (step 1, Table 6.1.10.3.2-1; step 2, TS 37.579-1 [2] Table 5.3C.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.5.2-1, condition MCDATA_SDS				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part		**SDP message**		
MIME-part-body	SDP message as described in Table 6.1.10.3.3-2			
MIME body part		**MCData-Info**		
MIME-part-body	MCData-Info as described in Table 6.1.10.3.3-3			

Table 6.1.10.3.3-2: SDP for SIP INVITE (Table 6.1.10.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.1.2-3, condition MCDATA_SDS, SDP_OFFER, MCD_1to1, SDS_SESSION

Table 6.1.10.3.3-3: MCData-Info (Table 6.1.10.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.2.2-3, condition MCD_1to1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
mcdata-info				
mcdata-Params				
request-type	"one-to-one-sds-session"			

Table 6.1.10.3.3-4: SIP 200 (OK) from the UE (step 1, Table 6.1.10.3.2-1; step 4, TS 37.579-1 [2] Table 5.3C.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.17.1.1-1, condition INVITE-RSP, MCDATA_SDS				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Content-Type				
value	"application/sdp"			
Message-body				
SDP message	As described in Table 6.1.10.3.3-5			

Table 6.1.10.3.3-5: SDP for SIP 200 (OK) (Table 6.1.10.3.3-4)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.1.1-3, condition MCDATA_SDS, SDP_ANSWER, SDS_SESSION

Table 6.1.10.3.3-6: MSRP SEND from the SS (step 6, Table 6.1.10.3.2-1; step 1, TS 37.579-1 [2] Table 5.3C.5.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.12.1.2-1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Content-Type				
media-type	"multipart/mixed"			
data	Message as specified in table 6.1.10.3.3-6A			

Table 6.1.10.3.3-6A: MIME Message (step 6, Table 6.1.10.3.2-1; step 1, TS 37.579-1 [2] Table 5.3C.5.3-1)

Derivation Path: RFC 2046 [38]				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
MIME body part		**MCData Data signalling message**		
MIME-part-headers				
Content-Type	"application/vnd.3gpp. mcdata-signalling"			
MIME-part-body	MCData Protected Payload Message containing SDS SIGNALLING PAYLOAD as described in table 6.1.10.3.3-6B			
MIME body part		**MCData Data message**		
MIME-part-headers				
Content-Type	"application/vnd.3gpp. mcdata-payload"			
MIME-part-body	DATA PAYLOAD as described in Table 6.1.10.3.3-7			

Table 6.1.10.3.3-6B: SDS SIGNALLING PAYLOAD (Table 6.1.10.3.3-6A)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.2-1, condition DELIVERED

Table 6.1.10.3.3-7: Data Payload (Table 6.1.10.3.3-6A)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.9.2-2

Table 6.1.10.3.3-8: MSRP SEND from the UE (step 8, Table 6.1.10.3.2-1; step 3, TS 37.579-1 [2] Table 5.3C.4.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.12.1.1-1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Content-Type				
media-type	"application/vnd.3gpp. mcdata-signalling"			
data	MCData Protected Payload Message containing SDS NOTIFICATION as specified in table 6.1.10.3.3-9			

Table 6.1.10.3.3-9: SDS NOTIFICATION (Table 6.1.10.3.3-8)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.3-1, condition DELIVERED

Table 6.1.10.3.3-10: MSRP SEND from the UE (step 12, Table 6.1.10.3.2-1; step 1, TS 37.579-1 [2] Table 5.3C.4.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.12.1.1-1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Content-Type				
media-type	"multipart/mixed"			
data	Message or chunk of message as specified in table 6.1.10.3.3-10A			

Table 6.1.10.3.3-10A: MIME Message (step 12, Table 6.1.10.3.2-1; step 3, TS 37.579-1 [2] Table 5.3C.4.3-1)

Derivation Path: RFC 2046 [38]				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
MIME body part		**MCData Data signalling message**		
MIME-part-headers				
Content-Type	"application/vnd.3gpp. mcdata-signalling"			
MIME-part-body	MCData Protected Payload Message containing SDS SIGNALLING PAYLOAD as described in table 6.1.10.3.3-11			
MIME body part		**MCData Data message**		
MIME-part-headers				
Content-Type	"application/vnd.3gpp. mcdata-payload"			
MIME-part-body	DATA PAYLOAD as described in Table 6.1.10.3.3-12			

Table 6.1.10.3.3-11: SDS SIGNALLING PAYLOAD (Table 6.1.10.3.3-10A)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.1-1, condition READ

Table 6.1.10.3.3-12: Data Payload (Table 6.1.10.3.3-10A)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.9.2-1

Table 6.1.10.3.3-13..14: Void

Table 6.1.10.3.3-15: MSRP SEND from the SS (step 13, Table 6.1.10.3.2-1; step 1, TS 37.579-1 [2] Table 5.3C.5.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.12.1.2-1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Content-Type				
media-type	"application/vnd.3gpp.mcdata-signalling"			
data	MCData Protected Payload Message containing SDS NOTIFICATION as specified in table 6.1.10.3.3-16			

Table 6.1.10.3.3-16: SDS NOTIFICATION (Table 6.1.10.3.3-15)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.4-1, condition READ

Table 6.1.10.3.3-17..18: Void

6.1.11 On-network / Short Data Service (SDS) / SDS Session / Group SDS Session / Client Originated (CO)

6.1.11.1 Test Purpose (TP)

(1)

```
with { UE (MCDATA Client) registered and authorised for MCDATA Service }
ensure that {
  when { the MCDATA User requests to initiate a group SDS session using the media plane}
    then { UE (MCDATA Client) sends a request to establish a group SDS session and a MSRP connection
via a SIP INVITE message and then responds to the SIP 200 (OK) message with a SIP ACK message }
            }
```

(2)

```
with { UE (MCDATA Client) having received a SIP 200 (OK) message with the a=setup attribute set to
"passive" }
ensure that {
  when { UE (MCDATA Client) responds to the SIP 200 (OK) message with a SIP ACK message }
    then { UE (MCDATA Client)  sends a blank MSRP SEND message to bind the MSRP connection and then
sends the group session SDS message via a MSRP SEND message with a disposition of "DELIVERY" }
            }
```

(3)

```
with { UE (MCDATA Client) having sent a group session SDS message using the media plane with a
disposition of "DELIVERY" }
ensure that {
  when { UE (MCDATA Client) receives a disposition response via a MSRP SEND message }
    then { UE (MCDATA Client) responds to the MSRP SEND message by sending a MSRP 200 (OK) message
and delivers the notification to the MCDATA User }
            }
```

(4)

```
with { UE (MCDATA Client) having established a group SDS session and a MSRP connection }
ensure that {
  when { UE (MCDATA Client) receives an MSRP SEND message with a disposition of "DELIVERY AND READ"
}
    then { UE (MCDATA Client) responds with a MSRP 200 (OK) message }
            }
```

(5)

```
with { UE (MCDATA Client) having responded with a MSRP 200(OK) message to a group SDS session
message with a disposition of "DELIVERY AND READ" and timer TDU1 (delivery and read) not yet expired
}
ensure that {
  when { the UE (MCDATA Client) determines that the payload contained in the DATA PAYLOAD message is
for user consumption and before timer TDU1 (delivery and read) expires }
    then { the UE (MCDATA Client) renders the contents of the Payload IE to the MCDATA User and then
sends a MSRP SEND message with a disposition notification of "DELIVERED AND READ" }
            }
```

(6)

```
with { UE (MCDATA Client) having responded with a MSRP 200(OK) message to a group SDS session
message with a disposition of "DELIVERY AND READ" and the UE (MCDATA Client) not yet rendering the
contents of the Payload IE to the MCDATA User }
ensure that {
  when { timer TDU1 (delivery and read) expires }
    then { UE (MCDATA Client) sends a MSRP SEND message with a disposition notification of
"DELIVERED" and then renders the contents of the Payload IE to the MCDATA User and then sends a MSRP
SEND message with a disposition notification of "READ" }
            }
```

(7)

```
with { UE (MCDATA Client) having established a group SDS session }
ensure that {
  when { the MCDATA User requests to release the group SDS session }
    then { UE (MCDATA Client) sends a SIP BYE message }
            }
```

6.1.11.2 Conformance requirements

References: The conformance requirements covered in the current TC are specified in: TS 24.282, clauses 9.2.4.2.3, 9.2.4.2.1, 13.2.2.2.2.1, TS 24.582 clauses 6.1.2.2.1, 6.1.2.3.1, 6.1.2.4, 6.1.2.5.1, 6.1.2.5.2, 6.1.2.5.3, 6.1.2.6. The following represents a copy/paste extraction of the requirements relevant to the test purpose; any references within the copy/paste text should be understood within the scope of the core spec they have been copied from. Unless otherwise stated, these are Rel-14 requirements.

[TS 24.282, clause 9.2.4.2.3]

The MCData client shall generate a SIP INVITE request in accordance with 3GPP TS 24.229 [5] with the clarifications given below.

The MCData client:

1) shall include the g.3gpp.mcdata.sds media feature tag and the g.3gpp.icsi-ref media feature tag with the value of "urn:urn-7:3gpp-service.ims.icsi.mcdata.sds" in the Contact header field of the SIP INVITE request according to IETF RFC 3840 [16];

2) shall include an Accept-Contact header field containing the g.3gpp.mcdata.sds media feature tag along with the "require" and "explicit" header field parameters according to IETF RFC 3841 [8];

3) shall include an Accept-Contact header field with the g.3gpp.icsi-ref media feature tag containing the value of "urn:urn-7:3gpp-service.ims.icsi.mcdata.sds" along with the "require" and "explicit" header field parameters according to IETF RFC 3841 [8];

4) shall include the ICSI value "urn:urn-7:3gpp-service.ims.icsi.mcdata.sds" (coded as specified in 3GPP TS 24.229 [5]), in a P-Preferred-Service header field according to IETF RFC 6050 [7] in the SIP INVITE request;

5) should include the "timer" option tag in the Supported header field;

6) should include the Session-Expires header field according to IETF RFC 4028 [38]. It is recommended that the "refresher" header field parameter is omitted. If included, the "refresher" header field parameter shall be set to "uac";

…

8) if a group SDS session is requested:

   a) if the "/<*x*>/<x>/Common/MCData/AllowedSDS" leaf node present in the group document of the requested MCData group, configured on the group management client as specified in 3GPP TS 24.483 [42] is set to "false", shall reject the request to send SDS and not continue with the rest of the steps in this subclause; and

   b) shall contain in an application/vnd.3gpp.mcdata-info+xml MIME body with the <mcdatainfo> element containing the <mcdata-Params> element with:

      i) the <request-type> element set to a value of "group-sds-session";

      ii) the <mcdata-request-uri> element set to the MCData group identity; and

      iii) the <mcdata-client-id> element set to the MCData client ID of the originating MCData client;

NOTE 1: The MCData client does not include the MCData ID of the originating MCData user in the body, as this will be inserted into the body of the SIP INVITE request that is sent from the originating participating MCData function.

9) shall set the Request-URI of the SIP INVITE request to the public service identity identifying the participating MCData function serving the MCData user;

NOTE 2: The MCData client is configured with public service identity identifying the participating MCData function serving the MCData user.

10) may include a P-Preferred-Identity header field in the SIP INVITE request containing a public user identity as specified in 3GPP TS 24.229 [5];

11) shall include an SDP offer according to 3GPP TS 24.229 [5] with the clarifications given in subclause 9.2.4.2.1; and

12) shall send the SIP INVITE request towards the MCData server according to 3GPP TS 24.229 [5].

On receipt of a SIP 2xx response to the SIP INVITE request, the MCData client:

1) shall send a SIP ACK request as specified in 3GPP TS 24.229 [5];

2) shall start the SIP Session timer according to rules and procedures of IETF RFC 4028 [38]; and

3) shall interact with the media plane as specified in 3GPP TS 24.582 [15] subclause 6.1.2.2.

[TS 24.282, clause 9.2.4.2.1]

When composing an SDP offer according to 3GPP TS 24.229 [5], IETF RFC 4975 [17], IETF RFC 6135 [19] and IETF RFC 6714 [20] the MCData client:

1) shall include an "m=message" media-level section for the MCData media stream consisting of:

   a) the port number;

   b) a protocol field value of "TCP/MSRP" or "TCP/TLS/MSRP" for TLS;

   c) an "a=sendrecv" attribute;

   d) an "a=path" attribute containing its own MSRP URI;

   e) set the content type as "a=accept-types:application/vnd.3gpp.mcdata-signalling application/vnd.3gpp.mcdata-payload"; and

   f) set the a=setup attribute as "actpass"; and

2) if end-to-end security is required for a one-to-one communication and the security context does not exist or if the existing security context has expired, shall include the MIKEY-SAKKE I_MESSAGE in an "a=key-mgmt" attribute as a "mikey" attribute value in the SDP offer as specified in IETF RFC 4567 [45].

[TS 24.282, clause 13.2.2.2.2.1]

When the MCData client wants to release a MCData communication established over the media plane, the MCData client:

1) shall generate a SIP BYE request according to 3GPP TS 24.229 [5];

2) shall set the Request-URI to the MCData session identity to be released; and

3) shall send the SIP BYE request towards MCData server according to 3GPP TS 24.229 [5].

Upon receiving a SIP 200 (OK) response to the SIP BYE request, the MCData client shall release all media plane resources corresponding to the MCData communication being released.

[TS 24.582, clause 6.1.2.2.1]

Upon receiving an indication to establish MSRP connection for SDS session as the originating MCData client, the MCData client:

1. shall act as an MSRP client according to IETF RFC 6135 [12];

2. shall act according to IETF RFC 6135 [12], as:

   a. an "active" endpoint, if a=setup attribute in the received SDP answer is set to "passive"; and

   b. an "passive" endpoint, if a=setup attribute in the received SDP answer is set to "active";

3. shall establish the MSRP connection according to the MSRP connection parameters in the SDP answer received in the SIP 200 (OK) response according to IETF RFC 4975 [11];

4. if acting as an "active" endpoint, shall send an empty MSRP SEND request to bind the MSRP connection to the MSRP session from the perspective of the passive endpoint according to the rules and procedures of IETF RFC 4975 [11] and IETF RFC 6135 [12];

Once the MSRP session is established, the MCData client:

1. on receipt of an MSRP request in the MSRP session, shall follow the rules and procedures defined in IETF RFC 4975 [11] and in IETF RFC 6714 [13];

2. If an MSRP SEND request indicates the use of chunking, shall wait until all further MSRP SEND requests for the remaining chunks have been received and shall reassemble the entire set of MSRP requests into the MCData SDS message before delivering the content to the application; and

3. shall handle the received content as described in subclause 6.1.2.6.

On receiving MSRP 200 (OK) response to the first MSRP SEND request, the MCData client can generate and send an SDS message as specified in subclause 6.1.2.4, or can generate and send an SDS disposition notification for a received SDS message as specified in subclause 6.1.2.5, if requested.

Received content and disposition requests shall be handled as specified in subclause 6.1.2.6.

[TS 24.582, clause 6.1.2.3.1]

Upon receiving an indication to establish MSRP connection for SDS session as the terminating MCData client, the MCData client:

1. shall act as an MSRP client according to IETF RFC 6135 [12];

2. shall act either as an active endpoint or as an passive endpoint to open the transport connection, according to IETF RFC 6135 [12];

3. shall establish the MSRP connection according to the MSRP connection parameters in the SDP offer received in the SIP INVITE request according to IETF RFC 4975 [11];

4. if acting as an "active" endpoint, shall send an empty MSRP SEND request to bind the MSRP connection to the MSRP session from the perspective of the passive endpoint according to the rules and procedures of IETF RFC 4975 [11] and IETF RFC 6135 [12];

Once the MSRP session is established, the MCData client:

1. on receipt of an MSRP request in the MSRP session, shall follow the rules and procedures defined in IETF RFC 4975 [11] and in IETF RFC 6714 [13];

2. If an MSRP SEND request indicates the use of chunking, shall wait until all further MSRP SEND requests for the remaining chunks have been received and shall reassemble the entire set of MSRP requests into the MCData SDS message before delivering the content to the application; and

3. shall handle the received content as described in subclause 6.1.2.6.

On receiving MSRP 200 (OK) response to the first MSRP SEND request sent as "active" endpoint, or after sending MSRP 200 (OK) response to the first MSRP SEND request received as "passive" endpoint, the MCData client can generate and send an SDS message as specified in subclause 6.1.2.4, or can generate and send an SDS disposition notification for a received SDS message as specified in subclause 6.1.2.5, if requested.

Received content and disposition requests shall be handled as specified in subclause 6.1.2.6.

[TS 24.582, clause 6.1.2.4]

An MCData client is allowed to send an one-to-one SDS message only if

1. the <allow-transmit-data> element of an <actions> element is present with a value "true" (see the MCData user profile document in 3GPP TS 24.484 [7]);

2. the size of the SDS message is less than or equal to the value of the <max-data-size-sds-bytes> element in the MCData service configuration document as specified in 3GPP TS 24.484 [7]; and

3. the size of the SDS message is less than or equal to the value of <MaxData1To1> element of the MCData user profile document (see the MCData user profile document in 3GPP TS 24.484 [7]).

An MCData client is allowed to send a group SDS message only if

1. the <mcdata-allow-transmit-data-in-this-group> element of an <action> element is present with a value "true" as defined in the MCData group document for this MCData group as specified in 3GPP TS 24.481 [4];

2. the size of the SDS message is less than or equal to the value contained in the <mcdata-on-network-max-data-size-for-SDS> as defined in the MCData group document for this MCData group as specified in 3GPP TS 24.481 [4]; and

3. the size of the SDS message is less than or equal to the value contained in the <mcdata-max-data-in-single-request> element of the <entry> element of the MCData group document for this MCData group as specified in 3GPP TS 24.481 [11].

If the above mentioned conditions satisfy, the MCData client:

1. shall generate a SDS SIGNALLING PAYLOAD as specified in subclause 6.1.1.2.2;

2. shall generate a SDS DATA PAYLOAD as specified in subclause 6.1.1.2.3;

3. shall include the SDS SIGNALLING PAYLOAD and SDS DATA PAYLOAD in an MSRP SEND request as specified in subclause 6.1.1.2.4, with the following clarification;

   a. shall set To-Path header according to the MSRP URI in the received SDP; and

4. shall send the MSRP SEND request on the established MSRP connection.

NOTE: MSRP chunking, if needed, may affect the number of "Content Type" lines in each MSRP SEND message conveying a chunk, as also specified in subclause 6.1.1.2.4.

[TS 24.582, clause 6.1.2.5.1]

To send an SDS disposition notification, the MCData client:

1. shall generate a SDS NOTIFICATION as specified in subclause 6.1.2.5.2;

2. shall include the SDS NOTIFICATION in an MSRP SEND request as specified in subclause 6.1.2.5.3, with the following clarification;

a. shall set To-Path header according to the MSRP URI in the received SDP; and

3. shall send the MSRP SEND request on the established MSRP connection.

If MSRP chunking is used, the MCData client:

1. shall send further MSRP SEND requests as necessary.

On receiving a non-200 MSRP response to the MSRP SEND request the MCData client shall handle the error as specified in IETF RFC 4975 [11]. To terminate the MSRP session, the MCData client:

1. if there are further MSRP chunks to send, shall abort transmission of these further MSRP chunks; and

2. shall indicate to MCData user that the SDS message or the SDS disposition notification could not be sent.

[TS 24.582, clause 6.1.2.5.2]

In order to generate an SDS notification, the MCData client:

1. shall generate an SDS NOTIFICATION message as specified in 3GPP TS 24.282 [8]; and

2. shall include the SDS NOTIFICATION message in an application/vnd.3gpp.mcdata-signalling MIME body as specified in 3GPP TS 24.282 [8].

When generating an SDS NOTIFICATION message, the MCData client:

1. if sending a delivered notification, shall set the SDS disposition notification type IE as "DELIVERED";

2. if sending a read notification, shall set the SDS disposition notification type IE as "READ";

3. if sending a delivered and read notification, shall set the SDS disposition notification type IE as "DELIVERED AND READ";

4. if the SDS message could not be delivered to the user or application (e.g. due to lack of storage), shall set the SDS disposition notification type IE as "UNDELIVERED";

5. shall set the Date and time IE to the current time;

6. shall set the Conversation ID to the value of the Conversation ID that was received in the SDS message;

7. shall set the Message ID to the value of the Message ID that was received in the SDS message;

8. if the SDS message was destined for the user, shall not include an Application ID IE; and

9. if the SDS message was destined for an application, shall include an Application ID IE set to the value of the Application ID that was included in the SDS message.

[TS 24.582, clause 6.1.2.6]

Upon receiving an SDS message, the MCData client:

1. shall follow the procedure defined in subclause 6.1.1.3.2, with the following clarification:

   a. if SDS Disposition request type IE is present in the received SDS SIGNALLING PAYLOAD message then, shall send an SDS disposition notification as described in subclause 6.1.2.5.

Upon receiving an SDS disposition notification, the MCData client:

1. shall decode the contents of the application/vnd.3gpp.mcdata-signalling MIME body; and

2. shall deliver the notification to the user or application.

6.1.11.3 Test description

6.1.11.3.1 Pre-test conditions

Test configuration:

- Single cell configuration according to TS 37.579-1 [2] clause 5.2.2.2.1.

Preamble:

- The UE has performed procedure 'Initial registration' as described in TS 37.579-1 [2] clause 5.4.2.
- UE States at the end of the preamble:
  - The UE is in RRC_IDLE state.
  - The client is registered for MCData.

6.1.11.3.2 Test procedure sequence

Table 6.1.11.3.2-1: Main Behaviour

St	Procedure	Message Sequence		TP	Verdict
		U - S	Message		
1	Make the UE (MCData client) send a group session SDS message with disposition request "**DELIVERY**". (NOTE 1)	-	-	-	-
2	Check: Does the UE (MCData client) correctly perform procedure '**CO MCData Call Establishment**' as described in TS 37.579-1 [2] Table 5.3C.2.3-1?	-	-	1,2	P
3-6	Void	-	-	-	-
7	Check: Does the UE (MCData client) correctly perform procedure '**CO MSRP message transfer**' as described in TS 37.579-1 [2] Table 5.3C.4.3-1 **to send an SDS message with disposition request "DELIVERY"**?	-	-	2	P
8	Check: Does the UE (MCData client) correctly perform procedure '**CT MSRP message transfer**' as described in TS 37.579-1 [2] Table 5.3C.5.3-1 **to receive the disposition notification** for the SDS message sent at step 7?	-	-	3	P
9	Void	-	-	-	-
10	Check: Does the UE (MCData client) provide the disposition notification to the user? (NOTE 1)	-	-	3	P
11	Check: Does the UE (MCData client) correctly perform procedure '**CT MSRP message transfer**' as described in TS 37.579-1 [2] Table 5.3C.5.3-1 **to receive an SDS message with disposition request "DELIVERY AND READ"**? (NOTE 3)	-	-	4	P
12	Void	-	-	-	-
-	EXCEPTION: In parallel to the event described in step 13 the events described in Table 6.1.11.3.2-2 take place. (NOTE 2)	-	-	-	-
13	Check: Does the UE (MCData client) provide the contents of the Payload IE to the user? (NOTE 1)	-	-	4	P
14	Make the UE (MCData client) release the group session. (NOTE 1)	-	-	-	-
15	Check: Does the UE (MCData client) correctly perform procedure 'CO MCData call release' as described in TS 37.579-1 [2] Table 5.3C.6.3-1? (NOTE 4)	-	-	3	P
16	The procedure 'MCX communication release' as described in TS 37.579-1 [2] clause 5.4.14 is performed to release the RRC connection.	-	-	-	-

NOTE 1: This is expected to be done via a suitable implementation dependent MMI.
NOTE 2: The behaviour is handled through parallel actions to allow for implementations which first indicate to the user that there is a message available, but render the message to the user only after the user takes an action to open the message.
NOTE 3: Timer TDU1 (delivery and read) is started upon receipt of the SIP MESSAGE message that contains a "DELIVERY AND READ" disposition request. Timer TDU1 (delivery and read)=120ms according to the default value defined in TS 24.282 [31].
NOTE 4: The procedure does not release the RRC connection.

Table 6.1.11.3.2-2: Parallel Behaviour

St	Procedure	Message Sequence		TP	Verdict
		U - S	Message		
-	EXCEPTION: Steps 1a1-1b2 describe behaviour that depends on the timing of UE execution; the "lower case letter" identifies a step sequence that takes place if the UE receives a display indication before (step 1a1) or after (steps 1b1-1b2) timer TDU1 (delivery and read) expires.	-	-	-	-
1a1	Check: Does the UE (MCData client) correctly perform procedure '**CO MSRP message transfer**' as described in TS 37.579-1 [2] Table 5.3C.4.3-1 **to send a disposition notification of "DELIVERED AND READ"**?	-	-	3	P
1b1	Check: Does the UE (MCData client) correctly perform procedure '**CO MSRP message transfer**' as described in TS 37.579-1 [2] Table 5.3C.4.3-1 **to send a disposition notification of "DELIVERED"**?	-	-	3	P
1b2	Check: Does the UE (MCData client) correctly perform procedure '**CO MSRP message transfer**' as described in TS 37.579-1 [2] Table 5.3C.4.3-1 **to send a disposition notification of "READ"**?	-	-	3	P

6.1.11.3.3 Specific message contents

Table 6.1.11.3.3-1: SIP INVITE from the UE (step 2, Table 6.1.11.3.2-1; step 2, TS 37.579-1 [2] Table 5.3C.2.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.5.1-1, condition MCDATA_SDS				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part		**SDP message**		
MIME-part-body	As described in Table 6.1.11.3.3-1A			
MIME body part		**MCData-Info**		
MIME-part-body	MCData-Info as described in Table 6.1.11.3.3-2			

Table 6.1.11.3.3-1A: SDP for SIP INVITE (Table 6.1.11.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.1.1-3, condition MCDATA_SDS, SDP_OFFER, SDS_SESSION

Table 6.1.11.3.3-2: MCData-Info (Table 6.1.11.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.2.1-3, condition MCD_grp				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
mcdata-info				
mcdata-Params				
request-type	"group-sds-session"			

Table 6.1.11.3.3-3: SIP 200 (OK) from the SS (step 2, Table 6.1.11.3.2-1; step 4, TS 37.579-1 [2] Table 5.3C.2.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.17.1.2-1, condition INVITE-RSP				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
SDP message	As described in Table 6.1.11.3.3-4			

Table 6.1.11.3.3-4: SDP for SIP 200 (OK) (Table 6.1.11.3.3-3)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.1.2-3, condition MCDATA_SDS, SDP_ANSWER, SDS_SESSION

Table 6.1.11.3.3-5: MSRP SEND from the UE (step 7, Table 6.1.11.3.2-1; step 1, TS 37.579-1 [2] Table 5.3C.4.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.12.1.1-1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Content-Type				
media-type	"multipart/mixed"			
data	Message or chunk of message as specified in table 6.1.11.3.3-5A			

Table 6.1.11.3.3-5A: MIME Message (step 7, Table 6.1.11.3.2-1; step 3, TS 37.579-1 [2] Table 5.3C.4.3-1)

Derivation Path: RFC 2046 [38]				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
MIME body part		**MCData Data signalling message**		
MIME-part-headers				
Content-Type	"application/vnd.3gpp. mcdata-signalling"			
MIME-part-body	MCData Protected Payload Message containing SDS SIGNALLING PAYLOAD as described in table 6.1.11.3.3-5B			
MIME body part		**MCData Data message**		
MIME-part-headers				
Content-Type	"application/vnd.3gpp. mcdata-payload"			
MIME-part-body	MCData Protected Payload Message containing DATA PAYLOAD as described in Table 6.1.11.3.3-6			

Table 6.1.11.3.3-5B: SDS SIGNALLING PAYLOAD (Table 6.1.11.3.3-5A)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.1-1, condition DELIVERED

Table 6.1.11.3.3-6: Data Payload (Table 6.1.11.3.3-5A)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.9.1-1

Table 6.1.11.3.3-7..8: Void

Table 6.1.11.3.3-9: MSRP SEND from the SS (step 8, Table 6.1.11.3.2-1; step 1, TS 37.579-1 [2] Table 5.3C.5.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.12.1.2-1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Content-Type				
media-type	"application/vnd.3gpp.mcdata-signalling"			
data	MCData Protected Payload Message containing SDS NOTIFICATION as specified in table 6.1.11.3.3-10			

Table 6.1.11.3.3-10: SDS NOTIFICATION (Table 6.1.11.3.3-9)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.4-1, condition DELIVERED

Table 6.1.11.3.3-11: MSRP SEND from the SS (step 11, Table 6.1.11.3.2-1; step 1, TS 37.579-1 [2] Table 5.3C.5.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.12.1.2-1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Content-Type				
media-type	"multipart/mixed"			
data	Message as specified in table 6.1.11.3.3-11A			

Table 6.1.11.3.3-11A: MIME Message (step 11, Table 6.1.11.3.2-1; step 1, TS 37.579-1 [2] Table 5.3C.5.3-1)

Derivation Path: RFC 2046 [38]				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
MIME body part		**MCData Data signalling message**		
MIME-part-headers				
Content-Type	"application/vnd.3gpp.mcdata-signalling"			
MIME-part-body	MCData Protected Payload Message containing SDS SIGNALLING PAYLOAD as described in table 6.1.11.3.3-12			
MIME body part		**MCData Data message**		
MIME-part-headers				
Content-Type	"application/vnd.3gpp.mcdata-payload"			
MIME-part-body	MCData Protected Payload Message containing DATA PAYLOAD as described in Table 6.1.11.3.3-12A			

Table 6.1.11.3.3-12: SDS SIGNALLING PAYLOAD (Table 6.1.11.3.3-11A)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.2-1, condition DELIVERED_READ

Table 6.1.11.3.3-12A: Data Payload (Table 6.1.11.3.3-11A)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.9.1-2

Table 6.1.11.3.3-13: MSRP SEND from the UE (step 1a1, Table 6.1.11.3.2-2; step 3, TS 37.579-1 [2] Table 5.3C.4.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.12.1.1-1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Content-Type				
media-type	"application/vnd.3gpp.mcdata-signalling"			
data	MCData Protected Payload Message containing SDS NOTIFICATION as specified in table 6.1.11.3.3-14			

Table 6.1.11.3.3-14: SDS NOTIFICATION (Table 6.1.11.3.3-13)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.3-1, condition DELIVERED_READ

Table 6.1.11.3.3-15: MSRP SEND from the UE (step 1b1, Table 6.1.11.3.2-2; step 3, TS 37.579-1 [2] Table 5.3C.4.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.12.1.1-1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Content-Type				
media-type	"application/vnd.3gpp. mcdata-signalling"			
data	MCData Protected Payload Message containing SDS NOTIFICATION as specified in table 6.1.11.3.3-16			

Table 6.1.11.3.3-16: SDS NOTIFICATION (Table 6.1.11.3.3-15)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.3-1, condition DELIVERED

Table 6.1.11.3.3-17: MSRP SEND from the UE (step 1b2, Table 6.1.11.3.2-2; step 3, TS 37.579-1 [2] Table 5.3C.4.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.12.1.1-1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Content-Type				
media-type	"application/vnd.3gpp. mcdata-signalling"			
data	MCData Protected Payload Message containing SDS NOTIFICATION as specified in table 6.1.11.3.3-18			

Table 6.1.11.3.3-18: SDS NOTIFICATION (Table 6.1.11.3.3-17)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.3-1, condition READ

Table 6.1.11.3.3-19..20: Void

6.1.12 On-network / Short Data Service (SDS) / SDS Session / Group SDS Session / Client Terminated (CT)

6.1.12.1 Test Purpose (TP)

(1)

```
with { UE (MCDATA Client) registered and authorised for MCDATA Service }
ensure that {
  when { the MCDATA User receives a SIP INVITE to initiate a group SDS session using the media plane
}
    then { UE (MCDATA Client) responds by sending a SIP 200 (OK) message }
            }
```

(2)

```
with { UE (MCDATA Client) having responded to the SIP INVITE message that initiated a group SDS
session using the media plane }
ensure that {
```

```
  when { UE (MCDATA Client) receives an MSRP SEND message }
    then { UE (MCDATA Client) responds with a MSRP 200 (OK) message and if the MSRP SEND message is
not blank, renders the contents of the Payload IE to the MCDATA User and sends a MSRP SEND message
with a disposition notification of "DELIVERED" }
            }
```

(3)

```
with { UE (MCDATA Client) being in a group SDS session initiated by the SS (MCDATA server) }
ensure that {
  when { the MCDATA User requests to send a group SDS Session message with a disposition of
"DELIVERY AND READ" }
    then { UE (MCDATA Client) sends a group session SDS message via a MSRP SEND message with a
disposition of "DELIVERY AND READ" }
            }
```

(4)

```
with { UE (MCDATA Client) having sent a group SDS session message using the media plane with a
disposition of "DELIVERY AND READ" }
ensure that {
  when { UE (MCDATA Client) receives a disposition response via a MSRP SEND message }
    then { UE (MCDATA Client) responds to the MSRP SEND message by sending a MSRP 200 (OK) message
and delivers the notification to the MCDATA User }
            }
```

(5)

```
with { UE (MCDATA Client) being in a group SDS session initiated by the SS (MCDATA Server) }
ensure that {
  when { UE (MCDATA Client) receives a SIP BYE message }
    then { UE (MCDATA Client) responds by sending a SIP 200 (OK) message }
            }
```

6.1.12.2 Conformance requirements

References: The conformance requirements covered in the current TC are specified in: TS 24.282, clauses 9.2.4.2.4, 9.2.4.2.2, 13.2.2.2.2.2, TS 24.582 clauses 6.1.2.3.1, 6.1.2.3.1, 6.1.2.4, 6.1.2.5.1, 6.1.2.5.2, 6.1.2.5.3, 6.1.2.6. The following represents a copy/paste extraction of the requirements relevant to the test purpose; any references within the copy/paste text should be understood within the scope of the core spec they have been copied from. Unless otherwise stated, these are Rel-14 requirements.

[TS 24.282, clause 9.2.4.2.4]

Upon receipt of an initial SIP INVITE request, the MCData client shall follow the procedures for termination of multimedia sessions in the IM CN subsystem as specified in 3GPP TS 24.229 [5] with the clarifications below.

The MCData client:

1) may reject the SIP INVITE request if either of the following conditions are met:

   a) MCData client does not have enough resources to handle the call; or

   b) any other reason outside the scope of this specification;

   and skip the rest of the steps after step 2;

2) if the SIP INVITE request is rejected in step 1), shall respond toward participating MCData function either with appropriate reject code as specified in 3GPP TS 24.229 [5] and warning texts as specified in subclause 4.9 or with SIP 480 (Temporarily unavailable) response not including warning texts if the user is authorised to restrict the reason for failure and skip the rest of the steps of this subclause;

3) if the SDP offer of the SIP INVITE request contains an "a=key-mgmt" attribute field with a "mikey" attribute value containing a MIKEY-SAKKE I_MESSAGE:

   a) shall extract the MCData ID of the originating MCData user from the initiator field (IDRi) of the I_MESSAGE as described in 3GPP TS 33.180 [26];

   b) shall convert the MCData ID to a UID as described in 3GPP TS 33.180 [26];

c) shall use the UID to validate the signature of the MIKEY-SAKKE I_MESSAGE as described in 3GPP TS 33.180 [26];

d) if authentication verification of the MIKEY-SAKKE I_MESSAGE fails, shall reject the SIP INVITE request with a SIP 488 (Not Acceptable Here) response as specified in IETF RFC 4567 [45], and include warning text set to "136 authentication of the MIKEY-SAKKE I_MESSAGE failed" in a Warning header field as specified in subclause 4.9 and not continue with rest of the steps in this subclause; and

e) if the signature of the MIKEY-SAKKE I_MESSAGE was successfully validated:

i) shall extract and decrypt the encapsulated PCK using the terminating user's (KMS provisioned) UID key as described in 3GPP TS 33.180 [26]; and

ii) shall extract the PCK-ID, from the payload as specified in 3GPP TS 33.180 [26];

NOTE: With the PCK successfully shared between the originating MCData client and the terminating MCData client, both clients are able to create an end-to-end secure session.

4) may display to the MCData user the MCData ID of the inviting MCData user and the type of SDS request;

5) shall accept the SIP INVITE request and generate a SIP 200 (OK) response according to rules and procedures of 3GPP TS 24.229 [5];

6) shall include the option tag "timer" in a Require header field of the SIP 200 (OK) response;

7) shall include the Session-Expires header field in the SIP 200 (OK) response and start the SIP session timer according to IETF RFC 4028 [38]. The "refresher" parameter in the Session-Expires header field shall be set to "uas";

8) shall include the g.3gpp.mcdata.sds media feature tag in the Contact header field of the SIP 200 (OK) response;

9) shall include the g.3gpp.icsi-ref media feature tag containing the value of "urn:urn-7:3gpp-service.ims.icsi.mcdata.sds" in the Contact header field of the SIP 200 (OK) response;

10) shall include an SDP answer in the SIP 200 (OK) response to the SDP offer in the incoming SIP INVITE request according to 3GPP TS 24.229 [5] with the clarifications given in subclause 9.2.4.2.2; and

11) shall send the SIP 200 (OK) response towards the MCData server according to rules and procedures of 3GPP TS 24.229 [5].

On receipt of an SIP ACK message to the sent SIP 200 (OK) message, the MCData client shall:

1) shall interact with the media plane as specified in 3GPP TS 24.582 [15] subclause 6.1.2.3.

To send a disposition notification after the media plane is released, the MCData client:

1) shall follow the procedures described in subclause 12.2.1.1.

[TS 24.282, clause 9.2.4.2.2]

When the MCData client receives an initial SDP offer for an MCData SDS session, the MCData client shall process the SDP offer and shall compose an SDP answer according to 3GPP TS 24.229 [5] and IETF RFC 4975 [17].

When composing an SDP answer, the MCData client:

1) shall include an "m=message" media-level section for the accepted MCData media stream consisting of:

a) the port number;

b) a protocol field value of "TCP/MSRP" or "TCP/TLS/MSRP" for TLS according to the received SDP offer;

c) an "a=sendrecv" attribute;

d) an "a=path" attribute containing its own MSRP URI;

e) set the content type as a=accept-types: application/vnd.3gpp.mcdata-signalling application/vnd.3gpp.mcdata-payload; and

f) set the a=setup attribute according to IETF RFC 6135 [19].

[TS 24.282, clause 13.2.2.2.2.2]

Upon receiving a SIP BYE request, the MCData client:

1) shall send SIP 200 (OK) response towards MCData server according to 3GPP TS 24.229 [5]; and

2) shall release all media plane resources corresponding to the MCData communication being released.

NOTE: Partially received data can be stored and processed.

[TS 24.582, clause 6.1.2.3.1]

Upon receiving an indication to establish MSRP connection for SDS session as the terminating MCData client, the MCData client:

1. shall act as an MSRP client according to IETF RFC 6135 [12];

2. shall act either as an active endpoint or as an passive endpoint to open the transport connection, according to IETF RFC 6135 [12];

3. shall establish the MSRP connection according to the MSRP connection parameters in the SDP offer received in the SIP INVITE request according to IETF RFC 4975 [11];

4. if acting as an "active" endpoint, shall send an empty MSRP SEND request to bind the MSRP connection to the MSRP session from the perspective of the passive endpoint according to the rules and procedures of IETF RFC 4975 [11] and IETF RFC 6135 [12];

Once the MSRP session is established, the MCData client:

1. on receipt of an MSRP request in the MSRP session, shall follow the rules and procedures defined in IETF RFC 4975 [11] and in IETF RFC 6714 [13];

2. If an MSRP SEND request indicates the use of chunking, shall wait until all further MSRP SEND requests for the remaining chunks have been received and shall reassemble the entire set of MSRP requests into the MCData SDS message before delivering the content to the application; and

3. shall handle the received content as described in subclause 6.1.2.6.

On receiving MSRP 200 (OK) response to the first MSRP SEND request sent as "active" endpoint, or after sending MSRP 200 (OK) response to the first MSRP SEND request received as "passive" endpoint, the MCData client can generate and send an SDS message as specified in subclause 6.1.2.4, or can generate and send an SDS disposition notification for a received SDS message as specified in subclause 6.1.2.5, if requested.

Received content and disposition requests shall be handled as specified in subclause 6.1.2.6.

[TS 24.582, clause 6.1.2.4]

An MCData client is allowed to send an one-to-one SDS message only if

1. the <allow-transmit-data> element of an <actions> element is present with a value "true" (see the MCData user profile document in 3GPP TS 24.484 [7]);

2. the size of the SDS message is less than or equal to the value of the <max-data-size-sds-bytes> element in the MCData service configuration document as specified in 3GPP TS 24.484 [7]; and

3. the size of the SDS message is less than or equal to the value of <MaxData1To1> element of the MCData user profile document (see the MCData user profile document in 3GPP TS 24.484 [7]).

An MCData client is allowed to send a group SDS message only if

1. the <mcdata-allow-transmit-data-in-this-group> element of an <action> element is present with a value "true" as defined in the MCData group document for this MCData group as specified in 3GPP TS 24.481 [4];

2. the size of the SDS message is less than or equal to the value contained in the <mcdata-on-network-max-data-size-for-SDS> as defined in the MCData group document for this MCData group as specified in 3GPP TS 24.481 [4]; and

3. the size of the SDS message is less than or equal to the value contained in the <mcdata-max-data-in-single-request> element of the <entry> element of the MCData group document for this MCData group as specified in 3GPP TS 24.481 [11].

If the above mentioned conditions satisfy, the MCData client:

1. shall generate a SDS SIGNALLING PAYLOAD as specified in subclause 6.1.1.2.2;

2. shall generate a SDS DATA PAYLOAD as specified in subclause 6.1.1.2.3;

3. shall include the SDS SIGNALLING PAYLOAD and SDS DATA PAYLOAD in an MSRP SEND request as specified in subclause 6.1.1.2.4, with the following clarification;

   a. shall set To-Path header according to the MSRP URI in the received SDP; and

4. shall send the MSRP SEND request on the established MSRP connection.

NOTE: MSRP chunking, if needed, may affect the number of "Content Type" lines in each MSRP SEND message conveying a chunk, as also specified in subclause 6.1.1.2.4.

[TS 24.582, clause 6.1.2.5.1]

To send an SDS disposition notification, the MCData client:

1. shall generate a SDS NOTIFICATION as specified in subclause 6.1.2.5.2;

2. shall include the SDS NOTIFICATION in an MSRP SEND request as specified in subclause 6.1.2.5.3, with the following clarification;

   a. shall set To-Path header according to the MSRP URI in the received SDP; and

3. shall send the MSRP SEND request on the established MSRP connection.

If MSRP chunking is used, the MCData client:

1. shall send further MSRP SEND requests as necessary.

On receiving a non-200 MSRP response to the MSRP SEND request the MCData client shall handle the error as specified in IETF RFC 4975 [11]. To terminate the MSRP session, the MCData client:

1. if there are further MSRP chunks to send, shall abort transmission of these further MSRP chunks; and

2. shall indicate to MCData user that the SDS message or the SDS disposition notification could not be sent.

[TS 24.582, clause 6.1.2.5.2]

In order to generate an SDS notification, the MCData client:

1. shall generate an SDS NOTIFICATION message as specified in 3GPP TS 24.282 [8]; and

2. shall include the SDS NOTIFICATION message in an application/vnd.3gpp.mcdata-signalling MIME body as specified in 3GPP TS 24.282 [8].

When generating an SDS NOTIFICATION message, the MCData client:

1. if sending a delivered notification, shall set the SDS disposition notification type IE as "DELIVERED";

2. if sending a read notification, shall set the SDS disposition notification type IE as "READ";

3. if sending a delivered and read notification, shall set the SDS disposition notification type IE as "DELIVERED AND READ";

4. if the SDS message could not be delivered to the user or application (e.g. due to lack of storage), shall set the SDS disposition notification type IE as "UNDELIVERED";

5. shall set the Date and time IE to the current time;
6. shall set the Conversation ID to the value of the Conversation ID that was received in the SDS message;
7. shall set the Message ID to the value of the Message ID that was received in the SDS message;
8. if the SDS message was destined for the user, shall not include an Application ID IE; and
9. if the SDS message was destined for an application, shall include an Application ID IE set to the value of the Application ID that was included in the SDS message.

[TS 24.582, clause 6.1.2.5.3]

The MCData client shall generate MSRP SEND requests for SDS disposition notification according to IETF RFC 4975 [11].

When generating an MSRP SEND request for SDS disposition notification containing an SDS NOTIFICATION message, the MCData client

1. shall set To-Path header according to the MSRP URI(s) received in the answer SDP;
2. shall set the content type as Content-Type = "application/vnd.3gpp.mcdata-signalling"; and
3. shall set the body of the MSRP SEND request to the generated SDS NOTIFICATION message.

[TS 24.582, clause 6.1.2.6]

Upon receiving an SDS message, the MCData client:

1. shall follow the procedure defined in subclause 6.1.1.3.2, with the following clarification:
    a. if SDS Disposition request type IE is present in the received SDS SIGNALLING PAYLOAD message then, shall send an SDS disposition notification as described in subclause 6.1.2.5.

Upon receiving an SDS disposition notification, the MCData client:

1. shall decode the contents of the application/vnd.3gpp.mcdata-signalling MIME body; and
2. shall deliver the notification to the user or application.

6.1.12.3 Test description

6.1.12.3.1 Pre-test conditions

Test configuration:

- Single cell configuration according to TS 37.579-1 [2] clause 5.2.2.2.1.

Preamble:

- The UE has performed procedure 'Initial registration' as described in TS 37.579-1 [2] clause 5.4.2.
- UE States at the end of the preamble:
    - The UE is in RRC_IDLE state.
    - The client is registered for MCData.

6.1.12.3.2 Test procedure sequence

Table 6.1.12.3.2-1: Main Behaviour

St	Procedure	Message Sequence		TP	Verdict
		U - S	Message		
1	Check: Does the UE (MCData client) correctly perform procedure '**CT MCData Call Establishment**' as described in TS 37.579-1 [2] Table 5.3C.3.3-1?	-	-	1,2	P
2-5	Void	-	-	-	-
6	Check: Does the UE (MCData client) correctly perform procedure '**CT MSRP message transfer**' as described in TS 37.579-1 [2] Table 5.3C.5.3-1 **to receive an SDS message with disposition request "DELIVERY"**?	-	-	2	P
7	Void	-	-	-	-
8	Check: Does the UE (MCData client) correctly perform procedure '**CO MSRP message transfer**' as described in TS 37.579-1 [2] Table 5.3C.4.3-1 **to send a disposition notification of "DELIVERED"**?	-	-	2	P
9	Void	-	-	-	-
10	Check: Does the UE (MCData client) provide the contents of the Payload IE to the user? (NOTE 1)	-	-	2	P
11	Make the UE (MCData client) send a group session SDS message over the media plane with disposition request "DELIVERY AND READ". (NOTE 1)	-	-	-	-
12	Check: Does the UE (MCData client) correctly perform procedure '**CO MSRP message transfer**' as described in TS 37.579-1 [2] Table 5.3C.4.3-1 **to send an SDS message with disposition request "DELIVERY AND READ"**?	-	-	3	P
13	Check: Does the UE (MCData client) correctly perform procedure '**CT MSRP message transfer**' as described in TS 37.579-1 [2] Table 5.3C.5.3-1 **to receive the disposition notification** for the SDS message sent at step 12?	-	-	4	P
14	Void	-	-	-	-
15	Check: Does the UE (MCData client) provide the disposition notification to the user? (NOTE 1)	-	-	4	P
16	Check: Does the UE (MCData client) correctly perform procedure '**CT MCData call release**' as described in TS 37.579-1 [2] Table 5.3C.7.3-1? (NOTE 2)	-	-	5	P
17	The procedure 'MCX communication release' as described in TS 37.579-1 [2] clause 5.4.14 is performed to release the RRC connection.	-	-	-	-
NOTE 1: This is expected to be done via a suitable implementation dependent MMI. NOTE 2: The procedure does not release the RRC connection.					

6.1.12.3.3 Specific message contents

Table 6.1.12.3.3-1: SIP INVITE from the SS (step 1, Table 6.1.12.3.2-1; step 2, TS 37.579-1 [2] Table 5.3C.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.5.2-1, condition MCDATA_SDS				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part		**SDP message**		
MIME-part-body	SDP message as described in Table 6.1.12.3.3-1A			
MIME body part		**MCData-Info**		
MIME-part-body	MCData-Info as described in Table 6.1.12.3.3-2			

Table 6.1.12.3.3-1A: SDP for SIP INVITE (Table 6.1.12.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.1.2-3, condition MCDATA_SDS, SDP_OFFER, SDS_SESSION

Table 6.1.12.3.3-2: MCData-Info (Table 6.1.12.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.2.1-3, condition MCD_grp				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
mcdata-info				
mcdata-Params				
request-type	"group-sds-session"			

Table 6.1.12.3.3-3: SIP 200 (OK) from the UE (step 1, Table 6.1.12.3.2-1; step 4, TS 37.579-1 [2] Table 5.3C.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.17.1.1-1, condition INVITE-RSP, MCDATA_SDS				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Content-Type				
value	"application/sdp"			
Message-body				
SDP message	As described in Table 6.1.12.3.3-4			

Table 6.1.12.3.3-4: SDP for SIP 200 (OK) (Table 6.1.12.3.3-3)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.1.1-3, condition MCDATA_SDS, SDP_ANSWER, SDS_SESSION

Table 6.1.12.3.3-5: MSRP SEND from the SS (step 6, Table 6.1.12.3.2-1; step 1, TS 37.579-1 [2] Table 5.3C.5.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.12.1.2-1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Content-Type				
media-type	"multipart/mixed"			
data	Message as specified in table 6.1.12.3.3-5A			

Table 6.1.12.3.3-5A: MIME Message (step 6, Table 6.1.12.3.2-1; step 1, TS 37.579-1 [2] Table 5.3C.5.3-1)

Derivation Path: RFC 2046 [38]				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
MIME body part		**MCData Data signalling message**		
MIME-part-headers				
Content-Type	"application/vnd.3gpp. mcdata-signalling"			
MIME-part-body	MCData Protected Payload Message containing SDS SIGNALLING PAYLOAD as described in table 6.1.12.3.3-5B			
MIME body part		**MCData Data message**		
MIME-part-headers				
Content-Type	"application/vnd.3gpp. mcdata-payload"			
MIME-part-body	MCData Protected Payload Message containing DATA PAYLOAD as described in Table 6.1.12.3.3-6			

Table 6.1.12.3.3-5B: SDS SIGNALLING PAYLOAD (Table 6.1.12.3.3-5A)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.2-1, condition DELIVERED

Table 6.1.12.3.3-6: Data Payload (Table 6.1.12.3.3-5A)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.9.1-2

Table 6.1.12.3.3-7: MSRP SEND from the UE (step 8, Table 6.1.12.3.2-1; step 3, TS 37.579-1 [2] Table 5.3C.4.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.12.1.1-1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Content-Type				
media-type	"application/vnd.3gpp. mcdata-signalling"			
data	MCData Protected Payload Message containing SDS NOTIFICATION as specified in table 6.1.12.3.3-8			

Table 6.1.12.3.3-8: SDS NOTIFICATION (Table 6.1.12.3.3-7)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.3-1, condition DELIVERED

Table 6.1.12.3.3-9: MSRP SEND from the UE (step 12, Table 6.1.12.3.2-1; step 1, TS 37.579-1 [2] Table 5.3C.4.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.12.1.1-1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Content-Type				
media-type	"multipart/mixed"			
data	Message or chunk of message as specified in table 6.1.12.3.3-9A			

Table 6.1.12.3.3-9A: MIME Message (step 12, Table 6.1.12.3.2-1; step 3, TS 37.579-1 [2] Table 5.3C.4.3-1)

Derivation Path: RFC 2046 [38]				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
MIME body part		**MCData Data signalling message**		
MIME-part-headers				
Content-Type	"application/vnd.3gpp. mcdata-signalling"			
MIME-part-body	MCData Protected Payload Message containing SDS SIGNALLING PAYLOAD as described in table 6.1.12.3.3-10			
MIME body part		**MCData Data message**		
MIME-part-headers				
Content-Type	"application/vnd.3gpp. mcdata-payload"			
MIME-part-body	MCData Protected Payload Message containing DATA PAYLOAD as described in Table 6.1.12.3.3-11			

Table 6.1.12.3.3-10: SDS SIGNALLING PAYLOAD (Table 6.1.12.3.3-9A)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.1-1, condition DELIVERED_READ

Table 6.1.12.3.3-11: Data Payload (Table 6.1.12.3.3-9A)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.9.1-1

Table 6.1.12.3.3-12..13: Void

Table 6.1.12.3.3-14: MSRP SEND from the SS (step 13, Table 6.1.12.3.2-1; step 1, TS 37.579-1 [2] Table 5.3C.5.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.12.1.2-1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Content-Type				
media-type	"application/vnd.3gpp. mcdata-signalling"			
data	MCData Protected Payload Message containing SDS NOTIFICATION as specified in table 6.1.12.3.3-15			

Table 6.1.12.3.3-15: SDS NOTIFICATION (Table 6.1.12.3.3-14)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.4-1, condition DELIVERED_READ

Table 6.1.12.3.3-16..17: Void

6.1.13 On-network / Short Data Service (SDS) / Standalone SDS Using Media Plane / One-to-one Standalone SDS / Pre-established session / Client Originated (CO)

6.1.13.1 Test Purpose (TP)

(1)

```
with { UE (MCDATA Client) registered and authorised for MCDATA Service }
ensure that {
  when { the MCDATA User requests to send a one-to-one standalone SDS message using the media plane
and using the pre-established session }
    then { UE (MCDATA Client) sends a request to establish an MSRP connection via a SIP REFER
message and responds to the SIP re-INVITE message with a SIP 200 (OK) message and delivers the
notification to the MCDATA User about successful communication establishment and sends a blank MSRP
SEND message to bind the MSRP connection }
            }
```

(2)

```
with { UE (MCDATA Client) having sent a blank MSRP SEND message to bind the MSRP connection }
ensure that {
  when { UE (MCDATA Client) receives an MSRP 200 (OK) message in response to the blank MSRP SEND
message }
    then { UE (MCDATA Client) sends the one-to-one standalone SDS message via a MSRP SEND message
with a disposition of "DELIVERY" }
            }
```

(3)

```
with { UE (MCDATA Client) having sent a one-to-one standalone SDS message using the media plane }
ensure that {
  when { UE (MCDATA Client receives a MSRP 200 (OK) message in response to the last MSRP SEND
message indicating that the standalone SDS message has been successfully transferred }
    then { UE (MCDATA Client) sends a SIP REFER message to release the MCData session and keep the
pre-established session and responds to the SIP re-INVITE message with a SIP 200 (OK) message and
delivers the notification to the MCDATA User about successful termination }
            }
```

(4)

```
with { UE (MCDATA Client) having sent a one-to-one standalone SDS message using the media plane with
a disposition of "DELIVERY" }
ensure that {
  when { UE (MCDATA Client receives a disposition response via a SIP MESSAGE message from the SS
(MCDATA Server }
    then { UE (MCDATA Client) responds to the SIP MESSAGE message by sending a SIP 200 (OK) message
and delivers the notification to the MCDATA User }
           }
```

6.1.13.2 Conformance requirements

References: The conformance requirements covered in the current TC are specified in: TS 24.282, clauses 9.2.5.2.1.1, 9.2.3.2.1, 9.2.5.4.1.1, 12.2.1.2, TS 24.582 clauses 12.1, 6.1.1.2.1, 6.1.1.2.2, 6.1.1.2.3, 6.1.1.2.4. The following represents a copy/paste extraction of the requirements relevant to the test purpose; any references within the copy/paste text should be understood within the scope of the core spec they have been copied from. Unless otherwise stated, these are Rel-16 requirements.

[TS 24.282, clause 9.2.5.2.1.1]

Upon receiving a request from an MCData user to initiate one-to-one standalone SDS using media plane or one-to-one SDS session within the pre-established session, the MCData client shall generate a SIP REFER request outside a dialog as specified in IETF RFC 3515 [51] as updated by IETF RFC 6665 [36] and IETF RFC 7647 [52], and in accordance with the UE procedures specified in 3GPP TS 24.229 [5], with the clarifications given below.

The MCData client:

1) shall set the Request URI of the SIP REFER request to the session identity of the pre-established session;

2) shall set the Refer-To header field of the SIP REFER request as specified in IETF RFC 3515 [51] with a Content-ID ("cid") Uniform Resource Locator (URL) as specified in IETF RFC 2392 [33] that points to an application/resource-lists MIME body as specified in IETF RFC 5366 [18], and with the Content-ID header field set to this "cid" URL;

3) if an end-to-end security context needs to be established and the security context does not exist or if the existing security context has expired, then:

   i) if necessary, shall instruct the key management client to request keying material from the key management server as described in 3GPP TS 33.180 [26];

   ii) shall use the keying material to generate a PCK as described in 3GPP TS 33.180 [26];

   iii) shall use the PCK to generate a PCK-ID with the four most significant bits set to "0001" to indicate that the purpose of the PCK is to protect one-to-one communications and with the remaining twenty-eight bits being randomly generated as described in 3GPP TS 33.180 [26];

   iv) shall encrypt the PCK to a UID associated to the MCData client using the MCData ID of the invited user and a time related parameter as described in 3GPP TS 33.180 [26];

   v) shall generate a MIKEY-SAKKE I_MESSAGE using the encapsulated PCK and PCK-ID as specified in 3GPP TS 33.180 [26];

   vi) shall add the MCData ID of the originating MCData to the initiator field (IDRi) of the I_MESSAGE as described in 3GPP TS 33.180 [26]; and

   vii) shall sign the MIKEY-SAKKE I_MESSAGE using the originating MCData user's signing key provided in the keying material together with a time related parameter, and add this to the MIKEY-SAKKE payload, as described in 3GPP TS 33.180 [26];

4) shall include in the application/resource-lists MIME body a single <entry> element containing a "uri" attribute set to MCData ID of the called user, extended with the following parameters in the headers portion of the SIP URI:

NOTE: Characters that are not formatted as ASCII characters are escaped in the following parameters in the headers portion of the SIP URI.

a) an hname "body" parameter populated with:

i) an application/sdp MIME body containing an SDP offer with media attributes specified in subclause 9.2.3.2.1, if a one-to-one standalone SDS message is requested;

ii) an application/vnd.3gpp.mcdata-info MIME body with:

A) if a one-to-one standalone SDS message is requested, the <request-type> element set to a value of "one-to-one-sds". If a one-to-one SDS session is requested, the <request-type> element set to a value of "one-to-one-sds-session";

B) the <mcdata-client-id> element set to the MCData client ID of the originating MCData client; and

C) if the MCData client is aware of active functional aliases and if an active functional alias is to be included in the SIP REFER request, the <functional-alias-URI> element set to the URI of the used functional alias;

5) shall include a P-Preferred-Service header field set to the ICSI value "urn:urn-7:3gpp-service.ims.icsi.mcdata.sds" (coded as specified in 3GPP TS 24.229 [5]), according to IETF RFC 6050 [7];

6) may include a P-Preferred-Identity header field in the SIP INVITE request containing a public user identity as specified in 3GPP TS 24.229 [5];

7) shall include the following according to IETF RFC 4488 [53]:

a) the option tag "norefersub" in the Supported header field; and

b) the value "false" in the Refer-Sub header field;

8) shall include a Target-Dialog header field as specified in IETF RFC 4538 [54] identifying the pre-established session;

9) shall include the g.3gpp.mcdata.sds media feature tag in the Contact header field of the SIP REFER request according to IETF RFC 3840 [16]; and

10) shall send the SIP REFER request according to 3GPP TS 24.229 [5].

On receiving a final SIP 2xx response to the SIP REFER request, the MCData client:

1) shall interact with the media plane as specified in 3GPP TS 24.582 [15].

On receiving a SIP re-INVITE request within the pre-established session targeted by the sent SIP REFER request, the MCData client:

1) if the <mcdata-communication-state> element in the application/vnd.3gpp.mcdata-info+xml MIME body of the SIP INVITE request is set to a value of "establish-success":

i) shall notify MCData user about successful the MCData communication establishment;

2) if the <mcdata-communication-state> element in the application/vnd.3gpp.mcdata-info+xml MIME body of the SIP INVITE request is set to a value of "establish-fail":

i) shall notify MCData user about the MCData communication establishment failure; and

3) shall interact with the media plane as specified in 3GPP TS 24.582 [15].

[TS 24.282, clause 9.2.3.2.1]

When composing an SDP offer according to 3GPP TS 24.229 [5], IETF RFC 4975 [17], IETF RFC 6135 [19] and IETF RFC 6714 [20] the MCData client:

1) shall include an "m=message" media-level section for the MCData media stream consisting of:

a) the port number;

b) a protocol field value of "TCP/MSRP", or "TCP/TLS/MSRP" for TLS;

c) a format list field set to '*';

d) an "a=sendonly" attribute;

e) an "a=path" attribute containing its own MSRP URI;

f) set the content type as "a=accept-types:application/vnd.3gpp.mcdata-signalling application/vnd.3gpp.mcdata-payload"; and

g) set the a=setup attribute as "actpass"; and

2) if end-to-end security is required for a one-to-one communication and the security context does not exist or if the existing security context has expired, shall include the MIKEY-SAKKE I_MESSAGE in an "a=key-mgmt" attribute as a "mikey" attribute value in the SDP offer as specified in IETF RFC 4567 [45].

[TS 24.282, clause 9.2.5.4.1.1]

Upon receiving a request from an MCData user to leave an MCData session within a pre-established session, the MCData client:

1) shall interact with the media plane as specified in 3GPP TS 24.582 [15];

2) shall generate an initial SIP REFER request outside a dialog in accordance with the procedures specified in 3GPP TS 24.229 [5], IETF RFC 4488 [53] and IETF RFC 3515 [51] as updated by IETF RFC 6665 [36] and IETF RFC 7647 [r7647];

3) shall set the Request-URI of the SIP REFER request to the public service identity identifying the pre-established session on the MCData server serving the MCData user;

4) shall include the Refer-Sub header field with value "false" according to rules and procedures of IETF RFC 4488 [53];

5) shall include the Supported header field with value "norefersub" according to rules and procedures of IETF RFC 4488 [53];

6) shall set the Refer-To header field of the SIP REFER request to the MCData session identity to leave;

7) shall include the "method" SIP URI parameter with the value "BYE" in the URI in the Refer-To header field;

8) shall include a Target-Dialog header field as specified in IETF RFC 4538 [54] identifying the pre-established session; and

9) shall send the SIP REFER request according to 3GPP TS 24.229 [5].

Upon receiving a SIP 2xx response to the SIP REFER request, the MCData client shall interact with media plane as specified in 3GPP TS 24.582 [15].

On receiving a SIP re-INVITE request within the pre-established session targeted by the sent SIP REFER request, the MCData client:

1) if the <mcdata-communication-state> element in the application/vnd.3gpp.mcdata-info+xml MIME body of the SIP INVITE request is set to a value of "terminated":

i) shall notify MCData user about successful the MCData communication termination.

[TS 24.282, clause 12.2.1.2]

Upon receipt of a:

"SIP MESSAGE request for SDS disposition notification for terminating MCData client"; or

"SIP MESSAGE request for FD disposition notification for terminating MCData client";

the MCData client:

1) shall decode the contents of the application/vnd.3gpp.mcdata-signalling MIME body; and

2) shall deliver the notification to the user or application.

[TS 24.582, clause 12.1]

Upon establishing one-to-one or group SDS using media plane or one-to-one or group SDS session using pre-established call, the MCData client shall follow procedures as descried in subclause 6.1.

[TS 24.582, clause 6.1.1.2.1]

Upon receiving an indication to establish MSRP connection for standalone SDS using media plane as the originating client, the MCData client:

1. shall act as an MSRP client according to IETF RFC 6135 [12];
2. shall act according to IETF RFC 6135 [12], as:
   a. an "active" endpoint, if a=setup attribute in the received SDP answer is set to "passive"; and
   b. an "passive" endpoint, if a=setup attribute in the received SDP answer is set to "active";
3. shall establish the MSRP connection according to the MSRP connection parameters in the SDP answer received in the SIP 200 (OK) response according to IETF RFC 4975 [11]; and
4. if acting as an "active" endpoint, shall send an empty MSRP SEND request to bind the MSRP connection to the MSRP session from the perspective of the passive endpoint according to the rules and procedures of IETF RFC 4975 [11] and IETF RFC 6135 [12].

On receiving MSRP 200 (OK) response to the first MSRP SEND request, the MCData client:

1. shall generate a SDS SIGNALLING PAYLOAD as specified in subclause 6.1.1.2.2;
2. shall generate a SDS DATA PAYLOAD as specified in subclause 6.1.1.2.3;
3. shall include the SDS SIGNALLING PAYLOAD and SDS DATA PAYLOAD in an MSRP SEND request as specified in subclause 6.1.1.2.4; and
4. shall send the MSRP SEND request on the established MSRP connection.

If MSRP chunking is not used then on receipt of a 200 (OK) response, the MCData client shall terminate the SIP session as specified in 3GPP TS 24.282 [8].

If MSRP chunking is used, the MCData client:

1. shall send further MSRP SEND requests as necessary;
2. shall wait for a 200 (OK) response to each MSRP SEND request sent; and
3. on receipt of the last 200 (OK) response shall terminate the SIP session as specified in 3GPP TS 24.282 [8].

On receiving a non-200 MSRP response to the MSRP SEND request the MCData client shall handle the error as specified in IETF RFC 4975 [11]. To terminate the MSRP session, the MCData client:

1. if there are further MSRP chunks to send, shall abort transmission of these further MSRP chunks;
2. shall indicate to MCData user that the SDS message could not be sent; and
3. shall terminate the SIP session as specified in 3GPP TS 24.282 [8].

On receiving an indication to terminate the session from the signalling plane, the MCData client:

1. if there are further MSRP chunks to send, shall abort transmission of these further MSRP chunks and may indicate to MCData user that the SDS message could not be sent.

[TS 24.582, clause 6.1.1.2.2]

In order to generate an SDS signalling payload, the MCData client:

1. shall generate an SDS SIGNALLING PAYLOAD message as specified in 3GPP TS 24.282 [8]; and

2. shall include the SDS SIGNALLING PAYLOAD message in an application/vnd.3gpp.mcdata-signalling MIME body as specified in 3GPP TS 24.282 [8]; and

When generating a an SDS SIGNALLING PAYLOAD message, the MCData client:

1. shall generate a SDS SIGNALLING PAYLOAD message as defined in 3GPP TS 24.282 [8]. In the SDS SIGNALLING PAYLOAD message, the MCData client:

   a. may include and set the Disposition request type IE to:

      i. "DELIVERY", if only delivery disposition is requested;

      ii. "READ", if only read disposition is requested; or

      iii. "DELIVERY AND READ", if both delivery and read dispositions are requested;

   b. shall set Date and time IE to current UTC time;

   c. shall set Conversation ID IE to a universally unique message ID generated as per IETF RFC 4122 [10];

   d. shall set Message ID IE to a universally unique message ID generated as per IETF RFC 4122 [10];

   e. if indicated that the SDS message is in reply to another SDS message then, shall include the Reply ID IE set to the message identifier of the indicated SDS message;

   f. if indicated that the target recipient of the SDS message is an application then, shall set Application Identifier IE to the application identifier; and

   g) shall set the Sender MCData user ID to its own MCData user ID as specified in subclause 15.2.15 of 3GPP TS 24.282 [8].

[TS 24.582, clause 6.1.1.2.3]

In order to generate SDS data payload, the MCData client:

1. shall generate a DATA PAYLOAD message as specified in 3GPP TS 24.282 [8]; and

2. shall include the DATA PAYLOAD message in an application/vnd.3gpp.mcdata-payload MIME body as specified in 3GPP TS 24.282 [8].

When generating a DATA PAYLOAD message, the MCData client:

1. shall generate a SDS DATA PAYLOAD message as defined in 3GPP TS 24.282 [8]. In the SDS DATA PAYLOAD message, the MCData client:

   a. shall set Number of payloads IE to the total number of payloads being sent; and

   b. for each payload, shall include Payload IE. In the Payload IE:

      i. shall set Payload content type to "TEXT", or "BINARY", or "HYPERLINKS", or "LOCATION" according to the payload type; and

      ii. shall set Payload data IE to actual payload.

[TS 24.582, clause 6.1.1.2.4]

The MCData client shall take the procedures in subclause 6.4.1 into consideration when generating MSRP SEND messages.

The MCData client shall generate MSRP SEND for SDS message requests according to IETF RFC 4975 [11].

When generating an MSRP SEND for SDS message request containing an SDS SIGNALLING PAYLOAD message and an SDS DATA PAYLOAD message, the MCData client

1. shall set To-Path header according to the MSRP URI(s) received in the answer SDP;

2. shall include two MIME bodies in accordance with subclause 6.4.1 where:

a. in the first body the Content-Type header field is set to "application/vnd.3gpp.mcdata-signalling" and the generated SDS SIGNALLING PAYLOAD message is included; and

b. in the second body the Content-Type header field is set to "application/vnd.3gpp.mcdata-payload" and the generated SDS DATA PAYLOAD message is included.

When generating an MSRP SEND for SDS message request containing only an SDS DATA PAYLOAD message, the MCData client:

1. shall set To-Path header according to the MSRP URI(s) received in the answer SDP;
2. shall set the Content-Type as "application/vnd.3gpp.mcdata-payload"; and
3. shall set the body of the MSRP SEND request to the generated SDS DATA PAYLOAD message.

When generating an MSRP SEND for SDS message request containing only an SDS SIGNALLING PAYLOAD, the MCData client.

1. shall set To-Path header according to the MSRP URI(s) received in the answer SDP;
2. shall set the Content-Type as "application/vnd.3gpp.mcdata-signalling"; and
3. shall set the body of the MSRP SEND request to the generated SDS SIGNALLING PAYLOAD message.

6.1.13.3 Test description

6.1.13.3.1 Pre-test conditions

Test configuration:

- Single cell configuration according to TS 37.579-1 [2] clause 5.2.2.2.1.

Preamble:

- The UE has performed procedure 'Initial registration' as described in TS 37.579-1 [2] clause 5.4.2 with the following clarifications:
  - The <max-payload-size-sds-cplane-bytes> element of the MCData Service Configuration document shall be set to 0 to force the MCData client to send the data using the media plane.
- The UE has performed procedure 'MCX pre-established session establishment' as described in TS 37.579-1 [2] clause 5.3.3.
- UE States at the end of the preamble:
  - The UE is in RRC_IDLE state.
  - The client is registered for MCData.
  - A pre-established session is established.

6.1.13.3.2 Test procedure sequence

Table 6.1.13.3.2-1: Main Behaviour

St	Procedure	Message Sequence		TP	Verdict
		U - S	Message		
1	Make the UE (MCData client) send a one-to-one standalone SDS message using the pre-established session with disposition request "**DELIVERY**". (NOTE 1)	-	-	-	-
2	Check: Does the UE (MCData client) correctly perform procedure '**CO MCData call establishment using a pre-established session**' as described in TS 37.579-1 [2] Table 5.3C.12.3-1?	-	-	1	P
3	Check: Does the UE (MCData client) notify the user about successful MCData communication establishment? (NOTE 1)	-	-	1	P
4	Check: Does the UE (MCData client) correctly perform procedure 'CO MSRP message transfer' as described in TS 37.579-1 [2] Table 5.3C.4.3-1 to **send an SDS message with disposition request "DELIVERY"**?	-	-	2	P
5	Check: Does the UE (MCData client) correctly perform procedure '**MCData CO call release keeping the pre-established session**' as described in TS 37.579-1 [2] Table 5.3C.13.3-1? (NOTE 2)	-	-	3	P
6	Check: Does the UE (MCData client) provide a notification to the MCData user about successful MCData communication termination? (NOTE 1)	-	-	3	P
7	Check: Does the UE (MCData client) correctly perform procedure 'MCX SIP MESSAGE CT' as described in TS 37.579-1 [2] Table 5.3.33.3-1 to **receive the disposition notification** for the SDS message sent at step 7?	-	-	-	-
8	Check: Does the UE (MCData client) provide the disposition notification to the user? (NOTE 1)	-	-	4	P
NOTE 1: This is expected to be done via a suitable implementation dependent MMI. NOTE 2: The procedure does not release the RRC connection.					

6.1.13.3.3 Specific message contents

Table 6.1.13.3.3-1: SIP REFER from the UE (step 2, Table 6.1.13.3.2-1; step 2, TS 37.579-1 [2] Table 5.3C.12.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.12-1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part		**Resource list**		
MIME-part-body	Resource-lists as described in Table 6.1.13.3.3-2			

Table 6.1.13.3.3-2: Resource-lists in SIP REFER (Table 6.1.13.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.3.1-3, condition PRE-ESTABLISH, MCD_1to1 with the uri attribute of the entry extended with the SIP URI header fields as specified in Table 6.1.13.3.3-3

Table 6.1.13.3.3-3: SIP header fields extending the uri attribute of the resource-lists' single entry (Table 6.1.13.3.3-2)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.12-2				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
body				
MIME body part		**SDP Message**		
MIME-part-headers				
Content-Type	“application/sdp”			
MIME-part-body	SDP Message as described in Table 6.1.13.3.3-4			
MIME body part		**MCData-Info**		
MIME-part-body	MCdata-Info as described in Table 6.1.13.3.3-5			

Table 6.1.13.3.3-4: SDP in SIP header fields (Table 6.1.13.3.3-3)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.1.1-3, condition PRE_ESTABLISHED_SESSION, SDP_OFFER, MCD_1to1, MCDATA_SDS

Table 6.1.13.3.3-5: MCData-Info in SIP header fields (Table 6.1.13.3.3-3)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.2.1-3, condition MCD_1to1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
mcdata-info				
mcdata-Params				
mcdata-client-id	Encrypted (NOTE 1) <mcdata-client-id> with mcdataString set to the mcdata-client-id as provided by the UE at registration		TS 24.282 [31] clause 9.2.5.2.1.1	
NOTE 1: Encrypted element as described in TS 37.579-1 [2] Table 5.5.3.2.1-3A				

Table 6.1.13.3.3-6: MSRP SEND from the UE (step 4, Table 6.1.13.3.2-1; step 1, TS 37.579-1 [2] Table 5.3C.4.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.12.1.1-1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Content-Type				
media-type	"multipart/mixed"			
data	Message or chunk of message as specified in table 6.1.13.3.3-7			

Table 6.1.13.3.3-7: MIME Message (step 4, Table 6.1.13.3.2-1; step 3, TS 37.579-1 [2] Table 5.3C.4.3-1)

Derivation Path: RFC 2046 [38]				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
MIME body part		**MCData Data signalling message**		
MIME-part-headers				
Content-Type	"application/vnd.3gpp. mcdata-signalling"			
MIME-part-body	MCData Protected Payload Message containing SDS SIGNALLING PAYLOAD as described in table 6.1.13.3.3-8			
MIME body part		**MCData Data message**		
MIME-part-headers				
Content-Type	"application/vnd.3gpp. mcdata-payload"			
MIME-part-body	DATA PAYLOAD as described in Table 6.1.13.3.3-9			

Table 6.1.13.3.3-8: SDS SIGNALLING PAYLOAD (Table 6.1.13.3.3-7)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.1-1, condition DELIVERED

Table 6.1.13.3.3-9: Data Payload (Table 6.1.13.3.3-7)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.9.2-1

Table 6.1.13.3.3-10: SIP MESSAGE from the SS (step 7, Table 6.1.13.3.2-1; step 2, TS 37.579-1 [2] Table 5.3.33.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.7.2-1, condition MCDATA_SDS, MCDATA_SIGNALLING				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part		**MCData Data signalling message**		
MIME-part-body	MCData Protected Payload Message containing SDS NOTIFICATION as described in Table 6.1.13.3.3-11			

Table 6.1.13.3.3-11: SDS NOTIFICATION (Table 6.1.13.3.3-12)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.4-1, condition DELIVERED

6.1.14 On-network / Short Data Service (SDS) / Standalone SDS Using Media Plane / One-to-one Standalone SDS / Pre-established session / Client Terminated (CT)

6.1.14.1 Test Purpose (TP)

(1)

```
with { UE (MCDATA Client) registered and authorised for MCDATA Service }
ensure that {
  when { the MCDATA User receives a SIP re-INVITE message to initiate a standalone one-to-one SDS
message using the media plane and using a pre-established session }
    then { UE (MCDATA Client) responds by sending a SIP 200 (OK) message }
            }
```

(2)

```
with { UE (MCDATA Client) having responded to the SIP re-INVITE message that initiated a standalone
one-to-one SDS message using the media plane and using a pre-established session }
ensure that {
  when { UE (MCDATA Client) receives an MSRP SEND message }
    then { UE (MCDATA Client) responds with an MSRP 200 (OK) message and if the MSRP SEND message is
not blank, renders the contents of the Payload IE to the MCDATA User and sends a SIP MESSAGE message
with a disposition notification of "DELIVERED" }
            }
```

(3)

```
with { UE (MCDATA Client) having responded to the MSRP SEND message from the SS (MCDATA server) }
ensure that {
  when { UE (MCDATA Client) receives a SIP re-INVITE message to release communications }
    then { UE (MCDATA Client) responds with a SIP 200 (OK) message }
            }
```

6.1.14.2 Conformance requirements

References: The conformance requirements covered in the current TC are specified in: TS 24.282, clauses 9.2.5.2.1.2, 9.2.3.2.4, 9.2.5.4.1.2, 9.2.1.3, 12.2.1.1, 6.2.4.1, 6.2.3.1, TS 24.582 clauses 6.1.1.3.1, 6.1.1.3.2. The following represents a copy/paste extraction of the requirements relevant to the test purpose; any references within the copy/paste text should be understood within the scope of the core spec they have been copied from. Unless otherwise stated, these are Rel-16 requirements.

[TS 24.282, clause 9.2.5.2.1.2]

Upon receiving a SIP re-INVITE request within a pre-established Session without an associated MCData session, the MCData client:

1) if the <mcdata-communication-state> element in the application/vnd.3gpp.mcdata-info+xml MIME body of the SIP INVITE request is set to a value of "establish-request":

   i) if the <request-type> element in the application/vnd.3gpp.mcdata-info+xml MIME body of the SIP INVITE request is set to a value of "one-to-one-sds", shall follow the procedures in subclause 9.2.3.2.4; and

   ii) if the <request-type> element in the application/vnd.3gpp.mcdata-info+xml MIME body of the SIP INVITE request is set to a value of "one-to-one-sds-session", shall follow the procedures in subclause 9.2.4.2.4.

[TS 24.282, clause 9.2.3.2.4]

Upon receipt of an "initial SIP INVITE request for standalone SDS over media plane for terminating MCData client" request, the MCData client shall follow the procedures for termination of multimedia sessions in the IM CN subsystem as specified in 3GPP TS 24.229 [5] with the clarifications below.

The MCData client:

1) may reject the SIP INVITE request if either of the following conditions are met:

a) MCData client does not have enough resources to handle the call; or

b) any other reason outside the scope of this specification;

and skip the rest of the steps after step 2;

2) if the SIP INVITE request is rejected in step 1), shall respond toward participating MCData function either with appropriate reject code as specified in 3GPP TS 24.229 [5] and warning texts as specified in subclause 4.9 or with SIP 480 (Temporarily unavailable) response not including warning texts if the user is authorised to restrict the reason for failure and skip the rest of the steps of this subclause;

3) if the SDP offer of the SIP INVITE request contains an "a=key-mgmt" attribute field with a "mikey" attribute value containing a MIKEY-SAKKE I_MESSAGE:

a) shall extract the MCData ID of the originating MCData user from the initiator field (IDRi) of the I_MESSAGE as described in 3GPP TS 33.180 [26];

b) shall convert the MCData ID to a UID as described in 3GPP TS 33.180 [26];

c) shall use the UID to validate the signature of the MIKEY-SAKKE I_MESSAGE as described in 3GPP TS 33.180 [26];

d) if authentication verification of the MIKEY-SAKKE I_MESSAGE fails, shall reject the SIP INVITE request with a SIP 488 (Not Acceptable Here) response as specified in IETF RFC 4567 [45], and include warning text set to "136 authentication of the MIKEY-SAKKE I_MESSAGE failed" in a Warning header field as specified in subclause 4.9 and not continue with rest of the steps in this subclause; and

e) if the signature of the MIKEY-SAKKE I_MESSAGE was successfully validated:

i) shall extract and decrypt the encapsulated PCK using the terminating user's (KMS provisioned) UID key as described in 3GPP TS 33.180 [26]; and

ii) shall extract the PCK-ID, from the payload as specified in 3GPP TS 33.180 [26];

NOTE: With the PCK successfully shared between the originating MCData client and the terminating MCData client, both clients are able to create an end-to-end secure session.

3) may display to the MCData user the MCData ID of the inviting MCData user and the type of SDS request;

4) shall accept the SIP INVITE request and generate a SIP 200 (OK) response according to rules and procedures of 3GPP TS 24.229 [5];

5) shall include the option tag "timer" in a Require header field of the SIP 200 (OK) response;

6) shall include the Session-Expires header field in the SIP 200 (OK) response and start the SIP session timer according to IETF RFC 4028 [38]. The "refresher" parameter in the Session-Expires header field shall be set to "uas";

7) shall include the g.3gpp.mcdata.sds media feature tag in the Contact header field of the SIP 200 (OK) response;

8) shall include the g.3gpp.icsi-ref media feature tag containing the value of "urn:urn-7:3gpp-service.ims.icsi.mcdata.sds" in the Contact header field of the SIP 200 (OK) response;

9) shall include an SDP answer in the SIP 200 (OK) response to the SDP offer in the incoming SIP INVITE request according to 3GPP TS 24.229 [5] with the clarifications given in subclause 9.2.3.2.2; and

10) shall send the SIP 200 (OK) response towards the MCData server according to rules and procedures of 3GPP TS 24.229 [5].

On receipt of an SIP ACK message to the sent SIP 200 (OK) message, the MCData client shall:

1) shall interact with the media plane as specified in 3GPP TS 24.582 [15] subclause 6.1.1.3.

[TS 24.282 clause 9.2.5.4.1.2]

Upon receiving a SIP re-INVITE request within a pre-established Session without an associated MCData session, the MCData client:

1) if the <mcdata-communication-state> element in the application/vnd.3gpp.mcdata-info+xml MIME body of the SIP INVITE request is set to a value of "terminate-request":

   i) shall send SIP 200 (OK) response towards MCData server according to 3GPP TS 24.229 [5]; and

   ii) shall release all media plane resources corresponding to the MCData communication being released.

[TS 24.282, clause 12.2.1.1]

The MCData client shall follow the procedures in this subclause to:

- indicate to an MCData client that an SDS message was delivered, read or delivered and read when the originating client requested a delivery, read or delivery and read report;

- indicate to the participating MCData function serving the MCData user that an SDS message was undelivered. The participating MCData function can store the message for later re-delivery;

- indicate to an MCData client that a request for FD was accepted, deferred or rejected; or

- indicate to an MCData client that a file download has been completed;

Before sending a disposition notification the MCData client needs to determine:

- the group identity related to an SDS or FD message request received as part of a group communication. The MCData client determines the group identity from the contents of the <mcdata-calling-group-id> element contained in the application/vnd.3gpp.mcdata-info+xml MIME body of the incoming SDS or FD message request; and

- the MCData user targeted for the disposition notification. The MCData client determines the targeted MCData user from the contents of the <mcdata-calling-user-id> element contained in the application/vnd.3gpp.mcdata-info+xml MIME body of the incoming SDS or FD message request.

The MCData client shall generate a SIP MESSAGE request in accordance with 3GPP TS 24.229 [5] and IETF RFC 3428 [6] with the clarifications given below.

The MCData client:

1) shall build the SIP MESSAGE request as specified in subclause 6.2.4.1;

2) shall follow the rules specified in subclause 6.4 for the handling of MIME bodies in a SIP message when processing the remaining steps in this subclause;

3) shall insert in the SIP MESSAGE request an application/resource-lists+xml MIME body containing the MCData ID of the targeted MCData user, according to rules and procedures of IETF RFC 5366 [18];

4) void;

5) if sending a disposition notification in response to an MCData group data request, shall include an <mcdata-calling-group-id> element set to the MCData group identity in the application/vnd.3gpp.mcdata-info+xml MIME body;

6) if requiring to send an SDS notification, shall generate an SDS NOTIFICATION message and include it in the SIP MESSAGE request as specified in subclause 6.2.3.1;

7) if requiring to send an FD notification, shall generate an FD NOTIFICATION message and include it in the SIP MESSAGE request as specified in subclause 6.2.3.2; and

8) shall send the SIP MESSAGE request according to rules and procedures of 3GPP TS 24.229 [5].

[TS 24.282, clause 6.2.4.1]

This subclause is referenced from other procedures.

In a SIP MESSAGE request, the MCData client:

1) when sending SDS messages or SDS disposition notifications:

a) shall include an Accept-Contact header field containing the g.3gpp.mcdata.sds media feature tag along with the "require" and "explicit" header field parameters according to IETF RFC 3841 [8];

b) shall include an Accept-Contact header field with the media feature tag g.3gpp.icsi-ref containing the value of "urn:urn-7:3gpp-service.ims.icsi.mcdata.sds" along with the "require" and "explicit" header field parameters according to IETF RFC 3841 [8]; and

c) shall include the ICSI value "urn:urn-7:3gpp-service.ims.icsi.mcdata.sds" (coded as specified in 3GPP TS 24.229 [5]), in a P-Preferred-Service header field according to IETF RFC 6050 [7] in the SIP MESSAGE request;

2) when sending FD messages, FD disposition notifications or FD media storage function discovery messages:

a) shall include an Accept-Contact header field containing the g.3gpp.mcdata.fd media feature tag along with the "require" and "explicit" header field parameters according to IETF RFC 3841 [8];

b) shall include an Accept-Contact header field with the media feature tag g.3gpp.icsi-ref containing the value of "urn:urn-7:3gpp-service.ims.icsi.mcdata.fd" along with the "require" and "explicit" header field parameters according to IETF RFC 3841 [8]; and

c) shall include the ICSI value "urn:urn-7:3gpp-service.ims.icsi.mcdata.fd" (coded as specified in 3GPP TS 24.229 [5]), in a P-Preferred-Service header field according to IETF RFC 6050 [7] in the SIP MESSAGE request;

3) may include a P-Preferred-Identity header field in the SIP MESSAGE request containing a public user identity as specified in 3GPP TS 24.229 [5]; and

4) shall set the Request-URI to the public service identity identifying the participating MCData function serving the MCData user.

[TS 24.282, clause 6.2.3.1]

In order to generate an SDS notification, the MCData client:

1) shall generate an SDS NOTIFICATION message as specified in subclause 15.1.5; and

2) shall include in the SIP request, the SDS NOTIFICATION message in an application/vnd.3gpp.mcdata-signalling MIME body as specified in subclause E.1.

When generating an SDS NOTIFICATION message as specified in subclause 15.1.5, the MCData client:

1) if sending a delivered notification, shall set the SDS disposition notification type IE as "DELIVERED" as specified in subclause 15.2.5;

2) if sending a read notification, shall set the SDS disposition notification type IE as "READ" as specified in subclause 15.2.5;

3) if sending a delivered and read notification, shall set the SDS disposition notification type IE as "DELIVERED AND READ" as specified in subclause 15.2.5;

4) if the SDS message could not be delivered to the user or application (e.g. due to lack of storage), shall set the SDS disposition notification type IE as "UNDELIVERED" as specified in subclause 15.2.5;

5) shall set the Date and time IE to the current time to as specified in subclause 15.2.8;

6) shall set the Conversation ID to the value of the Conversation ID that was received in the SDS message as specified in subclause 15.2.9;

7) shall set the Message ID to the value of the Message ID that was received in the SDS message as specified in subclause 15.2.10;

8) if the SDS message was destined for the user, shall not include an Application ID IE (as specified in subclause 15.2.7) and shall not include an Extended application ID IE (as specified in subclause 15.2.24); and

9) if the SDS message was destined for an application, shall include:

a) an Application ID IE set to the value of the Application ID that was included in the SDS message as specified in subclause 15.2.3; or

b) an Extended application ID IE set to the value of the Extended application ID that was included in the SDS message as specified in subclause 15.2.24.

[TS 24.582, clause 6.1.1.3.1]

Upon receiving an indication to establish MSRP connection for standalone SDS using media plane as the terminating client, the MCData client:

1. shall act as an MSRP client according to IETF RFC 6135 [12];

2. shall act either as an active endpoint or as an passive endpoint to open the transport connection, according to IETF RFC 6135 [12];

3. shall establish the MSRP connection according to the MSRP connection parameters in the SDP offer received in the SIP INVITE request according to IETF RFC 4975 [11];

4. if acting as an "active" endpoint, shall send an empty MSRP SEND request to bind the MSRP connection to the MSRP session from the perspective of the passive endpoint according to the rules and procedures of IETF RFC 4975 [11] and IETF RFC 6135 [12];

Once the MSRP connection is established, the MCData client:

1. on receipt of an MSRP request in an MSRP session, shall follow the rules and procedures defined in IETF RFC 4975 [11] and in IETF RFC 6714 [13];

2. If an MSRP SEND request indicates the use of chunking, shall wait until all further MSRP SEND requests for the remaining chunks have been received and shall reassemble the entire set of MSRP requests into the MCData standalone message before delivering the content to the application; and

3. shall handle the received content as described in subclause 6.1.1.3.2.

[TS 24.582, clause 6.1.1.3.2]

The MCData client:

1. shall decode the contents of the application/vnd.3gpp.mcdata-signalling MIME body;

2. shall decode the contents of the application/vnd.3gpp.mcdata-payload MIME body;

3. if the SDS SIGNALLING PAYLOAD message contains a new Conversation ID, shall instantiate a new conversation with the Message ID in the SDS SIGNALLING PAYLOAD identifying the first message in the conversation thread;

4. if the SDS SIGNALLING PAYLOAD message contains an existing Conversation ID and:

   a. if the SDS SIGNALLING PAYLOAD message does not contain an InReplyTo Message ID, shall use the Message ID in the SDS SIGNALLING PAYLOAD to identify a new message in the existing conversation thread; and

   b. if the SDS SIGNALLING PAYLOAD message contains an InReplyTo Message ID, shall associate the message to an existing message in the conversation thread as identified by the InReplyTo Message ID in the SDS SIGNALLING PAYLOAD and use the Message ID in the SDS SIGNALLING PAYLOAD to identify the new message;

5. shall identify the number of Payload IEs in the DATA PAYLOAD message from the Number of Payloads IE in the DATA PAYLOAD message;

6. if the SDS SIGNALLING PAYLOAD message does not contain an Application identifier IE:

   a. shall determine that the payload contained in the DATA PAYLOAD message is for user consumption;

   b. may notify the MCData user; and

   c. shall render the contents of the Payload IE(s) to the MCData user;

7. if the SDS SIGNALLING PAYLOAD message contains an Application identifier IE:
   a. shall determine that the payload contained in the DATA PAYLOAD message is not for user consumption;
   b. shall not notify the MCData user;
   c. if the Application identifier value is unknown, shall discard the SDS message; and
   d. if the Application identifier value is known, shall deliver the contents of the Payload IE(s) to the identified application; and
8. if SDS Disposition request type IE is present in the SDS SIGNALLING PAYLOAD message received in subclause 6.1.1.3.1 then, shall send a disposition notification as described in 3GPP TS 24.282 [8] subclause 9.2.1.3.

6.1.14.3 Test description

6.1.14.3.1 Pre-test conditions

Test configuration:

- Single cell configuration according to TS 37.579-1 [2] clause 5.2.2.2.1.

Preamble:

- The UE has performed procedure 'Initial registration' as described in TS 37.579-1 [2] clause 5.4.2 with the following clarifications:
  - The <max-payload-size-sds-cplane-bytes> element of the MCData Service Configuration document shall be set to 0 to force the MCData client to send the data using the media plane.
- The UE has performed procedure 'MCX pre-established session establishment' as described in TS 37.579-1 [2] clause 5.3.3.
- UE States at the end of the preamble:
  - The UE is in RRC_IDLE state.
  - The client is registered for MCData.
  - A pre-established session is established.

6.1.14.3.2 Test procedure sequence

Table 6.1.14.3.2-1: Main Behaviour

St	Procedure	Message Sequence		TP	Verdict
		U - S	Message		
1	Check: Does the UE (MCData client) correctly perform procedure '**CT MCData Call Establishment**' as described in TS 37.579-1 [2] Table 5.3C.3.3-1? NOTE: The SS (MCData server) sends a SIP re-INVITE request within a pre-established Session to initiate a one-to-one standalone SDS using the media plane.	-	-	1,2	P
2	Check: Does the UE (MCData client) correctly perform procedure 'CT MSRP message transfer' as described in TS 37.579-1 [2] Table 5.3C.5.3-1 to **receive an SDS message with disposition request "DELIVERY"**?	-	-	2	P
3-7	Check: Does the UE (MCData client) correctly perform step 3 to 7 of procedure '**MCData CO call release keeping the pre-established session**' as described in TS 37.579-1 [2] Table 5.3C.13.3-1? NOTE: The SS (MCData server) sends a SIP re-INVITE request to release the MCData call while keeping the pre-established Session. (NOTE 2)	-	-	3	P
8	Check: Does the UE (MCData client) correctly perform procedure '**CO SDS or FD message transfer** using signalling plane' as described in TS 37.579-1 [2] Table 5.3C.1.3-1 to **send a disposition notification of "DELIVERED"**?	-	-	2	P
9	Check: Does the UE (MCData client) provide the contents of the Payload IE to the user? (NOTE 1)	-	-	2	P
NOTE 1: This is expected to be done via a suitable implementation dependent MMI. NOTE 2: The procedure does not release the RRC connection.					

6.1.14.3.3 Specific message contents

Table 6.1.14.3.3-1: SIP INVITE from the SS (step 1, Table 6.1.14.3.2-1; step 2, TS 37.579-1 [2] Table 5.3C.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.5.2-1, condition MCDATA_SDS, re_INVITE				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Request-Line				
Request-URI	tsc_MCX_SessionID_B	session identity of the pre-established session	TS 24.282 [31] clause 9.2.5.2.2.2	
Message-body				
MIME body part		**SDP message**		
MIME-part-body	SDP message as described in Table 6.1.14.3.3-2			
MIME body part		**MCData-Info**		
MIME-part-body	MCData-Info as described in Table 6.1.14.3.3-3			

Table 6.1.14.3.3-2: SDP for SIP INVITE (Table 6.1.14.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.1.2-3, condition MCDATA_SDS, SDP_OFFER, MCD_1to1, PRE_ESTABLISHED_SESSION

Table 6.1.14.3.3-3: MCData-Info (Table 6.1.14.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.2.2-3, condition MCD_1to1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
mcdata-info				
mcdata-Params				
anyExt				
mcdata-communication-state	"establish-request"		TS 24.282 [31] clause 9.2.5.2.2.2	

Table 6.1.14.3.3-4: SIP 200 (OK) from the UE (step 1, Table 6.1.14.3.2-1; step 4, TS 37.579-1 [2] Table 5.3C.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.17.1.1-1, condition INVITE-RSP, MCDATA_SDS				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Content-Type				
value	"application/sdp"			
Message-body				
SDP message	As described in Table 6.1.14.3.3-5			

Table 6.1.14.3.3-5: SDP for SIP 200 (OK) (Table 6.1.14.3.3-4)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.1.1-3, condition MCDATA_SDS, SDP_ANSWER, PRE_ESTABLISHED_SESSION

Table 6.1.14.3.3-6: MSRP SEND from the SS (step 2, Table 6.1.14.3.2-1; step 1, TS 37.579-1 [2] Table 5.3C.5.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.12.1.2-1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Content-Type				
media-type	"multipart/mixed"			
data	Message as specified in table 6.1.14.3.3-7			

Table 6.1.14.3.3-7: MIME Message (Table 6.1.14.3.2-1; step 1, TS 37.579-1 [2] Table 5.3C.5.3-1)

Derivation Path: RFC 2046 [38]				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
MIME body part		**MCData Data signalling message**		
MIME-part-headers				
Content-Type	"application/vnd.3gpp. mcdata-signalling"			
MIME-part-body	MCData Protected Payload Message containing SDS SIGNALLING PAYLOAD as described in table 6.1.14.3.3-8			
MIME body part		**MCData Data message**		
MIME-part-headers				
Content-Type	"application/vnd.3gpp. mcdata-payload"			
MIME-part-body	DATA PAYLOAD as described in Table 6.1.14.3.3-9			

Table 6.1.14.3.3-8: SDS SIGNALLING PAYLOAD (Table 6.1.14.3.3-7)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.2-1, condition DELIVERED

Table 6.1.14.3.3-9: Data Payload (Table 6.1.14.3.3-7)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.9.2-2

Table 6.1.14.3.3-10: SIP re-INVITE from the SS (step 3, Table 6.1.14.3.2-1; step 3, TS 37.579-1 [2] Table 5.3C.13.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.5.2-1, condition MCDATA_SDS, re_INVITE				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Request-Line				
Request-URI	tsc_MCX_SessionID_B	session identity of the pre-established session	TS 24.282 [31] clause 9.2.5.4.2.1	
Message-body				
MIME body part	not present	**SDP message**		
MIME body part		**MCData Info**		
MIME-part-body	MCData-Info message as described in Table 6.1.14.3.3-11			

Table 6.1.14.3.3-11: MCData-Info (Table 6.1.14.3.3-10)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.2.2-3				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
mcdata-info				
mcdata-Params				
mcdata-request-uri	not present			
mcdata-calling-user-id	not present			
anyExt				
mcdata-communication-state	"terminate request"		TS 24.282 [31] clause 9.2.5.4.2.2	

Table 6.1.14.3.3-12: SIP MESSAGE from the UE (step 8, Table 6.1.14.3.2-1; step 2, TS 37.579-1 [2] Table 5.3C.1.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.7.1-1, condition MCDATA_SDS, RESOURCE_LISTS, MCDATA_SIGNALLING				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part	not present	**MCData-Info**		
MIME body part		**MCData Data signalling message**		
MIME-part-body	MCData Protected Payload Message containing SDS NOTIFICATION as described in Table 6.1.14.3.3-13			

Table 6.1.14.3.3-13: SDS NOTIFICATION (Table 6.1.14.3.3-12)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.3-1, condition DELIVERED

6.1.15 On-network / Short Data Service (SDS) / SDS Session / One-to-one SDS Session / Pre-established session / Client Originated (CO)

6.1.15.1 Test Purpose (TP)

(1)

```
with { UE (MCDATA Client) registered and authorised for MCDATA Service }
ensure that {
  when { the MCDATA User requests to initiate a one-to-one SDS session using the media plane and
using the pre-established session }
    then { UE (MCDATA Client) sends a request to establish a one-to-one SDS session and a MSRP
connection via a SIP REFER message and responds to the SIP re-INVITE message with a SIP 200 (OK)
message and delivers the notification to the MCDATA User about successful communication
establishment and sends a blank MSRP SEND message to bind the MSRP connection }
            }
```

(2)

```
with { UE (MCDATA Client) having sent a blank MSRP SEND message to bind the MSRP connection }
ensure that {
  when { UE (MCDATA Client) receives an MSRP 200 (OK) message in response to the blank MSRP SEND
message }
    then { UE (MCDATA Client) sends the one-to-one session SDS message via a MSRP SEND message with
a disposition of "DELIVERY" }
            }
```

(3)

```
with { UE (MCDATA Client) having sent a one-to-one session SDS message using the media plane with a
disposition of "DELIVERY" }
ensure that {
  when { UE (MCDATA Client) receives a disposition response via a MSRP SEND message }
    then { UE (MCDATA Client) responds to the MSRP SEND message by sending a MSRP 200 (OK) message
and delivers the notification to the MCDATA User }
            }
```

(4)

```
with { UE (MCDATA Client) having established a one-to-one SDS session using the pre-established
session }
ensure that {
  when { the MCDATA User requests to release the one-to-one SDS session while keeping the pre-
established session }
    then { UE (MCDATA Client) sends a SIP REFER message to release the MCData session and keep the
pre-established session and responds to the SIP re-INVITE message with a SIP 200 (OK) message and
delivers the notification to the MCDATA User about successful termination }
            }
```

6.1.15.2 Conformance requirements

References: The conformance requirements covered in the current TC are specified in: TS 24.282, clauses 9.2.5.2.1.1, 9.2.3.2.1, 9.2.5.4.1.1, TS 24.582 clauses 12.1, 6.1.2.2.1, 6.1.2.6. The following represents a copy/paste extraction of the requirements relevant to the test purpose; any references within the copy/paste text should be understood within the scope of the core spec they have been copied from. Unless otherwise stated, these are Rel-16 requirements.

[TS 24.282, clause 9.2.5.2.1.1]

Upon receiving a request from an MCData user to initiate one-to-one standalone SDS using media plane or one-to-one SDS session within the pre-established session, the MCData client shall generate a SIP REFER request outside a dialog as specified in IETF RFC 3515 [51] as updated by IETF RFC 6665 [36] and IETF RFC 7647 [52], and in accordance with the UE procedures specified in 3GPP TS 24.229 [5], with the clarifications given below.

The MCData client:

1) shall set the Request URI of the SIP REFER request to the session identity of the pre-established session;

2) shall set the Refer-To header field of the SIP REFER request as specified in IETF RFC 3515 [51] with a Content-ID ("cid") Uniform Resource Locator (URL) as specified in IETF RFC 2392 [33] that points to an application/resource-lists MIME body as specified in IETF RFC 5366 [18], and with the Content-ID header field set to this "cid" URL;

3) if an end-to-end security context needs to be established and the security context does not exist or if the existing security context has expired, then:

   i) if necessary, shall instruct the key management client to request keying material from the key management server as described in 3GPP TS 33.180 [26];

   ii) shall use the keying material to generate a PCK as described in 3GPP TS 33.180 [26];

   iii) shall use the PCK to generate a PCK-ID with the four most significant bits set to "0001" to indicate that the purpose of the PCK is to protect one-to-one communications and with the remaining twenty eight bits being randomly generated as described in 3GPP TS 33.180 [26];

   iv) shall encrypt the PCK to a UID associated to the MCData client using the MCData ID of the invited user and a time related parameter as described in 3GPP TS 33.180 [26];

   v) shall generate a MIKEY-SAKKE I_MESSAGE using the encapsulated PCK and PCK-ID as specified in 3GPP TS 33.180 [26];

   vi) shall add the MCData ID of the originating MCData to the initiator field (IDRi) of the I_MESSAGE as described in 3GPP TS 33.180 [26]; and

vii) shall sign the MIKEY-SAKKE I_MESSAGE using the originating MCData user's signing key provided in the keying material together with a time related parameter, and add this to the MIKEY-SAKKE payload, as described in 3GPP TS 33.180 [26];

4) shall include in the application/resource-lists MIME body a single <entry> element containing a "uri" attribute set to MCData ID of the called user, extended with the following parameters in the headers portion of the SIP URI:

NOTE: Characters that are not formatted as ASCII characters are escaped in the following parameters in the headers portion of the SIP URI.

a) an hname "body" parameter populated with:

i) an application/sdp MIME body containing an SDP offer with media attributes specified in subclause 9.2.3.2.1, if a one-to-one standalone SDS message is requested;

ii) an application/vnd.3gpp.mcdata-info MIME body with:

A) if a one-to-one standalone SDS message is requested, the <request-type> element set to a value of "one-to-one-sds". If a one-to-one SDS session is requested, the <request-type> element set to a value of "one-to-one-sds-session";

B) the <mcdata-client-id> element set to the MCData client ID of the originating MCData client; and

C) if the MCData client is aware of active functional aliases and if an active functional alias is to be included in the SIP REFER request, the <functional-alias-URI> element set to the URI of the used functional alias;

5) shall include a P-Preferred-Service header field set to the ICSI value "urn:urn-7:3gpp-service.ims.icsi.mcdata.sds" (coded as specified in 3GPP TS 24.229 [5]), according to IETF RFC 6050 [7];

6) may include a P-Preferred-Identity header field in the SIP INVITE request containing a public user identity as specified in 3GPP TS 24.229 [5];

7) shall include the following according to IETF RFC 4488 [53]:

a) the option tag "norefersub" in the Supported header field; and

b) the value "false" in the Refer-Sub header field;

8) shall include a Target-Dialog header field as specified in IETF RFC 4538 [54] identifying the pre-established session;

9) shall include the g.3gpp.mcdata.sds media feature tag in the Contact header field of the SIP REFER request according to IETF RFC 3840 [16]; and

10) shall send the SIP REFER request according to 3GPP TS 24.229 [5].

On receiving a final SIP 2xx response to the SIP REFER request, the MCData client:

1) shall interact with the media plane as specified in 3GPP TS 24.582 [15].

On receiving a SIP re-INVITE request within the pre-established session targeted by the sent SIP REFER request, the MCData client:

1) if the <mcdata-communication-state> element in the application/vnd.3gpp.mcdata-info+xml MIME body of the SIP INVITE request is set to a value of "establish-success":

i) shall notify MCData user about successful the MCData communication establishment;

2) if the <mcdata-communication-state> element in the application/vnd.3gpp.mcdata-info+xml MIME body of the SIP INVITE request is set to a value of "establish-fail":

i) shall notify MCData user about the MCData communication establishment failure; and

3) shall interact with the media plane as specified in 3GPP TS 24.582 [15].

[TS 24.282, clause 9.2.3.2.1]

When composing an SDP offer according to 3GPP TS 24.229 [5], IETF RFC 4975 [17], IETF RFC 6135 [19] and IETF RFC 6714 [20] the MCData client:

1) shall include an "m=message" media-level section for the MCData media stream consisting of:

   a) the port number;

   b) a protocol field value of "TCP/MSRP", or "TCP/TLS/MSRP" for TLS;

   c) a format list field set to '*';

   d) an "a=sendonly" attribute;

   e) an "a=path" attribute containing its own MSRP URI;

   f) set the content type as "a=accept-types:application/vnd.3gpp.mcdata-signalling application/vnd.3gpp.mcdata-payload"; and

   g) set the a=setup attribute as "actpass"; and

2) if end-to-end security is required for a one-to-one communication and the security context does not exist or if the existing security context has expired, shall include the MIKEY-SAKKE I_MESSAGE in an "a=key-mgmt" attribute as a "mikey" attribute value in the SDP offer as specified in IETF RFC 4567 [45].

[TS 24.282, clause 9.2.5.4.1.1]

Upon receiving a request from an MCData user to leave an MCData session within a pre-established session, the MCData client:

1) shall interact with the media plane as specified in 3GPP TS 24.582 [15];

2) shall generate an initial SIP REFER request outside a dialog in accordance with the procedures specified in 3GPP TS 24.229 [5], IETF RFC 4488 [53] and IETF RFC 3515 [51] as updated by IETF RFC 6665 [36] and IETF RFC 7647 [r7647];

3) shall set the Request-URI of the SIP REFER request to the public service identity identifying the pre-established session on the MCData server serving the MCData user;

4) shall include the Refer-Sub header field with value "false" according to rules and procedures of IETF RFC 4488 [53];

5) shall include the Supported header field with value "norefersub" according to rules and procedures of IETF RFC 4488 [53];

6) shall set the Refer-To header field of the SIP REFER request to the MCData session identity to leave;

7) shall include the "method" SIP URI parameter with the value "BYE" in the URI in the Refer-To header field;

8) shall include a Target-Dialog header field as specified in IETF RFC 4538 [54] identifying the pre-established session; and

9) shall send the SIP REFER request according to 3GPP TS 24.229 [5].

Upon receiving a SIP 2xx response to the SIP REFER request, the MCData client shall interact with media plane as specified in 3GPP TS 24.582 [15].

On receiving a SIP re-INVITE request within the pre-established session targeted by the sent SIP REFER request, the MCData client:

1) if the <mcdata-communication-state> element in the application/vnd.3gpp.mcdata-info+xml MIME body of the SIP INVITE request is set to a value of "terminated":

   i) shall notify MCData user about successful the MCData communication termination.

[TS 24.582, clause 12.1]

Upon establishing one-to-one or group SDS using media plane or one-to-one or group SDS session using pre-established call, the MCData client shall follow procedures as descried in subclause 6.1.

[TS 24.582, clause 6.1.2.2.1]

Upon receiving an indication to establish MSRP connection for SDS session as the originating MCData client, the MCData client:

1. shall act as an MSRP client according to IETF RFC 6135 [12];
2. shall act according to IETF RFC 6135 [12], as:
   a. an "active" endpoint, if a=setup attribute in the received SDP answer is set to "passive"; and
   b. an "passive" endpoint, if a=setup attribute in the received SDP answer is set to "active";
3. shall establish the MSRP connection according to the MSRP connection parameters in the SDP answer received in the SIP 200 (OK) response according to IETF RFC 4975 [11];
4. if acting as an "active" endpoint, shall send an empty MSRP SEND request to bind the MSRP connection to the MSRP session from the perspective of the passive endpoint according to the rules and procedures of IETF RFC 4975 [11] and IETF RFC 6135 [12];

Once the MSRP session is established, the MCData client:

1. on receipt of an MSRP request in the MSRP session, shall follow the rules and procedures defined in IETF RFC 4975 [11] and in IETF RFC 6714 [13];
2. If an MSRP SEND request indicates the use of chunking, shall wait until all further MSRP SEND requests for the remaining chunks have been received and shall reassemble the entire set of MSRP requests into the MCData SDS message before delivering the content to the application; and
3. shall handle the received content as described in subclause 6.1.2.6.

On receiving MSRP 200 (OK) response to the first MSRP SEND request, the MCData client can generate and send an SDS message as specified in subclause 6.1.2.4, or can generate and send an SDS disposition notification for a received SDS message as specified in subclause 6.1.2.5, if requested.

Received content and disposition requests shall be handled as specified in subclause 6.1.2.6.

[TS 24.582, clause 6.1.2.6]

Upon receiving an SDS message, the MCData client:

1. shall follow the procedure defined in subclause 6.1.1.3.2, with the following clarification:
   a. if SDS Disposition request type IE is present in the received SDS SIGNALLING PAYLOAD message then, shall send an SDS disposition notification as described in subclause 6.1.2.5.

Upon receiving an SDS disposition notification, the MCData client:

1. shall decode the contents of the application/vnd.3gpp.mcdata-signalling MIME body; and
2. shall deliver the notification to the user or application.

6.1.15.3 Test description

6.1.15.3.1 Pre-test conditions

Test configuration:

- Single cell configuration according to TS 37.579-1 [2] clause 5.2.2.2.1.

Preamble:

- The UE has performed procedure 'Initial registration' as described in TS 37.579-1 [2] clause 5.4.2.
- The UE has performed procedure 'MCX pre-established session establishment' as described in TS 37.579-1 [2] clause 5.3.3.
- UE States at the end of the preamble:
  - The UE is in RRC_IDLE state.
  - The client is registered for MCData.
  - A pre-established session is established.

6.1.15.3.2 Test procedure sequence

Table 6.1.15.3.2-1: Main Behaviour

St	Procedure	Message Sequence		TP	Verdict
		U - S	Message		
1	Make the UE (MCData client) send a one-to-one session SDS message using the pre-established session with disposition request "**DELIVERY**". (NOTE 1)	-	-	-	-
2	Check: Does the UE (MCData client) correctly perform procedure '**CO MCData call establishment using a pre-established session**' as described in TS 37.579-1 [2] Table 5.3C.12.3-1?	-	-	1	P
3	Check: Does the UE (MCData client) notify the user about successful MCData communication establishment? (NOTE 1)	-	-	1	P
4	Check: Does the UE (MCData client) correctly perform procedure 'CO MSRP message transfer' as described in TS 37.579-1 [2] Table 5.3C.4.3-1 to **send an SDS message with disposition request "DELIVERY"**?	-	-	2	P
5	Check: Does the UE (MCData client) correctly perform procedure '**CT MSRP message transfer**' as described in TS 37.579-1 [2] Table 5.3C.5.3-1 **to receive the disposition notification** for the SDS message sent at step 3?	-	-	3	P
6	Check: Does the UE (MCData client) provide the disposition notification to the user? (NOTE 1)	-	-	3	P
7	Make the UE (MCData client) release the one-to-one session while keeping the pre-established session. (NOTE 1)	-	-	-	-
8	Check: Does the UE (MCData client) correctly perform procedure '**MCData CO call release keeping the pre-established session**' as described in TS 37.579-1 [2] Table 5.3C.13.3-1? (NOTE 2)	-	-	4	P
8A	The procedure 'MCX communication release' as described in TS 37.579-1 [2] clause 5.4.14 is performed to release the RRC connection.	-	-	-	-
9	Check: Does the UE (MCData client) provide a notification to the MCData user about successful MCData communication termination? (NOTE 1)	-	-	4	P
NOTE 1: This is expected to be done via a suitable implementation dependent MMI. NOTE 2: The procedure does not release the RRC connection.					

6.1.15.3.3 Specific message contents

Table 6.1.15.3.3-1: SIP REFER from the UE (step 2, Table 6.1.15.3.2-1; step 2, TS 37.579-1 [2] Table 5.3C.12.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.12-1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part		**Resource list**		
MIME-part-body	Resource-lists as described in Table 6.1.15.3.3-2			

Table 6.1.15.3.3-2: Resource-lists in SIP REFER (Table 6.1.15.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.3.1-3, condition PRE-ESTABLISH, MCD_1to1 with the uri attribute of the entry extended with the SIP URI header fields as specified in Table 6.1.15.3.3-3

Table 6.1.15.3.3-3: SIP header fields extending the uri attribute of the resource-lists' single entry (Table 6.1.15.3.3-2)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.12-2				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
body				
MIME body part		**SDP Message**		
MIME-part-headers				
Content-Type	“application/sdp”			
MIME-part-body	SDP Message as described in Table 6.1.15.3.3-4			
MIME body part		**MCData-Info**		
MIME-part-body	MCdata-Info as described in Table 6.1.15.3.3-5			

Table 6.1.15.3.3-4: SDP in SIP header fields (Table 6.1.15.3.3-3)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.1.1-3, condition PRE_ESTABLISHED_SESSION, SDP_OFFER, MCD_1to1, MCDATA_SDS, SDS_SESSION

Table 6.1.15.3.3-5: MCData-Info in SIP header fields (Table 6.1.15.3.3-3)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.2.1-3, condition MCD_1to1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
mcdata-info				
mcdata-Params				
request-type	"one-to-one-sds-session"		TS 24.282 [31] clause 9.2.5.2.1.1	
mcdata-client-id	Encrypted (NOTE 1) <mcdata-client-id> with mcdataString set to the mcdata-client-id as provided by the UE at registration		TS 24.282 [31] clause 9.2.5.2.1.1	
NOTE 1: Encrypted element as described in TS 37.579-1 [2] Table 5.5.3.2.1-3A				

Table 6.1.15.3.3-6: MSRP SEND from the UE (step 4, Table 6.1.15.3.2-1; step 1, TS 37.579-1 [2] Table 5.3C.4.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.12.1.1-1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Content-Type				
media-type	"multipart/mixed"			
data	Message or chunk of message as specified in table 6.1.15.3.3-7			

Table 6.1.15.3.3-7: MIME Message (step 4, Table 6.1.15.3.2-1; step 3, TS 37.579-1 [2] Table 5.3C.4.3-1)

Derivation Path: RFC 2046 [38]				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
MIME body part		**MCData Data signalling message**		
MIME-part-headers				
Content-Type	"application/vnd.3gpp. mcdata-signalling"			
MIME-part-body	MCData Protected Payload Message containing SDS SIGNALLING PAYLOAD as described in table 6.1.15.3.3-8			
MIME body part		**MCData Data message**		
MIME-part-headers				
Content-Type	"application/vnd.3gpp. mcdata-payload"			
MIME-part-body	DATA PAYLOAD as described in Table 6.1.15.3.3-9			

Table 6.1.15.3.3-8: SDS SIGNALLING PAYLOAD (Table 6.1.15.3.3-7)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.1-1, condition DELIVERED

Table 6.1.15.3.3-9: Data Payload (Table 6.1.15.3.3-7)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.9.2-1

Table 6.1.15.3.3-10: MSRP SEND from the SS (step 5, Table 6.1.15.3.2-1; step 1, TS 37.579-1 [2] Table 5.3C.5.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.12.1.2-1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Content-Type				
media-type	"application/vnd.3gpp. mcdata-signalling"			
data	MCData Protected Payload Message containing SDS NOTIFICATION as specified in table 6.1.15.3.3-11			

Table 6.1.15.3.3-11: SDS NOTIFICATION (Table 6.1.15.3.3-10)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.4-1, condition DELIVERED

6.1.16 On-network / Short Data Service (SDS) / SDS Session / One-to-one SDS Session / Pre-established session / Client Terminated (CT)

6.1.16.1 Test Purpose (TP)

(1)

```
with { UE (MCDATA Client) registered and authorised for MCDATA Service }
ensure that {
  when { the MCDATA User receives a SIP re-INVITE message to initiate to initiate a one-to-one SDS
session using the media plane and using a pre-established session }
    then { UE (MCDATA Client) responds by sending a SIP 200 (OK) message }
            }
```

(2)

```
with { UE (MCDATA Client) having responded to the SIP re-INVITE message that initiated a one-to-one
SDS session using the media plane and using a pre-established session }
ensure that {
  when { UE (MCDATA Client) receives an MSRP SEND message }
    then { UE (MCDATA Client) responds with an MSRP 200 (OK) message and if the MSRP SEND message is
not blank, renders the contents of the Payload IE to the MCDATA User and sends a MSRP SEND message
with a disposition notification of "DELIVERED" }
            }
```

(3)

```
with { UE (MCDATA Client) being in a one-to-one SDS session initiated by the SS (MCDATA server) and
using a pre-established session }
ensure that {
  when { UE (MCDATA Client) receives a SIP re-INVITE message to release communications }
    then { UE (MCDATA Client) responds by sending a SIP 200 (OK) message }
            }
```

6.1.16.2 Conformance requirements

References: The conformance requirements covered in the current TC are specified in: TS 24.282, clauses 9.2.5.2.1.2, 9.2.4.2.4, 9.2.5.4.1.2, TS 24.582 clauses 12.1, 6.1.2.3.1, 6.1.2.6, 6.1.1.3.2, 6.1.2.5.1, 6.1.2.5.2, 6.1.2.5.3. The following represents a copy/paste extraction of the requirements relevant to the test purpose; any references within the copy/paste text should be understood within the scope of the core spec they have been copied from. Unless otherwise stated, these are Rel-16 requirements.

[TS 24.282, clause 9.2.5.2.1.2]

Upon receiving a SIP re-INVITE request within a pre-established Session without an associated MCData session, the MCData client:

1) if the <mcdata-communication-state> element in the application/vnd.3gpp.mcdata-info+xml MIME body of the SIP INVITE request is set to a value of "establish-request":

   i) if the <request-type> element in the application/vnd.3gpp.mcdata-info+xml MIME body of the SIP INVITE request is set to a value of "one-to-one-sds", shall follow the procedures in subclause 9.2.3.2.4; and

   ii) if the <request-type> element in the application/vnd.3gpp.mcdata-info+xml MIME body of the SIP INVITE request is set to a value of "one-to-one-sds-session", shall follow the procedures in subclause 9.2.4.2.4.

[TS 24.282, clause 9.2.4.2.4]

Upon receipt of an "initial SIP INVITE request for SDS session for terminating MCData client"request, the MCData client shall follow the procedures for termination of multimedia sessions in the IM CN subsystem as specified in 3GPP TS 24.229 [5] with the clarifications below.

The MCData client:

1) may reject the SIP INVITE request if either of the following conditions are met:

   a) MCData client does not have enough resources to handle the call; or

   b) any other reason outside the scope of this specification;

   and skip the rest of the steps after step 2;

2) if the SIP INVITE request is rejected in step 1), shall respond toward participating MCData function either with appropriate reject code as specified in 3GPP TS 24.229 [5] and warning texts as specified in subclause 4.9 or with SIP 480 (Temporarily unavailable) response not including warning texts if the user is authorised to restrict the reason for failure and skip the rest of the steps of this subclause;

3) if the SDP offer of the SIP INVITE request contains an "a=key-mgmt" attribute field with a "mikey" attribute value containing a MIKEY-SAKKE I_MESSAGE:

   a) shall extract the MCData ID of the originating MCData user from the initiator field (IDRi) of the I_MESSAGE as described in 3GPP TS 33.180 [26];

   b) shall convert the MCData ID to a UID as described in 3GPP TS 33.180 [26];

   c) shall use the UID to validate the signature of the MIKEY-SAKKE I_MESSAGE as described in 3GPP TS 33.180 [26];

   d) if authentication verification of the MIKEY-SAKKE I_MESSAGE fails, shall reject the SIP INVITE request with a SIP 488 (Not Acceptable Here) response as specified in IETF RFC 4567 [45], and include warning text set to "136 authentication of the MIKEY-SAKKE I_MESSAGE failed" in a Warning header field as specified in subclause 4.9 and not continue with rest of the steps in this subclause; and

   e) if the signature of the MIKEY-SAKKE I_MESSAGE was successfully validated:

      i) shall extract and decrypt the encapsulated PCK using the terminating user's (KMS provisioned) UID key as described in 3GPP TS 33.180 [26]; and

      ii) shall extract the PCK-ID, from the payload as specified in 3GPP TS 33.180 [26];

NOTE: With the PCK successfully shared between the originating MCData client and the terminating MCData client, both clients are able to create an end-to-end secure session.

4) may display to the MCData user the MCData ID of the inviting MCData user and the type of SDS request;

5) shall accept the SIP INVITE request and generate a SIP 200 (OK) response according to rules and procedures of 3GPP TS 24.229 [5];

6) shall include the option tag "timer" in a Require header field of the SIP 200 (OK) response;

7) shall include the Session-Expires header field in the SIP 200 (OK) response and start the SIP session timer according to IETF RFC 4028 [38]. The "refresher" parameter in the Session-Expires header field shall be set to "uas";

8) shall include the g.3gpp.mcdata.sds media feature tag in the Contact header field of the SIP 200 (OK) response;

9) shall include the g.3gpp.icsi-ref media feature tag containing the value of "urn:urn-7:3gpp-service.ims.icsi.mcdata.sds" in the Contact header field of the SIP 200 (OK) response;

10) shall include an SDP answer in the SIP 200 (OK) response to the SDP offer in the incoming SIP INVITE request according to 3GPP TS 24.229 [5] with the clarifications given in subclause 9.2.4.2.2; and

11) shall send the SIP 200 (OK) response towards the MCData server according to rules and procedures of 3GPP TS 24.229 [5].

On receipt of an SIP ACK message to the sent SIP 200 (OK) message, the MCData client shall:

1) shall interact with the media plane as specified in 3GPP TS 24.582 [15] subclause 6.1.2.3.

To send a disposition notification after the media plane is released, the MCData client:

1) shall follow the procedures described in subclause 12.2.1.1.

[TS 24.282, clause 9.2.5.4.1.2]

Upon receiving a SIP re-INVITE request within a pre-established Session without an associated MCData session, the MCData client:

1) if the <mcdata-communication-state> element in the application/vnd.3gpp.mcdata-info+xml MIME body of the SIP INVITE request is set to a value of "terminate-request":

   i) shall send SIP 200 (OK) response towards MCData server according to 3GPP TS 24.229 [5]; and

   ii) shall release all media plane resources corresponding to the MCData communication being released.

[TS 24.582, clause 12.1]

Upon establishing one-to-one or group SDS using media plane or one-to-one or group SDS session using pre-established call, the MCData client shall follow procedures as descried in subclause 6.1.

[TS 24.582, clause 6.1.2.3.1]

Upon receiving an indication to establish MSRP connection for SDS session as the terminating MCData client, the MCData client:

1. shall act as an MSRP client according to IETF RFC 6135 [12];

2. shall act either as an active endpoint or as an passive endpoint to open the transport connection, according to IETF RFC 6135 [12];

3. shall establish the MSRP connection according to the MSRP connection parameters in the SDP offer received in the SIP INVITE request according to IETF RFC 4975 [11];

4. if acting as an "active" endpoint, shall send an empty MSRP SEND request to bind the MSRP connection to the MSRP session from the perspective of the passive endpoint according to the rules and procedures of IETF RFC 4975 [11] and IETF RFC 6135 [12];

Once the MSRP session is established, the MCData client:

1. on receipt of an MSRP request in the MSRP session, shall follow the rules and procedures defined in IETF RFC 4975 [11] and in IETF RFC 6714 [13];

2. If an MSRP SEND request indicates the use of chunking, shall wait until all further MSRP SEND requests for the remaining chunks have been received and shall reassemble the entire set of MSRP requests into the MCData SDS message before delivering the content to the application; and

3. shall handle the received content as described in subclause 6.1.2.6.

On receiving MSRP 200 (OK) response to the first MSRP SEND request sent as "active" endpoint, or after sending MSRP 200 (OK) response to the first MSRP SEND request received as "passive" endpoint, the MCData client can generate and send an SDS message as specified in subclause 6.1.2.4, or can generate and send an SDS disposition notification for a received SDS message as specified in subclause 6.1.2.5, if requested.

Received content and disposition requests shall be handled as specified in subclause 6.1.2.6.

[TS 24.582, clause 6.1.2.6]

Upon receiving an SDS message, the MCData client:

1. shall follow the procedure defined in subclause 6.1.1.3.2, with the following clarification:

   a. if SDS Disposition request type IE is present in the received SDS SIGNALLING PAYLOAD message then, shall send an SDS disposition notification as described in subclause 6.1.2.5.

Upon receiving an SDS disposition notification, the MCData client:

1. shall decode the contents of the application/vnd.3gpp.mcdata-signalling MIME body; and
2. shall deliver the notification to the user or application.

[TS 24.582, clause 6.1.1.3.2]

The MCData client:

1. shall decode the contents of the application/vnd.3gpp.mcdata-signalling MIME body;
2. shall decode the contents of the application/vnd.3gpp.mcdata-payload MIME body;
3. if the SDS SIGNALLING PAYLOAD message contains a new Conversation ID, shall instantiate a new conversation with the Message ID in the SDS SIGNALLING PAYLOAD identifying the first message in the conversation thread;
4. if the SDS SIGNALLING PAYLOAD message contains an existing Conversation ID and:
    a. if the SDS SIGNALLING PAYLOAD message does not contain an InReplyTo Message ID, shall use the Message ID in the SDS SIGNALLING PAYLOAD to identify a new message in the existing conversation thread; and
    b. if the SDS SIGNALLING PAYLOAD message contains an InReplyTo Message ID, shall associate the message to an existing message in the conversation thread as identified by the InReplyTo Message ID in the SDS SIGNALLING PAYLOAD and use the Message ID in the SDS SIGNALLING PAYLOAD to identify the new message;
5. shall identify the number of Payload IEs in the DATA PAYLOAD message from the Number of Payloads IE in the DATA PAYLOAD message;
6. if the SDS SIGNALLING PAYLOAD message does not contain an Application identifier IE:
    a. shall determine that the payload contained in the DATA PAYLOAD message is for user consumption;
    b. may notify the MCData user; and
    c. shall render the contents of the Payload IE(s) to the MCData user;
7. if the SDS SIGNALLING PAYLOAD message contains an Application identifier IE:
    a. shall determine that the payload contained in the DATA PAYLOAD message is not for user consumption;
    b. shall not notify the MCData user;
    c. if the Application identifier value is unknown, shall discard the SDS message; and
    d. if the Application identifier value is known, shall deliver the contents of the Payload IE(s) to the identified application; and
8. if SDS Disposition request type IE is present in the SDS SIGNALLING PAYLOAD message received in subclause 6.1.1.3.1 then, shall send a disposition notification as described in 3GPP TS 24.282 [8] subclause 9.2.1.3.

[TS 24.582, clause 6.1.2.5.1]

To send an SDS disposition notification, the MCData client:

1. shall generate a SDS NOTIFICATION as specified in subclause 6.1.2.5.2;
2. shall include the SDS NOTIFICATION in an MSRP SEND request as specified in subclause 6.1.2.5.3, with the following clarification;
    a. shall set To-Path header according to the MSRP URI in the received SDP; and
3. shall send the MSRP SEND request on the established MSRP connection.

If MSRP chunking is used, the MCData client:

1. shall send further MSRP SEND requests as necessary.

On receiving a non-200 MSRP response to the MSRP SEND request the MCData client shall handle the error as specified in IETF RFC 4975 [11]. To terminate the MSRP session, the MCData client:

1. if there are further MSRP chunks to send, shall abort transmission of these further MSRP chunks; and
2. shall indicate to MCData user that the SDS message or the SDS disposition notification could not be sent.

[TS 24.582, clause 6.1.2.5.2]

In order to generate an SDS notification, the MCData client:

1. shall generate an SDS NOTIFICATION message as specified in 3GPP TS 24.282 [8]; and
2. shall include the SDS NOTIFICATION message in an application/vnd.3gpp.mcdata-signalling MIME body as specified in 3GPP TS 24.282 [8].

When generating an SDS NOTIFICATION message, the MCData client:

1. if sending a delivered notification, shall set the SDS disposition notification type IE as "DELIVERED";
2. if sending a read notification, shall set the SDS disposition notification type IE as "READ";
3. if sending a delivered and read notification, shall set the SDS disposition notification type IE as "DELIVERED AND READ";
4. if the SDS message could not be delivered to the user or application (e.g. due to lack of storage), shall set the SDS disposition notification type IE as "UNDELIVERED";
5. shall set the Date and time IE to the current time;
6. shall set the Conversation ID to the value of the Conversation ID that was received in the SDS message;
7. shall set the Message ID to the value of the Message ID that was received in the SDS message;
8. if the SDS message was destined for the user, shall not include an Application ID IE;
9. if the SDS message was destined for an application, shall include an Application ID IE set to the value of the Application ID that was included in the SDS message; and
10. shall set the Sender MCData user ID to its own MCData user ID as specified in subclause 15.2.15 of 3GPP TS 24.282 [8].

[TS 24.582, clause 6.1.2.5.3]

The MCData client shall generate MSRP SEND requests for SDS disposition notification according to IETF RFC 4975 [11].

When generating an MSRP SEND request for SDS disposition notification containing an SDS NOTIFICATION message, the MCData client

1. shall set To-Path header according to the MSRP URI(s) received in the answer SDP;
2. shall set the content type as Content-Type = "application/vnd.3gpp.mcdata-signalling"; and
3. shall set the body of the MSRP SEND request to the generated SDS NOTIFICATION message.

6.1.16.3 Test description

6.1.16.3.1 Pre-test conditions

Test configuration:

- Single cell configuration according to TS 37.579-1 [2] clause 5.2.2.2.1.

Preamble:

- The UE has performed procedure 'Initial registration' as described in TS 37.579-1 [2] clause 5.4.2.
- The UE has performed procedure 'MCX pre-established session establishment' as described in TS 37.579-1 [2] clause 5.3.3.
- UE States at the end of the preamble:
  - The UE is in RRC_IDLE state.
  - The client is registered for MCData.
  - A pre-established session is established.

6.1.16.3.2 Test procedure sequence

Table 6.1.16.3.2-1: Main Behaviour

St	Procedure	Message Sequence		TP	Verdict
		U - S	Message		
1	Check: Does the UE (MCData client) correctly perform procedure '**CT MCData Call Establishment**' as described in TS 37.579-1 [2] Table 5.3C.3.3-1? NOTE: The SS (MCData server) sends a SIP re-INVITE request within a pre-established Session to initiate a one-to-one SDS session using the media plane.	-	-	1,2	P
2	Check: Does the UE (MCData client) correctly perform procedure '**CT MSRP message transfer**' as described in TS 37.579-1 [2] Table 5.3C.5.3-1 **to receive an SDS message with disposition request "DELIVERY"**?	-	-	2	P
3	Check: Does the UE (MCData client) correctly perform procedure '**CO MSRP message transfer**' as described in TS 37.579-1 [2] Table 5.3C.4.3-1 **to send a disposition notification of "DELIVERED"**?	-	-	2	P
4	Check: Does the UE (MCData client) provide the contents of the Payload IE to the user? (NOTE 1)	-	-	2	P
5-9	Check: Does the UE (MCData client) correctly perform step 3 to 7 of procedure '**MCData CO call release keeping the pre-established session**' as described in TS 37.579-1 [2] Table 5.3C.13.3-1? NOTE: The SS (MCData server) sends a SIP re-INVITE request to release the MCData call while keeping the pre-established Session. (NOTE 2)	-	-	3	P
10	The procedure 'MCX communication release' as described in TS 37.579-1 [2] clause 5.4.14 is performed to release the RRC connection.	-	-	-	-
NOTE 1: This is expected to be done via a suitable implementation dependent MMI. NOTE 2: The procedure does not release the RRC connection.					

6.1.16.3.3 Specific message contents

Table 6.1.16.3.3-1: SIP INVITE from the SS (step 1, Table 6.1.16.3.2-1; step 2, TS 37.579-1 [2] Table 5.3C.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.5.2-1, condition MCDATA_SDS, re_INVITE				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Request-Line				
Request-URI	tsc_MCX_SessionID_B	session identity of the pre-established session	TS 24.282 [31] clause 9.2.5.2.2.2	
Message-body				
MIME body part		**SDP message**		
MIME-part-body	SDP message as described in Table 6.1.16.3.3-2			
MIME body part		**MCData-Info**		
MIME-part-body	MCData-Info as described in Table 6.1.16.3.3-3			

Table 6.1.16.3.3-2: SDP for SIP INVITE (Table 6.1.16.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.1.2-3, condition MCDATA_SDS, SDP_OFFER, MCD_1to1, SDS_SESSION, PRE_ESTABLISHED_SESSION

Table 6.1.16.3.3-3: MCData-Info (Table 6.1.16.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.2.2-3, condition MCD_1to1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
mcdata-info				
mcdata-Params				
request-type	"one-to-one-sds-session"		TS 24.282 [31] clause 9.2.5.2.2.2	
anyExt				
mcdata-communication-state	"establish-request"		TS 24.282 [31] clause 9.2.5.2.2.2	

Table 6.1.16.3.3-4: SIP 200 (OK) from the UE (step 1, Table 6.1.16.3.2-1; step 4, TS 37.579-1 [2] Table 5.3C.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.17.1.1-1, condition INVITE-RSP, MCDATA_SDS				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Content-Type				
value	"application/sdp"			
Message-body				
SDP message	As described in Table 6.1.16.3.3-5			

Table 6.1.16.3.3-5: SDP for SIP 200 (OK) (Table 6.1.16.3.3-4)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.1.1-3, condition MCDATA_SDS, SDP_ANSWER, SDS_SESSION, PRE_ESTABLISHED_SESSION

Table 6.1.16.3.3-6: MSRP SEND from the SS (step 2, Table 6.1.16.3.2-1; step 1, TS 37.579-1 [2] Table 5.3C.5.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.12.1.2-1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Content-Type				
media-type	"multipart/mixed"			
data	Message as specified in table 6.1.16.3.3-7			

Table 6.1.16.3.3-7: MIME Message (step 2, Table 6.1.16.3.2-1; step 1, TS 37.579-1 [2] Table 5.3C.5.3-1)

Derivation Path: RFC 2046 [38]				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
MIME body part		**MCData Data signalling message**		
MIME-part-headers				
Content-Type	"application/vnd.3gpp. mcdata-signalling"			
MIME-part-body	MCData Protected Payload Message containing SDS SIGNALLING PAYLOAD as described in table 6.1.16.3.3-8			
MIME body part		**MCData Data message**		
MIME-part-headers				
Content-Type	"application/vnd.3gpp. mcdata-payload"			
MIME-part-body	DATA PAYLOAD as described in Table 6.1.16.3.3-9			

Table 6.1.16.3.3-8: SDS SIGNALLING PAYLOAD (Table 6.1.16.3.3-6A)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.2-1, condition DELIVERED

Table 6.1.16.3.3-9: Data Payload (Table 6.1.16.3.3-6A)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.9.2-2

Table 6.1.16.3.3-10: MSRP SEND from the UE (step 3, Table 6.1.16.3.2-1; step 3, TS 37.579-1 [2] Table 5.3C.4.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.12.1.1-1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Content-Type				
media-type	"application/vnd.3gpp. mcdata-signalling"			
data	MCData Protected Payload Message containing SDS NOTIFICATION as specified in table 6.1.16.3.3-11			

Table 6.1.16.3.3-11: SDS NOTIFICATION (Table 6.1.16.3.3-10)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.3-1, condition DELIVERED

Table 6.1.16.3.3-12: SIP re-INVITE from the SS (step 5, Table 6.1.16.3.2-1; step 3, TS 37.579-1 [2] Table 5.3C.13.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.5.2-1, condition MCDATA_SDS, re_INVITE				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Request-Line				
Request-URI	tsc_MCX_SessionID_B	session identity of the pre-established session	TS 24.282 [31] clause 9.2.5.4.2.1	
Content-Type			RFC 5621 [58]	
media-type	"application/vnd.3gpp. mcdata-info+xml"		TS 24.282 [31] clause 9.2.5.4.2.1	
Message-body				
MCData-Info Message	MCData-Info message as described in Table 6.1.14.3.3-13			

Table 6.1.16.3.3-13: MCData-Info (Table 6.1.16.3.3-12)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.2.2-3				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
mcdata-info				
mcdata-Params				
mcdata-request-uri	not present			
mcdata-calling-user-id	not present			
anyExt				
mcdata-communication-state	"terminate request"		TS 24.282 [31] clause 9.2.5.4.2.2	

6.1.17 On-network / Short Data Service (SDS) / Standalone SDS Using Media Plane / Group Standalone SDS / Pre-established session / Client Originated (CO)

6.1.17.1 Test Purpose (TP)

(1)

```
with { UE (MCDATA Client) registered and authorised for MCDATA Service }
ensure that {
  when { the MCDATA User requests to send a group standalone SDS message using the media plane and
using the pre-established session }
    then { UE (MCDATA Client) sends a request to establish an MSRP connection via a SIP REFER
message and responds to the SIP re-INVITE message with a SIP 200 (OK) message and delivers the
notification to the MCDATA User about successful communication establishment and sends a blank MSRP
SEND message to bind the MSRP connection }
            }
```

(2)

```
with { UE (MCDATA Client) having sent a blank MSRP SEND message to bind the MSRP connection }
ensure that {
  when { UE (MCDATA Client) receives an MSRP 200 (OK) message in response to the blank MSRP SEND
message }
    then { UE (MCDATA Client) sends the group standalone SDS message via a MSRP SEND message with a
disposition of "DELIVERY" }
            }
```

(3)

```
with { UE (MCDATA Client) having sent a group standalone SDS message using the media plane }
ensure that {
  when { UE (MCDATA Client receives a MSRP 200 (OK) message in response to the last MSRP SEND
message indicating that the standalone SDS message has been successfully transferred }
    then { UE (MCDATA Client) sends a SIP REFER message to release the MCData session and keep the
pre-established session and responds to the SIP re-INVITE message with a SIP 200 (OK) message and
delivers the notification to the MCDATA User about successful termination }
            }
```

(4)

```
with { UE (MCDATA Client) having sent a group standalone SDS message using the media plane with a
disposition of "DELIVERY" }
ensure that {
  when { UE (MCDATA Client receives a disposition response via a SIP MESSAGE message from the SS
(MCDATA Server }
    then { UE (MCDATA Client) responds to the SIP MESSAGE message by sending a SIP 200 (OK) message
and delivers the notification to the MCDATA User }
            }
```

6.1.17.2 Conformance requirements

References: The conformance requirements covered in the current TC are specified in: TS 24.282, clauses 9.2.5.3.1.1, 9.2.3.2.1, 9.2.5.4.1.1, 12.2.1.2, TS 24.582 clauses 12.1, 6.1.1.2.1, 6.1.1.2.2, 6.1.1.2.3, 6.1.1.2.4. The following represents a copy/paste extraction of the requirements relevant to the test purpose; any references within the copy/paste text should be understood within the scope of the core spec they have been copied from. Unless otherwise stated, these are Rel-16 requirements.

[TS 24.282, clause 9.2.5.3.1.1]

Upon receiving a request from an MCData user to initiate group SDS session within the pre-established session, the MCData client shall generate a SIP REFER request outside a dialog as specified in IETF RFC 3515 [51] as updated by IETF RFC 6665 [36] and IETF RFC 7647 [52], and in accordance with the UE procedures specified in 3GPP TS 24.229 [5], with the clarifications given below.

The MCData client:

1) shall set the Request URI of the SIP REFER request to the session identity of the pre-established session;

2) shall set the Refer-To header field of the SIP REFER request as specified in IETF RFC 3515 [51] with a Content-ID ("cid") Uniform Resource Locator (URL) as specified in IETF RFC 2392 [33] that points to an application/resource-lists MIME body as specified in IETF RFC 5366 [18], and with the Content-ID header field set to this "cid" URL;

3) shall include in the application/resource-lists MIME body a single <entry> element containing a "uri" attribute set to the MCData group identity, extended with the following parameters in the headers portion of the SIP URI:

NOTE: Characters that are not formatted as ASCII characters are escaped in the following parameters in the headers portion of the SIP URI.

   a) an hname "body" parameter populated with:

      i) an application/sdp MIME body containing an SDP offer with media attributes specified in subclause 9.2.3.2.1, if a group standalone SDS message is requested;

      ii) an application/vnd.3gpp.mcdata-info MIME body with:

         A) if a group standalone SDS message is requested, the <request-type> element set to a value of "group-sds". If a group SDS session is requested, the <request-type> element set to a value of "group-sds-session";

         B) the <mcdata-request-uri> element set to the MCData group identity;

         C) the <mcdata-client-id> element set to the MCData client ID of the originating MCData client; and

D) if the MCData client is aware of active functional aliases and if an active functional alias is to be included in the SIP REFER request, the <functional-alias-URI> element set to the URI of the used functional alias;

4) shall include a P-Preferred-Service header field set to the ICSI value "urn:urn-7:3gpp-service.ims.icsi.mcdata.sds" (coded as specified in 3GPP TS 24.229 [5]), according to IETF RFC 6050 [7];

5) may include a P-Preferred-Identity header field in the SIP INVITE request containing a public user identity as specified in 3GPP TS 24.229 [5];

6) shall include the following according to IETF RFC 4488 [53]:

   a) the option tag "norefersub" in the Supported header field; and

   b) the value "false" in the Refer-Sub header field;

7) shall include a Target-Dialog header field as specified in IETF RFC 4538 [54] identifying the pre-established session;

8) shall include the g.3gpp.mcdata.sds media feature tag in the Contact header field of the SIP REFER request according to IETF RFC 3840 [16]; and

9) shall send the SIP REFER request according to 3GPP TS 24.229 [5].

On receiving a final SIP 2xx response to the SIP REFER request, the MCData client:

1) shall interact with the media plane as specified in 3GPP TS 24.582 [15].

On receiving a SIP re-INVITE request within the pre-established session targeted by the sent SIP REFER request, the MCData client:

1) if the <mcdata-communication-state> element in the application/vnd.3gpp.mcdata-info+xml MIME body of the SIP INVITE request is set to a value of "establish-success":

   i) shall notify MCData user about successful the MCData communication establishment;

2) if the <mcdata-communication-state> element in the application/vnd.3gpp.mcdata-info+xml MIME body of the SIP INVITE request is set to a value of "establish-fail":

   i) shall notify MCData user about the MCData communication establishment failure; and

3) shall interact with the media plane as specified in 3GPP TS 24.582 [15].

[TS 24.282, clause 9.2.3.2.1]

When composing an SDP offer according to 3GPP TS 24.229 [5], IETF RFC 4975 [17], IETF RFC 6135 [19] and IETF RFC 6714 [20] the MCData client:

1) shall include an "m=message" media-level section for the MCData media stream consisting of:

   a) the port number;

   b) a protocol field value of "TCP/MSRP", or "TCP/TLS/MSRP" for TLS;

   c) a format list field set to ‘*’;

   d) an "a=sendonly" attribute;

   e) an "a=path" attribute containing its own MSRP URI;

   f) set the content type as "a=accept-types:application/vnd.3gpp.mcdata-signalling application/vnd.3gpp.mcdata-payload"; and

   g) set the a=setup attribute as "actpass"; and

2) if end-to-end security is required for a one-to-one communication and the security context does not exist or if the existing security context has expired, shall include the MIKEY-SAKKE I_MESSAGE in an "a=key-mgmt" attribute as a "mikey" attribute value in the SDP offer as specified in IETF RFC 4567 [45].

[TS 24.282, clause 9.2.5.4.1.1]

Upon receiving a request from an MCData user to leave an MCData session within a pre-established session, the MCData client:

1) shall interact with the media plane as specified in 3GPP TS 24.582 [15];

2) shall generate an initial SIP REFER request outside a dialog in accordance with the procedures specified in 3GPP TS 24.229 [5], IETF RFC 4488 [53] and IETF RFC 3515 [51] as updated by IETF RFC 6665 [36] and IETF RFC 7647 [r7647];

3) shall set the Request-URI of the SIP REFER request to the public service identity identifying the pre-established session on the MCData server serving the MCData user;

4) shall include the Refer-Sub header field with value "false" according to rules and procedures of IETF RFC 4488 [53];

5) shall include the Supported header field with value "norefersub" according to rules and procedures of IETF RFC 4488 [53];

6) shall set the Refer-To header field of the SIP REFER request to the MCData session identity to leave;

7) shall include the "method" SIP URI parameter with the value "BYE" in the URI in the Refer-To header field;

8) shall include a Target-Dialog header field as specified in IETF RFC 4538 [54] identifying the pre-established session; and

9) shall send the SIP REFER request according to 3GPP TS 24.229 [5].

Upon receiving a SIP 2xx response to the SIP REFER request, the MCData client shall interact with media plane as specified in 3GPP TS 24.582 [15].

On receiving a SIP re-INVITE request within the pre-established session targeted by the sent SIP REFER request, the MCData client:

1) if the <mcdata-communication-state> element in the application/vnd.3gpp.mcdata-info+xml MIME body of the SIP INVITE request is set to a value of "terminated":

   i) shall notify MCData user about successful the MCData communication termination.

[TS 24.282, clause 12.2.1.2]

Upon receipt of a:

"SIP MESSAGE request for SDS disposition notification for terminating MCData client"; or

"SIP MESSAGE request for FD disposition notification for terminating MCData client";

the MCData client:

1) shall decode the contents of the application/vnd.3gpp.mcdata-signalling MIME body; and

2) shall deliver the notification to the user or application.

[TS 24.582, clause 12.1]

Upon establishing one-to-one or group SDS using media plane or one-to-one or group SDS session using pre-established call, the MCData client shall follow procedures as descried in subclause 6.1.

[TS 24.582, clause 6.1.1.2.1]

Upon receiving an indication to establish MSRP connection for standalone SDS using media plane as the originating client, the MCData client:

1. shall act as an MSRP client according to IETF RFC 6135 [12];
2. shall act according to IETF RFC 6135 [12], as:
   a. an "active" endpoint, if a=setup attribute in the received SDP answer is set to "passive"; and
   b. an "passive" endpoint, if a=setup attribute in the received SDP answer is set to "active";
3. shall establish the MSRP connection according to the MSRP connection parameters in the SDP answer received in the SIP 200 (OK) response according to IETF RFC 4975 [11]; and
4. if acting as an "active" endpoint, shall send an empty MSRP SEND request to bind the MSRP connection to the MSRP session from the perspective of the passive endpoint according to the rules and procedures of IETF RFC 4975 [11] and IETF RFC 6135 [12].

On receiving MSRP 200 (OK) response to the first MSRP SEND request, the MCData client:

1. shall generate a SDS SIGNALLING PAYLOAD as specified in subclause 6.1.1.2.2;
2. shall generate a SDS DATA PAYLOAD as specified in subclause 6.1.1.2.3;
3. shall include the SDS SIGNALLING PAYLOAD and SDS DATA PAYLOAD in an MSRP SEND request as specified in subclause 6.1.1.2.4; and
4. shall send the MSRP SEND request on the established MSRP connection.

If MSRP chunking is not used then on receipt of a 200 (OK) response, the MCData client shall terminate the SIP session as specified in 3GPP TS 24.282 [8].

If MSRP chunking is used, the MCData client:

1. shall send further MSRP SEND requests as necessary;
2. shall wait for a 200 (OK) response to each MSRP SEND request sent; and
3. on receipt of the last 200 (OK) response shall terminate the SIP session as specified in 3GPP TS 24.282 [8].

On receiving a non-200 MSRP response to the MSRP SEND request the MCData client shall handle the error as specified in IETF RFC 4975 [11]. To terminate the MSRP session, the MCData client:

1. if there are further MSRP chunks to send, shall abort transmission of these further MSRP chunks;
2. shall indicate to MCData user that the SDS message could not be sent; and
3. shall terminate the SIP session as specified in 3GPP TS 24.282 [8].

On receiving an indication to terminate the session from the signalling plane, the MCData client:

1. if there are further MSRP chunks to send, shall abort transmission of these further MSRP chunks and may indicate to MCData user that the SDS message could not be sent.

[TS 24.582, clause 6.1.1.2.2]

In order to generate an SDS signalling payload, the MCData client:

1. shall generate an SDS SIGNALLING PAYLOAD message as specified in 3GPP TS 24.282 [8]; and
2. shall include the SDS SIGNALLING PAYLOAD message in an application/vnd.3gpp.mcdata-signalling MIME body as specified in 3GPP TS 24.282 [8]; and

When generating a an SDS SIGNALLING PAYLOAD message, the MCData client:

1. shall generate a SDS SIGNALLING PAYLOAD message as defined in 3GPP TS 24.282 [8]. In the SDS SIGNALLING PAYLOAD message, the MCData client:
   a. may include and set the Disposition request type IE to:
      i. "DELIVERY", if only delivery disposition is requested;

ii. "READ", if only read disposition is requested; or

iii. "DELIVERY AND READ", if both delivery and read dispositions are requested;

b. shall set Date and time IE to current UTC time;

c. shall set Conversation ID IE to a universally unique message ID generated as per IETF RFC 4122 [10];

d. shall set Message ID IE to a universally unique message ID generated as per IETF RFC 4122 [10];

e. if indicated that the SDS message is in reply to another SDS message then, shall include the Reply ID IE set to the message identifier of the indicated SDS message;

f. if indicated that the target recipient of the SDS message is an application then, shall set Application Identifier IE to the application identifier; and

g) shall set the Sender MCData user ID to its own MCData user ID as specified in subclause 15.2.15 of 3GPP TS 24.282 [8].

[TS 24.582, clause 6.1.1.2.3]

In order to generate SDS data payload, the MCData client:

1. shall generate a DATA PAYLOAD message as specified in 3GPP TS 24.282 [8]; and

2. shall include the DATA PAYLOAD message in an application/vnd.3gpp.mcdata-payload MIME body as specified in 3GPP TS 24.282 [8].

When generating a DATA PAYLOAD message, the MCData client:

1. shall generate a SDS DATA PAYLOAD message as defined in 3GPP TS 24.282 [8]. In the SDS DATA PAYLOAD message, the MCData client:

   a. shall set Number of payloads IE to the total number of payloads being sent; and

   b. for each payload, shall include Payload IE. In the Payload IE:

      i. shall set Payload content type to "TEXT", or "BINARY", or "HYPERLINKS", or "LOCATION" according to the payload type; and

      ii. shall set Payload data IE to actual payload.

[TS 24.582, clause 6.1.1.2.4]

The MCData client shall take the procedures in subclause 6.4.1 into consideration when generating MSRP SEND messages.

The MCData client shall generate MSRP SEND for SDS message requests according to IETF RFC 4975 [11].

When generating an MSRP SEND for SDS message request containing an SDS SIGNALLING PAYLOAD message and an SDS DATA PAYLOAD message, the MCData client

1. shall set To-Path header according to the MSRP URI(s) received in the answer SDP;

2. shall include two MIME bodies in accordance with subclause 6.4.1 where:

   a. in the first body the Content-Type header field is set to "application/vnd.3gpp.mcdata-signalling" and the generated SDS SIGNALLING PAYLOAD message is included; and

   b. in the second body the Content-Type header field is set to "application/vnd.3gpp.mcdata-payload" and the generated SDS DATA PAYLOAD message is included.

When generating an MSRP SEND for SDS message request containing only an SDS DATA PAYLOAD message, the MCData client:

1. shall set To-Path header according to the MSRP URI(s) received in the answer SDP;

2. shall set the Content-Type as "application/vnd.3gpp.mcdata-payload"; and

3. shall set the body of the MSRP SEND request to the generated SDS DATA PAYLOAD message.

When generating an MSRP SEND for SDS message request containing only an SDS SIGNALLING PAYLOAD, the MCData client.

1. shall set To-Path header according to the MSRP URI(s) received in the answer SDP;
2. shall set the Content-Type as "application/vnd.3gpp.mcdata-signalling"; and
3. shall set the body of the MSRP SEND request to the generated SDS SIGNALLING PAYLOAD message.

6.1.17.3 Test description

6.1.17.3.1 Pre-test conditions

Test configuration:

- Single cell configuration according to TS 37.579-1 [2] clause 5.2.2.2.1.

Preamble:

- The UE has performed procedure 'Initial registration' as described in TS 37.579-1 [2] clause 5.4.2 with the following clarifications:
  - The <max-payload-size-sds-cplane-bytes> element of the MCData Service Configuration document shall be set to 0 to force the MCData client to send the data using the media plane.
- The UE has performed procedure 'MCX pre-established session establishment' as described in TS 37.579-1 [2] clause 5.3.3.
- UE States at the end of the preamble:
  - The UE is in RRC_IDLE state.
  - The client is registered for MCData.
  - A pre-established session is established.

6.1.17.3.2 Test procedure sequence

Table 6.1.17.3.2-1: Main Behaviour

St	Procedure	Message Sequence		TP	Verdict
		U - S	Message		
1	Make the UE (MCData client) send a group standalone SDS message using the pre-established session with disposition request "**DELIVERY**". (NOTE 1)	-	-	-	-
2	Check: Does the UE (MCData client) correctly perform procedure '**CO MCData call establishment using a pre-established session**' as described in TS 37.579-1 [2] Table 5.3C.12.3-1?	-	-	1	P
3	Check: Does the UE (MCData client) notify the user about successful MCData communication establishment? (NOTE 1)	-	-	1	P
4	Check: Does the UE (MCData client) correctly perform procedure 'CO MSRP message transfer' as described in TS 37.579-1 [2] Table 5.3C.4.3-1 to **send an SDS message with disposition request "DELIVERY"**?	-	-	2	P
5	Check: Does the UE (MCData client) correctly perform procedure '**MCData CO call release keeping the pre-established session**' as described in TS 37.579-1 [2] Table 5.3C.13.3-1? (NOTE 2)	-	-	3	P
6	Check: Does the UE (MCData client) provide a notification to the MCData user about successful MCData communication termination? (NOTE 1)	-	-	3	P
7	Check: Does the UE (MCData client) correctly perform procedure 'MCX SIP MESSAGE CT' as described in TS 37.579-1 [2] Table 5.3.33.3-1 to **receive the disposition notification** for the SDS message sent at step 7?	-	-	-	-
8	Check: Does the UE (MCData client) provide the disposition notification to the user? (NOTE 1)	-	-	4	P
NOTE 1: This is expected to be done via a suitable implementation dependent MMI. NOTE 2: The procedure does not release the RRC connection.					

6.1.17.3.3 Specific message contents

Table 6.1.17.3.3-1: SIP REFER from the UE (step 2, Table 6.1.17.3.2-1; step 2, TS 37.579-1 [2] Table 5.3C.12.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.12-1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part		**Resource list**		
MIME-part-body	Resource-lists as described in Table 6.1.17.3.3-2			

Table 6.1.17.3.3-2: Resource-lists in SIP REFER (Table 6.1.17.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.3.1-3, condition PRE-ESTABLISH, MCD_grp with the uri attribute of the entry extended with the SIP URI header fields as specified in Table 6.1.17.3.3-3

Table 6.1.17.3.3-3: SIP header fields extending the uri attribute of the resource-lists' single entry (Table 6.1.17.3.3-2)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.12-2, condition GROUP-CALL				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
body				
MIME body part		**SDP Message**		
MIME-part-headers				
Content-Type	“application/sdp”			
MIME-part-body	SDP Message as described in Table 6.1.17.3.3-4			
MIME body part		**MCData-Info**		
MIME-part-body	MCdata-Info as described in Table 6.1.17.3.3-5			

Table 6.1.17.3.3-4: SDP in SIP header fields (Table 6.1.17.3.3-3)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.1.1-3, condition PRE_ESTABLISHED_SESSION, SDP_OFFER, MCDATA_SDS

Table 6.1.17.3.3-5: MCData-Info in SIP header fields (Table 6.1.17.3.3-3)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.2.1-3, condition MCD_grp

Table 6.1.17.3.3-6: MSRP SEND from the UE (step 4, Table 6.1.17.3.2-1; step 1, TS 37.579-1 [2] Table 5.3C.4.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.12.1.1-1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Content-Type				
media-type	"multipart/mixed"			
data	Message or chunk of message as specified in table 6.1.17.3.3-7			

Table 6.1.17.3.3-7: MIME Message (step 4, Table 6.1.17.3.2-1; step 3, TS 37.579-1 [2] Table 5.3C.4.3-1)

Derivation Path: RFC 2046 [38]				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
MIME body part		**MCData Data signalling message**		
MIME-part-headers				
Content-Type	"application/vnd.3gpp.mcdata-signalling"			
MIME-part-body	MCData Protected Payload Message containing SDS SIGNALLING PAYLOAD as described in table 6.1.17.3.3-8			
MIME body part		**MCData Data message**		
MIME-part-headers				
Content-Type	"application/vnd.3gpp.mcdata-payload"			
MIME-part-body	DATA PAYLOAD as described in Table 6.1.17.3.3-9			

Table 6.1.17.3.3-8: SDS SIGNALLING PAYLOAD (Table 6.1.17.3.3-7)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.1-1, condition DELIVERED

Table 6.1.17.3.3-9: Data Payload (Table 6.1.17.3.3-7)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.9.2-1

Table 6.1.17.3.3-10: SIP MESSAGE from the SS (step 7, Table 6.1.17.3.2-1; step 2, TS 37.579-1 [2] Table 5.3.33.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.7.2-1, condition MCDATA_SDS, MCDATA_SIGNALLING				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part		**MCData-Info**		
MIME-part-body	MCData-Info as described in Table 6.1.17.3.3-11			
MIME body part		**MCData Data signalling message**		
MIME-part-body	MCData Protected Payload Message containing SDS NOTIFICATION as described in Table 6.1.17.3.3-12			

Table 6.1.17.3.3-11: MCData Info (Table 6.1.17.3.3-10)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.2.2-3				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
mcdata-info				
mcdata-Params				
mcdata-calling-group-id	Encrypted <mcdata-calling-group-id> with mcdataURI set to px_MCData_Group_A_ID	Encrypted according to TS 37.579-1 [2] Table 5.5.3.2.2-3A		

Table 6.1.17.3.3-12: SDS NOTIFICATION (Table 6.1.17.3.3-10)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.4-1, condition DELIVERED

6.1.18 On-network / Short Data Service (SDS) / Standalone SDS Using Media Plane / Group Standalone SDS / Pre-established session / Client Terminated (CT)

6.1.18.1 Test Purpose (TP)

(1)

```
with { UE (MCDATA Client) registered and authorised for MCDATA Service }
ensure that {
  when { the MCDATA User receives a SIP re-INVITE message to initiate a group standalone SDS message
using the media plane and using a pre-established session }
    then { UE (MCDATA Client) responds by sending a SIP 200 (OK) message }
            }
```

(2)

```
with { UE (MCDATA Client) having responded to the SIP re-INVITE message that initiated a standalone
group SDS message using the media plane and using a pre-established session }
ensure that {
  when { UE (MCDATA Client) receives an MSRP SEND message }
    then { UE (MCDATA Client) responds with an MSRP 200 (OK) message and if the MSRP SEND message is
not blank, renders the contents of the Payload IE to the MCDATA User and sends a SIP MESSAGE message
with a disposition notification of "DELIVERED" }
            }
```

(3)

```
with { UE (MCDATA Client) having responded to the MSRP SEND message from the SS (MCDATA server) }
ensure that {
  when { UE (MCDATA Client) receives a SIP re-INVITE message to release communications }
    then { UE (MCDATA Client) responds with a SIP 200 (OK) message }
            }
```

6.1.18.2 Conformance requirements

References: The conformance requirements covered in the current TC are specified in: TS 24.282, clauses 9.2.5.3.1.2, 9.2.3.2.4, 9.2.5.4.1.2, 9.2.1.3, 12.2.1.1, 6.2.4.1, 6.2.3.1, TS 24.582 clauses 6.1.1.3.1, 6.1.1.3.2. The following represents a copy/paste extraction of the requirements relevant to the test purpose; any references within the copy/paste text should be understood within the scope of the core spec they have been copied from. Unless otherwise stated, these are Rel-16 requirements.

[TS 24.282, clause 9.2.5.3.1.2]

Upon receiving a SIP re-INVITE request within a pre-established Session without an associated MCData session the MCData client:

1) if the <mcdata-communication-state> element in the application/vnd.3gpp.mcdata-info+xml MIME body of the SIP INVITE request is set to a value of "establish-request":

   i) if the <request-type> element in the application/vnd.3gpp.mcdata-info+xml MIME body of the SIP INVITE request is set to a value of "group-sds", shall follow the procedures in subclause 9.2.3.2.4;

   ii) if the <request-type> element in the application/vnd.3gpp.mcdata-info+xml MIME body of the SIP INVITE request is set to a value of "group-sds-session", shall follow the procedures in subclause 9.2.4.2.4;

[TS 24.282, clause 9.2.3.2.4]

Upon receipt of an "initial SIP INVITE request for standalone SDS over media plane for terminating MCData client" request, the MCData client shall follow the procedures for termination of multimedia sessions in the IM CN subsystem as specified in 3GPP TS 24.229 [5] with the clarifications below.

The MCData client:

1) may reject the SIP INVITE request if either of the following conditions are met:

   a) MCData client does not have enough resources to handle the call; or

   b) any other reason outside the scope of this specification;

   and skip the rest of the steps after step 2;

2) if the SIP INVITE request is rejected in step 1), shall respond toward participating MCData function either with appropriate reject code as specified in 3GPP TS 24.229 [5] and warning texts as specified in subclause 4.9 or with SIP 480 (Temporarily unavailable) response not including warning texts if the user is authorised to restrict the reason for failure and skip the rest of the steps of this subclause;

3) if the SDP offer of the SIP INVITE request contains an "a=key-mgmt" attribute field with a "mikey" attribute value containing a MIKEY-SAKKE I_MESSAGE:

   a) shall extract the MCData ID of the originating MCData user from the initiator field (IDRi) of the I_MESSAGE as described in 3GPP TS 33.180 [26];

   b) shall convert the MCData ID to a UID as described in 3GPP TS 33.180 [26];

   c) shall use the UID to validate the signature of the MIKEY-SAKKE I_MESSAGE as described in 3GPP TS 33.180 [26];

   d) if authentication verification of the MIKEY-SAKKE I_MESSAGE fails, shall reject the SIP INVITE request with a SIP 488 (Not Acceptable Here) response as specified in IETF RFC 4567 [45], and include warning text set to "136 authentication of the MIKEY-SAKKE I_MESSAGE failed" in a Warning header field as specified in subclause 4.9 and not continue with rest of the steps in this subclause; and

   e) if the signature of the MIKEY-SAKKE I_MESSAGE was successfully validated:

      i) shall extract and decrypt the encapsulated PCK using the terminating user's (KMS provisioned) UID key as described in 3GPP TS 33.180 [26]; and

      ii) shall extract the PCK-ID, from the payload as specified in 3GPP TS 33.180 [26];

NOTE: With the PCK successfully shared between the originating MCData client and the terminating MCData client, both clients are able to create an end-to-end secure session.

3) may display to the MCData user the MCData ID of the inviting MCData user and the type of SDS request;

4) shall accept the SIP INVITE request and generate a SIP 200 (OK) response according to rules and procedures of 3GPP TS 24.229 [5];

5) shall include the option tag "timer" in a Require header field of the SIP 200 (OK) response;

6) shall include the Session-Expires header field in the SIP 200 (OK) response and start the SIP session timer according to IETF RFC 4028 [38]. The "refresher" parameter in the Session-Expires header field shall be set to "uas";

7) shall include the g.3gpp.mcdata.sds media feature tag in the Contact header field of the SIP 200 (OK) response;

8) shall include the g.3gpp.icsi-ref media feature tag containing the value of "urn:urn-7:3gpp-service.ims.icsi.mcdata.sds" in the Contact header field of the SIP 200 (OK) response;

9) shall include an SDP answer in the SIP 200 (OK) response to the SDP offer in the incoming SIP INVITE request according to 3GPP TS 24.229 [5] with the clarifications given in subclause 9.2.3.2.2; and

10) shall send the SIP 200 (OK) response towards the MCData server according to rules and procedures of 3GPP TS 24.229 [5].

On receipt of an SIP ACK message to the sent SIP 200 (OK) message, the MCData client shall:

1) shall interact with the media plane as specified in 3GPP TS 24.582 [15] subclause 6.1.1.3.

[TS 24.282 clause 9.2.5.4.1.2]

Upon receiving a SIP re-INVITE request within a pre-established Session without an associated MCData session, the MCData client:

1) if the <mcdata-communication-state> element in the application/vnd.3gpp.mcdata-info+xml MIME body of the SIP INVITE request is set to a value of "terminate-request":

   i) shall send SIP 200 (OK) response towards MCData server according to 3GPP TS 24.229 [5]; and

   ii) shall release all media plane resources corresponding to the MCData communication being released.

[TS 24.282, clause 12.2.1.1]

The MCData client shall follow the procedures in this subclause to:

- indicate to an MCData client that an SDS message was delivered, read or delivered and read when the originating client requested a delivery, read or delivery and read report;

- indicate to the participating MCData function serving the MCData user that an SDS message was undelivered. The participating MCData function can store the message for later re-delivery;

- indicate to an MCData client that a request for FD was accepted, deferred or rejected; or

- indicate to an MCData client that a file download has been completed;

Before sending a disposition notification the MCData client needs to determine:

- the group identity related to an SDS or FD message request received as part of a group communication. The MCData client determines the group identity from the contents of the <mcdata-calling-group-id> element contained in the application/vnd.3gpp.mcdata-info+xml MIME body of the incoming SDS or FD message request; and

- the MCData user targeted for the disposition notification. The MCData client determines the targeted MCData user from the contents of the <mcdata-calling-user-id> element contained in the application/vnd.3gpp.mcdata-info+xml MIME body of the incoming SDS or FD message request.

The MCData client shall generate a SIP MESSAGE request in accordance with 3GPP TS 24.229 [5] and IETF RFC 3428 [6] with the clarifications given below.

The MCData client:

1) shall build the SIP MESSAGE request as specified in subclause 6.2.4.1;

2) shall follow the rules specified in subclause 6.4 for the handling of MIME bodies in a SIP message when processing the remaining steps in this subclause;

3) shall insert in the SIP MESSAGE request an application/resource-lists+xml MIME body containing the MCData ID of the targeted MCData user, according to rules and procedures of IETF RFC 5366 [18];

4) void;

5) if sending a disposition notification in response to an MCData group data request, shall include an <mcdata-calling-group-id> element set to the MCData group identity in the application/vnd.3gpp.mcdata-info+xml MIME body;

6) if requiring to send an SDS notification, shall generate an SDS NOTIFICATION message and include it in the SIP MESSAGE request as specified in subclause 6.2.3.1;

7) if requiring to send an FD notification, shall generate an FD NOTIFICATION message and include it in the SIP MESSAGE request as specified in subclause 6.2.3.2; and

8) shall send the SIP MESSAGE request according to rules and procedures of 3GPP TS 24.229 [5].

[TS 24.282, clause 6.2.4.1]

This subclause is referenced from other procedures.

In a SIP MESSAGE request, the MCData client:

1) when sending SDS messages or SDS disposition notifications:

   a) shall include an Accept-Contact header field containing the g.3gpp.mcdata.sds media feature tag along with the "require" and "explicit" header field parameters according to IETF RFC 3841 [8];

   b) shall include an Accept-Contact header field with the media feature tag g.3gpp.icsi-ref containing the value of "urn:urn-7:3gpp-service.ims.icsi.mcdata.sds" along with the "require" and "explicit" header field parameters according to IETF RFC 3841 [8]; and

   c) shall include the ICSI value "urn:urn-7:3gpp-service.ims.icsi.mcdata.sds" (coded as specified in 3GPP TS 24.229 [5]), in a P-Preferred-Service header field according to IETF RFC 6050 [7] in the SIP MESSAGE request;

2) when sending FD messages, FD disposition notifications or FD media storage function discovery messages:

   a) shall include an Accept-Contact header field containing the g.3gpp.mcdata.fd media feature tag along with the "require" and "explicit" header field parameters according to IETF RFC 3841 [8];

   b) shall include an Accept-Contact header field with the media feature tag g.3gpp.icsi-ref containing the value of "urn:urn-7:3gpp-service.ims.icsi.mcdata.fd" along with the "require" and "explicit" header field parameters according to IETF RFC 3841 [8]; and

   c) shall include the ICSI value "urn:urn-7:3gpp-service.ims.icsi.mcdata.fd" (coded as specified in 3GPP TS 24.229 [5]), in a P-Preferred-Service header field according to IETF RFC 6050 [7] in the SIP MESSAGE request;

3) may include a P-Preferred-Identity header field in the SIP MESSAGE request containing a public user identity as specified in 3GPP TS 24.229 [5]; and

4) shall set the Request-URI to the public service identity identifying the participating MCData function serving the MCData user.

[TS 24.282, clause 6.2.3.1]

In order to generate an SDS notification, the MCData client:

1) shall generate an SDS NOTIFICATION message as specified in subclause 15.1.5; and

2) shall include in the SIP request, the SDS NOTIFICATION message in an application/vnd.3gpp.mcdata-signalling MIME body as specified in subclause E.1.

When generating an SDS NOTIFICATION message as specified in subclause 15.1.5, the MCData client:

1) if sending a delivered notification, shall set the SDS disposition notification type IE as "DELIVERED" as specified in subclause 15.2.5;

2) if sending a read notification, shall set the SDS disposition notification type IE as "READ" as specified in subclause 15.2.5;

3) if sending a delivered and read notification, shall set the SDS disposition notification type IE as "DELIVERED AND READ" as specified in subclause 15.2.5;

4) if the SDS message could not be delivered to the user or application (e.g. due to lack of storage), shall set the SDS disposition notification type IE as "UNDELIVERED" as specified in subclause 15.2.5;

5) shall set the Date and time IE to the current time to as specified in subclause 15.2.8;

6) shall set the Conversation ID to the value of the Conversation ID that was received in the SDS message as specified in subclause 15.2.9;

7) shall set the Message ID to the value of the Message ID that was received in the SDS message as specified in subclause 15.2.10;

8) if the SDS message was destined for the user, shall not include an Application ID IE (as specified in subclause 15.2.7) and shall not include an Extended application ID IE (as specified in subclause 15.2.24); and

9) if the SDS message was destined for an application, shall include:

   a) an Application ID IE set to the value of the Application ID that was included in the SDS message as specified in subclause 15.2.3; or

   b) an Extended application ID IE set to the value of the Extended application ID that was included in the SDS message as specified in subclause 15.2.24.

[TS 24.582, clause 6.1.1.3.1]

Upon receiving an indication to establish MSRP connection for standalone SDS using media plane as the terminating client, the MCData client:

1. shall act as an MSRP client according to IETF RFC 6135 [12];

2. shall act either as an active endpoint or as an passive endpoint to open the transport connection, according to IETF RFC 6135 [12];

3. shall establish the MSRP connection according to the MSRP connection parameters in the SDP offer received in the SIP INVITE request according to IETF RFC 4975 [11];

4. if acting as an "active" endpoint, shall send an empty MSRP SEND request to bind the MSRP connection to the MSRP session from the perspective of the passive endpoint according to the rules and procedures of IETF RFC 4975 [11] and IETF RFC 6135 [12];

Once the MSRP connection is established, the MCData client:

1. on receipt of an MSRP request in an MSRP session, shall follow the rules and procedures defined in IETF RFC 4975 [11] and in IETF RFC 6714 [13];

2. If an MSRP SEND request indicates the use of chunking, shall wait until all further MSRP SEND requests for the remaining chunks have been received and shall reassemble the entire set of MSRP requests into the MCData standalone message before delivering the content to the application; and

3. shall handle the received content as described in subclause 6.1.1.3.2.

[TS 24.582, clause 6.1.1.3.2]

The MCData client:

1. shall decode the contents of the application/vnd.3gpp.mcdata-signalling MIME body;

2. shall decode the contents of the application/vnd.3gpp.mcdata-payload MIME body;

3. if the SDS SIGNALLING PAYLOAD message contains a new Conversation ID, shall instantiate a new conversation with the Message ID in the SDS SIGNALLING PAYLOAD identifying the first message in the conversation thread;

4. if the SDS SIGNALLING PAYLOAD message contains an existing Conversation ID and:

a. if the SDS SIGNALLING PAYLOAD message does not contain an InReplyTo Message ID, shall use the Message ID in the SDS SIGNALLING PAYLOAD to identify a new message in the existing conversation thread; and

b. if the SDS SIGNALLING PAYLOAD message contains an InReplyTo Message ID, shall associate the message to an existing message in the conversation thread as identified by the InReplyTo Message ID in the SDS SIGNALLING PAYLOAD and use the Message ID in the SDS SIGNALLING PAYLOAD to identify the new message;

5. shall identify the number of Payload IEs in the DATA PAYLOAD message from the Number of Payloads IE in the DATA PAYLOAD message;

6. if the SDS SIGNALLING PAYLOAD message does not contain an Application identifier IE:

   a. shall determine that the payload contained in the DATA PAYLOAD message is for user consumption;

   b. may notify the MCData user; and

   c. shall render the contents of the Payload IE(s) to the MCData user;

7. if the SDS SIGNALLING PAYLOAD message contains an Application identifier IE:

   a. shall determine that the payload contained in the DATA PAYLOAD message is not for user consumption;

   b. shall not notify the MCData user;

   c. if the Application identifier value is unknown, shall discard the SDS message; and

   d. if the Application identifier value is known, shall deliver the contents of the Payload IE(s) to the identified application; and

8. if SDS Disposition request type IE is present in the SDS SIGNALLING PAYLOAD message received in subclause 6.1.1.3.1 then, shall send a disposition notification as described in 3GPP TS 24.282 [8] subclause 9.2.1.3.

6.1.18.3 Test description

6.1.18.3.1 Pre-test conditions

Test configuration:

- Single cell configuration according to TS 37.579-1 [2] clause 5.2.2.2.1.

Preamble:

- The UE has performed procedure 'Initial registration' as described in TS 37.579-1 [2] clause 5.4.2 with the following clarifications:
  - The <max-payload-size-sds-cplane-bytes> element of the MCData Service Configuration document shall be set to 0 to force the MCData client to send the data using the media plane.
- The UE has performed procedure 'MCX pre-established session establishment' as described in TS 37.579-1 [2] clause 5.3.3.
- UE States at the end of the preamble:
  - The UE is in RRC_IDLE state.
  - The client is registered for MCData.
  - A pre-established session is established.

6.1.18.3.2 Test procedure sequence

Table 6.1.18.3.2-1: Main Behaviour

St	Procedure	Message Sequence		TP	Verdict
		U - S	Message		
1	Check: Does the UE (MCData client) correctly perform procedure '**CT MCData Call Establishment**' as described in TS 37.579-1 [2] Table 5.3C.3.3-1? NOTE: The SS (MCData server) sends a SIP re-INVITE request within a pre-established Session to initiate a group standalone SDS using the media plane.	-	-	1,2	P
2	Check: Does the UE (MCData client) correctly perform procedure 'CT MSRP message transfer' as described in TS 37.579-1 [2] Table 5.3C.5.3-1 to **receive an SDS message with disposition request "DELIVERY"**?	-	-	2	P
3-7	Check: Does the UE (MCData client) correctly perform step 3 to 7 of procedure '**MCData CO call release keeping the pre-established session**' as described in TS 37.579-1 [2] Table 5.3C.13.3-1? NOTE: The SS (MCData server) sends a SIP re-INVITE request to release the MCData call while keeping the pre-established Session. (NOTE 2)	-	-	3	P
8	Check: Does the UE (MCData client) correctly perform procedure '**CO SDS or FD message transfer** using signalling plane' as described in TS 37.579-1 [2] Table 5.3C.1.3-1 to **send a disposition notification of "DELIVERED"**?	-	-	2	P
9	Check: Does the UE (MCData client) provide the contents of the Payload IE to the user? (NOTE 1)	-	-	2	P
NOTE 1: This is expected to be done via a suitable implementation dependent MMI. NOTE 2: The procedure does not release the RRC connection.					

6.1.18.3.3 Specific message contents

Table 6.1.18.3.3-1: SIP INVITE from the SS (step 1, Table 6.1.18.3.2-1; step 2, TS 37.579-1 [2] Table 5.3C.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.5.2-1, condition MCDATA_SDS, re_INVITE				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Request-Line				
Request-URI	tsc_MCX_SessionID_B	session identity of the pre-established session	TS 24.282 [31] clause 9.2.5.2.2.2	
Message-body				
MIME body part		**SDP message**		
MIME-part-body	SDP message as described in Table 6.1.18.3.3-2			
MIME body part		**MCData-Info**		
MIME-part-body	MCData-Info as described in Table 6.1.18.3.3-3			

Table 6.1.18.3.3-2: SDP for SIP INVITE (Table 6.1.18.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.1.2-3, condition MCDATA_SDS, SDP_OFFER, PRE_ESTABLISHED_SESSION

Table 6.1.18.3.3-3: MCData-Info (Table 6.1.18.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.2.2-3, condition MCD_grp				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
mcdata-info				
mcdata-Params				
anyExt				
mcdata-communication-state	"establish-request"		TS 24.282 [31] clause 9.2.5.2.2.2	

Table 6.1.18.3.3-4: SIP 200 (OK) from the UE (step 1, Table 6.1.18.3.2-1; step 4, TS 37.579-1 [2] Table 5.3C.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.17.1.1-1, condition INVITE-RSP, MCDATA_SDS				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Content-Type				
value	"application/sdp"			
Message-body				
SDP message	As described in Table 6.1.18.3.3-5			

Table 6.1.18.3.3-5: SDP for SIP 200 (OK) (Table 6.1.18.3.3-4)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.1.1-3, condition MCDATA_SDS, SDP_ANSWER, PRE_ESTABLISHED_SESSION

Table 6.1.18.3.3-6: MSRP SEND from the SS (step 2, Table 6.1.18.3.2-1; step 1, TS 37.579-1 [2] Table 5.3C.5.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.12.1.2-1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Content-Type				
media-type	"multipart/mixed"			
data	Message as specified in table 6.1.18.3.3-7			

Table 6.1.18.3.3-7: MIME Message (Table 6.1.18.3.2-1; step 1, TS 37.579-1 [2] Table 5.3C.5.3-1)

Derivation Path: RFC 2046 [38]				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
MIME body part		**MCData Data signalling message**		
MIME-part-headers				
Content-Type	"application/vnd.3gpp. mcdata-signalling"			
MIME-part-body	MCData Protected Payload Message containing SDS SIGNALLING PAYLOAD as described in table 6.1.18.3.3-8			
MIME body part		**MCData Data message**		
MIME-part-headers				
Content-Type	"application/vnd.3gpp. mcdata-payload"			
MIME-part-body	DATA PAYLOAD as described in Table 6.1.18.3.3-9			

Table 6.1.18.3.3-8: SDS SIGNALLING PAYLOAD (Table 6.1.18.3.3-7)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.2-1, condition DELIVERED

Table 6.1.18.3.3-9: Data Payload (Table 6.1.18.3.3-7)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.9.2-2

Table 6.1.18.3.3-10: SIP re-INVITE from the SS (step 3, Table 6.1.18.3.2-1; step 3, TS 37.579-1 [2] Table 5.3C.13.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.5.2-1, condition MCDATA_SDS, re_INVITE				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Request-Line				
Request-URI	tsc_MCX_SessionID_B	session identity of the pre-established session	TS 24.282 [31] clause 9.2.5.4.2.1	
Message-body				
MIME body part	not present	**SDP message**		
MIME body part		**MCData Info**		
MIME-part-body	MCData-Info message as described in Table 6.1.18.3.3-11			

Table 6.1.18.3.3-11: MCData-Info (Table 6.1.18.3.3-10)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.2.2-3				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
mcdata-info				
mcdata-Params				
mcdata-request-uri	not present			
mcdata-calling-user-id	not present			
anyExt				
mcdata-communication-state	"terminate request"		TS 24.282 [31] clause 9.2.5.4.2.2	

Table 6.1.18.3.3-12: SIP MESSAGE from the UE (step 8, Table 6.1.18.3.2-1; step 2, TS 37.579-1 [2] Table 5.3C.1.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.7.1-1, condition MCDATA_SDS, RESOURCE_LISTS, MCDATA_SIGNALLING				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part		**MCData-Info**		
MIME-part-body	MCData-Info as described in Table 6.1.18.3.3-13			
MIME body part		**MCData Data signalling message**		
MIME-part-body	MCData Protected Payload Message containing SDS NOTIFICATION as described in Table 6.1.18.3.3-14			

Table 6.1.18.3.3-13: MCData-Info (Table 6.1.18.3.3-12)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.2.1-3				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
mcdata-info				
mcdata-Params				
mcdata-calling-group-id	Encrypted <mcdata-request-uri> with mcdataURI set to px_MCData_Group_A_ID	Encrypted according to TS 37.579-1 [2] Table 5.5.3.2.1-3A	TS 24.282 [31] clause 12.2.1.1	

Table 6.1.18.3.3-14: SDS NOTIFICATION (Table 6.1.18.3.3-12)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.3-1, condition DELIVERED

6.1.19 On-network / Short Data Service (SDS) / SDS Session / Group SDS Session / Pre-established session / Client Originated (CO)

6.1.19.1 Test Purpose (TP)

(1)

```
with { UE (MCDATA Client) registered and authorised for MCDATA Service }
ensure that {
  when { the MCDATA User requests to initiate a group SDS session using the media plane and using
the pre-established session }
```

```
    then { UE (MCDATA Client) sends a request to establish a group SDS session and a MSRP connection
via a SIP REFER message and responds to the SIP re-INVITE message with a SIP 200 (OK) message and
delivers the notification to the MCDATA User about successful communication establishment and sends
a blank MSRP SEND message to bind the MSRP connection }
            }
```

(2)

```
with { UE (MCDATA Client) having sent a blank MSRP SEND message to bind the MSRP connection }
ensure that {
  when { UE (MCDATA Client) receives an MSRP 200 (OK) message in response to the blank MSRP SEND
message }
    then { UE (MCDATA Client) sends the group session SDS message via a MSRP SEND message with a
disposition of "DELIVERY" }
            }
```

(3)

```
with { UE (MCDATA Client) having sent a group session SDS message using the media plane with a
disposition of "DELIVERY" }
ensure that {
  when { UE (MCDATA Client) receives a disposition response via a MSRP SEND message }
    then { UE (MCDATA Client) responds to the MSRP SEND message by sending a MSRP 200 (OK) message
and delivers the notification to the MCDATA User }
            }
```

(4)

```
with { UE (MCDATA Client) having established a group SDS session using the pre-established session }
ensure that {
  when { the MCDATA User requests to release the group SDS session while keeping the pre-established
session }
    then { UE (MCDATA Client) sends a SIP REFER message to release the MCData session and keep the
pre-established session and responds to the SIP re-INVITE message with a SIP 200 (OK) message and
delivers the notification to the MCDATA User about successful termination }
            }
```

6.1.19.2 Conformance requirements

References: The conformance requirements covered in the current TC are specified in: TS 24.282, clauses 9.2.5.3.1.1, 9.2.3.2.1, 9.2.5.4.1.1, TS 24.582 clauses 12.1, 6.1.2.2.1, 6.1.2.6. The following represents a copy/paste extraction of the requirements relevant to the test purpose; any references within the copy/paste text should be understood within the scope of the core spec they have been copied from. Unless otherwise stated, these are Rel-16 requirements.

[TS 24.282, clause 9.2.5.3.1.1]

Upon receiving a request from an MCData user to initiate group SDS session within the pre-established session, the MCData client shall generate a SIP REFER request outside a dialog as specified in IETF RFC 3515 [51] as updated by IETF RFC 6665 [36] and IETF RFC 7647 [52], and in accordance with the UE procedures specified in 3GPP TS 24.229 [5], with the clarifications given below.

The MCData client:

1) shall set the Request URI of the SIP REFER request to the session identity of the pre-established session;

2) shall set the Refer-To header field of the SIP REFER request as specified in IETF RFC 3515 [51] with a Content-ID ("cid") Uniform Resource Locator (URL) as specified in IETF RFC 2392 [33] that points to an application/resource-lists MIME body as specified in IETF RFC 5366 [18], and with the Content-ID header field set to this "cid" URL;

3) shall include in the application/resource-lists MIME body a single <entry> element containing a "uri" attribute set to the MCData group identity, extended with the following parameters in the headers portion of the SIP URI:

NOTE: Characters that are not formatted as ASCII characters are escaped in the following parameters in the headers portion of the SIP URI.

   a) an hname "body" parameter populated with:

i) an application/sdp MIME body containing an SDP offer with media attributes specified in subclause 9.2.3.2.1, if if a group standalone SDS message is requested;

ii) an application/vnd.3gpp.mcdata-info MIME body with:

A) if a group standalone SDS message is requested, the <request-type> element set to a value of "group-sds". If a group SDS session is requested, the <request-type> element set to a value of "group-sds-session";

B) the <mcdata-request-uri> element set to the MCData group identity;

C) the <mcdata-client-id> element set to the MCData client ID of the originating MCData client; and

D) if the MCData client is aware of active functional aliases and if an active functional alias is to be included in the SIP REFER request, the <functional-alias-URI> element set to the URI of the used functional alias;

4) shall include a P-Preferred-Service header field set to the ICSI value "urn:urn-7:3gpp-service.ims.icsi.mcdata.sds" (coded as specified in 3GPP TS 24.229 [5]), according to IETF RFC 6050 [7];

5) may include a P-Preferred-Identity header field in the SIP INVITE request containing a public user identity as specified in 3GPP TS 24.229 [5];

6) shall include the following according to IETF RFC 4488 [53]:

a) the option tag "norefersub" in the Supported header field; and

b) the value "false" in the Refer-Sub header field;

7) shall include a Target-Dialog header field as specified in IETF RFC 4538 [54] identifying the pre-established session;

8) shall include the g.3gpp.mcdata.sds media feature tag in the Contact header field of the SIP REFER request according to IETF RFC 3840 [16]; and

9) shall send the SIP REFER request according to 3GPP TS 24.229 [5].

On receiving a final SIP 2xx response to the SIP REFER request, the MCData client:

1) shall interact with the media plane as specified in 3GPP TS 24.582 [15].

On receiving a SIP re-INVITE request within the pre-established session targeted by the sent SIP REFER request, the MCData client:

1) if the <mcdata-communication-state> element in the application/vnd.3gpp.mcdata-info+xml MIME body of the SIP INVITE request is set to a value of "establish-success":

i) shall notify MCData user about successful the MCData communication establishment;

2) if the <mcdata-communication-state> element in the application/vnd.3gpp.mcdata-info+xml MIME body of the SIP INVITE request is set to a value of "establish-fail":

i) shall notify MCData user about the MCData communication establishment failure; and

3) shall interact with the media plane as specified in 3GPP TS 24.582 [15].

[TS 24.282, clause 9.2.3.2.1]

When composing an SDP offer according to 3GPP TS 24.229 [5], IETF RFC 4975 [17], IETF RFC 6135 [19] and IETF RFC 6714 [20] the MCData client:

1) shall include an "m=message" media-level section for the MCData media stream consisting of:

a) the port number;

b) a protocol field value of "TCP/MSRP", or "TCP/TLS/MSRP" for TLS;

c) a format list field set to '*';

d) an "a=sendonly" attribute;

e) an "a=path" attribute containing its own MSRP URI;

f) set the content type as "a=accept-types:application/vnd.3gpp.mcdata-signalling application/vnd.3gpp.mcdata-payload"; and

g) set the a=setup attribute as "actpass"; and

2) if end-to-end security is required for a one-to-one communication and the security context does not exist or if the existing security context has expired, shall include the MIKEY-SAKKE I_MESSAGE in an "a=key-mgmt" attribute as a "mikey" attribute value in the SDP offer as specified in IETF RFC 4567 [45].

[TS 24.282, clause 9.2.5.4.1.1]

Upon receiving a request from an MCData user to leave an MCData session within a pre-established session, the MCData client:

1) shall interact with the media plane as specified in 3GPP TS 24.582 [15];

2) shall generate an initial SIP REFER request outside a dialog in accordance with the procedures specified in 3GPP TS 24.229 [5], IETF RFC 4488 [53] and IETF RFC 3515 [51] as updated by IETF RFC 6665 [36] and IETF RFC 7647 [r7647];

3) shall set the Request-URI of the SIP REFER request to the public service identity identifying the pre-established session on the MCData server serving the MCData user;

4) shall include the Refer-Sub header field with value "false" according to rules and procedures of IETF RFC 4488 [53];

5) shall include the Supported header field with value "norefersub" according to rules and procedures of IETF RFC 4488 [53];

6) shall set the Refer-To header field of the SIP REFER request to the MCData session identity to leave;

7) shall include the "method" SIP URI parameter with the value "BYE" in the URI in the Refer-To header field;

8) shall include a Target-Dialog header field as specified in IETF RFC 4538 [54] identifying the pre-established session; and

9) shall send the SIP REFER request according to 3GPP TS 24.229 [5].

Upon receiving a SIP 2xx response to the SIP REFER request, the MCData client shall interact with media plane as specified in 3GPP TS 24.582 [15].

On receiving a SIP re-INVITE request within the pre-established session targeted by the sent SIP REFER request, the MCData client:

1) if the <mcdata-communication-state> element in the application/vnd.3gpp.mcdata-info+xml MIME body of the SIP INVITE request is set to a value of "terminated":

i) shall notify MCData user about successful the MCData communication termination.

[TS 24.582, clause 12.1]

Upon establishing one-to-one or group SDS using media plane or one-to-one or group SDS session using pre-established call, the MCData client shall follow procedures as descried in subclause 6.1.

[TS 24.582, clause 6.1.2.2.1]

Upon receiving an indication to establish MSRP connection for SDS session as the originating MCData client, the MCData client:

1. shall act as an MSRP client according to IETF RFC 6135 [12];

2. shall act according to IETF RFC 6135 [12], as:

   a. an "active" endpoint, if a=setup attribute in the received SDP answer is set to "passive"; and

   b. an "passive" endpoint, if a=setup attribute in the received SDP answer is set to "active";

3. shall establish the MSRP connection according to the MSRP connection parameters in the SDP answer received in the SIP 200 (OK) response according to IETF RFC 4975 [11];

4. if acting as an "active" endpoint, shall send an empty MSRP SEND request to bind the MSRP connection to the MSRP session from the perspective of the passive endpoint according to the rules and procedures of IETF RFC 4975 [11] and IETF RFC 6135 [12];

Once the MSRP session is established, the MCData client:

1. on receipt of an MSRP request in the MSRP session, shall follow the rules and procedures defined in IETF RFC 4975 [11] and in IETF RFC 6714 [13];

2. If an MSRP SEND request indicates the use of chunking, shall wait until all further MSRP SEND requests for the remaining chunks have been received and shall reassemble the entire set of MSRP requests into the MCData SDS message before delivering the content to the application; and

3. shall handle the received content as described in subclause 6.1.2.6.

On receiving MSRP 200 (OK) response to the first MSRP SEND request, the MCData client can generate and send an SDS message as specified in subclause 6.1.2.4, or can generate and send an SDS disposition notification for a received SDS message as specified in subclause 6.1.2.5, if requested.

Received content and disposition requests shall be handled as specified in subclause 6.1.2.6.

[TS 24.582, clause 6.1.2.6]

Upon receiving an SDS message, the MCData client:

1. shall follow the procedure defined in subclause 6.1.1.3.2, with the following clarification:

   a. if SDS Disposition request type IE is present in the received SDS SIGNALLING PAYLOAD message then, shall send an SDS disposition notification as described in subclause 6.1.2.5.

Upon receiving an SDS disposition notification, the MCData client:

1. shall decode the contents of the application/vnd.3gpp.mcdata-signalling MIME body; and

2. shall deliver the notification to the user or application.

6.1.19.3 Test description

6.1.19.3.1 Pre-test conditions

Test configuration:

- Single cell configuration according to TS 37.579-1 [2] clause 5.2.2.2.1.

Preamble:

- The UE has performed procedure 'Initial registration' as described in TS 37.579-1 [2] clause 5.4.2.

- The UE has performed procedure 'MCX pre-established session establishment' as described in TS 37.579-1 [2] clause 5.3.3.

- UE States at the end of the preamble:

  - The UE is in RRC_IDLE state.

  - The client is registered for MCData.

- A pre-established session is established.

6.1.19.3.2 Test procedure sequence

Table 6.1.19.3.2-1: Main Behaviour

St	Procedure	Message Sequence		TP	Verdict
		U - S	Message		
1	Make the UE (MCData client) send a group session SDS message using the pre-established session with disposition request "**DELIVERY**". (NOTE 1)	-	-	-	-
2	Check: Does the UE (MCData client) correctly perform procedure '**CO MCData call establishment using a pre-established session**' as described in TS 37.579-1 [2] Table 5.3C.12.3-1?	-	-	1	P
3	Check: Does the UE (MCData client) notify the user about successful MCData communication establishment? (NOTE 1)	-	-	1	P
4	Check: Does the UE (MCData client) correctly perform procedure 'CO MSRP message transfer' as described in TS 37.579-1 [2] Table 5.3C.4.3-1 to **send an SDS message with disposition request "DELIVERY"**?	-	-	2	P
5	Check: Does the UE (MCData client) correctly perform procedure '**CT MSRP message transfer**' as described in TS 37.579-1 [2] Table 5.3C.5.3-1 **to receive the disposition notification** for the SDS message sent at step 3?	-	-	3	P
6	Check: Does the UE (MCData client) provide the disposition notification to the user? (NOTE 1)	-	-	3	P
7	Make the UE (MCData client) release the group session while keeping the pre-established session. (NOTE 1)	-	-	-	-
8	Check: Does the UE (MCData client) correctly perform procedure '**MCData CO call release keeping the pre-established session**' as described in TS 37.579-1 [2] Table 5.3C.13.3-1? (NOTE 2)	-	-	4	P
8A	The procedure 'MCX communication release' as described in TS 37.579-1 [2] clause 5.4.14 is performed to release the RRC connection.	-	-	-	-
9	Check: Does the UE (MCData client) provide a notification to the MCData user about successful MCData communication termination? (NOTE 1)	-	-	4	P
NOTE 1: This is expected to be done via a suitable implementation dependent MMI. NOTE 2: The procedure does not release the RRC connection.					

6.1.19.3.3 Specific message contents

Table 6.1.19.3.3-1: SIP REFER from the UE (step 2, Table 6.1.19.3.2-1; step 2, TS 37.579-1 [2] Table 5.3C.12.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.12-1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part		**Resource list**		
MIME-part-body	Resource-lists as described in Table 6.1.19.3.3-2			

Table 6.1.19.3.3-2: Resource-lists in SIP REFER (Table 6.1.19.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.3.1-3, condition PRE-ESTABLISH, MCD_grp with the uri attribute of the entry extended with the SIP URI header fields as specified in Table 6.1.19.3.3-3

Table 6.1.19.3.3-3: SIP header fields extending the uri attribute of the resource-lists' single entry (Table 6.1.19.3.3-2)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.12-2				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
body				
MIME body part		**SDP Message**		
MIME-part-headers				
Content-Type	“application/sdp”			
MIME-part-body	SDP Message as described in Table 6.1.19.3.3-4			
MIME body part		**MCData-Info**		
MIME-part-body	MCdata-Info as described in Table 6.1.19.3.3-5			

Table 6.1.19.3.3-4: SDP in SIP header fields (Table 6.1.19.3.3-3)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.1.1-3, condition PRE_ESTABLISHED_SESSION, SDP_OFFER, MCDATA_SDS, SDS_SESSION

Table 6.1.19.3.3-5: MCData-Info in SIP header fields (Table 6.1.19.3.3-3)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.2.1-3, condition MCD_grp				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
mcdata-info				
mcdata-Params				
request-type	"group-sds-session"		TS 24.282 [31] clause 9.2.5.2.1.1	

Table 6.1.19.3.3-6: MSRP SEND from the UE (step 4, Table 6.1.19.3.2-1; step 1, TS 37.579-1 [2] Table 5.3C.4.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.12.1.1-1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Content-Type				
media-type	"multipart/mixed"			
data	Message or chunk of message as specified in table 6.1.19.3.3-7			

Table 6.1.19.3.3-7: MIME Message (step 4, Table 6.1.19.3.2-1; step 3, TS 37.579-1 [2] Table 5.3C.4.3-1)

Derivation Path: RFC 2046 [38]				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
MIME body part		**MCData Data signalling message**		
MIME-part-headers				
Content-Type	"application/vnd.3gpp. mcdata-signalling"			
MIME-part-body	MCData Protected Payload Message containing SDS SIGNALLING PAYLOAD as described in table 6.1.19.3.3-8			
MIME body part		**MCData Data message**		
MIME-part-headers				
Content-Type	"application/vnd.3gpp. mcdata-payload"			
MIME-part-body	DATA PAYLOAD as described in Table 6.1.19.3.3-9			

Table 6.1.19.3.3-8: SDS SIGNALLING PAYLOAD (Table 6.1.19.3.3-7)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.1-1, condition DELIVERED

Table 6.1.19.3.3-9: Data Payload (Table 6.1.19.3.3-7)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.9.2-1

Table 6.1.19.3.3-10: MSRP SEND from the SS (step 5, Table 6.1.19.3.2-1; step 1, TS 37.579-1 [2] Table 5.3C.5.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.12.1.2-1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Content-Type				
media-type	"application/vnd.3gpp. mcdata-signalling"			
data	MCData Protected Payload Message containing SDS NOTIFICATION as specified in table 6.1.19.3.3-11			

Table 6.1.19.3.3-11: SDS NOTIFICATION (Table 6.1.19.3.3-10)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.4-1, condition DELIVERED

6.1.20 On-network / Short Data Service (SDS) / SDS Session / Group SDS Session / Pre-established session / Client Terminated (CT)

6.1.20.1 Test Purpose (TP)

(1)

```
with { UE (MCDATA Client) registered and authorised for MCDATA Service }
ensure that {
  when { the MCDATA User receives a SIP re-INVITE message to initiate to initiate a group SDS
session using the media plane and using a pre-established session }
    then { UE (MCDATA Client) responds by sending a SIP 200 (OK) message }
            }
```

(2)

```
with { UE (MCDATA Client) having responded to the SIP re-INVITE message that initiated a group SDS
session using the media plane and using a pre-established session }
ensure that {
  when { UE (MCDATA Client) receives an MSRP SEND message }
    then { UE (MCDATA Client) responds with an MSRP 200 (OK) message and if the MSRP SEND message is
not blank, renders the contents of the Payload IE to the MCDATA User and sends a MSRP SEND message
with a disposition notification of "DELIVERED" }
            }
```

(3)

```
with { UE (MCDATA Client) being in a group SDS session initiated by the SS (MCDATA server) and using
a pre-established session }
ensure that {
  when { UE (MCDATA Client) receives a SIP re-INVITE message to release communications }
    then { UE (MCDATA Client) responds by sending a SIP 200 (OK) message }
            }
```

6.1.20.2 Conformance requirements

References: The conformance requirements covered in the current TC are specified in: TS 24.282, clauses 9.2.5.3.1.2, 9.2.4.2.4, 9.2.5.4.1.2, TS 24.582 clauses 12.1, 6.1.2.3.1, 6.1.2.6, 6.1.1.3.2, 6.1.2.5.1, 6.1.2.5.2, 6.1.2.5.3. The following represents a copy/paste extraction of the requirements relevant to the test purpose; any references within the copy/paste text should be understood within the scope of the core spec they have been copied from. Unless otherwise stated, these are Rel-16 requirements.

[TS 24.282, clause 9.2.5.3.1.2]

Upon receiving a SIP re-INVITE request within a pre-established Session without an associated MCData session the MCData client:

1) if the <mcdata-communication-state> element in the application/vnd.3gpp.mcdata-info+xml MIME body of the SIP INVITE request is set to a value of "establish-request":

   i) if the <request-type> element in the application/vnd.3gpp.mcdata-info+xml MIME body of the SIP INVITE request is set to a value of "group-sds", shall follow the procedures in subclause 9.2.3.2.4;

   ii) if the <request-type> element in the application/vnd.3gpp.mcdata-info+xml MIME body of the SIP INVITE request is set to a value of "group-sds-session", shall follow the procedures in subclause 9.2.4.2.4;

[TS 24.282, clause 9.2.4.2.4]

Upon receipt of an "initial SIP INVITE request for SDS session for terminating MCData client"request, the MCData client shall follow the procedures for termination of multimedia sessions in the IM CN subsystem as specified in 3GPP TS 24.229 [5] with the clarifications below.

The MCData client:

1) may reject the SIP INVITE request if either of the following conditions are met:

   a) MCData client does not have enough resources to handle the call; or

   b) any other reason outside the scope of this specification;

   and skip the rest of the steps after step 2;

2) if the SIP INVITE request is rejected in step 1), shall respond toward participating MCData function either with appropriate reject code as specified in 3GPP TS 24.229 [5] and warning texts as specified in subclause 4.9 or with SIP 480 (Temporarily unavailable) response not including warning texts if the user is authorised to restrict the reason for failure and skip the rest of the steps of this subclause;

3) if the SDP offer of the SIP INVITE request contains an "a=key-mgmt" attribute field with a "mikey" attribute value containing a MIKEY-SAKKE I_MESSAGE:

   a) shall extract the MCData ID of the originating MCData user from the initiator field (IDRi) of the I_MESSAGE as described in 3GPP TS 33.180 [26];

   b) shall convert the MCData ID to a UID as described in 3GPP TS 33.180 [26];

   c) shall use the UID to validate the signature of the MIKEY-SAKKE I_MESSAGE as described in 3GPP TS 33.180 [26];

   d) if authentication verification of the MIKEY-SAKKE I_MESSAGE fails, shall reject the SIP INVITE request with a SIP 488 (Not Acceptable Here) response as specified in IETF RFC 4567 [45], and include warning text set to "136 authentication of the MIKEY-SAKKE I_MESSAGE failed" in a Warning header field as specified in subclause 4.9 and not continue with rest of the steps in this subclause; and

   e) if the signature of the MIKEY-SAKKE I_MESSAGE was successfully validated:

      i) shall extract and decrypt the encapsulated PCK using the terminating user's (KMS provisioned) UID key as described in 3GPP TS 33.180 [26]; and

      ii) shall extract the PCK-ID, from the payload as specified in 3GPP TS 33.180 [26];

NOTE: With the PCK successfully shared between the originating MCData client and the terminating MCData client, both clients are able to create an end-to-end secure session.

4) may display to the MCData user the MCData ID of the inviting MCData user and the type of SDS request;

5) shall accept the SIP INVITE request and generate a SIP 200 (OK) response according to rules and procedures of 3GPP TS 24.229 [5];

6) shall include the option tag "timer" in a Require header field of the SIP 200 (OK) response;

7) shall include the Session-Expires header field in the SIP 200 (OK) response and start the SIP session timer according to IETF RFC 4028 [38]. The "refresher" parameter in the Session-Expires header field shall be set to "uas";

8) shall include the g.3gpp.mcdata.sds media feature tag in the Contact header field of the SIP 200 (OK) response;

9) shall include the g.3gpp.icsi-ref media feature tag containing the value of "urn:urn-7:3gpp-service.ims.icsi.mcdata.sds" in the Contact header field of the SIP 200 (OK) response;

10) shall include an SDP answer in the SIP 200 (OK) response to the SDP offer in the incoming SIP INVITE request according to 3GPP TS 24.229 [5] with the clarifications given in subclause 9.2.4.2.2; and

11) shall send the SIP 200 (OK) response towards the MCData server according to rules and procedures of 3GPP TS 24.229 [5].

On receipt of an SIP ACK message to the sent SIP 200 (OK) message, the MCData client shall:

1) shall interact with the media plane as specified in 3GPP TS 24.582 [15] subclause 6.1.2.3.

To send a disposition notification after the media plane is released, the MCData client:

1) shall follow the procedures described in subclause 12.2.1.1.

[TS 24.282, clause 9.2.5.4.1.2]

Upon receiving a SIP re-INVITE request within a pre-established Session without an associated MCData session, the MCData client:

1) if the <mcdata-communication-state> element in the application/vnd.3gpp.mcdata-info+xml MIME body of the SIP INVITE request is set to a value of "terminate-request":

   i) shall send SIP 200 (OK) response towards MCData server according to 3GPP TS 24.229 [5]; and

   ii) shall release all media plane resources corresponding to the MCData communication being released.

[TS 24.582, clause 12.1]

Upon establishing one-to-one or group SDS using media plane or one-to-one or group SDS session using pre-established call, the MCData client shall follow procedures as descried in subclause 6.1.

[TS 24.582, clause 6.1.2.3.1]

Upon receiving an indication to establish MSRP connection for SDS session as the terminating MCData client, the MCData client:

1. shall act as an MSRP client according to IETF RFC 6135 [12];

2. shall act either as an active endpoint or as an passive endpoint to open the transport connection, according to IETF RFC 6135 [12];

3. shall establish the MSRP connection according to the MSRP connection parameters in the SDP offer received in the SIP INVITE request according to IETF RFC 4975 [11];

4. if acting as an "active" endpoint, shall send an empty MSRP SEND request to bind the MSRP connection to the MSRP session from the perspective of the passive endpoint according to the rules and procedures of IETF RFC 4975 [11] and IETF RFC 6135 [12];

Once the MSRP session is established, the MCData client:

1. on receipt of an MSRP request in the MSRP session, shall follow the rules and procedures defined in IETF RFC 4975 [11] and in IETF RFC 6714 [13];

2. If an MSRP SEND request indicates the use of chunking, shall wait until all further MSRP SEND requests for the remaining chunks have been received and shall reassemble the entire set of MSRP requests into the MCData SDS message before delivering the content to the application; and

3. shall handle the received content as described in subclause 6.1.2.6.

On receiving MSRP 200 (OK) response to the first MSRP SEND request sent as "active" endpoint, or after sending MSRP 200 (OK) response to the first MSRP SEND request received as "passive" endpoint, the MCData client can generate and send an SDS message as specified in subclause 6.1.2.4, or can generate and send an SDS disposition notification for a received SDS message as specified in subclause 6.1.2.5, if requested.

Received content and disposition requests shall be handled as specified in subclause 6.1.2.6.

[TS 24.582, clause 6.1.2.6]

Upon receiving an SDS message, the MCData client:

1. shall follow the procedure defined in subclause 6.1.1.3.2, with the following clarification:

   a. if SDS Disposition request type IE is present in the received SDS SIGNALLING PAYLOAD message then, shall send an SDS disposition notification as described in subclause 6.1.2.5.

Upon receiving an SDS disposition notification, the MCData client:

1. shall decode the contents of the application/vnd.3gpp.mcdata-signalling MIME body; and
2. shall deliver the notification to the user or application.

[TS 24.582, clause 6.1.1.3.2]

The MCData client:

1. shall decode the contents of the application/vnd.3gpp.mcdata-signalling MIME body;
2. shall decode the contents of the application/vnd.3gpp.mcdata-payload MIME body;
3. if the SDS SIGNALLING PAYLOAD message contains a new Conversation ID, shall instantiate a new conversation with the Message ID in the SDS SIGNALLING PAYLOAD identifying the first message in the conversation thread;
4. if the SDS SIGNALLING PAYLOAD message contains an existing Conversation ID and:
    a. if the SDS SIGNALLING PAYLOAD message does not contain an InReplyTo Message ID, shall use the Message ID in the SDS SIGNALLING PAYLOAD to identify a new message in the existing conversation thread; and
    b. if the SDS SIGNALLING PAYLOAD message contains an InReplyTo Message ID, shall associate the message to an existing message in the conversation thread as identified by the InReplyTo Message ID in the SDS SIGNALLING PAYLOAD and use the Message ID in the SDS SIGNALLING PAYLOAD to identify the new message;
5. shall identify the number of Payload IEs in the DATA PAYLOAD message from the Number of Payloads IE in the DATA PAYLOAD message;
6. if the SDS SIGNALLING PAYLOAD message does not contain an Application identifier IE:
    a. shall determine that the payload contained in the DATA PAYLOAD message is for user consumption;
    b. may notify the MCData user; and
    c. shall render the contents of the Payload IE(s) to the MCData user;
7. if the SDS SIGNALLING PAYLOAD message contains an Application identifier IE:
    a. shall determine that the payload contained in the DATA PAYLOAD message is not for user consumption;
    b. shall not notify the MCData user;
    c. if the Application identifier value is unknown, shall discard the SDS message; and
    d. if the Application identifier value is known, shall deliver the contents of the Payload IE(s) to the identified application; and
8. if SDS Disposition request type IE is present in the SDS SIGNALLING PAYLOAD message received in subclause 6.1.1.3.1 then, shall send a disposition notification as described in 3GPP TS 24.282 [8] subclause 9.2.1.3.

[TS 24.582, clause 6.1.2.5.1]

To send an SDS disposition notification, the MCData client:

1. shall generate a SDS NOTIFICATION as specified in subclause 6.1.2.5.2;
2. shall include the SDS NOTIFICATION in an MSRP SEND request as specified in subclause 6.1.2.5.3, with the following clarification;
    a. shall set To-Path header according to the MSRP URI in the received SDP; and
3. shall send the MSRP SEND request on the established MSRP connection.

If MSRP chunking is used, the MCData client:

1. shall send further MSRP SEND requests as necessary.

On receiving a non-200 MSRP response to the MSRP SEND request the MCData client shall handle the error as specified in IETF RFC 4975 [11]. To terminate the MSRP session, the MCData client:

1. if there are further MSRP chunks to send, shall abort transmission of these further MSRP chunks; and
2. shall indicate to MCData user that the SDS message or the SDS disposition notification could not be sent.

[TS 24.582, clause 6.1.2.5.2]

In order to generate an SDS notification, the MCData client:

1. shall generate an SDS NOTIFICATION message as specified in 3GPP TS 24.282 [8]; and
2. shall include the SDS NOTIFICATION message in an application/vnd.3gpp.mcdata-signalling MIME body as specified in 3GPP TS 24.282 [8].

When generating an SDS NOTIFICATION message, the MCData client:

1. if sending a delivered notification, shall set the SDS disposition notification type IE as "DELIVERED";
2. if sending a read notification, shall set the SDS disposition notification type IE as "READ";
3. if sending a delivered and read notification, shall set the SDS disposition notification type IE as "DELIVERED AND READ";
4. if the SDS message could not be delivered to the user or application (e.g. due to lack of storage), shall set the SDS disposition notification type IE as "UNDELIVERED";
5. shall set the Date and time IE to the current time;
6. shall set the Conversation ID to the value of the Conversation ID that was received in the SDS message;
7. shall set the Message ID to the value of the Message ID that was received in the SDS message;
8. if the SDS message was destined for the user, shall not include an Application ID IE;
9. if the SDS message was destined for an application, shall include an Application ID IE set to the value of the Application ID that was included in the SDS message; and
10. shall set the Sender MCData user ID to its own MCData user ID as specified in subclause 15.2.15 of 3GPP TS 24.282 [8].

[TS 24.582, clause 6.1.2.5.3]

The MCData client shall generate MSRP SEND requests for SDS disposition notification according to IETF RFC 4975 [11].

When generating an MSRP SEND request for SDS disposition notification containing an SDS NOTIFICATION message, the MCData client

1. shall set To-Path header according to the MSRP URI(s) received in the answer SDP;
2. shall set the content type as Content-Type = "application/vnd.3gpp.mcdata-signalling"; and
3. shall set the body of the MSRP SEND request to the generated SDS NOTIFICATION message.

6.1.20.3 Test description

6.1.20.3.1 Pre-test conditions

Test configuration:

- Single cell configuration according to TS 37.579-1 [2] clause 5.2.2.2.1.

Preamble:

- The UE has performed procedure 'Initial registration' as described in TS 37.579-1 [2] clause 5.4.2.
- The UE has performed procedure 'MCX pre-established session establishment' as described in TS 37.579-1 [2] clause 5.3.3.
- UE States at the end of the preamble:
  - The UE is in RRC_IDLE state.
  - The client is registered for MCData.
  - A pre-established session is established.

6.1.20.3.2 Test procedure sequence

Table 6.1.20.3.2-1: Main Behaviour

St	Procedure	Message Sequence		TP	Verdict
		U - S	Message		
1	Check: Does the UE (MCData client) correctly perform procedure '**CT MCData Call Establishment**' as described in TS 37.579-1 [2] Table 5.3C.3.3-1? NOTE: The SS (MCData server) sends a SIP re-INVITE request within a pre-established Session to initiate a group SDS session using the media plane.	-	-	1,2	P
2	Check: Does the UE (MCData client) correctly perform procedure '**CT MSRP message transfer**' as described in TS 37.579-1 [2] Table 5.3C.5.3-1 **to receive an SDS message with disposition request "DELIVERY"**?	-	-	2	P
3	Check: Does the UE (MCData client) correctly perform procedure '**CO MSRP message transfer**' as described in TS 37.579-1 [2] Table 5.3C.4.3-1 **to send a disposition notification of "DELIVERED"**?	-	-	2	P
4	Check: Does the UE (MCData client) provide the contents of the Payload IE to the user? (NOTE 1)	-	-	2	P
5-9	Check: Does the UE (MCData client) correctly perform step 3 to 7 of procedure '**MCData CO call release keeping the pre-established session**' as described in TS 37.579-1 [2] Table 5.3C.13.3-1? NOTE: The SS (MCData server) sends a SIP re-INVITE request to release the MCData call while keeping the pre-established Session. (NOTE 2)	-	-	3	P
10	The procedure 'MCX communication release' as described in TS 37.579-1 [2] clause 5.4.14 is performed to release the RRC connection.	-	-	-	-
NOTE 1: This is expected to be done via a suitable implementation dependent MMI. NOTE 2: The procedure does not release the RRC connection.					

6.1.20.3.3 Specific message contents

Table 6.1.20.3.3-1: SIP INVITE from the SS (step 1, Table 6.1.20.3.2-1; step 2, TS 37.579-1 [2] Table 5.3C.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.5.2-1, condition MCDATA_SDS, re_INVITE				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Request-Line				
Request-URI	tsc_MCX_SessionID_B	session identity of the pre-established session	TS 24.282 [31] clause 9.2.5.2.2.2	
Message-body				
MIME body part		**SDP message**		
MIME-part-body	SDP message as described in Table 6.1.20.3.3-2			
MIME body part		**MCData-Info**		
MIME-part-body	MCData-Info as described in Table 6.1.20.3.3-3			

Table 6.1.20.3.3-2: SDP for SIP INVITE (Table 6.1.20.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.1.2-3, condition MCDATA_SDS, SDP_OFFER, SDS_SESSION, PRE_ESTABLISHED_SESSION

Table 6.1.20.3.3-3: MCData-Info (Table 6.1.20.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.2.2-3, condition MCD_grp				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
mcdata-info				
mcdata-Params				
request-type	"group-sds-session"		TS 24.282 [31] clause 9.2.5.2.2.2	
anyExt				
mcdata-communication-state	"establish-request"		TS 24.282 [31] clause 9.2.5.2.2.2	

Table 6.1.20.3.3-4: SIP 200 (OK) from the UE (step 1, Table 6.1.20.3.2-1; step 4, TS 37.579-1 [2] Table 5.3C.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.17.1.1-1, condition INVITE-RSP, MCDATA_SDS				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Content-Type				
value	"application/sdp"			
Message-body				
SDP message	As described in Table 6.1.20.3.3-5			

Table 6.1.20.3.3-5: SDP for SIP 200 (OK) (Table 6.1.20.3.3-4)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.1.1-3, condition MCDATA_SDS, SDP_ANSWER, SDS_SESSION, PRE_ESTABLISHED_SESSION

Table 6.1.20.3.3-6: MSRP SEND from the SS (step 2, Table 6.1.20.3.2-1; step 1, TS 37.579-1 [2] Table 5.3C.5.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.12.1.2-1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Content-Type				
media-type	"multipart/mixed"			
data	Message as specified in table 6.1.20.3.3-7			

Table 6.1.20.3.3-7: MIME Message (step 2, Table 6.1.20.3.2-1; step 1, TS 37.579-1 [2] Table 5.3C.5.3-1)

Derivation Path: RFC 2046 [38]				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
MIME body part		**MCData Data signalling message**		
MIME-part-headers				
Content-Type	"application/vnd.3gpp. mcdata-signalling"			
MIME-part-body	MCData Protected Payload Message containing SDS SIGNALLING PAYLOAD as described in table 6.1.20.3.3-8			
MIME body part		**MCData Data message**		
MIME-part-headers				
Content-Type	"application/vnd.3gpp. mcdata-payload"			
MIME-part-body	DATA PAYLOAD as described in Table 6.1.20.3.3-9			

Table 6.1.20.3.3-8: SDS SIGNALLING PAYLOAD (Table 6.1.20.3.3-6A)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.2-1, condition DELIVERED

Table 6.1.20.3.3-9: Data Payload (Table 6.1.20.3.3-6A)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.9.2-2

Table 6.1.20.3.3-10: MSRP SEND from the UE (step 3, Table 6.1.20.3.2-1; step 3, TS 37.579-1 [2] Table 5.3C.4.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.12.1.1-1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Content-Type				
media-type	"application/vnd.3gpp. mcdata-signalling"			
data	MCData Protected Payload Message containing SDS NOTIFICATION as specified in table 6.1.20.3.3-11			

Table 6.1.20.3.3-11: SDS NOTIFICATION (Table 6.1.20.3.3-10)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.3-1, condition DELIVERED

Table 6.1.20.3.3-12: SIP re-INVITE from the SS (step 5, Table 6.1.20.3.2-1; step 3, TS 37.579-1 [2] Table 5.3C.13.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.5.2-1, condition MCDATA_SDS, re_INVITE				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Request-Line				
Request-URI	tsc_MCX_SessionID_B	session identity of the pre-established session	TS 24.282 [31] clause 9.2.5.4.2.1	
Content-Type			RFC 5621 [58]	
media-type	"application/vnd.3gpp. mcdata-info+xml"		TS 24.282 [31] clause 9.2.5.4.2.1	
Message-body				
MCData-Info Message	MCData-Info message as described in Table 6.1.14.3.3-13			

Table 6.1.20.3.3-13: MCData-Info (Table 6.1.20.3.3-12)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.2.2-3				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
mcdata-info				
mcdata-Params				
mcdata-request-uri	not present			
mcdata-calling-user-id	not present			
anyExt				
mcdata-communication-state	"terminate request"		TS 24.282 [31] clause 9.2.5.4.2.2	

6.1.21 On-network / Short Data Service (SDS) / Standalone SDS using signalling control plane / One-to-one Standalone SDS / Active functional alias / Client Originated (CO)

6.1.21.1 Test Purpose (TP)

(1)

```
with { UE (MCDATA Client) registered and authorised for MCDATA Service }
ensure that {
  when { the MCDATA User requests to send a standalone one-to-one SDS message with a disposition of
only Delivery using an active functional alias }
    then { UE (MCDATA Client) sends a standalone one-to-one SDS message with a disposition of only
Delivery using an active functional alias via a SIP MESSAGE message }
            }
```

(2)

```
with { UE (MCDATA Client) having sent a standalone one-to-one SDS message using an active Functional
Alias }
ensure that {
  when { UE (MCDATA Client receives a disposition response via a SIP MESSAGE message from the SS
(MCDATA Server) }
    then { UE (MCDATA Client) responds to the SIP MESSAGE message by sending a SIP 200 (OK) message
and delivers the notification to the MCDATA User }
            }
```

6.1.21.2 Conformance requirements

References: The conformance requirements covered in the current TC are specified in: TS 24.282, clauses 9.2.2.2.1, 6.2.2.1, 6.2.4.1, 12.2.1.2. The following represents a copy/paste extraction of the requirements relevant to the test purpose; any references within the copy/paste text should be understood within the scope of the core spec they have been copied from. Unless otherwise stated, these are Rel-16 requirements.

[TS 24.282, clause 9.2.2.2.1]

The MCData client shall generate a SIP MESSAGE request in accordance with 3GPP TS 24.229 [5] and IETF RFC 3428 [6] with the clarifications given below.

The MCData client:

1) shall build the SIP MESSAGE request as specified in subclause 6.2.4.1;

2) if a one-to-one standalone SDS message is to be sent, shall insert in the SIP MESSAGE request:

   a) an application/resource-lists+xml MIME body with the MCData ID of the target MCData user, according to rules and procedures of IETF RFC 4826 [9];

   b) an application/vnd.3gpp.mcdata-info+xml MIME body with:

      i) a <request-type> element set to a value of "one-to-one-sds"; and

      ii) if the MCData client is aware of active functional aliases and if an active functional alias is to be included in the SIP MESSAGE request, the <functional-alias-URI> element set to the URI of the used functional alias; and

   c) if end-to-end security is required and the security context does not exist or if the existing security context has expired, an application/mikey MIME body with the MIKEY-SAKKE I_MESSAGE as specified in 3GPP TS 33.180 [26]. The MCData client:

      i) if necessary, shall instruct the key management client to request keying material from the key management server as described in 3GPP TS 33.180 [26];

      ii) shall use the keying material to generate a PCK as described in 3GPP TS 33.180 [26];

      iii) shall use the PCK to generate a PCK-ID with the four most significant bits set to "0001" to indicate that the purpose of the PCK is to protect one-to-one communications and with the remaining twenty eight bits being randomly generated as described in 3GPP TS 33.180 [26];

      iv) shall encrypt the PCK to a UID associated to the MCData client using the MCData ID of the invited user and a time related parameter as described in 3GPP TS 33.180 [26];

      v) shall generate a MIKEY-SAKKE I_MESSAGE using the encapsulated PCK and PCK-ID as specified in 3GPP TS 33.180 [26]; and

      vi) shall add the MCData ID of the originating MCData to the initiator field (IDRi) of the I_MESSAGE as described in 3GPP TS 33.180 [26];

      vii) shall sign the MIKEY-SAKKE I_MESSAGE using the originating MCData user's signing key provided in the keying material together with a time related parameter; and

      viii) shall include the MIKEY-SAKKE I_MESSAGE in an application/mikey MIME body as specified in 3GPP TS 33.180 [26];

…

4) shall generate a standalone SDS message as specified in subclause 6.2.2.1; and

5) shall send the SIP MESSAGE request according to rules and procedures of 3GPP TS 24.229 [5].

[TS 24.282, clause 6.2.2.1]

In order to generate an SDS message, the MCData client:

1) shall generate an SDS SIGNALLING PAYLOAD message as specified in subclause 15.1.2;

2) shall generate a DATA PAYLOAD message as specified in subclause 15.1.4;

3) shall include in the SIP request, the SDS SIGNALLING PAYLOAD message in an application/vnd.3gpp.mcdata-signalling MIME body as specified in subclause E.1; and

4) shall include in the SIP request, the DATA PAYLOAD message in an application/vnd.3gpp.mcdata-payload MIME body as specified in subclause E.2.

When generating an SDS SIGNALLING PAYLOAD message as specified in subclause 15.1.2, the MCData client:

1) shall set the Date and time IE to the current time as specified in subclause 15.2.8;

2) if the SDS message starts a new conversation, shall set the Conversation ID IE to a newly generated Conversation ID value as specified in subclause 15.2.9;

3) if the SDS message continues an existing unfinished conversation, shall set the Conversation ID IE to the Conversation ID value of the existing conversation as specified in subclause 15.2.9;

4) shall set the Message ID IE to a newly generated Message ID value as specified in subclause 15.2.10;

5) if the SDS message is in reply to a previously received SDS message, shall include the InReplyTo message ID IE with the Message ID value in the previously received SDS message;

6) if the SDS message is for user consumption, shall not include an Application ID IE as specified in subclause 15.2.7and shall not include an Extended application ID IE as specified in subclause 15.2.24;

7) if the SDS message is intended for an application on the terminating MCData client, shall include:

   a) an Application ID IE with a Application ID value representing the intended application as specified in subclause 15.2.7; or

   b) an Extended application ID IE with an Extended application ID value representing the intended application as specified in subclause 15.2.24;

NOTE: The value chosen for the Application ID value is decided by the mission critical organisation.

8) if only a delivery disposition notification is required shall include a SDS disposition request type IE set to "DELIVERY" as specified in subclause 15.2.3;

9) if only a read disposition notification is required shall include a SDS disposition request type IE set to "READ" as specified in subclause 15.2.3;

10) if both a delivery and read disposition notification is required shall include a SDS disposition request type IE set to "DELIVERY AND READ" as specified in subclause 15.2.3; and

11) may set the User location IE to the current location of the UE as specified in subclause 15.2.25.

When generating an DATA PAYLOAD message for SDS as specified in subclause 15.1.4, the MCData client:

1) shall set the Number of payloads IE to the number of Payload IEs that needs to be encoded, as specified in subclause 15.2.12;

2) if end-to-end security is required for a one-to-one communication, shall include the Security parameters and Payload IE with security parameters as described in 3GPP TS 33.180 [26]. Otherwise, if end-to-end security is not required for a one-to-one communication, shall include the Payload IE as specified in subclause 15.1.4; and

3) for each Payload IE included:

   a) if the payload is text, shall set the Payload content type as "TEXT" as specified in subclause 15.2.13;

   b) if the payload is binary data, shall set the Payload content type as "BINARY" as specified in subclause 15.2.13;

   c) if the payload is hyperlinks, shall set the Payload content type as "HYPERLINKS" as specified in subclause 15.2.13;

d) if the payload is location, shall set the Payload content type as "LOCATION" as specified in subclause 15.2.13;

e) if payload is enhanced status for a group, shall set the Payload content type as "ENHANCED STATUS" as specified in subclase 15.2.13; and

f) shall include the data to be sent in the Payload data.

[TS 24.282, clause 6.2.4.1]

This subclause is referenced from other procedures.

In a SIP MESSAGE request, the MCData client:

1) when sending SDS messages or SDS disposition notifications:

a) shall include an Accept-Contact header field containing the g.3gpp.mcdata.sds media feature tag along with the "require" and "explicit" header field parameters according to IETF RFC 3841 [8];

b) shall include an Accept-Contact header field with the media feature tag g.3gpp.icsi-ref containing the value of "urn:urn-7:3gpp-service.ims.icsi.mcdata.sds" along with the "require" and "explicit" header field parameters according to IETF RFC 3841 [8]; and

c) shall include the ICSI value "urn:urn-7:3gpp-service.ims.icsi.mcdata.sds" (coded as specified in 3GPP TS 24.229 [5]), in a P-Preferred-Service header field according to IETF RFC 6050 [7] in the SIP MESSAGE request;

…

3) may include a P-Preferred-Identity header field in the SIP MESSAGE request containing a public user identity as specified in 3GPP TS 24.229 [5]; and

4) shall set the Request-URI to the public service identity identifying the participating MCData function serving the MCData user.

[TS 24.282, clause 12.2.1.2]

Upon receipt of a:

"SIP MESSAGE request for SDS disposition notification for terminating MCData client"; or

"SIP MESSAGE request for FD disposition notification for terminating MCData client";

the MCData client:

1) shall decode the contents of the application/vnd.3gpp.mcdata-signalling MIME body; and

2) shall deliver the notification to the user or application.

6.1.21.3 Test description

6.1.21.3.1 Pre-test conditions

Test configuration:

- Single cell configuration according to TS 37.579-1 [2] clause 5.2.2.2.1.

Preamble:

- The UE has performed procedure 'Initial registration' as described in TS 37.579-1 [2] clause 5.4.2 with the following clarifications:

  - The <max-payload-size-sds-cplane-bytes> element shall not be present in the MCData Service Configuration document so that according to TS 24.484 [24] there is no size limit imposed for the use of C-plane procedures for the SDS message.

- The UE has performed procedure 'UE initiated MCX functional alias status determination and subscription' as specified in TS 37.579-1 [2] clause 5.3.36.
- The UE has performed procedure 'UE initiated MCX functional alias status change' as specified in TS 37.579-1 [2] clause 5.3.37.
- UE States at the end of the preamble:
  - The UE is in RRC_IDLE state.
  - The client is registered for MCData.
  - The client is subscribed for notification of functional alias status changes and has activated a functional alias.

6.1.21.3.2 Test procedure sequence

Table 6.1.21.3.2-1: Main Behaviour

St	Procedure	Message Sequence		TP	Verdict
		U - S	Message		
1	Make the UE (MCData client) send a standalone one-to-one SDS message with disposition request "**DELIVERY**" using an active Functional Alias. (NOTE 1)	-	-	-	-
2-4	Check: Does the UE (MCData client) correctly perform steps 1a1-3 of procedure '**CO SDS or FD message transfer** using signalling plane' as described in TS 37.579-1 [2] Table 5.3C.1.3-1 **to send a standalone one-to-one SDS message with disposition request "DELIVERY"**? (NOTE 2)	-	-	1	P
5	Check: Does the UE (MCData client) correctly perform procedure '**MCX SIP MESSAGE CT**' as described in TS 37.579-1 [2] Table 5.3.33.3-1 **to receive the disposition notification** for the SDS message sent at step 2A?	-	-	2	P
6	Check: Does the UE (MCData client) provide the disposition notification to the user? (NOTE 1)	-	-	2	P
NOTE 1: This is expected to be done via a suitable implementation dependent MMI. NOTE 2: The RRC connection is not released at the end of the procedure.					

6.1.21.3.3 Specific message contents

Table 6.1.21.3.3-1: SIP MESSAGE from the UE (step 2A, Table 6.1.21.3.2-1; step 2, TS 37.579-1 [2] Table 5.3C.1.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.7.1-1, condition MCDATA_SDS, RESOURCE_LISTS, MIKEY, MCDATA_SIGNALLING, MCDATA_PAYLOAD				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part		**MCData-Info**		
MIME-part-body	MCData-Info as described in Table 6.1.21.3.3-2			
MIME body part		**MCData Data signalling message**		
MIME-part-body	MCData Protected Payload Message containing SDS SIGNALLING PAYLOAD as described in Table 6.1.21.3.3-3			
MIME body part		**MCData Data message**		
MIME-part-body	DATA PAYLOAD as described in Table 6.1.21.3.3-4			

Table 6.1.21.3.3-2: MCData-Info (Table 6.1.21.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.2.1-3, condition MCD_1to1, FUNCTIONAL_ALIAS

Table 6.1.21.3.3-3: SDS SIGNALLING PAYLOAD (Table 6.1.21.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.1-1, condition DELIVERED

Table 6.1.21.3.3-4: DATA PAYLOAD (Table 6.1.21.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.9.2-1

Table 6.1.21.3.3-5: SIP MESSAGE from the SS (step 5, Table 6.1.21.3.2-1; step 2, TS 37.579-1 [2] Table 5.3.33.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.7.2-1, condition MCDATA_SDS, MCDATA_SIGNALLING				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part		**MCData Data signalling message**		
MIME-part-body	MCData Protected Payload Message containing SDS NOTIFICATION as described in Table 6.1.21.3.3-6			

Table 6.1.21.3.3-6: SDS NOTIFICATION (Table 6.1.21.3.3-5)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.4-1, condition DELIVERED

6.1.22 On-network / Short Data Service (SDS) / Standalone SDS Using Media Plane / One-to-one Standalone SDS / Active functional alias / Client Originated (CO)

6.1.22.1 Test Purpose (TP)

(1)

```
with { UE (MCDATA Client) registered and authorised for MCDATA Service }
ensure that {
  when { the MCDATA User requests to send a one-to-one standalone SDS message using the media plane
using an active functional alias }
    then { UE (MCDATA Client) sends a request to establish an MSRP connection via a SIP INVITE
message and then responds to the SIP 200 (OK) message with a SIP ACK message }
            }
```

(2)

```
with { UE (MCDATA Client) having requested the establishment of a MSRP connection }
ensure that {
  when { UE (MCDATA Client) receives a SIP 200 (OK) message with the a=setup attribute set to
"passive"  from the SS (MCDATA server) }
    then { UE (MCDATA Client) sends a blank MSRP SEND message to bind the MSRP connection and then
sends the one-to-one standalone SDS message via a MSRP SEND message with a disposition of "DELIVERY"
}
            }
```

(3)

```
with { UE (MCDATA Client) having sent a one-to-one standalone SDS message using the media plane }
ensure that {
  when { UE (MCDATA Client receives a MSRP 200 (OK) message in response to the last MSRP SEND
message indicating that the standalone SDS message has been successfully transferred }
    then { UE (MCDATA Client) sends a SIP BYE message }
            }
```

(4)

```
with { UE (MCDATA Client) having sent a one-to-one standalone SDS message using the media plane with
a disposition of "DELIVERY" }
ensure that {
  when { UE (MCDATA Client receives a disposition response via a SIP MESSAGE message from the SS
(MCDATA Server }
    then { UE (MCDATA Client) responds to the SIP MESSAGE message by sending a SIP 200 (OK) message
and delivers the notification to the MCDATA User }
            }
```

6.1.22.2 Conformance requirements

References: The conformance requirements covered in the current TC are specified in: TS 24.282, clauses 9.2.3.2.3, 9.2.3.2.1, 13.2.2.2.2.1, 12.2.1.2, TS 24.582 clauses 6.1.1.2.1, 6.1.1.2.2, 6.1.1.2.3, 6.1.1.2.4. The following represents a copy/paste extraction of the requirements relevant to the test purpose; any references within the copy/paste text should be understood within the scope of the core spec they have been copied from. Unless otherwise stated, these are Rel-16 requirements.

[TS 24.282, clause 9.2.3.2.3]

The MCData client shall generate a SIP INVITE request in accordance with 3GPP TS 24.229 [5] with the clarifications given below.

The MCData client:

1) shall include the g.3gpp.mcdata.sds media feature tag and the g.3gpp.icsi-ref media feature tag with the value of "urn:urn-7:3gpp-service.ims.icsi.mcdata.sds" in the Contact header field of the SIP INVITE request according to IETF RFC 3840 [16];

2) shall include an Accept-Contact header field containing the g.3gpp.mcdata.sds media feature tag along with the "require" and "explicit" header field parameters according to IETF RFC 3841 [8];

3) shall include an Accept-Contact header field with the g.3gpp.icsi-ref media feature tag containing the value of "urn:urn-7:3gpp-service.ims.icsi.mcdata.sds" along with the "require" and "explicit" header field parameters according to IETF RFC 3841 [8];

4) shall include the ICSI value "urn:urn-7:3gpp-service.ims.icsi.mcdata.sds" (coded as specified in 3GPP TS 24.229 [5]), in a P-Preferred-Service header field according to IETF RFC 6050 [7] in the SIP INVITE request;

5) should include the "timer" option tag in the Supported header field;

6) should include the Session-Expires header field according to IETF RFC 4028 [38]. It is recommended that the "refresher" header field parameter is omitted. If included, the "refresher" header field parameter shall be set to "uac";

7) if a one-to-one standalone SDS message is to be sent:

   a) shall insert in the SIP INVITE request a MIME resource-lists body with the MCData ID of the invited MCData user, according to rules and procedures of IETF RFC 5366 [18];

   b) shall contain an application/vnd.3gpp.mcdata-info+xml MIME body with the <mcdatainfo> element containing the <mcdata-Params> element with:

      i) the <request-type> element set to a value of "one-to-one-sds"; and

      ii) if the MCData client is aware of active functional aliases and if an active functional alias is to be included in the SIP INVITE request, the <functional-alias-URI> element set to the URI of the used functional alias; and

NOTE 0: The MCData client learns the functional aliases that are activated for an MCData ID from procedures specified in subclause 22.2.1.3.

   c) if an end-to-end security context needs to be established and the security context does not exist or if the existing security context has expired, then:

      i) if necessary, shall instruct the key management client to request keying material from the key management server as described in 3GPP TS 33.180 [26];

      ii) shall use the keying material to generate a PCK as described in 3GPP TS 33.180 [26];

      iii) shall use the PCK to generate a PCK-ID with the four most significant bits set to "0001" to indicate that the purpose of the PCK is to protect one-to-one communications and with the remaining twenty eight bits being randomly generated as described in 3GPP TS 33.180 [26];

      iv) shall encrypt the PCK to a UID associated to the MCData client using the MCData ID of the invited user and a time related parameter as described in 3GPP TS 33.180 [26];

      v) shall generate a MIKEY-SAKKE I_MESSAGE using the encapsulated PCK and PCK-ID as specified in 3GPP TS 33.180 [26];

      vi) shall add the MCData ID of the originating MCData to the initiator field (IDRi) of the I_MESSAGE as described in 3GPP TS 33.180 [26]; and

      vii) shall sign the MIKEY-SAKKE I_MESSAGE using the originating MCData user's signing key provided in the keying material together with a time related parameter, and add this to the MIKEY-SAKKE payload, as described in 3GPP TS 33.180 [26];

…

9) shall set the Request-URI of the SIP INVITE request to the public service identity identifying the participating MCData function serving the MCData user;

NOTE 2: The MCData client is configured with public service identity identifying the participating MCData function serving the MCData user.

10) may include a P-Preferred-Identity header field in the SIP INVITE request containing a public user identity as specified in 3GPP TS 24.229 [5];

11) shall include an SDP offer according to 3GPP TS 24.229 [5] with the clarifications given in subclause 9.2.3.2.1; and

12) shall send the SIP INVITE request towards the MCData server according to 3GPP TS 24.229 [5].

On receipt of a SIP 2xx response to the SIP INVITE request, the MCData client:

1) shall send a SIP ACK request as specified in 3GPP TS 24.229 [5];

2) shall start the SIP Session timer according to rules and procedures of IETF RFC 4028 [38]; and

3) shall interact with the media plane as specified in 3GPP TS 24.582 [15] subclause 6.1.1.2.

On receipt of a SIP 4xx response, a SIP 5xx response or a SIP 6xx response to the SIP INVITE request:

1) shall indicate to the MCData user that the SDS message could not be sent; and

2) shall send a SIP ACK request as specified in 3GPP TS 24.229 [5].

On receipt of an indication from the media plane indicating that the standalone SDS message was not sent successfully, the MCData client shall:

1) shall generate a SIP BYE request according to 3GPP TS 24.229 [5] with:

   a) Reason code set to "SIP";

   b) cause set to "480"; and

   c) text set to "transmission failed";

2) shall set the Request-URI to the MCData session identity to release; and

3) shall send a SIP BYE request towards MCData server according to 3GPP TS 24.229 [5].

On receipt of an indication from the media plane indicating that the standalone SDS message has been successfully transferred, the MCData client shall:

1) shall generate a SIP BYE request according to 3GPP TS 24.229 [5] with:

   a) Reason code set to "SIP";

   b) cause set to "200"; and

   c) text set to "transmission succeeded";

2) shall set the Request-URI to the MCData session identity to release; and

3) shall send a SIP BYE request towards MCData server according to 3GPP TS 24.229 [5].

Upon receiving a SIP 200 (OK) response to the SIP BYE request, the MCData client shall interact with the media plane and indicate to terminate the session, as specified in 3GPP TS 24.582 [15].

[TS 24.282, clause 9.2.3.2.1]

When composing an SDP offer according to 3GPP TS 24.229 [5], IETF RFC 4975 [17], IETF RFC 6135 [19] and IETF RFC 6714 [20] the MCData client:

1) shall include an "m=message" media-level section for the MCData media stream consisting of:

   a) the port number;

   b) a protocol field value of "TCP/MSRP", or "TCP/TLS/MSRP" for TLS;

   c) a format list field set to ‘*’;

d) an "a=sendonly" attribute;

e) an "a=path" attribute containing its own MSRP URI;

f) set the content type as "a=accept-types:application/vnd.3gpp.mcdata-signalling application/vnd.3gpp.mcdata-payload"; and

g) set the a=setup attribute as "actpass"; and

2) if end-to-end security is required for a one-to-one communication and the security context does not exist or if the existing security context has expired, shall include the MIKEY-SAKKE I_MESSAGE in an "a=key-mgmt" attribute as a "mikey" attribute value in the SDP offer as specified in IETF RFC 4567 [45].

[TS 24.282, clause 13.2.2.2.2.1]

When the MCData client wants to release a MCData communication established over the media plane, the MCData client:

1) shall generate a SIP BYE request according to 3GPP TS 24.229 [5];

2) shall set the Request-URI to the MCData session identity to be released; and

3) shall send the SIP BYE request towards MCData server according to 3GPP TS 24.229 [5].

Upon receiving a SIP 200 (OK) response to the SIP BYE request, the MCData client shall release all media plane resources corresponding to the MCData communication being released.

[TS 24.282, clause 12.2.1.2]

Upon receipt of a:

"SIP MESSAGE request for SDS disposition notification for terminating MCData client"; or

"SIP MESSAGE request for FD disposition notification for terminating MCData client";

the MCData client:

1) shall decode the contents of the application/vnd.3gpp.mcdata-signalling MIME body; and

2) shall deliver the notification to the user or application.

[TS 24.582, clause 6.1.1.2.1]

Upon receiving an indication to establish MSRP connection for standalone SDS using media plane as the originating client, the MCData client:

1. shall act as an MSRP client according to IETF RFC 6135 [12];

2. shall act according to IETF RFC 6135 [12], as:

   a. an "active" endpoint, if a=setup attribute in the received SDP answer is set to "passive"; and

   b. an "passive" endpoint, if a=setup attribute in the received SDP answer is set to "active";

3. shall establish the MSRP connection according to the MSRP connection parameters in the SDP answer received in the SIP 200 (OK) response according to IETF RFC 4975 [11]; and

4. if acting as an "active" endpoint, shall send an empty MSRP SEND request to bind the MSRP connection to the MSRP session from the perspective of the passive endpoint according to the rules and procedures of IETF RFC 4975 [11] and IETF RFC 6135 [12].

On receiving MSRP 200 (OK) response to the first MSRP SEND request, the MCData client:

1. shall generate a SDS SIGNALLING PAYLOAD as specified in subclause 6.1.1.2.2;

2. shall generate a SDS DATA PAYLOAD as specified in subclause 6.1.1.2.3;

3. shall include the SDS SIGNALLING PAYLOAD and SDS DATA PAYLOAD in an MSRP SEND request as specified in subclause 6.1.1.2.4; and

4. shall send the MSRP SEND request on the established MSRP connection.

If MSRP chunking is not used then on receipt of a 200 (OK) response, the MCData client shall terminate the SIP session as specified in 3GPP TS 24.282 [8].

If MSRP chunking is used, the MCData client:

1. shall send further MSRP SEND requests as necessary;

2. shall wait for a 200 (OK) response to each MSRP SEND request sent; and

3. on receipt of the last 200 (OK) response shall terminate the SIP session as specified in 3GPP TS 24.282 [8].

On receiving a non-200 MSRP response to the MSRP SEND request the MCData client shall handle the error as specified in IETF RFC 4975 [11]. To terminate the MSRP session, the MCData client:

1. if there are further MSRP chunks to send, shall abort transmission of these further MSRP chunks;

2. shall indicate to MCData user that the SDS message could not be sent; and

3. shall terminate the SIP session as specified in 3GPP TS 24.282 [8].

On receiving an indication to terminate the session from the signalling plane, the MCData client:

1. if there are further MSRP chunks to send, shall abort transmission of these further MSRP chunks and may indicate to MCData user that the SDS message could not be sent.

[TS 24.582, clause 6.1.1.2.2]

In order to generate an SDS signalling payload, the MCData client:

1. shall generate an SDS SIGNALLING PAYLOAD message as specified in 3GPP TS 24.282 [8]; and

2. shall include the SDS SIGNALLING PAYLOAD message in an application/vnd.3gpp.mcdata-signalling MIME body as specified in 3GPP TS 24.282 [8]; and

When generating a an SDS SIGNALLING PAYLOAD message, the MCData client:

1. shall generate a SDS SIGNALLING PAYLOAD message as defined in 3GPP TS 24.282 [8]. In the SDS SIGNALLING PAYLOAD message, the MCData client:

   a. may include and set the Disposition request type IE to:

      i. "DELIVERY", if only delivery disposition is requested;

      ii. "READ", if only read disposition is requested; or

      iii. "DELIVERY AND READ", if both delivery and read dispositions are requested;

   b. shall set Date and time IE to current UTC time;

   c. shall set Conversation ID IE to a universally unique message ID generated as per IETF RFC 4122 [10];

   d. shall set Message ID IE to a universally unique message ID generated as per IETF RFC 4122 [10];

   e. if indicated that the SDS message is in reply to another SDS message then, shall include the Reply ID IE set to the message identifier of the indicated SDS message;

   f. if indicated that the target recipient of the SDS message is an application then, shall set Application Identifier IE to the application identifier; and

   g) shall set the Sender MCData user ID to its own MCData user ID as specified in subclause 15.2.15 of 3GPP TS 24.282 [8].

[TS 24.582, clause 6.1.1.2.3]

In order to generate SDS data payload, the MCData client:

1. shall generate a DATA PAYLOAD message as specified in 3GPP TS 24.282 [8]; and
2. shall include the DATA PAYLOAD message in an application/vnd.3gpp.mcdata-payload MIME body as specified in 3GPP TS 24.282 [8].

When generating a DATA PAYLOAD message, the MCData client:

1. shall generate a SDS DATA PAYLOAD message as defined in 3GPP TS 24.282 [8]. In the SDS DATA PAYLOAD message, the MCData client:
   a. shall set Number of payloads IE to the total number of payloads being sent; and
   b. for each payload, shall include Payload IE. In the Payload IE:
      i. shall set Payload content type to "TEXT", or "BINARY", or "HYPERLINKS", or "LOCATION" according to the payload type; and
      ii. shall set Payload data IE to actual payload.

[TS 24.582, clause 6.1.1.2.4]

The MCData client shall take the procedures in subclause 6.4.1 into consideration when generating MSRP SEND messages.

The MCData client shall generate MSRP SEND for SDS message requests according to IETF RFC 4975 [11].

When generating an MSRP SEND for SDS message request containing an SDS SIGNALLING PAYLOAD message and an SDS DATA PAYLOAD message, the MCData client

1. shall set To-Path header according to the MSRP URI(s) received in the answer SDP;
2. shall include two MIME bodies in accordance with subclause 6.4.1 where:
   a. in the first body the Content-Type header field is set to "application/vnd.3gpp.mcdata-signalling" and the generated SDS SIGNALLING PAYLOAD message is included; and
   b. in the second body the Content-Type header field is set to "application/vnd.3gpp.mcdata-payload" and the generated SDS DATA PAYLOAD message is included.

When generating an MSRP SEND for SDS message request containing only an SDS DATA PAYLOAD message, the MCData client:

1. shall set To-Path header according to the MSRP URI(s) received in the answer SDP;
2. shall set the Content-Type as "application/vnd.3gpp.mcdata-payload"; and
3. shall set the body of the MSRP SEND request to the generated SDS DATA PAYLOAD message.

When generating an MSRP SEND for SDS message request containing only an SDS SIGNALLING PAYLOAD, the MCData client.

1. shall set To-Path header according to the MSRP URI(s) received in the answer SDP;
2. shall set the Content-Type as "application/vnd.3gpp.mcdata-signalling"; and
3. shall set the body of the MSRP SEND request to the generated SDS SIGNALLING PAYLOAD message.

6.1.22.3 Test description

6.1.22.3.1 Pre-test conditions

Test configuration:

- Single cell configuration according to TS 37.579-1 [2] clause 5.2.2.2.1.

Preamble:

- The UE has performed procedure 'Initial registration' as described in TS 37.579-1 [2] clause 5.4.2 with the following clarifications:
  - The <max-payload-size-sds-cplane-bytes> element of the MCData Service Configuration document shall be set to 0 to force the MCData client to send the data using the media plane.
- The UE has performed procedure 'UE initiated MCX functional alias status determination and subscription' as specified in TS 37.579-1 [2] clause 5.3.36.
- The UE has performed procedure 'UE initiated MCX functional alias status change' as specified in TS 37.579-1 [2] clause 5.3.37.
- UE States at the end of the preamble:
  - The UE is in RRC_IDLE state.
  - The client is registered for MCData.
  - The client is subscribed for notification of functional alias status changes and has activated a functional alias.

6.1.22.3.2 Test procedure sequence

Table 6.1.22.3.2-1: Main Behaviour

St	Procedure	Message Sequence		TP	Verdict
		U - S	Message		
1	Make the UE (MCData client) send a one-to-one standalone SDS message with disposition request "**DELIVERY**" using an active Functional Alias. (NOTE 1)	-	-	-	-
2	Check: Does the UE (MCData client) correctly perform procedure '**CO MCData Call Establishment**' as described in TS 37.579-1 [2] Table 5.3C.2.3-1?	-	-	1,2	P
3	Check: Does the UE (MCData client) correctly perform procedure 'CO MSRP message transfer' as described in TS 37.579-1 [2] Table 5.3C.4.3-1 to **send an SDS message with disposition request "DELIVERY"**?	-	-	2	P
4	Check: Does the UE (MCData client) correctly perform procedure '**CO MCData call release**' as described in TS 37.579-1 [2] Table 5.3C.6.3-1? (NOTE 2)	-	-	3	P
5	Check: Does the UE (MCData client) correctly perform procedure 'MCX SIP MESSAGE CT' as described in TS 37.579-1 [2] Table 5.3.33.3-1 to **receive the disposition notification** for the SDS message sent at step 3?	-	-	-	-
6	Check: Does the UE (MCData client) provide the disposition notification to the user? (NOTE 1)	-	-	4	P
NOTE 1: This is expected to be done via a suitable implementation dependent MMI. NOTE 2: The procedure does not release the RRC connection.					

6.1.22.3.3 Specific message contents

Table 6.1.22.3.3-1: SIP INVITE from the UE (step 2, Table 6.1.22.3.2-1; step 2, TS 37.579-1 [2] Table 5.3C.2.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.5.1-1, condition MCDATA_SDS, MCD_1to1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part		**SDP message**		
MIME-part-body	As described in Table 6.1.22.3.3-2			
MIME body part		**MCData-Info**		
MIME-part-body	MCData-Info as described in Table 6.1.22.3.3-3			

Table 6.1.22.3.3-2: SDP for SIP INVITE (Table 6.1.22.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.1.1-3, condition MCDATA_SDS, SDP_OFFER, MCD_1to1

Table 6.1.22.3.3-3: MCData-Info (Table 6.1.22.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.2.1-3, condition MCD_1to1, FUNCTIONAL_ALIAS

Table 6.1.22.3.3-4: SIP 200 (OK) from the SS (step 2, Table 6.1.22.3.2-1; step 4, TS 37.579-1 [2] Table 5.3C.2.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.17.1.2-1, condition INVITE-RSP				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
SDP message	As described in Table 6.1.22.3.3-5			

Table 6.1.22.3.3-5: SDP for SIP 200 (OK) (Table 6.1.22.3.3-4)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.1.2-3, condition MCDATA_SDS, SDP_ANSWER

Table 6.1.22.3.3-6: MSRP SEND from the UE (step 3, Table 6.1.22.3.2-1; step 1, TS 37.579-1 [2] Table 5.3C.4.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.12.1.1-1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Content-Type				
media-type	"multipart/mixed"			
data	Message or chunk of message as specified in table 6.1.22.3.3-7			

Table 6.1.22.3.3-7: MIME Message (step 3, Table 6.1.22.3.2-1; step 3, TS 37.579-1 [2] Table 5.3C.4.3-1)

Derivation Path: RFC 2046 [38]				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
MIME body part		**MCData Data signalling message**		
MIME-part-headers				
Content-Type	"application/vnd.3gpp.mcdata-signalling"			
MIME-part-body	MCData Protected Payload Message containing SDS SIGNALLING PAYLOAD as described in table 6.1.22.3.3-8			
MIME body part		**MCData Data message**		
MIME-part-headers				
Content-Type	"application/vnd.3gpp.mcdata-payload"			
MIME-part-body	DATA PAYLOAD as described in Table 6.1.22.3.3-9			

Table 6.1.22.3.3-8: SDS SIGNALLING PAYLOAD (Table 6.1.22.3.3-7)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.1-1, condition DELIVERED

Table 6.1.22.3.3-9: Data Payload (Table 6.1.22.3.3-7)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.9.2-1

Table 6.1.22.3.3-10: SIP BYE from the UE (step 4, Table 6.1.22.3.2-1; step 1, TS 37.579-1 [2] Table 5.3C.6.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.2.1-1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Reason			RFC 3326 [125]	
reason-value	"SIP"			
protocol-cause	"cause="200""			
reason-text	"text="transmission succeeded""			

Table 6.1.22.3.3-11: SIP MESSAGE from the SS (step 5, Table 6.1.22.3.2-1; step 2, TS 37.579-1 [2] Table 5.3.33.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.7.2-1, condition MCDATA_SDS, MCDATA_SIGNALLING				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part		**MCData Data signalling message**		
MIME-part-body	MCData Protected Payload Message containing SDS NOTIFICATION as described in Table 6.1.22.3.3-12			

Table 6.1.22.3.3-12: SDS NOTIFICATION (Table 6.1.22.3.3-11)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.4-1, condition DELIVERED

6.1.23 On-network / Short Data Service (SDS) / SDS Session / Group SDS Session / Pre-established session / Preconfigured Group Use Only

6.1.23.1 Test Purpose (TP)

(1)

```
with { UE (MCDATA Client) registered and authorised for MCDATA Service }
ensure that {
  when { the MCDATA User requests to initiate a group SDS session using the media plane and using
the pre-established session to a group configured for preconfigured group use only  }
    then { UE (MCDATA Client) indicate to the MCDATA user that group standalone SDS message  is not
allowed on the indicated group and does not send a SIP INVITE request }
            }
```

6.1.23.2 Conformance requirements

References: The conformance requirements covered in the current TC are specified in: TS 24.282, clause 9.2.5.3.1. The following represents a copy/paste extraction of the requirements relevant to the test purpose; any references within the copy/paste text should be understood within the scope of the core spec they have been copied from. Unless otherwise stated, these are Rel-17 requirements.

[TS 24.282, clause 9.2.5.3.1]

Upon receiving a request from an MCData user to initiate group SDS session within the pre-established session, the MCData client shall determine whether the group document contains a <list-service> element that contains a <preconfigured-group-use-only> element. If a <preconfigured-group-use-only> element exists and is set to the value "true", then the MCData client:

1) should indicate to the MCData user that SDS sessions are not allowed on the indicated group; and

2) shall skip the remainder of this procedure.

Upon receiving a request from an MCData user to initiate group SDS session within the pre-established session, the MCData client shall generate a SIP REFER request outside a dialog as specified in IETF RFC 3515 [51] as updated by IETF RFC 6665 [36] and IETF RFC 7647 [52], and in accordance with the UE procedures specified in 3GPP TS 24.229 [5], with the clarifications given below.

The MCData client:

1) shall set the Request URI of the SIP REFER request to the session identity of the pre-established session;

2) shall set the Refer-To header field of the SIP REFER request as specified in IETF RFC 3515 [51] with a Content-ID ("cid") Uniform Resource Locator (URL) as specified in IETF RFC 2392 [33] that points to an application/resource-lists MIME body as specified in IETF RFC 5366 [18], and with the Content-ID header field set to this "cid" URL;

3) shall include in the application/resource-lists MIME body a single <entry> element containing a "uri" attribute set to the MCData group identity, extended with the following parameters in the headers portion of the SIP URI:

NOTE: Characters that are not formatted as ASCII characters are escaped in the following parameters in the headers portion of the SIP URI.

a) an hname "body" parameter populated with:

i) an application/sdp MIME body containing an SDP offer with media attributes specified in clause 9.2.3.2.1, if a group standalone SDS message is requested;

ii) an application/vnd.3gpp.mcdata-info MIME body with:

A) if a group standalone SDS message is requested, the <request-type> element set to a value of "group-sds". If a group SDS session is requested, the <request-type> element set to a value of "group-sds-session";

B) the <mcdata-request-uri> element set to the MCData group identity;

C) the <mcdata-client-id> element set to the MCData client ID of the originating MCData client;

D) if the MCData client is aware of active functional aliases and if an active functional alias is to be included in the SIP REFER request, the <functional-alias-URI> element set to the URI of the used functional alias; and

E) if the MCData user has requested an application priority, the <anyExt> element with the <user-requested-priority> element set to the user provided value;

3A) if the MCData user has requested the origination of an MCData emergency group communication or is originating an MCData group communication and the MCData emergency state is already set:

a) if this is an authorised request for an MCData emergency group communication as determined by the procedures of clause 6.2.8.1.8, shall execute the procedures in clause 6.2.8.1.1; and

b) if this is an unauthorised request for an MCData emergency group communication as determined in step a) above, should indicate to the MCData user that they are not authorised to initiate an MCData emergency group communication;

3B) if the MCData client emergency group state for this group is set to "MDEG 2: in-progress" or "MDEG 4: confirm-pending", shall include the Resource-Priority header field and execute the procedures in clause 6.2.8.1.2;

3C) if the MCData user has requested the origination of an MCData imminent peril group communication:

a) if this is an authorised request for an MCData imminent peril group communication as determined by the procedures of clause 6.2.8.1.8, shall execute the procedures in clause 6.2.8.1.9; and

b) if this is an unauthorised request for an MCData imminent peril group communication as determined in step a) above, should indicate to the MCData user that they are not authorised to initiate an MCData imminent peril group communication;

3D) if the MCData client imminent peril group state for this group is set to "MDIG 2: in-progress" or "MDIG 4: confirm-pending", shall include the Resource-Priority header field and execute the procedures in clause 6.2.8.1.12;

4) shall include a P-Preferred-Service header field set to the ICSI value "urn:urn-7:3gpp-service.ims.icsi.mcdata.sds" (coded as specified in 3GPP TS 24.229 [5]), according to IETF RFC 6050 [7];

5) may include a P-Preferred-Identity header field in the SIP INVITE request containing a public user identity as specified in 3GPP TS 24.229 [5];

6) shall include the following according to IETF RFC 4488 [53]:

a) the option tag "norefersub" in the Supported header field; and

b) the value "false" in the Refer-Sub header field;

7) shall include a Target-Dialog header field as specified in IETF RFC 4538 [54] identifying the pre-established session;

8) shall include the g.3gpp.mcdata.sds media feature tag in the Contact header field of the SIP REFER request according to IETF RFC 3840 [16]; and

9) shall send the SIP REFER request according to 3GPP TS 24.229 [5].

On receiving a final SIP 2xx response to the SIP REFER request, the MCData client:

1) shall interact with the media plane as specified in 3GPP TS 24.582 [15].

On receiving a SIP 4xx response, SIP 5xx response or a SIP 6xx response to the SIP REFER request:

1) if the MCData emergency group communication state is set to "MDEGC 2: emergency-communication-requested" or "MDEGC 3: emergency-communication-granted" or if the MCData imminent peril group communication state is set to "MDIGC 2: imminent-peril-communication-requested" or "MDIGC 3: imminent-peril-communication-granted", the MCData client shall perform the actions specified in clause 6.2.8.1.5 and shall skip the remaining steps.

On receiving a SIP re-INVITE request within the pre-established session targeted by the sent SIP REFER request, the MCData client:

0) if the sent SIP REFER request was a request for an MCData emergency group communication or an MCData imminent peril group communication, the MCData client:

   a) shall perform the actions specified in clause 6.2.8.1.16;

   b) shall check if a Resource-Priority header field is included in the incoming SIP re-INVITE request and may perform further actions outside the scope of this specification to act upon an included Resource-Priority header field as specified in 3GPP TS 24.229 [5];

   c) shall accept the SIP re-INVITE request and generate a SIP 200 (OK) response according to rules and procedures of 3GPP TS 24.229 [5];

   d) shall include an SDP answer in the SIP 200 (OK) response to the SDP offer in the incoming SIP re-INVITE request according to 3GPP TS 24.229 [5], based upon the parameters already negotiated for the pre-established session; and

   e) shall send the SIP 200 (OK) response towards the participating MCData function according to rules and procedures of 3GPP TS 24.229 [5].

1) if the <mcdata-communication-state> element in the application/vnd.3gpp.mcdata-info+xml MIME body of the SIP INVITE request is set to a value of "establish-success":

   i) shall notify MCData user about successful the MCData communication establishment;

2) if the <mcdata-communication-state> element in the application/vnd.3gpp.mcdata-info+xml MIME body of the SIP INVITE request is set to a value of "establish-fail":

   i) shall notify MCData user about the MCData communication establishment failure; and

3) shall interact with the media plane as specified in 3GPP TS 24.582 [15].

On communication release by interaction with the media, if the sent SIP REFER request was a request for an MCData emergency group communication or an MCData imminent peril group communication, the MCData client shall perform the procedures specified in clause 6.2.8.1.17.

On receiving a SIP INFO request where the Request-URI contains an MCData session ID identifying an ongoing group session, the MCData client shall perform the procedures specified in clause 6.2.8.1.13.

6.1.23.3 Test description

6.1.23.3.1 Pre-test conditions

Test configuration:

- Single cell configuration according to TS 37.579-1 [2] clause 5.2.2.2.1.

Preamble:

- The UE has performed procedure 'Initial registration' as described in TS 37.579-1 [2] clause 5.4.2 with the following clarifications:

  - The <max-payload-size-sds-cplane-bytes> element of the MCData Service Configuration document shall be set to 0 to force the MCData client to send the data using the media plane.

  - In the group configuration document the <preconfigured-group-use-only> element is set to "true".

- The UE has performed procedure 'MCX pre-established session establishment' as described in TS 37.579-1 [2] clause 5.3.3.

- UE States at the end of the preamble:

  - The UE is in RRC_IDLE state.

  - The client is registered for MCData.

  - A pre-established session is established.

6.1.23.3.2 Test procedure sequence

Table 6.1.23.3.2-1: Main Behaviour

St	Procedure	Message Sequence		TP	Verdict
		U - S	Message		
1	Make the UE (MCData client) send a group session SDS message using the pre-established session with disposition request "**DELIVERY**". (NOTE 1)	-	-	-	-
2	Check: Does the UE (MCData client) send a SIP REFER request to establish a MCData call within the next 5s?	-	REFER	1	F
-	EXCEPTION: Step 3a1 describes behaviour that depends on the UE implementation; the "lower case letter" identifies a step sequence that take place if the UE displays an indication to the MCData user that group session SDS messagesare not allowed on the indicated group.	-	-	-	-
3a1	IF pc_MCX_DisplayInfoSDSNotAllowedOnGroup THEN Check: Does the UE (MCData client) indicate to the MCData user that group SDS is not allowed on the indicated group? (NOTE 1)	-	-	1	P
NOTE 1: This is expected to be done via a suitable implementation dependent MMI.					

6.1.23.3.3 Specific message contents

Table 6.1.23.3.3-1: Group Configuration document (Preamble)

Derivation Path: TS 37.579-1 [2], Table 5.5.7.4-2				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
list-service[1]				
mcpttgi:preconfigured-group-use-only	true		TS 24.481 [31] clause 7.2.4.2	

6.2 File Distribution

6.2.1 On-network / File Distribution (FD) / FD Using HTTP / One-to-one Standalone FD / Non-Mandatory Download / FILE DOWNLOAD REQUEST ACCEPTED / FILE DOWNLOAD COMPLETED / FILE DOWNLOAD REQUEST REJECTED / FILE DOWNLOAD DEFERRED / Client Originated (CO)

6.2.1.1 Test Purpose (TP)

(1)

```
with { UE (MCDATA Client) registered and authorised for MCDATA Service }
ensure that {
  when { MCDATA User wants to send a file that is larger than <max-data-size-auto-recv-bytes> via a
standalone one-to-one FD message with a non-mandatory download and with a disposition request of
"FILE DOWNLOAD COMPLETED UPDATE", and, the UE (MCDATA Client) is unaware of the URL of the Media
Storage Function }
    then { UE (MCDATA Client) sends a SIP MESSAGE to find the URL of the Media Storage Function and
responds to a SIP MESSAGE that contains the URL of the Media Storage Function with a SIP 200 (OK)
message }
            }
```

(2)

```
with { UE (MCDATA Client) registered and authorised for MCDATA Service }
ensure that {
  when { MCDATA User wants to send a file that is larger than <max-data-size-auto-recv-bytes> via a
standalone one-to-one FD message with a non-mandatory download and with a disposition request of
"FILE DOWNLOAD COMPLETED UPDATE", and, the UE (MCDATA Client) is aware of the URL of the Media
Storage Function }
    then { UE (MCDATA Client) uploads the file to the Media Storage Function via an HTTP POST
message and then sends the URL of the file location to the recipient via a SIP MESSAGE message }
            }
```

(3)

```
with { MCDATA User having requesting the sending of a file that is larger than <max-data-size-auto-
recv-bytes> via a standalone one-to-one FD message with a non-mandatory download and with a
disposition request of "FILE DOWNLOAD COMPLETED UPDATE" and the UE (MCDATA Client) having sent the
URL of the file location to the recipient }
ensure that {
  when { UE (MCDATA Client) receives a FD notification via a SIP MESSAGE with disposition
notification type of "FILE DOWNLOAD REQUEST REJECTED" }
    then { UE (MCDATA Client) responds to the SIP MESSAGE with a SIP 200 (OK) message and delivers
the notification that the remote Client has not accepted the download to the MCDATA User }
            }
```

(4)

```
with { MCDATA User having requesting the sending of a file that is larger than <max-data-size-auto-
recv-bytes> via a standalone one-to-one FD message with a non-mandatory download and with a
disposition request of "FILE DOWNLOAD COMPLETED UPDATE" and the UE (MCDATA Client) having sent the
URL of the file location to the recipient }
ensure that {
  when { UE (MCDATA Client) receives a FD notification via a SIP MESSAGE with disposition
notification type of "FILE DOWNLOAD DEFERRED", followed by a SIP MESSAGE with disposition
notification type of "FILE DOWNLOAD REQUEST ACCEPTED", followed by SIP MESSAGE with disposition
notification type of "FILE DOWNLOAD COMPLETED" }
    then { UE (MCDATA Client) responds to each SIP MESSAGE with a SIP 200 (OK) message and delivers
suitable notification on the respective remote Client action to the MCDATA User }
            }
```

6.2.1.2 Conformance requirements

References: The conformance requirements covered in the current TC are specified in: TS 24.282, clauses 10.2.1.3.2, 10.2.2.1, 10.2.4.2.1, 12.2.1.2. The following represents a copy/paste extraction of the requirements relevant to the test

purpose; any references within the copy/paste text should be understood within the scope of the core spec they have been copied from. Unless otherwise stated, these are Rel-14 requirements.

[TS 24.282, clause 10.2.1.3.2]

To discover the absolute URI of the media storage function, the MCData client shall generate a SIP MESSAGE request towards the participating MCData function, in accordance with 3GPP TS 24.229 [5] and IETF RFC 3428 [6] with the clarifications given below.

The MCData client:

1) shall build the SIP MESSAGE request as specified in subclause 6.2.4.1;

2) shall follow the rules specified in subclause 6.4 for the handling of MIME bodies in a SIP message when processing the remaining steps in this subclause;

3) shall insert in the SIP MESSAGE request an application/vnd.3gpp.mcdata-info+xml MIME body with a <request-type> element containing the value "msf-disc-req";

4) if the upload of a file is for a group standalone FD request, shall include in an application/vnd.3gpp.mcdata-info+xml MIME body, the <mcdata-calling-group-id> element set to the required MCData group identity; and

NOTE 1: The absence of a group identity in the <mcdata-calling-group-id> element of the application/vnd.3gpp.mcdata-info+xml MIME body implies that the MCData client intends to upload a file for a one-to-one FD request. In this case, the participating MCData function identifies the MCData ID of the user from the binding between the public user identity and the MCData ID.

5) shall send the SIP MESSAGE request according to rules and procedures of 3GPP TS 24.229 [5].

On receipt of a "SIP MESSAGE request for absolute URI discovery response", the MCData client:

1) shall store the absolute URI found in the <mcdata-controller-psi> element;

2) shall generate a SIP 200 (OK) response according to rules and procedures of 3GPP TS 24.229 [5]; and

3) shall send the SIP 200 (OK) response towards the MCData server according to rules and procedures of 3GPP TS 24.229 [5].

[TS 24.282, clause 10.2.2.1]

If the media storage client is not aware of the absolute URI of the media storage function, the media storage client shall request the MCData client to discover the absolute URI associated with the media storage function by following the procedures in subclause 10.2.1.3.

The media storage client shall send HTTP requests over a TLS connection as specified for the HTTP client in the UE in annex A of 3GPP TS 24.482 [24].

NOTE 1: The HTTP client encodes the MCData ID in the bearer access token of the Authorization header field of an HTTP request as specified in 3GPP TS 24.482 [24].

NOTE 2: The HTTP client always sends the HTTP requests to an HTTP proxy. Annex A of 3GPP TS 24.482 [24] indicates how the HTTP proxy forwards the HTTP request to the HTTP server.

To upload a file to media storage function, the media storage client:

1) shall generate an HTTP POST request as specified in IETF RFC 7230 [22] and IETF RFC 7231 [23];

2) shall set the Request-URI to the absolute URI identifying the resource on a media storage function;

3) shall set the Host header field to a hostname identifying the media storage function;

4) shall set the Content-Type header field to multipart/mixed and with a boundary delimiter parameter set to any chosen value;

5) if the file upload is for one-to-one file distribution, shall insert an application/vnd.3gpp.mcdata-info+xml MIME body with:

a) the <request-type> element set to a value of "one-to-one-fd"; and

b) the <mcdata-calling-user-id> element set to the originating MCData ID;

6) if the file upload is for group file distribution, shall insert an application/vnd.3gpp.mcdata-info+xml MIME body with:

a) the <request-type> element set to a value of "group-fd";

b) the <mcdata-request-uri> element set to the MCData group identity; and

c) the <mcdata-calling-user-id> element set to the originating MCData ID;

7) if end-to-end security is required for a one-to-one communication, the MCData client protects the binary data representing the file and prefixes the protected binary data with security parameters as described in 3GPP TS 33.180 [26];

8) if

i) end-to-end security is not required for a one-to-one communication, or

ii) the file upload is for group file distribution;

shall include the binary data representing the file with Content-Type field set to application/octet-stream and Content-Length field set to the file size; and

9) shall send the HTTP POST request towards the media storage function.

On receipt of a HTTP 201 Created containing a Location header field with a URL identifying the location of the resource where the file has been stored on the media storage function, then the media storage client shall store this information.

[TS 24.282, clause 10.2.4.2.1]

The MCData client shall generate a SIP MESSAGE request in accordance with 3GPP TS 24.229 [5] and IETF RFC 3428 [6] with the clarifications given below.

The MCData client:

1) shall build the SIP MESSAGE request as specified in subclause 6.2.4.1;

2) if a one-to-one standalone FD message is to be sent shall insert in the SIP MESSAGE request:

a) an application/resource-lists+xml MIME body with the MCData ID of the target MCData user, according to rules and procedures of IETF RFC 4826 [9]; and

b) an application/vnd.3gpp.mcdata-info+xml MIME body with a <request-type> element set to a value of "one-to-one-fd";

…

4) shall generate a standalone FD message as specified in subclause 6.2.2.2; and

5) shall send the SIP MESSAGE request according to rules and procedures of 3GPP TS 24.229 [5].

[TS 24.282, clause 12.2.1.2]

Upon receipt of a:

"SIP MESSAGE request for SDS disposition notification for terminating MCData client"; or

"SIP MESSAGE request for FD disposition notification for terminating MCData client";

the MCData client:

1) shall decode the contents of the application/vnd.3gpp.mcdata-signalling MIME body; and

2) shall deliver the notification to the user or application.

6.2.1.3 Test description

6.2.1.3.1 Pre-test conditions

Test configuration:

- Single cell configuration according to TS 37.579-1 [2] clause 5.2.2.2.1.
- Test File 1 for CO FD as specified in annex A.2.1 and test File 2 for CO FD as specified in Annex A.2.2 are available at the UE for upload.

Preamble:

- The UE has performed procedure 'Initial registration' as described in TS 37.579-1 [2] clause 5.4.2 with the following clarifications:
  - In the <on-network> element of the MCData Service Configuration document the <max-data-size-auto-recv-bytes> element of the <tx-and-rx-control> element shall be set to 0 to indicate non-mandatory download independent from the file size.
- UE States at the end of the preamble:
  - The UE is in RRC_IDLE state.
  - The client is registered for MCData.

6.2.1.3.2 Test procedure sequence

Table 6.2.1.3.2-1: Main Behaviour

St	Procedure	Message Sequence		TP	Verdict
		U - S	Message		
1-12	Void	-	-	-	-
13	Make the UE (MCData client) send test file 1 (Annex A.2.1) for CO one-to-one FD over HTTP for non-mandatory download and with disposition request "FILE DOWNLOAD COMPLETED UPDATE". (NOTE 1, NOTE 3)	-	-	-	-
14	Check: Does the UE (MCData client) correctly perform procedure '**discovery of the absolute URI of the media storage function (one-to-one communication)**' as described in TS 37.579-1 [2] Table 5.3C.8.3-1 ?	-	-	1	P
15	Check: Does the UE (MCData client) correctly perform procedure '**FD file upload using HTTP**' as described in TS 37.579-1 [2] Table 5.3C.10.3-1?	-	-	2	P
15A	Check: Is the content of the uploaded file the same as specified in annex A.2.1?	-	-	2	P
16-18	Void	-	-	-	-
19	Check: Does the UE (MCData client) correctly perform procedure '**MCX SIP MESSAGE CT**' as described in TS 37.579-1 [2] Table 5.3.33.3-1 **to receive an FD NOTIFICATION with disposition notification type "FILE DOWNLOAD REQUEST REJECTED"** for the FD message sent at step 15?	-	-	3	P
20	Void	-	-	-	-
21	Check: Does the UE (MCData client) notify the user that the remote client has rejected the download? (NOTE 1)	-	-	3	P
22	Make the UE (MCData client) send test file 2 (Annex A.2.2) for CO one-to-one FD over HTTP for non-mandatory download and with disposition request "FILE DOWNLOAD COMPLETED UPDATE". (NOTE 1, NOTE 2, NOTE 3)	-	-	-	-
-	EXCEPTION: Step 23a1 describes behaviour that depends on UE implementation.	-	-	-	-
23a1	IF the client needs to discover again the absolute URI of the media storage function THEN the UE (MCData client) performs procedure '**Discovery of the absolute URI of the media storage function (one-to-one communication)**' as described in TS 37.579-1 [2] Table 5.3C.8.3-1.	-	-	-	-
23a2 - 23a4	Void	-	-	-	-
24	Check: Does the UE (MCData client) correctly perform procedure '**FD file upload using HTTP**' as described in TS 37.579-1 [2] Table 5.3C.10.3-1?	-	-	2	P
24A	Check: Is the content of the uploaded file the same as specified in annex A.2.2?	-	-	2	P
25-27	Void	-	-	-	-
28	Check: Does the UE (MCData client) correctly perform procedure '**MCX SIP MESSAGE CT**' as described in TS 37.579-1 [2] Table 5.3.33.3-1 **to receive an FD NOTIFICATION with disposition notification type "FILE DOWNLOAD DEFERRED"** for the FD message sent at step 24?	-	-	4	P
29	Void	-	-	-	-

30	Check: Does the UE (MCData client) notify the user that the remote client has deferred the acceptance of the download? (NOTE 1)	-	-	4	P
31	Check: Does the UE (MCData client) correctly perform procedure '**MCX SIP MESSAGE CT**' as described in TS 37.579-1 [2] Table 5.3.33.3-1 **to receive an FD NOTIFICATION with disposition notification type "FILE DOWNLOAD REQUEST ACCEPTED"** for the FD message sent at step 24?	-	-	4	P
32	Void	-	-	-	-
33	Check: Does the UE (MCData client) notify the user that the remote client has accepted the download? (NOTE 1)	-	-	4	P
34	Check: Does the UE (MCData client) correctly perform procedure '**MCX SIP MESSAGE CT**' as described in TS 37.579-1 [2] Table 5.3.33.3-1 **to receive an FD NOTIFICATION with disposition notification type "FILE DOWNLOAD COMPLETED"** for the FD message sent at step 24?	-	-	4	P
35	Void	-	-	-	-
36	Check: Does the UE (MCData client) notify the user that the remote client has completed the download? (NOTE 1)	-	-	4	P
NOTE 1: This is expected to be done via a suitable implementation dependent MMI. NOTE 2: To avoid unpredicted behaviour at the UE side due to the file upload in the previous steps, the UE shall attempt to upload a different file here. NOTE 3: Test file 1 and 2 for CO FD as specified in annex A.2.1 and A.2.2.					

6.2.1.3.3 Specific message contents

Table 6.2.1.3.3-1..6: Void

Table 6.2.1.3.3-7: HTTP POST from the UE (steps 15, 24, Table 6.2.1.3.2-1; step 2, TS 37.579-1 [2] Table 5.3C.10.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.4.3-1, condition FD_HTTP				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part		**MCData-Info**		
MIME-part-body	MCData-Info as described in Table 6.2.1.3.3-8			

Table 6.2.1.3.3-8: MCData-Info (Table 6.2.1.3.3-7)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.2.1-3				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
mcdata-info				
mcdata-Params				
request-type	"one-to-one-fd"			
mcdata-calling-user-id	px_MCData_ID_User_A	NOTE: the element is not encrypted		

Table 6.2.1.3.3-9..10: Void

Table 6.2.1.3.3-11: HTTP 201 Created from the SS (step 15, Table 6.2.1.3.2-1; step 3, TS 37.579-1 [2] Table 5.3C.10.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.4.7-1, condition FD_HTTP

Table 6.2.1.3.3-11A: HTTP 201 Created from the SS (step 24, Table 6.2.1.3.2-1; step 3, TS 37.579-1 [2] Table 5.3C.10.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.4.7-1, condition FD_HTTP				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Location				
uri	tsc_MCData_MSF_URI & "/file-location-2"			

Table 6.2.1.3.3-12: SIP MESSAGE from the UE (steps 15, 24, Table 6.2.1.3.2-1; step 4, TS 37.579-1 [2] Table 5.3C.10.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.7.1-1, condition MCDATA_FD, RESOURCE_LISTS, MCDATA_SIGNALLING				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part		**MCData-Info**		
MIME-part-body	MCData-Info as described in Table 6.2.1.3.3-13			
MIME body part		**MCData Data signalling message**		
MIME-part-body	MCData Protected Payload Message containing FD SIGNALLING PAYLOAD as described in Table 6.2.1.3.3-13A			

Table 6.2.1.3.3-13: MCData-Info (Table 6.2.1.3.3-12)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.2.1-3, condition MCD_1to1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
mcdata-info				
mcdata-Params				
request-type	"one-to-one-fd"			

Table 6.2.1.3.3-13A: FD SIGNALLING PAYLOAD (Table 6.2.1.3.3-12)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.5-1, condition FD_HTTP

Table 6.2.1.3.3-14: SIP MESSAGE from the SS (step 19, Table 6.2.1.3.2-1; step 2, TS 37.579-1 [2] Table 5.3.33.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.7.2-1, condition MCDATA_FD, MCDATA_SIGNALLING				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part		**MCData Data signalling message**		
MIME-part-body	MCData Protected Payload Message containing FD NOTIFICATION as described in Table 6.2.1.3.3-16			

Table 6.2.1.3.3-15: Void

Table 6.2.1.3.3-16: FD NOTIFICATION (Table 6.2.1.3.3-14)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.8-1, condition FD_REJECTED

Table 6.2.1.3.3-17: SIP MESSAGE from the SS (step 28, Table 6.2.1.3.2-1; step 2, TS 37.579-1 [2] Table 5.3.33.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.7.2-1, condition MCDATA_FD, MCDATA_SIGNALLING				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part		**MCData Data signalling message**		
MIME-part-body	MCData Protected Payload Message containing FD NOTIFICATION as described in Table 6.2.1.3.3-18			

Table 6.2.1.3.3-18: FD NOTIFICATION (Table 6.2.1.3.3-17)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.8-1, condition FD_DEFERRED

Table 6.2.1.3.3-19: SIP MESSAGE from the SS (step 31, Table 6.2.1.3.2-1; step 2, TS 37.579-1 [2] Table 5.3.33.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.7.2-1, condition MCDATA_FD, MCDATA_SIGNALLING				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part		**MCData Data signalling message**		
MIME-part-body	MCData Protected Payload Message containing FD NOTIFICATION as described in Table 6.2.1.3.3-20			

Table 6.2.1.3.3-20: FD NOTIFICATION (Table 6.2.1.3.3-19)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.8-1, condition FD_ACCEPTED

Table 6.2.1.3.3-21: SIP MESSAGE from the SS (step 34, Table 6.2.1.3.2-1; step 2, TS 37.579-1 [2] Table 5.3.33.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.7.2-1, condition MCDATA_FD, MCDATA_SIGNALLING				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part		**MCData Data signalling message**		
MIME-part-body	MCData Protected Payload Message containing FD NOTIFICATION as described in Table 6.2.1.3.3-22			

Table 6.2.1.3.3-22: FD NOTIFICATION (Table 6.2.1.3.3-21)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.8-1, condition FD_COMPLETED

6.2.2 On-network / File Distribution (FD) / FD Using HTTP / One-to-one Standalone FD / Non-Mandatory Download / Before TDU2 Timers Expires / FILE DOWNLOAD REQUEST ACCEPTED / FILE DOWNLOAD COMPLETED / FILE DOWNLOAD REQUEST REJECTED / FILE DOWNLOAD DEFERRED / FD Client Terminated (CT)

6.2.2.1 Test Purpose (TP)

(1)

```
with { UE (MCDATA Client) registered and authorised for MCDATA Service }
ensure that {
  when { UE (MCDATA Client) receives a SIP MESSAGE message for a standalone one-to-one FD message
with a non-mandatory download and with a disposition of "FILE DOWNLOAD COMPLETE UPDATE" }
    then { UE (MCDATA Client) responds with a SIP 200 (OK) message and notifies the MCDATA User
about the incoming FD request }
            }
```

(2)

```
with { UE (MCDATA Client) having received a standalone one-to-one FD message with a non-mandatory
download and with a disposition of "FILE DOWNLOAD COMPLETE UPDATE" }
ensure that {
  when { the MCDATA User requests to accept the FD request }
    then { UE (MCDATA Client) generates an FD NOTIFICATION indicating acceptance of the FD request
and attempts to download the file with an HTTP GET message }
            }
```

(3)

```
with { MCDATA User having accepted an FD request with a disposition of "FILE DOWNLOAD COMPLETE
UPDATE" }
ensure that {
  when { UE (MCDATA Client) has successfully downloaded the file }
    then { UE (MCDATA Client) notifies the MCDATA User that the file has successfully downloaded and
generates an FD NOTIFICATION indicating the successful download of the file }
            }
```

(4)

```
with { UE (MCDATA Client) having received a standalone one-to-one FD message with a non-mandatory
download and with a disposition of "FILE DOWNLOAD COMPLETE UPDATE" }
ensure that {
```

```
  when { the MCDATA User requests to reject the FD request }
    then { UE (MCDATA Client) generates an FD NOTIFICATION indicating the rejection of the FD
request }
            }
```

(5)

```
with { UE (MCDATA Client) having received a standalone one-to-one FD message with a non-mandatory
download and with a disposition of "FILE DOWNLOAD COMPLETE UPDATE" }
ensure that {
  when { the MCDATA User requests to defer the FD request before the expiration of the TDU2 (FD non-
mandatory download timer) timer }
    then { UE (MCDATA Client) generates an FD NOTIFICATION indicating the deferral of the FD request
}
            }
```

6.2.2.2 Conformance requirements

References: The conformance requirements covered in the current TC are specified in: TS 24.282, clauses 10.2.4.2.2, 10.2.1.2.3, 12.2.1.1, 10.2.3.1. The following represents a copy/paste extraction of the requirements relevant to the test purpose; any references within the copy/paste text should be understood within the scope of the core spec they have been copied from. Unless otherwise stated, these are Rel-14 requirements.

[TS 24.282, clause 10.2.4.2.2]

Upon receipt of a "SIP MESSAGE request for FD using HTTP for terminating MCData client", the MCData client:

1) may reject the SIP MESSAGE request if there are not enough resources to handle the SIP MESSAGE request;

2) if the SIP MESSAGE request is rejected in step 1), shall respond towards the participating MCData function with a SIP 480 (Temporarily unavailable) response and skip the rest of the steps of this subclause;

3) shall generate a SIP 200 (OK) response according to rules and procedures of 3GPP TS 24.229 [5];

4) shall send the SIP 200 (OK) response towards the MCData server according to rules and procedures of 3GPP TS 24.229 [5]; and

5) shall handle the received message as specified in subclause 10.2.1.2.

[TS 24.282, clause 10.2.1.2.3]

The MCData client:

1) if the FD SIGNALLING PAYLOAD message does not contain an Application ID IE:

   a) shall determine that the payload contained in the Payload IE in the FD SIGNALLING PAYLOAD message is for user consumption;

   b) shall notify the user about the incoming FD request; and

   c) if the FD SIGNALLING PAYLOAD message contains a Metadata IE, shall deliver the contents of the Metadata IE to the user;

2) if the FD SIGNALLING PAYLOAD message contains an Application ID IE:

   a) shall determine that the payload contained in the Payload IE in the FD SIGNALLING PAYLOAD message is not for user consumption;

   b) if the Application ID value is unknown, shall discard the FD message and exit this subclause;

   c) if the Application ID value is known, shall notify the application of the incoming FD request; and

NOTE 1: If FD request is addressed to a non-MCData application that is not running, the MCData client starts the local non-MCData application.

   d) if the FD SIGNALLING PAYLOAD message contains a Metadata IE, shall deliver the contents of the Metadata IE to the application;

3) shall start a timer TDU2 (FD non-mandatory download timer) with the timer value as specified in subclause F.2.3;

4) shall wait for the user or application to request to download the file indicated by file URL in the Payload data in the Payload IE in the FD SIGNALLING PAYLOAD message;

5) if the user or application accepts or rejects or decides to defer the FD request, shall stop timer TDU2 (FD non-mandatory download timer);

6) if the user deferred the FD request while the timer TDU2 (FD non-mandatory download timer) was running, shall generate an FD NOTIFICATION indicating deferral of the FD request as specified in subclause 12.2.1.1;

NOTE 2: Once the timer TDU2 (FD non-mandatory download timer) has expired the FD request can only be accepted or rejected with an appropriate action by the MCData client.

NOTE 3: Once the timer TDU2 (FD non-mandatory download timer) has expired, no action is taken by the MCData client if the FD request is deferred.

7) if the user or application rejects the FD request, shall generate an FD NOTIFICATION indicating rejection of the FD request as specified in subclause 12.2.1.1 and shall exit this subclause; and

8) if the user accepts the FD request:

   a) shall generate an FD NOTIFICATION indicating acceptance of the FD request as specified in subclause 12.2.1.1;

   b) if the FD SIGNALLING PAYLOAD message contains a new Conversation ID, shall instantiate a new conversation with the Message ID in the FD SIGNALLING PAYLOAD identifying the first message in the conversation thread;

   c) if the FD SIGNALLING PAYLOAD message contains an existing Conversation ID and:

      i) if the FD SIGNALLING PAYLOAD message does not contain an InReplyTo message ID, shall use the Message ID in the FD SIGNALLING PAYLOAD to identify a new message in the existing conversation thread; and

      ii) if the FD SIGNALLING PAYLOAD message contains an InReplyTo message ID, shall associate the message to an existing message in the conversation thread as identified by the InReplyTo message ID in the FD SIGNALLING PAYLOAD, and use the Message ID in the FD SIGNALLING PAYLOAD to identify the new message;

   d) may store the Conversation ID, Message ID, InReplyTo message ID and Date and time in local storage;

   e) shall attempt to download the file as identified by the file URL in the Payload IE in the FD SIGNALLING PAYLOAD message, as specified in subclause 10.2.3.1; and

   f) if the received FD SIGNALLING PAYLOAD message contains an FD disposition request type IE requesting a file download completed update, then after the file download has been successfully downloaded, shall generate an FD NOTIFICATION by following the procedures in subclause 12.2.1.1.

[TS 24.282, clause 12.2.1.1]

The MCData client shall follow the procedures in this subclause to:

- indicate to an MCData client that an SDS message was delivered, read or delivered and read when the originating client requested a delivery, read or delivery and read report;

- indicate to the participating MCData function serving the MCData user that an SDS message was undelivered. The participating MCData function can store the message for later re-delivery;

- indicate to an MCData client that a request for FD was accepted, deferred or rejected; or

- indicate to an MCData client that a file download has been completed;

Before sending a disposition notification the MCData client needs to determine:

- the group identity related to an SDS or FD message request received as part of a group communication. The MCData client determines the group identity from the contents of the <mcdata-calling-group-id> element contained in the application/vnd.3gpp.mcdata-info+xml MIME body of the incoming SDS or FD message request; and

- the MCData user targeted for the disposition notification. The MCData client determines the targeted MCData user from the contents of the <mcdata-calling-user-id> element contained in the application/vnd.3gpp.mcdata-info+xml MIME body of the incoming SDS or FD message request.

The MCData client shall generate a SIP MESSAGE request in accordance with 3GPP TS 24.229 [5] and IETF RFC 3428 [6] with the clarifications given below.

The MCData client:

1) shall build the SIP MESSAGE request as specified in subclause 6.2.4.1;

2) shall follow the rules specified in subclause 6.4 for the handling of MIME bodies in a SIP message when processing the remaining steps in this subclause;

3) shall insert in the SIP MESSAGE request an application/resource-lists+xml MIME body containing the MCData ID of the targeted MCData user, according to rules and procedures of IETF RFC 5366 [18];

4) void;

5) if sending a disposition notification in response to an MCData group data request, shall include an <mcdata-calling-group-id> element set to the MCData group identity in the application/vnd.3gpp.mcdata-info+xml MIME body;

6) if requiring to send an SDS notification, shall generate an SDS NOTIFICATION message and include it in the SIP MESSAGE request as specified in subclause 6.2.3.1;

7) if requiring to send an FD notification, shall generate an FD NOTIFICATION message and include it in the SIP MESSAGE request as specified in subclause 6.2.3.2; and

8) shall send the SIP MESSAGE request according to rules and procedures of 3GPP TS 24.229 [5].

[TS 24.282, clause 10.2.3.1]

The media storage client on the MCData client shall send HTTP requests over a TLS connection as specified for the HTTP client in the UE, in annex A of 3GPP TS 24.482 [24].

NOTE 1: The HTTP client encodes the MCData ID in the bearer access token of the Authorization header field of an HTTP request as specified in 3GPP TS 24.482 [24].

NOTE 2: The HTTP client always sends the HTTP requests to an HTTP proxy. Annex A of 3GPP TS 24.482 [24] indicates how the HTTP proxy forwards the HTTP request to the HTTP server.

To download a file from the media storage function on the controlling MCData function, the media storage client on the MCData client:

1) shall generate an HTTP GET request as specified in IETF RFC 7230 [22] and IETF RFC 7231 [23] with a Request-URI set to an absolute URI identifying the URL of the file being requested from the media storage function on the controlling MCData function; and

2) shall send the HTTP GET request towards the media storage function on the controlling MCData function.

On receipt of a HTTP 200 OK response containing the requested file, the MCData client shall notify the user or application that the file has been successfully downloaded.

6.2.2.3 Test description

6.2.2.3.1 Pre-test conditions

Test configuration:

- Single cell configuration according to TS 37.579-1 [2] clause 5.2.2.2.1.
- Test files downloaded or received at previous test runs are deleted.

Preamble:

- The UE has performed procedure 'Initial registration' as described in TS 37.579-1 [2] clause 5.4.2 with the following clarifications:
  - In the <on-network> element of the MCData Service Configuration document the <max-data-size-auto-recv-bytes> element of the <tx-and-rx-control> element shall be set to 0 to indicate non-mandatory download independent from the file size.
  - TDU2 (FD non-mandatory download timer) is set to the default value of 60 seconds.
- UE States at the end of the preamble:
  - The UE is in RRC_IDLE state.
  - The client is registered for MCData.

6.2.2.3.2 Test procedure sequence

Table 6.2.2.3.2-1: Main Behaviour

St	Procedure	Message Sequence		TP	Verdict
		U - S	Message		
1	Check: Does the UE (MCData client) correctly perform procedure '**MCX SIP MESSAGE CT**' as described in TS 37.579-1 [2] Table 5.3.33.3-1 **to receive an FD message for one-to-one file distribution with disposition request "FILE DOWNLOAD COMPLETED UPDATE"**? (NOTE 2)	-	-	1	P
2	Void	-	-	-	-
3	Check: Does the UE (MCData client) notify the user of the incoming FD request? (NOTE 1)	-	-	1	P
4	Make the UE (MCData client) accept the FD request and download the file before timer TDU2 expires. (NOTE 1)	-	-	-	-
5	Check: Does the UE (MCData client) correctly perform procedure '**FD file accept and download using HTTP**' as described in TS 37.579-1 [2] Table 5.3C.11.3-1 to download test file 1? (NOTE 3)	-	-	2,3	P
6-8	Void	-	-	-	-
9	Check: Does the UE (MCData client) notify the user of the file download? (NOTE 1)	-	-	3	P
9A	Check: Has the UE (MCData client) downloaded test file 1 (Annex A.3.1)? (NOTE 1)	-	-	2	P
10-11	Void	-	-	-	-
12	Check: Does the UE (MCData client) correctly perform procedure '**MCX SIP MESSAGE CT**' as described in TS 37.579-1 [2] Table 5.3.33.3-1 **to receive an FD message for one-to-one file distribution with disposition request "FILE DOWNLOAD COMPLETED UPDATE"**? (NOTE 2)	-	-	1	P
13	Void	-	-	-	-
14	Check: Does the UE (MCData client) notify the user of the incoming FD request? (NOTE 1)	-	-	1	P
15	Make the UE (MCData client) reject the FD request before timer TDU2 expires. (NOTE 1)	-	-	-	-
16	Check: Does the UE (MCData client) correctly perform procedure '**CO SDS or FD message transfer using signalling plane**' as described in TS 37.579-1 [2] Table 5.3C.1.3-1 **to send an FD NOTIFICATION with disposition notification type "FILE DOWNLOAD REQUEST REJECTED"?**	-	-	4	P
17	Void	-	-	-	-
18	Check: Does the UE (MCData client) correctly perform procedure '**MCX SIP MESSAGE CT**' as described in TS 37.579-1 [2] Table 5.3.33.3-1 **to receive an FD message for one-to-one file distribution with disposition request "FILE DOWNLOAD COMPLETED UPDATE"**? (NOTE 2)	-	-	1	P
19	Void	-	-	-	-

20	Check: Does the UE (MCData client) notify the user of the incoming FD request? (NOTE 1)	-	-	1	P
21	Make the UE (MCData client) defer the FD request before timer TDU2 expires. (NOTE 1)	-	-	-	-
22	Check: Does the UE (MCData client) correctly perform procedure '**CO SDS or FD message transfer using signalling plane**' as described in TS 37.579-1 [2] Table 5.3C.1.3-1 **to send an FD NOTIFICATION with disposition notification type "FILE DOWNLOAD DEFERRED"?**	-	-	5	P
23	Void	-	-	-	-
24	Make the UE (MCData client) accept the deferred FD request and download the file. (NOTE 1)	-	-	-	-
25	Check: Does the UE (MCData client) correctly perform procedure '**FD file accept and download using HTTP**' as described in TS 37.579-1 [2] Table 5.3C.11.3-1 to download test file 2? (NOTE 3)	-	-	2,3	P
26-28	Void	-	-	-	-
29	Check: Does the UE (MCData client) notify the user of the file download? (NOTE 1)	-	-	3	P
29A	Check: Has the UE (MCData client) downloaded test file 2 (Annex A.3.3)? (NOTE 1)	-	-	2	P
30-31	Void	-	-	-	-

NOTE 1: This is expected to be done via a suitable implementation dependent MMI.
NOTE 2: Timer TDU2 (FD non-mandatory download timer) starts on reception of the FD request via the SIP MESSAGE request.
NOTE 3: Test file 1 and 2 for CT FD as specified in annex A.3.1 and A.3.2.

6.2.2.3.3 Specific message contents

Table 6.2.2.3.3-1: SIP MESSAGE from the SS (steps 1, 12, 18, Table 6.2.2.3.2-1; step 2, TS 37.579-1 [2] Table 5.3.33.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.7.2-1, condition MCDATA_FD, MCDATA_SIGNALLING				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part		**MCData-Info**		
MIME-part-body	MCData-Info as described in Table 6.2.2.3.3-2			
MIME body part		**MCData Data signalling message**		
MIME-part-body	MCData Protected Payload Message containing FD SIGNALLING PAYLOAD as described in Table 6.2.2.3.3-2A			

Table 6.2.2.3.3-2: MCData-Info (Table 6.2.2.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.2.2-3, condition MCD_1to1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
mcdata-info				
mcdata-Params				
request-type	"one-to-one-fd"			

Table 6.2.2.3.3-2A: FD SIGNALLING PAYLOAD (Table 6.2.2.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.6-1, condition FD_HTTP

Table 6.2.2.3.3-3: Void

Table 6.2.2.3.3-4: SIP MESSAGE from the UE (steps 5, 25, Table 6.2.2.3.2-1; step 2, TS 37.579-1 [2] Table 5.3C.11.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.7.1-1, condition MCDATA_FD, RESOURCE_LISTS, MCDATA_SIGNALLING				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part	not present	**MCData-Info**		
MIME body part		**MCData Data signalling message**		
MIME-part-body	MCData Protected Payload Message containing FD NOTIFICATION as described in Table 6.2.2.3.3-5			

Table 6.2.2.3.3-5: FD NOTIFICATION (Table 6.2.2.3.3-4)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.7-1, condition FD_ACCEPTED

Table 6.2.2.3.3-6: HTTP GET from the UE (steps 5, 25, Table 6.2.2.3.2-1; step 4, TS 37.579-1 [2] Table 5.3C.11.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.4.2-1, condition FD_HTTP

Table 6.2.2.3.3-7: HTTP 200 (OK) from the SS (steps 5, 25, Table 6.2.2.3.2-1; step 5, TS 37.579-1 [2] Table 5.3C.11.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.4.6-1, condition FD_HTTP

Table 6.2.2.3.3-8..9: Void

Table 6.2.2.3.3-10: SIP MESSAGE from the UE (steps 5, 25, Table 6.2.2.3.2-1; step 6a1, TS 37.579-1 [2] Table 5.3C.11.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.7.1-1, condition MCDATA_FD, RESOURCE_LISTS, MCDATA_SIGNALLING				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part	not present	**MCData-Info**		
MIME body part		**MCData Data signalling message**		
MIME-part-body	MCData Protected Payload Message containing FD NOTIFICATION as described in Table 6.2.2.3.3-11			

Table 6.2.2.3.3-11: FD NOTIFICATION (Table 6.2.2.3.3-10)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.7-1, condition FD_COMPLETED

Table 6.2.2.3.3-12: SIP MESSAGE from the UE (step 16, Table 6.2.2.3.2-1; step 2, TS 37.579-1 [2] Table 5.3C.1.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.7.1-1, condition MCDATA_FD, RESOURCE_LISTS, MCDATA_SIGNALLING				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part	not present	**MCData-Info**		
MIME body part		**MCData Data signalling message**		
MIME-part-body	MCData Protected Payload Message containing FD NOTIFICATION as described in Table 6.2.2.3.3-13			

Table 6.2.2.3.3-13: FD NOTIFICATION (Table 6.2.2.3.3-12)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.7-1, condition FD_REJECTED

Table 6.2.2.3.3-14: SIP MESSAGE from the UE (step 22, Table 6.2.2.3.2-1; step 2, TS 37.579-1 [2] Table 5.3C.1.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.7.1-1, condition MCDATA_FD, RESOURCE_LISTS, MCDATA_SIGNALLING				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part	not present	**MCData-Info**		
MIME body part		**MCData Data signalling message**		
MIME-part-body	MCData Protected Payload Message containing FD NOTIFICATION as described in Table 6.2.2.3.3-15			

Table 6.2.2.3.3-15: FD NOTIFICATION (Table 6.2.2.3.3-14)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.7-1, condition FD_DEFERRED

6.2.3 On-network / File Distribution (FD) / FD Using HTTP / Group Standalone FD / Non-Mandatory Download / FILE DOWNLOAD REQUEST ACCEPTED / FILE DOWNLOAD COMPLETED / FILE DOWNLOAD REQUEST REJECTED / Client Originated (CO)

6.2.3.1 Test Purpose (TP)

(1)

```
with { UE (MCDATA Client) registered and authorised for MCDATA Service }
ensure that {
  when { the MCDATA User requests to send a Group Standalone FD message with a non-mandatory
download and with a disposition of "FILE DOWNLOAD COMPLETE UPDATE" and the UE (MCDATA Client) is
unaware of the URL of the Media Storage Function }
    then { UE (MCDATA Client) sends a SIP MESSAGE to find the URL of the Media Storage Function and
responds to a SIP MESSAGE that contains the URL of the Media Storage Function with a SIP 200 (OK)
message }
            }
```

(2)

```
with { UE (MCDATA Client) registered and authorised for MCDATA Service }
ensure that {
  when { the MCDATA User requests to send a Group Standalone FD message with a non-mandatory
download and with a disposition of "FILE DOWNLOAD COMPLETE UPDATE" and the UE (MCDATA Client) is
aware of the URL of the Media Storage Function }
    then { UE (MCDATA Client) uploads the file to the Media Storage Function via an HTTP POST
message and then sends the URL of the file location to the recipient via a SIP MESSAGE message }
            }
```

(3)

```
with { UE (MCDATA Client) having sent the URL of the file location to the recipient }
ensure that {
  when { UE (MCDATA Client) receives a FD notification via a SIP MESSAGE message }
    then { UE (MCDATA Client) responds to the SIP MESSAGE message with a SIP 200 (OK) message and
delivers the notification to the MCDATA User }
            }
```

6.2.3.2 Conformance requirements

References: The conformance requirements covered in the current TC are specified in: TS 24.282, clauses 10.2.1.3.2, 10.2.2.1, 10.2.4.2.1, 12.2.1.2. The following represents a copy/paste extraction of the requirements relevant to the test purpose; any references within the copy/paste text should be understood within the scope of the core spec they have been copied from. Unless otherwise stated, these are Rel-14 requirements.

[TS 24.282, clause 10.2.1.3.2]

To discover the absolute URI of the media storage function, the MCData client shall generate a SIP MESSAGE request towards the participating MCData function, in accordance with 3GPP TS 24.229 [5] and IETF RFC 3428 [6] with the clarifications given below.

The MCData client:

1) shall build the SIP MESSAGE request as specified in subclause 6.2.4.1;

2) shall follow the rules specified in subclause 6.4 for the handling of MIME bodies in a SIP message when processing the remaining steps in this subclause;

3) shall insert in the SIP MESSAGE request an application/vnd.3gpp.mcdata-info+xml MIME body with a <request-type> element containing the value "msf-disc-req";

4) if the upload of a file is for a group standalone FD request, shall include in an application/vnd.3gpp.mcdata-info+xml MIME body, the <mcdata-calling-group-id> element set to the required MCData group identity; and

NOTE 1: The absence of a group identity in the <mcdata-calling-group-id> element of the application/vnd.3gpp.mcdata-info+xml MIME body implies that the MCData client intends to upload a file for a one-to-one FD request. In this case, the participating MCData function identifies the MCData ID of the user from the binding between the public user identity and the MCData ID.

5) shall send the SIP MESSAGE request according to rules and procedures of 3GPP TS 24.229 [5].

On receipt of a "SIP MESSAGE request for absolute URI discovery response", the MCData client:

1) shall store the absolute URI found in the <mcdata-controller-psi> element;

2) shall generate a SIP 200 (OK) response according to rules and procedures of 3GPP TS 24.229 [5]; and

3) shall send the SIP 200 (OK) response towards the MCData server according to rules and procedures of 3GPP TS 24.229 [5].

[TS 24.282, clause 10.2.2.1]

If the media storage client is not aware of the absolute URI of the media storage function, the media storage client shall request the MCData client to discover the absolute URI associated with the media storage function by following the procedures in subclause 10.2.1.3.

The media storage client shall send HTTP requests over a TLS connection as specified for the HTTP client in the UE in annex A of 3GPP TS 24.482 [24].

NOTE 1: The HTTP client encodes the MCData ID in the bearer access token of the Authorization header field of an HTTP request as specified in 3GPP TS 24.482 [24].

NOTE 2: The HTTP client always sends the HTTP requests to an HTTP proxy. Annex A of 3GPP TS 24.482 [24] indicates how the HTTP proxy forwards the HTTP request to the HTTP server.

To upload a file to media storage function, the media storage client:

1) shall generate an HTTP POST request as specified in IETF RFC 7230 [22] and IETF RFC 7231 [23];

2) shall set the Request-URI to the absolute URI identifying the resource on a media storage function;

3) shall set the Host header field to a hostname identifying the media storage function;

4) shall set the Content-Type header field to multipart/mixed and with a boundary delimiter parameter set to any chosen value;

5) if the file upload is for one-to-one file distribution, shall insert an application/vnd.3gpp.mcdata-info+xml MIME body with:

   a) the <request-type> element set to a value of "one-to-one-fd"; and

   b) the <mcdata-calling-user-id> element set to the originating MCData ID;

6) if the file upload is for group file distribution, shall insert an application/vnd.3gpp.mcdata-info+xml MIME body with:

   a) the <request-type> element set to a value of "group-fd";

   b) the <mcdata-request-uri> element set to the MCData group identity; and

   c) the <mcdata-calling-user-id> element set to the originating MCData ID;

7) if end-to-end security is required for a one-to-one communication, the MCData client protects the binary data representing the file and prefixes the protected binary data with security parameters as described in 3GPP TS 33.180 [26];

8) if

   i) end-to-end security is not required for a one-to-one communication, or

   ii) the file upload is for group file distribution;

   shall include the binary data representing the file with Content-Type field set to application/octet-stream and Content-Length field set to the file size; and

9) shall send the HTTP POST request towards the media storage function.

On receipt of a HTTP 201 Created containing a Location header field with a URL identifying the location of the resource where the file has been stored on the media storage function, then the media storage client shall store this information.

[TS 24.282, clause 10.2.4.2.1]

The MCData client shall generate a SIP MESSAGE request in accordance with 3GPP TS 24.229 [5] and IETF RFC 3428 [6] with the clarifications given below.

The MCData client:

1) shall build the SIP MESSAGE request as specified in subclause 6.2.4.1;

2) if a one-to-one standalone FD message is to be sent shall insert in the SIP MESSAGE request:

   a) an application/resource-lists+xml MIME body with the MCData ID of the target MCData user, according to rules and procedures of IETF RFC 4826 [9]; and

   b) an application/vnd.3gpp.mcdata-info+xml MIME body with a <request-type> element set to a value of "one-to-one-fd";

…

4) shall generate a standalone FD message as specified in subclause 6.2.2.2; and

5) shall send the SIP MESSAGE request according to rules and procedures of 3GPP TS 24.229 [5].

[TS 24.282, clause 12.2.1.2]

Upon receipt of a:

"SIP MESSAGE request for SDS disposition notification for terminating MCData client"; or

"SIP MESSAGE request for FD disposition notification for terminating MCData client";

the MCData client:

1) shall decode the contents of the application/vnd.3gpp.mcdata-signalling MIME body; and

2) shall deliver the notification to the user or application.

6.2.3.3 Test description

6.2.3.3.1 Pre-test conditions

Test configuration:

- Single cell configuration according to TS 37.579-1 [2] clause 5.2.2.2.1.
- Test File 1 for CO FD as specified in annex A.2.1 and test File 2 for CO FD as specified in Annex A.2.2 are available at the UE for upload.

Preamble:

- The UE has performed procedure 'Initial registration' as described in TS 37.579-1 [2] clause 5.4.2 with the following clarifications:
  - In the MCData Group Configuration document the <mcdata-on-network-max-data-size-auto-recv> shall be set to 0 to indicate non-mandatory download independent from the file size.
- UE States at the end of the preamble:
  - The UE is in RRC_IDLE state.
  - The client is registered for MCData.

6.2.3.3.2 Test procedure sequence

Table 6.2.3.3.2-1: Main Behaviour

St	Procedure	Message Sequence		TP	Verdict
		U - S	Message		
1	Make the UE (MCData client) send test file 1 (Annex A.2.1) for CO group FD over HTTP for non-mandatory download and with disposition request "FILE DOWNLOAD COMPLETED UPDATE". (NOTE 1, NOTE 2)	-	-	-	-
2	Check: Does the UE (MCData client) correctly perform procedure '**Discovery of the absolute URI of the media storage function (one-to-one communication)**' as described in TS 37.579-1 [2] Table 5.3C.9.3-1 ?	-	-	1	P
3	Check: Does the UE (MCData client) correctly perform procedure '**FD file upload using HTTP**' as described in TS 37.579-1 [2] Table 5.3C.10.3-1?	-	-	2	P
3A	Check: Is the content of the uploaded file the same as specified in annex A.2.1?	-	-	2	P
4-6	Void	-	-	-	-
7	Check: Does the UE (MCData client) correctly perform procedure '**MCX SIP MESSAGE CT**' as described in TS 37.579-1 [2] Table 5.3.33.3-1 **to receive an FD NOTIFICATION with disposition notification type "FILE DOWNLOAD REQUEST ACCEPTED"** for the FD message sent at step 3?	-	-	3	P
8	Void	-	-	-	-
9	Check: Does the UE (MCData client) notify the user that the remote client has accepted the download? (NOTE 1)	-	-	3	P
10	Check: Does the UE (MCData client) correctly perform procedure '**MCX SIP MESSAGE CT**' as described in TS 37.579-1 [2] Table 5.3.33.3-1 **to receive an FD NOTIFICATION with disposition notification type "FILE DOWNLOAD COMPLETED"** for the FD message sent at step 3?	-	-	3	P
11	Void	-	-	-	-
12	Check: Does the UE (MCData client) notify the user that the remote client has completed the download? (NOTE 1)	-	-	3	P
13	Make the UE (MCData client) send test file 2 (Annex A.2.2) for CO group FD over HTTP for non-mandatory download and with disposition request "FILE DOWNLOAD COMPLETED UPDATE". (NOTE 1, NOTE 2)	-	-	-	-
-	EXCEPTION: Step 14a1 describes behaviour that depends on UE implementation.	-	-	-	-
14a1	IF the client needs to discover again the absolute URI of the media storage function THEN the UE (MCData client) performs procedure '**Discovery of the absolute URI of the media storage function (one-to-one communication)**' as described in TS 37.579-1 [2] Table 5.3C.9.3-1.	-	-	-	-
14a2 - 14a4	Void	-	-	-	-
15	Check: Does the UE (MCData client) correctly perform procedure '**FD file upload using HTTP**' as described in TS 37.579-1 [2] Table 5.3C.10.3-1?	-	-	2	P

15A	Check: Is the content of the uploaded file the same as specified in annex A.2.2?	-	-	2	P
16-18	Void	-	-	-	-
19	Check: Does the UE (MCData client) correctly perform procedure '**MCX SIP MESSAGE CT**' as described in TS 37.579-1 [2] Table 5.3.33.3-1 **to receive an FD NOTIFICATION with disposition notification type "FILE DOWNLOAD REQUEST REJECTED"** for the FD message sent at step 15?	-	-	3	P
20	Void	-	-	-	-
21	Check: Does the UE (MCData client) notify the user that the remote client has rejected the download? (NOTE 1)	-	-	3	P
NOTE 1: This is expected to be done via a suitable implementation dependent MMI. NOTE 2: Test file 1 and 2 for CO FD as specified in annex A.2.1 and A.2.2.					

6.2.3.3.3 Specific message contents

Table 6.2.1.3.3-1..6: Void

Table 6.2.3.3.3-7: HTTP POST from the UE (steps 3, 15, Table 6.2.3.3.2-1; step 2, TS 37.579-1 [2] Table 5.3C.10.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.4.3-1, condition FD_HTTP				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part		**MCData-Info**		
MIME-part-body	MCData-Info as described in Table 6.2.3.3.3-8			

Table 6.2.3.3.3-8: MCData-Info (Table 6.2.3.3.3-7)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.2.1-3				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
mcdata-info				
mcdata-Params				
request-type	"group-fd"			
mcdata-request-uri	px_MCData_Group_A_ID	NOTE: the element is not encrypted		
mcdata-calling-user-id	px_MCData_ID_User_A	NOTE: the element is not encrypted		

Table 6.2.3.3.3-9: Void

Table 6.2.3.3.3-10: HTTP 201 Created from the SS (step 3, Table 6.2.3.3.2-1; step 3, TS 37.579-1 [2] Table 5.3C.10.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.4.7-1, condition FD_HTTP

Table 6.2.3.3.3-10A: HTTP 201 Created from the SS (step 15, Table 6.2.3.3.2-1; step 3, TS 37.579-1 [2] Table 5.3C.10.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.4.7-1, condition FD_HTTP				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Location				
absoluteURI	tsc_MCData_MSF_URI & "/file-location-2"			

Table 6.2.3.3.3-11: SIP MESSAGE from the UE (steps 3, 15, Table 6.2.3.3.2-1; step 4, TS 37.579-1 [2] Table 5.3C.10.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.7.1-1, condition MCDATA_FD, MCDATA_SIGNALLING				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part		**MCData-Info**		
MIME-part-body	MCData-Info as described in Table 6.2.3.3.3-12			
MIME body part		**MCData Data signalling message**		
MIME-part-body	MCData Protected Payload Message containing FD SIGNALLING PAYLOAD as described in Table 6.2.3.3.3-12A			

Table 6.2.3.3.3-12: MCData-Info (Table 6.2.3.3.3-11)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.2.1-3, condition MCD_grp				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
mcdata-info				
mcdata-Params				
request-type	"group-fd"			

Table 6.2.3.3.3-12A: FD SIGNALLING PAYLOAD (Table 6.2.3.3.3-11)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.5-1, condition FD_HTTP

Table 6.2.3.3.3-13: SIP MESSAGE from the SS (step 7, Table 6.2.3.3.2-1; step 2, TS 37.579-1 [2] Table 5.3.33.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.7.2-1, condition MCDATA_FD, MCDATA_SIGNALLING				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part		**MCData-Info**		
MIME-part-body	MCData-Info as described in Table 6.2.1.3.3-14			
MIME body part		**MCData Data signalling message**		
MIME-part-body	MCData Protected Payload Message containing FD NOTIFICATION as described in Table 6.2.3.3.3-15			

Table 6.2.3.3.3-14: MCData-Info (Table 6.2.3.3.3-13)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.2.2-3				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
mcdata-info				
mcdata-Params				
mcdata-calling-group-id	Encrypted <mcdata-calling-group-id> with mcdataURI set to px_MCData_Group_A_ID	Encrypted according to TS 37.579-1 [2] Table 5.5.3.2.2-3A		

Table 6.2.3.3.3-15: FD NOTIFICATION (Table 6.2.3.3.3-13)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.8-1, condition FD_ACCEPTED

Table 6.2.3.3.3-16: SIP MESSAGE from the SS (step 10, Table 6.2.3.3.2-1; step 2, TS 37.579-1 [2] Table 5.3.33.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.7.2-1, condition MCDATA_FD, MCDATA_SIGNALLING				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part		**MCData-Info**		
MIME-part-body	MCData-Info as described in Table 6.2.1.3.3-14			
MIME body part		**MCData Data signalling message**		
MIME-part-body	MCData Protected Payload Message containing FD NOTIFICATION as described in Table 6.2.3.3.3-17			

Table 6.2.3.3.3-17: FD NOTIFICATION (Table 6.2.3.3.3-16)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.8-1, condition FD_COMPLETED

Table 6.2.3.3.3-18: SIP MESSAGE from the SS (step 19, Table 6.2.3.3.2-1; step 2, TS 37.579-1 [2] Table 5.3.33.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.7.2-1, condition MCDATA_FD, MCDATA_SIGNALLING				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part		**MCData-Info**		
MIME-part-body	MCData-Info as described in Table 6.2.1.3.3-14			
MIME body part		**MCData Data signalling message**		
MIME-part-body	MCData Protected Payload Message containing FD NOTIFICATION as described in Table 6.2.3.3.3-19			

Table 6.2.3.3.3-19: FD NOTIFICATION (Table 6.2.3.3.3-18)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.8-1, condition FD_REJECTED

6.2.4 On-network / File Distribution (FD) / FD Using HTTP / Group Standalone FD / Non-Mandatory Download / After TDU2 Timers Expires / FILE DOWNLOAD REQUEST ACCEPTED / FILE DOWNLOAD COMPLETED / FILE DOWNLOAD REQUEST REJECTED / Client Terminated (CT)

6.2.4.1 Test Purpose (TP)

(1)

```
with { UE (MCDATA Client) registered and authorised for MCDATA Service }
ensure that {
  when { UE (MCDATA Client) receives a SIP MESSAGE message for a group standalone FD message with a
non-mandatory download and with a disposition of "FILE DOWNLOAD COMPLETE UPDATE" }
    then { UE (MCDATA Client) responds with a SIP 200 (OK) message and notifies the MCDATA User
about the incoming FD request }
            }
```

(2)

```
with { UE (MCDATA Client) having received a group standalone FD message with a non-mandatory
download and with a disposition of "FILE DOWNLOAD COMPLETE UPDATE" }
ensure that {
  when { the MCDATA User requests to accept the FD request }
    then { UE (MCDATA Client) generates an FD NOTIFICATION indicating acceptance of the FD request
and attempts to download the file with an HTTP GET message }
            }
```

(3)

```
with { MCDATA User having accepted an FD request with a disposition of "FILE DOWNLOAD COMPLETE
UPDATE" }
ensure that {
  when { UE (MCDATA Client) has successfully downloaded the file }
    then { UE (MCDATA Client) notifies the MCDATA User that the file has successfully downloaded and
generates an FD NOTIFICATION indicating the successful download of the file }
            }
```

(4)

```
with { UE (MCDATA Client) having received a group standalone FD message with a non-mandatory
download and with a disposition of "FILE DOWNLOAD COMPLETE UPDATE" }
ensure that {
  when { the MCDATA User requests to reject the FD request }
    then { UE (MCDATA Client) generates an FD NOTIFICATION indicating the rejection of the FD
request }
            }
```

(5)

```
Void
```

6.2.4.2 Conformance requirements

References: The conformance requirements covered in the current TC are specified in: TS 24.282, clauses 10.2.4.2.2, 10.2.1.2.3, 12.2.1.1, 10.2.3.1. The following represents a copy/paste extraction of the requirements relevant to the test purpose; any references within the copy/paste text should be understood within the scope of the core spec they have been copied from. Unless otherwise stated, these are Rel-14 requirements.

[TS 24.282, clause 10.2.4.2.2]

Upon receipt of a "SIP MESSAGE request for FD using HTTP for terminating MCData client", the MCData client:

1) may reject the SIP MESSAGE request if there are not enough resources to handle the SIP MESSAGE request;

2) if the SIP MESSAGE request is rejected in step 1), shall respond towards the participating MCData function with a SIP 480 (Temporarily unavailable) response and skip the rest of the steps of this subclause;

3) shall generate a SIP 200 (OK) response according to rules and procedures of 3GPP TS 24.229 [5];

4) shall send the SIP 200 (OK) response towards the MCData server according to rules and procedures of 3GPP TS 24.229 [5]; and

5) shall handle the received message as specified in subclause 10.2.1.2.

[TS 24.282, clause 10.2.1.2.3]

The MCData client:

1) if the FD SIGNALLING PAYLOAD message does not contain an Application ID IE:

   a) shall determine that the payload contained in the Payload IE in the FD SIGNALLING PAYLOAD message is for user consumption;

   b) shall notify the user about the incoming FD request; and

   c) if the FD SIGNALLING PAYLOAD message contains a Metadata IE, shall deliver the contents of the Metadata IE to the user;

2) if the FD SIGNALLING PAYLOAD message contains an Application ID IE:

   a) shall determine that the payload contained in the Payload IE in the FD SIGNALLING PAYLOAD message is not for user consumption;

   b) if the Application ID value is unknown, shall discard the FD message and exit this subclause;

   c) if the Application ID value is known, shall notify the application of the incoming FD request; and

NOTE 1: If FD request is addressed to a non-MCData application that is not running, the MCData client starts the local non-MCData application.

   d) if the FD SIGNALLING PAYLOAD message contains a Metadata IE, shall deliver the contents of the Metadata IE to the application;

3) shall start a timer TDU2 (FD non-mandatory download timer) with the timer value as specified in subclause F.2.3;

4) shall wait for the user or application to request to download the file indicated by file URL in the Payload data in the Payload IE in the FD SIGNALLING PAYLOAD message;

5) if the user or application accepts or rejects or decides to defer the FD request, shall stop timer TDU2 (FD non-mandatory download timer);

6) if the user deferred the FD request while the timer TDU2 (FD non-mandatory download timer) was running, shall generate an FD NOTIFICATION indicating deferral of the FD request as specified in subclause 12.2.1.1;

NOTE 2: Once the timer TDU2 (FD non-mandatory download timer) has expired the FD request can only be accepted or rejected with an appropriate action by the MCData client.

NOTE 3: Once the timer TDU2 (FD non-mandatory download timer) has expired, no action is taken by the MCData client if the FD request is deferred.

7) if the user or application rejects the FD request, shall generate an FD NOTIFICATION indicating rejection of the FD request as specified in subclause 12.2.1.1 and shall exit this subclause; and

8) if the user accepts the FD request:

a) shall generate an FD NOTIFICATION indicating acceptance of the FD request as specified in subclause 12.2.1.1;

b) if the FD SIGNALLING PAYLOAD message contains a new Conversation ID, shall instantiate a new conversation with the Message ID in the FD SIGNALLING PAYLOAD identifying the first message in the conversation thread;

c) if the FD SIGNALLING PAYLOAD message contains an existing Conversation ID and:

i) if the FD SIGNALLING PAYLOAD message does not contain an InReplyTo message ID, shall use the Message ID in the FD SIGNALLING PAYLOAD to identify a new message in the existing conversation thread; and

ii) if the FD SIGNALLING PAYLOAD message contains an InReplyTo message ID, shall associate the message to an existing message in the conversation thread as identified by the InReplyTo message ID in the FD SIGNALLING PAYLOAD, and use the Message ID in the FD SIGNALLING PAYLOAD to identify the new message;

d) may store the Conversation ID, Message ID, InReplyTo message ID and Date and time in local storage;

e) shall attempt to download the file as identified by the file URL in the Payload IE in the FD SIGNALLING PAYLOAD message, as specified in subclause 10.2.3.1; and

f) if the received FD SIGNALLING PAYLOAD message contains an FD disposition request type IE requesting a file download completed update, then after the file download has been successfully downloaded, shall generate an FD NOTIFICATION by following the procedures in subclause 12.2.1.1.

[TS 24.282, clause 12.2.1.1]

The MCData client shall follow the procedures in this subclause to:

- indicate to an MCData client that an SDS message was delivered, read or delivered and read when the originating client requested a delivery, read or delivery and read report;

- indicate to the participating MCData function serving the MCData user that an SDS message was undelivered. The participating MCData function can store the message for later re-delivery;

- indicate to an MCData client that a request for FD was accepted, deferred or rejected; or

- indicate to an MCData client that a file download has been completed;

Before sending a disposition notification the MCData client needs to determine:

- the group identity related to an SDS or FD message request received as part of a group communication. The MCData client determines the group identity from the contents of the <mcdata-calling-group-id> element contained in the application/vnd.3gpp.mcdata-info+xml MIME body of the incoming SDS or FD message request; and

- the MCData user targeted for the disposition notification. The MCData client determines the targeted MCData user from the contents of the <mcdata-calling-user-id> element contained in the application/vnd.3gpp.mcdata-info+xml MIME body of the incoming SDS or FD message request.

The MCData client shall generate a SIP MESSAGE request in accordance with 3GPP TS 24.229 [5] and IETF RFC 3428 [6] with the clarifications given below.

The MCData client:

1) shall build the SIP MESSAGE request as specified in subclause 6.2.4.1;

2) shall follow the rules specified in subclause 6.4 for the handling of MIME bodies in a SIP message when processing the remaining steps in this subclause;

3) shall insert in the SIP MESSAGE request an application/resource-lists+xml MIME body containing the MCData ID of the targeted MCData user, according to rules and procedures of IETF RFC 5366 [18];

4) void;

5) if sending a disposition notification in response to an MCData group data request, shall include an <mcdata-calling-group-id> element set to the MCData group identity in the application/vnd.3gpp.mcdata-info+xml MIME body;

6) if requiring to send an SDS notification, shall generate an SDS NOTIFICATION message and include it in the SIP MESSAGE request as specified in subclause 6.2.3.1;

7) if requiring to send an FD notification, shall generate an FD NOTIFICATION message and include it in the SIP MESSAGE request as specified in subclause 6.2.3.2; and

8) shall send the SIP MESSAGE request according to rules and procedures of 3GPP TS 24.229 [5].

[TS 24.282, clause 10.2.3.1]

The media storage client on the MCData client shall send HTTP requests over a TLS connection as specified for the HTTP client in the UE, in annex A of 3GPP TS 24.482 [24].

NOTE 1: The HTTP client encodes the MCData ID in the bearer access token of the Authorization header field of an HTTP request as specified in 3GPP TS 24.482 [24].

NOTE 2: The HTTP client always sends the HTTP requests to an HTTP proxy. Annex A of 3GPP TS 24.482 [24] indicates how the HTTP proxy forwards the HTTP request to the HTTP server.

To download a file from the media storage function on the controlling MCData function, the media storage client on the MCData client:

1) shall generate an HTTP GET request as specified in IETF RFC 7230 [22] and IETF RFC 7231 [23] with a Request-URI set to an absolute URI identifying the URL of the file being requested from the media storage function on the controlling MCData function; and

2) shall send the HTTP GET request towards the media storage function on the controlling MCData function.

On receipt of a HTTP 200 OK response containing the requested file, the MCData client shall notify the user or application that the file has been successfully downloaded.

6.2.4.3 Test description

6.2.4.3.1 Pre-test conditions

Test configuration:

- Single cell configuration according to TS 37.579-1 [2] clause 5.2.2.2.1.
- Test files downloaded or received at previous test runs are deleted.

Preamble:

- The UE has performed procedure 'Initial registration' as described in TS 37.579-1 [2] clause 5.4.2 with the following clarifications:
  - In the MCData Group Configuration document the <mcdata-on-network-max-data-size-auto-recv> shall be set to 0 to indicate non-mandatory download independent from the file size.
  - Timer TDU2 (FD non-mandatory download timer) is configured to be 15 seconds.
- UE States at the end of the preamble:
  - The UE is in RRC_IDLE state.
  - The client is registered for MCData.

6.2.4.3.2 Test procedure sequence

Table 6.2.4.3.2-1: Main Behaviour

St	Procedure	Message Sequence		TP	Verdict
		U - S	Message		
1	Check: Does the UE (MCData client) correctly perform procedure '**MCX SIP MESSAGE CT**' as described in TS 37.579-1 [2] Table 5.3.33.3-1 **to receive an FD message for group file distribution with disposition request "FILE DOWNLOAD COMPLETED UPDATE"**? (NOTE 2)	-	-	1	P
2	Void	-	-	-	-
3	Check: Does the UE (MCData client) notify the user of the incoming FD request? (NOTE 1)	-	-	1	P
4	The SS waits 15s for expiry of timer TDU2.	-	-	-	-
4A	Make the UE (MCData client) accept the FD request and download the file. (NOTE 1)	-	-	-	-
5	Check: Does the UE (MCData client) correctly perform procedure '**FD file accept and download using HTTP**' as described in TS 37.579-1 [2] Table 5.3C.11.3-1 to download test file 1? (NOTE 3)	-	-	2,3	P
6-8	Void	-	-	-	-
9	Check: Does the UE (MCData client) notify the user of the file download? (NOTE 1)	-	-	3	P
9A	Check: Has the UE (MCData client) downloaded test file 1 (Annex A.3.1)? (NOTE 1)	-	-	2	P
10-11	Void	-	-	-	-
12	Check: Does the UE (MCData client) correctly perform procedure '**MCX SIP MESSAGE CT**' as described in TS 37.579-1 [2] Table 5.3.33.3-1 **to receive an FD message for group file distribution with disposition request "FILE DOWNLOAD COMPLETED UPDATE"**? (NOTE 2)	-	-	1	P
13	Void	-	-	-	-
14	Check: Does the UE (MCData client) notify the user of the incoming FD request? (NOTE 1)	-	-	1	P
15	The SS waits 15s for expiry of timer TDU2.	-	-	-	-
15A	Make the UE (MCData client) reject the FD request. (NOTE 1)	-	-	-	-
16	Check: Does the UE (MCData client) correctly perform procedure '**CO SDS or FD message transfer using signalling plane**' as described in TS 37.579-1 [2] Table 5.3C.1.3-1 **to send an FD NOTIFICATION with disposition notification type "FILE DOWNLOAD REQUEST REJECTED"?**	-	-	4	P
17	Void	-	-	-	-

NOTE 1: This is expected to be done via a suitable implementation dependent MMI.
NOTE 2: Timer TDU2 (FD non-mandatory download timer) starts on reception of the FD request via the SIP MESSAGE request.
NOTE 3: Test file 1 for CT FD as specified in annex A.3.1.

6.2.4.3.3 Specific message contents

Table 6.2.4.3.3-1: SIP MESSAGE from the SS (steps 1, 12, Table 6.2.4.3.2-1; step 2, TS 37.579-1 [2] Table 5.3.33.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.7.2-1, condition MCDATA_FD, MCDATA_SIGNALLING				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part		**MCData-Info**		
MIME-part-body	MCData-Info as described in Table 6.2.4.3.3-2			
MIME body part		**MCData Data signalling message**		
MIME-part-body	MCData Protected Payload Message containing FD SIGNALLING PAYLOAD as described in Table 6.2.4.3.3-2A			

Table 6.2.4.3.3-2: MCData-Info (Table 6.2.4.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.2.2-3, condition MCD_grp				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
mcdata-info				
mcdata-Params				
request-type	"group-fd"			

Table 6.2.4.3.3-2A: FD SIGNALLING PAYLOAD (Table 6.2.2.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.6-1, condition FD_HTTP

Table 6.2.4.3.3-3: Void

Table 6.2.4.3.3-4: SIP MESSAGE from the UE (step 5, Table 6.2.4.3.2-1; step 2, TS 37.579-1 [2] Table 5.3C.11.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.7.1-1, condition MCDATA_FD, RESOURCE_LISTS, MCDATA_SIGNALLING				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part		**MCData-Info**		
MIME-part-body	MCData-Info as described in Table 6.2.4.3.3-5			
MIME body part		**MCData Data signalling message**		
MIME-part-body	MCData Protected Payload Message containing FD NOTIFICATION as described in Table 6.2.4.3.3-6			

Table 6.2.4.3.3-5: MCData-Info (Table 6.2.4.3.3-4)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.2.1-3				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
mcdata-info				
mcdata-Params				
mcdata-calling-group-id	Encrypted <mcdata-request-uri> with mcdataURI set to px_MCData_Group_A_ID	Encrypted according to TS 37.579-1 [2] Table 5.5.3.2.1-3A		

Table 6.2.4.3.3-6: FD NOTIFICATION (Table 6.2.4.3.3-4)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.7-1, condition FD_ACCEPTED

Table 6.2.4.3.3-7: HTTP GET from the UE (step 5, Table 6.2.4.3.2-1; step 4, TS 37.579-1 [2] Table 5.3C.11.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.4.2-1, condition FD_HTTP

Table 6.2.4.3.3-8: HTTP 200 (OK) from the SS (step 5, Table 6.2.4.3.2-1; step 5, TS 37.579-1 [2] Table 5.3C.11.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.4.6-1, condition FD_HTTP

Table 6.2.4.3.3-9: Void

Table 6.2.4.3.3-10: SIP MESSAGE from the UE (step 5, Table 6.2.4.3.2-1; step 6a1, TS 37.579-1 [2] Table 5.3C.11.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.7.1-1, condition MCDATA_FD, RESOURCE_LISTS, MCDATA_SIGNALLING				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part		**MCData-Info**		
MIME-part-headers	MCData-Info as described in Table 6.2.4.3.3-5			
MIME body part		**MCData Data signalling message**		
MIME-part-body	MCData Protected Payload Message containing FD NOTIFICATION as described in Table 6.2.4.3.3-11			

Table 6.2.4.3.3-11: FD NOTIFICATION (Table 6.2.4.3.3-10)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.7-1, condition FD_COMPLETED

Table 6.2.4.3.3-12: SIP MESSAGE from the UE (step 16, Table 6.2.4.3.2-1; step 2, TS 37.579-1 [2] Table 5.3C.1.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.7.1-1, condition MCDATA_FD, RESOURCE_LISTS, MCDATA_SIGNALLING				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part		**MCData-Info**		
MIME-part-headers	MCData-Info as described in Table 6.2.4.3.3-5			
MIME body part		**MCData Data signalling message**		
MIME-part-body	MCData Protected Payload Message containing FD NOTIFICATION as described in Table 6.2.4.3.3-13			

Table 6.2.4.3.3-13: FD NOTIFICATION (Table 6.2.4.3.3-12)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.7-1, condition FD_REJECTED

6.2.5 On-network / File Distribution (FD) / FD Using HTTP / One-to-one Standalone FD / Mandatory Download / With Disposition Request / Client Originated (CO)

6.2.5.1 Test Purpose (TP)

(1)

```
with { UE (MCDATA Client) registered and authorised for MCDATA Service }
ensure that {
  when { the MCDATA User requests to send a standalone one-to-one FD message with a mandatory
download and with a disposition of "FILE DOWNLOAD COMPLETE UPDATE" and the UE (MCDATA Client) is
unaware of the URL of the Media Storage Function }
    then { UE (MCDATA Client) sends a SIP MESSAGE to find the URL of the Media Storage Function and
responds to a SIP MESSAGE that contains the URL of the Media Storage Function with a SIP 200 (OK)
message }
            }
```

(2)

```
with { UE (MCDATA Client) registered and authorised for MCDATA Service }
ensure that {
  when { the MCDATA User requests to send a standalone one-to-one FD message with a mandatory
download and with a disposition of "FILE DOWNLOAD COMPLETE UPDATE" and the UE (MCDATA Client) is
aware of the URL of the Media Storage Function }
    then { UE (MCDATA Client) uploads the file to the Media Storage Function via an HTTP POST
message and then sends the URL of the file location to the recipient via a SIP MESSAGE message }
            }
```

(3)

```
with { UE (MCDATA Client) having sent the URL of the file location to the recipient }
ensure that {
  when { UE (MCDATA Client) receives a FD notification via a SIP MESSAGE message }
    then { UE (MCDATA Client) responds to the SIP MESSAGE message with a SIP 200 (OK) message and
delivers the notification to the MCDATA User }
            }
```

6.2.5.2 Conformance requirements

References: The conformance requirements covered in the current TC are specified in: TS 24.282, clauses 10.2.1.3.2, 10.2.2.1, 10.2.4.2.1, 12.2.1.2. The following represents a copy/paste extraction of the requirements relevant to the test purpose; any references within the copy/paste text should be understood within the scope of the core spec they have been copied from. Unless otherwise stated, these are Rel-14 requirements.

[TS 24.282, clause 10.2.1.3.2]

To discover the absolute URI of the media storage function, the MCData client shall generate a SIP MESSAGE request towards the participating MCData function, in accordance with 3GPP TS 24.229 [5] and IETF RFC 3428 [6] with the clarifications given below.

The MCData client:

1) shall build the SIP MESSAGE request as specified in subclause 6.2.4.1;

2) shall follow the rules specified in subclause 6.4 for the handling of MIME bodies in a SIP message when processing the remaining steps in this subclause;

3) shall insert in the SIP MESSAGE request an application/vnd.3gpp.mcdata-info+xml MIME body with a <request-type> element containing the value "msf-disc-req";

4) if the upload of a file is for a group standalone FD request, shall include in an application/vnd.3gpp.mcdata-info+xml MIME body, the <mcdata-calling-group-id> element set to the required MCData group identity; and

NOTE 1: The absence of a group identity in the <mcdata-calling-group-id> element of the application/vnd.3gpp.mcdata-info+xml MIME body implies that the MCData client intends to upload a file for a one-to-one FD request. In this case, the participating MCData function identifies the MCData ID of the user from the binding between the public user identity and the MCData ID.

5) shall send the SIP MESSAGE request according to rules and procedures of 3GPP TS 24.229 [5].

On receipt of a "SIP MESSAGE request for absolute URI discovery response", the MCData client:

1) shall store the absolute URI found in the <mcdata-controller-psi> element;

2) shall generate a SIP 200 (OK) response according to rules and procedures of 3GPP TS 24.229 [5]; and

3) shall send the SIP 200 (OK) response towards the MCData server according to rules and procedures of 3GPP TS 24.229 [5].

[TS 24.282, clause 10.2.2.1]

If the media storage client is not aware of the absolute URI of the media storage function, the media storage client shall request the MCData client to discover the absolute URI associated with the media storage function by following the procedures in subclause 10.2.1.3.

The media storage client shall send HTTP requests over a TLS connection as specified for the HTTP client in the UE in annex A of 3GPP TS 24.482 [24].

NOTE 1: The HTTP client encodes the MCData ID in the bearer access token of the Authorization header field of an HTTP request as specified in 3GPP TS 24.482 [24].

NOTE 2: The HTTP client always sends the HTTP requests to an HTTP proxy. Annex A of 3GPP TS 24.482 [24] indicates how the HTTP proxy forwards the HTTP request to the HTTP server.

To upload a file to media storage function, the media storage client:

1) shall generate an HTTP POST request as specified in IETF RFC 7230 [22] and IETF RFC 7231 [23];

2) shall set the Request-URI to the absolute URI identifying the resource on a media storage function;

3) shall set the Host header field to a hostname identifying the media storage function;

4) shall set the Content-Type header field to multipart/mixed and with a boundary delimiter parameter set to any chosen value;

5) if the file upload is for one-to-one file distribution, shall insert an application/vnd.3gpp.mcdata-info+xml MIME body with:

   a) the <request-type> element set to a value of "one-to-one-fd"; and

   b) the <mcdata-calling-user-id> element set to the originating MCData ID;

6) if the file upload is for group file distribution, shall insert an application/vnd.3gpp.mcdata-info+xml MIME body with:

   a) the <request-type> element set to a value of "group-fd";

   b) the <mcdata-request-uri> element set to the MCData group identity; and

   c) the <mcdata-calling-user-id> element set to the originating MCData ID;

7) if end-to-end security is required for a one-to-one communication, the MCData client protects the binary data representing the file and prefixes the protected binary data with security parameters as described in 3GPP TS 33.180 [26];

8) if

   i) end-to-end security is not required for a one-to-one communication, or

   ii) the file upload is for group file distribution;

   shall include the binary data representing the file with Content-Type field set to application/octet-stream and Content-Length field set to the file size; and

9) shall send the HTTP POST request towards the media storage function.

On receipt of a HTTP 201 Created containing a Location header field with a URL identifying the location of the resource where the file has been stored on the media storage function, then the media storage client shall store this information.

[TS 24.282, clause 10.2.4.2.1]

The MCData client shall generate a SIP MESSAGE request in accordance with 3GPP TS 24.229 [5] and IETF RFC 3428 [6] with the clarifications given below.

The MCData client:

1) shall build the SIP MESSAGE request as specified in subclause 6.2.4.1;

2) if a one-to-one standalone FD message is to be sent shall insert in the SIP MESSAGE request:

   a) an application/resource-lists+xml MIME body with the MCData ID of the target MCData user, according to rules and procedures of IETF RFC 4826 [9]; and

   b) an application/vnd.3gpp.mcdata-info+xml MIME body with a <request-type> element set to a value of "one-to-one-fd";

…

4) shall generate a standalone FD message as specified in subclause 6.2.2.2; and

5) shall send the SIP MESSAGE request according to rules and procedures of 3GPP TS 24.229 [5].

[TS 24.282, clause 12.2.1.2]

Upon receipt of a:

"SIP MESSAGE request for SDS disposition notification for terminating MCData client"; or

"SIP MESSAGE request for FD disposition notification for terminating MCData client";

the MCData client:

1) shall decode the contents of the application/vnd.3gpp.mcdata-signalling MIME body; and

2) shall deliver the notification to the user or application.

6.2.5.3 Test description

6.2.5.3.1 Pre-test conditions

Test configuration:

- Single cell configuration according to TS 37.579-1 [2] clause 5.2.2.2.1.
- Test File 1 for CO FD as specified in annex A.2.1 is available at the UE for upload.

Preamble:

- The UE has performed procedure 'Initial registration' as described in TS 37.579-1 [2] clause 5.4.2.
- UE States at the end of the preamble:
  - The UE is in RRC_IDLE state.
  - The client is registered for MCData.

6.2.5.3.2 Test procedure sequence

Table 6.2.5.3.2-1: Main Behaviour

St	Procedure	Message Sequence		TP	Verdict
		U - S	Message		
1	Make the UE (MCData client) send test file 1 (Annex A.2.1) for CO one-to-one FD over HTTP for mandatory download and with disposition request "FILE DOWNLOAD COMPLETED UPDATE". (NOTE 1, NOTE 2)	-	-	-	-
2	Check: Does the UE (MCData client) correctly perform procedure '**Discovery of the absolute URI of the media storage function (one-to-one communication)**' as described in TS 37.579-1 [2] Table 5.3C.8.3-1 ?	-	-	1	P
3	Check: Does the UE (MCData client) correctly perform procedure '**FD file upload using HTTP**' as described in TS 37.579-1 [2] Table 5.3C.10.3-1?	-	-	2	P
3A	Check: Is the content of the uploaded file the same as specified in annex A.2.1?	-	-	2	P
4-6	Void	-	-	-	-
7	Check: Does the UE (MCData client) correctly perform procedure '**MCX SIP MESSAGE CT**' as described in TS 37.579-1 [2] Table 5.3.33.3-1 **to receive an FD NOTIFICATION with disposition notification type "FILE DOWNLOAD REQUEST ACCEPTED"** for the FD message sent at step 3?	-	-	3	P
8	Void	-	-	-	-
9	Check: Does the UE (MCData client) notify the user that the remote client has accepted the download? (NOTE 1)	-	-	3	P
10	Check: Does the UE (MCData client) correctly perform procedure '**MCX SIP MESSAGE CT**' as described in TS 37.579-1 [2] Table 5.3.33.3-1 **to receive an FD NOTIFICATION with disposition notification type "FILE DOWNLOAD COMPLETED"** for the FD message sent at step 3?	-	-	3	P
11	Void	-	-	-	-
12	Check: Does the UE (MCData client) notify the user that the remote client has completed the download? (NOTE 1)	-	-	3	P
NOTE 1: This is expected to be done via a suitable implementation dependent MMI. NOTE 2: Test file 1 for CO FD as specified in annex A.2.1.					

6.2.5.3.3 Specific message contents

Table 6.2.5.3.3-1..6: Void

Table 6.2.5.3.3-7: HTTP POST from the UE (step 3, Table 6.2.5.3.2-1; step 2, TS 37.579-1 [2] Table 5.3C.10.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.4.3-1, condition FD_HTTP				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part		**MCData-Info**		
MIME-part-body	MCData-Info as described in Table 6.2.1.3.3-8			

Table 6.2.5.3.3-8: MCData-Info (Table 6.2.5.3.3-7)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.2.1-3				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
mcdata-info				
mcdata-Params				
request-type	"one-to-one-fd"			
mcdata-calling-user-id	px_MCData_ID_User_A			

Table 6.2.5.3.3-9..10: Void

Table 6.2.5.3.3-11: HTTP 201 Created from the SS (step 3, Table 6.2.5.3.2-1; step 3, TS 37.579-1 [2] Table 5.3C.10.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.4.7-1, condition FD_HTTP

Table 6.2.5.3.3-12: SIP MESSAGE from the UE (step 3, Table 6.2.5.3.2-1; step 4, TS 37.579-1 [2] Table 5.3C.10.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.7.1-1, condition MCDATA_FD, RESOURCE_LISTS, MCDATA_SIGNALLING				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part		**MCData-Info**		
MIME-part-body	MCData-Info as described in Table 6.2.5.3.3-13			
MIME body part		**MCData Data signalling message**		
MIME-part-body	MCData Protected Payload Message containing FD SIGNALLING PAYLOAD as described in Table 6.2.5.3.3-14			

Table 6.2.5.3.3-13: MCData-Info (Table 6.2.5.3.3-12)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.2.1-3, condition MCD_1to1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
mcdata-info				
mcdata-Params				
request-type	"one-to-one-fd"			

Table 6.2.5.3.3-14: FD Signalling Payload (Table 6.2.5.3.3-12)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.5-1, condition FD_HTTP				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Mandatory download	'0001'B	MANDATORY DOWNLOAD	TS 24.282 [31] clause 15.2.16	

Table 6.2.5.3.3-15: SIP MESSAGE from the SS (step 7, Table 6.2.5.3.2-1; step 2, TS 37.579-1 [2] Table 5.3.33.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.7.2-1, condition MCDATA_FD, MCDATA_SIGNALLING				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part		**MCData Data signalling message**		
MIME-part-body	MCData Protected Payload Message containing FD NOTIFICATION from the SS as described in Table 6.2.5.3.3-17			

Table 6.2.5.3.3-16: Void

Table 6.2.5.3.3-17: FD NOTIFICATION (Table 6.2.5.3.3-15)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.8-1, condition FD_ACCEPTED

Table 6.2.5.3.3-18: SIP MESSAGE from the SS (step 10, Table 6.2.5.3.2-1; step 2, TS 37.579-1 [2] Table 5.3.33.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.7.2-1, condition MCDATA_FD, MCDATA_SIGNALLING				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part		**MCData Data signalling message**		
MIME-part-body	MCData Protected Payload Message containing FD NOTIFICATION from the SS as described in Table 6.2.5.3.3-19			

Table 6.2.5.3.3-19: FD NOTIFICATION (Table 6.2.5.3.3-18)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.8-1, condition FD_COMPLETED

6.2.6 On-network / File Distribution (FD) / FD Using HTTP / One-to-one Standalone FD / Mandatory Download / With Disposition Request / Client Terminated (CT)

6.2.6.1 Test Purpose (TP)

(1)

```
with { UE (MCDATA Client) registered and authorised for MCDATA Service }
ensure that {
```

```
  when { UE (MCDATA Client) receives a SIP MESSAGE message for a standalone one-to-one FD message
with a mandatory download and with a disposition of "FILE DOWNLOAD COMPLETE UPDATE" }
    then { UE (MCDATA Client) responds with a SIP 200 (OK) message and notifies the MCDATA User
about the incoming FD request and that the file identified by file URL in the Payload data in the
Payload IE will be downloaded automatically and generates an FD NOTIFICATION indicating acceptance
of the FD request and attempts to download the file with an HTTP GET message }
            }
```

(2)

```
with { UE (MCDATA Client) having started to download the file by sending an HTTP GET message }
ensure that {
  when { UE (MCDATA Client) has successfully downloaded the file }
    then { UE (MCDATA Client) notifies the MCDATA User that the file has successfully downloaded and
generates an FD NOTIFICATION indicating the successful download of the file }
            }
```

6.2.6.2 Conformance requirements

References: The conformance requirements covered in the current TC are specified in: TS 24.282, clauses 10.2.4.2.2, 10.2.1.2.3, 12.2.1.1, 10.2.3.1. The following represents a copy/paste extraction of the requirements relevant to the test purpose; any references within the copy/paste text should be understood within the scope of the core spec they have been copied from. Unless otherwise stated, these are Rel-14 requirements.

[TS 24.282, clause 10.2.4.2.2]

Upon receipt of a "SIP MESSAGE request for FD using HTTP for terminating MCData client", the MCData client:

1) may reject the SIP MESSAGE request if there are not enough resources to handle the SIP MESSAGE request;

2) if the SIP MESSAGE request is rejected in step 1), shall respond towards the participating MCData function with a SIP 480 (Temporarily unavailable) response and skip the rest of the steps of this subclause;

3) shall generate a SIP 200 (OK) response according to rules and procedures of 3GPP TS 24.229 [5];

4) shall send the SIP 200 (OK) response towards the MCData server according to rules and procedures of 3GPP TS 24.229 [5]; and

5) shall handle the received message as specified in subclause 10.2.1.2.

[TS 24.282, clause 10.2.1.2.3]

The MCData client:

1) if the FD SIGNALLING PAYLOAD message does not contain an Application ID IE:

   a) shall determine that the payload contained in the Payload IE in the FD SIGNALLING PAYLOAD message is for user consumption;

   b) shall notify the user about the incoming FD request; and

   c) if the FD SIGNALLING PAYLOAD message contains a Metadata IE, shall deliver the contents of the Metadata IE to the user;

2) if the FD SIGNALLING PAYLOAD message contains an Application ID IE:

   a) shall determine that the payload contained in the Payload IE in the FD SIGNALLING PAYLOAD message is not for user consumption;

   b) if the Application ID value is unknown, shall discard the FD message and exit this subclause;

   c) if the Application ID value is known, shall notify the application of the incoming FD request; and

NOTE 1: If FD request is addressed to a non-MCData application that is not running, the MCData client starts the local non-MCData application.

   d) if the FD SIGNALLING PAYLOAD message contains a Metadata IE, shall deliver the contents of the Metadata IE to the application;

3) shall start a timer TDU2 (FD non-mandatory download timer) with the timer value as specified in subclause F.2.3;

4) shall wait for the user or application to request to download the file indicated by file URL in the Payload data in the Payload IE in the FD SIGNALLING PAYLOAD message;

5) if the user or application accepts or rejects or decides to defer the FD request, shall stop timer TDU2 (FD non-mandatory download timer);

6) if the user deferred the FD request while the timer TDU2 (FD non-mandatory download timer) was running, shall generate an FD NOTIFICATION indicating deferral of the FD request as specified in subclause 12.2.1.1;

NOTE 2: Once the timer TDU2 (FD non-mandatory download timer) has expired the FD request can only be accepted or rejected with an appropriate action by the MCData client.

NOTE 3: Once the timer TDU2 (FD non-mandatory download timer) has expired, no action is taken by the MCData client if the FD request is deferred.

7) if the user or application rejects the FD request, shall generate an FD NOTIFICATION indicating rejection of the FD request as specified in subclause 12.2.1.1 and shall exit this subclause; and

8) if the user accepts the FD request:

   a) shall generate an FD NOTIFICATION indicating acceptance of the FD request as specified in subclause 12.2.1.1;

   b) if the FD SIGNALLING PAYLOAD message contains a new Conversation ID, shall instantiate a new conversation with the Message ID in the FD SIGNALLING PAYLOAD identifying the first message in the conversation thread;

   c) if the FD SIGNALLING PAYLOAD message contains an existing Conversation ID and:

      i) if the FD SIGNALLING PAYLOAD message does not contain an InReplyTo message ID, shall use the Message ID in the FD SIGNALLING PAYLOAD to identify a new message in the existing conversation thread; and

      ii) if the FD SIGNALLING PAYLOAD message contains an InReplyTo message ID, shall associate the message to an existing message in the conversation thread as identified by the InReplyTo message ID in the FD SIGNALLING PAYLOAD, and use the Message ID in the FD SIGNALLING PAYLOAD to identify the new message;

   d) may store the Conversation ID, Message ID, InReplyTo message ID and Date and time in local storage;

   e) shall attempt to download the file as identified by the file URL in the Payload IE in the FD SIGNALLING PAYLOAD message, as specified in subclause 10.2.3.1; and

   f) if the received FD SIGNALLING PAYLOAD message contains an FD disposition request type IE requesting a file download completed update, then after the file download has been successfully downloaded, shall generate an FD NOTIFICATION by following the procedures in subclause 12.2.1.1.

[TS 24.282, clause 12.2.1.1]

The MCData client shall follow the procedures in this subclause to:

- indicate to an MCData client that an SDS message was delivered, read or delivered and read when the originating client requested a delivery, read or delivery and read report;

- indicate to the participating MCData function serving the MCData user that an SDS message was undelivered. The participating MCData function can store the message for later re-delivery;

- indicate to an MCData client that a request for FD was accepted, deferred or rejected; or

- indicate to an MCData client that a file download has been completed;

Before sending a disposition notification the MCData client needs to determine:

- the group identity related to an SDS or FD message request received as part of a group communication. The MCData client determines the group identity from the contents of the <mcdata-calling-group-id> element contained in the application/vnd.3gpp.mcdata-info+xml MIME body of the incoming SDS or FD message request; and

- the MCData user targeted for the disposition notification. The MCData client determines the targeted MCData user from the contents of the <mcdata-calling-user-id> element contained in the application/vnd.3gpp.mcdata-info+xml MIME body of the incoming SDS or FD message request.

The MCData client shall generate a SIP MESSAGE request in accordance with 3GPP TS 24.229 [5] and IETF RFC 3428 [6] with the clarifications given below.

The MCData client:

1) shall build the SIP MESSAGE request as specified in subclause 6.2.4.1;

2) shall follow the rules specified in subclause 6.4 for the handling of MIME bodies in a SIP message when processing the remaining steps in this subclause;

3) shall insert in the SIP MESSAGE request an application/resource-lists+xml MIME body containing the MCData ID of the targeted MCData user, according to rules and procedures of IETF RFC 5366 [18];

4) void;

5) if sending a disposition notification in response to an MCData group data request, shall include an <mcdata-calling-group-id> element set to the MCData group identity in the application/vnd.3gpp.mcdata-info+xml MIME body;

6) if requiring to send an SDS notification, shall generate an SDS NOTIFICATION message and include it in the SIP MESSAGE request as specified in subclause 6.2.3.1;

7) if requiring to send an FD notification, shall generate an FD NOTIFICATION message and include it in the SIP MESSAGE request as specified in subclause 6.2.3.2; and

8) shall send the SIP MESSAGE request according to rules and procedures of 3GPP TS 24.229 [5].

[TS 24.282, clause 10.2.3.1]

The media storage client on the MCData client shall send HTTP requests over a TLS connection as specified for the HTTP client in the UE, in annex A of 3GPP TS 24.482 [24].

NOTE 1: The HTTP client encodes the MCData ID in the bearer access token of the Authorization header field of an HTTP request as specified in 3GPP TS 24.482 [24].

NOTE 2: The HTTP client always sends the HTTP requests to an HTTP proxy. Annex A of 3GPP TS 24.482 [24] indicates how the HTTP proxy forwards the HTTP request to the HTTP server.

To download a file from the media storage function on the controlling MCData function, the media storage client on the MCData client:

1) shall generate an HTTP GET request as specified in IETF RFC 7230 [22] and IETF RFC 7231 [23] with a Request-URI set to an absolute URI identifying the URL of the file being requested from the media storage function on the controlling MCData function; and

2) shall send the HTTP GET request towards the media storage function on the controlling MCData function.

On receipt of a HTTP 200 OK response containing the requested file, the MCData client shall notify the user or application that the file has been successfully downloaded.

6.2.6.3 Test description

6.2.6.3.1 Pre-test conditions

Test configuration:

- Single cell configuration according to TS 37.579-1 [2] clause 5.2.2.2.1.
- Test files downloaded or received at previous test runs are deleted.

Preamble:

- The UE has performed procedure 'Initial registration' as described in TS 37.579-1 [2] clause 5.4.2.
- UE States at the end of the preamble:
  - The UE is in RRC_IDLE state.
  - The client is registered for MCData.

6.2.6.3.2 Test procedure sequence

Table 6.2.6.3.2-1: Main Behaviour

St	Procedure	Message Sequence		TP	Verdict
		U - S	Message		
1-1B	Check: Does the UE (MCData client) correctly perform steps 1a1-3 of procedure '**MCX SIP MESSAGE CT**' as described in TS 37.579-1 [2] Table 5.3.33.3-1 **to receive an FD message for one-to-one file distribution with disposition request "FILE DOWNLOAD COMPLETED UPDATE" and Mandatory Download IE**?	-	-	1	P
2-3	Void	-	-	-	-
4	Check: Does the UE (MCData client) correctly perform procedure '**FD file accept and download using HTTP**' as described in TS 37.579-1 [2] Table 5.3C.11.3-1 to download test file 1? (NOTE 2)	-	-	1,2	P
5-10	Void	-	-	-	-
11	Check: Does the UE (MCData client) notify the user of the incoming FD request and the file download? (NOTE 1)	-	-	1,2	P
12	Check: Has the UE (MCData client) downloaded test file 1 (Annex A.3.1)? (NOTE 1)	-	-	2	P
NOTE 1: This is expected to be done via a suitable implementation dependent MMI. NOTE 2: Test file 1 for CT FD as specified in annex A.3.1.					

6.2.6.3.3 Specific message contents

Table 6.2.6.3.3-1: SIP MESSAGE from the SS (step 1A, Table 6.2.6.3.2-1; step 2, TS 37.579-1 [2] Table 5.3.33.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.7.2-1, condition MCDATA_FD, MCDATA_SIGNALLING				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part		**MCData Info**		
MIME-part-body	MCData-Info as described in Table 6.2.6.3.3-2			
MIME body part		**MCData Data signalling message**		
MIME-part-body	MCData Protected Payload Message containing FD SIGNALLING PAYLOAD as described in Table 6.2.6.3.3-3			

Table 6.2.6.3.3-2: MCData-Info (Table 6.2.6.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.2.2-3, condition MCD_1to1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
mcdata-info				
mcdata-Params				
request-type	"one-to-one-fd"			

Table 6.2.6.3.3-3: FD Signalling Payload (Table 6.2.6.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.6-1, condition FD_HTTP				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Mandatory download	'0001'B	MANDATORY DOWNLOAD	TS 24.282 [31] clause 15.2.16	

Table 6.2.6.3.3-4: Void

Table 6.2.6.3.3-5: SIP MESSAGE from the UE (step 4, Table 6.2.6.3.2-1; step 2, TS 37.579-1 [2] Table 5.3C.11.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.7.1-1, condition MCDATA_FD, RESOURCE_LISTS, MCDATA_SIGNALLING				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part	not present	**MCData Info**		
MIME body part		**MCData Data signalling message**		
MIME-part-body	MCData Protected Payload Message containing FD NOTIFICATION as described in Table 6.2.6.3.3-6			

Table 6.2.6.3.3-6: FD NOTIFICATION (Table 6.2.6.3.3-5)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.7-1, condition FD_ACCEPTED

Table 6.2.6.3.3-7: HTTP GET from the UE (step 4, Table 6.2.6.3.2-1; step 4, TS 37.579-1 [2] Table 5.3C.11.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.4.2-1, condition FD_HTTP

Table 6.2.6.3.3-8: HTTP 200 (OK) from the SS (step 4, Table 6.2.6.3.2-1; step 5, TS 37.579-1 [2] Table 5.3C.11.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.4.6-1, condition FD_HTTP

Table 6.2.6.3.3-9..10: Void

Table 6.2.6.3.3-11: SIP MESSAGE from the UE (step 4, Table 6.2.6.3.2-1; step 6a1, TS 37.579-1 [2] Table 5.3C.11.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.7.1-1, condition MCDATA_FD, RESOURCE_LISTS, MCDATA_SIGNALLING				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part	not present	**MCData Info**		
MIME body part		**MCData Data signalling message**		
MIME-part-body	MCData Protected Payload Message containing FD NOTIFICATION as described in Table 6.2.6.3.3-12			

Table 6.2.6.3.3-12: FD NOTIFICATION (Table 6.2.6.3.3-11)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.7-1, condition FD_COMPLETED

6.2.7 On-network / File Distribution (FD) / FD Using HTTP / Group Standalone FD / Mandatory Download / Without Disposition Request / Client Originated (CO)

6.2.7.1 Test Purpose (TP)

(1)

```
with { UE (MCDATA Client) registered and authorised for MCDATA Service }
ensure that {
  when { the MCDATA User requests to send a Group Standalone FD message with a mandatory download
and without a disposition request and the UE (MCDATA Client) is unaware of the URL of the Media
Storage Function }
    then { UE (MCDATA Client) sends a SIP MESSAGE to find the URL of the Media Storage Function and
responds to a SIP MESSAGE that contains the URL of the Media Storage Function with a SIP 200 (OK)
message }
            }
```

(2)

```
with { UE (MCDATA Client) registered and authorised for MCDATA Service }
ensure that {
  when { the MCDATA User requests to send a Group Standalone FD message with a mandatory download
and without a disposition request and the UE (MCDATA Client) is aware of the URL of the Media
Storage Function }
    then { UE (MCDATA Client) uploads the file to the Media Storage Function via an HTTP POST
message and then sends the URL of the file location to the recipient via a SIP MESSAGE message }
            }
```

(3)

```
with { UE (MCDATA Client) having sent the URL of the file location to the recipient }
ensure that {
  when { UE (MCDATA Client) receives a FD notification via a SIP MESSAGE message }
    then { UE (MCDATA Client) responds to the SIP MESSAGE message with a SIP 200 (OK) message and
delivers the notification to the MCDATA User }
           }
```

6.2.7.2 Conformance requirements

References: The conformance requirements covered in the current TC are specified in: TS 24.282, clauses 10.2.1.3.2, 10.2.2.1, 10.2.4.2.1, 12.2.1.2. The following represents a copy/paste extraction of the requirements relevant to the test purpose; any references within the copy/paste text should be understood within the scope of the core spec they have been copied from. Unless otherwise stated, these are Rel-14 requirements.

[TS 24.282, clause 10.2.1.3.2]

To discover the absolute URI of the media storage function, the MCData client shall generate a SIP MESSAGE request towards the participating MCData function, in accordance with 3GPP TS 24.229 [5] and IETF RFC 3428 [6] with the clarifications given below.

The MCData client:

1) shall build the SIP MESSAGE request as specified in subclause 6.2.4.1;

2) shall follow the rules specified in subclause 6.4 for the handling of MIME bodies in a SIP message when processing the remaining steps in this subclause;

3) shall insert in the SIP MESSAGE request an application/vnd.3gpp.mcdata-info+xml MIME body with a <request-type> element containing the value "msf-disc-req";

4) if the upload of a file is for a group standalone FD request, shall include in an application/vnd.3gpp.mcdata-info+xml MIME body, the <mcdata-calling-group-id> element set to the required MCData group identity; and

NOTE 1: The absence of a group identity in the <mcdata-calling-group-id> element of the application/vnd.3gpp.mcdata-info+xml MIME body implies that the MCData client intends to upload a file for a one-to-one FD request. In this case, the participating MCData function identifies the MCData ID of the user from the binding between the public user identity and the MCData ID.

5) shall send the SIP MESSAGE request according to rules and procedures of 3GPP TS 24.229 [5].

On receipt of a "SIP MESSAGE request for absolute URI discovery response", the MCData client:

1) shall store the absolute URI found in the <mcdata-controller-psi> element;

2) shall generate a SIP 200 (OK) response according to rules and procedures of 3GPP TS 24.229 [5]; and

3) shall send the SIP 200 (OK) response towards the MCData server according to rules and procedures of 3GPP TS 24.229 [5].

[TS 24.282, clause 10.2.2.1]

If the media storage client is not aware of the absolute URI of the media storage function, the media storage client shall request the MCData client to discover the absolute URI associated with the media storage function by following the procedures in subclause 10.2.1.3.

The media storage client shall send HTTP requests over a TLS connection as specified for the HTTP client in the UE in annex A of 3GPP TS 24.482 [24].

NOTE 1: The HTTP client encodes the MCData ID in the bearer access token of the Authorization header field of an HTTP request as specified in 3GPP TS 24.482 [24].

NOTE 2: The HTTP client always sends the HTTP requests to an HTTP proxy. Annex A of 3GPP TS 24.482 [24] indicates how the HTTP proxy forwards the HTTP request to the HTTP server.

To upload a file to media storage function, the media storage client:

1) shall generate an HTTP POST request as specified in IETF RFC 7230 [22] and IETF RFC 7231 [23];

2) shall set the Request-URI to the absolute URI identifying the resource on a media storage function;

3) shall set the Host header field to a hostname identifying the media storage function;

4) shall set the Content-Type header field to multipart/mixed and with a boundary delimiter parameter set to any chosen value;

5) if the file upload is for one-to-one file distribution, shall insert an application/vnd.3gpp.mcdata-info+xml MIME body with:

   a) the <request-type> element set to a value of "one-to-one-fd"; and

   b) the <mcdata-calling-user-id> element set to the originating MCData ID;

6) if the file upload is for group file distribution, shall insert an application/vnd.3gpp.mcdata-info+xml MIME body with:

   a) the <request-type> element set to a value of "group-fd";

   b) the <mcdata-request-uri> element set to the MCData group identity; and

   c) the <mcdata-calling-user-id> element set to the originating MCData ID;

7) if end-to-end security is required for a one-to-one communication, the MCData client protects the binary data representing the file and prefixes the protected binary data with security parameters as described in 3GPP TS 33.180 [26];

8) if

   i) end-to-end security is not required for a one-to-one communication, or

   ii) the file upload is for group file distribution;

   shall include the binary data representing the file with Content-Type field set to application/octet-stream and Content-Length field set to the file size; and

9) shall send the HTTP POST request towards the media storage function.

On receipt of a HTTP 201 Created containing a Location header field with a URL identifying the location of the resource where the file has been stored on the media storage function, then the media storage client shall store this information.

[TS 24.282, clause 10.2.4.2.1]

The MCData client shall generate a SIP MESSAGE request in accordance with 3GPP TS 24.229 [5] and IETF RFC 3428 [6] with the clarifications given below.

The MCData client:

1) shall build the SIP MESSAGE request as specified in subclause 6.2.4.1;

2) if a one-to-one standalone FD message is to be sent shall insert in the SIP MESSAGE request:

   a) an application/resource-lists+xml MIME body with the MCData ID of the target MCData user, according to rules and procedures of IETF RFC 4826 [9]; and

   b) an application/vnd.3gpp.mcdata-info+xml MIME body with a <request-type> element set to a value of "one-to-one-fd";

…

4) shall generate a standalone FD message as specified in subclause 6.2.2.2; and

5) shall send the SIP MESSAGE request according to rules and procedures of 3GPP TS 24.229 [5].

[TS 24.282, clause 12.2.1.2]

Upon receipt of a:

"SIP MESSAGE request for SDS disposition notification for terminating MCData client"; or

"SIP MESSAGE request for FD disposition notification for terminating MCData client";

the MCData client:

1) shall decode the contents of the application/vnd.3gpp.mcdata-signalling MIME body; and
2) shall deliver the notification to the user or application.

6.2.7.3 Test description

6.2.7.3.1 Pre-test conditions

Test configuration:

- Single cell configuration according to TS 37.579-1 [2] clause 5.2.2.2.1.
- Test File 1 for CO FD as specified in annex A.2.1 is available at the UE for upload.

Preamble:

- The UE has performed procedure 'Initial registration' as described in TS 37.579-1 [2] clause 5.4.2.
- UE States at the end of the preamble:
  - The UE is in RRC_IDLE state.
  - The client is registered for MCData.

6.2.7.3.2 Test procedure sequence

Table 6.2.7.3.2-1: Main Behaviour

St	Procedure	Message Sequence		TP	Verdict
		U - S	Message		
1	Make the UE (MCData client) send test file 1 (Annex A.2.1) for CO group FD over HTTP for mandatory download and without disposition request. (NOTE 1, NOTE 2)	-	-	-	-
2	Check: Does the UE (MCData client) correctly perform procedure '**Discovery of the absolute URI of the media storage function (one-to-one communication)**' as described in TS 37.579-1 [2] Table 5.3C.9.3-1 ?	-	-	1	P
3	Check: Does the UE (MCData client) correctly perform procedure '**FD file upload using HTTP**' as described in TS 37.579-1 [2] Table 5.3C.10.3-1?	-	-	2	P
3A	Check: Is the content of the uploaded file the same as specified in annex A.2.1?	-	-	2	P
4-6	Void	-	-	-	-
7	Check: Does the UE (MCData client) correctly perform procedure '**MCX SIP MESSAGE CT**' as described in TS 37.579-1 [2] Table 5.3.33.3-1 **to receive an FD NOTIFICATION with disposition notification type "FILE DOWNLOAD REQUEST ACCEPTED"** for the FD message sent at step 3?	-	-	3	P
8	Void	-	-	-	-
9	Check: Does the UE (MCData client) notify the user that the remote client has accepted the download? (NOTE 1)	-	-	3	P
NOTE 1: This is expected to be done via a suitable implementation dependent MMI. NOTE 2: Test file 1 for CO FD as specified in annex A.2.1.					

6.2.7.3.3 Specific message contents

Table 6.2.7.3.3-1..6: Void

Table 6.2.7.3.3-7: HTTP POST from the UE (step 3, Table 6.2.7.3.2-1; step 2, TS 37.579-1 [2] Table 5.3C.10.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.4.3-1, condition FD_HTTP				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part		**MCData-Info**		
MIME-part-body	MCData-Info as described in Table 6.2.7.3.3-8			

Table 6.2.7.3.3-8: MCData-Info (Table 6.2.7.3.3-7)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.2.1-3				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
mcdata-info				
mcdata-Params				
request-type	"group-fd"			
mcdata-request-uri	px_MCData_Group_A_ID	NOTE: the element is not encrypted		
mcdata-calling-user-id	px_MCData_ID_User_A	NOTE: the element is not encrypted		

Table 6.2.7.3.3-9: Void

Table 6.2.7.3.3-10: HTTP 201 Created from the SS (step 3, Table 6.2.7.3.2-1; step 2, TS 37.579-1 [2] Table 5.3C.10.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.4.7-1, condition FD_HTTP

Table 6.2.7.3.3-11: SIP MESSAGE from the UE (step 3, Table 6.2.7.3.2-1; step 4, TS 37.579-1 [2] Table 5.3C.10.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.7.1-1, condition MCDATA_FD, MCDATA_SIGNALLING				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part		**MCData-Info**		
MIME-part-body	MCData-Info as described in Table 6.2.7.3.3-12			
MIME body part		**MCData Data signalling message**		
MIME-part-body	MCData Protected Payload Message containing FD SIGNALLING PAYLOAD as described in Table 6.2.7.3.3-13			

Table 6.2.7.3.3-12: MCData-Info (Table 6.2.7.3.3-11)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.2.1-3, condition MCD_grp				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
mcdata-info				
mcdata-Params				
request-type	"group-fd"			

Table 6.2.7.3.3-13: FD Signalling Payload (Table 6.2.5.3.3-12)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.5-1, condition FD_HTTP				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
FD disposition request type	Not present	no disposition request		
Mandatory download	'0001'B	MANDATORY DOWNLOAD	TS 24.282 [31] clause 15.2.16	

Table 6.2.7.3.3-14: SIP MESSAGE from the SS (step 7, Table 6.2.7.3.2-1; step 2, TS 37.579-1 [2] Table 5.3.33.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.7.2-1, condition MCDATA_FD, MCDATA_SIGNALLING				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part		**MCData-Info**		
MIME-part-body	MCData-Info as described in Table 6.2.1.3.3-15			
MIME body part		**MCData Data signalling message**		
MIME-part-body	MCData Protected Payload Message containing FD NOTIFICATION from the SS as described in Table 6.2.3.3.3-17			

Table 6.2.7.3.3-15: MCData-Info (Table 6.2.7.3.3-14)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.2.2-3				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
mcdata-info				
mcdata-Params				
mcdata-calling-group-id	Encrypted <mcdata-calling-group-id> with mcdataURI set to px_MCData_Group_A_ID	Encrypted according to TS 37.579-1 [2] Table 5.5.3.2.2-3A		

Table 6.2.7.3.3-16: FD NOTIFICATION (Table 6.2.7.3.3-14)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.8-1, condition FD_ACCEPTED

6.2.8 On-network / File Distribution (FD) / FD Using HTTP / Group Standalone FD / Mandatory Download / Without Disposition Request / Client Terminated (CT)

6.2.8.1 Test Purpose (TP)

(1)

```
with { UE (MCDATA Client) registered and authorised for MCDATA Service }
ensure that {
  when { UE (MCDATA Client) receives a SIP MESSAGE message for a group standalone FD message with a
mandatory download and without a disposition request }
    then { UE (MCDATA Client) responds with a SIP 200 (OK) message and notifies the MCDATA User
about the incoming FD request and that the file identified by file URL in the Payload data in the
Payload IE will be downloaded automatically and generates an FD NOTIFICATION indicating acceptance
of the FD request and attempts to download the file with an HTTP GET message }
            }
```

(2)

```
with { UE (MCDATA Client) having started to download the file by sending an HTTP GET message }
ensure that {
  when { UE (MCDATA Client) has successfully downloaded the file }
    then { UE (MCDATA Client) notifies the MCDATA User that the file has successfully downloaded }
            }
```

6.2.8.2 Conformance requirements

References: The conformance requirements covered in the current TC are specified in: TS 24.282, clauses 10.2.4.2.2, 10.2.1.2.3, 12.2.1.1, 10.2.3.1. The following represents a copy/paste extraction of the requirements relevant to the test purpose; any references within the copy/paste text should be understood within the scope of the core spec they have been copied from. Unless otherwise stated, these are Rel-14 requirements.

[TS 24.282, clause 10.2.4.2.2]

Upon receipt of a "SIP MESSAGE request for FD using HTTP for terminating MCData client", the MCData client:

1) may reject the SIP MESSAGE request if there are not enough resources to handle the SIP MESSAGE request;

2) if the SIP MESSAGE request is rejected in step 1), shall respond towards the participating MCData function with a SIP 480 (Temporarily unavailable) response and skip the rest of the steps of this subclause;

3) shall generate a SIP 200 (OK) response according to rules and procedures of 3GPP TS 24.229 [5];

4) shall send the SIP 200 (OK) response towards the MCData server according to rules and procedures of 3GPP TS 24.229 [5]; and

5) shall handle the received message as specified in subclause 10.2.1.2.

[TS 24.282, clause 10.2.1.2.3]

The MCData client:

1) if the FD SIGNALLING PAYLOAD message does not contain an Application ID IE:

   a) shall determine that the payload contained in the Payload IE in the FD SIGNALLING PAYLOAD message is for user consumption;

   b) shall notify the user about the incoming FD request; and

   c) if the FD SIGNALLING PAYLOAD message contains a Metadata IE, shall deliver the contents of the Metadata IE to the user;

2) if the FD SIGNALLING PAYLOAD message contains an Application ID IE:

   a) shall determine that the payload contained in the Payload IE in the FD SIGNALLING PAYLOAD message is not for user consumption;

   b) if the Application ID value is unknown, shall discard the FD message and exit this subclause;

   c) if the Application ID value is known, shall notify the application of the incoming FD request; and

NOTE 1: If FD request is addressed to a non-MCData application that is not running, the MCData client starts the local non-MCData application.

   d) if the FD SIGNALLING PAYLOAD message contains a Metadata IE, shall deliver the contents of the Metadata IE to the application;

3) shall start a timer TDU2 (FD non-mandatory download timer) with the timer value as specified in subclause F.2.3;

4) shall wait for the user or application to request to download the file indicated by file URL in the Payload data in the Payload IE in the FD SIGNALLING PAYLOAD message;

5) if the user or application accepts or rejects or decides to defer the FD request, shall stop timer TDU2 (FD non-mandatory download timer);

6) if the user deferred the FD request while the timer TDU2 (FD non-mandatory download timer) was running, shall generate an FD NOTIFICATION indicating deferral of the FD request as specified in subclause 12.2.1.1;

NOTE 2: Once the timer TDU2 (FD non-mandatory download timer) has expired the FD request can only be accepted or rejected with an appropriate action by the MCData client.

NOTE 3: Once the timer TDU2 (FD non-mandatory download timer) has expired, no action is taken by the MCData client if the FD request is deferred.

7) if the user or application rejects the FD request, shall generate an FD NOTIFICATION indicating rejection of the FD request as specified in subclause 12.2.1.1 and shall exit this subclause; and

8) if the user accepts the FD request:

   a) shall generate an FD NOTIFICATION indicating acceptance of the FD request as specified in subclause 12.2.1.1;

   b) if the FD SIGNALLING PAYLOAD message contains a new Conversation ID, shall instantiate a new conversation with the Message ID in the FD SIGNALLING PAYLOAD identifying the first message in the conversation thread;

   c) if the FD SIGNALLING PAYLOAD message contains an existing Conversation ID and:

      i) if the FD SIGNALLING PAYLOAD message does not contain an InReplyTo message ID, shall use the Message ID in the FD SIGNALLING PAYLOAD to identify a new message in the existing conversation thread; and

      ii) if the FD SIGNALLING PAYLOAD message contains an InReplyTo message ID, shall associate the message to an existing message in the conversation thread as identified by the InReplyTo message ID in the FD SIGNALLING PAYLOAD, and use the Message ID in the FD SIGNALLING PAYLOAD to identify the new message;

   d) may store the Conversation ID, Message ID, InReplyTo message ID and Date and time in local storage;

   e) shall attempt to download the file as identified by the file URL in the Payload IE in the FD SIGNALLING PAYLOAD message, as specified in subclause 10.2.3.1; and

   f) if the received FD SIGNALLING PAYLOAD message contains an FD disposition request type IE requesting a file download completed update, then after the file download has been successfully downloaded, shall generate an FD NOTIFICATION by following the procedures in subclause 12.2.1.1.

[TS 24.282, clause 12.2.1.1]

The MCData client shall follow the procedures in this subclause to:

- indicate to an MCData client that an SDS message was delivered, read or delivered and read when the originating client requested a delivery, read or delivery and read report;

- indicate to the participating MCData function serving the MCData user that an SDS message was undelivered. The participating MCData function can store the message for later re-delivery;

- indicate to an MCData client that a request for FD was accepted, deferred or rejected; or

- indicate to an MCData client that a file download has been completed;

Before sending a disposition notification the MCData client needs to determine:

- the group identity related to an SDS or FD message request received as part of a group communication. The MCData client determines the group identity from the contents of the <mcdata-calling-group-id> element contained in the application/vnd.3gpp.mcdata-info+xml MIME body of the incoming SDS or FD message request; and

- the MCData user targeted for the disposition notification. The MCData client determines the targeted MCData user from the contents of the <mcdata-calling-user-id> element contained in the application/vnd.3gpp.mcdata-info+xml MIME body of the incoming SDS or FD message request.

The MCData client shall generate a SIP MESSAGE request in accordance with 3GPP TS 24.229 [5] and IETF RFC 3428 [6] with the clarifications given below.

The MCData client:

1) shall build the SIP MESSAGE request as specified in subclause 6.2.8.1;

2) shall follow the rules specified in subclause 6.4 for the handling of MIME bodies in a SIP message when processing the remaining steps in this subclause;

3) shall insert in the SIP MESSAGE request an application/resource-lists+xml MIME body containing the MCData ID of the targeted MCData user, according to rules and procedures of IETF RFC 5366 [18];

4) void;

5) if sending a disposition notification in response to an MCData group data request, shall include an <mcdata-calling-group-id> element set to the MCData group identity in the application/vnd.3gpp.mcdata-info+xml MIME body;

6) if requiring to send an SDS notification, shall generate an SDS NOTIFICATION message and include it in the SIP MESSAGE request as specified in subclause 6.2.3.1;

7) if requiring to send an FD notification, shall generate an FD NOTIFICATION message and include it in the SIP MESSAGE request as specified in subclause 6.2.3.2; and

8) shall send the SIP MESSAGE request according to rules and procedures of 3GPP TS 24.229 [5].

[TS 24.282, clause 10.2.3.1]

The media storage client on the MCData client shall send HTTP requests over a TLS connection as specified for the HTTP client in the UE, in annex A of 3GPP TS 24.482 [24].

NOTE 1: The HTTP client encodes the MCData ID in the bearer access token of the Authorization header field of an HTTP request as specified in 3GPP TS 24.482 [24].

NOTE 2: The HTTP client always sends the HTTP requests to an HTTP proxy. Annex A of 3GPP TS 24.482 [24] indicates how the HTTP proxy forwards the HTTP request to the HTTP server.

To download a file from the media storage function on the controlling MCData function, the media storage client on the MCData client:

1) shall generate an HTTP GET request as specified in IETF RFC 7230 [22] and IETF RFC 7231 [23] with a Request-URI set to an absolute URI identifying the URL of the file being requested from the media storage function on the controlling MCData function; and

2) shall send the HTTP GET request towards the media storage function on the controlling MCData function.

On receipt of a HTTP 200 OK response containing the requested file, the MCData client shall notify the user or application that the file has been successfully downloaded.

6.2.8.3 Test description

6.2.8.3.1 Pre-test conditions

Test configuration:

- Single cell configuration according to TS 37.579-1 [2] clause 5.2.2.2.1.
- Test files downloaded or received at previous test runs are deleted.

Preamble:

- The UE has performed procedure 'Initial registration' as described in TS 37.579-1 [2] clause 5.4.2.
- UE States at the end of the preamble:
  - The UE is in RRC_IDLE state.
  - The client is registered for MCData.

6.2.8.3.2 Test procedure sequence

Table 6.2.8.3.2-1: Main Behaviour

St	Procedure	Message Sequence		TP	Verdict
		U - S	Message		
1-1B	Check: Does the UE (MCData client) correctly perform steps 1a1-3 of the procedure '**MCX SIP MESSAGE CT**' as described in TS 37.579-1 [2] Table 5.3.33.3-1 **to receive an FD message for group file distribution with disposition request "FILE DOWNLOAD COMPLETED UPDATE" and Mandatory Download IE**?	-	-	1	P
2-3	Void	-	-	-	-
4-4C	Check: Does the UE (MCData client) correctly perform steps 2-5 of procedure '**FD file accept and download using HTTP**' as described in TS 37.579-1 [2] Table 5.3C.11.3-1 to download test file 1? (NOTE 2)	-	-	1,2	P
5-7	Void	-	-	-	-
-	EXCEPTION: In parallel to the events described in step 8 and step 9 the events described in Table 6.2.8.3.2-2 take place.	-	-	-	-
8	Check: Does the UE (MCData client) notify the user of the incoming FD request and the file download? (NOTE 1)	-	-	1,2	P
9	Check: Has the UE (MCData client) downloaded test file 1 (Annex A.3.1)? (NOTE 1)	-	-	2	P
10	The procedure 'MCX communication release' as described in TS 37.579-1 [2] clause 5.4.14 is performed to release the RRC connection.	-	-	-	-
NOTE 1: This is expected to be done via a suitable implementation dependent MMI. NOTE 2: Test file 1 for CT FD as specified in annex A.3.1.					

Table 6.2.8.3.2-2: Parallel Behaviour

St	Procedure	Message Sequence		TP	Verdict
		U - S	Message		
1	Check: Does the UE (MCData client) send a SIP MESSAGE request for notification of file download completed in parallel to step 8 and step 9 of Table 6.2.8.3.22-1 or at least for 10s?	-->	SIP MESSAGE	-	F

6.2.8.3.3 Specific message contents

Table 6.2.8.3.3-1: SIP MESSAGE from the SS (step 1A, Table 6.2.8.3.2-1; step 2, TS 37.579-1 [2] Table 5.3.33.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.7.2-1, condition MCDATA_FD, MCDATA_SIGNALLING				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part		**MCData-Info**		
MIME-part-body	MCData-Info as described in Table 6.2.8.3.3-2			
MIME body part		**MCData Data signalling message**		
MIME-part-body	MCData Protected Payload Message containing FD SIGNALLING PAYLOAD as described in Table 6.2.8.3.3-3			

Table 6.2.8.3.3-2: MCData-Info (Table 6.2.8.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.2.2-3, condition MCD_grp				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
mcdata-info				
mcdata-Params				
request-type	"group-fd"			

Table 6.2.8.3.3-3: FD Signalling Payload (Table 6.2.6.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.6-1, condition FD_HTTP				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
FD disposition request type	Not present	no disposition request		
Mandatory download	'0001'B	MANDATORY DOWNLOAD	TS 24.282 [31] clause 15.2.16	

Table 6.2.8.3.3-4: Void

Table 6.2.8.3.3-5: SIP MESSAGE from the UE (step 4, Table 6.2.8.3.2-1; step 2, TS 37.579-1 [2] Table 5.3C.11.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.7.1-1, condition MCDATA_FD, RESOURCE_LISTS, MCDATA_SIGNALLING				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part		**MCData-Info**		
MIME-part-headers	MCData-Info as described in Table 6.2.8.3.3-6			
MIME body part		**MCData Data signalling message**		
MIME-part-body	MCData Protected Payload Message containing FD NOTIFICATION as described in Table 6.2.8.3.3-7			

Table 6.2.8.3.3-6: MCData-Info (Table 6.2.8.3.3-5)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.2.1-3				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
mcdata-info				
mcdata-Params				
mcdata-calling-group-id	Encrypted <mcdata-request-uri> with mcdataURI set to px_MCData_Group_A_ID	Encrypted according to TS 37.579-1 [2] Table 5.5.3.2.1-3A		

Table 6.2.8.3.3-7: FD NOTIFICATION (Table 6.2.8.3.3-5)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.7-1, condition FD_ACCEPTED

Table 6.2.8.3.3-8: HTTP GET from the UE (step 4, Table 6.2.8.3.2-1; step 4, TS 37.579-1 [2] Table 5.3C.11.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.4.2-1, condition FD_HTTP

Table 6.2.8.3.3-9: HTTP 200 (OK) from the SS (step 4, Table 6.2.8.3.2-1; step 5, TS 37.579-1 [2] Table 5.3C.11.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.4.6-1, condition FD_HTTP

Table 6.2.8.3.3-10: Void

6.2.9 On-network / File Distribution (FD) / FD Using Media Plane / One-to-one Standalone FD / Client Originated (CO)

6.2.9.1 Test Purpose (TP)

(1)

```
with { UE (MCDATA Client) registered and authorised for MCDATA Service }
ensure that {
  when { the MCDATA User requests to send a one-to-one standalone FD message using the media plane}
    then { UE (MCDATA Client) sends a request to establish an MSRP connection via a SIP INVITE
message and then responds to the SIP 200 (OK) message with a SIP ACK message }
            }
```

(2)

```
with { UE (MCDATA Client) having requested the establishment of a MSRP connection }
ensure that {
  when { UE (MCDATA Client) receives a SIP 200 (OK) message with the a=setup attribute set to
"passive"  from the SS (MCDATA server) }
    then { UE (MCDATA Client) sends a blank MSRP SEND message to bind the MSRP connection and then
sends the one-to-one standalone FD message via a MSRP SEND message }
            }
```

(3)

```
with { UE (MCDATA Client) having sent a one-to-one standalone FD message using the media plane }
ensure that {
  when { UE (MCDATA Client receives a MSRP 200 (OK) message in response to the last MSRP SEND
message indicating that the standalone FD message has been successfully transferred }
    then { UE (MCDATA Client) sends a SIP BYE message }
            }
```

(4)

```
with { UE (MCDATA Client) having sent a one-to-one standalone FD message using the media plane with
a disposition of "FILE DOWNLOAD COMPLETED UPDATE" }
ensure that {
  when { UE (MCDATA Client receives a disposition response via a SIP MESSAGE message from the SS
(MCDATA Server }
    then { UE (MCDATA Client) responds to the SIP MESSAGE message by sending a SIP 200 (OK) message
and delivers the notification to the MCDATA User }
            }
```

6.2.9.2 Conformance requirements

References: The conformance requirements covered in the current TC are specified in: TS 24.282, clauses 10.2.5.2.3, 6.2.2.3, 12.2.1.2, TS 24.582 clause 7.1.2.1. The following represents a copy/paste extraction of the requirements relevant to the test purpose; any references within the copy/paste text should be understood within the scope of the core spec they have been copied from. Unless otherwise stated, these are Rel-14 requirements.

[TS 24.282, clause 10.2.5.2.3]

The MCData client shall generate a SIP INVITE request in accordance with 3GPP TS 24.229 [5] with the clarifications given below.

The MCData client:

1) shall include the g.3gpp.mcdata.fd media feature tag and the g.3gpp.icsi-ref media feature tag with the value of "urn:urn-7:3gpp-service.ims.icsi.mcdata.fd" in the Contact header field of the SIP INVITE request according to IETF RFC 3840 [16];

2) shall include an Accept-Contact header field containing the g.3gpp.mcdata.fd media feature tag along with the "require" and "explicit" header field parameters according to IETF RFC 3841 [8];

3) shall include an Accept-Contact header field with the g.3gpp.icsi-ref media feature tag containing the value of "urn:urn-7:3gpp-service.ims.icsi.mcdata.fd" along with the "require" and "explicit" header field parameters according to IETF RFC 3841 [8];

4) shall include the ICSI value "urn:urn-7:3gpp-service.ims.icsi.mcdata.fd" (coded as specified in 3GPP TS 24.229 [5]), in a P-Preferred-Service header field according to IETF RFC 6050 [7] in the SIP INVITE request;

5) should include the "timer" option tag in the Supported header field;

6) should include the Session-Expires header field according to IETF RFC 4028 [38]. It is recommended that the "refresher" header field parameter is omitted. If included, the "refresher" header field parameter shall be set to "uac";

7) shall generate and contain an application/vnd.3gpp.mcdata-signalling MIME body with the FD SIGNALLING PAYLOAD as described in subclause 6.2.2.3;

8) if a one-to-one file distribution is requested:

   a) shall insert in the SIP INVITE request a MIME resource-lists body with the MCData ID of the invited MCData user, according to rules and procedures of IETF RFC 5366 [18]; and

   b) shall contain an application/vnd.3gpp.mcdata-info+xml MIME body with the <mcdatainfo> element containing the <mcdata-Params> element with:

      i) the <request-type> element set to a value of "one-to-one-fd";

   c) if an end-to-end security context needs to be established and the security context does not exist or if the existing security context has expired, then:

      i) if necessary, shall instruct the key management client to request keying material from the key management server as described in 3GPP TS 33.180 [26];

      ii) shall use the keying material to generate a PCK as described in 3GPP TS 33.180 [26];

iii) shall use the PCK to generate a PCK-ID with the four most significant bits set to "0001" to indicate that the purpose of the PCK is to protect one-to-one communications and with the remaining twenty eight bits being randomly generated as described in 3GPP TS 33.180 [26];

iv) shall encrypt the PCK to a UID associated to the MCData client using the MCData ID of the invited user and a time related parameter as described in 3GPP TS 33.180 [26];

v) shall generate a MIKEY-SAKKE I_MESSAGE using the encapsulated PCK and PCK-ID as specified in 3GPP TS 33.180 [26]; and

vi) shall add the MCData ID of the originating MCData to the initiator field (IDRi) of the I_MESSAGE as described in 3GPP TS 33.180 [26]; and

vii) shall sign the MIKEY-SAKKE I_MESSAGE using the originating MCData user's signing key provided in the keying material together with a time related parameter, and add this to the MIKEY-SAKKE payload, as described in 3GPP TS 33.180 [26];

9) if a group file distribution is requested:

a) if the "/<*x*>/<x>/Common/MCData/AllowedFD" leaf node present in the group document of the requested MCData group, configured on the group management client as specified in 3GPP TS 24.483 [42] is set to "false", shall reject the request for FD and not continue with the rest of the steps in this subclause; and

b) shall contain in an application/vnd.3gpp.mcdata-info+xml MIME body with the <mcdatainfo> element containing the <mcdata-Params> element with:

i) the <request-type> element set to a value of "group-fd";

ii) the <mcdata-request-uri> element set to the MCData group identity; and

iii) the <mcdata-client-id> element set to the MCData client ID of the originating MCData client;

NOTE 1: The MCData client does not include the MCData ID of the originating MCData user in the body, as this will be inserted into the body of the SIP INVITE request that is sent from the originating participating MCData function.

10) shall set the Request-URI of the SIP INVITE request to the public service identity identifying the participating MCData function serving the MCData user;

NOTE 2: The MCData client is configured with public service identity identifying the participating MCData function serving the MCData user.

11) may include a P-Preferred-Identity header field in the SIP INVITE request containing a public user identity as specified in 3GPP TS 24.229 [5];

12) shall include an SDP offer according to 3GPP TS 24.229 [5] with the clarifications given in subclause 10.2.5.2.1; and

13) shall send the SIP INVITE request towards the MCData server according to 3GPP TS 24.229 [5].

On receipt of a SIP 2xx response to the SIP INVITE request, the MCData client:

1) shall send a SIP ACK request as specified in 3GPP TS 24.229 [5];

2) shall start the SIP Session timer according to rules and procedures of IETF RFC 4028 [38]; and

3) shall interact with the media plane as specified in 3GPP TS 24.582 [15] subclause 10.2.5.1.1..

[TS 24.282, clause 6.2.2.3]

In order to generate an FD message, the MCData client:

1) shall generate an FD SIGNALLING PAYLOAD message as specified in subclause 15.1.3; and

2) shall include in the SIP request, the FD SIGNALLING PAYLOAD message in an application/vnd.3gpp.mcdata-signalling MIME body as specified in subclause E.1.

When generating an FD SIGNALLING PAYLOAD message as specified in subclause 15.1.3, the MCData client:

1) shall set the Date and time IE to the current time as specified in subclause 15.2.8;

2) if the filestarts a new conversation, shall set the Conversation ID IE to a newly generated Conversation ID value as specified in subclause 15.2.9;

3) if the file continues an existing conversation, shall set the Conversation ID IE to the Conversation ID value of the existing conversation as specified in subclause 15.2.9;

4) shall set the Message ID IE to a newly generated Message ID value as specified in subclause 15.2.10;

5) if the files in reply to a previously received SDS message or file, shall include the InReplyTo message ID IE with the Message ID value in the previously received SDS message or file;

6) if the file is for user consumption, shall not include an Application ID IE as specified in subclause 15.2.7;

7) if the file is intended for an application on the terminating MCData client, shall include an Application ID IE with an Application ID value representing the intended application as specified in subclause 15.2.7;

NOTE: The value chosen for the Application ID value is decided by the mission critical organisation.

8) if a file download complete notification is required shall include a FD disposition request type IE set to "FILE DOWNLOAD COMPLETED UPDATE" as specified in subclause 15.2.4; and

9) shall include and set the Mandatory download IE to "MANDATORY DOWNLOAD" as described in subclause 15.2.16.

[TS 24.282, clause 12.2.1.2]

Upon receipt of a:

"SIP MESSAGE request for SDS disposition notification for terminating MCData client"; or

"SIP MESSAGE request for FD disposition notification for terminating MCData client";

the MCData client:

1) shall decode the contents of the application/vnd.3gpp.mcdata-signalling MIME body; and

2) shall deliver the notification to the user or application.

[TS 24.582, clause 6.1.1.2.1]

Upon receiving an indication to establish MSRP connection for standalone SDS using media plane as the originating client, the MCData client:

1. shall act as an MSRP client according to IETF RFC 6135 [12];

2. shall act according to IETF RFC 6135 [12], as:

   a. an "active" endpoint, if a=setup attribute in the received SDP answer is set to "passive"; and

   b. an "passive" endpoint, if a=setup attribute in the received SDP answer is set to "active";

3. shall establish the MSRP connection according to the MSRP connection parameters in the SDP answer received in the SIP 200 (OK) response according to IETF RFC 4975 [11]; and

4. if acting as an "active" endpoint, shall send an empty MSRP SEND request to bind the MSRP connection to the MSRP session from the perspective of the passive endpoint according to the rules and procedures of IETF RFC 4975 [11] and IETF RFC 6135 [12].

On receiving MSRP 200 (OK) response to the first MSRP SEND request, the MCData client:

1. shall generate a SDS SIGNALLING PAYLOAD as specified in subclause 6.1.1.2.2;

2. shall generate a SDS DATA PAYLOAD as specified in subclause 6.1.1.2.3;

3. shall include the SDS SIGNALLING PAYLOAD and SDS DATA PAYLOAD in an MSRP SEND request as specified in subclause 6.1.1.2.4; and

4. shall send the MSRP SEND request on the established MSRP connection.

NOTE: MSRP chunking, if needed, may affect the number of "Content Type" lines in each MSRP SEND message conveying a chunk, as also specified in subclause 6.1.1.2.4.

If MSRP chunking is not used then on receipt of a 200 (OK) response, the MCData client shall terminate the SIP session as specified in 3GPP TS 24.282 [8].

If MSRP chunking is used, the MCData client:

1. shall send further MSRP SEND requests as necessary;

2. shall wait for a 200 (OK) response to each MSRP SEND request sent; and

3. on receipt of the last 200 (OK) response shall terminate the SIP session as specified in 3GPP TS 24.282 [8].

On receiving a non-200 MSRP response to the MSRP SEND request the MCData client shall handle the error as specified in IETF RFC 4975 [11]. To terminate the MSRP session, the MCData client:

1. if there are further MSRP chunks to send, shall abort transmission of these further MSRP chunks;

2. shall indicate to MCData user that the SDS message could not be sent; and

3. shall terminate the SIP session as specified in 3GPP TS 24.282 [8].

On receiving an indication to terminate the session from the signalling plane, the MCData client:

1. if there are further MSRP chunks to send, shall abort transmission of these further MSRP chunks and may indicate to MCData user that the SDS message could not be sent.

[TS 24.582, clause 7.1.2.1]

Upon receiving an indication to establish MSRP connection for file distribution as the originating client, the MCData client:

1. shall act as an MSRP client according to IETF RFC 6135 [12];

2. shall act according to IETF RFC 6135 [12], as:

   a. an "active" endpoint, if a=setup attribute in the received SDP answer is set to "passive"; and

   b. an "passive" endpoint, if a=setup attribute in the received SDP answer is set to "active";

3. shall establish the MSRP connection according to the MSRP connection parameters in the SDP answer received in the SIP 200 (OK) response according to IETF RFC 4975 [11]; and

4. if acting as an "active" endpoint, shall send an empty MSRP SEND request to bind the MSRP connection to the MSRP session from the perspective of the passive endpoint according to the rules and procedures of IETF RFC 4975 [11] and IETF RFC 6135 [12].

On receiving MSRP 200 (OK) response to the first MSRP SEND request, the MCData client can send the file. To send the file, the MCData client:

1. shall generate MSRP SEND for file distribution request according to IETF RFC 4975 [11]. When generating an MSRP SEND, the MCData client:

   a. shall set To-Path header according to the MSRP URI(s) received in the answer SDP;

   b. shall set the first content type as Content-Type = "application/vnd.3gpp.mcdata-file"; and

   c. shall set the body of the MSRP SEND request with MSRP payload. MSRP payload is set to the file or part of the file.

2. shall send the MSRP SEND request(s) on the established MSRP connection.

If MSRP chunking is used, the MCData client:

1. shall send further MSRP SEND requests containing the file as necessary;
2. shall wait for a 200 (OK) response to each MSRP SEND request sent; and
3. on receipt of the last 200 (OK) response shall terminate the SIP session as specified in 3GPP TS 24.282 [8].

On receiving a non-200 MSRP response to the MSRP SEND request the MCData client shall handle the error as specified in IETF RFC 4975 [11]. To terminate the MSRP session, the MCData client:

1. if there are further MSRP chunks to send, shall abort transmission of these further MSRP chunks;
2. shall indicate to MCData user that the file could not be distributed; and
3. shall terminate the SIP session as specified in 3GPP TS 24.282 [8].

6.2.9.3 Test description

6.2.9.3.1 Pre-test conditions

Test configuration:

- Single cell configuration according to TS 37.579-1 [2] clause 5.2.2.2.1.
- Test File 1 for CO FD as specified in annex A.2.1 is available at the UE for upload.

Preamble:

- The UE has performed procedure 'Initial registration' as described in TS 37.579-1 [2] clause 5.4.2.
- UE States at the end of the preamble:
  - The UE is in RRC_IDLE state.
  - The client is registered for MCData.

6.2.9.3.2 Test procedure sequence

Table 6.2.9.3.2-1: Main Behaviour

St	Procedure	Message Sequence		TP	Verdict
		U - S	Message		
1	Make the UE (MCData client) send test file 1 (Annex A.2.1) for CO one-to-one FD over media plane with disposition notification type "FILE DOWNLOAD COMPLETED UPDATE". (NOTE 1, NOTE 2)	-	-	-	-
2	Check: Does the UE (MCData client) correctly perform procedure '**CO MCData Call Establishment**' as described in TS 37.579-1 [2] Table 5.3C.2.3-1?	-	-	1,2	P
3-6	Void	-	-	-	-
7	Check: Does the UE (MCData client) correctly perform procedure '**CO MSRP message transfer**' as described in TS 37.579-1 [2] Table 5.3C.4.3-1 **to send an FD message containing test file 1 for CO FD**?	-	-	2	P
7A	Check: Is the content of the transferred file the same as specified in annex A.2.1?	-	-	2	P
8	Check: Does the UE (MCData client) correctly perform procedure '**CO MCData call release**' as described in TS 37.579-1 [2] Table 5.3C.6.3-1? (NOTE 3)	-	-	3	P
9	Void	-	-	-	-
10	Check: Does the UE (MCData client) correctly perform procedure '**MCX SIP MESSAGE CT**' as described in TS 37.579-1 [2] Table 5.3.33.3-1 **to receive the disposition notification** for the FD message sent at step 7?	-	-	4	P
11	Void	-	-	-	-
12	Check: Does the UE (MCData client) provide the disposition notification to the user? (NOTE 1)	-	-	4	P
NOTE 1: This is expected to be done via a suitable implementation dependent MMI. NOTE 2: Test file 1 for CO FD as specified in annex A.2.1. NOTE 3: The procedure does not release the RRC connection.					

6.2.9.3.3 Specific message contents

Table 6.2.9.3.3-1: SIP INVITE from the UE (step 2, Table 6.2.9.3.2-1; step 2, TS 37.579-1 [2] Table 5.3C.2.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.5.1-1, condition MCDATA_FD, MCD_1to1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part		**SDP message**		
MIME-part-body	SDP message as described in Table 6.2.9.3.3-2			
MIME body part		**MCData-Info**		
MIME-part-body	MCData-Info as described in Table 6.2.9.3.3-3			
MIME body part		**MCData Data signalling message**		
MIME-part-headers				
MIME-Content-Type	"application/vnd.3gpp. mcdata-signalling"			
MIME-part-body	MCData Protected Payload Message containing FD SIGNALLING PAYLOAD as described in Table 6.2.9.3.3-3A			

Table 6.2.9.3.3-2: SDP for SIP INVITE (Table 6.2.9.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.1.1-3, condition MCDATA_FD, SDP_OFFER, MCD_1to1

Table 6.2.9.3.3-3: MCData-Info (Table 6.2.9.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.2.1-3, condition MCD_1to1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
mcdata-info				
mcdata-Params				
request-type	"one-to-one-fd"			

Table 6.2.9.3.3-3A: FD SIGNALLING PAYLOAD (Table 6.2.9.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.5-1, condition FD_MSRP

Table 6.2.9.3.3-4: SIP 200 (OK) from the SS (step 2, Table 6.2.9.3.2-1; step 4, TS 37.579-1 [2] Table 5.3C.2.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.17.1.2-1, condition INVITE-RSP				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
SDP message	As described in Table 6.2.9.3.3-5			

Table 6.2.9.3.3-5: SDP for SIP 200 (OK) (Table 6.2.9.3.3-4)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.1.2-3, condition MCDATA_FD, SDP_ANSWER

Table 6.2.9.3.3-6: MSRP SEND from the UE (step 7, Table 6.2.9.3.2-1; step 1, TS 37.579-1 [2] Table 5.3C.4.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.12.1.1-1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Content-Type				
media-type	"application/vnd.3gpp. mcdata-file"			
data	As specified in table 6.2.9.3.3-8			

Table 6.2.9.3.3-7: Void

Table 6.2.9.3.3-8: MCData Protected Payload Message (Table 6.2.9.3.3-6)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.10-1, condition PROTECTED_FILE, PCK

Table 6.2.9.3.3-9..10: Void

Table 6.2.9.3.3-11: SIP BYE from the UE (step 8, Table 6.2.9.3.2-1; step 1, TS 37.579-1 [2] Table 5.3C.6.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.2.1-1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Reason			RFC 3326 [125]	
reason-value	"SIP"			
protocol-cause	"cause="200""			
reason-text	"text="transmission succeeded""			

Table 6.2.9.3.3-12: Void

Table 6.2.9.3.3-13: SIP MESSAGE from the SS (step 10, Table 6.2.9.3.2-1; step 2, TS 37.579-1 [2] Table 5.3.33.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.7.2-1, condition MCDATA_FD, MCDATA_SIGNALLING				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part		**MCData Data signalling message**		
MIME-part-body	MCData Protected Payload Message containing FD NOTIFICATION as described in Table 6.2.9.3.3-15			

Table 6.2.9.3.3-14: Void

Table 6.2.9.3.3-15: FD NOTIFICATION (Table 6.2.9.3.3-13)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.8-1, condition FD_COMPLETED

Table 6.2.9.3.3-16: Void

6.2.10 On-network / File Distribution (FD) / FD Using Media Plane / One-to-one Standalone FD / Client Terminated (CT)

6.2.10.1 Test Purpose (TP)

(1)

```
with { UE (MCDATA Client) registered and authorised for MCDATA Service }
ensure that {
  when { the MCDATA User receives a SIP INVITE to initiate a standalone one-to-one FD message using
the media plane }
    then { UE (MCDATA Client) responds by sending a SIP 200 (OK) message }
            }
```

(2)

```
with { UE (MCDATA Client) having responded to the SIP INVITE message that initiated a standalone
one-to-one FD message using the media plane }
ensure that {
  when { UE (MCDATA Client) receives an MSRP SEND message from the SS (MCDATA Server) }
    then { UE (MCDATA Client) responds with an MSRP 200 (OK) message }
            }
```

(3)

```
with { UE (MCDATA Client) having finished receiving the file from the SS (MCDATA server) }
ensure that {
  when { UE (MCDATA Client) receives a SIP BYE message to release communications }
    then { UE (MCDATA Client) responds with a SIP 200 (OK) message and then sends a "FILE DOWNLOAD
COMPLETED" disposition via a SIP MESSAGE message }
            }
```

6.2.10.2 Conformance requirements

References: The conformance requirements covered in the current TC are specified in: TS 24.282, clauses 10.2.5.2.4, 12.2.1.1, 6.2.3.2, TS 24.582 clauses 7.1.3.1, 7.1.3.2. The following represents a copy/paste extraction of the requirements relevant to the test purpose; any references within the copy/paste text should be understood within the scope of the core spec they have been copied from. Unless otherwise stated, these are Rel-14 requirements.

[TS 24.282, clause 10.2.5.2.4]

Upon receipt of an initial SIP INVITE request, the MCData client shall follow the procedures for termination of multimedia sessions in the IM CN subsystem as specified in 3GPP TS 24.229 [5] with the clarifications below.

The MCData client:

1) may reject the SIP INVITE request if either of the following conditions are met:

   a) MCData client does not have enough resources to handle the call; or

   b) any other reason outside the scope of this specification;

   and skip the rest of the steps after step 2;

2) if the SIP INVITE request is rejected in step 1), shall respond toward participating MCData function either with appropriate reject code as specified in 3GPP TS 24.229 [5] and warning texts as specified in subclause 4.9 or with SIP 480 (Temporarily unavailable) response not including warning texts if the user is authorised to restrict the reason for failure and skip the rest of the steps of this subclause;

3) if the SDP offer of the SIP INVITE request contains an "a=key-mgmt" attribute field with a "mikey" attribute value containing a MIKEY-SAKKE I_MESSAGE:

   a) shall extract the MCData ID of the originating MCData user from the initiator field (IDRi) of the I_MESSAGE as described in 3GPP TS 33.180 [26];

   b) shall convert the MCData ID to a UID as described in 3GPP TS 33.180 [26];

c) shall use the UID to validate the signature of the MIKEY-SAKKE I_MESSAGE as described in 3GPP TS 33.180 [26];

d) if authentication verification of the MIKEY-SAKKE I_MESSAGE fails, shall reject the SIP INVITE request with a SIP 488 (Not Acceptable Here) response as specified in IETF RFC 4567 [45], and include warning text set to "136 authentication of the MIKEY-SAKKE I_MESSAGE failed" in a Warning header field as specified in subclause 4.9 and not continue with rest of the steps in this subclause; and

e) if the signature of the MIKEY-SAKKE I_MESSAGE was successfully validated:

i) shall extract and decrypt the encapsulated PCK using the terminating user's (KMS provisioned) UID key as described in 3GPP TS 33.180 [26]; and

ii) shall extract the PCK-ID, from the payload as specified in 3GPP TS 33.180 [26];

NOTE: With the PCK successfully shared between the originating MCData client and the terminating MCData client, both clients are able to create an end-to-end secure session.

4) may display to the MCData user the MCData ID of the inviting MCData user;

5) may display to the MCData user the file meta-data of the incoming file as described by the SDP included in the received SIP INVITE request;

6) if the Mandatory indication IE of the FD SIGNALLING PAYLOAD contained in the application/vnd.3gpp.mcdata-signalling MIME body received in the SIP INVITE request is set to "MANDATORY", then:

i) shall accept the SIP INVITE request and generate a SIP 200 (OK) response according to rules and procedures of 3GPP TS 24.229 [5];

ii) shall include the option tag "timer" in a Require header field of the SIP 200 (OK) response;

iii) shall include the Session-Expires header field in the SIP 200 (OK) response and start the SIP session timer according to IETF RFC 4028 [38]. The "refresher" parameter in the Session-Expires header field shall be set to "uas";

iv) shall include the g.3gpp.mcdata.fd media feature tag in the Contact header field of the SIP 200 (OK) response;

v) shall include the g.3gpp.icsi-ref media feature tag containing the value of "urn:urn-7:3gpp-service.ims.icsi.mcdata.fd" in the Contact header field of the SIP 200 (OK) response;

vi) shall include an SDP answer in the SIP 200 (OK) response to the SDP offer in the incoming SIP INVITE request according to 3GPP TS 24.229 [5] with the clarifications given in subclause 10.2.5.2.2; and

vii) shall send the SIP 200 (OK) response towards the MCData server according to rules and procedures of 3GPP TS 24.229 [5].

On receipt of an SIP ACK message to the sent SIP 200 (OK) message, the MCData client shall:

1) shall interact with the media plane as specified in 3GPP TS 24.582 [15] subclause 10.2.5.1.2.

On receipt of an indication from the media plane of the successful download of the file and if the received FD SIGNALLING PAYLOAD message contained an FD disposition request type IE requesting a file download completed update indication, then, the MCData client:

1) shall follow the procedures described in subclause 12.2.1.1.

[TS 24.282, clause 12.2.1.1]

The MCData client shall follow the procedures in this subclause to:

- indicate to an MCData client that an SDS message was delivered, read or delivered and read when the originating client requested a delivery, read or delivery and read report;

- indicate to the participating MCData function serving the MCData user that an SDS message was undelivered. The participating MCData function can store the message for later re-delivery;

- indicate to an MCData client that a request for FD was accepted, deferred or rejected; or
- indicate to an MCData client that a file download has been completed;

Before sending a disposition notification the MCData client needs to determine:

- the controlling MCData function that sent the SDS or FD message request. The MCData client determines the controlling MCData function from the contents of the <mcdata-controller-psi> element contained in the application/vnd.3gpp.mcdata-info+xml MIME body of the incoming SDS or FD message request;
- the group identity related to an SDS or FD message request received as part of a group communication. The MCData client determines the group identity from the contents of the <mcdata-calling-group-id> element contained in the application/vnd.3gpp.mcdata-info+xml MIME body of the incoming SDS or FD message request; and
- the MCData user targeted for the disposition notification. The MCData client determines the targeted MCData user from the contents of the <mcdata-calling-user-id> element contained in the application/vnd.3gpp.mcdata-info+xml MIME body of the incoming SDS or FD message request.

The MCData client shall generate a SIP MESSAGE request in accordance with 3GPP TS 24.229 [5] and IETF RFC 3428 [6] with the clarifications given below.

The MCData client:

1) shall build the SIP MESSAGE request as specified in subclause 6.2.4.1;
2) shall follow the rules specified in subclause 6.4 for the handling of MIME bodies in a SIP message when processing the remaining steps in this subclause;
3) shall insert in the SIP MESSAGE request an application/resource-lists+xml MIME body containing the MCData ID of the targeted MCData user, according to rules and procedures of IETF RFC 5366 [18];
4) shall insert in the SIP MESSAGE request an application/vnd.3gpp.mcdata-info+xml MIME body with an <mcdata-controller-psi> element containing the PSI of the controlling MCData function;
5) if sending a disposition notification in response to an MCData group data request, shall include an <mcdata-calling-group-id> element set to the MCData group identity in the application/vnd.3gpp.mcdata-info+xml MIME body;
6) if requiring to send an SDS notification, shall generate an SDS NOTIFICATION message and include it in the SIP MESSAGE request as specified in subclause 6.2.3.1;
7) if requiring to send an FD notification, shall generate an FD NOTIFICATION message and include it in the SIP MESSAGE request as specified in subclause 6.2.3.2; and
8) shall send the SIP MESSAGE request according to rules and procedures of 3GPP TS 24.229 [5].

[TS 24.282, clause 6.2.3.2]

In order to generate an FD notification, the MCData client:

1) shall generate an FD NOTIFICATION message as specified in subclause 15.1.6; and
2) shall include in the SIP request, the FD NOTIFICATION message in an application/vnd.3gpp.mcdata-signalling MIME body as specified in subclause E.1.

When generating an FD NOTIFICATION message as specified in subclause 15.1.6, the MCData client:

1) if sending a file download accept notification, shall set the FD disposition notification type IE as "FILE DOWNLOAD REQUEST ACCEPTED" as specified in subclause 15.2.6;
2) if sending a file download reject notification, shall set the FD disposition notification type IE as "FILE DOWNLOAD REQUEST REJECTED" as specified in subclause 15.2.6;
3) if sending a file download deferred notification, shall set the FD disposition notification type IE as "FILE DOWNLOAD REQUEST DEFERRED" as specified in subclause 15.2.6;

4) shall set the Conversation ID to the value of the Conversation ID that was received in the FD message as specified in subclause 15.2.9;

5) shall set the Date and time IE to the current time as specified in subclause 15.2.8; and

6) if sending a file download completed notification:

   a) shall set the FD disposition notification type IE as "FILE DOWNLOAD COMPLETED" as specified in subclause 15.2.6;

   b) shall set the Message ID to the value of the Message ID that was received in the FD message as specified in subclause 15.2.10;

   c) if the FD message was destined for the user, shall not include an Application ID IE as specified in subclause 15.2.7; and

   d) if the FD message was destined for an application, shall include an Application ID IE set to the value of the Application ID that was included in the FD message as specified in subclause 15.2.3.

[TS 24.582, clause 7.1.3.1]

Upon receiving an indication to establish MSRP connection for file distribution as the terminating client, the MCData client:

1. shall act as an MSRP client according to IETF RFC 6135 [12];

2. shall act either as an active endpoint or as an passive endpoint to open the transport connection, according to IETF RFC 6135 [12];

3. shall establish the MSRP connection according to the MSRP connection parameters in the SDP offer received in the SIP INVITE request according to IETF RFC 4975 [11];

4. if acting as an "active" endpoint, shall send an empty MSRP SEND request to bind the MSRP connection to the MSRP session from the perspective of the passive endpoint according to the rules and procedures of IETF RFC 4975 [11] and IETF RFC 6135 [12];

Once the MSRP session is established, the MCData client:

1. on receipt of an MSRP request in the MSRP session, shall follow the rules and procedures defined in IETF RFC 4975 [11] and in IETF RFC 6714 [13];

2. If an MSRP SEND request indicates the use of chunking, shall wait until all further MSRP SEND requests for the remaining chunks have been received and shall reassemble the entire set of MSRP requests into the file before delivering the content to the application; and

3. shall handle the received content as described in subclause 7.1.3.2.

[TS 24.582, clause 7.1.3.2]

Upon receiving a file, the MCData client:

1. shall decode the contents of the application/vnd.3gpp.mcdata-file MIME body; and

2. once all the chunks of the file are successfully received, shall indicate to the signalling plane that the file download is completed.

6.2.10.3 Test description

6.2.10.3.1 Pre-test conditions

Test configuration:

- Single cell configuration according to TS 37.579-1 [2] clause 5.2.2.2.1.

- Test files downloaded or received at previous test runs are deleted.

Preamble:

- The UE has performed procedure 'Initial registration' as described in TS 37.579-1 [2] clause 5.4.2.
- UE States at the end of the preamble:
  - The UE is in RRC_IDLE state.
  - The client is registered for MCData.

6.2.10.3.2 Test procedure sequence

Table 6.2.10.3.2-1: Main Behaviour

St	Procedure	Message Sequence		TP	Verdict
		U - S	Message		
1	Check: Does the UE (MCData client) correctly perform procedure '**CT MCData Call Establishment**' as described in TS 37.579-1 [2] Table 5.3C.3.3-1?	-	-	1,2	P
2-5	Void	-	-	-	-
6	Check: Does the UE (MCData client) correctly perform procedure '**CT MSRP message transfer**' as described in TS 37.579-1 [2] Table 5.3C.5.3-1 **to receive an FD message containing** test file 1? (NOTE 2)	-	-	2	P
7	Void	-	-	-	-
8	Check: Does the UE (MCData client) correctly perform procedure '**CT MCData call release**' as described in TS 37.579-1 [2] Table 5.3C.7.3-1? (NOTE 3)	-	-	3	P
9-10	Void	-	-	-	-
11	Check: Does the UE (MCData client) correctly perform procedure '**CO SDS or FD message transfer using signalling plane**' as described in TS 37.579-1 [2] Table 5.3C.1.3-1 to **send a disposition notification for the file received at step 6**?	-	-	2	P
12	Void	-	-	-	-
13	Check: Has the UE (MCData client) downloaded test file 1 (ANNEX A.3.1)? (NOTE 1)	-	-	2	P
NOTE 1: This is expected to be done via a suitable implementation dependent MMI. NOTE 2: Test file 1 for CT FD as specified in annex A.3.1. NOTE 3: The procedure does not release the RRC connection.					

6.2.10.3.3 Specific message contents

Table 6.2.10.3.3-1: SIP INVITE from the SS (step 1, Table 6.2.10.3.2-1; step 2, TS 37.579-1 [2] Table 5.3C.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.5.2-1, condition MCDATA_FD				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part		**SDP message**		
MIME-part-body	SDP message as described in Table 6.2.10.3.3-2			
MIME body part		**MCData-Info**		
MIME-part-body	MCData-Info as described in Table 6.2.10.3.3-3			
MIME body part		**MCData Data signalling message**		
MIME-part-headers				
MIME-Content-Type	"application/vnd.3gpp. mcdata-signalling"			
MIME-part-body	MCData Protected Payload Message containing FD SIGNALLING PAYLOAD as described in Table 6.2.10.3.3-3A			

Table 6.2.10.3.3-2: SDP for SIP INVITE (Table 6.2.10.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.1.2-3, condition MCDATA_FD, SDP_OFFER, MCD_1to1

Table 6.2.10.3.3-3: MCData-Info (Table 6.2.10.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.2.2-3, condition MCD_1to1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
mcdata-info				
mcdata-Params				
request-type	"one-to-one-fd"			

Table 6.2.10.3.3-3A: FD SIGNALLING PAYLOAD (Table 6.2.10.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.6-1, condition FD_MSRP

Table 6.2.10.3.3-4: SIP 200 (OK) from the UE (step 1, Table 6.2.10.3.2-1; step 4, TS 37.579-1 [2] Table 5.3C.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.17.1.1-1, condition INVITE-RSP				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Content-Type				
value	"application/sdp"			
Message-body				
SDP message	As described in Table 6.2.10.3.3-5			

Table 6.2.10.3.3-5: SDP for SIP 200 (OK) (Table 6.2.10.3.3-4)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.1.1-3, condition MCDATA_FD, SDP_ANSWER

Table 6.2.10.3.3-6: MSRP SEND from the SS (step 6, Table 6.2.10.3.2-1; step 1, TS 37.579-1 [2] Table 5.3C.5.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.12.1.2-1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Content-Type				
media-type	"application/vnd.3gpp.mcdata-file"			
data	As specified in table 6.2.10.3.3-8			

Table 6.2.10.3.3-7: Void

Table 6.2.10.3.3-8: MCData Protected Payload Message (Table 6.2.9.3.3-6)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.10-2, condition PROTECTED_FILE, PCK

Table 6.2.10.3.3-9: SIP BYE from the SS (step 8, Table 6.2.10.3.2-1; step 1, TS 37.579-1 [2] Table 5.3C.7.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.2.2-1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Reason				
reason-value	"SIP"			
protocol-cause	"cause="200""			
reason-text	"text="transmission succeeded""			

Table 6.2.10.3.3-10: Void

Table 6.2.10.3.3-11: SIP MESSAGE from the UE (step 11, Table 6.2.10.3.2-1; step 2, TS 37.579-1 [2] Table 5.3C.1.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.7.1-1, condition MCDATA_FD, RESOURCE_LISTS, MCDATA_SIGNALLING				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part	not present	**MCData-Info**		
MIME body part		**MCData Data signalling message**		
MIME-part-body	SDS NOTIFICATION as described in Table 6.2.10.3.3-12			

Table 6.2.10.3.3-12: FD NOTIFICATION (Table 6.2.2.3.3-11)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.7-1, condition FD_COMPLETED

6.2.11 On-network / File Distribution (FD) / FD Using Media Plane / Group Standalone FD / Client Originated (CO)

6.2.11.1 Test Purpose (TP)

(1)

```
with { UE (MCDATA Client) registered and authorised for MCDATA Service }
ensure that {
  when { the MCDATA User requests to send a group standalone FD message using the media plane}
```

```
    then { UE (MCDATA Client) sends a request to establish an MSRP connection via a SIP INVITE
message and then responds to the SIP 200 (OK) message with a SIP ACK message }
            }
```

(2)

```
with { UE (MCDATA Client) having requested the establishment of a MSRP connection }
ensure that {
  when { UE (MCDATA Client) receives a SIP 200 (OK) message with the a=setup attribute set to
"passive"  from the SS (MCDATA server) }
    then { UE (MCDATA Client) sends a blank MSRP SEND message to bind the MSRP connection and then
sends the group standalone FD message via a MSRP SEND message }
            }
```

(3)

```
with { UE (MCDATA Client) having sent a group standalone FD message using the media plane }
ensure that {
  when { UE (MCDATA Client receives a MSRP 200 (OK) message in response to the last MSRP SEND
message indicating that the standalone FD message has been successfully transferred }
    then { UE (MCDATA Client) sends a SIP BYE message }
            }
```

(4)

```
with { UE (MCDATA Client) having sent a group standalone FD message using the media plane with a
disposition of "FILE DOWNLOAD COMPLETED UPDATE" }
ensure that {
  when { UE (MCDATA Client receives a disposition response via a SIP MESSAGE message from the SS
(MCDATA Server }
    then { UE (MCDATA Client) responds to the SIP MESSAGE message by sending a SIP 200 (OK) message
and delivers the notification to the MCDATA User }
            }
```

6.2.11.2 Conformance requirements

References: The conformance requirements covered in the current TC are specified in: TS 24.282, clauses 10.2.5.2.3, 6.2.2.3, 12.2.1.2, TS 24.582 clause 7.1.2.1. The following represents a copy/paste extraction of the requirements relevant to the test purpose; any references within the copy/paste text should be understood within the scope of the core spec they have been copied from. Unless otherwise stated, these are Rel-14 requirements.

[TS 24.282, clause 10.2.5.2.3]

The MCData client shall generate a SIP INVITE request in accordance with 3GPP TS 24.229 [5] with the clarifications given below.

The MCData client:

1) shall include the g.3gpp.mcdata.fd media feature tag and the g.3gpp.icsi-ref media feature tag with the value of "urn:urn-7:3gpp-service.ims.icsi.mcdata.fd" in the Contact header field of the SIP INVITE request according to IETF RFC 3840 [16];

2) shall include an Accept-Contact header field containing the g.3gpp.mcdata.fd media feature tag along with the "require" and "explicit" header field parameters according to IETF RFC 3841 [8];

3) shall include an Accept-Contact header field with the g.3gpp.icsi-ref media feature tag containing the value of "urn:urn-7:3gpp-service.ims.icsi.mcdata.fd" along with the "require" and "explicit" header field parameters according to IETF RFC 3841 [8];

4) shall include the ICSI value "urn:urn-7:3gpp-service.ims.icsi.mcdata.fd" (coded as specified in 3GPP TS 24.229 [5]), in a P-Preferred-Service header field according to IETF RFC 6050 [7] in the SIP INVITE request;

5) should include the "timer" option tag in the Supported header field;

6) should include the Session-Expires header field according to IETF RFC 4028 [38]. It is recommended that the "refresher" header field parameter is omitted. If included, the "refresher" header field parameter shall be set to "uac";

7) shall generate and contain an application/vnd.3gpp.mcdata-signalling MIME body with the FD SIGNALLING PAYLOAD as described in subclause 6.2.2.3;

8) if a one-to-one file distribution is requested:

   a) shall insert in the SIP INVITE request a MIME resource-lists body with the MCData ID of the invited MCData user, according to rules and procedures of IETF RFC 5366 [18]; and

   b) shall contain an application/vnd.3gpp.mcdata-info+xml MIME body with the <mcdatainfo> element containing the <mcdata-Params> element with:

      i) the <request-type> element set to a value of "one-to-one-fd";

   c) if an end-to-end security context needs to be established and the security context does not exist or if the existing security context has expired, then:

      i) if necessary, shall instruct the key management client to request keying material from the key management server as described in 3GPP TS 33.180 [26];

      ii) shall use the keying material to generate a PCK as described in 3GPP TS 33.180 [26];

      iii) shall use the PCK to generate a PCK-ID with the four most significant bits set to "0001" to indicate that the purpose of the PCK is to protect one-to-one communications and with the remaining twenty eight bits being randomly generated as described in 3GPP TS 33.180 [26];

      iv) shall encrypt the PCK to a UID associated to the MCData client using the MCData ID of the invited user and a time related parameter as described in 3GPP TS 33.180 [26];

      v) shall generate a MIKEY-SAKKE I_MESSAGE using the encapsulated PCK and PCK-ID as specified in 3GPP TS 33.180 [26]; and

      vi) shall add the MCData ID of the originating MCData to the initiator field (IDRi) of the I_MESSAGE as described in 3GPP TS 33.180 [26]; and

      vii) shall sign the MIKEY-SAKKE I_MESSAGE using the originating MCData user's signing key provided in the keying material together with a time related parameter, and add this to the MIKEY-SAKKE payload, as described in 3GPP TS 33.180 [26];

9) if a group file distribution is requested:

   a) if the "/<*x*>/<x>/Common/MCData/AllowedFD" leaf node present in the group document of the requested MCData group, configured on the group management client as specified in 3GPP TS 24.483 [42] is set to "false", shall reject the request for FD and not continue with the rest of the steps in this subclause; and

   b) shall contain in an application/vnd.3gpp.mcdata-info+xml MIME body with the <mcdatainfo> element containing the <mcdata-Params> element with:

      i) the <request-type> element set to a value of "group-fd";

      ii) the <mcdata-request-uri> element set to the MCData group identity; and

      iii) the <mcdata-client-id> element set to the MCData client ID of the originating MCData client;

NOTE 1: The MCData client does not include the MCData ID of the originating MCData user in the body, as this will be inserted into the body of the SIP INVITE request that is sent from the originating participating MCData function.

10) shall set the Request-URI of the SIP INVITE request to the public service identity identifying the participating MCData function serving the MCData user;

NOTE 2: The MCData client is configured with public service identity identifying the participating MCData function serving the MCData user.

11) may include a P-Preferred-Identity header field in the SIP INVITE request containing a public user identity as specified in 3GPP TS 24.229 [5];

12) shall include an SDP offer according to 3GPP TS 24.229 [5] with the clarifications given in subclause 10.2.5.2.1; and

13) shall send the SIP INVITE request towards the MCData server according to 3GPP TS 24.229 [5].

On receipt of a SIP 2xx response to the SIP INVITE request, the MCData client:

1) shall send a SIP ACK request as specified in 3GPP TS 24.229 [5];

2) shall start the SIP Session timer according to rules and procedures of IETF RFC 4028 [38]; and

3) shall interact with the media plane as specified in 3GPP TS 24.582 [15] subclause 10.2.5.1.1..

[TS 24.282, clause 6.2.2.3]

In order to generate an FD message, the MCData client:

1) shall generate an FD SIGNALLING PAYLOAD message as specified in subclause 15.1.3; and

2) shall include in the SIP request, the FD SIGNALLING PAYLOAD message in an application/vnd.3gpp.mcdata-signalling MIME body as specified in subclause E.1.

When generating an FD SIGNALLING PAYLOAD message as specified in subclause 15.1.3, the MCData client:

1) shall set the Date and time IE to the current time as specified in subclause 15.2.8;

2) if the filestarts a new conversation, shall set the Conversation ID IE to a newly generated Conversation ID value as specified in subclause 15.2.9;

3) if the file continues an existing conversation, shall set the Conversation ID IE to the Conversation ID value of the existing conversation as specified in subclause 15.2.9;

4) shall set the Message ID IE to a newly generated Message ID value as specified in subclause 15.2.10;

5) if the files in reply to a previously received SDS message or file, shall include the InReplyTo message ID IE with the Message ID value in the previously received SDS message or file;

6) if the file is for user consumption, shall not include an Application ID IE as specified in subclause 15.2.7;

7) if the file is intended for an application on the terminating MCData client, shall include an Application ID IE with an Application ID value representing the intended application as specified in subclause 15.2.7;

NOTE: The value chosen for the Application ID value is decided by the mission critical organisation.

8) if a file download complete notification is required shall include a FD disposition request type IE set to "FILE DOWNLOAD COMPLETED UPDATE" as specified in subclause 15.2.4; and

9) shall include and set the Mandatory download IE to "MANDATORY DOWNLOAD" as described in subclause 15.2.16.

[TS 24.282, clause 12.2.1.2]

Upon receipt of a:

"SIP MESSAGE request for SDS disposition notification for terminating MCData client"; or

"SIP MESSAGE request for FD disposition notification for terminating MCData client";

the MCData client:

1) shall decode the contents of the application/vnd.3gpp.mcdata-signalling MIME body; and

2) shall deliver the notification to the user or application.

[TS 24.582, clause 6.1.1.2.1]

Upon receiving an indication to establish MSRP connection for standalone SDS using media plane as the originating client, the MCData client:

1. shall act as an MSRP client according to IETF RFC 6135 [12];
2. shall act according to IETF RFC 6135 [12], as:
   a. an "active" endpoint, if a=setup attribute in the received SDP answer is set to "passive"; and
   b. an "passive" endpoint, if a=setup attribute in the received SDP answer is set to "active";
3. shall establish the MSRP connection according to the MSRP connection parameters in the SDP answer received in the SIP 200 (OK) response according to IETF RFC 4975 [11]; and
4. if acting as an "active" endpoint, shall send an empty MSRP SEND request to bind the MSRP connection to the MSRP session from the perspective of the passive endpoint according to the rules and procedures of IETF RFC 4975 [11] and IETF RFC 6135 [12].

On receiving MSRP 200 (OK) response to the first MSRP SEND request, the MCData client:

1. shall generate a SDS SIGNALLING PAYLOAD as specified in subclause 6.1.1.2.2;
2. shall generate a SDS DATA PAYLOAD as specified in subclause 6.1.1.2.3;
3. shall include the SDS SIGNALLING PAYLOAD and SDS DATA PAYLOAD in an MSRP SEND request as specified in subclause 6.1.1.2.4; and
4. shall send the MSRP SEND request on the established MSRP connection.

NOTE: MSRP chunking, if needed, may affect the number of "Content Type" lines in each MSRP SEND message conveying a chunk, as also specified in subclause 6.1.1.2.4.

If MSRP chunking is not used then on receipt of a 200 (OK) response, the MCData client shall terminate the SIP session as specified in 3GPP TS 24.282 [8].

If MSRP chunking is used, the MCData client:

1. shall send further MSRP SEND requests as necessary;
2. shall wait for a 200 (OK) response to each MSRP SEND request sent; and
3. on receipt of the last 200 (OK) response shall terminate the SIP session as specified in 3GPP TS 24.282 [8].

On receiving a non-200 MSRP response to the MSRP SEND request the MCData client shall handle the error as specified in IETF RFC 4975 [11]. To terminate the MSRP session, the MCData client:

1. if there are further MSRP chunks to send, shall abort transmission of these further MSRP chunks;
2. shall indicate to MCData user that the SDS message could not be sent; and
3. shall terminate the SIP session as specified in 3GPP TS 24.282 [8].

On receiving an indication to terminate the session from the signalling plane, the MCData client:

1. if there are further MSRP chunks to send, shall abort transmission of these further MSRP chunks and may indicate to MCData user that the SDS message could not be sent.

[TS 24.582, clause 7.1.2.1]

Upon receiving an indication to establish MSRP connection for file distribution as the originating client, the MCData client:

1. shall act as an MSRP client according to IETF RFC 6135 [12];
2. shall act according to IETF RFC 6135 [12], as:
   a. an "active" endpoint, if a=setup attribute in the received SDP answer is set to "passive"; and
   b. an "passive" endpoint, if a=setup attribute in the received SDP answer is set to "active";

3. shall establish the MSRP connection according to the MSRP connection parameters in the SDP answer received in the SIP 200 (OK) response according to IETF RFC 4975 [11]; and

4. if acting as an "active" endpoint, shall send an empty MSRP SEND request to bind the MSRP connection to the MSRP session from the perspective of the passive endpoint according to the rules and procedures of IETF RFC 4975 [11] and IETF RFC 6135 [12].

On receiving MSRP 200 (OK) response to the first MSRP SEND request, the MCData client can send the file. To send the file, the MCData client:

1. shall generate MSRP SEND for file distribution request according to IETF RFC 4975 [11]. When generating an MSRP SEND, the MCData client:

   a. shall set To-Path header according to the MSRP URI(s) received in the answer SDP;

   b. shall set the first content type as Content-Type = "application/vnd.3gpp.mcdata-file"; and

   c. shall set the body of the MSRP SEND request with MSRP payload. MSRP payload is set to the file or part of the file.

2. shall send the MSRP SEND request(s) on the established MSRP connection.

If MSRP chunking is used, the MCData client:

1. shall send further MSRP SEND requests containing the file as necessary;

2. shall wait for a 200 (OK) response to each MSRP SEND request sent; and

3. on receipt of the last 200 (OK) response shall terminate the SIP session as specified in 3GPP TS 24.282 [8].

On receiving a non-200 MSRP response to the MSRP SEND request the MCData client shall handle the error as specified in IETF RFC 4975 [11]. To terminate the MSRP session, the MCData client:

1. if there are further MSRP chunks to send, shall abort transmission of these further MSRP chunks;

2. shall indicate to MCData user that the file could not be distributed; and

3. shall terminate the SIP session as specified in 3GPP TS 24.282 [8].

6.2.11.3 Test description

6.2.11.3.1 Pre-test conditions

Test configuration:

- Single cell configuration according to TS 37.579-1 [2] clause 5.2.2.2.1.
- Test File 1 for CO FD as specified in annex A.2.1 is available at the UE for upload.

Preamble:

- The UE has performed procedure 'Initial registration' as described in TS 37.579-1 [2] clause 5.4.2.
- UE States at the end of the preamble:
  - The UE is in RRC_IDLE state.
  - The client is registered for MCData.

6.2.11.3.2 Test procedure sequence

Table 6.2.11.3.2-1: Main Behaviour

St	Procedure	Message Sequence		TP	Verdict
		U - S	Message		
1	Make the UE (MCData client) send test file 1 (ANNEX A.2.1) for CO group FD over media plane with disposition notification type "FILE DOWNLOAD COMPLETED UPDATE". (NOTE 1, NOTE 2)	-	-	-	-
2	Check: Does the UE (MCData client) correctly perform procedure '**CO MCData Call Establishment**' as described in TS 37.579-1 [2] Table 5.3C.2.3-1?	-	-	1,2	P
3-6	Void	-	-	-	-
7	Check: Does the UE (MCData client) correctly perform procedure '**CO MSRP message transfer**' as described in TS 37.579-1 [2] Table 5.3C.4.3-1 **to send an FD message containing test file 1 for CO FD**?	-	-	2	P
7A	Check: Is the content of the transferred file the same as specified in annex A.2.1?	-	-	2	P
8	Check: Does the UE (MCData client) correctly perform procedure '**CO MCData call release**' as described in TS 37.579-1 [2] Table 5.3C.6.3-1? (NOTE 3)	-	-	3	P
9	Void	-	-	-	-
10	Check: Does the UE (MCData client) correctly perform procedure '**MCX SIP MESSAGE CT**' as described in TS 37.579-1 [2] Table 5.3.33.3-1 **to receive the disposition notification** for the FD message sent at step 7?	-	-	4	P
11	Void	-	-	-	-
12	Check: Does the UE (MCData client) provide the disposition notification to the user? (NOTE 1)	-	-	4	P
NOTE 1: This is expected to be done via a suitable implementation dependent MMI. NOTE 2: Test file 1 for CO FD as specified in annex A.2.1. NOTE 3: The procedure does not release the RRC connection.					

6.2.11.3.3 Specific message contents

Table 6.2.11.3.3-1: SIP INVITE from the UE (step 2, Table 6.2.11.3.2-1; step 2, TS 37.579-1 [2] Table 5.3C.2.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.5.1-1, condition MCDATA_FD				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part		**SDP message**		
MIME-part-body	SDP message as described in Table 6.2.11.3.3-2			
MIME body part		**MCData-Info**		
MIME-part-body	MCData-Info as described in Table 6.2.11.3.3-3			
MIME body part		**MCData Data signalling message**		
MIME-part-headers				
MIME-Content-Type	"application/vnd.3gpp. mcdata-signalling"			
MIME-part-body	MCData Protected Payload Message containing FD SIGNALLING PAYLOAD as described in Table 6.2.11.3.3-3A			

Table 6.2.11.3.3-2: SDP for SIP INVITE (Table 6.2.11.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.1.1-3, condition MCDATA_FD, SDP_OFFER

Table 6.2.11.3.3-3: MCData-Info (Table 6.2.11.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.2.1-3, condition MCD_grp				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
mcdata-info				
mcdata-Params				
request-type	"group-fd"			

Table 6.2.11.3.3-3A: FD SIGNALLING PAYLOAD (Table 6.2.11.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.5-1, condition FD_MSRP

Table 6.2.11.3.3-4: SIP 200 (OK) from the SS (step 2, Table 6.2.11.3.2-1; step 4, TS 37.579-1 [2] Table 5.3C.2.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.17.1.2-1, condition INVITE-RSP				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
SDP message	As described in Table 6.2.11.3.3-5			

Table 6.2.11.3.3-5: SDP for SIP 200 (OK) (Table 6.2.11.3.3-4)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.1.2-3, condition MCDATA_FD, SDP_ANSWER

Table 6.2.11.3.3-6: MSRP SEND from the UE (step 7, Table 6.2.11.3.2-1; step 1, TS 37.579-1 [2] Table 5.3C.4.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.12.1.1-1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Content-Type				
media-type	"application/vnd.3gpp.mcdata-file"			
data	As specified in table 6.2.11.3.3-7			

Table 6.2.11.3.3-7: MCData Protected Payload Message (Table 6.2.11.3.3-6)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.10-1, condition PROTECTED_FILE, GMK

Table 6.2.11.3.3-8..9: Void

Table 6.2.11.3.3-10: SIP BYE from the UE (step 8, Table 6.2.11.3.2-1; step 1, TS 37.579-1 [2] Table 5.3C.6.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.2.1-1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Reason			RFC 3326 [125]	
reason-value	"SIP"			
protocol-cause	"cause="200""			
reason-text	"text="transmission succeeded""			

Table 6.2.11.3.3-11: Void

Table 6.2.11.3.3-13: SIP MESSAGE from the SS (step 10, Table 6.2.11.3.2-1; step 2, TS 37.579-1 [2] Table 5.3.33.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.7.2-1, condition MCDATA_FD, MCDATA_SIGNALLING				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part		**MCData-Info**		
MIME-part-body	As described in Table 6.2.11.3.3-14			
MIME body part		**MCData Data signalling message**		
MIME-part-body	MCData Protected Payload Message containing FD NOTIFICATION as described in Table 6.2.11.3.3-15			

Table 6.2.11.3.3-14: MCData-Info (Table 6.2.11.3.3-13)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.2.2-3				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
mcdata-info				
mcdata-Params				
mcdata-calling-group-id	Encrypted <mcdata-calling-group-id> with mcdataURI set to px_MCData_Group_A_ID	Encrypted according to TS 37.579-1 [2] Table 5.5.3.2.2-3A		

Table 6.2.11.3.3-15: FD NOTIFICATION (Table 6.2.11.3.3-13)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.8-1, condition FD_COMPLETED

Table 6.2.11.3.3-16: Void

6.2.12 On-network / File Distribution (FD) / FD Using Media Plane / Group Standalone FD / Client Terminated (CT)

6.2.12.1 Test Purpose (TP)

(1)

```
with { UE (MCDATA Client) registered and authorised for MCDATA Service }
ensure that {
  when { the MCDATA User receives a SIP INVITE to initiate a standalone group FD message using the
media plane }
    then { UE (MCDATA Client) responds by sending a SIP 200 (OK) message }
            }
```

(2)

```
with { UE (MCDATA Client) having responded to the SIP INVITE message that initiated a standalone
group FD message using the media plane }
ensure that {
  when { UE (MCDATA Client) receives an MSRP SEND message from the SS (MCDATA Server) }
    then { UE (MCDATA Client) responds with an MSRP 200 (OK) message }
            }
```

(3)

```
with { UE (MCDATA Client) having finished receiving the file from the SS (MCDATA server) }
ensure that {
  when { UE (MCDATA Client) receives a SIP BYE message to release communications }
    then { UE (MCDATA Client) responds with a SIP 200 (OK) message and then sends a "FILE DOWNLOAD
COMPLETED" disposition via a SIP MESSAGE message }
            }
```

6.2.12.2 Conformance requirements

References: The conformance requirements covered in the current TC are specified in: TS 24.282, clauses 10.2.5.2.4, 12.2.1.1, 6.2.3.2, TS 24.582 clauses 7.1.3.1, 7.1.3.2. The following represents a copy/paste extraction of the requirements relevant to the test purpose; any references within the copy/paste text should be understood within the scope of the core spec they have been copied from. Unless otherwise stated, these are Rel-14 requirements.

[TS 24.282, clause 10.2.5.2.4]

Upon receipt of an initial SIP INVITE request, the MCData client shall follow the procedures for termination of multimedia sessions in the IM CN subsystem as specified in 3GPP TS 24.229 [5] with the clarifications below.

The MCData client:

1) may reject the SIP INVITE request if either of the following conditions are met:

   a) MCData client does not have enough resources to handle the call; or

   b) any other reason outside the scope of this specification;

   and skip the rest of the steps after step 2;

2) if the SIP INVITE request is rejected in step 1), shall respond toward participating MCData function either with appropriate reject code as specified in 3GPP TS 24.229 [5] and warning texts as specified in subclause 4.9 or

with SIP 480 (Temporarily unavailable) response not including warning texts if the user is authorised to restrict the reason for failure and skip the rest of the steps of this subclause;

3) if the SDP offer of the SIP INVITE request contains an "a=key-mgmt" attribute field with a "mikey" attribute value containing a MIKEY-SAKKE I_MESSAGE:

   a) shall extract the MCData ID of the originating MCData user from the initiator field (IDRi) of the I_MESSAGE as described in 3GPP TS 33.180 [26];

   b) shall convert the MCData ID to a UID as described in 3GPP TS 33.180 [26];

   c) shall use the UID to validate the signature of the MIKEY-SAKKE I_MESSAGE as described in 3GPP TS 33.180 [26];

   d) if authentication verification of the MIKEY-SAKKE I_MESSAGE fails, shall reject the SIP INVITE request with a SIP 488 (Not Acceptable Here) response as specified in IETF RFC 4567 [45], and include warning text set to "136 authentication of the MIKEY-SAKKE I_MESSAGE failed" in a Warning header field as specified in subclause 4.9 and not continue with rest of the steps in this subclause; and

   e) if the signature of the MIKEY-SAKKE I_MESSAGE was successfully validated:

      i) shall extract and decrypt the encapsulated PCK using the terminating user's (KMS provisioned) UID key as described in 3GPP TS 33.180 [26]; and

      ii) shall extract the PCK-ID, from the payload as specified in 3GPP TS 33.180 [26];

NOTE: With the PCK successfully shared between the originating MCData client and the terminating MCData client, both clients are able to create an end-to-end secure session.

4) may display to the MCData user the MCData ID of the inviting MCData user;

5) may display to the MCData user the file meta-data of the incoming file as described by the SDP included in the received SIP INVITE request;

6) if the Mandatory indication IE of the FD SIGNALLING PAYLOAD contained in the application/vnd.3gpp.mcdata-signalling MIME body received in the SIP INVITE request is set to "MANDATORY", then:

   i) shall accept the SIP INVITE request and generate a SIP 200 (OK) response according to rules and procedures of 3GPP TS 24.229 [5];

   ii) shall include the option tag "timer" in a Require header field of the SIP 200 (OK) response;

   iii) shall include the Session-Expires header field in the SIP 200 (OK) response and start the SIP session timer according to IETF RFC 4028 [38]. The "refresher" parameter in the Session-Expires header field shall be set to "uas";

   iv) shall include the g.3gpp.mcdata.fd media feature tag in the Contact header field of the SIP 200 (OK) response;

   v) shall include the g.3gpp.icsi-ref media feature tag containing the value of "urn:urn-7:3gpp-service.ims.icsi.mcdata.fd" in the Contact header field of the SIP 200 (OK) response;

   vi) shall include an SDP answer in the SIP 200 (OK) response to the SDP offer in the incoming SIP INVITE request according to 3GPP TS 24.229 [5] with the clarifications given in subclause 10.2.5.2.2; and

   vii) shall send the SIP 200 (OK) response towards the MCData server according to rules and procedures of 3GPP TS 24.229 [5].

On receipt of an SIP ACK message to the sent SIP 200 (OK) message, the MCData client shall:

1) shall interact with the media plane as specified in 3GPP TS 24.582 [15] subclause 10.2.5.1.2.

On receipt of an indication from the media plane of the successful download of the file and if the received FD SIGNALLING PAYLOAD message contained an FD disposition request type IE requesting a file download completed update indication, then, the MCData client:

1) shall follow the procedures described in subclause 12.2.1.1.

[TS 24.282, clause 12.2.1.1]

The MCData client shall follow the procedures in this subclause to:

- indicate to an MCData client that an SDS message was delivered, read or delivered and read when the originating client requested a delivery, read or delivery and read report;

- indicate to the participating MCData function serving the MCData user that an SDS message was undelivered. The participating MCData function can store the message for later re-delivery;

- indicate to an MCData client that a request for FD was accepted, deferred or rejected; or

- indicate to an MCData client that a file download has been completed;

Before sending a disposition notification the MCData client needs to determine:

- the controlling MCData function that sent the SDS or FD message request. The MCData client determines the controlling MCData function from the contents of the <mcdata-controller-psi> element contained in the application/vnd.3gpp.mcdata-info+xml MIME body of the incoming SDS or FD message request;

- the group identity related to an SDS or FD message request received as part of a group communication. The MCData client determines the group identity from the contents of the <mcdata-calling-group-id> element contained in the application/vnd.3gpp.mcdata-info+xml MIME body of the incoming SDS or FD message request; and

- the MCData user targeted for the disposition notification. The MCData client determines the targeted MCData user from the contents of the <mcdata-calling-user-id> element contained in the application/vnd.3gpp.mcdata-info+xml MIME body of the incoming SDS or FD message request.

The MCData client shall generate a SIP MESSAGE request in accordance with 3GPP TS 24.229 [5] and IETF RFC 3428 [6] with the clarifications given below.

The MCData client:

1) shall build the SIP MESSAGE request as specified in subclause 6.2.4.1;

2) shall follow the rules specified in subclause 6.4 for the handling of MIME bodies in a SIP message when processing the remaining steps in this subclause;

3) shall insert in the SIP MESSAGE request an application/resource-lists+xml MIME body containing the MCData ID of the targeted MCData user, according to rules and procedures of IETF RFC 5366 [18];

4) shall insert in the SIP MESSAGE request an application/vnd.3gpp.mcdata-info+xml MIME body with an <mcdata-controller-psi> element containing the PSI of the controlling MCData function;

5) if sending a disposition notification in response to an MCData group data request, shall include an <mcdata-calling-group-id> element set to the MCData group identity in the application/vnd.3gpp.mcdata-info+xml MIME body;

6) if requiring to send an SDS notification, shall generate an SDS NOTIFICATION message and include it in the SIP MESSAGE request as specified in subclause 6.2.3.1;

7) if requiring to send an FD notification, shall generate an FD NOTIFICATION message and include it in the SIP MESSAGE request as specified in subclause 6.2.3.2; and

8) shall send the SIP MESSAGE request according to rules and procedures of 3GPP TS 24.229 [5].

[TS 24.282, clause 6.2.3.2]

In order to generate an FD notification, the MCData client:

1) shall generate an FD NOTIFICATION message as specified in subclause 15.1.6; and

2) shall include in the SIP request, the FD NOTIFICATION message in an application/vnd.3gpp.mcdata-signalling MIME body as specified in subclause E.1.

When generating an FD NOTIFICATION message as specified in subclause 15.1.6, the MCData client:

1) if sending a file download accept notification, shall set the FD disposition notification type IE as "FILE DOWNLOAD REQUEST ACCEPTED" as specified in subclause 15.2.6;

2) if sending a file download reject notification, shall set the FD disposition notification type IE as "FILE DOWNLOAD REQUEST REJECTED" as specified in subclause 15.2.6;

3) if sending a file download deferred notification, shall set the FD disposition notification type IE as "FILE DOWNLOAD REQUEST DEFERRED" as specified in subclause 15.2.6;

4) shall set the Conversation ID to the value of the Conversation ID that was received in the FD message as specified in subclause 15.2.9;

5) shall set the Date and time IE to the current time as specified in subclause 15.2.8; and

6) if sending a file download completed notification:

   a) shall set the FD disposition notification type IE as "FILE DOWNLOAD COMPLETED" as specified in subclause 15.2.6;

   b) shall set the Message ID to the value of the Message ID that was received in the FD message as specified in subclause 15.2.10;

   c) if the FD message was destined for the user, shall not include an Application ID IE as specified in subclause 15.2.7; and

   d) if the FD message was destined for an application, shall include an Application ID IE set to the value of the Application ID that was included in the FD message as specified in subclause 15.2.3.

[TS 24.582, clause 7.1.3.1]

Upon receiving an indication to establish MSRP connection for file distribution as the terminating client, the MCData client:

1. shall act as an MSRP client according to IETF RFC 6135 [12];

2. shall act either as an active endpoint or as an passive endpoint to open the transport connection, according to IETF RFC 6135 [12];

3. shall establish the MSRP connection according to the MSRP connection parameters in the SDP offer received in the SIP INVITE request according to IETF RFC 4975 [11];

4. if acting as an "active" endpoint, shall send an empty MSRP SEND request to bind the MSRP connection to the MSRP session from the perspective of the passive endpoint according to the rules and procedures of IETF RFC 4975 [11] and IETF RFC 6135 [12];

Once the MSRP session is established, the MCData client:

1. on receipt of an MSRP request in the MSRP session, shall follow the rules and procedures defined in IETF RFC 4975 [11] and in IETF RFC 6714 [13];

2. If an MSRP SEND request indicates the use of chunking, shall wait until all further MSRP SEND requests for the remaining chunks have been received and shall reassemble the entire set of MSRP requests into the file before delivering the content to the application; and

3. shall handle the received content as described in subclause 7.1.3.2.

[TS 24.582, clause 7.1.3.2]

Upon receiving a file, the MCData client:

1. shall decode the contents of the application/vnd.3gpp.mcdata-file MIME body; and

2. once all the chunks of the file are successfully received, shall indicate to the signalling plane that the file download is completed.

6.2.12.3 Test description

6.2.12.3.1 Pre-test conditions

Test configuration:

- Single cell configuration according to TS 37.579-1 [2] clause 5.2.2.2.1.
- Test files downloaded or received at previous test runs are deleted.

Preamble:

- The UE has performed procedure 'Initial registration' as described in TS 37.579-1 [2] clause 5.4.2.
- UE States at the end of the preamble:
  - The UE is in RRC_IDLE state.
  - The client is registered for MCData.

6.2.12.3.2 Test procedure sequence

Table 6.2.12.3.2-1: Main Behaviour

St	Procedure	Message Sequence		TP	Verdict
		U - S	Message		
1	Check: Does the UE (MCData client) correctly perform procedure '**CT MCData Call Establishment**' as described in TS 37.579-1 [2] Table 5.3C.3.3-1?	-	-	1,2	P
2-5	Void	-	-	-	-
6	Check: Does the UE (MCData client) correctly perform procedure '**CT MSRP message transfer**' as described in TS 37.579-1 [2] Table 5.3C.5.3-1 **to receive an FD message containing** test file 1? (NOTE 2)	-	-	2	P
7	Void	-	-	-	-
8	Check: Does the UE (MCData client) correctly perform procedure '**CT MCData call release**' as described in TS 37.579-1 [2] Table 5.3C.7.3-1? (NOTE 3)	-	-	3	P
9-10	Void	-	-	-	-
11	Check: Does the UE (MCData client) correctly perform procedure '**CO SDS or FD message transfer using signalling plane**' as described in TS 37.579-1 [2] Table 5.3C.1.3-1 to **send a disposition notification for the file received at step 6**?	-	-	2	P
12	Void	-	-	-	-
13	Check: Has the UE (MCData client) downloaded test file 1 (ANNEX A.3.1)? (NOTE 1)	-	-	2	P
NOTE 1: This is expected to be done via a suitable implementation dependent MMI. NOTE 2: Test file 1 for CT FD as specified in annex A.3.1. NOTE 3: The procedure does not release the RRC connection.					

6.2.12.3.3 Specific message contents

Table 6.2.12.3.3-1: SIP INVITE from the SS (step 1, Table 6.2.12.3.2-1; step 2, TS 37.579-1 [2] Table 5.3C.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.5.2-1, condition MCDATA_FD				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part		**SDP message**		
MIME-part-body	SDP message as described in Table 6.2.12.3.3-2			
MIME body part		**MCData-Info**		
MIME-part-body	MCData-Info as described in Table 6.2.12.3.3-3			
MIME body part		**MCData Data signalling message**		
MIME-part-headers				
MIME-Content-Type	"application/vnd.3gpp. mcdata-signalling"			
MIME-part-body	MCData Protected Payload Message containing FD SIGNALLING PAYLOAD as described in Table 6.2.12.3.3-3A			

Table 6.2.12.3.3-2: SDP for SIP INVITE (Table 6.2.12.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.1.2-3, condition MCDATA_FD, SDP_OFFER

Table 6.2.12.3.3-3: MCData-Info (Table 6.2.12.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.2.2-3, condition MCD_grp				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
mcdata-info				
mcdata-Params				
request-type	"group-fd"			

Table 6.2.12.3.3-3A: FD SIGNALLING PAYLOAD (Table 6.2.12.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.6-1, condition FD_MSRP

Table 6.2.12.3.3-4: SIP 200 (OK) from the UE (step 1, Table 6.2.12.3.2-1; step 4, TS 37.579-1 [2] Table 5.3C.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.17.1.1-1, condition INVITE-RSP				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Content-Type				
value	"application/sdp"			
Message-body				
SDP message	As described in Table 6.2.12.3.3-5			

Table 6.2.12.3.3-5: SDP for SIP 200 (OK) (Table 6.2.12.3.3-4)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.1.1-3, condition MCDATA_FD, SDP_ANSWER

Table 6.2.12.3.3-6: MSRP SEND from the SS (step 6, Table 6.2.12.3.2-1; step 1, TS 37.579-1 [2] Table 5.3C.5.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.12.1.2-1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Content-Type				
media-type	"application/vnd.3gpp.mcdata-file"			
data	As specified in table 6.2.12.3.3-7			

Table 6.2.12.3.3-7: MCData Protected Payload Message (Table 6.2.12.3.3-6)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.10-2, condition PROTECTED_FILE, GMK

Table 6.2.12.3.3-8: SIP BYE from the SS (step 8, Table 6.2.12.3.2-1; step 1, TS 37.579-1 [2] Table 5.3C.7.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.2.2-1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Reason				
reason-value	"SIP"			
protocol-cause	"cause="200""			
reason-text	"text="transmission succeeded""			

Table 6.2.12.3.3-9: Void

Table 6.2.12.3.3-10: SIP MESSAGE from the UE (step 11, Table 6.2.12.3.2-1; step 2, TS 37.579-1 [2] Table 5.3C.1.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.7.1-1, condition MCDATA_FD, RESOURCE_LISTS, MCDATA_SIGNALLING				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part		**MCData Info**		
MIME-part-body	MCData-Info as described in Table 6.2.12.3.3-10A			
MIME body part		**MCData Data signalling message**		
MIME-part-body	SDS NOTIFICATION as described in Table 6.2.12.3.3-11			

Table 6.2.12.3.3-10A: MCData-Info (Table 6.2.12.3.3-10)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.2.1-3				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
mcdata-info				
mcdata-Params				
mcdata-calling-group-id	Encrypted <mcdata-request-uri> with mcdataURI set to px_MCData_Group_A_ID	Encrypted according to TS 37.579-1 [2] Table 5.5.3.2.1-3A		

Table 6.2.12.3.3-11: FD NOTIFICATION (Table 6.2.2.3.3-10)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.7-1, condition FD_COMPLETED

6.2.13 On-network / File Distribution (FD) / Accessing list of deferred data group communications / Client Originated (CO)

6.2.13.1 Test Purpose (TP)

(1)

```
with { UE (MCDATA Client) registered and authorised for MCDATA Service }
ensure that {
  when { the MCDATA User requests to send a Group Standalone FD message with a non-mandatory
download and with a disposition of "FILE DOWNLOAD COMPLETE UPDATE" and the UE (MCDATA Client) is
unaware of the URL of the Media Storage Function }
    then { UE (MCDATA Client) sends a SIP MESSAGE to find the URL of the Media Storage Function and
responds to a SIP MESSAGE that contains the URL of the Media Storage Function with a SIP 200 (OK)
message }
            }
```

(2)

```
with { UE (MCDATA Client) registered and authorised for MCDATA Service }
ensure that {
  when { the MCDATA User requests to send a Group Standalone FD message with a non-mandatory
download and with a disposition of "FILE DOWNLOAD COMPLETE UPDATE" and the UE (MCDATA Client) is
aware of the URL of the Media Storage Function }
    then { UE (MCDATA Client) uploads the file to the Media Storage Function via an HTTP POST
message and then sends the URL of the file location to the recipient via a SIP MESSAGE message }
            }
```

(3)

```
with { UE (MCDATA Client) having sent the URL of the file location to the recipient }
ensure that {
  when { UE (MCDATA Client) receives a FD notification via a SIP MESSAGE message }
    then { UE (MCDATA Client) responds to the SIP MESSAGE message with a SIP 200 (OK) message and
delivers the notification to the MCDATA User }
            }
```

(4)

```
with { UE (MCDATA Client) having received a notification that a sent message was deferred by the
recipient }
ensure that {
  when { MCData User requests to access the list of deferred group communication }
    then { UE (MCDATA Client) sends a SIP MESSAGE message requesting to access the list of deferred
communication and responds to a received SIP MESSAGE message with a SIP 200 (OK message and delivers
the notification to the MCDATA User }
            }
```

6.2.13.2 Conformance requirements

References: The conformance requirements covered in the current TC are specified in: TS 24.282, clauses 10.2.1.3.2, 10.2.2.1, 10.2.4.2.1, 12.2.1.2, 11.3.2.1, 11.3.2.2. The following represents a copy/paste extraction of the requirements relevant to the test purpose; any references within the copy/paste text should be understood within the scope of the core spec they have been copied from. Unless otherwise stated, these are Rel-14 requirements.

[TS 24.282, clause 10.2.1.3.2]

To discover the absolute URI of the media storage function, the MCData client shall generate a SIP MESSAGE request towards the participating MCData function, in accordance with 3GPP TS 24.229 [5] and IETF RFC 3428 [6] with the clarifications given below.

The MCData client:

1) shall build the SIP MESSAGE request as specified in subclause 6.2.4.1;

2) shall follow the rules specified in subclause 6.4 for the handling of MIME bodies in a SIP message when processing the remaining steps in this subclause;

3) shall insert in the SIP MESSAGE request an application/vnd.3gpp.mcdata-info+xml MIME body with a <request-type> element containing the value "msf-disc-req";

4) if the upload of a file is for a group standalone FD request, shall include in an application/vnd.3gpp.mcdata-info+xml MIME body, the <mcdata-calling-group-id> element set to the required MCData group identity; and

NOTE 1: The absence of a group identity in the <mcdata-calling-group-id> element of the application/vnd.3gpp.mcdata-info+xml MIME body implies that the MCData client intends to upload a file for a one-to-one FD request. In this case, the participating MCData function identifies the MCData ID of the user from the binding between the public user identity and the MCData ID.

5) shall send the SIP MESSAGE request according to rules and procedures of 3GPP TS 24.229 [5].

On receipt of a "SIP MESSAGE request for absolute URI discovery response", the MCData client:

1) shall store the absolute URI found in the <mcdata-controller-psi> element;

2) shall generate a SIP 200 (OK) response according to rules and procedures of 3GPP TS 24.229 [5]; and

3) shall send the SIP 200 (OK) response towards the MCData server according to rules and procedures of 3GPP TS 24.229 [5].

[TS 24.282, clause 10.2.2.1]

If the media storage client is not aware of the absolute URI of the media storage function, the media storage client shall request the MCData client to discover the absolute URI associated with the media storage function by following the procedures in subclause 10.2.1.3.

The media storage client shall send HTTP requests over a TLS connection as specified for the HTTP client in the UE in annex A of 3GPP TS 24.482 [24].

NOTE 1: The HTTP client encodes the MCData ID in the bearer access token of the Authorization header field of an HTTP request as specified in 3GPP TS 24.482 [24].

NOTE 2: The HTTP client always sends the HTTP requests to an HTTP proxy. Annex A of 3GPP TS 24.482 [24] indicates how the HTTP proxy forwards the HTTP request to the HTTP server.

To upload a file to media storage function, the media storage client:

1) shall generate an HTTP POST request as specified in IETF RFC 7230 [22] and IETF RFC 7231 [23];

2) shall set the Request-URI to the absolute URI identifying the resource on a media storage function;

3) shall set the Host header field to a hostname identifying the media storage function;

4) shall set the Content-Type header field to multipart/mixed and with a boundary delimiter parameter set to any chosen value;

5) if the file upload is for one-to-one file distribution, shall insert an application/vnd.3gpp.mcdata-info+xml MIME body with:

   a) the <request-type> element set to a value of "one-to-one-fd"; and

   b) the <mcdata-calling-user-id> element set to the originating MCData ID;

6) if the file upload is for group file distribution, shall insert an application/vnd.3gpp.mcdata-info+xml MIME body with:

   a) the <request-type> element set to a value of "group-fd";

   b) the <mcdata-request-uri> element set to the MCData group identity; and

c) the <mcdata-calling-user-id> element set to the originating MCData ID;

7) if end-to-end security is required for a one-to-one communication, the MCData client protects the binary data representing the file and prefixes the protected binary data with security parameters as described in 3GPP TS 33.180 [26];

8) if

i) end-to-end security is not required for a one-to-one communication, or

ii) the file upload is for group file distribution;

shall include the binary data representing the file with Content-Type field set to application/octet-stream and Content-Length field set to the file size; and

9) shall send the HTTP POST request towards the media storage function.

On receipt of a HTTP 201 Created containing a Location header field with a URL identifying the location of the resource where the file has been stored on the media storage function, then the media storage client shall store this information.

[TS 24.282, clause 10.2.4.2.1]

The MCData client shall generate a SIP MESSAGE request in accordance with 3GPP TS 24.229 [5] and IETF RFC 3428 [6] with the clarifications given below.

The MCData client:

1) shall build the SIP MESSAGE request as specified in subclause 6.2.4.1;

2) if a one-to-one standalone FD message is to be sent shall insert in the SIP MESSAGE request:

a) an application/resource-lists+xml MIME body with the MCData ID of the target MCData user, according to rules and procedures of IETF RFC 4826 [9]; and

b) an application/vnd.3gpp.mcdata-info+xml MIME body with a <request-type> element set to a value of "one-to-one-fd";

…

4) shall generate a standalone FD message as specified in subclause 6.2.2.2; and

5) shall send the SIP MESSAGE request according to rules and procedures of 3GPP TS 24.229 [5].

[TS 24.282, clause 12.2.1.2]

Upon receipt of a:

"SIP MESSAGE request for SDS disposition notification for terminating MCData client"; or

"SIP MESSAGE request for FD disposition notification for terminating MCData client";

the MCData client:

1) shall decode the contents of the application/vnd.3gpp.mcdata-signalling MIME body; and

2) shall deliver the notification to the user or application.

[TS 24.282, clause 11.3.2.1]

Upon receiving a request from the MCData user to access the list of deferred data group communications, the MCData client:

1) shall build the SIP MESSAGE request as specified in subclause 6.2.4.1;

2) shall generate DEFERRED DATA REQUEST message as specified in subclause 15.1.11.1;

3) shall include in the SIP request, the DEFERRED DATA GROUP COMM message in an application/vnd.3gpp.mcdata-signalling MIME body as specified in subclause E.1; and

4) shall send the SIP MESSAGE request towards the participating MCData function according to rules and procedures of 3GPP TS 24.229 [5].

[TS 24.282, clause 11.3.2.2]

Upon receipt of a "SIP MESSAGE response for the list of deferred group communications request", the MCData client:

1) shall generate a SIP 200 (OK) response according to rules and procedures of 3GPP TS 24.229 [5];

2) shall send the SIP 200 (OK) response towards the MCData server according to rules and procedures of 3GPP TS 24.229 [5];

3) shall decode the contents of the application/vnd.3gpp.mcdata-signalling MIME body:

   a) if the application/vnd.3gpp.mcdata-signalling MIME body contains DEFERRED DATA RESPONSE message as specified in subclause 15.1.12:

      i) for each payload, if payload type is set to "FILEURL", shall store the payload data; and

4) shall present to MCData user, the list of file URLs which were deferred.

6.2.13.3 Test description

6.2.13.3.1 Pre-test conditions

Test configuration:

- Single cell configuration according to TS 37.579-1 [2] clause 5.2.2.2.1.
- Test File 1 for CO FD as specified in annex A.2.1 is available at the UE for upload.

Preamble:

- The UE has performed procedure 'Initial registration' as described in TS 37.579-1 [2] clause 5.4.2 with the following clarifications:
  - In the MCData Group Configuration document the <mcdata-on-network-max-data-size-auto-recv> shall be set to 0 to indicate non-mandatory download independent from the file size.
- UE States at the end of the preamble:
  - The UE is in RRC_IDLE state.
  - The client is registered for MCData.

6.2.13.3.2 Test procedure sequence

Table 6.2.13.3.2-1: Main Behaviour

St	Procedure	Message Sequence		TP	Verdict
		U - S	Message		
1	Make the UE (MCData client) send test file 1 (ANNEX A.2.1) for CO group FD over HTTP for non-mandatory download and with disposition request "FILE DOWNLOAD COMPLETED UPDATE". (NOTE 1, NOTE 2)	-	-	-	-
2	Check: Does the UE (MCData client) correctly perform procedure '**Discovery of the absolute URI of the media storage function (one-to-one communication)**' as described in TS 37.579-1 [2] Table 5.3C.9.3-1 ?	-	-	1	P
3	Check: Does the UE (MCData client) correctly perform procedure '**FD file upload using HTTP**' as described in TS 37.579-1 [2] Table 5.3C.10.3-1?	-	-	2	P
3A	Check: Is the content of the uploaded file the same as specified in annex A.2.1?	-	-	2	P
4-6	Void	-	-	-	-
7	Check: Does the UE (MCData client) correctly perform procedure '**MCX SIP MESSAGE CT**' as described in TS 37.579-1 [2] Table 5.3.33.3-1 **to receive an FD NOTIFICATION with disposition notification type "FILE DOWNLOAD DEFERRED"** for the FD message sent at step 3?	-	-	4	P
8	Void	-	-	-	-
9	Check: Does the UE (MCData client) notify the user that the remote Client has deferred the acceptance of the download? (NOTE 1)	-	-	3	P
10	Make the UE (MCData client) access the list of deferred data group communications. (NOTE 1)	-	-	-	-
11	Check: Does the UE (MCData client) correctly perform procedure '**MCX SIP MESSAGE Request - Accept CO**' as described in TS 37.579-1 [2] Table 5.3.30.3-1 **to retrieve the list of deferred data group communication**?	-	-	4	P
12-14	Void	-	-	-	-
15	Check: Does the UE (MCData client) provide the list of file URLs which were deferred to the user? (NOTE 1)	-	-	4	P
NOTE 1: This is expected to be done via a suitable implementation dependent MMI. NOTE 2: Test file 1 for CO FD as specified in annex A.2.1.					

6.2.13.3.3 Specific message contents

Table 6.2.13.3.3-1..6: Void

Table 6.2.13.3.3-7: HTTP POST from the UE (step 3, Table 6.2.13.3.2-1; step 2, TS 37.579-1 [2] Table 5.3C.10.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.4.3-1, condition FD_HTTP				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part		**MCData-Info**		
MIME-part-body	MCData-Info as described in Table 6.2.1.3.3-8			

Table 6.2.13.3.3-8: MCData-Info (Table 6.2.13.3.3-7)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.2.1-3				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
mcdata-info				
mcdata-Params				
request-type	"group-fd"			
mcdata-request-uri	px_MCData_Group_A_ID	NOTE: the element is not encrypted		
mcdata-calling-user-id	px_MCData_ID_User_A	NOTE: the element is not encrypted		

Table 6.2.13.3.3-9: Void

Table 6.2.13.3.3-10: HTTP 201 Created from the SS (step 3, Table 6.2.13.3.2-1; step 3, TS 37.579-1 [2] Table 5.3C.10.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.4.7-1, condition FD_HTTP

Table 6.2.13.3.3-11: SIP MESSAGE from the UE (step 3, Table 6.2.13.3.2-1; step 3, TS 37.579-1 [2] Table 5.3C.10.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.7.1-1, condition MCDATA_FD, MCDATA_SIGNALLING				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part		**MCData-Info**		
MIME-part-body	MCData-Info as described in Table 6.2.13.3.3-12			
MIME body part		**MCData Data signalling message**		
MIME-part-body	MCData Protected Payload Message containing FD SIGNALLING PAYLOAD as described in Table 6.2.13.3.3-12A			

Table 6.2.13.3.3-12: MCData-Info (Table 6.2.13.3.3-11)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.2.1-3, condition MCD_grp				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
mcdata-info				
mcdata-Params				
request-type	"group-fd"			

Table 6.2.13.3.3-12A: FD SIGNALLING PAYLOAD (Table 6.2.13.3.3-11)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.5-1, condition FD_HTTP

Table 6.2.13.3.3-13: SIP MESSAGE from the SS (step 7, Table 6.2.13.3.2-1; step 2, TS 37.579-1 [2] Table 5.3.33.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.7.2-1, condition MCDATA_FD, MCDATA_SIGNALLING				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part		**MCData-Info**		
MIME-part-body	MCData-Info as described in Table 6.2.1.3.3-14			
MIME body part		**MCData Data signalling message**		
MIME-part-body	MCData Protected Payload Message containing FD NOTIFICATION as described in Table 6.2.13.3.3-15			

Table 6.2.13.3.3-14: MCData-Info (Table 6.2.13.3.3-13)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.2.2-3				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
mcdata-info				
mcdata-Params				
mcdata-calling-group-id	Encrypted <mcdata-calling-group-id> with mcdataURI set to px_MCData_Group_A_ID	Encrypted according to TS 37.579-1 [2] Table 5.5.3.2.2-3A		

Table 6.2.13.3.3-15: FD NOTIFICATION (Table 6.2.13.3.3-13)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.8-1, condition FD_DEFERRED

Table 6.2.13.3.3-16: SIP MESSAGE from the UE (step 11, Table 6.2.13.3.2-1; step 2, TS 37.579-1 [2] Table 5.3.30.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.7.1-1, condition MCDATA				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Content-Type				
media-type	"application/vnd.3gpp.mcdata-signalling"			
Message-body				
MCData Signalling message	MCData Protected Payload Message containing DEFERRED DATA REQUEST as described in Table 6.2.13.3.3-17			

Table 6.2.13.3.3-17: DEFERRED DATA REQUEST (Table 6.2.13.3.3-16)

Derivation Path: TS 24.282 [31], clause 15.1.11				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Deferred data request message identity	'00001011'B	Deferred List Access Request	TS 24.282 [31] clause 15.2.2	

Table 6.2.13.3.3-18: SIP MESSAGE from the SS (step 11, Table 6.2.13.3.2-1; step 4, TS 37.579-1 [2] Table 5.3.30.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.7.2-1, condition MCDATA				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Content-Type				
media-type	"application/vnd.3gpp.mcdata-signalling"			
Message-body				
MCData Signalling message	MCData Protected Payload Message containing DEFERRED DATA RESPONSE as described in Table 6.2.13.3.3-19			

Table 6.2.13.3.3-19: DEFERRED DATA RESPONSE (Table 6.2.13.3.3-18)

Derivation Path: TS 24.282 [31], clause 15.1.12				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Deferred data response message identity	'00001100'B	Deferred List Access Response	TS 24.282 [31] clause 15.2.2	
Number of payloads	"1"		TS 24.282 [31] clause 15.2.12	
Security parameters and Payload	Not present			
Payload			TS 24.282 [31] clauses 11.3.3.2 and 15.2.13	
Length of Payload contents	Length of the payload contents			
Payload content type	“00000100”	FILEURL		
Payload contents	same URI as assigned by the HTTP 201 (Created) at step 3			
MCData group ID	Not present	Rel-17	TS 24.282 [31] clause 15.2.14	
Deferred FD signalling payload	Not present	Rel-17	TS 24.282 [31] clause 15.2.27	

6.2.14 On-network / File Distribution (FD) / FD Using HTTP / One-to-one Standalone FD / Non-Mandatory Download / Active functional alias / Client Originated (CO)

6.2.14.1 Test Purpose (TP)

(1)

```
with { UE (MCDATA Client) registered and authorised for MCDATA Service }
ensure that {
  when { MCDATA User wants to send a file that is larger than <max-data-size-auto-recv-bytes> via a
standalone one-to-one FD message with a non-mandatory download and with a disposition request of
"FILE DOWNLOAD COMPLETED UPDATE", and, the UE (MCDATA Client) is aware of the URL of the Media
Storage Function }
    then { UE (MCDATA Client) uploads the file to the Media Storage Function via an HTTP POST
message and then sends the URL of the file location to the recipient via a SIP MESSAGE message using
the active functional alias }
            }
```

(2)

```
with { MCDATA User having requesting the sending of a file that is larger than <max-data-size-auto-
recv-bytes> via a standalone one-to-one FD message with a non-mandatory download and with a
disposition request of "FILE DOWNLOAD COMPLETED UPDATE" and the UE (MCDATA Client) having sent the
URL of the file location to the recipient }
ensure that {
  when { UE (MCDATA Client) receives a FD notification via a SIP MESSAGE with disposition
notification type of "FILE DOWNLOAD DEFERRED", followed by a SIP MESSAGE with disposition
notification type of "FILE DOWNLOAD REQUEST ACCEPTED", followed by SIP MESSAGE with disposition
notification type of "FILE DOWNLOAD COMPLETED" }
    then { UE (MCDATA Client) responds to each SIP MESSAGE with a SIP 200 (OK) message and delivers
suitable notification on the respective remote Client action to the MCDATA User }
            }
```

6.2.14.2 Conformance requirements

References: The conformance requirements covered in the current TC are specified in: TS 24.282, clauses 10.2.2.1, 10.2.4.2.1, 12.2.1.2. The following represents a copy/paste extraction of the requirements relevant to the test purpose; any references within the copy/paste text should be understood within the scope of the core spec they have been copied from. Unless otherwise stated, these are Rel-16 requirements.

[TS 24.282, clause 10.2.2.1]

The media storage client shall determine the value of the absolute URI associated with the media storage function of the MCData content server from the <MCDataContentServerURI> element of the MCPTT user profile document (see the MCPTT user profile document in 3GPP TS 24.484 [50]).

The media storage client shall send HTTP requests over a TLS connection as specified for the HTTP client in the UE in annex A of 3GPP TS 24.482 [24].

NOTE 1: The HTTP client encodes the MCData ID in the bearer access token of the Authorization header field of an HTTP request as specified in 3GPP TS 24.482 [24].

NOTE 2: The HTTP client always sends the HTTP requests to an HTTP proxy. Annex A of 3GPP TS 24.482 [24] indicates how the HTTP proxy forwards the HTTP request to the HTTP server.

To upload a file to media storage function on the MCData content server, the media storage client:

1) shall generate an HTTP POST request as specified in IETF RFC 7230 [22] and IETF RFC 7231 [23];

2) shall set the Request-URI to the absolute URI identifying the resource on a media storage function;

3) shall set the Host header field to a hostname identifying the media storage function;

4) shall set the Content-Type header field to multipart/mixed and with a boundary delimiter parameter set to any chosen value;

5) if the file upload is for one-to-one file distribution, shall insert an application/vnd.3gpp.mcdata-info+xml MIME body with:

   a) the <request-type> element set to a value of "one-to-one-fd"; and

   b) the <mcdata-calling-user-id> element set to the originating MCData ID;

6) if the file upload is for group file distribution, shall insert an application/vnd.3gpp.mcdata-info+xml MIME body with:

   a) the <request-type> element set to a value of "group-fd";

   b) the <mcdata-request-uri> element set to the MCData group identity; and

   c) the <mcdata-calling-user-id> element set to the originating MCData ID;

7) if end-to-end security is required for a one-to-one communication, the MCData client protects the binary data representing the file and prefixes the protected binary data with security parameters as described in 3GPP TS 33.180 [26];

8) if

   i) end-to-end security is not required for a one-to-one communication, or

   ii) the file upload is for group file distribution;

   shall include the binary data representing the file with Content-Type field set to application/octet-stream and Content-Length field set to the file size; and

9) shall send the HTTP POST request towards the media storage function.

On receipt of a HTTP 201 Created containing a Location header field with a URL identifying the location of the resource where the file has been stored on the media storage function, then the media storage client shall store this information.

[TS 24.282, clause 10.2.4.2.1]

The MCData client shall generate a SIP MESSAGE request in accordance with 3GPP TS 24.229 [5] and IETF RFC 3428 [6] with the clarifications given below.

The MCData client:

1) shall build the SIP MESSAGE request as specified in subclause 6.2.4.1;

2) if a one-to-one standalone FD message is to be sent shall insert in the SIP MESSAGE request:

   a) an application/resource-lists+xml MIME body with the MCData ID of the target MCData user, according to rules and procedures of IETF RFC 4826 [9]; and

   b) an application/vnd.3gpp.mcdata-info+xml MIME body with:

      i) a <request-type> element set to a value of "one-to-one-fd"; and

      ii) if the MCData client is aware of active functional aliases and if an active functional alias is to be included in the SIP MESSAGE request, the <functional-alias-URI> element set to the URI of the used functional alias;

3) if a group standalone FD message is to be sent:

   a) if the "/<*x*>/<x>/Common/MCData/AllowedFD" leaf node present in the group document of the requested MCData group, configured on the group management client as specified in 3GPP TS 24.483 [42] is set to "false", shall reject the request for FD and not continue with the rest of the steps in this subclause; and

   b) shall insert in the SIP MESSAGE request an application/vnd.3gpp.mcdata-info+xml MIME body with:

      i) the <request-type> element set to a value of "group-fd";

      ii) the <mcdata-request-uri> element set to the MCData group identity;

      iii) the <mcdata-client-id> element set to the MCData client ID of the originating MCData client; and

      iv) if the MCData client is aware of active functional aliases and if an active functional alias is to be included in the SIP MESSAGE request, the <functional-alias-URI> element set to the URI of the used functional alias;

4) shall generate a standalone FD message as specified in subclause 6.2.2.2; and

5) shall send the SIP MESSAGE request according to rules and procedures of 3GPP TS 24.229 [5].

[TS 24.282, clause 12.2.1.2]

Upon receipt of a:

"SIP MESSAGE request for SDS disposition notification for terminating MCData client"; or

"SIP MESSAGE request for FD disposition notification for terminating MCData client";

the MCData client:

1) shall decode the contents of the application/vnd.3gpp.mcdata-signalling MIME body; and

2) shall deliver the notification to the user or application.

6.2.14.3 Test description

6.2.14.3.1 Pre-test conditions

Test configuration:

- Single cell configuration according to TS 37.579-1 [2] clause 5.2.2.2.1.
- Test File 2 for CO FD as specified in aAnnex A.2.2 are available at the UE for upload.

Preamble:

- The UE has performed procedure 'Initial registration' as described in TS 37.579-1 [2] clause 5.4.2 with the following clarifications:

- In the <on-network> element of the MCData Service Configuration document the <max-data-size-auto-recv-bytes> element of the <tx-and-rx-control> element shall be set to 0 to indicate non-mandatory download independent from the file size.

- The UE has performed procedure 'UE initiated MCX functional alias status determination and subscription' as specified in TS 37.579-1 [2] clause 5.3.36.

- The UE has performed procedure 'UE initiated MCX functional alias status change' as specified in TS 37.579-1 [2] clause 5.3.37.

- UE States at the end of the preamble:

  - The UE is in RRC_IDLE state.

  - The client is registered for MCData.

  - The client is subscribed for notification of functional alias status changes and has activated a functional alias.

6.2.14.3.2 Test procedure sequence

Table 6.2.14.3.2-1: Main Behaviour

St	Procedure	Message Sequence		TP	Verdict
		U - S	Message		
1	Make the UE (MCData client) send test file 2 (ANNEX A.2.2) for CO one-to-one FD over HTTP for non-mandatory download and with disposition request "FILE DOWNLOAD COMPLETED UPDATE" using the active functional alias. (NOTE 1, NOTE 2)	-	-	-	-
2	Check: Does the UE (MCData client) correctly perform procedure '**FD file upload using HTTP**' as described in TS 37.579-1 [2] Table 5.3C.10.3-1?	-	-	1	P
3	Check: Is the content of the uploaded file the same as specified in annex A.2.2?	-	-	1	P
4	Check: Does the UE (MCData client) correctly perform procedure '**MCX SIP MESSAGE CT**' as described in TS 37.579-1 [2] Table 5.3.33.3-1 **to receive an FD NOTIFICATION with disposition notification type "FILE DOWNLOAD DEFERRED"** for the FD message sent at step 24?	-	-	2	P
5	Check: Does the UE (MCData client) notify the user that the remote client has deferred the acceptance of the download? (NOTE 1)	-	-	2	P
6	Check: Does the UE (MCData client) correctly perform procedure '**MCX SIP MESSAGE CT**' as described in TS 37.579-1 [2] Table 5.3.33.3-1 **to receive an FD NOTIFICATION with disposition notification type "FILE DOWNLOAD REQUEST ACCEPTED"** for the FD message sent at step 24?	-	-	2	P
7	Check: Does the UE (MCData client) notify the user that the remote client has accepted the download? (NOTE 1)	-	-	2	P
8	Check: Does the UE (MCData client) correctly perform procedure '**MCX SIP MESSAGE CT**' as described in TS 37.579-1 [2] Table 5.3.33.3-1 **to receive an FD NOTIFICATION with disposition notification type "FILE DOWNLOAD COMPLETED"** for the FD message sent at step 24?	-	-	2	P
9	Check: Does the UE (MCData client) notify the user that the remote client has completed the download? (NOTE 1)	-	-	2	P
NOTE 1: This is expected to be done via a suitable implementation dependent MMI. NOTE 2: Test file 2 for CO FD as specified in annex A.2.2.					

6.2.14.3.3 Specific message contents

Table 6.2.14.3.3-1: HTTP POST from the UE (step 2, Table 6.2.14.3.2-1; step 2, TS 37.579-1 [2] Table 5.3C.10.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.4.3-1, condition FD_HTTP				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part		**MCData-Info**		
MIME-part-body	MCData-Info as described in Table 6.2.14.3.3-2			

Table 6.2.14.3.3-2: MCData-Info (Table 6.2.14.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.2.1-3				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
mcdata-info				
mcdata-Params				
request-type	"one-to-one-fd"			
mcdata-calling-user-id	px_MCData_ID_User_A	NOTE: the element is not encrypted		

Table 6.2.14.3.3-3: HTTP 201 Created from the SS (step 2, Table 6.2.14.3.2-1; step 3, TS 37.579-1 [2] Table 5.3C.10.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.4.7-1, condition FD_HTTP				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Location				
uri	tsc_MCData_MSF_URI & "/file-location-2"			

Table 6.2.14.3.3-4: SIP MESSAGE from the UE (step 2, Table 6.2.14.3.2-1; step 4, TS 37.579-1 [2] Table 5.3C.10.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.7.1-1, condition MCDATA_FD, RESOURCE_LISTS, MCDATA_SIGNALLING				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part		**MCData-Info**		
MIME-part-body	MCData-Info as described in Table 6.2.14.3.3-5			
MIME body part		**MCData Data signalling message**		
MIME-part-body	MCData Protected Payload Message containing FD SIGNALLING PAYLOAD as described in Table 6.2.14.3.3-6			

Table 6.2.14.3.3-5: MCData-Info (Table 6.2.14.3.3-4)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.2.1-3, condition FUNCTIONAL_ALIAS				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
mcdata-info				
mcdata-Params				
request-type	"one-to-one-fd"			

Table 6.2.14.3.3-6: FD SIGNALLING PAYLOAD (Table 6.2.14.3.3-4)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.5-1, condition FD_HTTP

Table 6.2.14.3.3-7: SIP MESSAGE from the SS (step 4, Table 6.2.14.3.2-1; step 2, TS 37.579-1 [2] Table 5.3.33.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.7.2-1, condition MCDATA_FD, MCDATA_SIGNALLING				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part		**MCData Data signalling message**		
MIME-part-body	MCData Protected Payload Message containing FD NOTIFICATION as described in Table 6.2.14.3.3-8			

Table 6.2.14.3.3-8: FD NOTIFICATION (Table 6.2.14.3.3-7)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.8-1, condition FD_DEFERRED

Table 6.2.14.3.3-9: SIP MESSAGE from the SS (step 6, Table 6.2.14.3.2-1; step 2, TS 37.579-1 [2] Table 5.3.33.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.7.2-1, condition MCDATA_FD, MCDATA_SIGNALLING				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part		**MCData Data signalling message**		
MIME-part-body	MCData Protected Payload Message containing FD NOTIFICATION as described in Table 6.2.14.3.3-10			

Table 6.2.14.3.3-10: FD NOTIFICATION (Table 6.2.14.3.3-9)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.8-1, condition FD_ACCEPTED

Table 6.2.14.3.3-11: SIP MESSAGE from the SS (step 8, Table 6.2.14.3.2-1; step 2, TS 37.579-1 [2] Table 5.3.33.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.7.2-1, condition MCDATA_FD, MCDATA_SIGNALLING				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part		**MCData Data signalling message**		
MIME-part-body	MCData Protected Payload Message containing FD NOTIFICATION as described in Table 6.2.14.3.3-12			

Table 6.2.14.3.3-12: FD NOTIFICATION (Table 6.2.14.3.3-11)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.8-1, condition FD_COMPLETED

6.2.15 On-network / File Distribution (FD) / FD Using Media Plane / One-to-one Standalone FD / Active Functional Alias / Client Originated (CO)

6.2.15.1 Test Purpose (TP)

(1)

```
with { UE (MCDATA Client) registered and authorised for MCDATA Service }
ensure that {
  when { the MCDATA User requests to send a one-to-one standalone FD message using the media plane}
    then { UE (MCDATA Client) sends a request to establish an MSRP connection via a SIP INVITE
message using the active functional alias and then responds to the SIP 200 (OK) message with a SIP
ACK message }
            }
```

(2)

```
with { UE (MCDATA Client) having requested the establishment of a MSRP connection }
ensure that {
  when { UE (MCDATA Client) receives a SIP 200 (OK) message with the a=setup attribute set to
"passive"  from the SS (MCDATA server) }
    then { UE (MCDATA Client) sends a blank MSRP SEND message to bind the MSRP connection and then
sends the one-to-one standalone FD message via a MSRP SEND message }
            }
```

(3)

```
with { UE (MCDATA Client) having sent a one-to-one standalone FD message using the media plane }
ensure that {
  when { UE (MCDATA Client receives a MSRP 200 (OK) message in response to the last MSRP SEND
message indicating that the standalone FD message has been successfully transferred }
    then { UE (MCDATA Client) sends a SIP BYE message }
            }
```

(4)

```
with { UE (MCDATA Client) having sent a one-to-one standalone FD message using the media plane with
a disposition of "FILE DOWNLOAD COMPLETED UPDATE" }
ensure that {
  when { UE (MCDATA Client receives a disposition response via a SIP MESSAGE message from the SS
(MCDATA Server }
    then { UE (MCDATA Client) responds to the SIP MESSAGE message by sending a SIP 200 (OK) message
and delivers the notification to the MCDATA User }
            }
```

6.2.15.2 Conformance requirements

References: The conformance requirements covered in the current TC are specified in: TS 24.282, clauses 10.2.5.2.3, 6.2.2.3, 12.2.1.2, TS 24.582 clause 7.1.2.1. The following represents a copy/paste extraction of the requirements relevant to the test purpose; any references within the copy/paste text should be understood within the scope of the core spec they have been copied from. Unless otherwise stated, these are Rel-16 requirements.

[TS 24.282, clause 10.2.5.2.3]

The MCData client shall generate a SIP INVITE request in accordance with 3GPP TS 24.229 [5] with the clarifications given below.

The MCData client:

1) shall include the g.3gpp.mcdata.fd media feature tag and the g.3gpp.icsi-ref media feature tag with the value of "urn:urn-7:3gpp-service.ims.icsi.mcdata.fd" in the Contact header field of the SIP INVITE request according to IETF RFC 3840 [16];

2) shall include an Accept-Contact header field containing the g.3gpp.mcdata.fd media feature tag along with the "require" and "explicit" header field parameters according to IETF RFC 3841 [8];

3) shall include an Accept-Contact header field with the g.3gpp.icsi-ref media feature tag containing the value of "urn:urn-7:3gpp-service.ims.icsi.mcdata.fd" along with the "require" and "explicit" header field parameters according to IETF RFC 3841 [8];

4) shall include the ICSI value "urn:urn-7:3gpp-service.ims.icsi.mcdata.fd" (coded as specified in 3GPP TS 24.229 [5]), in a P-Preferred-Service header field according to IETF RFC 6050 [7] in the SIP INVITE request;

5) should include the "timer" option tag in the Supported header field;

6) should include the Session-Expires header field according to IETF RFC 4028 [38]. It is recommended that the "refresher" header field parameter is omitted. If included, the "refresher" header field parameter shall be set to "uac";

7) shall generate and contain an application/vnd.3gpp.mcdata-signalling MIME body with the FD SIGNALLING PAYLOAD as described in subclause 6.2.2.3;

8) if a one-to-one file distribution is requested:

   a) shall insert in the SIP INVITE request a MIME resource-lists body with the MCData ID of the invited MCData user, according to rules and procedures of IETF RFC 5366 [18]; and

   b) shall contain an application/vnd.3gpp.mcdata-info+xml MIME body with the <mcdatainfo> element containing the <mcdata-Params> element with:

      i) the <request-type> element set to a value of "one-to-one-fd"; and

      ii) if the MCData client is aware of active functional aliases and if an active functional alias is to be included in the SIP INVITE request, the <functional-alias-URI> element set to the URI of the used functional alias;

   c) if an end-to-end security context needs to be established and the security context does not exist or if the existing security context has expired, then:

      i) if necessary, shall instruct the key management client to request keying material from the key management server as described in 3GPP TS 33.180 [26];

      ii) shall use the keying material to generate a PCK as described in 3GPP TS 33.180 [26];

      iii) shall use the PCK to generate a PCK-ID with the four most significant bits set to "0001" to indicate that the purpose of the PCK is to protect one-to-one communications and with the remaining twenty eight bits being randomly generated as described in 3GPP TS 33.180 [26];

      iv) shall encrypt the PCK to a UID associated to the MCData client using the MCData ID of the invited user and a time related parameter as described in 3GPP TS 33.180 [26];

      v) shall generate a MIKEY-SAKKE I_MESSAGE using the encapsulated PCK and PCK-ID as specified in 3GPP TS 33.180 [26]; and

      vi) shall add the MCData ID of the originating MCData to the initiator field (IDRi) of the I_MESSAGE as described in 3GPP TS 33.180 [26]; and

      vii) shall sign the MIKEY-SAKKE I_MESSAGE using the originating MCData user's signing key provided in the keying material together with a time related parameter, and add this to the MIKEY-SAKKE payload, as described in 3GPP TS 33.180 [26];

9) if a group file distribution is requested:

   a) if the "/<*x*>/<x>/Common/MCData/AllowedFD" leaf node present in the group document of the requested MCData group, configured on the group management client as specified in 3GPP TS 24.483 [42] is set to "false", shall reject the request for FD and not continue with the rest of the steps in this subclause; and

b) shall contain in an application/vnd.3gpp.mcdata-info+xml MIME body with the <mcdatainfo> element containing the <mcdata-Params> element with:

i) the <request-type> element set to a value of "group-fd";

ii) the <mcdata-request-uri> element set to the MCData group identity;

iii) the <mcdata-client-id> element set to the MCData client ID of the originating MCData client; and

NOTE 1: The MCData client does not include the MCData ID of the originating MCData user in the body, as this will be inserted into the body of the SIP INVITE request that is sent from the originating participating MCData function.

iv) if the MCData client is aware of active functional aliases and if an active functional alias is to be included in the SIP INVITE request, the <functional-alias-URI> element set to the URI of the used functional alias;

10) shall set the Request-URI of the SIP INVITE request to the public service identity identifying the participating MCData function serving the MCData user;

NOTE 2: The MCData client is configured with public service identity identifying the participating MCData function serving the MCData user.

11) may include a P-Preferred-Identity header field in the SIP INVITE request containing a public user identity as specified in 3GPP TS 24.229 [5];

12) shall include an SDP offer according to 3GPP TS 24.229 [5] with the clarifications given in subclause 10.2.5.2.1; and

13) shall send the SIP INVITE request towards the MCData server according to 3GPP TS 24.229 [5].

On receipt of a SIP 2xx response to the SIP INVITE request, the MCData client:

1) shall send a SIP ACK request as specified in 3GPP TS 24.229 [5];

2) shall start the SIP Session timer according to rules and procedures of IETF RFC 4028 [38]; and

3) shall interact with the media plane as specified in 3GPP TS 24.582 [15] subclause 10.2.5.1.1..

On receipt of a SIP 4xx response, a SIP 5xx response or a SIP 6xx response to the SIP INVITE request:

1) shall indicate to the MCData user that the file could not be sent; and

2) shall send a SIP ACK request as specified in 3GPP TS 24.229 [5].

On receipt of an indication from the media plane indicating that the file was not sent successfully, the MCData client shall:

1) shall generate a SIP BYE request according to 3GPP TS 24.229 [5] with:

a) Reason code set to "SIP";

b) cause set to "480"; and

c) text set to "transmission failed";

2) shall set the Request-URI to the MCData session identity to release; and

3) shall send a SIP BYE request towards MCData server according to 3GPP TS 24.229 [5].

[TS 24.282, clause 6.2.2.3]

In order to generate an FD message, the MCData client:

1) shall generate an FD SIGNALLING PAYLOAD message as specified in subclause 15.1.3; and

2) shall include in the SIP request, the FD SIGNALLING PAYLOAD message in an application/vnd.3gpp.mcdata-signalling MIME body as specified in subclause E.1.

When generating an FD SIGNALLING PAYLOAD message as specified in subclause 15.1.3, the MCData client:

1) shall set the Date and time IE to the current time as specified in subclause 15.2.8;

2) if the filestarts a new conversation, shall set the Conversation ID IE to a newly generated Conversation ID value as specified in subclause 15.2.9;

3) if the filecontinues an existing conversation, shall set the Conversation ID IE to the Conversation ID value of the existing conversation as specified in subclause 15.2.9;

4) shall set the Message ID IE to a newly generated Message ID value as specified in subclause 15.2.10;

5) if the fileis in reply to a previously received SDS message or file, shall include the InReplyTo message ID IE with the Message ID value in the previously received SDS message or file;

6) if the file is for user consumption, shall not include an Application ID IE as specified in subclause 15.2.7 and shall not include an Extended application ID IE as specified in subclause 15.2.24;

7) if the file is intended for an application on the terminating MCData client, shall include:

   a) an Application ID IE with a Application ID value representing the intended application as specified in subclause 15.2.7; or

   b) an Extended application ID IE with an Extended application ID value representing the intended application as specified in subclause 15.2.24;

NOTE: The value and field chosen for coding the identity of the application are coordinated by the mission critical organisation.

8) if a file download complete notification is required shall include a FD disposition request type IE set to "FILE DOWNLOAD COMPLETED UPDATE" as specified in subclause 15.2.4; and

9) shall include and set the Mandatory download IE to "MANDATORY DOWNLOAD" as described in subclause 15.2.16.

[TS 24.282, clause 12.2.1.2]

Upon receipt of a:

"SIP MESSAGE request for SDS disposition notification for terminating MCData client"; or

"SIP MESSAGE request for FD disposition notification for terminating MCData client";

the MCData client:

1) shall decode the contents of the application/vnd.3gpp.mcdata-signalling MIME body; and

2) shall deliver the notification to the user or application.

[TS 24.582, clause 7.1.2.1]

Upon receiving an indication to establish MSRP connection for file distribution as the originating client, the MCData client:

1. shall act as an MSRP client according to IETF RFC 6135 [12];

2. shall act according to IETF RFC 6135 [12], as:

   a. an "active" endpoint, if a=setup attribute in the received SDP answer is set to "passive"; and

   b. an "passive" endpoint, if a=setup attribute in the received SDP answer is set to "active";

3. shall establish the MSRP connection according to the MSRP connection parameters in the SDP answer received in the SIP 200 (OK) response according to IETF RFC 4975 [11]; and

4. if acting as an "active" endpoint, shall send an empty MSRP SEND request to bind the MSRP connection to the MSRP session from the perspective of the passive endpoint according to the rules and procedures of IETF RFC 4975 [11] and IETF RFC 6135 [12].

On receiving MSRP 200 (OK) response to the first MSRP SEND request, the MCData client can send the file. To send the file, the MCData client:

1. shall generate MSRP SEND for file distribution request according to IETF RFC 4975 [11]. When generating an MSRP SEND, the MCData client:

   a. shall set To-Path header according to the MSRP URI(s) received in the answer SDP;

   b. shall set the Content-Type header field = to "application/vnd.3gpp.mcdata-file"; and

   c. shall include in the body of the MSRP SEND request the MSRP payload. The MSRP payload is set to the file or part of the file.

2. shall send the MSRP SEND request(s) on the established MSRP connection.

If MSRP chunking is used, the MCData client:

1. shall send further MSRP SEND requests containing the file as necessary;

2. shall wait for a 200 (OK) response to each MSRP SEND request sent; and

3. on receipt of the last 200 (OK) response shall terminate the SIP session as specified in 3GPP TS 24.282 [8].

On receiving a non-200 MSRP response to the MSRP SEND request the MCData client shall handle the error as specified in IETF RFC 4975 [11]. To terminate the MSRP session, the MCData client:

1. if there are further MSRP chunks to send, shall abort transmission of these further MSRP chunks;

2. shall indicate to MCData user that the file could not be distributed; and

3. shall terminate the SIP session as specified in 3GPP TS 24.282 [8].

6.2.15.3 Test description

6.2.15.3.1 Pre-test conditions

Test configuration:

- Single cell configuration according to TS 37.579-1 [2] clause 5.2.2.2.1.
- Test File 1 for CO FD as specified in annex A.2.1 is available at the UE for upload.

Preamble:

- The UE has performed procedure 'Initial registration' as described in TS 37.579-1 [2] clause 5.4.2.
- The UE has performed procedure 'UE initiated MCX functional alias status determination and subscription' as specified in TS 37.579-1 [2] clause 5.3.36.
- The UE has performed procedure 'UE initiated MCX functional alias status change' as specified in TS 37.579-1 [2] clause 5.3.37.
- UE States at the end of the preamble:
  - The UE is in RRC_IDLE state.
  - The client is registered for MCData.
  - The client is subscribed for notification of functional alias status changes and has activated a functional alias.

6.2.15.3.2 Test procedure sequence

Table 6.2.15.3.2-1: Main Behaviour

St	Procedure	Message Sequence		TP	Verdict
		U - S	Message		
1	Make the UE (MCData client) send test file 1 (ANNEX A.2.1) for CO one-to-one FD over media plane with disposition notification type "FILE DOWNLOAD COMPLETED UPDATE" using the active functional alias. (NOTE 1, NOTE 2)	-	-	-	-
2	Check: Does the UE (MCData client) correctly perform procedure '**CO MCData Call Establishment**' as described in TS 37.579-1 [2] Table 5.3C.2.3-1?	-	-	1,2	P
3	Check: Does the UE (MCData client) correctly perform procedure '**CO MSRP message transfer**' as described in TS 37.579-1 [2] Table 5.3C.4.3-1 **to send an FD message containing test file 1 for CO FD**?	-	-	2	P
4	Check: Is the content of the transferred file the same as specified in annex A.2.1?	-	-	2	P
5	Check: Does the UE (MCData client) correctly perform procedure '**CO MCData call release**' as described in TS 37.579-1 [2] Table 5.3C.6.3-1? (NOTE 3)	-	-	3	P
6	Check: Does the UE (MCData client) correctly perform procedure '**MCX SIP MESSAGE CT**' as described in TS 37.579-1 [2] Table 5.3.33.3-1 **to receive the disposition notification** for the FD message sent at step 7?	-	-	4	P
7	Check: Does the UE (MCData client) provide the disposition notification to the user? (NOTE 1)	-	-	4	P
NOTE 1: This is expected to be done via a suitable implementation dependent MMI. NOTE 2: Test file 1 for CO FD as specified in annex A.2.1. NOTE 3: The procedure does not release the RRC connection.					

6.2.15.3.3 Specific message contents

Table 6.2.15.3.3-1: SIP INVITE from the UE (step 2, Table 6.2.15.3.2-1; step 2, TS 37.579-1 [2] Table 5.3C.2.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.5.1-1, condition MCDATA_FD, MCD_1to1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part		**SDP message**		
MIME-part-body	SDP message as described in Table 6.2.15.3.3-2			
MIME body part		**MCData-Info**		
MIME-part-body	MCData-Info as described in Table 6.2.15.3.3-3			
MIME body part		**MCData Data signalling message**		
MIME-part-headers				
MIME-Content-Type	"application/vnd.3gpp. mcdata-signalling"			
MIME-part-body	MCData Protected Payload Message containing FD SIGNALLING PAYLOAD as described in Table 6.2.15.3.3-4			

Table 6.2.15.3.3-2: SDP for SIP INVITE (Table 6.2.15.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.1.1-3, condition MCDATA_FD, SDP_OFFER, MCD_1to1

Table 6.2.15.3.3-3: MCData-Info (Table 6.2.15.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.2.1-3, condition FUNCTIONAL_ALIAS				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
mcdata-info				
mcdata-Params				
request-type	"one-to-one-fd"			

Table 6.2.15.3.3-4: FD SIGNALLING PAYLOAD (Table 6.2.15.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.5-1, condition FD_MSRP

Table 6.2.15.3.3-5: SIP 200 (OK) from the SS (step 2, Table 6.2.15.3.2-1; step 4, TS 37.579-1 [2] Table 5.3C.2.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.17.1.2-1, condition INVITE-RSP				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
SDP message	As described in Table 6.2.15.3.3-6			

Table 6.2.15.3.3-6: SDP for SIP 200 (OK) (Table 6.2.15.3.3-5)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.1.2-3, condition MCDATA_FD, SDP_ANSWER

Table 6.2.15.3.3-7: MSRP SEND from the UE (step 3, Table 6.2.15.3.2-1; step 1, TS 37.579-1 [2] Table 5.3C.4.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.12.1.1-1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Content-Type				
media-type	"application/vnd.3gpp. mcdata-file"			
data	As specified in table 6.2.15.3.3-8			

Table 6.2.15.3.3-8: MCData Protected Payload Message (Table 6.2.15.3.3-7)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.10-1, condition PROTECTED_FILE, PCK

Table 6.2.15.3.3-9: SIP BYE from the UE (step 5, Table 6.2.15.3.2-1; step 1, TS 37.579-1 [2] Table 5.3C.6.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.2.1-1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Reason			RFC 3326 [125]	
reason-value	"SIP"			
protocol-cause	"cause="200""			
reason-text	"text="transmission succeeded""			

Table 6.2.15.3.3-10: SIP MESSAGE from the SS (step 6, Table 6.2.15.3.2-1; step 2, TS 37.579-1 [2] Table 5.3.33.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.7.2-1, condition MCDATA_FD, MCDATA_SIGNALLING				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part		**MCData Data signalling message**		
MIME-part-body	MCData Protected Payload Message containing FD NOTIFICATION as described in Table 6.2.15.3.3-11			

Table 6.2.15.3.3-11: FD NOTIFICATION (Table 6.2.15.3.3-10)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.8-1, condition FD_COMPLETED

6.2.16 On-network / File Distribution (FD) / FD Using HTTP / Group Standalone FD / Preconfigured Group Use Only

6.2.16.1 Test Purpose (TP)

(1)

```
with { UE (MCDATA Client) registered and authorised for MCDATA Service }
ensure that {
  when { the MCDATA User requests to send a Group Standalone FD message to a group configured for
preconfigured group use only }
    then { UE (MCDATA Client) indicate to the MCDATA user that group standalone FD is not allowed on
the indicated group and does not send a HTTP POST request }
```

}

6.2.16.2 Conformance requirements

References: The conformance requirements covered in the current TC are specified in: TS 24.282, clause 10.2.4.2.1. Unless otherwise stated, these are Rel-17 requirements.

[TS 24.282, clause 10.2.4.2.1]

If a group standalone FD message is to be sent, the MCData client shall determine whether the group document contains a <list-service> element that contains a <preconfigured-group-use-only> element. If a <preconfigured-group-use-only> element exists and is set to the value "true", then the MCData client:

1) should indicate to the MCData user that group standalone FD is not allowed on the indicated group; and

2) shall skip the remainder of this procedure.

The MCData client shall generate a SIP MESSAGE request in accordance with 3GPP TS 24.229 [5] and IETF RFC 3428 [6] with the clarifications given below.

The MCData client:

1) shall build the SIP MESSAGE request as specified in clause 6.2.4.1;

2) if a one-to-one standalone FD message is to be sent shall insert in the SIP MESSAGE request:

   a) an application/resource-lists+xml MIME body with the MCData ID of the target MCData user or the functional alias to be called, according to rules and procedures of IETF RFC 4826 [9]; and

   b) an application/vnd.3gpp.mcdata-info+xml MIME body with:

      i) a <request-type> element set to a value of "one-to-one-fd";

      ii) a <call-to-functional-alias-ind> set to "true" if the functional alias is used in the step a) above;

      iii) if the MCData client is aware of active functional aliases and if an active functional alias is to be included in the SIP MESSAGE request, the <functional-alias-URI> element set to the URI of the used functional alias; and

      iv) if the MCData user has requested an application priority, the <anyExt> element with the <user-requested-priority> element set to the user provided value;

3) if a group standalone FD message is to be sent:

   a) if the "/<*x*>/<x>/Common/MCData/AllowedFD" leaf node present in the group document of the requested MCData group, configured on the group management client as specified in 3GPP TS 24.483 [42] is set to "false", shall reject the request for FD and not continue with the rest of the steps in this clause; and

   b) shall insert in the SIP MESSAGE request an application/vnd.3gpp.mcdata-info+xml MIME body with:

      i) the <request-type> element set to a value of "group-fd";

      ii) the <mcdata-request-uri> element set to the MCData group identity;

      iii) the <mcdata-client-id> element set to the MCData client ID of the originating MCData client; and

      iv) if the MCData client is aware of active functional aliases and if an active functional alias is to be included in the SIP MESSAGE request, the <functional-alias-URI> element set to the URI of the used functional alias; and

      v) if the MCData user has requested an application priority, the <anyExt> element with the <user-requested-priority> element set to the user provided value;

4) shall generate a standalone FD message as specified in clause 6.2.2.2; and

5) shall send the SIP MESSAGE request according to rules and procedures of 3GPP TS 24.229 [5].

Upon receiving a SIP 300 (Multiple Choices) response to the SIP MESSAGE request the MCData client shall use the MCData ID contained in the <mcdata-request-uri> element of the received application/vnd.3gpp.mcdata-info MIME body as the MCData ID of the invited MCData user and shall generate a new SIP MESSAGE request in accordance with 3GPP TS 24.229 [5] and IETF RFC 3428 [6], with the clarifications given in this clause and with the following additional clarifications:

1) shall insert in the newly generated SIP MESSAGE request a MIME resource-lists body with the MCData ID of the invited MCData user in the <mcdata-request-uri> element of the application/vnd.3gpp.mcdata-info MIME body in the received SIP 300 (Multiple Choices) response;

2) shall not include a <call-to-functional-alias-ind> element into the <mcdata-Params> element of the <mcdatainfo> element of the application/vnd.3gpp.mcdata-info+xml MIME body; and

3) shall include a <called-functional-alias-URI> element into the <mcdata-Params> element of the <mcdatainfo> element of the application/vnd.3gpp.mcdata-info+xml MIME body with the target functional alias used in the initial SIP MESSAGE request for for sending one-to-one standalone FD message.

6.2.16.3 Test description

6.2.16.3.1 Pre-test conditions

Test configuration:

- Single cell configuration according to TS 37.579-1 [2] clause 5.2.2.2.1.
- Test File 1 for CO FD as specified in annex A.2.1 as specified in Annex A.2.2 is available at the UE for upload.

Preamble:

- The UE has performed procedure 'Initial registration' as described in TS 37.579-1 [2] clause 5.4.2 with the following clarifications:
- In the group configuration document the <preconfigured-group-use-only> element is set to "true".
- UE States at the end of the preamble:
  - The UE is in RRC_IDLE state.
  - The client is registered for MCData.

6.2.16.3.2 Test procedure sequence

Table 6.2.16.3.2-1: Main Behaviour

St	Procedure	Message Sequence		TP	Verdict
		U - S	Message		
1	Make the UE (MCData client) send test file 1 (Annex A.2.1) for CO group FD over HTTP. (NOTE 1, NOTE 2)	-	-	-	-
2	Check: Does the UE (MCData client) send an HTTP POST request to upload a file to the media storage function within the next 5s?	-->	HTTP POST	1	F
-	EXCEPTION: Step 3a1 describes behaviour that depends on the UE implementation; the "lower case letter" identifies a step sequence that take place if the UE displays an indication to the MCData user that group standalone FD is not allowed on the indicated group1.	-	-	-	-
3a1	IF pc_MCX_DisplayInfoFDNotAllowedOnGroup THEN Check: Does the UE (MCData client) indicate to the MCData user that group standalone FD is not allowed on the indicated group? (NOTE 1)	-	-	1	P
NOTE 1: This is expected to be done via a suitable implementation dependent MMI. NOTE 2: Test file 1 for CO FD as specified in annex A.2.1.					

6.2.16.3.3 Specific message contents

Table 6.2.16.3.3-1: Group Configuration document (Preamble)

Derivation Path: TS 37.579-1 [2], Table 5.5.7.4-2				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
list-service[1]				
mcpttgi:preconfigured-group-use-only	true		TS 24.481 [31] clause 7.2.4.2	

6.2.17 On-network / File Distribution (FD) / FD Using Media Plane / Group Standalone FD / Preconfigured Group Use Only

6.2.17.1 Test Purpose (TP)

(1)

```
with { UE (MCDATA Client) registered and authorised for MCDATA Service }
ensure that {
  when { the MCDATA User requests to send a Group Standalone FD message using the media plane to a
group configured for preconfigured group use only }
    then { UE (MCDATA Client) indicate to the MCDATA user that group standalone FD is not allowed on
the indicated group and does not send a SIP INVITE request }
            }
```

6.2.17.2 Conformance requirements

References: The conformance requirements covered in the current TC are specified in: TS 24.282, clause 10.2.5.2.3. Unless otherwise stated, these are Rel-17 requirements.

[TS 24.282, clause 10.2.5.2.3]

The MCData client shall generate a SIP INVITE request in accordance with 3GPP TS 24.229 [5] with the clarifications given below.

The MCData client:

1) shall include the g.3gpp.mcdata.fd media feature tag and the g.3gpp.icsi-ref media feature tag with the value of "urn:urn-7:3gpp-service.ims.icsi.mcdata.fd" in the Contact header field of the SIP INVITE request according to IETF RFC 3840 [16];

2) shall include an Accept-Contact header field containing the g.3gpp.mcdata.fd media feature tag along with the "require" and "explicit" header field parameters according to IETF RFC 3841 [8];

3) shall include an Accept-Contact header field with the g.3gpp.icsi-ref media feature tag containing the value of "urn:urn-7:3gpp-service.ims.icsi.mcdata.fd" along with the "require" and "explicit" header field parameters according to IETF RFC 3841 [8];

4) shall include the ICSI value "urn:urn-7:3gpp-service.ims.icsi.mcdata.fd" (coded as specified in 3GPP TS 24.229 [5]), in a P-Preferred-Service header field according to IETF RFC 6050 [7] in the SIP INVITE request;

5) should include the "timer" option tag in the Supported header field;

6) should include the Session-Expires header field according to IETF RFC 4028 [38]. It is recommended that the "refresher" header field parameter is omitted. If included, the "refresher" header field parameter shall be set to "uac";

7) shall generate and contain an application/vnd.3gpp.mcdata-signalling MIME body with the FD SIGNALLING PAYLOAD as described in clause 6.2.2.3;

8) if a one-to-one file distribution is requested:

   a0) if the MCData user has requested the origination of an MCData emergency one-to-one communication or is originating an MCData one-to-one communication and the MCData emergency state is already set, then:

      i) if this is an authorised request for an MCData emergency one-to-one communication as determined by the procedures of clause 6.2.8.3.1.1, shall comply with the procedures in clause 6.2.8.3.2; or

      ii) if this is an unauthorised request for an MCData emergency one-to-one communication as determined in step i) above, should indicate to the MCData user that initiation of an MCData emergency one-to-one communication is not authorized and shall release the generated SIP INVITE request and end the procedure;

   a) shall insert in the SIP INVITE request a MIME resource-lists body with the MCData ID of the invited MCData user or the functional alias to be called, according to rules and procedures of IETF RFC 5366 [18];

   NOTE 0: The MCData client indicates whether an MCData ID or a functional alias is to be called as specified in step 8) b) below.

   b) shall contain an application/vnd.3gpp.mcdata-info+xml MIME body with the <mcdatainfo> element containing the <mcdata-Params> element with:

      i) the <request-type> element set to a value of "one-to-one-fd";

      ii) with the <call-to-functional-alias-ind> set to "true" if the functional alias is used as a target of the call request;

      iii) if the MCData client is aware of active functional aliases and if an active functional alias is to be included in the SIP INVITE request, the <functional-alias-URI> element set to the URI of the used functional alias; and

      iv) if the MCData user has requested an application priority, the <anyExt> element with the <user-requested-priority> element set to the user provided value;

   c) if an end-to-end security context needs to be established and the security context does not exist or if the existing security context has expired, then:

i) if necessary, shall instruct the key management client to request keying material from the key management server as described in 3GPP TS 33.180 [26];

ii) shall use the keying material to generate a PCK as described in 3GPP TS 33.180 [26];

iii) shall use the PCK to generate a PCK-ID with the four most significant bits set to "0001" to indicate that the purpose of the PCK is to protect one-to-one communications and with the remaining twenty eight bits being randomly generated as described in 3GPP TS 33.180 [26];

iv) shall encrypt the PCK to a UID associated to the MCData client using the MCData ID of the invited user and a time related parameter as described in 3GPP TS 33.180 [26];

v) shall generate a MIKEY-SAKKE I_MESSAGE using the encapsulated PCK and PCK-ID as specified in 3GPP TS 33.180 [26]; and

vi) shall add the MCData ID of the originating MCData user to the initiator field (IDRi) of the I_MESSAGE as described in 3GPP TS 33.180 [26]; and

vii) shall sign the MIKEY-SAKKE I_MESSAGE using the originating MCData user's signing key provided in the keying material together with a time related parameter, and add this to the MIKEY-SAKKE payload, as described in 3GPP TS 33.180 [26]; and

d) if the MCData emergency private communication state is set to either "MDEPC 2: emergency-pc-requested" or "MDEPC 3: emergency-pc-granted" or if the MCData emergency private priority state of this one-to-one communication is set to a value other than "MDEPP 2: in-progress" or "MDEPP 3: confirm-pending", shall execute the procedures in clause 6.2.8.3.3 to include the Resource-Priority header field;

9) if a group file distribution is requested:

a) if the "/<*x*>/<x>/Common/MCData/AllowedFD" leaf node present in the group document of the requested MCData group, configured on the group management client as specified in 3GPP TS 24.483 [42] is set to "false", shall reject the request for FD and not continue with the rest of the steps in this clause;

a1) if the group document contains a <list-service> element that contains a <preconfigured-group-use-only> element. If a <preconfigured-group-use-only> element exists and is set to the value "true", then the MCData client:

i) should indicate to the MCData user that group file distribution is not allowed on the indicated group; and

ii) shall skip the remainder of this procedure; and

b) shall contain in an application/vnd.3gpp.mcdata-info+xml MIME body with the <mcdatainfo> element containing the <mcdata-Params> element with:

i) the <request-type> element set to a value of "group-fd";

ii) the <mcdata-request-uri> element set to the MCData group identity;

iii) the <mcdata-client-id> element set to the MCData client ID of the originating MCData client;

NOTE 1: The MCData client does not include the MCData ID of the originating MCData user in the body, as this will be inserted into the body of the SIP INVITE request that is sent from the originating participating MCData function.

iv) if the MCData client is aware of active functional aliases and if an active functional alias is to be included in the SIP INVITE request, the <functional-alias-URI> element set to the URI of the used functional alias; and

v) if the MCData user has requested an application priority, the <anyExt> element with the <user-requested-priority> element set to the user provided value;

c) if the MCData user has requested the origination of an MCData emergency group communication or is originating an MCData pre-arranged group communication and the MCData emergency state is already set, the MCData client shall execute the procedures in clause 6.2.8.1.1;

d) if the MCData user has requested the origination of an MCData imminent peril group communication, the MCData client shall execute the procedures in clause 6.2.8.1.9;

e) if the MCData client emergency group state for this group is set to "MDEG 2: in-progress" or "MDEG 4: confirm-pending", the MCData client shall execute the procedures in clause 6.2.8.1.2 to include the Resource-Priority header field; and

f) if the MCData client imminent peril group state for this group is set to "MDIG 2: in-progress" or "MDIG 4: confirm-pending", shall execute the procedures in clause 6.2.8.1.12 to include the Resource-Priority header field;

10) shall set the Request-URI of the SIP INVITE request to the public service identity identifying the participating MCData function serving the MCData user;

NOTE 2: The MCData client is configured with public service identity identifying the participating MCData function serving the MCData user.

11) may include a P-Preferred-Identity header field in the SIP INVITE request containing a public user identity as specified in 3GPP TS 24.229 [5];

12) shall include an SDP offer according to 3GPP TS 24.229 [5] with the clarifications given in clause 10.2.5.2.1; and

13) shall send the SIP INVITE request towards the MCData server according to 3GPP TS 24.229 [5].

Upon receiving a SIP 300 (Multiple Choices) response to the SIP INVITE request the MCData client shall use the MCData ID of MCData user contained in the <mcdata-request-uri> element of the received application/vnd.3gpp.mcdata-info MIME body as the MCData ID of the invited MCData user and shall generate an initial SIP MCData request by following the UE originating session procedures specified in 3GPP TS 24.229 [5], with the clarifications given in this clause and with the following additional clarifications:

1) shall insert in the newly generated SIP INVITE request a MIME resource-lists body with the MCData ID of the invited MCData user in the <mcdata-request-uri> element of the application/vnd.3gpp.mcdata-info MIME body in the received SIP 300 (Multiple Choices) response;

2) shall not include a <call-to-functional-alias-ind> element into the <mcdata-Params> element of the <mcdatainfo> element of the application/vnd.3gpp.mcdata-info+xml MIME body; and

3) shall include a <called-functional-alias-URI> element into the <mcdata-Params> element of the <mcdatainfo> element of the application/vnd.3gpp.mcdata-info+xml MIME body with the target functional alias used in the initial SIP INVITE request for establishing a session for one-to-one file distribution.

On receipt of a SIP 2xx response to the SIP INVITE request, the MCData client:

0) if the response is to a SIP INVITE request for an MCData emergency group an MCData imminent peril group communication, shall perform the actions specified in clause 6.2.8.1.4;

1) if the response is to a SIP INVITE request for an MCData emergency one-to-one communication, shall perform the actions specified in clause 6.2.8.3.4;

2) shall send a SIP ACK request as specified in 3GPP TS 24.229 [5];

3) shall start the SIP Session timer according to rules and procedures of IETF RFC 4028 [38]; and

4) shall interact with the media plane as specified in 3GPP TS 24.582 [15] clause 7.1.2.

On receipt of a SIP 4xx response, a SIP 5xx response or a SIP 6xx response to the SIP INVITE request, the MCData client:

0) if the response is to a SIP INVITE request for an MCData emergency group communication an MCData imminent peril group communication, shall perform the actions specified in clause 6.2.8.1.5;

1) if the response is to a SIP INVITE request for an MCData emergency one-to-one communication, shall perform the actions specified in clause 6.2.8.3.5;

2) shall indicate to the MCData user that the file could not be sent; and

3) shall send a SIP ACK request as specified in 3GPP TS 24.229 [5].

On receipt of a SIP INFO request where the Request-URI contains an MCData session ID identifying an ongoing group session, the MCData client shall follow the actions specified in clause 6.2.8.1.13.

On receipt of a SIP INFO request where the Request-URI contains an MCData session ID identifying an ongoing one to-one session, the MCData client shall follow the actions specified in clause 6.2.8.3.7.

On receipt of an indication from the media plane indicating that the file was not sent successfully, the MCData client shall:

1) shall generate a SIP BYE request according to 3GPP TS 24.229 [5] with:

   a) Reason code set to "SIP";

   b) cause set to "480"; and

   c) text set to "transmission failed";

2) shall set the Request-URI to the MCData session identity to release; and

3) shall send a SIP BYE request towards MCData server according to 3GPP TS 24.229 [5].

6.2.17.3 Test description

6.2.17.3.1 Pre-test conditions

Test configuration:

- Single cell configuration according to TS 37.579-1 [2] clause 5.2.2.2.1.
- Test File 1 for CO FD as specified in annex A.2.1 as specified in Annex A.2.2 is available at the UE for upload.

Preamble:

- The UE has performed procedure 'Initial registration' as described in TS 37.579-1 [2] clause 5.4.2 with the following clarifications:
- In the group configuration document the <preconfigured-group-use-only> element is set to "true".
- UE States at the end of the preamble:
  - The UE is in RRC_IDLE state.
  - The client is registered for MCData.

6.2.17.3.2 Test procedure sequence

Table 6.2.17.3.2-1: Main Behaviour

St	Procedure	Message Sequence		TP	Verdict
		U - S	Message		
1	Make the UE (MCData client) send test file 1 (Annex A.2.1) for CO group FD over media plane. (NOTE 1, NOTE 2)	-	-	-	-
2	Check: Does the UE (MCData client) send an SIP INVITE request to establish a MCData call within the next 5s?	-->	SIP INVITE	1	F
-	EXCEPTION: Step 3a1 describes behaviour that depends on the UE implementation; the "lower case letter" identifies a step sequence that take place if the UE displays an indication to the MCData user that group standalone FD is not allowed on the indicated group1.	-	-	-	-
3a1	IF pc_MCX_DisplayInfoFDNotAllowedOnGroup THEN Check: Does the UE (MCData client) indicate to the MCData user that group standalone FD is not allowed on the indicated group? (NOTE 1)	-	-	1	P
NOTE 1: This is expected to be done via a suitable implementation dependent MMI. NOTE 2: Test file 1 for CO FD as specified in annex A.2.1.					

6.2.17.3.3 Specific message contents

Table 6.2.17.3.3-1: Group Configuration document (Preamble)

Derivation Path: TS 37.579-1 [2], Table 5.5.7.4-2				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
list-service[1]				
mcpttgi:preconfigured-group-use-only	true		TS 24.481 [31] clause 7.2.4.2	

6.3 Enhanced Status (ES)

6.3.1 On-network / Enhanced Status (ES) / Client Originated (CO)

6.3.1.1 Test Purpose (TP)

(1)

```
with { UE (MCDATA Client) registered and authorised for MCDATA Service }
ensure that {
  when { the MCDATA User requests to send an Enhanced Status with a disposition of only Delivery }
    then { UE (MCDATA Client) sends an Enhanced Status with a disposition request of only Delivery
via s SIP MESSAGE message }
            }
```

(2)

```
with { UE (MCDATA Client) having sent an Enhanced Status with a disposition request of DELIVERY }
ensure that {
  when { the UE (MCDATA Client) receives a disposition response via a SIP MESSAGE message from the
SS (MCDATA Server) }
```

```
    then { UE (MCData Client) responds to the SIP MESSAGE message by sending a SIP 200 (OK) message
and delivers the notification to the MCDATA User }
            }
```

6.3.1.2 Conformance requirements

References: The conformance requirements covered in the current TC are specified in: TS 24.282, clauses 14.2.1.1, 9.2.2.2.1, 6.2.2.1, 6.2.4.1, 12.2.1.2. The following represents a copy/paste extraction of the requirements relevant to the test purpose; any references within the copy/paste text should be understood within the scope of the core spec they have been copied from. Unless otherwise stated, these are Rel-15 requirements.

[TS 24.282, clause 14.2.1.1]

Upon receiving a request from the MCData user to send an enhanced status to an MCData group and the <mcdata-allow-enhanced-status> element under the <list-service> element as defined in 3GPP TS 24.481 [11] is set to "true", the MCData client:

1) shall use the "id" attribute of the MCData user selected operation value from <mcdata-enhanced-status-operational-values> element under <list-service> element as defined in 3GPP TS 24.481 [11], to generate a group standalone SDS message by following the procedure described in clause 9.2.2.2.1.

[TS 24.282, clause 9.2.2.2.1]

The MCData client shall generate a SIP MESSAGE request in accordance with 3GPP TS 24.229 [5] and IETF RFC 3428 [6] with the clarifications given below.

The MCData client:

1) shall build the SIP MESSAGE request as specified in subclause 6.2.4.1;

...

3) if a group standalone SDS message is to be sent:

   a) if the "/<*x*>/<*x*>/Common/MCData/AllowedSDS" leaf node present in the group document of the requested MCData group, configured on the group management client as specified in 3GPP TS 24.483 [42] is set to "false", shall reject the request to send SDS and not continue with the rest of the steps in this subclause; and

   b) shall insert in the SIP MESSAGE request an application/vnd.3gpp.mcdata-info+xml MIME body with:

      i) the <request-type> element set to a value of "group-sds";

      ii) the <mcdata-request-uri> element set to the MCData group identity; and

      iii) the <mcdata-client-id> element set to the MCData client ID of the originating MCData client;

4) shall generate a standalone SDS message as specified in subclause 6.2.2.1; and

5) shall send the SIP MESSAGE request according to rules and procedures of 3GPP TS 24.229 [5].

[TS 24.282, clause 6.2.2.1]

In order to generate an SDS message, the MCData client:

1) shall generate an SDS SIGNALLING PAYLOAD message as specified in clause 15.1.2;

2) shall generate a DATA PAYLOAD message as specified in clause 15.1.4;

3) shall include in the SIP request, the SDS SIGNALLING PAYLOAD message in an application/vnd.3gpp.mcdata-signalling MIME body as specified in clause E.1; and

4) shall include in the SIP request, the DATA PAYLOAD message in an application/vnd.3gpp.mcdata-payload MIME body as specified in clause E.2.

When generating an SDS SIGNALLING PAYLOAD message as specified in clause 15.1.2, the MCData client:

1) shall set the Date and time IE to the current time as specified in clause 15.2.8;

2) if the SDS message starts a new conversation, shall set the Conversation ID IE to a newly generated Conversation ID value as specified in clause 15.2.9;

3) if the SDS message continues an existing unfinished conversation, shall set the Conversation ID IE to the Conversation ID value of the existing conversation as specified in clause 15.2.9;

4) shall set the Message ID IE to a newly generated Message ID value as specified in clause 15.2.10;

5) if the SDS message is in reply to a previously received SDS message, shall include the InReplyTo message ID IE with the Message ID value in the previously received SDS message;

6) if the SDS message is for user consumption, shall not include an Application ID IE as specified in clause 15.2.7and shall not include an Extended application ID IE as specified in clause 15.2.24;

7) if the SDS message is intended for an application on the terminating MCData client, shall include:

   a) an Application ID IE with a Application ID value representing the intended application as specified in clause 15.2.7; or

   b) an Extended application ID IE with an Extended application ID value representing the intended application as specified in clause 15.2.24;

NOTE: The value chosen for the Application ID value is decided by the mission critical organisation.

8) if only a delivery disposition notification is required shall include a SDS disposition request type IE set to "DELIVERY" as specified in clause 15.2.3;

9) if only a read disposition notification is required shall include a SDS disposition request type IE set to "READ" as specified in clause 15.2.3; and

10) if both a delivery and read disposition notification is required shall include a SDS disposition request type IE set to "DELIVERY AND READ" as specified in clause 15.2.3.

When generating an DATA PAYLOAD message for SDS as specified in clause 15.1.4, the MCData client:

1) shall set the Number of payloads IE to the number of Payload IEs that needs to be encoded, as specified in clause 15.2.12;

2) if end-to-end security is required for a one-to-one communication, shall include the Security parameters and Payload IE with security parameters as described in 3GPP TS 33.180 [26]. Otherwise, if end-to-end security is not required for a one-to-one communication, shall include the Payload IE as specified in clause 15.1.4; and

3) for each Payload IE included:

   a) if the payload is text, shall set the Payload content type as "TEXT" as specified in clause 15.2.13;

   b) if the payload is binary data, shall set the Payload content type as "BINARY" as specified in clause 15.2.13;

   c) if the payload is hyperlinks, shall set the Payload content type as "HYPERLINKS" as specified in clause 15.2.13;

   d) if the payload is location, shall set the Payload content type as "LOCATION" as specified in clause 15.2.13;

   e) if payload is enhanced status for a group, shall set the Payload content type as "ENHANCED STATUS" as specified in subclause 15.2.13; and

   f) shall include the data to be sent in the Payload data.

[TS 24.282, clause 6.2.4.1]

This subclause is referenced from other procedures.

In a SIP MESSAGE request, the MCData client:

1) when sending SDS messages or SDS disposition notifications:

a) shall include an Accept-Contact header field containing the g.3gpp.mcdata.sds media feature tag along with the "require" and "explicit" header field parameters according to IETF RFC 3841 [8];

b) shall include an Accept-Contact header field with the media feature tag g.3gpp.icsi-ref containing the value of "urn:urn-7:3gpp-service.ims.icsi.mcdata.sds" along with the "require" and "explicit" header field parameters according to IETF RFC 3841 [8]; and

c) shall include the ICSI value "urn:urn-7:3gpp-service.ims.icsi.mcdata.sds" (coded as specified in 3GPP TS 24.229 [5]), in a P-Preferred-Service header field according to IETF RFC 6050 [7] in the SIP MESSAGE request;

…

3) may include a P-Preferred-Identity header field in the SIP MESSAGE request containing a public user identity as specified in 3GPP TS 24.229 [5]; and

4) shall set the Request-URI to the public service identity identifying the participating MCData function serving the MCData user.

[TS 24.282, clause 12.2.1.2]

Upon receipt of a:

"SIP MESSAGE request for SDS disposition notification for terminating MCData client"; or

"SIP MESSAGE request for FD disposition notification for terminating MCData client";

the MCData client:

1) shall decode the contents of the application/vnd.3gpp.mcdata-signalling MIME body; and

2) shall deliver the notification to the user or application.

6.3.1.3 Test description

6.3.1.3.1 Pre-test conditions

Test configuration:

- Single cell configuration according to TS 37.579-1 [2] clause 5.2.2.2.1.

Preamble:

- The UE has performed procedure 'Initial registration' as described in TS 37.579-1 [2] clause 5.4.2 with the following clarifications:
  - The <max-payload-size-sds-cplane-bytes> element in the MCData service configuration document as specified in 3GPP TS 24.484 [12], shall be large enough to allow the sending of the standalone SDS message using the signalling plane.
- UE States at the end of the preamble:
  - The UE is in RRC_IDLE state.
  - The client is registered for MCData.

6.3.1.3.2 Test procedure sequence

Table 6.3.1.3.2-1: Main Behaviour

St	Procedure	Message Sequence		TP	Verdict
		U - S	Message		
1	Make the UE (MCData client) send an enhanced status to Group A using Enhanced Status Id "1" with disposition request "DELIVERY". (NOTE 1)	-	-	-	-
2-2B	Check: Does the UE (MCData client) correctly perform steps 1a1-3 of procedure '**CO SDS or FD message transfer using signalling plane**' as described in TS 37.579-1 [2] Table 5.3C.1.3-1 **to send an Enhanced Status with Enhanced Status Id "1" and disposition request "DELIVERY"**? (NOTE 2)	-	-	1	P
3	Void	-	-	-	-
4	Check: Does the UE (MCData client) correctly perform procedure '**MCX SIP MESSAGE CT**' as described in TS 37.579-1 [2] Table 5.3.33.3-1 **to receive the disposition notification** for the SDS message sent at step 2A?	-	-	2	P
5	Void	-	-	-	-
6	Check: Does the UE (MCData client) provide the disposition notification to the user? (NOTE 1)	-	-	2	P
NOTE 1: This is expected to be done via a suitable implementation dependent MMI. NOTE 2: The RRC connection is not released at the end of the procedure.					

6.3.1.3.3 Specific message contents

Table 6.3.1.3.3-1: SIP MESSAGE from the UE (step 2A, Table 6.3.1.3.2-1; step 2, TS 37.579-1 [2] Table 5.3C.1.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.7.1-1, condition MCDATA_SDS, MCDATA_SIGNALLING, MCDATA_PAYLOAD				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part		**MCData-Info**		
MIME-part-body	MCData-Info as described in Table 6.3.1.3.3-2			
MIME body part		**MCData Data signalling message**		
MIME-part-body	MCData Protected Payload Message containing SDS SIGNALLING PAYLOAD as described in Table 6.1.3.3.3-2A			
MIME body part		**MCData Data message**		
MIME-part-body	MCData Protected Payload Message containing DATA PAYLOAD as described in Table 6.3.1.3.3-3			

Table 6.3.1.3.3-2: MCData-Info (Table 6.3.1.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.2.1-3, condition MCD_grp

Table 6.3.1.3.3-2A: SDS SIGNALLING PAYLOAD (Table 6.3.1.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.1-1, condition DELIVERED

Table 6.3.1.3.3-3: DATA PAYLOAD (Table 6.3.1.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.9.1-1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Payload				
Payload content type	'00000110'B	ENHANCED STATUS	TS 24.282 [31], Table 15.2.13-2	
Payload data	"1"	The id as defined in the MCData Group Configuration Document	TS 37.579-1 [2], Table 5.5.7.3-1	

Table 6.3.1.3.3-4: SIP MESSAGE from the SS (step 4, Table 6.3.1.3.2-1; step 2, TS 37.579-1 [2] Table 5.3.33.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.7.2-1, condition MCDATA_SDS, MCDATA_SIGNALLING				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part		**MCData Info**		
MIME-part-body	As described in Table 6.3.1.3.3-5			
MIME body part		**MCData Data signalling message**		
MIME-part-body	MCData Protected Payload Message containing SDS NOTIFICATION as described in Table 6.3.1.3.3-6			

Table 6.3.1.3.3-5: MCData-Info (Table 6.3.1.3.3-4)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.2.2-3				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
mcdata-info				
mcdata-Params				
mcdata-calling-group-id	Encrypted <mcdata-calling-group-id> with mcdataURI set to px_MCData_Group_A_ID	Encrypted according to TS 37.579-1 [2] Table 5.5.3.2.2-3A		

Table 6.3.1.3.3-6: SDS NOTIFICATION (Table 6.3.1.3.3-4)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.4-1, condition DELIVERED

Table 6.3.1.3.3-7: Void

6.3.2 On-network / Enhanced Status (ES) / Client Terminated (CT)

6.3.2.1 Test Purpose (TP)

(1)

```
with { UE (MCDATA Client) registered and authorised for MCDATA Service }
ensure that {
  when { the MCDATA User receives an Enhanced Status with a disposition request of "DELIVERY" }
    then { UE (MCDATA Client) responds by sending a SIP 200 (OK) message and sends a SIP MESSAGE
message with a disposition notification of "DELIVERED" and renders the operational value of the
received Enhanced Status ID as enhanced status to the MCDATA User }
            }
```

6.3.2.2 Conformance requirements

References: The conformance requirements covered in the current TC are specified in: TS 24.282, clauses 14.2.1.2, 9.2.2.2.2, 9.2.1.2, 9.2.1.3, 12.2.1.1, 6.2.3.1, 6.2.4.1. The following represents a copy/paste extraction of the requirements relevant to the test purpose; any references within the copy/paste text should be understood within the scope of the core spec they have been copied from. Unless otherwise stated, these are Rel-15 requirements.

[TS 24.282, clause 14.2.1.2]

Upon receiving a "SIP MESSAGE request for standalone SDS for terminating MCData client", the MCData client:

1) shall follow the procedure defined in clause 9.2.2.2.2;

2) shall match the received value with an "id" attribute of the operational values from the <mcdata-enhanced-status-operational-values> element of the MCData group document as defined in 3GPP TS 24.481 [11]; and

3) if a match is found, shall render the operational value as enhanced status to the MCData user. Otherwise shall discard the received message.

[TS 24.282, clause 9.2.2.2.2]

Upon receipt of a "SIP MESSAGE request for standalone SDS for terminating MCData client", the MCData client:

…

3) if the SIP MESSAGE request contains an application/mikey MIME body containing a MIKEY-SAKKE I_MESSAGE:

   a) shall extract the MCData ID of the originating MCData user from the initiator field (IDRi) of the I_MESSAGE as described in 3GPP TS 33.180 [26];

   b) shall convert the MCData ID to a UID as described in 3GPP TS 33.180 [26];

   c) shall use the UID to validate the signature of the MIKEY-SAKKE I_MESSAGE as described in 3GPP TS 33.180 [26];

   d) if authentication verification of the MIKEY-SAKKE I_MESSAGE fails, shall reject the SIP MESSAGE request with a SIP 606 (Not Acceptable) response, and include warning text set to "136 authentication of the MIKEY-SAKKE I_MESSAGE failed" in a Warning header field as specified in subclause 4.9 and not continue with rest of the steps in this subclause; and

   e) if the signature of the MIKEY-SAKKE I_MESSAGE was successfully validated:

      i) shall extract and decrypt the encapsulated PCK using the terminating user's (KMS provisioned) UID key as described in 3GPP TS 33.180 [26]; and

      ii) shall extract the PCK-ID, from the payload as specified in 3GPP TS 33.180 [26];

NOTE: With the PCK successfully shared between the originating MCData client and the terminating MCData client, both clients are able to exchange end-to-end secure message.

4) shall generate a SIP 200 (OK) response according to rules and procedures of 3GPP TS 24.229 [5];

5) shall send the SIP 200 (OK) response towards the MCData server according to rules and procedures of 3GPP TS 24.229 [5]; and

6) shall handle the received message as specified in subclause 9.2.1.2.

[TS 24.282, clause 9.2.1.2]

When a MCData client has received a SIP request containing:

- an application/vnd.3gpp.mcdata-signalling MIME body as specified in subclause E.1; and
- an application/vnd.3gpp.mcdata-payload MIME body as specified in subclause E.2;

the MCData Client:

1) shall decode the contents of the application/vnd.3gpp.mcdata-signalling MIME body;

2) shall decode the contents of the application/vnd.3gpp.mcdata-payload MIME body;

…

5) shall identify the number of Payload IEs in the DATA PAYLOAD message from the Number of payloads IE in the DATA PAYLOAD message;

6) if the SDS SIGNALLING PAYLOAD message does not contain an Application ID IE:

   a) shall determine that the payload contained in the DATA PAYLOAD message is for user consumption

   b) may notify the MCData user; and

   c) shall render the contents of the Payload IE(s) to the MCData user;

7) if the SDS SIGNALLING PAYLOAD message contains an Application ID IE:

   a) shall determine that the payload contained in the DATA PAYLOAD message is not for user consumption,

   b) shall not notify the MCData user;

   c) if the Application ID value is unknown, shall discard the SDS message; and

   d) if the Application ID value is known, shall deliver the contents of the Payload IE(s) to the identified application;

NOTE 1: If required, the MCData client decrypts the Payload IEs before rendering the SDS message to the user or delivering the SDS message to the application.

…

NOTE 3: User consent is not required before accepting the data.

8) may store the message payload in local storage along with the Conversation ID, Message ID, InReplyTo message ID and Date and time; and

9) if the received SDS SIGNALLING PAYLOAD message contains an SDS disposition request type IE shall follow the procedures in subclause 9.2.1.3.

[TS 24.282, clause 9.2.1.3]

To handle the disposition requests, the MCData client:

1) If the SDS disposition request type IE is set to:

   a) "DELIVERY" then, shall send a delivered notification as described in subclause 12.2.1.1;

   b) "READ", shall send a read notification as described in subclause 12.2.1.1, when a display indication is received; or

   c) "DELIVERY AND READ" then, shall start timer TDU1 (delivery and read).

[TS 24.282, clause 12.2.1.1]

The MCData client shall follow the procedures in this subclause to:

- indicate to an MCData client that an SDS message was delivered, read or delivered and read when the originating client requested a delivery, read or delivery and read report;
- indicate to the participating MCData function serving the MCData user that an SDS message was undelivered. The participating MCData function can store the message for later re-delivery;
- indicate to an MCData client that a request for FD was accepted, deferred or rejected; or
- indicate to an MCData client that a file download has been completed;

Before sending a disposition notification the MCData client needs to determine:

- the controlling MCData function that sent the SDS or FD message request. The MCData client determines the controlling MCData function from the contents of the <mcdata-controller-psi> element contained in the application/vnd.3gpp.mcdata-info+xml MIME body of the incoming SDS or FD message request;
- the group identity related to an SDS or FD message request received as part of a group communication. The MCData client determines the group identity from the contents of the <mcdata-calling-group-id> element contained in the application/vnd.3gpp.mcdata-info+xml MIME body of the incoming SDS or FD message request; and
- the MCData user targeted for the disposition notification. The MCData client determines the targeted MCData user from the contents of the <mcdata-calling-user-id> element contained in the application/vnd.3gpp.mcdata-info+xml MIME body of the incoming SDS or FD message request.

The MCData client shall generate a SIP MESSAGE request in accordance with 3GPP TS 24.229 [5] and IETF RFC 3428 [6] with the clarifications given below.

The MCData client:

1) shall build the SIP MESSAGE request as specified in subclause 6.2.4.1;
2) shall follow the rules specified in subclause 6.4 for the handling of MIME bodies in a SIP message when processing the remaining steps in this subclause;
3) shall insert in the SIP MESSAGE request an application/resource-lists+xml MIME body containing the MCData ID of the targeted MCData user, according to rules and procedures of IETF RFC 5366 [18];
4) shall insert in the SIP MESSAGE request an application/vnd.3gpp.mcdata-info+xml MIME body with an <mcdata-controller-psi> element containing the PSI of the controlling MCData function;
5) if sending a disposition notification in response to an MCData group data request, shall include an <mcdata-calling-group-id> element set to the MCData group identity in the application/vnd.3gpp.mcdata-info+xml MIME body;
6) if requiring to send an SDS notification, shall generate an SDS NOTIFICATION message and include it in the SIP MESSAGE request as specified in subclause 6.2.3.1;

…

8) shall send the SIP MESSAGE request according to rules and procedures of 3GPP TS 24.229 [5].

[TS 24.282, clause 6.2.3.1]

In order to generate an SDS notification, the MCData client:

1) shall generate an SDS NOTIFICATION message as specified in subclause 15.1.5; and
2) shall include in the SIP request, the SDS NOTIFICATION message in an application/vnd.3gpp.mcdata-signalling MIME body as specified in subclause E.1.

When generating an SDS NOTIFICATION message as specified in subclause 15.1.5, the MCData client:

1) if sending a delivered notification, shall set the SDS disposition notification type IE as "DELIVERED" as specified in subclause 15.2.5;

…

5) shall set the Date and time IE to the current time to as specified in subclause 15.2.8;

6) shall set the Conversation ID to the value of the Conversation ID that was received in the SDS message as specified in subclause 15.2.9;

7) shall set the Message ID to the value of the Message ID that was received in the SDS message as specified in subclause 15.2.10;

8) if the SDS message was destined for the user, shall not include an Application ID IE as specified in subclause 15.2.7; and

[TS 24.282, clause 6.2.4.1]

This subclause is referenced from other procedures.

In a SIP MESSAGE request, the MCData client:

1) when sending SDS messages or SDS disposition notifications:

   a) shall include an Accept-Contact header field containing the g.3gpp.mcdata.sds media feature tag along with the "require" and "explicit" header field parameters according to IETF RFC 3841 [8];

   b) shall include an Accept-Contact header field with the media feature tag g.3gpp.icsi-ref containing the value of "urn:urn-7:3gpp-service.ims.icsi.mcdata.sds" along with the "require" and "explicit" header field parameters according to IETF RFC 3841 [8]; and

   c) shall include the ICSI value "urn:urn-7:3gpp-service.ims.icsi.mcdata.sds" (coded as specified in 3GPP TS 24.229 [5]), in a P-Preferred-Service header field according to IETF RFC 6050 [7] in the SIP MESSAGE request;

…

3) may include a P-Preferred-Identity header field in the SIP MESSAGE request containing a public user identity as specified in 3GPP TS 24.229 [5]; and

4) shall set the Request-URI to the public service identity identifying the participating MCData function serving the MCData user.

6.3.2.3 Test description

6.3.2.3.1 Pre-test conditions

Test configuration:

- Single cell configuration according to TS 37.579-1 [2] clause 5.2.2.2.1.

Preamble:

- The UE has performed procedure 'Initial registration' as described in TS 37.579-1 [2] clause 5.4.2 with the following clarifications:

  - The <max-payload-size-sds-cplane-bytes> element in the MCData service configuration document as specified in 3GPP TS 24.484 [12], shall be large enough to allow the sending of the standalone SDS message using the signalling plane.

- UE States at the end of the preamble:

  - The UE is in RRC_IDLE state.

  - The client is registered for MCData.

6.3.2.3.2 Test procedure sequence

Table 6.3.2.3.2-1: Main Behaviour

St	Procedure	Message Sequence		TP	Verdict
		U - S	Message		
1-1B	Check: Does the UE (MCData client) correctly perform steps 1a1-3 of procedure '**MCX SIP MESSAGE CT**' as described in TS 37.579-1 [2] Table 5.3.33.3-1 **to receive an Enhanced Status with disposition request "DELIVERY" and an enhanced status payload with id=0**? (NOTE 2)	-	-	1	P
3	Check: Does the UE (MCData client) correctly perform procedure '**CO SDS or FD message transfer using signalling plane**' as described in TS 37.579-1 [2] Table 5.3C.1.3-1 **to send a disposition notification of "DELIVERED"**?	-	-	1	P
4	Void	-	-	-	-
5	Check: Does the UE (MCData client) provide the operational value of the enhanced status with id=0 to the user ("going to the operation site")? (NOTE 1)	-	-	1	P
NOTE 1: This is expected to be done via a suitable implementation dependent MMI. NOTE 2: The RRC connection is not released at the end of the procedure.					

6.3.2.3.3 Specific message contents

Table 6.3.2.3.3-1: SIP MESSAGE from the SS (step 1A, Table 6.3.2.3.2-1; step 2, TS 37.579-1 [2] Table 5.3.33.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.7.2-1, condition MCDATA, PRIVATE-CALL				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part		**MCData-Info**		
MIME-part-body	MCData-Info as described in Table 6.3.2.3.3-2			
MIME body part		**MCData Data signalling message**		
MIME-part-body	MCData Protected Payload Message containing SDS SIGNALLING PAYLOAD as described in Table 6.3.2.3.3-3			
MIME body part		**MCData Data message**		
MIME-part-body	MCData Protected Payload Message containing DATA PAYLOAD as described in TS 37.579-1 [2] Table 6.3.2.3.3-4			

Table 6.3.2.3.3-2: MCData-Info (Table 6.3.2.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.2.2-3, condition MCD_grp

Table 6.3.2.3.3-3: SDS SIGNALLING PAYLOAD (Table 6.3.2.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.2-1, condition DELIVERED

Table 6.3.2.3.3-4: DATA PAYLOAD (Table 6.3.2.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.9.1-2				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Payload				
Payload content type	'00000110'B	ENHANCED STATUS	TS 24.282 [31], Table 15.2.13-2	
Payload data	"0"	The id as defined in the MCData Group Configuration Document	TS 37.579-1 [2], Table 5.5.7.3-1	

Table 6.3.2.3.3-5: Void

Table 6.3.2.3.3-6: SIP MESSAGE from the UE (step 3, Table 6.3.2.3.2-1; step 2, TS 37.579-1 [2] Table 5.3C.1.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.7.1-1, condition MCDATA_SDS, RESOURCE_LISTS, MCDATA_SIGNALLING				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part		**MCData-Info**		
MIME-part-headers	MCData-Info described in Table 6.3.2.3.3-7			
MIME body part		**MCData Data signalling message**		
MIME-part-body	MCData Protected Payload Message containing SDS NOTIFICATION as described in Table 6.3.2.3.3-8			

Table 6.3.2.3.3-7: MCData-Info (Table 6.3.2.3.3-6)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.2.1-3				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
mcdata-info				
mcdata-Params				
mcdata-calling-group-id	Encrypted <mcdata-request-uri> with mcdataURI set to px_MCData_Group_A_ID	Encrypted according to TS 37.579-1 [2] Table 5.5.3.2.1-3A		

Table 6.3.2.3.3-8: SDS NOTIFICATION (Table 6.3.2.3.3-6)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.3-1, condition DELIVERED

6.4 Emergency Alert

6.4.1 On-network / Emergency Alert / Cancel Emergency Alert / Client Originated (CO)

6.4.1.1 Test Purpose (TP)

(1)

```
with { UE (MCDATA Client) registered and authorized for MCDATA Service, including authorized to
initiate an emergency alert }
ensure that {
  when { the MCDATA User requests to send an emergency alert with the location of emergency }
    then { UE (MCDATA Client) sends a SIP MESSAGE initiating an emergency alert and reporting
location information and gives the MCDATA User an indication of success upon the receipt of a SIP
200 (OK) message }
            }
```

(2)

```
with { UE (MCDATA Client) in the “MDEA3: emergency-alert-initiated” state}
ensure that {
  when { the MCDATA User requests to cancel the emergency alert}
    then { UE (MCDATA Client) sends a SIP MESSAGE requesting the cancelation of the emergency alert}
            }
```

6.4.1.2 Conformance requirements

References: The conformance requirements covered in the current TC are specified in: TS 24.282, clauses 16.2.1.1, 16.2.1.2. The following represents a copy/paste extraction of the requirements relevant to the test purpose; any references within the copy/paste text should be understood within the scope of the core spec they have been copied from. Unless otherwise stated, these are Rel-16 requirements.

[TS 24.282 clause 16.2.1.1]

Upon receiving a request from the MCData user to send an MCData emergency alert, the MCData client shall determine whether or not it is authorised to originate an emergency alert, as follows:

1) if the <allow-activate-emergency-alert> element of the <actions> element of a <rule> element of the <ruleset> element of the MCData user profile document identified by the MCData ID and profile index associated with MCData user (see 3GPP TS 24.484 [12]) is present and is set to a value of "true", then the MCData emergency alert request shall be considered to be an authorised request for an MCData emergency alert. In all other cases, the MCData client shall indicate to the MCData user that the request for sending an MCData emergency alert is unauthorised and shall terminate this procedure.

If the request was authorised, but the MCData user has not indicated the identity of the MCData group to receive the emergency alert, the MCData client shall use, in descending order of preference, one of the following: the value of the <entry> element of the <GroupEmergencyAlert> element of the <Common> element in the MCData user profile, if present; if not, the identity of the MCData group to which the most recent communication or affiliation request was made by the MCData client since last acquiring the MCData service. If an MCData group identity cannot be determined, the MCData client shall indicate the fact to the MCData user and shall terminate this procedure.

The MCData client shall generate a SIP MESSAGE as an out-of-dialog request, in accordance with 3GPP TS 24.229 [5] and IETF RFC 3428 [6], and:

1) shall include the ICSI value "urn:urn-7:3gpp-service.ims.icsi.mcdata" (coded as specified in 3GPP TS 24.229 [5]), in a P-Preferred-Service header field according to IETF RFC 6050 [7] in the SIP MESSAGE request;

2) shall include an Accept-Contact header field with the g.3gpp.icsi-ref media feature tag containing the value of "urn:urn-7:3gpp-service.ims.icsi.mcdata" along with the "require" and "explicit" header field parameters according to IETF RFC 3841 [8];

3) may include a P-Preferred-Identity header field in the SIP MESSAGE request containing a public user identity as specified in 3GPP TS 24.229 [5];

4) shall include an application/vnd.3gpp.mcdata-info+xml MIME body with the <mcdatainfo> element containing the <mcdata-Params> element (see clause D.1) with:

   a) the <mcdata-request-uri> element set to the MCData group identity;

   b) the <alert-ind> element set to a value of "true";

   c) the <mcdata-client-id> element set to the MCData client ID of the originating MCData client; and

   d) if the MCData client is aware of active functional aliases and if an active functional alias is to be included in the SIP MESSAGE request, the <functional-alias-URI> element set to the URI of the used functional alias;

5) shall include an application/vnd.3gpp.mcdata-location-info+xml MIME body with a <Report> element included in the <location-info> root element (see clause D.x);

6) shall include in the <Report> element the specific location information configured for the MCData emergency alert location trigger;

7) shall set the MCData emergency state if not already set;

8) shall set the MCData emergency alert state to "MDEA 2: emergency-alert-confirm-pending";

9) shall set the Request-URI to the public service identity identifying the participating MCData function serving the group identity; and

10) shall send the SIP MESSAGE request according to rules and procedures of 3GPP 24.229 [5];

On receiving a SIP 2xx response to the SIP MESSAGE request, the MCData client shall set the MCData emergency alert state to "MDEA 3: emergency-alert-initiated" and shall give the MCData user an indication of success.

On receiving a SIP 4xx response a SIP 5xx response or a SIP 6xx response to the SIP MESSAGE request, the MCData client shall set the MCData emergency alert state to "MDEA 1: no-alert" and shall indicate the failure to the MCData user.

NOTE: If no response is received after an implementation dependent amount of time or if there is an indication of communication failure, the MCData client can inform the user, and can clear the MCData emergency alert state or can retry sending the emergency alert to the MCData participating server. The MCData emergency state is left unchanged, as the MCData user presumably is in the best position to determine whether or not there still is an emergency situation and can use manual clearing, as necessary.

[TS 24.282 clause 16.2.1.2]

Upon receiving a request from the MCData user to send an MCData emergency alert cancellation, the MCData client shall determine whether or not it is authorised to cancel an emergency alert, as follows:

1) if the MCData emergency cancellation request is for an MCData emergency alert originated by this MCData user, then the request shall be considered authorised if <allow-cancel-emergency-alert> element of the <actions> element of a <rule> element of the <ruleset> element of the MCData user profile document identified by the MCData ID and profile index associated with MCData user (see 3GPP TS 24.484 [12]) is present and is set to a value of "true"; and

2) if the MCData emergency cancellation request is for an MCData emergency alert originated by a different MCData user, then the request shall be considered authorised if <allow-cancel-emergency-alert-any-user> element of the <actions> element of a <rule> element of the <ruleset> element of the MCData user profile document identified by the MCData ID and profile index associated with MCData user (see 3GPP TS 24.484 [12]) is present and is set to a value of "true".

If the MCData emergency cancellation request is not considered authorised, the MCData client shall indicate this fact to the requesting MCData user and shall terminate this procedure.

If the authorised MCData emergency cancellation request is for an MCData emergency alert originated by this MCData user and if there are more than one outstanding emergency alerts from this MCData user and the MCData user has not

indicated which one to cancel, the MCData client shall terminate this procedure after giving an indication of the condition to the MCData user.

The MCData client shall generate a SIP MESSAGE out-of dialog request in accordance with 3GPP TS 24.229 [5] and IETF RFC 3428 [6] and:

1) shall include the ICSI value "urn:urn-7:3gpp-service.ims.icsi.mcdata" (coded as specified in 3GPP TS 24.229 [5]), in a P-Preferred-Service header field according to IETF RFC 6050 [7];

2) shall include an Accept-Contact header field with the g.3gpp.icsi-ref media feature tag containing the value of "urn:urn-7:3gpp-service.ims.icsi.mcdata" along with the "require" and "explicit" header field parameters according to IETF RFC 3841 [8];

3) may include a P-Preferred-Identity header field containing a public user identity as specified in 3GPP TS 24.229 [5];

4) if the MCData emergency alert was originated by this MCData user, shall include an application/vnd.3gpp.mcdata-info+xml MIME body with the <mcdatainfo> element containing the <mcdata-Params> element (see clause D.1) with:

   a) the <mcdata-request-uri> element set to the MCData group identity;

   b) the <alert-ind> element set to a value of "false";

   c) the <mcdata-client-id> element set to the MCData client ID of this MCData client; and

   d) if the MCData client is aware of active functional aliases and if an active functional alias is to be included in the SIP MESSAGE request, the <functional-alias-URI> element set to the URI of the used functional alias;

5) if the MCData emergency alert was originated by a different MCData user, shall include an application/vnd.3gpp.mcdata-info+xml MIME body with the <mcdatainfo> element containing the <mcdata-Params> element (see clause D.1) with:

   a) the <mcdata-request-uri> element set to the MCData group identity;

   b) the <alert-ind> element set to a value of "false";

   c) the <originated-by> element set to the MCData ID of the MCData user who originated the MCData emergency alert; and

   d) if the MCData client is aware of active functional aliases, and an active functional alias is to be included in the SIP MESSAGE request, the <functional-alias-URI> set to the URI of the used functional alias;

6) shall set the Request-URI to the public service identity identifying the participating MCData function serving the group identity;

7) if the generated SIP MESSAGE request does not contain an <originated-by> element in the application/vnd.3gpp.MCData-info+xml MIME body, shall set the MCData emergency alert state to "MDEA 4: emergency-alert-cancel-pending"; and

8) shall send the SIP MESSAGE request according to rules and procedures of 3GPP TS 24.229 [5].

On receipt of a SIP MESSAGE request containing an application/vnd.3gpp.mcdata-info+xml MIME body with an <alert-ind-rcvd> element set to "true" and an <mcdata-client-id> matching the MCData client ID included in the sent SIP MESSAGE request and if the sent SIP MESSAGE request did not contain an <originated-by> element in its application/vnd.3gpp.mcdata-info+xml MIME body, the MCData client shall:

1) if the <alert-ind> element in the application/vnd.3gpp.mcdata-info+xml MIME body of the received SIP MESSAGE request is set to a value of "false":

   a) set the MCData emergency alert state to "MDEA 1: no-alert"; and

   b) clear the MCData emergency state if not already cleared; and

2) if the <alert-ind> element in the application/vnd.3gpp.mcdata-info+xml MIME body of the received SIP MESSAGE request is set to a value of "true" and if the MCData emergency alert state is set to "MDEA 4: emergency-alert-cancel-pending":

   a) set the MCData emergency alert state to "MDEA 1: no-alert".

NOTE: It would appear to be an unusual situation for the initiator of an MCData emergency alert to not be able to clear their own alert. Nevertheless, an MCData user can be configured to be authorised to initiate MCData emergency alerts but not have the authority to clear them. Hence, the case is covered here.

On receiving a SIP 4xx response, SIP 5xx response or SIP 6xx response to the sent SIP MESSAGE emergency alert cancellation request, if the sent SIP MESSAGE request did not contain an <originated-by> element in the application/vnd.3gpp.mcdata-info+xml MIME body and the MCData emergency alert state is set to "MDEA 4: emergency-alert-cancel-pending":

1) if the received SIP 4xx response, SIP 5xx response or SIP 6xx response does not contain an application/vnd.3gpp.mcdata-info+xml MIME body with the <mcdatainfo> element containing the <mcdata-Params> element containing the <alert-ind> element OR if it contains an application/vnd.3gpp.mcdata-info+xml MIME body with the <mcdatainfo> element containing the <mcdata-Params> element with the <alert-ind> element set to a value of "true" (see clause D.1), the MCData client shall set the MCData emergency alert state to "MDEA 3: emergency-alert-initiated".

6.4.1.3 Test description

6.4.1.3.1 Pre-test conditions

Test configuration:

- Single cell configuration according to TS 37.579-1 [2] clause 5.2.2.2.1.

Preamble:

- The UE has performed procedure 'Initial registration' as described in TS 37.579-1 [2] clause 5.4.2.
- UE States at the end of the preamble:
  - The UE is in RRC_IDLE state.
  - The client is registered for MCData.

6.4.1.3.2 Test procedure sequence

Table 6.4.1.3.2-1: Main Behaviour

St	Procedure	Message Sequence		TP	Verdict
		U - S	Message		
1	Make the UE (MCData Client) send an emergency alert. (NOTE 1)	-	-	-	-
2	Check: Does the UE (MCData Client) correctly perform procedure 'MCX SIP MESSAGE Request - Accept CO' as described in TS 37.579-1 [2] Table 5.3.30.3-1 to request an emergency alert providing location information?	-	-	1	P
3	Check: Does the UE (MCData Client) give the MCData User an indication of success?	-	-	1	P
4	Make the UE (MCData Client) cancel the emergency alert. (NOTE 1)	-	-	-	-
5	Check: Does the UE (MCData Client) correctly perform procedure 'MCX SIP MESSAGE Request - Accept CO' as described in TS 37.579-1 [2] Table 5.3.30.3-1 to cancel the emergency alert?	-	-	2	P
NOTE 1: This is expected to be done via a suitable implementation dependent MMI.					

6.4.1.3.3 Specific message contents

Table 6.4.1.3.3-1: SIP MESSAGE from the UE (step 2, Table 6.4.1.3.2-1; step 2, TS 37.579-1 [2] Table 5.3.30.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.7.1-1, condition LOCATION-INFO				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part		**MCData-Info**		
MIME-part-body	MCData-Info as described in Table 6.4.1.3.3-2			
MIME body part		**Location-info**		
MIME-part-body	Location-info as described in Table 6.4.1.3.3-3			

Table 6.4.1.3.3-2: MCData-Info in SIP MESSAGE (Table 6.4.1.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.2.1-3, condition MCD_grp				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
mcdata-info				
mcdata-Params				
request-type	not present			
alert-ind	Encrypted <alert-ind> with mcdataBoolean set to true	Encryption according to NOTE 2 in TS 37.579-1 [2] Table 5.5.3.2.1-3		

Table 6.4.1.3.3-3: Location-Info in SIP MESSAGE (Table 6.4.1.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.4.1-3				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
location-info				
Report				
CurrentLocation				
CurrentCoordinate				
longitude	Encrypted <longitude> with any content	Encryption according to NOTE 1 in TS 37.579-1 [2] Table 5.5.3.4.1-3		
latitude	Encrypted <latitude> with any content	Encryption according to NOTE 1 in TS 37.579-1 [2] Table 5.5.3.4.1-3		

Table 6.4.1.3.3-4: SIP MESSAGE from the SS (step 2, Table 6.4.1.3.2-1; step 4, TS 37.579-1 [2] Table 5.3.30.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.7.2-1, condition ACCEPT-CONTACT-WITH-MEDIA-FEATURE-TAG				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part		**MCData-Info**		
MIME-part-body	MCData-Info as described in Table 6.4.1.3.3-5			

Table 6.4.1.3.3-5: MCData-Info in SIP MESSAGE (Table 6.4.1.3.3-4)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.2.2-3				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
mcdata-info				
mcdata-Params				
mcdata-calling-user-id	not present			
alert-ind	Encrypted <alert-ind> with mcdataBoolean set to true	Encryption according to NOTE 1 in TS 37.579-1 [2] Table 5.5.3.2.2-3		
mcdata-client-id	Encrypted <mcdata-client-id> with mcdataString set to the client-id as received from the UE	Encryption according to NOTE 1 in TS 37.579-1 [2] Table 5.5.3.2.2-3		
anyEXT				
alert-ind-rcvd	mcdataBoolean set to true			

Table 6.4.1.3.3-6: SIP MESSAGE from the UE (step 5, Table 6.4.1.3.2-1; step 2, TS 37.579-1 [2] Table 5.3.30.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.7.1-1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part		**MCData-Info**		
MIME-part-body	MCData-Info as described in Table 6.4.1.3.3-7			

Table 6.4.1.3.3-7: MCData-Info in SIP MESSAGE (Table 6.4.1.3.3-6)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.2.1-3, condition MCD_grp				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
mcdata-info				
mcdata-Params				
request-type	not present			
alert-ind	Encrypted <alert-ind> with mcdataBoolean set to false	Encryption according to NOTE 2 in TS 37.579-1 [2] Table 5.5.3.2.1-3		

Table 6.4.1.3.3-8: SIP MESSAGE from the SS (step 5, Table 6.4.1.3.2-1; step 4, TS 37.579-1 [2] Table 5.3.30.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.7.2-1, condition ACCEPT-CONTACT-WITH-MEDIA-FEATURE-TAG				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part		**MCData-Info**		
MIME-part-body	MCData-Info as described in Table 6.4.1.3.3-9			

Table 6.4.1.3.3-9: MCData-Info in SIP MESSAGE (Table 6.4.1.3.3-8)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.2.2-3				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
mcdata-info				
mcdata-Params				
mcdata-calling-user-id	not present			
alert-ind	Encrypted <alert-ind> with mcdataBoolean set to false	Encryption according to NOTE 1 in TS 37.579-1 [2] Table 5.5.3.2.2-3		
mcdata-client-id	Encrypted <mcdata-client-id> with mcdataString set to the client-id as received from the UE	Encryption according to NOTE 1 in TS 37.579-1 [2] Table 5.5.3.2.2-3		
anyExt				
emergency-ind	mcdataBoolean set to false			
alert-ind-rcvd	mcdataBoolean set to true			

6.4.2 On-network / Emergency Alert / Client Terminated (CT)

6.4.2.1 Test Purpose (TP)

(1)

```
with { UE (MCDATA Client) registered and authorized for MCDATA Service }
ensure that {
  when { the MCDATA Server notifies the UE (MCDATA Client) with an emergency alert with the location
of emergency by sending the UE (MCDATA Client) a SIP MESSAGE }
    then { UE (MCDATA Client) acknowledges the emergency alert by sending a SIP 200 (OK) response
and optionally notifies the user of the emergency alert }
            }
```

(2)

```
with { UE (MCDATA Client) having been previously notified of an emergency alert}
ensure that {
  when { MCDATA Server sends an emergency alert cancellation to the UE (MCDATA Client) }
```

```
    then { UE (MCDATA Client) acknowledges the cancellation of the emergency state by sending a SIP
200 (OK) response and optionally notifies the user of the cancellation }
            }
```

6.4.2.2 Conformance requirements

References: The conformance requirements covered in the current TC are specified in: TS 24.282, clauses 16.2.1.3. The following represents a copy/paste extraction of the requirements relevant to the test purpose; any references within the copy/paste text should be understood within the scope of the core spec they have been copied from. Unless otherwise stated, these are Rel-16 requirements.

[TS 24.282 clause 16.2.1.3]

Upon receipt of a "SIP MESSAGE request for emergency notification", the MCData client:

1) if the received SIP MESSAGE request contains an application/vnd.3gpp.mcdata-info+xml MIME body with the <alert-ind> element set to a value of "true", should display to the MCData user an indication of the MCData emergency alert and associated information, including:

   a) the MCData group identity contained in <mcdata-calling-group-id> element of the application/vnd.3gpp.mcdata-info+xml MIME body;

   b) the originator of the MCData emergency alert contained in the <mcdata-calling-user-id> element of the application/vnd.3gpp.mcdata-info+xml MIME body; and

   c) the mission critical organization of the MCData emergency alert originator contained in the <mc-org> element of the application/vnd.3gpp.mcdata-info+xml MIME body;

NOTE 1: This is the case of the MCData client receiving the notification of another MCData user's emergency alert.

2) if the received SIP MESSAGE request contains an application/vnd.3gpp.mcdata-info+xml MIME body with the <alert-ind> element set to a value of "false":

   a) should display to the MCData user an indication of the MCData emergency alert cancellation and associated information, including:

      i) the MCData group identity contained in the <mcdata-calling-group-id> element of the application/vnd.3gpp.mcdata-info+xml MIME body; and

      ii) the originator of the MCData emergency alert contained in:

         A) if present, the <originated-by> element of the application/vnd.3gpp.mcdata-info+xml MIME body; or

         B) the <mcdata-calling-user-id> element of the application/vnd.3gpp.mcdata-info+xml MIME body;

   b) if the MCData ID contained in the <originated-by> element is the MCData ID of the receiving MCData user, shall set the MCData emergency alert state to "MDEA 1: no-alert"; and

   c) if the received SIP MESSAGE request contains an application/vnd.3gpp.mcdata-info+xml MIME body with the <emergency-ind> element is set to a value of "false":

      i) shall set the MCData emergency group state to "MDEG 1: no-emergency"; and

      ii) shall set the MCData emergency group communication state to "MDEGC 1: emergency-gc-capable";

NOTE 2: This is the case of the MCData client receiving the notification of the cancellation by a third party of an MCData emergency alert. This can be the MCData emergency alert of another MCData user or the MCData emergency alert of the recipient, as determined by the contents of the <originated-by> element. Optionally, notification of the cancellation of the in-progress emergency state of the MCData group can be included.

3) if the received SIP MESSAGE request contains an application/vnd.3gpp.mcdata-info+xml MIME body with the <emergency-ind> element set to a value of "true":

a) should display to the MCData user an indication of the additional emergency MCData user participating in the MCData emergency group communication including the following, if not already displayed as part of step 1):

i) the MCData group identity contained in the <mcdata-calling-group-id> element application/vnd.3gpp.mcdata-info+xml MIME body; and

ii) the <mcdata-calling-user-id> element of the application/vnd.3gpp.mcdata-info+xml MIME body; and

b) shall set the MCData emergency group state to "MDEG 2: in-progress" if not already set to that value;

NOTE 3: This is the case of the MCData client receiving notification of an additional MCData user in an MCData emergency state (i.e., not the MCData user that originally triggered the in-progress emergency state of the group) joining the in-progress emergency group communication. An emergency alert indication, if included, is handled in step 1).

4) if the received SIP MESSAGE request contains an application/vnd.3gpp.mcdata-info+xml MIME body with the <emergency-ind> element set to a value of "false":

a) should display to the MCData user an indication of the cancellation of the in-progress emergency state of the MCData group communication including the following if not already displayed as part of step 2):

i) the MCData group identity contained in the <mcdata-calling-group-id> element of the application/vnd.3gpp.mcdata-info+xml MIME body; and

ii) the <mcdata-calling-user-id> element of the application/vnd.3gpp.mcdata-info+xml MIME body;

b) shall set the MCData emergency group state to "MDEG 1: no-emergency"; and

c) shall set the MCData emergency group communication state to "MDEGC 1: emergency-gc-capable";

NOTE 4: This is the case of the MCData client receiving the notification of the cancellation of the in-progress emergency state of the MCData group. In this case, the receiving MCData client is affiliated with the MCData group but not participating in the session. An emergency alert cancellation, if included, is handled in step 2).

5) shall generate a SIP 200 (OK) response according to rules and procedures of TS 24.229 [5]; and

6) shall send the SIP 200 (OK) response towards the MCData server according to rules and procedures of TS 24.229 [5].

6.4.2.3 Test description

6.4.2.3.1 Pre-test conditions

Same pre-test conditions as for MCPTT test case 6.1.1.16 (TS 37.579-2 [24]) with the following exception(s):

- The term "MCPTT" is replaced with "MCData"

6.4.2.3.2 Test procedure sequence

Same test procedure sequence as for MCPTT test case 6.1.1.16 (TS 37.579-2 [24]) with the following exception(s):

- The term "MCPTT" is replaced with "MCData"

6.4.2.3.3 Specific message contents

Same specific message contents as for MCPTT test case 6.1.1.16 (TS 37.579-2 [24]) with the following exception(s):

- The term "MCPTT" is replaced with "MCData"
- Condition MCDATA is used for all messages.
- In the SIP MESSAGE from the SS at step 1 the <mc-org> element in the MCData-Info is contained in the <anyExt> of the <mcdata-Params>.

6.4.3 On-network / Emergency Alert / Group geographic area

6.4.3.1 Test Purpose (TP)

(1)

```
with { UE (MCData Client) registered and authorized for MCData Service }
ensure that {
  when { the MCData Server notifies the UE (MCData Client) of entry into a group geographic area by
sending the UE (MCData Client) a SIP MESSAGE }
    then { UE (MCData Client) acknowledges the entry into a group geographic area notification by
sending a SIP 200 (OK) response and notifies the user of the entry into the group geographic area }
            }
```

(2)

```
with { UE (MCData Client) having been previously notified of entry into a group geographic area }
ensure that {
  when { MCData User requests to affiliate to the received MCData group }
    then { UE (MCData Client) requests to subscribe to affiliation status changes for the MCData
User by sending the SS a SIP SUBSCRIBE message and starts informing the MCData User of any
affiliation status changes for the MCData User after the subscription is accepted }
            }
```

(3)

```
with { UE (MCData Client) affiliated with a group geographic area  }
ensure that {
  when { the MCData Server notifies the UE (MCData Client) of exit from a group geographic area by
sending the UE (MCData Client) a SIP MESSAGE }
    then { UE (MCData Client) acknowledges the exit from a group geographic area notification by
sending a SIP 200 (OK) response and notifies the user of the exit from the group geographic area }
            }
```

(4)

```
with { UE (MCData Client) having been previously notified of exit from a group geographic area }
ensure that {
  when { MCData User requests to de-affiliate from the received MCData group }
    then { UE (MCData Client) requests to de-affiliate from an MCData group by sending the SS a SIP
PUBLISH message }
            }
```

6.4.3.2 Conformance requirements

References: The conformance requirements covered in the current TC are specified in: 24.282 clause 16.2.1.4. Unless otherwise stated, these are Rel-17 requirements.

[24.282 clause 16.2.1.4]

Upon receipt of a "SIP MESSAGE request for notification of entry into or exit from a group geographic area", the MCData client:

1) shall send a SIP 200 (OK) to the participating MCData function that sent the SIP MESSAGE request; and

2) if the <group-geo-area-ind> element of the application/vnd.3gpp.mcdata-info+xml MIME body is:

   a) set to "true":

      i) may display to the MCData user an indication that a group geographic area has been entered; and

      ii) shall execute the procedure in clause 8.2.2 to affiliate to the group indicated by the participating MCData function; and

   b) set to "false":

      i) may display to the MCData user an indication that a group geographic area has been exited; and

ii) shall execute the procedure in clause 8.2.2 to de-affiliate from the group indicated by the participating MCData function.

6.4.3.3 Test description

6.4.3.3.1 Pre-test conditions

Same pre-test conditions as for MCPTT test case 6.6.3 (TS 37.579-2 [24]) with the following exception(s):

- The term "MCPTT" is replaced with "MCData"

6.4.3.3.2 Test procedure sequence

Same test procedure sequence as for MCPTT test case 6.6.3 (TS 37.579-2 [24]) with the following exception(s):

- The term "MCPTT" is replaced with "MCData"

6.4.3.3.3 Specific message contents

Same specific message contents as for MCPTT test case 6.6.3 (TS 37.579-2 [24]) with the following exception(s):

- The term "MCPTT" is replaced with "MCData"
- Condition MCDATA is used for all messages.
- The <associated-group-id> in the MCData-Info of the SIP MESSAGE from the SS at steps 1 and 9 is not encrypted.

Editor's Note: For MCPTT the type of <associated-group-id> has been changed from "xs:string" to "contentType" which allows the encryption. But for MCData the type of <associated-group-id> is still "xs:string".

6.4.4 On-network / Emergency Alert / Emergency alert area

6.4.4.1 Test Purpose (TP)

(1)

```
with { UE (MCData Client) registered and authorized for MCData Service }
ensure that {
  when { the MCData Server notifies the UE (MCData Client) of entry into a emergency alert area by
sending the UE (MCData Client) a SIP MESSAGE }
    then { UE (MCData Client) acknowledges the entry into a emergency alert area notification by
sending a SIP 200 (OK) response and notifies the user of the entry into the emergency alert area }
            }
```

(2)

```
with { UE (MCData Client) having been previously notified of entry into an emergency alert area }
ensure that {
  when { the MCData User requests to send an emergency alert with the location of emergency }
    then { UE (MCData Client) sends a SIP MESSAGE initiating an emergency alert and reporting
location information }
            }
```

(3)

```
with { UE (MCData Client) in the “MDEA 3: emergency-alert-initiated” state}
ensure that {
  when { the MCData Server notifies the UE (MCData Client) of exit from a emergency alert area by
sending the UE (MCData Client) a SIP MESSAGE }
    then { UE (MCData Client) acknowledges the exit from emergency alert area notification by
sending a SIP 200 (OK) response and notifies the user of the exit from the emergency alert area }
            }
```

6.6.4.2 Conformance requirements

References: The conformance requirements covered in the current TC are specified in: TS 24.282, clauses 16.2.1.1 and 16.2.1.5. Unless otherwise stated, these are Rel-17 requirements.

[TS 24.282, clause 16.2.1.1]

Upon receiving a request from the MCData user to send an MCData emergency alert, the MCData client shall determine whether or not it is authorised to originate an emergency alert, by following the procedures in clause 6.2.8.1.6.

If the MCData emergency alert origination request is considered an unauthorised request for an MCData emergency alert, the MCData client shall indicate to the MCData user that an MCData emergency alert is not allowed on this group and shall terminate this procedure.

If the request was authorised, but the MCData user has not indicated the identity of the MCData group to receive the emergency alert, the MCData client shall use, in descending order of preference, one of the following: the value of the <uri-entry> element of the <entry> element of the <GroupEmergencyAlert> element of the <Common> element in the MCData user profile, if present; if not, the identity of the MCData group to which the most recent communication or affiliation request was made by the MCData client since last acquiring the MCData service. If an MCData group identity cannot be determined, the MCData client shall indicate the fact to the MCData user and shall terminate this procedure.

The MCData client shall generate a SIP MESSAGE as an out-of-dialog request, in accordance with 3GPP TS 24.229 [5] and IETF RFC 3428 [6], and:

1) shall include the ICSI value "urn:urn-7:3gpp-service.ims.icsi.mcdata" (coded as specified in 3GPP TS 24.229 [5]), in a P-Preferred-Service header field according to IETF RFC 6050 [7] in the SIP MESSAGE request;

2) shall include an Accept-Contact header field with the g.3gpp.icsi-ref media feature tag containing the value of "urn:urn-7:3gpp-service.ims.icsi.mcdata" along with the "require" and "explicit" header field parameters according to IETF RFC 3841 [8];

3) may include a P-Preferred-Identity header field in the SIP MESSAGE request containing a public user identity as specified in 3GPP TS 24.229 [5];

4) shall include an application/vnd.3gpp.mcdata-info+xml MIME body with the <mcdatainfo> element containing the <mcdata-Params> element (see clause D.1) with:

   a) the <mcdata-request-uri> element set to the MCData group identity;

   b) the <alert-ind> element set to a value of "true";

   c) the <mcdata-client-id> element set to the MCData client ID of the originating MCData client; and

   d) if the MCData client is aware of active functional aliases and if an active functional alias is to be included in the SIP MESSAGE request, the <functional-alias-URI> element set to the URI of the used functional alias; and

   e) if the MCData user has requested an application priority, the <anyExt> element with the <user-requested-priority> element set to the user provided value;

5) shall include an application/vnd.3gpp.mcdata-location-info+xml MIME body with a <Report> element included in the <location-info> root element (see clause D.4);

6) shall include in the <Report> element the specific location information configured for the MCData emergency alert location trigger;

7) shall set the MCData emergency state if not already set;

8) shall set the MCData emergency alert state to "MDEA 2: emergency-alert-confirm-pending";

9) shall set the Request-URI to the public service identity identifying the participating MCData function serving the group identity; and

10) shall send the SIP MESSAGE request according to rules and procedures of 3GPP 24.229 [5];

On receiving a SIP 2xx response to the SIP MESSAGE request, the MCData client shall set the MCData emergency alert state to "MDEA 3: emergency-alert-initiated" and shall give the MCData user an indication of success.

On receiving a SIP 4xx response a SIP 5xx response or a SIP 6xx response to the SIP MESSAGE request, the MCData client shall set the MCData emergency alert state to "MDEA 1: no-alert" and shall indicate the failure to the MCData user.

NOTE: If no response is received after an implementation dependent amount of time or if there is an indication of communication failure, the MCData client can inform the user, and can clear the MCData emergency alert state or can retry sending the emergency alert to the MCData participating server. The MCData emergency state is left unchanged, as the MCData user presumably is in the best position to determine whether or not there still is an emergency situation and can use manual clearing, as necessary.

[TS 24.282, clause 16.2.1.5]

Upon receipt of a "SIP MESSAGE request for notification of entry into or exit from an emergency alert area", the MCData client:

1) if the received SIP MESSAGE request contains an application/vnd.3gpp.mcdata-info+xml MIME body with the <emergency-alert-area-ind> element of the value:

   a) set to "true":

      i) may display to the MCData user an indication that MCData client has entered a pre-defined emergency alert area; and

      ii) if the MCData user is not in emergency state, shall initiate the emergency alert origination procedure as specified in clause 12.1.1.1; or

   b) set to "false":

      i) may display to the MCData user an indication that MCData client has exited a pre-defined emergency alert area.

NOTE: In this case, the MCData emergency state remains set, as the MCData user is in the best position to determine whether or not they are in a life-threatening condition. The MCData user can clear the MCData emergency state manually, if needed.

2) shall generate a SIP 200 (OK) response according to rules and procedures of 3GPP TS 24.229 [5]; and

3) shall send the SIP 200 (OK) response towards the MCData server according to rules and procedures of 3GPP TS 24.229 [5].

6.4.4.3 Test description

6.4.4.3.1 Pre-test conditions

Same pre-test conditions as for MCPTT test case 6.6.4 (TS 37.579-2 [24]) with the following exception(s):

- The term "MCPTT" is replaced with "MCData"

6.4.4.3.2 Test procedure sequence

Same test procedure sequence as for MCPTT test case 6.6.4 (TS 37.579-2 [24]) with the following exception(s):

- The term "MCPTT" is replaced with "MCData"

6.4.4.3.3 Specific message contents

Same specific message contents as for MCPTT test case 6.6.4 (TS 37.579-2 [24]) with the following exception(s):

- The term "MCPTT" is replaced with "MCData"

- Condition MCDATA is used for all messages.
- In the SIP MESSAGE from the SS at step 3 the <alert-ind-rcvd> element in the MCData-Info is contained in the <anyExt> of the <mcdata-Params>.

6.5 Location

6.5.1 On-network / Location/ Location Information Request

6.5.1.1 Test Purpose (TP)

(1)

with { UE (MCData Client)registered and authorized for MCData service **and** not in an emergency state **and** having received a location information configuration message providing configuration parameters for both NonEmergencyLocationInformation and EmergencyLocationInformation }
ensure that {
  when { UE (MCData Client) receives a location information request before the minimumReportInterval timer has expired }
    then { UE (MCData Client)does not wait for the *minimumReportInterval* timer to expire, and sends "immediately" a SIP MESSAGE containing location information report including information in accordance with the NonEmergencyLocationInformation configuration and the <ReportID> attribute set to the value of the <RequestID> attribute in the received Request, **and** resets the *minimumReportInterval* timer }
            }

(2)

with { UE (MCData Client)registered and authorized for MCData service **and** not in an emergency state **and** having received a location information configuration message providing configuration parameters for both NonEmergencyLocationInformation and EmergencyLocationInformation }
ensure that {
  when { UE (MCData Client) determines that the periodic location reporting trigger has fired **and** the *minimumReportInterval* timer has expired }
    then { UE (MCData Client)sends a SIP MESSAGE containing location information report including information in accordance with the NonEmergencyLocationInformation configuration and the <TriggerID> attribute set to the value of the <TriggerID> attribute in the received location information configuration message, **and** resets the *minimumReportInterval* timer }
            }

(3)

with { UE (MCData Client)registered and authorized for MCData service **and** not in an emergency state **and** having received a location information configuration message }
ensure that {
  when { UE (MCData Client) receives a new location information configuration message and ConfigScope set to 'Full' }
    then { UE (MCData Client) replies with a SIP 200 (OK) message, **and** stores the contents of the <Configuration> elements thereby overriding the previous configuration }
            }

6.5.1.2 Conformance requirements

References: The conformance requirements covered in the current TC are specified in: TS 24.282, clauses 17.3.1, 17.3.2, 17.3.3, 17.3.4.1, 17.3.4.2. Unless otherwise stated, these are Rel-16 requirements.

[TS 24.282 clause 17.3.1]

The MCData client sends a location report when one of the trigger criteria is fulfilled or when it receives a request from the participating MCData function to send a location report. To send the location report the MCData client can use an appropriate SIP message that it needs to send for other reasons, or it can include the location report in a SIP MESSAGE request.

To send a location report, the MCData client includes in the SIP MESSAGE request an application/vnd.3gpp.mcdata-location-info+xml MIME body as specified in clause D.4. The MCData client populates the elements in accordance with its reporting configuration. Further location information may also be included in the P-Access-Network-Info header field.

[TS 24.282 clause 17.3.2]

Upon receiving a SIP MESSAGE request containing:

1) an Accept-Contact header field with the media feature tag g.3gpp.icsi-ref set to the value "urn:urn-7:3gpp-service.ims.icsi.mcdata";

2) a Content-Type header field set to "application/vnd.3gpp.mcdata-location-info+xml"; and

3) an application/vnd.3gpp.mcdata-location-info+xml MIME body with a <Configuration> root element included in the <location-info> root element;

the MCData client:

1) shall store the contents of the <Configuration> elements;

2) shall set the location reporting triggers accordingly; and

3) shall start the minimumReportInterval timer.

[TS 24.282 clause 17.3.3]

Upon receiving a SIP MESSAGE request containing:

1) an Accept-Contact header field with the media feature tag g.3gpp.icsi-ref set to the value "urn:urn-7:3gpp-service.ims.icsi.mcdata";

2) a Content-Type header field set to "application/vnd.3gpp.mcdata-location-info+xml"; and

3) an application/vnd.3gpp.mcdata-location-info+xml MIME body with a <Request> element included in the <location-info> root element;

the MCData client:

1) shall send a location report as specified in subclause 17.3.4; and

2) shall reset the minimumReportInterval timer.

[TS 24.282 clause 17.3.4.1]

If a location reporting trigger fires, the MCData client checks if the minimumReportInterval timer is running. If the timer is running the MCData client waits until the timer expires. When the minimumReportInterval timer expires, the MCData client:

1) shall, if any of the reporting triggers are still true, send a location information report as specified in subclause 17.3.4.2.

If the MCData client receives a location information request as specified in subclause 17.3.3, the MCData client shall send a location report as specified in subclause 17.3.4.2.

[TS 24.282 clause 17.3.4.2]

If the MCData client needs to send a SIP request anyway (i.e. for reasons other than explicit location reporting request or the firing of a configured location trigger), the MCData client:

1) shall include an application/vnd.3gpp.mcdata-location-info+xml MIME body and in the <location-info> root element the MCData client shall include:

   a) a <Report> element and, if the Report was triggered by a location request, include the <ReportID> attribute set to the value of the <RequestID> attribute in the received Request;

   b) <TriggerId> child elements, if triggers have fired, where each element is set to the value of the <Trigger-Id> attribute associated with the triggers that have fired; and

   c) the location reporting elements corresponding to the triggers that have fired, if at least one trigger has fired;

2) shall set the minimumReportInterval timer to the minimumReportInterval time and start the timer; and

3) shall reset all triggers.

If the MCData client does not need to send a SIP request for reasons other than explicit location reporting request or the firing of a configured location trigger, the MCData client shall generate a SIP MESSAGE request in accordance with 3GPP TS 24.229 [5] and IETF RFC 3428 [6]. The MCData client;

1) shall include in the Request-URI, the SIP URI received in the P-Asserted-Identity header field in the received SIP MESSAGE request for location report configuration;

2) shall include a Content-Type header field set to "application/vnd.3gpp.mcdata-location-info+xml";

3) shall include an application/vnd.3gpp.mcdata-location-info+xml MIME body and in the <location-info> root element include:

   a) a <Report> element and if the Report was triggered by a location request include the <ReportID> attribute set to the value of the <RequestID> attribute in the received Request;

   b) <TriggerId> child elements, if triggers have fired, where each element is set to the value of the <Trigger-Id> attribute associated with the triggers that have fired; and

   c) the location reporting elements corresponding to the triggers that have fired, if at least one trigger has fired;

4) shall include an Accept-Contact header field with the media feature tag g.3gpp.mcdata along with parameters "require" and "explicit" in accordance with IETF RFC 3841 [8];

5) shall set the minimumReportInterval timer to the minimumReportInterval time and start the timer;

6) shall reset all triggers; and

7) shall send the SIP MESSAGE request as specified in 3GPP TS 24.229 [5].

6.5.1.3 Test description

6.5.1.3.1 Pre-test conditions

Test configuration:

- Single cell configuration according to TS 37.579-1 [2] clause 5.2.2.2.1.

Preamble:

- The UE has performed procedure 'Initial registration' as described in TS 37.579-1 [2] clause 5.4.2.
- UE States at the end of the preamble:
  - The UE is in RRC_IDLE state.
  - The client is registered for MCData.

6.5.1.3.2 Test procedure sequence

Table 6.5.1.3.2-1: Main Behaviour

St	Procedure	Message Sequence		TP	Verdict
		U - S	Message		
1-3	Steps 1a1-3 of procedure 'MCX SIP MESSAGE CT' as described in TS 37.579-1 [2] Table 5.3.33.3-1 are performed to configure location reporting with *minimumIntervalLength* timer set to 20s and *PeriodicReport* reporting interval set to 15s.	-	-	-	-
4	Start timer t_Wait=10s (NOTE 1)	-	-	-	-
5	Start timer t_PeriodicReport=15s (*PeriodicReport* timer set in step 1).	-	-	-	-
6	The procedure 'MCX communication release' as described in TS 37.579-1 [2] clause 5.4.14 is performed to release the RRC connection.	-	-	-	-
7	t_Wait expires.	-	-	-	-
8-10	Steps 1a1-3 of procedure 'MCX SIP MESSAGE CT' as described in TS 37.579-1 [2] Table 5.3.33.3-1 are performed to request a location report.	-	-	-	-
11-12	Check: Does the UE (MCData Client) correctly perform steps 2-3 of procedure 'MCX SIP MESSAGE CO' as described in TS 37.579-1 [2] Table 5.3.32.3-1 before t_PeriodicReport expires to provide location information for the NonEmergencyLocationInformation configured at step 2?	-	-	1	P
13	Start timer t_MinimumReportInterval=20s	-	-	-	-
14	Stop timer t_PeriodicReport	-	-	-	-
15	The procedure 'MCX communication release' as described in TS 37.579-1 [2] clause 5.4.14 is performed to release the RRC connection.	-	-	-	-
16	t_MinimumReportInterval expires	-	-	-	-
17-19	Check: Does the UE (MCData Client) correctly perform steps 1a1-3 of procedure 'MCX SIP MESSAGE CO' as described in TS 37.579-1 [2] Table 5.3.32.3-1 to provide periodic location information?	-	-	2	P
20-21	Check: Does the UE (MCData Client) correctly perform step 2-3 of procedure 'MCX SIP MESSAGE CT' as described in TS 37.579-1 [2] Table 5.3.33.3-1 to remove the periodic trigger criteria from the location reporting configuration?	-	-	3	P
22-23	Steps 2-3 of procedure 'MCX SIP MESSAGE CT' as described in TS 37.579-1 [2] Table 5.3.33.3-1 are performed to request a location report.	-	-	-	-
24-25	Check: Does the UE (MCData Client) correctly perform steps 2-3 of procedure 'MCX SIP MESSAGE CO' as described in TS 37.579-1 [2] Table 5.3.32.3-1 to provide location information for the configuration done at steps 18-19?	-	-	1	P
26	Check: Does the UE (MCData Client) send any SIP MESSAGE in the next 25s?	-->	SIP MESSAGE	2	F
27	The procedure 'MCX communication release' as described in TS 37.579-1 [2] clause 5.4.14 is performed to release the RRC connection.	-	-	-	-
NOTE 1: The value of 10s is arbitrary chosen.					

6.5.1.3.3 Specific message contents

Table 6.5.1.3.3-1: SIP MESSAGE from the SS (Step 2, Table 6.5.1.3.2-1; step 2, TS 37.579-1 [2], Table 5.3.33.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.7.2-1, condition LOCATION-CONFIG				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part		**MCData-Info**		
MIME-part-body	MCData-info as described in Table 6.5.1.3.3-2			
MIME body part		**Location-info**	TS 24.282 [31] clause D.4	
MIME-part-body	Location-info as described in Table 6.5.1.3.3-3			

Table 6.5.1.3.3-2: MCData-Info in SIP MESSAGE (Table 6.5.1.3.3-1, 6.5.1.3.3-4, 6.5.1.3.3-10, 6.5.1.3.3-12)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.2.2-3				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
mcdatainfo				
mcdata-Params				
mcdata-calling-user-id	not present			

Table 6.5.1.3.3-3: Location-Info in SIP MESSAGE (Table 6.5.1.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.4.2-3				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
location-info				
Configuration				
NonEmergencyLocationInformation				
ServingEcgi	not present			
NeighbouringEcgi	not present			
MbmsSaId	not present			
MbsfnArea	not present			
GeographicalCoordinate	present	Provision of <GeographicalCoordinate> in the report is requested.		
minimumIntervalLength	"20"			
TriggeringCriteria				
PeriodicReport				
extension base	"15"	periodicity of the reports (in seconds)		
TiggerID	"PERIODIC"			

Table 6.5.1.3.3-4: SIP MESSAGE from the SS (Step 9, Table 6.5.1.3.2-1; step 2, TS 37.579-1 [2], Table 5.3.33.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.7.2-1, condition LOCATION-INFO				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part		**MCData-Info**		
MIME-part-body	MCData-info as described in Table 6.5.1.3.3-2			
MIME body part		**Location-info**	TS 24.282 [31] clause D.4	
MIME-part-body	Location-info as described in Table 6.5.1.3.3-5			

Table 6.5.1.3.3-5: Location-Info in SIP MESSAGE (Table 6.5.1.3.3-4)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.4.3-3

Table 6.5.1.3.3-6: SIP MESSAGE from the UE (Step 11, Table 6.5.1.3.2-1; step 2, TS 37.579-1 [2], Table 5.3.32.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.7.1-1, condition LOCATION-INFO				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Request-URI	tsc_MCData_PublicServiceId_PF_A	same URI as provided in the Asserted-Identity header field of the SIP MESSAGE for location reporting configuration		
Message-body				
MIME body part	Not present	**MCData-Info**		
MIME body part		**Location-info**	TS 24.282 [31] clause D.4	
MIME-part-body	Location-info as described in Table 6.5.1.3.3-7			

Table 6.5.1.3.3-7: Location-Info in SIP MESSAGE (Table 6.5.1.3.3-6)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.4.1-3				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
location-info				
Report				
ReportID attribute	"1"	The same as the ID in the request message.		
ReportType attribute	"NonEmergency"			
CurrentLocation		Information corresponding to the location reporting configuration of table 6.5.1.3.3-3		
CurrentServingEcgi	not present			
NeighbouringEcgi	not present			
MbmsSaId	not present			
MbsfnArea	not present			
CurrentCoordinate				
longitude	Encrypted <longitude> with any content	Encryption according to NOTE 1 in TS 37.579-1 [2] Table 5.5.3.4.1-3		
latitude	Encrypted <latitude> with any content	Encryption according to NOTE 1 in TS 37.579-1 [2] Table 5.5.3.4.1-3		

Table 6.5.1.3.3-8: SIP MESSAGE from the UE (Step 18, Table 6.5.1.3.2-1; step 2, TS 37.579-1 [2], Table 5.3.32.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.7.1-1, condition LOCATION-INFO				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Request-URI	tsc_MCData_PublicServiceId_PF_A	same URI as provided in the Asserted-Identity header field of the SIP MESSAGE for location reporting configuration		
Message-body				
MIME body part	Not present	**MCData-Info**		
MIME body part		**Location-info**	TS 24.282 [31] clause D.4	
MIME-part-body	Location-info as described in Table 6.5.1.3.3-9			

Table 6.5.1.3.3-9: Location-Info in SIP MESSAGE (Table 6.5.1.3.3-8)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.4.1-3				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
location-info				
Report				
ReportType attribute	"NonEmergency"			
TriggerID	"PERIODIC"			
CurrentLocation		Information corresponding to the location reporting configuration of table 6.5.1.3.3-3		
CurrentServingEcgi	not present			
NeighbouringEcgi	not present			
MbmsSaId	not present			
MbsfnArea	not present			
CurrentCoordinate				
longitude	Encrypted <longitude> with any content	Encryption according to NOTE 1 in TS 37.579-1 [2] Table 5.5.3.4.1-2		
latitude	Encrypted <latitude> with any content	Encryption according to NOTE 1 in TS 37.579-1 [2] Table 5.5.3.4.1-2		

Table 6.5.1.3.3-10: SIP MESSAGE from the SS (Step 20, Table 6.5.1.3.2-1; step 2, TS 37.579-1 [2], Table 5.3.33.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.7.2-1, condition LOCATION-CONFIG				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part		**MCData-Info**		
MIME-part-body	MCData-info as described in Table 6.5.1.3.3-2			
MIME body part		**Location-info**	TS 24.282 [31] clause D.4	
MIME-part-body	Location-info as described in Table 6.5.1.3.3-11			

Table 6.5.1.3.3-11: Location-Info in SIP MESSAGE (Table 6.5.1.3.3-10)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.4.2-3				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
location-info				
Configuration				
NonEmergencyLocationInformation				
ServingEcgi	present	Provision of <ServingEcgi> in the report is requested.		
NeighbouringEcgi	not present			
MbmsSaId	not present			
MbsfnArea	not present			
GeographicalCoordinate	not present			

Table 6.5.1.3.3-12: SIP MESSAGE from the SS (Step 22, Table 6.5.1.3.2-1; step 2, TS 37.579-1 [2], Table 5.3.33.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.7.2-1, condition LOCATION-INFO				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part		**MCData-Info**		
MIME-part-body	MCData-info as described in Table 6.5.1.3.3-2			
MIME body part		**Location-info**	TS 24.282 [31] clause D.4	
MIME-part-body	Location-info as described in Table 6.5.1.3.3-13			

Table 6.5.1.3.3-13: Location-Info in SIP MESSAGE (Table 6.5.1.3.3-12)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.4.3-3				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
location-info				
Request				
RequestID	"2"	The RequestID that the MCData client shall reference in the Report		

Table 6.5.1.3.3-14: SIP MESSAGE from the UE (Step 24, Table 6.5.1.3.2-1; step 2, TS 37.579-1 [2], Table 5.3.32.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.7.1-1, condition LOCATION-INFO				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Request-URI	tsc_MCData_PublicServiceId_PF_A	same URI as provided in the Asserted-Identity header field of the SIP MESSAGE for location reporting configuration		
Message-body				
MIME body part	Not present	**MCData-Info**		
MIME body part		**Location-info**	TS 24.282 [31] clause D.4	
MIME-part-body	Location-info as described in Table 6.5.1.3.3-15			

Table 6.5.1.3.3-15: Location-Info in SIP MESSAGE (Table 6.5.1.3.3-14)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.4.1-3				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
location-info	present			
Report	present			
ReportID	"2"	The same as the ID in the request message.		
ReportType	"NonEmergency"			
CurrentLocation	present	Information corresponding to the location reporting configuration of table 6.5.1.3.3-8		
CurrentServingEcgi	Encrypted <CurrentServingEcgi> with any content	Encryption according to NOTE 1 in TS 37.579-1 [2] Table 5.5.3.4.1-2		
NeighbouringEcgi	not present			
MbmsSaId	not present			
MbsfnArea	not present			
CurrentCoordinate	not present			

6.5.2 On-network / Location / Report triggering

6.5.2.1 Test Purpose (TP)

(1)

with { UE (MCData Client)registered and authorized for MCData service **and** not in an emergency state **and** having received a location information configuration message providing configuration parameters for *NonEmergencyLocationInformation* requesting indication of ESGIs and location information, and, TriggeringCriteria set to “CellChange”, and a none zero *minimumIntervalLength* timer }
ensure that {
  when { UE moves to a different cell }
    then { UE (MCData Client) sends location report obeying the set in the location configuration parameters for *NonEmergencyLocationInformation* including waiting for the expiry of *minimumReportInterval* timer for before reporting }
            }

(2)

with { UE (MCData Client)registered and authorized for MCData service **and** not in an emergency state **and** having received a location information configuration message providing configuration parameters for *NonEmergencyLocationInformation* requesting indication of ESGIs and location information, and TriggeringCriteria including “PlmnChange” and “PeriodicReport”, and a none zero *minimumIntervalLength* timer }
ensure that {
  when { UE moves to a cell belonging to a different PLMN however allowed for communication }
    then { UE (MCData Client) sends location report obeying the set in the location configuration parameters for *NonEmergencyLocationInformation and* resets all triggers }
            }

(3)

with { UE (MCData Client)registered and authorized for MCData service **and** not in an emergency state **and** having received a location information configuration message providing configuration parameters for *NonEmergencyLocationInformation* requesting indication of ESGIs and location information, and TriggeringCriteria including “PlmnChange” and “PeriodicReport”, and a none zero *minimumIntervalLength* timer }
ensure that {
  when { when the PeriodicReport trigger fires }
    then { UE (MCData Client) sends location report obeying the set in the location configuration parameters for *NonEmergencyLocationInformation* }
            }

6.5.2.2 Conformance requirements

References: The conformance requirements covered in the current TC are specified in: TS 24.282, clauses 17.3.1, 17.3.2, 17.3.3, 17.3.4.1, 17.3.4.2. Unless otherwise stated, these are Rel-16 requirements.

[TS 24.282 clause 17.3.1]

The MCData client sends a location report when one of the trigger criteria is fulfilled or when it receives a request from the participating MCData function to send a location report. To send the location report the MCData client can use an appropriate SIP message that it needs to send for other reasons, or it can include the location report in a SIP MESSAGE request.

To send a location report, the MCData client includes in the SIP MESSAGE request an application/vnd.3gpp.mcdata-location-info+xml MIME body as specified in clause D.4. The MCData client populates the elements in accordance with its reporting configuration. Further location information may also be included in the P-Access-Network-Info header field.

[TS 24.282 clause 17.3.2]

Upon receiving a SIP MESSAGE request containing:

1) an Accept-Contact header field with the media feature tag g.3gpp.icsi-ref set to the value "urn:urn-7:3gpp-service.ims.icsi.mcdata";

2) a Content-Type header field set to "application/vnd.3gpp.mcdata-location-info+xml"; and

3) an application/vnd.3gpp.mcdata-location-info+xml MIME body with a <Configuration> root element included in the <location-info> root element;

the MCData client:

1) shall store the contents of the <Configuration> elements;

2) shall set the location reporting triggers accordingly; and

3) shall start the minimumReportInterval timer.

[TS 24.282 clause 17.3.3]

Upon receiving a SIP MESSAGE request containing:

1) an Accept-Contact header field with the media feature tag g.3gpp.icsi-ref set to the value "urn:urn-7:3gpp-service.ims.icsi.mcdata";

2) a Content-Type header field set to "application/vnd.3gpp.mcdata-location-info+xml"; and

3) an application/vnd.3gpp.mcdata-location-info+xml MIME body with a <Request> element included in the <location-info> root element;

the MCData client:

1) shall send a location report as specified in subclause 17.3.4; and

2) shall reset the minimumReportInterval timer.

[TS 24.282 clause 17.3.4.1]

If a location reporting trigger fires, the MCData client checks if the minimumReportInterval timer is running. If the timer is running the MCData client waits until the timer expires. When the minimumReportInterval timer expires, the MCData client:

1) shall, if any of the reporting triggers are still true, send a location information report as specified in subclause 17.3.4.2.

If the MCData client receives a location information request as specified in subclause 17.3.3, the MCData client shall send a location report as specified in subclause 17.3.4.2.

[TS 24.282 clause 17.3.4.2]

If the MCData client needs to send a SIP request anyway (i.e. for reasons other than explicit location reporting request or the firing of a configured location trigger), the MCData client:

1) shall include an application/vnd.3gpp.mcdata-location-info+xml MIME body and in the <location-info> root element the MCData client shall include:

   a) a <Report> element and, if the Report was triggered by a location request, include the <ReportID> attribute set to the value of the <RequestID> attribute in the received Request;

   b) <TriggerId> child elements, if triggers have fired, where each element is set to the value of the <Trigger-Id> attribute associated with the triggers that have fired; and

   c) the location reporting elements corresponding to the triggers that have fired, if at least one trigger has fired;

2) shall set the minimumReportInterval timer to the minimumReportInterval time and start the timer; and

3) shall reset all triggers.

If the MCData client does not need to send a SIP request for reasons other than explicit location reporting request or the firing of a configured location trigger, the MCData client shall generate a SIP MESSAGE request in accordance with 3GPP TS 24.229 [5] and IETF RFC 3428 [6]. The MCData client;

1) shall include in the Request-URI, the SIP URI received in the P-Asserted-Identity header field in the received SIP MESSAGE request for location report configuration;

2) shall include a Content-Type header field set to "application/vnd.3gpp.mcdata-location-info+xml";

3) shall include an application/vnd.3gpp.mcdata-location-info+xml MIME body and in the <location-info> root element include:

   a) a <Report> element and if the Report was triggered by a location request include the <ReportID> attribute set to the value of the <RequestID> attribute in the received Request;

   b) <TriggerId> child elements, if triggers have fired, where each element is set to the value of the <Trigger-Id> attribute associated with the triggers that have fired; and

   c) the location reporting elements corresponding to the triggers that have fired, if at least one trigger has fired;

4) shall include an Accept-Contact header field with the media feature tag g.3gpp.mcdata along with parameters "require" and "explicit" in accordance with IETF RFC 3841 [8];

5) shall set the minimumReportInterval timer to the minimumReportInterval time and start the timer;

6) shall reset all triggers; and

7) shall send the SIP MESSAGE request as specified in 3GPP TS 24.229 [5].

6.5.2.3 Test description

6.5.2.3.1 Pre-test conditions

Test configuration:

- Multi-cell configuration according to TS 37.579-1 [2] clause 5.2.2.2.2 with 3 cells according to the initial conditions of procedure 'MCX communication in E-UTRA / Change of cells' as described in TS 37.579-1 [2] clause 5.4.9.

- GNSS simulator to simulate a location.

Preamble:

- The UE has performed procedure 'Initial registration' as described in TS 37.579-1 [2] clause 5.4.2.

- The GNSS simulator is configured to simulate a location in the centre of Geographical area #1 to provide a location, as defined in TS 36.508 [24] Table 4.11.2-2, step 1 of scenario #4.
- UE States at the end of the preamble:
  - The UE is in RRC_IDLE state.
  - The client is registered for MCData.

6.5.2.3.2 Test procedure sequence

Table 6.5.2.3.2-1: Main Behaviour

St	Procedure	Message Sequence		TP	Verdict
		U - S	Message		
1	Trigger the UE to reset UTC time and location. NOTE: The UTC time and location reset may be performed by MMI or AT command (+CUTCR).	-	-	-	-
2-4	Steps 1a1-3 of procedure 'MCX SIP MESSAGE CT' as described in TS 37.579-1 [2] Table 5.3.33.3-1 are performed to configure location reporting with the non-emergency *minimumIntervalLength* timer set to 25s. NOTE: The SS sends a location reporting configuration containing the cell change trigger criteria and the minimum report interval. Provision of serving and neighbouring cells ECGIs is requested in addition to the Location Information.	-	-	-	-
5	SS starts timer=25 sec (the non-emergency *minimumReportInterval* interval length defined in the SIP MESSAGE sent in step 3 as *minimumIntervalLength*).	-	-	-	-
6	The procedure 'MCX communication release' as described in TS 37.579-1 [2] clause 5.4.14 is performed to release the RRC connection.	-	-	-	-
7	Trigger the GNSS simulator to start step 2 of Scenario #4 to simulate the UE moving to location #7 inside Geographical area #1 as defined in TS 36.508 [24] Table 4.11.2-2.	-	-	-	-
8	Wait 10 sec to allow the simulated location to move approximately 100 m from the original location to location #7.	-	-	-	-
9	Make the SS simulate cell change (same PLMN) as described in TS 37.579-1 [2], clause 5.4.9 'MCX communication in E-UTRA / Change of cells' steps 1 and 2. The test sequence below shows only the MCData relevant messages exchanged. NOTE: Cell 2 and Cell 1 will be active.	-	-	-	-
10	Timer=25 sec expires.	-	-	-	-
11-13	Check: Does the UE (MCData Client) correctly perform steps 1a1-3 of procedure 'MCX SIP MESSAGE CO' as described in TS 37.579-1 [2] Table 5.3.32.3-1 to send a SIP MESSAGE containing the Cell change trigger identification along with the location information report, the current location coordinates as specified in step 3, and the ECGIs of Cells 1 and 2?	-	-	1	P
14-15	Steps 2-3 of procedure 'MCX SIP MESSAGE CT' as described in TS 37.579-1 [2] Table 5.3.33.3-1 are performed to configure location reporting. NOTE: The SS sends a location reporting configuration containing the PLMN change trigger criteria, and periodic trigger criteria with *PeriodicReport* reporting interval set to 60 sec and the minimum report interval. Provision of cells ECGIs is requested in addition to the Location Information. The *minimumIntervalLength* time is set to 10 sec.	-	-	-	-

16	SS starts timer=60 sec (the *PeriodicReport* interval defined in the SIP MESSAGE sent in step 14). NOTE: The value of 60 sec has been chosen arbitrary however if the behaviour described in steps 18-23 takes longer than 60 sec then this value needs to be adjusted.	-	-	-	-
17	The procedure 'MCX communication release' as described in TS 37.579-1 [2] clause 5.4.14 is performed to release the RRC connection.	-	-	-	-
18	Trigger the GNSS simulator to start step 4 of Scenario #4 to simulate the UE moving to location #8 inside Geographical area #1 as defined in TS 36.508 [24] Table 4.11.2-2.	-	-	-	-
19	Wait 10 sec to allow the simulated location to move approximately 100 m from the original location to location #8.	-	-	-	-
20	Make the SS simulate PLMN change as described in TS 37.579-1 [2], clause 5.4.9 'MCX communication in E-UTRA / Change of cells' steps 3 and 4. The test sequence below shows only the MCData relevant messages exchanged. NOTE: Cell 4 only will be active.	-	-	-	-
21-23	Check: Does the UE (MCData Client) correctly perform steps 1a1-3 of procedure 'MCX SIP MESSAGE CO' as described in TS 37.579-1 [2] Table 5.3.32.3-1 to send a SIP MESSAGE containing the PLMN change trigger identification along with the location information report, the current location coordinates as specified in step 14, and the ECGI of cell 4 (the only cell being active at this moment of time)? NOTE: The *minimumReportInterval* time (set in step 14 as *minimumIntervalLength = 10 sec.*) has already expired latest at the end of step 18.	-	-	2	P
24	SS cancels Timer=60 sec.	-	-	-	-
25	SS starts Timer=60 sec.	-	-	-	-
26	The procedure 'MCX communication release' as described in TS 37.579-1 [2] clause 5.4.14 is performed to release the RRC connection.	-	-	-	-
27	Timer=60 sec expires	-	-	-	-
28	Check: Does the UE (MCData Client) correctly perform the procedure 'MCX SIP MESSAGE CO' as described in TS 37.579-1 [2] Table 5.3.32.3-1 to send a SIP MESSAGE containing the periodic trigger identification along with location information report after the non-emergency minimum interval length expired? NOTE: The *minimumReportInterval* time (set in step 14 as *minimumIntervalLength = 10 sec.*) has already expired before step 27.	-	-	3	P

6.5.2.3.3 Specific message contents

Table 6.5.2.3.3-1: SIP MESSAGE from the SS (Step 3, Table 6.5.2.3.2-1; step 2, TS 37.579-1 [2], Table 5.3.33.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.7.2-1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body	MIME body not including MCPTT-Info and not including MCPTT-Affiliation-Command	not including any MIME body part with Content-Type being "application/vnd.3gpp.mcptt-info+xml" or "application/vnd.3gpp.mcptt-affiliation-command+xml"		
MIME body part		**MCData-Info**		
MIME-part-body	MCData-info as described in Table 6.5.2.3.3-2			
MIME body part		**Location-info**	TS 24.282 [31] clause D.4	
MIME-part-body	Location-info as described in Table 6.5.2.3.3-3			

Table 6.5.2.3.3-2: MCData-Info in SIP MESSAGE (Table 6.5.2.3.3-1, Table 6.5.2.3.3-6)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.2.2-3				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
mcdatainfo				
mcdata-Params				
mcdata-calling-user-id	not present			

Table 6.5.2.3.3-3: Location-Info in SIP MESSAGE (Table 6.5.2.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.4.2-3				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
location-info				
Configuration				
NonEmergencyLocationInformation				
MbmsSaId	not present	Provision of information in the report is not requested.		
MbsfnArea	not present	Provision of information in the report is not requested.		
minimumIntervalLength	"25"	the value in seconds		
EmergencyLocationInformation"				
MbmsSaId	not present	Provision of information in the report is not requested.		
MbsfnArea	not present	Provision of information in the report is not requested.		
minimumIntervalLength	"30"	the value in seconds		
TriggeringCriteria				
CellChange				
AnyCellChange				
TriggerID	"CELLCHANGE"			

Table 6.5.2.3.3-4: SIP MESSAGE from the UE (Step 12, Table 6.5.2.3.2-1; step 2, TS 37.579-1 [2], Table 5.3.32.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.7.1-1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part	Not present	**MCData-Info**		
MIME body part		**Location-info**	TS 24.282 [31] clause D.4	
MIME-part-body	Location-info as described in Table 6.5.2.3.3-5			

Table 6.5.2.3.3-5: Location-Info in SIP MESSAGE (Table 6.5.2.3.3-4)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.4.1-3				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
location-info				
Report				
ReportType	"NonEmergency"			
TriggerID	"CELLCHANGE"			
CurrentLocation				
CurrentServingEcgi	Encrypted - The E-UTRAN Cell Global Identification (ECGI) of Cell 2	Encryption according to NOTE 2 in TS 37.579-1 [2] Table 5.5.3.4.1-3		
NeighbouringEcgi	Encrypted - The ECGI of Cell 1	Encryption according to NOTE 2 in TS 37.579-1 [2] Table 5.5.3.4.1-3		
CurrentCoordinate		The location simulated by the GNSS simulator at the time of transmission of the message.		
longitude	Encrypted - The longitude value as specified for location number #7 defined in TS 36.508 [24] Table 4.11.2-3 +/- 0.00016 degrees.	Encryption according to NOTE 1 in TS 37.579-1 [2] Table 5.5.3.4.1-3		
latitude	Encrypted - The latitude value as specified for location number #7 defined in TS 36.508 [24] Table 4.11.2-3 +/- 0.00013 degrees.	Encryption according to NOTE 1 in TS 37.579-1 [2] Table 5.5.3.4.1-3		

Table 6.5.2.3.3-6: SIP MESSAGE from the SS (Step 14, Table 6.5.2.3.2-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.7.2-1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part		**MCData-Info**		
MIME-part-body	MCData-info as described in Table 6.5.2.3.3-2			
MIME body part		**Location-info**	TS 24.282 [31] clause D.4	
MIME-part-body	Location-info as described in Table 6.5.2.3.3-7			

Table 6.5.2.3.3-7: Location-Info in SIP MESSAGE (Table 6.5.2.3.3-6)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.4.2-3				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
location-info				
Configuration				
NonEmergencyLocationInformation				
MbmsSaId	not present	Provision of information in the report is not requested.		
MbsfnArea	not present	Provision of information in the report is not requested.		
EmergencyLocationInformation"				
MbmsSaId	not present	Provision of information in the report is not requested.		
MbsfnArea	not present	Provision of information in the report is not requested.		
minimumIntervalLength	"70"	the value in seconds		
TriggeringCriteria				
PLMNChange				
AnyPLMNChange				
TriggerID	"ANY PLMN"			
PeriodicReport				
extension base	"60"	the value in seconds of the time which determines the periodic provision of the report		
TiggerID	"PERIODIC"			

Table 6.5.2.3.3-8: SIP MESSAGE from the UE (Step 22, Table 6.5.2.3.2-1; step 2, TS 37.579-1 [2], Table 5.3.32.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.7.1-1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part	Not present	**MCData-Info**		
MIME body part		**Location-info**	TS 24.282 [31] clause D.4	
MIME-part-body	Location-info as described in Table 6.5.2.3.3-9			

Table 6.5.2.3.3-9: Location-Info in SIP MESSAGE (Table 6.5.2.3.3-8)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.4.1-3				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
location-info				
Report				
ReportType	"NonEmergency"			
TriggerID	"ANY PLMN"			
CurrentLocation				
CurrentServingEcgi	Encrypted - The ECGI of Cell 4	Encryption according to NOTE 2 in TS 37.579-1 [2] Table 5.5.3.4.1-3		
NeighbouringEcgi	not present	Only Cell 4 is active at this moment of time (see TS 37.579-1 [2], clause 5.4.9)		
CurrentCoordinate		The location simulated by the GNSS simulator at the time of transmission of the message.		
longitude	Encrypted - The longitude value as specified for location number #8 defined in TS 36.508 [24] Table 4.11.2-3 +/- 0.00016 degrees.	Encryption according to NOTE 1 in TS 37.579-1 [2] Table 5.5.3.4.1-3		
latitude	Encrypted - The latitude value as specified for location number #8 defined in TS 36.508 [24] Table 4.11.2-3 +/- 0.00013 degrees.	Encryption according to NOTE 1 in TS 37.579-1 [2] Table 5.5.3.4.1-3		

Table 6.5.2.3.3-10: SIP MESSAGE from the UE (Step 28, Table 6.5.2.3.2-1; step 2, TS 37.579-1 [2], Table 5.3.32.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.7.1-1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part	Not present	**MCData-Info**		
MIME body part		**Location-info**	TS 24.282 [31] clause D.4	
MIME-part-body	Location-info as described in Table 6.5.2.3.3-11			

Table 6.5.2.3.3-11: Location-Info in SIP MESSAGE (Table 6.5.2.3.3-10)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.4.1-3				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
location-info				
Report				
ReportType	"NonEmergency"			
TriggerID	"PERIODIC"			
CurrentLocation				
CurrentServingEcgi	Encrypted - The ECGI of Cell 4	Encryption according to NOTE 2 in TS 37.579-1 [2] Table 5.5.3.4.1-3		
NeighbouringEcgi	not present	Only Cell 4 is active at this moment of time (see TS 37.579-1 [2], clause 5.4.9)		
CurrentCoordinate		The location simulated by the GNSS simulator at the time of transmission of the message.		
longitude	Encrypted - The longitude value as specified for location number #8 defined in TS 36.508 [24] Table 4.11.2-3 +/- 0.00016 degrees.	Encryption according to NOTE 1 in TS 37.579-1 [2] Table 5.5.3.4.1-3		
latitude	Encrypted - The latitude value as specified for location number #8 defined in TS 36.508 [24] Table 4.11.2-3 +/- 0.00013 degrees.	Encryption according to NOTE 1 in TS 37.579-1 [2] Table 5.5.3.4.1-3		

6.6 MBMS

6.6.1 On-network / MBMS / MBMS Bearer Announcement / MBMS Bearer Listening Status / Transition to MBMS from Unicast

6.6.1.1 Test Purpose (TP)

(1)

```
with { UE (MCData Client) having established a group SDS session }
ensure that {
  when { the UE (MCData Client) receives an MBMS bearer announcements via SIP MESSAGE messages }
    then { UE (MCData Client) responds by sending a SIP 200 (OK) to the SIP MESSAGE message and the
UE (MCData Client) sends an MBMS listening status message via a SIP MESSAGE message }
            }
```

(2)

```
with { UE (MCData Client) having established an MCPTT On-demand Pre-arranged Group Call with
Automatic Commencement Mode }
ensure that {
  when { the UE (MCData Client) receives MBMS subchannel control messages (Map Group TO Bearer,
Unmap Group To Bearer) }
    then { UE (MCData Client) responds by sending an MBMS listening status message via SIP MESSAGE
message }
            }
```

(3)

```
with { UE (MCData Client) having established a group SDS session }
ensure that {
  when { the UE (MCData Client) receives an explicit MuSiK download message }
    then { UE (MCData Client) sends a 200 OK response to accept the key and associates the key with
the group}
            }
```

(4)

```
with { UE (MCDATA Client) being in a group SDS session initiated by the SS (MCDATA Server) }
ensure that {
  when { UE (MCDATA Client) receives a SIP BYE message }
    then { UE (MCDATA Client) responds by sending a SIP 200 (OK) message }
            }
```

6.6.1.2 Conformance requirements

References: The conformance requirements covered in the current TC are specified in: TS 24.282, clauses 19.3.2, 19.3.3.1, 19.3.3.2, 19.3.4, TS 24.582, clauses 6.5.2.2, 6.5.2.3,. Unless otherwise stated, these are Rel-16 requirements.

[TS 24.282, clause 19.3.2]

The MCData client associates each received application/sdp MIME body and each received security key with a general purpose MBMS subchannel announced in the same MBMS Bearer Announcement message. When receiving a Map Group To Bearer message, the MCData client interprets its content (e.g. the m= line number) in the context of the application/sdp MIME body associated with the general purpose MBMS subchannel on which the Map Group To Bearer message was received.

When the MCData client receives a SIP MESSAGE request containing:

1) a P-Asserted-Service header field containing the "urn:urn-7:3gpp-service.ims.icsi.mcdata"; and

2) an application/vnd.3gpp.mcdata-mbms-usage-info+xml MIME body containing one or more an <announcement> element(s);

then the MCData client for each <announcement> element in the application/vnd.3gpp.mcdata-mbms-usage-info+xml MIME body:

1) if the <mbms-service-areas> element is present:

   a) if an <announcement> element with the same value of the <TMGI> element is already stored:

      i) shall replace the old <announcement> element with the <announcement> element received in the application/vnd.3gpp.mcdata-mbms-usage-info+xml MIME body;

   b) if there is no <announcement> element with the same value of the <TMGI> element stored:

      i) shall store the received <announcement> element;

   c) shall associate the received announcement with the received application/sdp MIME body;

   d) shall associate the received announcement with the received <GPMS> element;

   e) shall store the MBMS public service identity of the participating MCData function received in the P-Asserted-Identity header field and associate the MBMS public service identity with the new <announcement> element;

   f) if a "a=key-mgmt" media-level attribute with the "mikey" key management and protocol identifier and a MIKEY-SAKKE I_MESSAGE is included for the general purpose MBMS subchannel defined in the "m=application" media line in the application/sdp MIME body in the received SIP MESSAGE request,

      i) shall extract the initiator URI from the initiator field (IDRi) of the I_MESSAGE as described in 3GPP TS 33.180 [26]. If the initiator URI deviates from the public service identity of the participating MCData function serving the MCData user, shall reject the SIP MESSAGE request with a SIP 488 (Not Acceptable Here) response as specified in IETF RFC 4567 [45], and include warning text set to "136

authentication of the MIKEY-SAKE I_MESSAGE failed" in a Warning header field as specified in subclause 4.9 and shall not continue with the rest of the steps;

ii) shall convert the initiator URI to a UID as described in 3GPP TS 33.180 [26];

iii) shall use the UID to validate the signature of the MIKEY-SAKKE I_MESSAGE as described in 3GPP TS 33.180 [26];

iv) if authentication verification of the MIKEY-SAKKE I_MESSAGE fails, shall reject the SIP MESSAGE request with a SIP 488 (Not Acceptable Here) response as specified in IETF RFC 4567 [45], and include warning text set to "136 authentication of the MIKEY-SAKE I_MESSAGE failed" in a Warning header field as specified in subclause 4.4 and shall not continue with the rest of the steps;

v) shall extract and decrypt the encapsulated MSCCK using the participating MCData function's (KMS provisioned) UID key as described in 3GPP TS 33.180 [26]; and

vi) shall extract the MSCCK-ID, from the payload as specified in 3GPP TS 33.180 [26];

NOTE: With the MSCCK successfully shared between the participating MCData function and the served UEs, the participating MCData function is able to securely send MBMS subchannel control messages to the MCData clients.

g) shall listen to the general purpose MBMS subchannel defined in the "m=application" media line in the application/sdp MIME body in the received SIP MESSAGE request when entering an MBMS service area where the announced MBMS bearer is available; and

h) shall check the condition for sending a listening status report as specified in the subclause 19.3.3; and

2) if no <mbms-service-areas> element is present:

a) shall discard a previously stored <announcement> element identified by the value of the <TMGI>;

b) shall remove the association with the stored application/sdp MIME body and stop listening to the general purpose MBMS subchannel;

c) if no more <announcement> elements associated with the stored application/sdp MIME body are stored in the MCData client, shall remove the stored application/sdp MIME body; and

d) check the condition for sending a listening status report as specified in the subclause 19.3.3.

[TS 24.282, clause 19.3.3.1]

If one of the following conditions is fulfilled:

1) if the MCData client:

a) receives a Map Group To Bearer message over the general purpose MBMS channel;

b) participates in a group session identified by the Map Group To Bearer message; and

c) the status "listening" is not already reported; or

2) if the MCData client:

a) receives an announcement as described in subclause 19.3.2;

b) enters an MBMS service area where a general purpose MBMS is available; and

c) experiences good MBMS bearer radio condition;

then the MCData client shall report that the MCData client is listening to the MBMS bearer as specified in subclause 19.3.3.2.

If one of the following conditions is fulfilled:

1) if the MCData client:

a) receives an MBMS bearer announcement as described in the subclause 19.3.2;

b) the MBMS bearer announcement contains a cancellation of an <announcement> element identified by the same TGMI value as received in a Map Group To Bearer message in an ongoing conversation; and

c) the status "not-listening" is not already reported;

2) if the MCData client:

a) receives an MBMS bearer announcement as described in the subclause 19.3.2;

b) the MBMS bearer announcement contains a cancellation of an <announcement> element;

c) does not participate in an ongoing conversation;

d) the MCData client has reported the "listening" status due to the availability of the general purpose MBMS subchannel in the <announcement> element; and

e) the status "not-listening" is not already reported; or

3. if the MCData client:

a) suffers from bad MBMS bearer radio condition,

then the MCData client shall report that the MCData client is not listening to the MBMS subchannels as specified in subclause 19.3.3.2.

If all the following conditions are fulfilled:

1) the MCData client has reported "listening" as the most recent listening status relative to an MBMS bearer;

2) the MCData client is notified that the MBMS bearer is about to be suspended by the RAN; and

3) the MCData client has not received a MBMS bearer announcement containing a <report-suspension> element set to "false",

then the MCData client shall report that the MBMS bearer is about to be suspended, as specified in subclause 19.3.3.2.

If all the following conditions are fulfilled:

1) the MCData client has reported "listening" as the most recent listening status relative to an MBMS bearer;

2) the MCData client has reported that the MBMS bearer is about to be suspended, but the suspension of the bearer has not been detected yet by the MCData client;

3) the MCData client is notified that the MBMS bearer is no longer to be suspended by the RAN; and

4) the MCData client has not received a MBMS bearer announcement containing a <report-suspension> element set to "false",

then the MCData client shall report that the MBMS bearer is no longer to be suspended, as specified in subclause 19.3.3.2.

[TS 24.282, clause 19.3.3.2]

When the MCData client wants to report the MBMS bearer listening status, the MCData client:

NOTE 1: The application/vnd.3gpp.mcdata-mbms-usage-info+xml can contain both the listening status "listening" and "not listening" at the same time.

1) shall generate a SIP MESSAGE request in accordance with 3GPP TS 24.229 [5] and IETF RFC 3428 [6] and

a) shall include in the Request-URI the MBMS public service identity of the participating MCData function received in the P-Asserted-Identity header field of the announcement message;

b) shall include an Accept-Contact header field with the g.3gpp.icsi-ref media-feature tag with the value of "urn:urn-7:3gpp-service.ims.icsi.mcdata" along with parameters "require" and "explicit" according to IETF RFC 3841 [8];

c) should include a public user identity in the P-Preferred-Identity header field as specified in 3GPP TS 24.229 [5];

d) shall include a P-Preferred-Service header field with the value "urn:urn-7:3gpp-service.ims.icsi.mcdata";

e) shall include an application/vnd.3gpp.mcdata-mbms-usage-info+xml MIME body with the <version> element set to "1";

f) if the MCData client is listening to the MBMS bearer, the application/vnd.3gpp.mcdata-mbms-usage-info+xml MIME body:

i) shall include an <mbms-listening-status> element set to "listening";

ii) if the intention is to report that the MCData client is listening to the MBMS subchannel for an ongoing conversation in a session (e.g. as the response to the Map Group To Bearer message), shall include the MCData session identity of the ongoing conversation in a <session-id> element;

iii) shall include one or more <TGMI> elements for which the listening status applies; and

iv) if the intention is to report that the MCData client is listening to the general purpose MBMS subchannel, shall include the <general-purpose> element set to "true";

g) if the MCData client is not listening, the application/vnd.3gpp.mcdata-mbms-usage-info+xml MIME body:

i) shall include an <mbms-listening-status> element set to "not-listening";

iii) shall include one or more <TGMI> elements for which the listening status applies;

iii) if the intention is to report that the MCData client is no longer listening to the MBMS subchannel in an ongoing session (e.g. as the response to Unmap Group to Bearer message), shall include the MCData session identity in a <session-id> element; and

iv) if the intention is to report that the MCData client is no longer listening to general purpose MBMS subchannel, shall include the <general-purpose> element set to "false"; and

NOTE 2: If the MCData client reports that the MCData client is no longer listening to the general purpose MBMS subchannel, it is implicitly understood that the MCData client no longer listens to any MBMS subchannel in ongoing conversations that the MCData client previously reported status "listening".

h) shall include an application/vnd.3gpp.mcdata-info+xml MIME body with the <mcdata-request-uri> set to the MCData ID; and

2) shall send the SIP MESSAGE request according to 3GPP TS 24.229 [5].

When the MCData client meets all the conditions specified in subclause 19.3.3.1 for reporting a change in an MBMS bearer suspension status, the MCData client:

1) shall generate a SIP MESSAGE request in accordance with 3GPP TS 24.229 [5] and IETF RFC 3428 [6] and

a) shall include in the Request-URI the MBMS public service identity of the participating MCData function received in the P-Asserted-Identity header field of the announcement message;

b) shall include an Accept-Contact header field with the g.3gpp.icsi-ref media-feature tag with the value of "urn:urn-7:3gpp-service.ims.icsi.mcdata" along with parameters "require" and "explicit" according to IETF RFC 3841 [8];

c) should include a public user identity in the P-Preferred-Identity header field as specified in 3GPP TS 24.229 [5];

d) shall include a P-Preferred-Service header field with the value "urn:urn-7:3gpp-service.ims.icsi.mcdata";

e) shall include an application/vnd.3gpp.mcdata-mbms-usage-info+xml MIME body with the <version> element set to "1";

f) if at least one MBMS bearer is about to be suspended, the application/vnd.3gpp.mcdata-mbms-usage-info+xml MIME body:

i) shall include an <mbms-suspension-status> element set to "suspending";

ii) shall set the <number-of-reported-bearers> element to the total number of the included <suspended-TMGI> elements and <other-TMGI> elements;

iii) shall include <suspended-TMGI> element(s) set to the TMGI value for each of the MTCHs on the same MCH corresponding to the MBMS bearers about to be suspended; and

iv) may include <other-TMGI> elements, if available, corresponding to the TMGI values for other MTCHs on the same MCH as the MBMS bearers to be suspended

NOTE 3: To report the suspension of MTCHs on different MCHs, the MCData client sends a separate message for each of the involved MCHs.

g) if the MBMS bearer is no longer about to be suspended, the application/vnd.3gpp.mcdata-mbms-usage-info+xml MIME body:

i) shall include an <mbms-suspension-status> element set to "not-suspending";

ii) shall set the <number-of-reported-bearers> element to the number of included <suspended-TMGI> elements; and

iii) shall include a <suspended-TMGI> element set to the corresponding TMGI value for each of the MTCHs of the MBMS bearers that are no longer about to be suspended; and

h) shall include an application/vnd.3gpp.mcdata-info+xml MIME body with the <mcdata-request-uri> set to the MCData ID; and

2) shall send the SIP MESSAGE request according to 3GPP TS 24.229 [5].

NOTE 4: The MCData client reports in separate messages the MBMS bearers that are about to be suspended and the MBMS bearers that are no longer about to be suspended.

[TS 24.282, clause 19.3.4]

When the MCData client receives a SIP MESSAGE request containing:

1) a P-Asserted-Service header field containing the "urn:urn-7:3gpp-service.ims.icsi.mcdata"; and

2) with one of the following:

a) an application/vnd.3gpp.mcdata-mbms-usage-info+xml MIME body containing an <mbms-explicitMuSiK-download> element with at least one <group> subelement; or

b) an application/vnd.3gpp.mcdata-mbms-usage-info+xml MIME body containing an <mbms-defaultMuSiK-download> element with zero or more <group> subelements;

the MCData client shall:

1) if the received message contains an <mbms-explicitMuSiK-download> element, set the impacted groups to be those groups identified by the <group> subelements;

2) if the received message contains an <mbms-defaultMuSiK-download> element without <group> subelements, set the impacted groups to be all groups not associated with currently valid explicit MuSiK downloads; and

3) if the received message contains an <mbms-defaultMuSiK-download> element with <group> subelements, first dissociate those groups identified by the <group> subelements from currently valid associations with explicit MuSiK downloads and then set the impacted groups to be all groups not associated with currently valid explicit MuSiK downloads.

If the key identifier within the CSB-ID of the MIKEY payload is a MuSiK-ID (4 most-significant bits have the value '6'), the MCData client:

1) shall process the MIKEY payload according to 3GPP TS 33.180 [26], as follows:

a) if the initiator field (IDRi) has type 'URI' (identity hiding is not used), the client:

i) shall extract the initiator URI from the initiator field (IDRi) of the I_MESSAGE as described in 3GPP TS 33.180 [26]. If the initiator URI deviates from the public service identity of the participating MCData function serving the MCData client, shall reject the SIP MESSAGE request by sending a SIP 488 (Not Acceptable Here) response as specified in IETF RFC 4567 [45], and including warning text set to "136 authentication of the MIKEY-SAKKE I_MESSAGE failed" in a Warning header field as specified in subclause 4.9 and shall not continue with the rest of the steps; and

ii) shall convert the initiator URI to a UID as described in 3GPP TS 33.180 [26];

b) otherwise, if the initiator field (IDRi) has type 'UID' (identity hiding in use), the client:

i) shall convert the public service identity of participating MCData function serving the MCData user to a UID as described in 3GPP TS 33.180 [26]; and

ii) shall compare the generated UID with the UID in the initiator field (IDRi) of the I_MESSAGE as described in 3GPP TS 33.180 [26]. If the two initiator UIDs deviate from each other, shall reject the SIP MESSAGE request by sending a SIP 488 (Not Acceptable Here) response as specified in IETF RFC 4567 [45], and including warning text set to "136 authentication of the MIKEY-SAKKE I_MESSAGE failed" in a Warning header field as specified in subclause 4.4 and shall not continue with the rest of the steps;

c) otherwise, shall reject the SIP MESSAGE request by sending a SIP 488 (Not Acceptable Here) response as specified in IETF RFC 4567 [45], and including warning text set to "136 authentication of the MIKEY-SAKKE I_MESSAGE failed" in a Warning header field as specified in subclause 4.4 and shall not continue with the rest of the steps;

d) shall use the UID to validate the signature of the I_MESSAGE as described in 3GPP TS 33.180 [26];

e) if authentication verification of the I_MESSAGE fails or the I_MESSAGE does not contain a Status attribute, shall reject the SIP MESSAGE request by sending SIP 488 (Not Acceptable Here) response as specified in IETF RFC 4567 [45], and including warning text set to "136 authentication of the MIKEY-SAKKE I_MESSAGE failed" in a Warning header field as specified in subclause 4.4 and shall not continue with the rest of the steps; and

f) shall examine the Status attribute and shall either mark the associated security functions as "not in use" or shall extract and store the encapsulated MuSiK and the corresponding MuSiK-ID from the payload as specified in 3GPP TS 33.180 [26]; and

2) for each of the impacted groups, shall either associate the status 'security not in use' or shall add/replace in the storage associated with the group the MuSiK-ID and the MuSiK, for use (decrypted) as security key.

NOTE: It is expected that the MCData client is capable of storing a different MuSiK for each MCData group of interest.

The MCData client shall respond with SIP 200 OK only if it finds the message syntactically correct and recognizes it as a valid and error-free MuSiK download (default or explicit) message.

[TS 24.582 clause 6.5.2.2]

While MBMS delivery is expected, the terminating MCData client shall monitor the general purpose MBMS subchannel.

When receiving a Map Group To Bearer message over the general purpose MBMS subchannel, the MBMS interface in the MCData client:

1) shall associate the TMGI in the TMGI field, the MBMS subchannel for media with the MCData group identity in the MCData Group ID field; and

2) shall start or continue the procedure described in subclause 6.5.2.3.

When receiving the Unmap Group To Bearer message referring to the current communication over a MBMS subchannel, the MBMS interface in the MCData client:

1) shall remove the association between the TMGI, the MBMS subchannel for media in the group session identified by the MCData Group ID field, if such an association exists; and

2) shall cease monitoring the associated MBMS bearer and subchannel for media and, if the SDS session is still ongoing, shall resume or continue SDS delivery via media plane over unicast.

[TS 24.582 clause 6.5.2.3]

The terminating MCData client:

1. While MBMS delivery is expected, the terminating MCData client shall monitor the MBMS bearer and subchannel indicated by the Map Group To Bearer message; and
2. For each received (S)RTP media packet, until a SIP BYE is received or until an implementation dependent timeout occurs:
   a. Decapsulate the payload out of the (S)RTP packet and, if SRTP rather than RTP is used (see IETF RFC 3711 [17]), decrypt and validate the payload; and
   b. Process the payload as a received MSRP SEND message according to subclause 6.1.2.3.1, in the context of the media flow formed by previously received MSRP SEND messages, whether delivered via unicast or via MBMS.

6.6.1.3 Test description

6.6.1.3.1 Pre-test conditions

Test configuration:

- Single cell configuration according to TS 37.579-1 [2] clause 5.2.2.2.1.

Preamble:

- The UE has performed procedure 'Initial registration' as described in TS 37.579-1 [2] clause 5.4.2.
- UE States at the end of the preamble:
  - The UE is in RRC_IDLE state.
  - The client is registered for MCData.
- A pre-activated MBMS bearer exists

6.6.1.3.2 Test procedure sequence

Table 6.6.1.3.2-1: Main Behaviour

St	Procedure	Message Sequence		TP	Verdict
		U - S	Message		
1	The UE (MCData client) correctly perform procedure '**CT MCData Call Establishment**' as described in TS 37.579-1 [2] Table 5.3C.3.3-1?	-	-	-	-
2	The UE (MCData client) correctly perform procedure '**CT MSRP message transfer**' as described in TS 37.579-1 [2] Table 5.3C.5.3-1 **to receive an SDS message with disposition request "DELIVERY"**?	-	-	-	-
3	The UE (MCData client) correctly perform procedure '**CO MSRP message transfer**' as described in TS 37.579-1 [2] Table 5.3C.4.3-1 **to send a disposition notification of "DELIVERED"**?	-	-	-	-
4	The UE (MCData client) provide the contents of the Payload IE to the user? (NOTE 1)	-	-	-	-
5	The SS pre-activates an MBMS bearer and sends a SIP MESSAGE containing an MBMS bearer announcement message to announce the availability of an MBMS bearer. NOTE: The related E-UTRA/EPC actions are described in TS 37.579-1 [2], clause 5.4.12 'MCX communication over MBMS'. The test sequence below shows only the MCPTT relevant messages exchanged.	<--	SIP MESSAGE	-	-
6	Check: Does the UE (MCData Client) respond with a SIP 200 (OK)?	-->	SIP 200 (OK)	1	P
7	Check: Does the UE (MCData client) send a SIP MESSAGE containing an MBMS Bearer listening status report?	-->	SIP MESSAGE	1	P
8	The SS responds with a SIP 200 (OK).	<--	SIP 200 (OK)	-	-
9	Check: Does the UE (MCData client) correctly perform procedure '**CO MSRP message transfer**' as described in TS 37.579-1 [2] Table 5.3C.4.3-1 **to send an SDS message with disposition request "DELIVERY"**?				
10	Check: Does the UE (MCData client) correctly perform procedure '**CT MSRP message transfer**' as described in TS 37.579-1 [2] Table 5.3C.5.3-1 **to receive the disposition notification** for the SDS message sent at step 7?				
11	Check: Does the UE (MCData client) provide the disposition notification to the user? (NOTE 1)				
12	The SS decides that a MBMS subchannel shall be used for the conversation and sends a Map Group To Bearer message over the general purpose MBMS subchannel. NOTE: The related E-UTRA/EPC actions are described in TS 37.579-1 [2], clause 5.4.12 'MCX communication over MBMS'. The test sequence below shows only the MCPTT relevant messages exchanged.	<--	Map Group To Bearer	-	-
13	Check: Does the UE (MCData Client) respond to the Map Group To Bearer message by sending a SIP MESSAGE containing an MBMS Bearer listening status report?	-->	SIP MESSAGE	2	P
14	The SS responds with a SIP 200 (OK).	<--	SIP 200 (OK)	-	-

15	The UE (MCData client) correctly perform procedure '**CT MSRP message transfer**' as described in TS 37.579-1 [2] Table 5.3C.5.3-1 **to receive an SDS message with disposition request "DELIVERY"** with the MSRP SEND message sent over the MBMS subchannel?	-	-	-	-
16	The UE (MCData client) correctly perform procedure '**CO MSRP message transfer**' as described in TS 37.579-1 [2] Table 5.3C.4.3-1 **to send a disposition notification of "DELIVERED"**?	-	-	-	-
17	The UE (MCData client) provide the contents of the Payload IE to the user? (NOTE 1)	-	-	-	-
18	The SS sends a SIP MESSAGE containing a MuSiK download message to set the explicit MuSiK key to be used for the floor control encryption over the MBMS subchannel.	<--	SIP MESSAGE	-	-
19	Check: Does the UE (MCData Client) respond with a SIP 200 (OK)?	-->	SIP 200 (OK)	3	P
20	The SS ends the conversation on the MBMS subchannel and sends an Unmap Group to Bearer message on the MBMS subchannel. NOTE: The related E-UTRA/EPC actions are described in TS 37.579-1 [2], clause 5.4.12 'MCX communication over MBMS'. The test sequence below shows only the MCPTT relevant messages exchanged.	<--	Unmap Group to Bearer	-	-
21	Check: Does the UE (MCData Client) respond to the Unmap Group To Bearer message with a SIP MESSAGE containing an MBMS bearer listening status report?	-->	SIP MESSAGE	2	P
22	The SS responds with a SIP 200 (OK).	<--	SIP 200 (OK)	-	-
23	The SS cancels the MBMS bearer announcement and sends a SIP MESSAGE.	<--	SIP MESSAGE	-	-
24	Check: Does the UE (MCData Client) respond with a SIP 200 (OK)?	-->	SIP 200 (OK)	1	P
25	Check: Does the UE (MCData Client) send a SIP MESSAGE containing an MBMS Bearer listening status report?	-->	SIP MESSAGE	1	P
26	The SS responds with a SIP 200 (OK).	<--	SIP 200 (OK)	-	-
27	Check: Does the UE (MCData client) correctly perform procedure '**CT MCData call release**' as described in TS 37.579-1 [2] Table 5.3C.7.3-1? (NOTE 2)	-	-	4	P
28	The procedure 'MCX communication release' as described in TS 37.579-1 [2] clause 5.4.14 is performed to release the RRC connection.	-	-	-	-
NOTE 1: This is expected to be done via a suitable implementation dependent MMI. NOTE 2: The procedure does not release the RRC connection.					

6.6.1.3.3 Specific message contents

Table 6.6.1.3.3-1: SIP INVITE from the SS (step 1, Table 6.6.1.3.2-1; step 2, TS 37.579-1 [2] Table 5.3C.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.5.2-1, condition MCDATA_SDS				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part		**SDP message**		
MIME-part-body	SDP message as described in Table 6.6.1.3.3-2			
MIME body part		**MCData-Info**		
MIME-part-body	MCData-Info as described in Table 6.6.1.3.3-3			

Table 6.6.1.3.3-2: SDP for SIP INVITE (Table 6.6.1.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.1.2-3, condition MCDATA_SDS, SDP_OFFER, SDS_SESSION

Table 6.6.1.3.3-3: MCData-Info (Table 6.6.1.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.2.1-3, condition MCD_grp				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
mcdata-info				
mcdata-Params				
request-type	"group-sds-session"			

Table 6.6.1.3.3-4: SIP 200 (OK) from the UE (step 1, Table 6.6.1.3.2-1; step 4, TS 37.579-1 [2] Table 5.3C.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.17.1.1-1, condition INVITE-RSP, MCDATA_SDS				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Content-Type				
value	"application/sdp"			
Message-body				
SDP message	As described in Table 6.6.1.3.3-5			

Table 6.6.1.3.3-5: SDP for SIP 200 (OK) (Table 6.6.1.3.3-4)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.1.1-3, condition MCDATA_SDS, SDP_ANSWER, SDS_SESSION

Table 6.6.1.3.3-6: MSRP SEND from the SS (steps 2, 15, Table 6.6.1.3.2-1; step 1, TS 37.579-1 [2] Table 5.3C.5.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.12.1.2-1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Content-Type				
media-type	"multipart/mixed"			
data	Message as specified in table 6.6.1.3.3-7			

Table 6.6.1.3.3-7: MIME Message (steps 2, 15, Table 6.6.1.3.2-1; step 1, TS 37.579-1 [2] Table 5.3C.5.3-1)

Derivation Path: RFC 2046 [38]				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
MIME body part		**MCData Data signalling message**		
MIME-part-headers				
Content-Type	"application/vnd.3gpp.mcdata-signalling"			
MIME-part-body	MCData Protected Payload Message containing SDS SIGNALLING PAYLOAD as described in table 6.6.1.3.3-8			
MIME body part		**MCData Data message**		
MIME-part-headers				
Content-Type	"application/vnd.3gpp.mcdata-payload"			
MIME-part-body	MCData Protected Payload Message containing DATA PAYLOAD as described in Table 6.6.1.3.3-9			

Table 6.6.1.3.3-8: SDS SIGNALLING PAYLOAD (Table 6.6.1.3.3-7)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.2-1, condition DELIVERED

Table 6.6.1.3.3-9: Data Payload (Table 6.6.1.3.3-7)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.9.1-2

Table 6.6.1.3.3-10: MSRP SEND from the UE (steps 3, 16, Table 6.6.1.3.2-1; step 1, TS 37.579-1 [2] Table 5.3C.4.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.12.1.1-1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Content-Type				
media-type	"application/vnd.3gpp.mcdata-signalling"			
data	MCData Protected Payload Message containing SDS NOTIFICATION as specified in table 6.6.1.3.3-11			

Table 6.6.1.3.3-11: SDS NOTIFICATION (Table 6.6.1.3.3-10)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.3-1, condition DELIVERED

Table 6.6.1.3.3-12: SIP MESSAGE (step 5, Table 6.6.1.3.2-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.7.2-1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
P-Asserted-Identity				
addr-spec	px_MBMS_Service_ID	The MBMS public service identity of the participating MCData function		
Message-body	MIME body not including MCPTT-Affiliation-Command	not including any MIME body part with Content-Type "application/vnd.3gpp.mcptt-affiliation-command+xml"		
MIME body part		**SDP message**		
MIME-part-headers				
Content-Type	"application/sdp"			
Content-Disposition	"render"			
MIME-part-body	SDP message as described in Table 6.6.1.3.3-13			
MIME body part		**MCData MBMS usage info**		
MIME-part-headers				
Content-Type	"application/vnd.3gpp.mcdata-mbms-usage-info+xml"			
MIME-part-body	MCData-MBMS-Usage-Info as described in Table 6.6.1.3.3-14			
MIME body part		**MCData-Info**		
MIME-part-headers				
Content-Type	"application/vnd.3gpp.mcdata-info+xml"			
MIME-part-body	MCData-Info as described in Table 6.6.1.3.3-15			

Table 6.6.1.3.3-13: SDP in SIP MESSAGE (Table 6.6.1.3.3-12)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.1.2-3				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Media descriptions				
media description		m= line media = message		
media	"message"			
port	"9"			
proto	"RTP/AVP"			
fmt	"*"			
Connection Data		c= line		
nettype	"IN"			
addrtype	"IP4" or “IP6” depending on IP address			
connection-address	"0.0.0.0" (IPv4) or domain name within “.invalid” DNS top level domain (IPv6)			
media description		m= line media = application		
media	"application"			
port	"9"			
proto	"udp"			
fmt	"MCDATA"			
Connection Data		c= line		
nettype	"IN"			
addrtype	"IP4" or “IP6” depending on IP address			
connection-address	"0.0.0.0" (IPv4) or domain name within “.invalid” DNS top level domain (IPv6)			
media description		m= line media = application		
media	"application"			
port	port number assigned by the SS			
proto	"udp"			
fmt	"MCDATA"			
Connection Data		c= line		
nettype	"IN"			
addrtype	"IP4"			
connection-address	multicast IP assigned by the SS			
media attribute		a= line attribute = key-mgmt		
key-mgmt			TS 24.282 [31] clause 19.2.2.2	
mikey	MIKEY-SAKKE I_MESSAGE as specified in TS 37.579-1 [2], Table 5.5.9.1-4.	MSCCK distribution as specified in TS 33.180 [30] Annex H	RFC 4567 [41]	

Table 6.6.1.3.3-14: MCData-MBMS-Usage-Info in SIP MESSAGE (Table 6.6.1.3.3-12)

Derivation Path: TS 24.282 [31], Clause D.5				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
mcdata-mbms-usage-info				
mbms-listening-status	not present			
mbms-suspension-status	not present			
announcement				
TMGI				
MBMS Service ID	"0F0F0F"	The selected value is randomly chosen - a 6 digit hexadecimal number between 000000 and FFFFFF (see TS 23.003 [X] clause 15.2. The coding of the MBMS Service ID is the responsibility of each administration		
MCC	The same value as for PLMN1 specified in Table 5.5.8.1-x	Mobile Country Code		
MNC	The same value as for PLMN1 specified in Table 5.5.8.1-x	Mobile Network Code		
QCI	"70"	Mission Critical Data user plane		
frequency	not present			
mbms-service-areas	"0"	The selected value is randomly chosen. The value 0 has a special meaning; it shall denote the whole PLMN as the MBMS Service Area		
GPMS	"2"	The number of the "m=application" media line in the application/sdp MIME		
report-suspension	“True”	True indicates that the MCData client is instructed to notify the MCData server when it becomes aware of an intended change in the suspension status of a listened MBMS bearer. False indicates that the MCData client is instructed not to notify the MCData server if it becomes aware of an intended change in the suspension status of a listened MBMS bearer.		
version	"1"			

Table 6.6.1.3.3-15: MCData-Info (Table 6.6.1.3.3-12)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.2.2-3				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
mcdata-info				
mcdata-Params				
mcdata-calling-user-id	not present			

Table 6.6.1.3.3-16: SIP MESSAGE (steps 7, 13, Table 6.6.1.3.2-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.7.1-1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Request-Line				
Request-URI	The value received in the P-Asserted-Identity header field of the announcement message (px_MBMS_Service_ID)			
Message-body	MIME body not including MCPTT-Affiliation-Command	not including any MIME body part with Content-Type "application/vnd.3gpp. mcptt-affiliation-command+xml"		
MIME body part		**MCData MBMS usage info**		
MIME-part-headers				
Content-Type	"application/vnd.3gpp. mcdata-mbms-usage-info "			
MIME-part-body	MCData-MBMS-Usage-Info as described in Table 6.6.1.3.3-17			
MIME body part		**MCData-Info**		
MIME-part-headers				
Content-Type	"application/vnd.3gpp. mcdata-info+xml"			
MIME-part-body	MCData-Info as described in Table 6.6.1.3.3-18			

Table 6.6.1.3.3-17: MCData-MBMS-Usage-Info in SIP MESSAGE (Table 6.6.1.3.3-16)

Derivation Path: TS 24.282 [31], Clause D.5				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
mcdata-mbms-usage-info				
mbms-listening-status				
mbms-listening-status	“listening”			
session-id	not present			
general-purpose	"true"			
TMGI				
MBMS Service ID	"0F0F0F"			
MCC	The same value as for PLMN1 specified in Table 5.5.8.1-x			
MNC	The same value as for PLMN1 specified in Table 5.5.8.1-x			
mbms-suspension-status	not present			
announcement	not present			
version	"1"			

Table 6.6.1.3.3-18: MCData-Info (Table 6.6.1.3.3-16)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.2.1-3				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
mcdata-info				
mcdata-Params				
mcdata-request-uri	px_MCData_ID_User_A	The MCData ID of the MCData user	TS 24.282 [31], Clause 19.3.3.2	

Table 6.6.1.3.3-19: MSRP SEND from the UE (step 9, Table 6.6.1.3.2-1; step 1, TS 37.579-1 [2] Table 5.3C.4.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.12.1.1-1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Content-Type				
media-type	"multipart/mixed"			
data	Message or chunk of message as specified in table 6.6.1.3.3-20			

Table 6.6.1.3.3-20: MIME Message (step 9, Table 6.6.1.3.2-1; step 3, TS 37.579-1 [2] Table 5.3C.4.3-1)

Derivation Path: RFC 2046 [38]				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
MIME body part		**MCData Data signalling message**		
MIME-part-headers				
Content-Type	"application/vnd.3gpp.mcdata-signalling"			
MIME-part-body	MCData Protected Payload Message containing SDS SIGNALLING PAYLOAD as described in table 6.6.1.3.3-21			
MIME body part		**MCData Data message**		
MIME-part-headers				
Content-Type	"application/vnd.3gpp.mcdata-payload"			
MIME-part-body	MCData Protected Payload Message containing DATA PAYLOAD as described in Table 6.6.1.3.3-22			

Table 6.6.1.3.3-21: SDS SIGNALLING PAYLOAD (Table 6.6.1.3.3-20)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.1-1, condition DELIVERED

Table 6.6.1.3.3-22: Data Payload (Table 6.6.1.3.3-20)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.9.1-1

Table 6.6.1.3.3-23: MSRP SEND from the SS (step 10, Table 6.6.1.3.2-1; step 1, TS 37.579-1 [2] Table 5.3C.5.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.12.1.2-1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Content-Type				
media-type	"application/vnd.3gpp.mcdata-signalling"			
data	MCData Protected Payload Message containing SDS NOTIFICATION as specified in table 6.6.1.3.3-24			

Table 6.6.1.3.3-24: SDS NOTIFICATION (Table 6.6.1.3.3-23)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.4-1, condition DELIVERED

Table 6.6.1.3.3-25: SIP MESSAGE (step 18, Table 6.6.1.3.2-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.7.2-1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part		**MCData MBMS usage info**		
MIME-part-headers				
Content-Type	"application/vnd.3gpp.mcdata-mbms-usage-info+xml"			
MIME-part-body	MCData-MBMS-Usage-Info as described in Table 6.6.1.3.3-26			
MIME body part		**MIKEY message**		
MIME-part-headers				
Content-Type	"application/mikey"			
MIME-part-body	As described in TS 37.579-1 [2], Table 5.5.9.1-5.	MIKEY message containing the MuSiK		

Table 6.6.1.3.3-26: MCData-MBMS-Usage-Info in SIP MESSAGE (Table 6.6.1.3.3-25)

Derivation Path: TS 24.282 [31], Clause D.5				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
mcdata-mbms-usage-info				
mbms-listening-status	not present			
mbms-suspension-status	not present			
announcement	not present			
version	"1"			
anyExt				
mbms-defaultMuSiK-download				
group	px_MCPTT_Group_A_ID			
mbms-explicitMuSiK-download	not present			

Table 6.6.1.3.3-27: SIP MESSAGE (steps 21, 25, Table 6.6.1.3.2-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.7.1-1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Request-Line				
Request-URI	The value received in the P-Asserted-Identity header field of the announcement message (px_MBMS_Service_ID)			
Message-body	MIME body not including MCPTT-Affiliation-Command	not including any MIME body part with Content-Type "application/vnd.3gpp. mcptt-affiliation-command+xml"		
MIME body part		**MCData MBMS usage info**		
MIME-part-headers				
Content-Type	"application/vnd.3gpp. mcdata-mbms-usage-info "			
MIME-part-body	MCData-MBMS-Usage-Info as described in Table 6.6.1.3.3-28			
MIME body part		**MCData-Info**		
MIME-part-headers				
Content-Type	"application/vnd.3gpp. mcdata-info+xml"			
MIME-part-body	MCData-Info as described in Table 6.6.1.3.3-18			

Table 6.6.1.3.3-28: MCData-MBMS-Usage-Info in SIP MESSAGE (Table 6.6.1.3.3-27)

Derivation Path: TS 24.282 [31], Clause D.5				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
mcdata-mbms-usage-info				
mbms-listening-status				
mbms-listening-status	“not listening”			
session-id	px_sesson_A_ID			
general-purpose	not present			
TMGI				
MBMS Service ID	"0F0F0F"			
MCC	The same value as for PLMN1 specified in Table 5.5.8.1-x			
MNC	The same value as for PLMN1 specified in Table 5.5.8.1-x			
mbms-suspension-status	not present			
announcement	not present			
version	"1"			

Table 6.6.1.3.3-29: SIP MESSAGE (step 23, Table 6.6.1.3.2-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.7.2-1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
P-Asserted-Identity				
addr-spec	px_MBMS_Service_ID	The MBMS public service identity of the participating MCData function		
Message-body	MIME body not including MCPTT-Affiliation-Command	not including any MIME body part with Content-Type "application/vnd.3gpp.mcptt-affiliation-command+xml"		
MIME body part		**MCData MBMS usage info**		
MIME-part-headers				
Content-Type	"application/vnd.3gpp.mcdata-mbms-usage-info+xml"			
MIME-part-body	MCData-MBMS-Usage-Info as described in Table 6.6.1.3.3-30			
MIME body part		**MCData-Info**		
MIME-part-headers				
Content-Type	"application/vnd.3gpp.mcdata-info+xml"			
MIME-part-body	MCData-Info as described in Table 6.6.1.3.3-15			

Table 6.6.1.3.3-30: MCData-MBMS-Usage-Info in SIP MESSAGE (Table 6.6.1.3.3-29)

Derivation Path: TS 24.282 [31], Clause D.5				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
mcdata-mbms-usage-info				
mbms-listening-status	not present			
mbms-suspension-status	not present			
announcement				
TMGI				
MBMS Service ID	"0F0F0F"	The selected value is randomly chosen - a 6 digit hexadecimal number between 000000 and FFFFFF (see TS 23.003 [X] clause 15.2. The coding of the MBMS Service ID is the responsibility of each administration		
MCC	The same value as for PLMN1 specified in Table 5.5.8.1-x	Mobile Country Code		
MNC	The same value as for PLMN1 specified in Table 5.5.8.1-x	Mobile Network Code		
QCI	"70"	Mission Critical Data user plane		
frequency	not present			
mbms-service-areas	not present			
GPMS	not present			
report-suspension	“True”	True indicates that the MCData client is instructed to notify the MCData server when it becomes aware of an intended change in the suspension status of a listened MBMS bearer. False indicates that the MCData client is instructed not to notify the MCData server if it becomes aware of an intended change in the suspension status of a listened MBMS bearer.		
version	"1"			

6.7 IP Connectivity

6.7.1 On-network / IP Connectivity / Client Originated (CO)

6.7.1.1 Test Purpose (TP)

(1)

```
with { UE (MCDATA Client) registered and authorised for MCDATA Service }
ensure that {
  when { the MCDATA User requests to initiate a IP Connectivity session }
    then { UE (MCDATA Client) sends a request to establish a IP Connectivity session via a SIP
INVITE message and then responds to the SIP 200 (OK) message with a SIP ACK message and sends a
payload using GRE-in-UDP Encapsulation }
            }
```

(2)

```
with { UE (MCDATA Client) having established a IP Connectivity session }
ensure that {
  when { the MCDATA User requests to release the IP Connectivity session }
    then { UE (MCDATA Client) sends a SIP BYE message }
           }
```

6.7.1.2 Conformance requirements

References: The conformance requirements covered in the current TC are specified in: TS 24.282, clause 20.2.1 and 20.2.0a, TS 24.582, clause 13.1.2. Unless otherwise stated, these are Rel-17 requirements.

[TS 24.282, clause 20.2.1]

When a MCData client receives the request by a user or user application to establish a IP Connectivity session with another MCData client the MCData client shall generate a SIP INVITE request in accordance with 3GPP TS 24.229 [5] with the clarifications given below. The MCData ID or the functional alias of the target MCData client may be explicitly included in the request from the user or user application. If the target MCData ID or functional alias is not included in the request, the MCData client may implicitly determine the target MCData ID by using the target IP Information included in the request to find a match in the One-to-One communication list of the MCData user profile document as specified in 3GPP TS 24.484 [12]. If the MCData ID of the target MCData client is determined implicitly by the target IP Information included in the request, the client searches in leaves below /<x>/<x>/Common/OnetoOne/UserList/<x>/Entry/IPInformation/<x>/Entry/ for a match in the IP Information. The MCData ID is given by matching the user entry.

The MCData client:

1) shall include the g.3gpp.mcdata.ipconn media feature tag and the g.3gpp.icsi-ref media feature tag with the value of "urn:urn-7:3gpp-service.ims.icsi.mcdata.ipconn " in the Contact header field of the SIP INVITE request according to IETF RFC 3840 [16];

2) shall include an Accept-Contact header field containing the g.3gpp.mcdata.ipconn media feature tag along with the "require" and "explicit" header field parameters according to IETF RFC 3841 [8];

3) shall include an Accept-Contact header field with the g.3gpp.icsi-ref media feature tag containing the value of "urn:urn-7:3gpp-service.ims.icsi.mcdata.ipconn" along with the "require" and "explicit" header field parameters according to IETF RFC 3841 [8];

4) shall include the ICSI value "urn:urn-7:3gpp-service.ims.icsi.mcdata.ipconn" (coded as specified in 3GPP TS 24.229 [5]), in a P-Preferred-Service header field according to IETF RFC 6050 [7] in the SIP INVITE request;

5) should include the "timer" option tag in the Supported header field;

6) should include the Session-Expires header field according to IETF RFC 4028 [38]. It is recommended that the "refresher" header field parameter is omitted. If included, the "refresher" header field parameter shall be set to "uac";

7) shall insert in the SIP INVITE request a MIME resource-lists body with the MCData ID of the invited MCData user or the functional alias, according to rules and procedures of IETF RFC 5366 [18];

8) shall contain an application/vnd.3gpp.mcdata-info+xml MIME body with the <mcdatainfo> element containing the <mcdata-Params> element with:

   a) the <request-type> element set to a value of "one-to-one-ipconn";

   b) the <call-to-functional-alias-ind> set to "true" if the functional alias is used as a target of the communication request;

   c) if the MCData client is aware of active functional aliases and if an active functional alias is to be included in the SIP INVITE request, the <functional-alias-URI> element set to the URI of the used functional alias; and

   d) if the MCData user has requested an application priority, the <anyExt> element with the <user-requested-priority> element set to the user provided value.

9) shall set the Request-URI of the SIP INVITE request to the public service identity identifying the participating MCData function serving the MCData user;

NOTE 1: The MCData client is configured with public service identity identifying the participating MCData function serving the MCData user.

10) may include a P-Preferred-Identity header field in the SIP INVITE request containing a public user identity as specified in 3GPP TS 24.229 [5];

11) shall include an SDP offer according to 3GPP TS 24.229 [5] with the clarifications given in clause 20.2.0a; and

12) shall send the SIP INVITE request towards the MCData server according to 3GPP TS 24.229 [5].

On receipt of a SIP 2xx response to the SIP INVITE request, the MCData client:

1) shall send a SIP ACK request as specified in 3GPP TS 24.229 [5];

2) shall start the SIP Session timer according to rules and procedures of IETF RFC 4028 [38]; and

3) shall interact with the media plane as specified in 3GPP TS 24.582 [15] clause 13.1.2.

Upon receiving a SIP 300 (Multiple Choices) response to the SIP INVITE request the MCData client shall use the MCData ID of MCData user contained in the <mcdata-request-uri> element of the received application/vnd.3gpp.mcdata-info MIME body as the MCData ID of the invited MCData user and shall generate an initial SIP INVITE request by following the UE originating session procedures specified in 3GPP TS 24.229 [5], with the clarifications given in this clause and with the following additional clarifications:

1) shall insert in the newly generated SIP INVITE request a MIME resource-lists body with the MCData ID of the invited MCData user in the <mcdata-request-uri> element of the application/vnd.3gpp.mcdata-info MIME body in the received SIP 300 (Multiple Choices) response;

2) shall not include a <call-to-functional-alias-ind> element into the <mcdata-Params> element of the <mcdatainfo> element of the application/vnd.3gpp.mcdata-info+xml MIME body; and

3) shall include a <called-functional-alias-URI> element into the <mcdata-Params> element of the <mcdatainfo> element of the application/vnd.3gpp.mcdata-info+xml MIME body with the target functional alias used in the initial SIP INVITE request for the IP connectivity session establishment.

On receipt of a SIP 4xx response, a SIP 5xx response or a SIP 6xx response to the SIP INVITE request, the MCData client:

1) shall indicate to the MCData user or user application that the IP Connectivity session could not be established; and

2) shall send a SIP ACK request as specified in 3GPP TS 24.229 [5].

On receipt of an indication from the media plane indicating that the IP Connectivity session could not be established, the MCData client:

1) shall generate a SIP BYE request according to 3GPP TS 24.229 [5] with:

   a) Reason code set to "FAILURE_CAUSE";

   b) cause set to "1"; and

   c) text set to "Media bearer or QoS lost";

2) shall set the Request-URI to the MCData session identity to release; and

3) shall send a SIP BYE request towards MCData server according to 3GPP TS 24.229 [5].

[TS 24.282, clause 20.2.0a]

The SDP offer shall contain one SDP media-level section for MCData including an attribute for IP Connectivity according to 3GPP TS 24.582 [15]. When composing an SDP offer the MCData client shall:

1) set the IP address of the MCData client for the offered MCData IP Connectivity session; and

NOTE: The MC service operator policy determines if the MCData client can use an already assigned IP address or can request a new IP address following the procedures defined in 3GPP TS 24.301 [43].

2) shall include an "m=application" media-level section as specified in 3GPP TS 24.582 [15] consisting of:

   a) the port number selected for the media plane as specified in 3GPP TS 24.582 [15] clause 13.5; and

   b) the 'fmtp' attribute as specified in 3GPP TS 24.582 [15] clause 13.6.

[TS 24.582, clause 13.1.2]

Upon receiving a request by an MCData user, or an IP packet from an IP application, the MCData client shall follow the procedure in 20.2.1 in 3GPP TS 24.282 [8]. The IP address and port number received in the SDP payload of the 200 OK response in this procedure shall be used to establish an IP tunnel. The IP tunnel shall be based on GRE-in-UDP Encapsulation as specified in IETF RFC 8086 [23], and as specified in clause 13.4. Generic Routing Encapsulation (GRE) as specified in IETF RFC 2784 [19] is used as a basis of GRE-in-UDP Encapsulation.

The MCData client shall perform encapsulation and decapsulation according to clause 13.4.

The MCData client acts as an IP relay for IP traffic between the IP application and the IP tunnel to the far endpoint. Once the IP tunnel is established, the IP applications can exchange IP data. The MCData client that receives the IP packets from the IP application shall perform encapsulation to the tunnelling protocol adding a GRE header and a UDP header to the IP packet, and send the outgoing UDP traffic to the IP address and port present in the SDP answer. When the originating MCData client receives IP packets from the IP tunnel it shall perform de-capsulation from the tunnelling protocol, removing the UDP header and the GRE header from the received packet, before passing the IP data to the IP application.

6.7.1.3 Test description

6.7.1.3.1 Pre-test conditions

Test configuration:

- Single cell configuration according to TS 37.579-1 [2] clause 5.2.2.2.1.

Preamble:

- The UE has performed procedure 'Initial registration' as described in TS 37.579-1 [2] clause 5.4.2.
- UE States at the end of the preamble:
  - The UE is in RRC_IDLE state.
  - The client is registered for MCData.

6.7.1.3.2 Test procedure sequence

Table 6.7.1.3.2-1: Main Behaviour

St	Procedure	Message Sequence		TP	Verdict
		U - S	Message		
1	Make the UE (MCData client) establish a IP Connectivity session with another MCData client. (NOTE 1)	-	-	-	-
2-6	Check: Does the UE (MCData client) correctly perform steps 1 through 5 of procedure '**CO MCData Call Establishment**' as described in TS 37.579-1 [2] Table 5.3C.2.3-1 **to establish an IP Connectivity session with another MCData client**?	-	-	1	P
6A	Make the application at the UE send data through the GRE-in-UDP tunnel. (NOTE 1)	-	-	-	-
-	EXCEPTION: The communication described in in step 7 is transmitted over an IP connection that has been established based on GRE-in-UDP Encapsulation.	-	-	-	-
7	Check: Does the UE (MCData client) correctly send a payload packet via the GRE-in-UDP tunnel?	-	-	1	P
8	Make the UE (MCData client) release the IP Connectivity session. (NOTE 1)	-	-	-	-
9	Check: Does the UE (MCData client) correctly perform procedure '**CO MCData call release**' as described in TS 37.579-1 [2] Table 5.3C.6.3-1? (NOTE 2)	-	-	2	P
10	The procedure **'MCX communication release'** as described in TS 37.579-1 [2] clause 5.4.14 is performed to release the RRC connection.	-	-	-	-
NOTE 1: This is expected to be done via a suitable implementation dependent MMI. NOTE 2: The procedure does not release the RRC connection.					

6.7.1.3.3 Specific message contents

Table 6.7.1.3.3-1: SIP INVITE from the UE (step 3, Table 6.7.1.3.2-1; step 2, TS 37.579-1 [2] Table 5.3C.2.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.5.1-1, condition MCDATA_IPCONN, MCD_1to1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part		**SDP message**		
MIME-part-body	As described in Table 6.7.1.3.3-2			
MIME body part		**MCData-Info**		
MIME-part-body	MCData-Info as described in Table 6.7.1.3.3-3			

Table 6.7.1.3.3-2: SDP for SIP INVITE (Table 6.7.1.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.1.1-3, condition MCDATA_SDS, SDP_OFFER, SDS_SESSION, MCD_1to1				
Media description[1]		**Media description for data**		
media description		m= line media = application		
media	“application”		TS 24.582 [32] clause 13.5	
port	any allowed value		TS 24.582 [32] clause 13.5	
proto	“udp”		TS 24.582 [32] clause 13.5	
fmt	“MCDATA”		TS 24.582 [32] clause 13.5	
media attribute		a= line attribute = fmtp		
fmtp	"fmtp"		TS 24.582 [32] clause 13.5	
fmtp-attr-ipconn	“MCDATA”		TS 24.582 [32] clause 13.5	
attr-param	"mcdata-ipconn-s-port=<any allowed value>”	UDP source port of the GRE-in-UDP tunnel	TS 24.582 [32] clause 13.5	

Table 6.7.1.3.3-3: MCData-Info (Table 6.7.1.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.2.1-3				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
mcdata-info				
mcdata-Params				
request-type	"one-to-one-ipconn"			

Table 6.7.1.3.3-4: SIP 200 (OK) from the SS (step 5, Table 6.7.1.3.2-1; step 4, TS 37.579-1 [2] Table 5.3C.2.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.17.1.2-1, condition INVITE-RSP, MCDATA_IPCONN				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
SDP message	As described in Table 6.1.5.9.3-5			

Table 6.7.1.3.3-5: SDP for SIP 200 (OK) (Table 6.7.1.3.3-4)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.1.2-3, condition MCDATA_SDS, SDP_ANSWER, SDS_SESSION				
Media description[1]		**Media description for data**		
media description		m= line media = application		
media	“application”		TS 24.582 [32] clause 13.5	
port	same number as indicated by the <attr-param> parameter in Table 6.7.1.3.3-2			
proto	“udp”		TS 24.582 [32] clause 13.5	
fmt	“MCDATA”		TS 24.582 [32] clause 13.5	
media attribute		a= line attribute = fmtp		
fmtp	"fmtp"		TS 24.582 [32] clause 13.5	
fmtp-attr-ipconn	“MCDATA”		TS 24.582 [32] clause 13.5	
attr-param	"mcdata-ipconn-s-port=<port number assigned by the SS>”	UDP source port of the GRE-in-UDP tunnel	TS 24.582 [32] clause 13.5	

Table 6.7.1.3.3-6: GRE-in-UDP encapsulated user data packet (step 7, Table 6.7.1.3.2-1)

Derivation Path: 24.582 [32], Clause 13.4			
Information Element	**Value/remark**	**Comment**	**Condition**
GRE header			
C	0		
Reserved	0		
K	0		
S	0		
Reserved	0000		
Reserved	00000		
Ver	000		
Protocol Type	‘0800’H		IPv4
Protocol Type	‘86DD’H		IPv6
Payload packet			
Payload packet	valid IP packet	Editor's note: It needs to be clarified what "valid IP packet" means and how this shall be checked (e.g. destination address may be checked to be px_MCData_IPConnectivityEndpointAddress_B)	

6.7.2 On-network / IP Connectivity / Client Terminated (CT)

6.7.2.1 Test Purpose (TP)

(1)

```
with { UE (MCDATA Client) registered and authorised for MCDATA Service }
```

```
ensure that {
  when { the MCDATA User receives a SIP INVITE to initiate a IP Connectivity session }
    then { UE (MCDATA Client) responds by sending a SIP 200 (OK) message and responds to any
received ICMP ECHO request sent over the IP Connectivity session }
            }
```

(2)

```
with { UE (MCDATA Client) being in a IP Connectivity session initiated by the SS (MCDATA server) }
ensure that {
  when { UE (MCDATA Client) receives a SIP BYE message }
    then { UE (MCDATA Client) responds by sending a SIP 200 (OK) message }
            }
```

6.7.2.2 Conformance requirements

References: The conformance requirements covered in the current TC are specified in: TS 24.282, clause 20.2.2 and 20.2.0a, TS 24.582, clause 13.1.3. Unless otherwise stated, these are Rel-17 requirements.

[TS 24.282, clause 20.2.2]

Upon receipt of a SIP INVITE request for IP Connectivity session for terminating MCData client"request, the MCData client shall follow the procedures for termination of multimedia sessions in the IM CN subsystem as specified in 3GPP TS 24.229 [5] with the clarifications below.

The MCData client:

1) may reject the SIP INVITE request if either of the following conditions are met:

   a) MCData client does not have enough resources to handle the IP Connectivity session; or

   b) any other reason outside the scope of this specification;

2) if the SIP INVITE request is rejected in step 1), shall respond toward participating MCData function either with appropriate reject code as specified in 3GPP TS 24.229 [5] and warning texts as specified in clause 4.9 or with SIP 480 (Temporarily unavailable) response not including warning texts if the user is authorised to restrict the reason for failure and skip the rest of the steps of this clause;

3) may provide to the MCData user or user application the MCData ID of the inviting MCData user;

3A) may display to the MCData user the functional alias of the inviting MCData user, if provided;

3B) may display to the MCData user the functional alias used in the initial communication request, if provided;

4) shall accept the SIP INVITE request and generate a SIP 200 (OK) response according to rules and procedures of 3GPP TS 24.229 [5];

5) shall include the option tag "timer" in a Require header field of the SIP 200 (OK) response;

6) shall include the Session-Expires header field in the SIP 200 (OK) response and start the SIP session timer according to IETF RFC 4028 [38]. The "refresher" parameter in the Session-Expires header field shall be set to "uas";

7) shall include the g.3gpp.mcdata.ipconn media feature tag in the Contact header field of the SIP 200 (OK) response;

8) shall include the g.3gpp.icsi-ref media feature tag containing the value of "urn:urn-7:3gpp-service.ims.icsi.mcdata.ipconn" in the Contact header field of the SIP 200 (OK) response;

9) shall include an SDP answer in the SIP 200 (OK) response to the SDP offer in the incoming SIP INVITE request according to 3GPP TS 24.229 [5] with the clarifications given in clause 20.2.0b; and

10) shall send the SIP 200 (OK) response towards the MCData server according to rules and procedures of 3GPP TS 24.229 [5].

On receipt of an SIP ACK message to the sent SIP 200 (OK) message, the MCData client:

1) shall interact with the media plane as specified in 3GPP TS 24.582 [15] clause 13.1.3.

[TS 24.282, clause 20.2.0b]

When the MCData client receives an initial SDP offer for a MCData including an attribute for IP Connectivity, the MCData client shall process the SDP offer and shall compose an SDP answer.

When composing an SDP answer, the MCData client:

1) shall accept the MCData media stream in the SDP offer;

2) shall set the IP address of the MCData client for the accepted MCData media stream; and

NOTE: The MC service operator policy determines if the MCData client can use an already assigned IP address or can request a new IP address following the procedures defined in 3GPP TS 24.301 [43].

3) shall include an "m=application" media-level section for the accepted MCData media stream consisting of:

   a) the port number selected for the media plane as specified in 3GPP TS 24.582 [15] clause 13.5; and

   b) the 'fmtp' attribute as specified in 3GPP TS 24.582 [15] clause 13.6.

[TS 24.582, clause 13.1.3]

The successful outcome of the procedure 20.2.2 in 3GPP TS 24.282 [8] shall be the trigger to start the establishment of the IP tunnel. The IP tunnel is based on GRE-in-UDP Encapsulation as specified in IETF RFC 8086 [23], and as specified in clause 13.4.

The MCData client shall perform encapsulation and decapsulation in accordance with clause 13.4.

The MCData client acts as an IP relay for IP traffic between the IP tunnel and the IP application. Once the IP tunnel is established, the IP applications can exchange IP data. The client that receives IP packets from the IP tunnel shall perform de-capsulation from the tunnelling protocol, removing the UDP header and the GRE header from the received packet, before passing the IP data to the IP application. When the terminating MCData client receives an IP packet from the IP application, it shall perform encapsulation to the tunnelling protocol adding a GRE header and a UDP header to the IP packet, and send the outgoing UDP traffic to the IP address and port present in the SDP offer.

6.7.2.3 Test description

6.7.2.3.1 Pre-test conditions

Test configuration:

- Single cell configuration according to TS 37.579-1 [2] clause 5.2.2.2.1.

Preamble:

- The UE has performed procedure 'Initial registration' as described in TS 37.579-1 [2] clause 5.4.2.
- UE States at the end of the preamble:
  - The UE is in RRC_IDLE state.
  - The client is registered for MCData.

6.7.2.3.2 Test procedure sequence

Table 6.7.2.3.2-1: Main Behaviour

St	Procedure	Message Sequence		TP	Verdict
		U - S	Message		
1-5	Check: Does the UE (MCData client) correctly perform steps 1 through 5 of procedure '**CT MCData Call Establishment**' as described in TS 37.579-1 [2] Table 5.3C.3.3-1?	-	-	1,2	P
-	EXCEPTION: The communication described in in steps 6 and 7 is transmitted over an IP connection that has been established based on GRE-in-UDP Encapsulation.	-	-	-	-
6	The SS (MCX Server) sends a ICMP ECHO request via the GRE-in-UDP tunnel.	-	-	-	-
7	Check: Does the UE (MCData client) provide an ICMP ECHO reply via the GRE-in-UDP tunnel?	-	-	1	P
8	Check: Does the UE (MCData client) correctly perform procedure '**CT MCData call release**' as described in TS 37.579-1 [2] Table 5.3C.7.3-1? (NOTE 1)	-	-	2	P
9	The procedure 'MCX communication release' as described in TS 37.579-1 [2] clause 5.4.14 is performed to release the RRC connection.	-	-	-	-
NOTE 1: The procedure does not release the RRC connection.					

6.7.2.3.3 Specific message contents

Table 6.7.2.3.3-1: SIP INVITE from the SS (step 2, Table 6.7.2.3.2-1; step 2, TS 37.579-1 [2] Table 5.3C.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.5.2-1, condition MCDATA_SDS				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Contact				
addr-spec	SIP URI			
user-info and host	IP address or FQDN			
port	protected server port of UE	as assigned during registration		
feature-param	"+g.3gpp.mcdata.ipconn"			
feature-param	"+g.3gpp.icsi-ref=urn:urn-7:3gpp-service.ims.icsi.mcdata.ipconn"			
Accept-Contact				
ac-value[1]				
feature-param	"+g.3gpp.icsi-ref=urn:urn-7:3gpp-service.ims.icsi.mcdata.ipconn"			
req-param	"require"			
explicit-param	"explicit"			
ac-value[2]				
feature-param	"+g.3gpp.mcdata.ipconn"			
req-param	"require"			
explicit-param	"explicit"			
Message-body				
MIME body part		**SDP message**		
MIME-part-body	SDP message as described in Table 6.7.2.3.3-2			
MIME body part		**MCData-Info**		
MIME-part-body	MCData-Info as described in Table 6.7.2.3.3-3			

Table 6.7.2.3.3-2: SDP for SIP INVITE (Table 6.7.2.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.1.2-3, condition MCDATA_SDS, SDP_OFFER, MCD_1to1, SDS_SESSION				
Media description[1]		**Media description for data**		
media description		m= line media = application		
media	“application”		TS 24.582 [32] clause 13.5	
port	port number assigned by the SS			
proto	“udp”		TS 24.582 [32] clause 13.5	
fmt	“MCDATA”		TS 24.582 [32] clause 13.5	
media attribute		a= line attribute = fmtp		
fmtp	"fmtp"		TS 24.582 [32] clause 13.5	
fmtp-attr-ipconn	“MCDATA”		TS 24.582 [32] clause 13.5	
attr-param	"mcdata-ipconn-s-port=<port number assigned by the SS>”	UDP source port of the GRE-in-UDP tunnel	TS 24.582 [32] clause 13.5	

Table 6.7.2.3.3-3: MCData-Info (Table 6.7.2.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.2.2-3, condition MCD_1to1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
mcdata-info				
mcdata-Params				
request-type	"one-to-one-ipconn"			

Table 6.7.2.3.3-4: SIP 200 (OK) from the UE (step 4, Table 6.7.2.3.2-1; step 4, TS 37.579-1 [2] Table 5.3C.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.17.1.1-1, condition INVITE-RSP, MCDATA_SDS				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Contact				
addr-spec				
user-info and host	tsc_MCData_SessionId			
port	not present			
feature-param	"+g.3gpp.mcdata.ipconn"			
feature-param	"+g.3gpp.icsi-ref=urn:urn-7:3gpp-service.ims.icsi.mcdata.ipconn"			
feature-param	"isfocus"			
Content-Type				
value	"application/sdp"			
Message-body				
SDP message	As described in Table 6.7.2.3.3-5			

Table 6.7.2.3.3-5: SDP for SIP 200 (OK) (Table 6.7.2.3.3-4)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.1.1-3, condition MCDATA_SDS, SDP_ANSWER, SDS_SESSION				
Media description[1]		**Media description for data**		
media description		m= line media = application		
port	same number as indicated by the <attr-param> parameter in Table 6.7.2.3.3-2			
proto	“udp”		TS 24.582 [32] clause 13.5	
fmt	“MCDATA”		TS 24.582 [32] clause 13.5	
media attribute		a= line attribute = fmtp		
fmtp	"fmtp"		TS 24.582 [32] clause 13.5	
fmtp-attr-ipconn	“MCDATA”		TS 24.582 [32] clause 13.5	
attr-param	"mcdata-ipconn-s-port=<any allowed value>”	UDP source port of the GRE-in-UDP tunnel	TS 24.582 [32] clause 13.5	

Table 6.7.2.3.3-6: GRE encapsulated user data packet (step 6, Table 6.7.2.3.2-1)

Derivation Path: 24.582 [32], Table 13.4-1			
Information Element	**Value/remark**	**Comment**	**Condition**
GRE header			
C	0		
Reserved	0		
K	0		
S	0		
Reserved	0000		
Reserved	00000		
Ver	000		
Protocol Type	‘0800’H		IPv4
Protocol Type	‘86DD’H		IPv6
Payload packet			
Payload packet	ICMP ECHO	ICMP ECHO reply	

6.8 MCData Message Store

6.8.1 On-network / MCData Message Store / Objects / Object upload / Object search / Update Object / Object retrieval / Delete stored object

6.8.1.1 Test Purpose (TP)

(1)

```
with { UE (MCData Client)registered and authorized for MCData service }
ensure that {
  when { the MCDATA User requests to upload a file to the Message Store Function }
    then { UE (MCData Client) uploads the file to the Message Store Function via an HTTP POST
message }
            }
```

(2)

```
with { UE (MCData Client)registered and authorized for MCData service }
ensure that {
  when { the MCDATA User requests to search for created objects in the Message Store Function }
    then { UE (MCData Client) requests for created objects in the Message Store Function via an HTTP
POST message }
            }
```

(3)

```
with { UE (MCData Client)registered and authorized for MCData service }
ensure that {
  when { the MCDATA User requests to update a file in the Message Store Function by adding a flag }
    then { UE (MCData Client) updates the file in the Message Store Function via an HTTP PUT message
}
            }
```

(4)

```
with { UE (MCData Client)registered and authorized for MCData service }
ensure that {
  when { the MCDATA User requests to retrieve information about an object from the Message Store
Function }
    then { UE (MCData Client) downloads the object from the Message Store Function via an HTTP GET
message }
            }
```

(5)

```
with { UE (MCData Client)registered and authorized for MCData service }
ensure that {
  when { the MCDATA User requests to delete a file from the Message Store Function }
    then { UE (MCData Client) deletes the file from the Message Store Function via an HTTP DELETE
message }
            }
```

6.8.1.2 Conformance requirements

References: The conformance requirements covered in the current TC are specified in: TS 24.282, clauses 21.2.15.1, 21.2.2.1, 21.2.3.1, 21.2.1.1, 21.2.4.1. Unless otherwise stated, these are Rel-16 requirements.

[TS 24.282 clause 21.2.15.1]

To upload the object(s) to the message store, the message store client acting as an HTTP client, shall follow the procedure described in subclause 6.1 for single upload and subclause 6.10 for bulk upload as specified in the OMA-TS-REST_NetAPI_NMS-V1_0-20190528-C [66] with following clarification:

1) shall generate an HTTP POST request as specified in subclause 6.1.5 and 6.10.5 of OMA-TS-REST_NetAPI_NMS-V1_0-20190528-C [66] with following clarifications:

   a) shall set the Host header field to a hostname identifying the message store function;

   b) shall include a valid MCData access token in the HTTP Authorization header; and

   c) shall send the HTTP POST request towards the message store function.

Upon receipt of an HTTP response, the message store client shall follow the procedure as described in subclause 6.1.2 for single upload and 6.10.2 for bulk upload as specified in the OMA-TS-REST_NetAPI_NMS-V1_0-20190528-C [66].

[TS 24.282 clause 21.2.2.1]

To search for information about a selected set of objects in the message store, the message store client, acting as an HTTP client shall follow the procedure described in subclause 6.8 of OMA-TS-REST_NetAPI_NMS-V1_0-20190528-C [66] with following clarification:

1) shall generate an HTTP POST request as specified in subclause 6.8.5 of OMA-TS-REST_NetAPI_NMS-V1_0-20190528-C [66] with following clarifications:

a) shall set the Host header field to a hostname identifying the message store function;

b) shall include a valid MCData access token in the HTTP Authorization header; and

c) shall send the HTTP POST request, which may include a SelectionCriteria, towards the message store function.

Upon receipt of a HTTP response, the message store client shall follow the procedure as describe in subclause 6.8.2 of OMA-TS-REST_NetAPI_NMS-V1_0-20190528-C [66].

[TS 24.282 clause 21.2.3.1]

To update object(s) in the message store, the message store client, acting as an HTTP client, shall either follow the procedure described in subclause 6.3 or 6.4, for individual object update, or 6.11 for bulk update of objects, of OMA-TS-REST_NetAPI_NMS-V1_0-20190528-C [66] with following clarification:

1) shall either generate an HTTP PUT request as specified in subclause 6.3.4, 6.4.4, for individual object update, or an HTTP POST request, as specified in subclause 6.11.5, for bulk update of objects, of OMA-TS-REST_NetAPI_NMS-V1_0-20190528-C [66], with following clarifications:

   a) shall set the Host header field to a hostname identifying the message store function;

   b) shall include a valid MCData access token in the HTTP Authorization header; and

   c) shall send HTTP PUT request, for individual object update, or HTTP POST request, for bulk update of objects, towards the message store function.

Upon receipt of a HTTP response, the message store client shall either follow the procedure as described in subclause 6.3.2, 6.4.2 for individual object update response, or subclause 6.11.2 for bulk update of objects response, of OMA-TS-REST_NetAPI_NMS-V1_0-20190528-C [66].

[TS 24.282 clause 21.2.1.1]

To retrieve the object from message store function, the message store client, acting as an HTTP client shall follow the procedure described in subclause 6.2 of OMA-TS-REST_NetAPI_NMS-V1_0-20190528-C [66] with following clarification:

1) shall generate an HTTP GET request as specified in subclause 6.2.3 of OMA-TS-REST_NetAPI_NMS-V1_0-20190528-C [66] with following clarifications:

   a) shall set the Host header field to a hostname identifying the message store function

   b) shall include a valid MCData access token in the HTTP Authorization header; and

   c) shall send the HTTP GET request towards the message store function.

Upon receipt of a HTTP response, the message store client shall follow the procedure as described in subclause 6.2.2 of OMA-TS-REST_NetAPI_NMS-V1_0-20190528-C [66].

[TS 24.282 clause 21.2.4.1]

To delete object(s) in the message store, the message store client, acting as an HTTP client, shall either follow the procedure described in subclause 6.2, for individual object delete, or subclause 6.12 for bulk delete of objects, of OMA-TS-REST_NetAPI_NMS-V1_0-20190528-C [66] with following clarification:

1) shall either generate an HTTP DELETE request as specified in subclause 6.2.6, for individual object delete, or an HTTP POST request as specified in subclause 6.12.6, for bulk delete of objects, of OMA-TS-REST_NetAPI_NMS-V1_0-20190528-C [66], with following clarifications:

   a) shall set the Host header field to a hostname identifying the message store function;

   b) shall include a valid MCData access token in the HTTP Authorization header; and

   c) shall send HTTP DELETE request, for individual object delete, or HTTP POST request, for bulk delete of objects, towards the message store function.

Upon receipt of a HTTP response, the message store client shall either follow the procedure as described in subclause 6.2.2, for individual object delete response, or subclause 6.12.2, for bulk delete of objects response, of OMA-TS-REST_NetAPI_NMS-V1_0-20190528-C [66].

6.8.1.3 Test description

6.8.1.3.1 Pre-test conditions

Test configuration:

- Single cell configuration according to TS 36.879-1 [2] clause 5.2.2.2.1.

Preamble:

- The UE has performed procedure 'Initial registration' as described in TS 36.879-1 [2] clause 5.4.2.
- UE States at the end of the preamble:
  - The UE is in RRC_IDLE state.
  - The client is registered for MCData.

6.8.1.3.2 Test procedure sequence

Table 6.8.1.3.2-1: Main Behaviour

St	Procedure	Message Sequence		TP	Verdict
		U - S	Message		
1	Make the UE (MCData client) upload an object, test file 1 (ANNEX A.2.1), to the message store. (NOTE 1)	-	-	-	-
2	Check: Does the UE (MCData client) correctly perform procedure **'Message Store Function Object Upload using HTTP'** as described in TS 37.579-1 [2] Table 5.3C.14.2-1 to upload an object to the message store?	-	-	1	P
3	Make the UE (MCData client) search for existing objects that were created in the message store. (NOTE 1)	-	-	-	-
4	Check: Does the UE (MCData client) correctly perform procedure **'Message Store Function Post Request using HTTP'** as described in TS 37.579-1 [2] Table 5.3C.17.2-1 to search for existing objects that were created in the message store?	-	-	2	P
5	Make the UE (MCData client) update an object by adding a flag. (NOTE 1)	-	-	-	-
6	Check: Does the UE (MCData client) correctly perform procedure **'Message Store Function Put Request using HTTP'** as described in TS 37.579-1 [2] Table 5.3C.18.2-1 to update an object by adding a flag?	-	-	3	P
7	Make the UE (MCData client) retrieve an object. (NOTE 1)	-	-	-	-
8	Check: Does the UE (MCData client) correctly perform procedure **'Message Store Function Retrieve using HTTP'** as described in TS 37.579-1 [2] Table 5.3C.16.2-1 to retrieve an object in the message store?	-	-	4	P
9	Make the UE (MCData client) delete an object. (NOTE 1)	-	-	-	-
10	Check: Does the UE (MCData client) correctly perform procedure **'Message Store Function Delete using HTTP'** as described in TS 37.579-1 [2] Table 5.3C.15.2-1 to delete an object in the message store?	-	-	5	P
NOTE 1: This is expected to be done via a suitable implementation dependent MMI.					

6.8.1.3.3 Specific message contents

Table 6.8.1.3.3-1: HTTP POST from the UE (Step 2, Table 6.8.1.3.2-1; step 2, TS 37.579-1 [2] Table 5.3C.14.2-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.4.3-1, condition MSG_STORE				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Request-Line				
Request-URI				
uri	tsc_MCData_MsgSF_BaseURL & "/objects"			
Content-Type				
media-type	"multipart/form-data"		RFC 2388 [43]	
Message-body				
MIME body part		**Object**		
MIME-part-headers				
MIME-Content-Type	"application/xml"			
MIME-Content-Disposition				
type	form-data		RESTful Network API common [42] clause 5.7	
param	name=”root-fields”		RESTful Network API common [42] clause 5.7	
MIME-part-body				
NMS Object			RESTful Network API for NMS [40], clause 5.3.2.1 and XML schema defined in [48]	
parentFolder	Not present (NOTE 1)			
parentFolderPath	Not present (NOTE 1)			
attributes	empty list			
flags	empty list			
imdns	Not present			
resourceURL	Not present			
path	Not present			
payloadURL	Not present			
payloadPart	Not present			
lastModSeq	Not present			
correlationId	Any value if present			
correlationTag	Any value if present			
MIME body part		**File content**		
MIME-part-headers				
MIME-Content-Type	"application/octet-stream"			
MIME-Content-Disposition				
type	attachments		RESTful Network API common [42] clause 5.7	
param	filename with any value		RESTful Network API common [42] clause 5.7	
MIME-part-body	binary data representing the file	The binary for test file 1		
NOTE 1: As the client does not know the resourceURL or path of any folder yet, it is assumed that the client does neither provide a <parentFolder> nor a <parentFolderPath>				

Table 6.8.1.3.3-2: HTTP 201 Created from the SS (step 2, Table 6.8.1.3.2-1; step 3, TS 37.579-1 [2] Table 5.3C.14.2-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.4.7-1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Location				
uri	tsc_MCData_MsgSF_AbsoluteBaseURL & "/objects/objectId0001"	"objectId0001" arbitrarily selected		
Content-Type				
media-type	"application/xml"			
Message-body: NMS Reference				
resourceURL	tsc_MCData_MsgSF_AbsoluteBaseURL & "/objects/objectId0001"	same as in Location		
path	"main/test-file-1"	arbitrarily selected		

Table 6.8.1.3.3-3: HTTP POST from the UE (Step 4, Table 6.8.1.3.2-1; step 2, TS 37.579-1 [2] Table 5.3C.17.2-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.4.3-1, condition MSG_STORE				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Request-Line				
Request-URI				
uri	tsc_MCData_MsgSF_BaseURL & "/objects/operations/search"	URI addressing the search operation		
Content-Type				
media-type	"application/xml"			
Message-body: NMS SelectionCriteria			RESTful Network API for NMS [40], clause 6.8 and XML schema defined in [48]	
fromCursor	Not present			
maxEntries	any value	the maximum number of entries in the response		
searchCriteria				
Criterion [1]				
type	CreatedObjects			
name	Not present			
value	""	Searching for existing objects that were created in the store since a previous CreatedObjects search. Searching an empty string ("") denotes all existing objects in the store		
operator	Not present			
searchScope	Not present			
nonRecursiveScope	Not present			
sortCriteria	Not present			
inlineImdn	Not present			

Table 6.8.1.3.3-4: HTTP 200 (OK) from the SS (step 4, Table 6.8.1.3.2-1; step 3, TS 37.579-1 [2] Table 5.3C.17.2-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.4.6-1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Content-Type				
media-type	"application/xml"			
Message-body: NMS ObjectList				
Object [1]				
parentFolder	tsc_MCData_MsgSF_AbsoluteBaseURL & "/folders/folderId0001"	"folderId0001" arbitrarily selected as id of the root folder		
attributes	empty list			
flags	empty list			
imdns	Not present			
resourceURL	tsc_MCData_MsgSF_AbsoluteBaseURL & "/objects/objectId0001"			
path	"main/test-file-1"			
payloadURL	tsc_MCData_MsgSF_BaseURL & "/objects/objectId0001/payload"			
payloadPart	Not present			
lastModSeq	Not present			
correlationId	As received in POST request at step 2 (if so)			
correlationTag	As received in POST request at step 2 (if so)			

Table 6.8.1.3.3-5: HTTP PUT from the UE (Step 6, Table 6.8.1.3.2-1; step 2, TS 37.579-1 [2] Table 5.3C.18.2-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.4.4-1, condition MSG_STORE				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Request-Line				
Request-URI				
uri	tsc_MCData_MsgSF_BaseURL & "/objects/objectId0001/flags"	URI addressing the object's flags		
Content-Type				
media-type	"application/xml"			
Message-body: NMS flagList			RESTful Network API for NMS [40], clause 6.3 and XML schema defined in [48]	
flag [1]	Any value	Flag provided by MMI at step 5		
resourceURL	tsc_MCData_MsgSF_AbsoluteBaseURL & "/objects/objectId0001/flags"	mandatory for PUT request		

Table 6.8.1.3.3-6: HTTP 200 (OK) from the SS (step 6, Table 6.8.1.3.2-1; step 3, TS 37.579-1 [2] Table 5.3C.18.2-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.4.6-1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Content-Type				
media-type	"application/xml"			
Message-body: NMS flagList			RESTful Network API for NMS [40], clause 6.3 and XML schema defined in [48]	
flag [1]	same flag as in the PUT request			
resourceURL	tsc_MCData_MsgSF_AbsoluteBaseURL & "/objects/objectId0001/flags"			

Table 6.8.1.3.3-7: HTTP GET from the UE (Step 8, Table 6.8.1.3.2-1; step 2, TS 37.579-1 [2] Table 5.3C.16.2-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.4.2-1, condition MSG_STORE				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Request-Line				
Request-URI				
uri	tsc_MCData_MsgSF_BaseURL & "/objects/objectId0001"	URI addressing the object		

Table 6.8.1.3.3-8: HTTP 200 (OK) from the SS (step 8, Table 6.8.1.3.2-1; step 3, TS 37.579-1 [2] Table 5.3C.16.2-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.4.6-1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Content-Type				
media-type	"application/xml"			
Message-body: NMS Object		same object as in the HTTP 200 (OK) at step 4 but with flag added at step 6		
parentFolder	tsc_MCData_MsgSF_AbsoluteBaseURL & "/folders/folderId0001"			
attributes	empty list			
flags				
flag[1]	same flag as in the PUT request of step 6			
resourceURL	tsc_MCData_MsgSF_AbsoluteBaseURL & "/objects/objectId0001/flags"			
imdns	Not present			
resourceURL	tsc_MCData_MsgSF_AbsoluteBaseURL & "/objects/objectId0001"			
path	"main/test-file-1"			
payloadURL	tsc_MCData_MsgSF_BaseURL & "/objects/objectId0001/payload"			
payloadPart	Not present			
lastModSeq	Not present			
correlationId	As received in POST request at step 2 (if so)			
correlationTag	As received in POST request at step 2 (if so)			

Table 6.8.1.3.3-9: HTTP DELETE from the UE (Step 10, Table 6.8.1.3.2-1; step 2, TS 37.579-1 [2] Table 5.3C.15.2-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.4.5-1, condition MSG_STORE				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Request-Line				
Request-URI				
uri	tsc_MCData_MsgSF_BaseURL & "/objects/objectId0001"	URI addressing the object		

6.8.2 On-network / MCData Message Store / Folders / Discover a folder / Create a folder / Object and folder copy / Search a folder / Move a folder / Delete a folder

6.8.2.1 Test Purpose (TP)

(1)

```
with { UE (MCData Client)registered and authorized for MCData service }
ensure that {
  when { the MCDATA User requests to discover its main folder ID in the Message Store Function }
    then { UE (MCData Client) requests to discover its main folder ID in the Message Store Function
via an HTTP POST message }
```

```
            }
```

(2)

```
with { UE (MCData Client)registered and authorized for MCData service }
ensure that {
  when { the MCDATA User requests to create a folder in the Message Store Function }
    then { UE (MCData Client) requests to create a folder in the Message Store Function via an HTTP
POST message }
            }
```

(3)

```
with { UE (MCData Client)registered and authorized for MCData service }
ensure that {
  when { the MCDATA User requests to upload a file to the Message Store Function }
    then { UE (MCData Client) uploads the file to the Message Store Function via an HTTP POST
message }
            }
```

(4)

```
with { UE (MCData Client)registered and authorized for MCData service }
ensure that {
  when { the MCDATA User requests to copy an object from one folder to another folder in the Message
Store Function }
    then { UE (MCData Client) copies an object from one folder to another folder in the Message
Store Function via an HTTP POST message }
            }
```

(5)

```
with { UE (MCData Client)registered and authorized for MCData service }
ensure that {
  when { the MCDATA User requests to search for information about the main folder in the  Message
Store Function }
    then { UE (MCData Client) searches for information about the main folder in the Message Store
Function via an HTTP GET message }
            }
```

(6)

```
with { UE (MCData Client)registered and authorized for MCData service }
ensure that {
  when { the MCDATA User requests to move a folder and its contents into another folder in the
Message Store Function }
    then { UE (MCData Client) moves the folder into another folder in the Message Store Function via
an HTTP POST message }
            }
```

(7)

```
with { UE (MCData Client)registered and authorized for MCData service }
ensure that {
  when { the MCDATA User requests to delete a folder from the Message Store Function }
    then { UE (MCData Client) deletes the folder from the Message Store Function via an HTTP DELETE
message }
            }
```

6.8.2.2 Conformance requirements

References: The conformance requirements covered in the current TC are specified in: TS 24.282, clauses 21.2.11.1, 21.2.8.1, 21.2.15.1, 21.2.6.1, 21.2.18.1, 21.2.10.1, 21.2.7.1. Unless otherwise stated, these are Rel-16 requirements.

[TS 24.282 clause 21.2.11.1]

To search for information about a selected set of folder(s) in the message store, the message store client, acting as an HTTP client shall follow the procedure described in subclause 6.16 of OMA-TS-REST_NetAPI_NMS-V1_0-20190528-C [66] with following clarification:

1) shall generate an HTTP POST request as specified in subclause 6.16.5 of OMA-TS-REST_NetAPI_NMS-V1_0-20190528-C [66] with following clarifications:

   a) shall set the Host header field to a hostname identifying the message store function;

   b) shall include a valid MCData access token in the HTTP Authorization header; and

   c) shall send the HTTP POST request, which may include a SelectionCriteria, towards the message store function.

Upon receipt of a HTTP response, the message store client should follow the procedure as described in subclause 6.16.2 of OMA-TS-REST_NetAPI_NMS-V1_0-20190528-C [66].

[TS 24.282 clause 21.2.8.1]

To create a folder in message store using the message store function, the message store client, acting as an HTTP client shall follow the procedure described in subclause 6.13 of OMA-TS-REST_NetAPI_NMS-V1_0-20190528-C [66] with following clarification:

1) shall generate an HTTP POST request as specified in subclause 6.13.5 of OMA-TS-REST_NetAPI_NMS-V1_0-20190528-C [66] with following clarifications:

   a) shall set the Host header field to a hostname identifying the message store function;

   b) shall include a valid MCData access token in the HTTP Authorization header; and

   c) shall send towards the message store function the HTTP POST request identifying the target folder where the new folder is to be created.

Upon receipt of a HTTP response, the message store client should follow the procedure as described in subclause 6.13.2 of OMA-TS-REST_NetAPI_NMS-V1_0-20190528-C [66].

[TS 24.282 clause 21.2.15.1]

To upload the object(s) to the message store, the message store client acting as an HTTP client, shall follow the procedure described in subclause 6.1 for single upload and subclause 6.10 for bulk upload as specified in the OMA-TS-REST_NetAPI_NMS-V1_0-20190528-C [66] with following clarification:

1) shall generate an HTTP POST request as specified in subclause 6.1.5 and 6.10.5 of OMA-TS-REST_NetAPI_NMS-V1_0-20190528-C [66] with following clarifications:

   a) shall set the Host header field to a hostname identifying the message store function;

   b) shall include a valid MCData access token in the HTTP Authorization header; and

   c) shall send the HTTP POST request towards the message store function.

Upon receipt of an HTTP response, the message store client shall follow the procedure as described in subclause 6.1.2 for single upload and 6.10.2 for bulk upload as specified in the OMA-TS-REST_NetAPI_NMS-V1_0-20190528-C [66].

[TS 24.282 clause 21.2.6.1]

To copy object(s) and/or folder(s) to a destination folder in message store, the message store client, acting as an HTTP client, shall follow the procedure described in subclause 6.18 of OMA-TS-REST_NetAPI_NMS-V1_0-20190528-C [66] with following clarification:

1) shall generate an HTTP POST request as specified in subclause 6.18.5 of OMA-TS-REST_NetAPI_NMS-V1_0-20190528-C [66] with following clarifications:

   a) shall set the Host header field to a hostname identifying the message store function;

   b) shall include a valid MCData access token in the HTTP Authorization header; and

   c) shall send HTTP POST request identifying the target folder and the source objects(s) and/or folder(s) for copying operation towards the message store function.

Upon receipt of an HTTP response, the message store client should follow the procedure as described in subclause 6.18.2 of OMA-TS-REST_NetAPI_NMS-V1_0-20190528-C [66].

[TS 24.282 clause 21.2.18.1]

To list subfolders of a given folder identified by its folder ID in the message store using the message store function, the message store client, acting as an HTTP client shall follow the procedure described in clause 6.14 of OMA-TS-REST_NetAPI_NMS-V1_0-20190528-C [66] with the following clarification:

1) shall generate an HTTP GET request as specified in clause 6.14.3 of OMA-TS-REST_NetAPI_NMS-V1_0-20190528-C [66] with the following clarifications:

   a) shall set the Host header field to a hostname identifying the message store function;

   b) shall include a valid MCData access token in the HTTP Authorization header;

   c) shall set the query string "listFilter" to:

      i) "Subfolders" if only a list of subfolders is to be returned;

      ii) "Objects" if only a list of objects is to be returned; or

      iii) "All" if a list all contents of the specified folder is to be returned; and

2) shall send the HTTP GET request towards the message store function.

NOTE: in order for the message store client to list the subfolders of the root folder, it first needs to discover its folder ID as described in clause 5.1.6 of OMA-TS-REST_NetAPI_NMS-V1_0-20190528-C [66] using Folder search procedure specified in clause 21.2.11 of the present document.

Upon receipt of an HTTP response, the message store client should follow the procedure as described in clause 6.14.2 of OMA-TS-REST_NetAPI_NMS-V1_0-20190528-C [66].

[TS 24.282 clause 21.2.10.1]

To move object(s) and/or folder(s) to a destination folder in the message store, the message store client, acting as an HTTP client shall follow the procedure described in subclause 6.19 of OMA-TS-REST_NetAPI_NMS-V1_0-20190528-C [66] with following clarification:

1) shall generate an HTTP POST request as specified in subclause 6.19.5 of OMA-TS-REST_NetAPI_NMS-V1_0-20190528-C [66] with following clarifications:

   a) shall set the Host header field to a hostname identifying the message store function;

   b) shall include a valid MCData access token in the HTTP Authorization header; and

   c) shall send the HTTP POST request, identifying source objects and/or folder(s) to be moved to the designated destination folder, towards the message store function.

Upon receipt of a HTTP response, the message store client shall follow the procedure as described in subclause 6.19.2 of OMA-TS-REST_NetAPI_NMS-V1_0-20190528-C [66].

[TS 24.282 clause 21.2.7.1]

To delete a folder in message store using the message store function, the message store client, acting as an HTTP client shall follow the procedure described in subclause 6.14 of OMA-TS-REST_NetAPI_NMS-V1_0-20190528-C [66] with following clarification:

1) shall generate an HTTP DELETE request as specified in subclause 6.14.6 of OMA-TS-REST_NetAPI_NMS-V1_0-20190528-C [66] with following clarifications:

   a) shall set the Host header field to a hostname identifying the message store function;

   b) shall include a valid MCData access token in the HTTP Authorization header; and

   c) shall send the HTTP DELETE request identifying the folder to be deleted towards the message store function.

Upon receipt of a HTTP response, the message store client should follow the procedure as described in subclause 6.14.2 of OMA-TS-REST_NetAPI_NMS-V1_0-20190528-C [66].

6.8.2.3 Test description

6.8.2.3.1 Pre-test conditions

Test configuration:

- Single cell configuration according to TS 36.879-1 [2] clause 5.2.2.2.1.

Preamble:

- The UE has performed procedure 'Initial registration' as described in TS 36.879-1 [2] clause 5.4.2.
- UE States at the end of the preamble:
  - The UE is in RRC_IDLE state.
  - The client is registered for MCData.

6.8.2.3.2 Test procedure sequence

Table 6.8.2.3.2-1: Main Behaviour

St	Procedure	Message Sequence		TP	Verdict
		U - S	Message		
1	Make the UE (MCData client) search for information about the main folder in the message store. (NOTE 1)	-	-	-	-
2	Check: Does the UE (MCData client) correctly perform procedure **'Message Store Function Post Request using HTTP'** as described in TS 37.579-1 [2] Table 5.3C.17.2-1 to search for information about the main folder in the message store?	-	-	1	P
3	Make the UE (MCData client) create folder "Folder1" in the message store. (NOTE 1)	-	-	-	-
4	Check: Does the UE (MCData client) correctly perform procedure **'Message Store Function Object Upload or Creation using HTTP'** as described in TS 37.579-1 [2] Table 5.3C.14.2-1 to create a folder in the message store?	-	-	2	P
5	Make the UE (MCData client) upload an object, test file 1 (ANNEX A.2.1), to the message store in the new created folder "Folder1". (NOTE 1)	-	-	-	-
6	Check: Does the UE (MCData client) correctly perform procedure **'Message Store Function Object Upload or Creation using HTTP'** as described in TS 37.579-1 [2] Table 5.3C.14.2-1 to upload an object to the message store?	-	-	3	P
7	Make the UE (MCData client) create another folder "Folder2" in the message store. (NOTE 1)	-	-	-	-
8	Check: Does the UE (MCData client) correctly perform procedure **'Message Store Function Object Upload or Creation using HTTP'** as described in TS 37.579-1 [2] Table 5.3C.14.2-1 to create a folder in the message store?	-	-	2	P
9	Make the UE (MCData client) copy an object, test file 1 (ANNEX A.2.1), from Folder1 to Folder2 in the message store. (NOTE 1)	-	-	-	-
10	Check: Does the UE (MCData client) correctly perform procedure **'Message Store Function Post Request using HTTP'** as described in TS 37.579-1 [2] Table 5.3C.17.2-1 to copy an object, test file 1 (ANNEX A.2.1), from Folder1 to Folder2 in the message store?	-	-	4	P
11	Make the UE (MCData client) retrieve all information about the main folder in the message store. (NOTE 1, 2)	-	-	-	-
12	Check: Does the UE (MCData client) correctly perform procedure **'Message Store Function Retrieve using HTTP'** as described in TS 37.579-1 [2] Table 5.3C.16.2-1 to search for information about the main folder in the message store?	-	-	5	P
13	Make the UE (MCData client) move a folder and its contents, Folder2, into Folder1 in the message store. (NOTE 1)	-	-	-	-
14	Check: Does the UE (MCData client) correctly perform procedure **'Message Store Function Post Request using HTTP'** as described in TS 37.579-1 [2] Table 5.3C.17.2-1 to move a folder and its contents, Folder2, into Folder1 in the message store?	-	-	6	P

15	Make the UE (MCData client) delete a folder, Folder1, including all the contained folders and objects. (NOTE 1)	-	-	-	-
16	Check: Does the UE (MCData client) correctly perform procedure **'Message Store Function Delete using HTTP'** as described in TS 37.579-1 [2] Table 5.3C.15.2-1 to delete a folder in the message store?	-	-	7	P
NOTE 1: This is expected to be done via a suitable implementation dependent MMI. NOTE 2: "all information" means the main folder's subfolders and objects ⇒ the HTTP GET request shall have the query string "listFilter" set to "All".					

6.8.2.3.3 Specific message contents

Table 6.8.2.3.3-1: HTTP POST from the UE (Step 2, Table 6.8.2.3.2-1; step 2, TS 37.579-1 [2] Table 5.3C.17.2-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.4.3-1, condition MSG_STORE				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Request-Line				
Request-URI				
uri	tsc_MCData_MsgSF_BaseURL & "/folders/operations/search"	URI addressing the search operation		
Content-Type				
media-type	"application/xml"			
SelectionCriteria			RESTful Network API for NMS [40], clauses 6.8, 6.16 and XML schema defined in [48]	
fromCursor	Not present			
maxEntries	any value	the maximum number of entries in the response		
searchCriteria				
criterion [1]				
type	attribute			
name	"Root"			
value	"Yes"			
operator	Not present			
searchScope	Not present			
nonRecursiveScope	Not present			
sortCriteria	Not present			
inlineImdn	Not present			

Table 6.8.2.3.3-2: HTTP 200 (OK) from the SS (step 2, Table 6.8.2.3.2-1; step 3, TS 37.579-1 [2] Table 5.3C.17.2-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.4.6-1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Content-Type				
media-type	"application/xml"			
Message-body: NMS folderList			RESTful Network API for NMS [40], clauses 6.8, 6.16 and XML schema defined in [48]	
folder [1]			RESTful Network API for NMS [40], clause 5.3.2.8 and XML schema defined in [48]	
parentFolder	Not present	root folder does not have parent		
parentFolderPath	Not present	root folder does not have parent		
attributes				
attribute[1]				
name	"Root"			
value	"True"			
resourceURL	tsc_MCData_MsgSF_AbsoluteBaseURL & "/folders/folderId0000"	"folderId0000" arbitrarily selected as id of the root folder		
path	"/main"	arbitrarily selected		
name	Not present			
lastModSeq	555	arbitrarily selected		
cursor	Not present			
subFolders	empty list	The root folder is assumed to be empty		
objects	empty list	The root folder is assumed to be empty		

Table 6.8.2.3.3-3: HTTP POST from the UE (Step 4, Table 6.8.2.3.2-1; step 2, TS 37.579-1 [2] Table 5.3C.14.2-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.4.3-1, condition MSG_STORE				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Request-Line				
Request-URI				
uri	tsc_MCData_MsgSF_BaseURL & "/folders"			
Content-Type				
media-type	"application/xml"			
Message-body: NMS Folder			RESTful Network API for NMS [40], clause 6.13 and clause 5.3.2.8 and XML schema defined in [48]	
parentFolder	tsc_MCData_MsgSF_BaseURL & "/folders/folderId0000" (NOTE 1)	resourceURL of the root folder as provided to the client at step 2		
parentFolderPath	"/main" if present (NOTE 1)	path of the root folder as provided to the client at step 2		
attributes	any value if present	Attributes are not checked		
resourceURL	Not present	shall not be included in POST requests by the client		
path	Not present	shall not be included in POST requests by the client		
name	"Folder1"	According to step 3		
lastModSeq	Not present			
cursor	Not present			
subFolders	Not present			
objects	Not present			
NOTE 1: Either parentFolder or parentFolderPath shall be present				

Table 6.8.2.3.3-4: HTTP 201 Created from the SS (step 4, Table 6.8.2.3.2-1; step 2, TS 37.579-1 [2] Table 5.3C.14.2-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.4.7-1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Location				
uri	tsc_MCData_MsgSF_BaseURL & "/folders/folderId0001"	"folderId0001" arbitrarily selected		
Content-Type				
media-type	"application/xml"			
Message-body: NMS Reference			RESTful Network API for NMS [40], clause 6.13 and XML schema defined in [48]	
resourceURL	tsc_MCData_MsgSF_AbsoluteBaseURL & "/folders/folderId0001"	same as in Location		
path	"/main/Folder1"	arbitrarily selected		

Table 6.8.2.3.3-5: HTTP POST from the UE (Step 6, Table 6.8.2.3.2-1; step 2, TS 37.579-1 [2] Table 5.3C.14.2-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.4.3-1, condition MSG_STORE				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Request-Line				
Request-URI				
uri	tsc_MCData_MsgSF_BaseURL & "/objects"			
Content-Type				
media-type	"multipart/form-data"		RFC 2388 [43]	
Message-body				
MIME body part		**Object**		
MIME-part-headers				
MIME-Content-Type	"application/xml"			
MIME-Content-Disposition				
type	form-data		RESTful Network API common [42] clause 5.7	
param	name=”root-fields”		RESTful Network API common [42] clause 5.7	
MIME-part-body				
NMS Object			RESTful Network API for NMS [40], clause 5.3.2.1 and XML schema defined in [48]	
parentFolder	tsc_MCData_MsgSF_BaseURL & "/folders/folderId0001" (NOTE 1)			
parentFolderPath	"/main/Folder1" (NOTE 1)			
attributes	empty list			
flags	empty list			
imdns	Not present			
resourceURL	Not present			
path	Not present			
payloadURL	Not present			
payloadPart	Not present			
lastModSeq	Not present			
correlationId	Any value if present			
correlationTag	Any value if present			
MIME body part		**File content**		
MIME-part-headers				
MIME-Content-Type	"application/octet-stream"			
MIME-Content-Disposition				
type	attachments		RESTful Network API common [42] clause 5.7	
param	filename with any value		RESTful Network API common [42] clause 5.7	
MIME-part-body	binary data representing the file			
NOTE 1: Either parentFolder or parentFolderPath shall be present				

Table 6.8.2.3.3-6: HTTP 201 Created from the SS (step 6, Table 6.8.2.3.2-1; step 3, TS 37.579-1 [2] Table 5.3C.14.2-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.4.7-1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Location			RESTful Network API for NMS [40], clause 6.1 and XML schema defined in [48]	
uri	tsc_MCData_MsgSF_AbsoluteBaseURL & "/objects/objectId0001"	"objectId0001" arbitrarily selected		
Content-Type				
media-type	"application/xml"			
Message-body: NMS Reference				
resourceURL	tsc_MCData_MsgSF_AbsoluteBaseURL & "/objects/objectId0001"	same as in Location		
path	"main/Folder1/test-file-1"	"test-file-1" arbitrarily selected		

Table 6.8.2.3.3-7: HTTP POST from the UE (Step 8, Table 6.8.2.3.2-1; step 2, TS 37.579-1 [2] Table 5.3C.14.2-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.4.3-1, condition MSG_STORE				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Request-Line				
Request-URI				
uri	tsc_MCData_MsgSF_BaseURL & "/folders"			
Content-Type				
media-type	"application/xml"			
Message-body: NMS Folder			RESTful Network API for NMS [40], clause 6.13 and clause 5.3.2.8 and XML schema defined in [48]	
parentFolder	tsc_MCData_MsgSF_BaseURL & "/folders/folderId0000" (NOTE 1)	resourceURL of the root folder as provided to the client at step 2		
parentFolderPath	"/main" if present (NOTE 1)	path of the root folder as provided to the client at step 2		
attributes	any value if present	Attributes are not checked		
resourceURL	Not present	shall not be included in POST requests by the client		
path	Not present	shall not be included in POST requests by the client		
name	"Folder2"	According to step 7		
lastModSeq	Not present			
cursor	Not present			
subFolders	Not present			
objects	Not present			
NOTE 1: Either parentFolder or parentFolderPath shall be present				

Table 6.8.2.3.3-8: HTTP 201 Created from the SS (step 8, Table 6.8.2.3.2-1; step 3, TS 37.579-1 [2] Table 5.3C.14.2-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.4.7-1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Location				
uri	tsc_MCData_MsgSF_BaseURL & "/folders/folderId0002"	"folderId0002" arbitrarily selected		
Content-Type				
media-type	"application/xml"			
Message-body: NMS Reference			RESTful Network API for NMS [40], clause 6.13 and XML schema defined in [48]	
resourceURL	tsc_MCData_MsgSF_AbsoluteBaseURL & "/folders/folderId0002"	same as in Location		
path	"/main/Folder2"	arbitrarily selected		

Table 6.8.2.3.3-9: HTTP POST from the UE (Step 10, Table 6.8.2.3.2-1; step 2, TS 37.579-1 [2] Table 5.3C.17.2-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.4.3-1, condition MSG_STORE				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Request-Line				
Request-URI				
uri	tsc_MCData_MsgSF_BaseURL & "/folders/operations/copyToFolder"	URI addressing the copy-to operation		
Content-Type				
media-type	"application/xml"			
Message-body: NMS targetSourceRef			RESTful Network API for NMS [40], clause 6.18 and XML schema defined in [48]	
targetRef				
resourceURL	tsc_MCData_MsgSF_AbsoluteBaseURL & "/folders/folderId0002"			
path	"/main/Folder2" if present			
sourceRefs				
folders	empty list			
objects				
objectReference[1]				
resourceURL	tsc_MCData_MsgSF_AbsoluteBaseURL & "/objects/objectId0001"			
path	"main/Folder1/test-file-1" if present			

Table 6.8.2.3.3-10: HTTP 200 (OK) from the SS (step 10, Table 6.8.2.3.2-1; step 3, TS 37.579-1 [2] Table 5.3C.17.2-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.4.6-1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Content-Type				
media-type	"application/xml"			
Message-body: NMS bulkResponseList			RESTful Network API for NMS [40], clause 6.18 and XML schema defined in [48]	
allSuccess	"true"			
Response [1]				
code	"200"			
reason	"OK"			
success				
resourceURL	tsc_MCData_MsgSF_AbsoluteBaseURL & "/objects/objectId0002"	"objectId0002" arbitrarily selected		
path	"main/Folder2/test-file-1"			
cursor	Not present			

Table 6.8.2.3.3-11: HTTP GET from the UE (Step 12, Table 6.8.2.3.2-1; step 2, TS 37.579-1 [2] Table 5.3C.16.2-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.4.2-1, condition MSG_STORE				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Request-Line				
Request-URI				
uri	tsc_MCData_MsgSF_BaseURL & "/folders/folderId0000"	URI addressing the root folder		
query	"&" separated list of query strings containing "listFilter=All"	NOTE: "listFilter=All" shall be achieved by an appropriate MMI	RESTful Network API for NMS [40], clause 6.14.3 and XML schema defined in [48]	

Table 6.8.2.3.3-12: HTTP 200 (OK) from the SS (step 12, Table 6.8.2.3.2-1; step 3, TS 37.579-1 [2] Table 5.3C.16.2-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.4.6-1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Content-Type				
media-type	"application/xml"			
Message-body: NMS Folder		same folder as in the HTTP 200 (OK) at step 2 but with references to the folders created at steps 4 and 8 and with path information removed	RESTful Network API for NMS [40], clause 6.14 and XML schema defined in [48]	
parentFolder	Not present	root folder does not have parent		
parentFolderPath	Not present	root folder does not have parent		
attributes				
attribute[1]				
name	"Root"			
value	"True"			
resourceURL	tsc_MCData_MsgSF_AbsoluteBaseURL & "/folders/folderId0000"			
path	not present	present only if query string "path" is present in the Request URI of the HTTP GET		
name	Not present			
lastModSeq	555			
cursor	Not present			
subFolders	empty list	The root folder is assumed to be empty		
folderReference[1]		Folder1		
resourceURL	tsc_MCData_MsgSF_AbsoluteBaseURL & "/objects/objectId0001"			
path	Not present			
folderReference[2]		Folder1		
resourceURL	tsc_MCData_MsgSF_AbsoluteBaseURL & "/objects/objectId0002"			
path	Not present			
objects	empty list	there are no objects in the root folder		

Table 6.8.2.3.3-13: HTTP POST from the UE (Step 14, Table 6.8.2.3.2-1; step 2, TS 37.579-1 [2] Table 5.3C.17.2-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.4.3-1, condition MSG_STORE				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Request-Line				
Request-URI				
uri	tsc_MCData_MsgSF_BaseURL & "/folders/operations/moveToFolder"	URI addressing the move-to operation		
Content-Type				
media-type	"application/xml"			
Message-body: NMS targetSourceRef			RESTful Network API for NMS [40], clause 6.19 and XML schema defined in [48]	
targetRef				
resourceURL	tsc_MCData_MsgSF_AbsoluteBaseURL & "/folders/folderId0001"	Folder 1		
path	"/main/Folder1" if present			
sourceRefs				
folders				
folderReference[1]		Folder 2		
resourceURL	tsc_MCData_MsgSF_AbsoluteBaseURL & "/folders/folderId0002"			
path	"/main/Folder2" if present			

Table 6.8.2.3.3-14: HTTP 200 (OK) from the SS (step 14, Table 6.8.2.3.2-1; step 3, TS 37.579-1 [2] Table 5.3C.17.2-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.4.6-1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Content-Type				
media-type	"application/xml"			
Message-body: NMS bulkResponseList			RESTful Network API for NMS [40], clause 6.19 and XML schema defined in [48]	
allSuccess	"true"			
Response [1]				
code	"200"			
reason	"OK"			
success				
resourceURL	tsc_MCData_MsgSF_AbsoluteBaseURL & "/folders/folderId0002"			
path	"main/Folder1/Folder2"			
cursor	Not present			

Table 6.8.2.3.3-15: HTTP DELETE from the UE (Step 16, Table 6.8.2.3.2-1; step 2, TS 37.579-1 [2] Table 5.3C.15.2-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.4.5-1, condition MSG_STORE				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Request-Line				
Request-URI				
uri	tsc_MCData_MsgSF_BaseURL & "/folders/folderId0001"	URI addressing the Folder1		

6.8.3 On-network / MCData Message Store / Subscription / Create a subscription to notifications / Update a subscription to notifications / Delete a subscription to notifications

6.8.3.1 Test Purpose (TP)

(1)

```
with { UE (MCData Client)registered and authorized for MCData service }
ensure that {
  when { the MCDATA User requests to create a subscription to notifications about changes in the
message store using the Message Store Function }
    then { UE (MCData Client) requests create a subscription to notifications about changes in the
message store using the Message Store Function via an HTTP POST message }
            }
```

(2)

```
with { UE (MCData Client)registered and authorized for MCData service }
ensure that {
  when { the MCDATA User requests to update a subscription to notifications about changes in the
message store using the Message Store Function }
    then { UE (MCData Client) requests to update a subscription to notifications about changes in
the message store using the Message Store Function via an HTTP POST message }
            }
```

(3)

```
with { UE (MCData Client)registered and authorized for MCData service }
ensure that {
  when { the MCDATA User requests to delete a subscription to notifications about changes in the
message store using to the Message Store Function }
    then { UE (MCData Client) requests to delete a subscription to notifications about changes in
the message store using the Message Store Function via an HTTP DELETE message }
            }
```

6.8.3.2 Conformance requirements

References: The conformance requirements covered in the current TC are specified in: TS 24.282, clauses 21.2.12A.1, 21.2.14A.1, 21.2.13A.1. Unless otherwise stated, these are Rel-16 requirements.

[TS 24.282 clause 21.2.12A.1]

In order for the message store client to keep its local store in sync with the MCData message store, it needs to receive notifications about changes in the message store. For this purpose, the message store client would need to subscribe to notification from the message store, Synchronization using subscriptions and notifications is described in clause 5.1.5.1 of OMA-TS-REST_NetAPI_NMS-V1_0-20190528-C [66].

To create a subscription to notifications about changes in the message store using the message store function, the message store client, acting as an HTTP client shall follow the procedure described in clause 6.20 of OMA-TS-REST_NetAPI_NMS-V1_0-20190528-C [66] with the following clarification:

1) shall generate an HTTP POST request as specified in subclause 6.20.5 of OMA-TS-REST_NetAPI_NMS-V1_0-20190528-C [66] with the following clarifications:

   a) shall set the Host header field to a hostname identifying the message store function; and

   b) shall include a valid MCData access token in the HTTP Authorization header; and

2) shall send the HTTP POST request towards the message store function.

Upon receipt of an HTTP response, the message store client should follow the procedure as described in clause 6.20.2 of OMA-TS-REST_NetAPI_NMS-V1_0-20190528-C [66].

[TS 24.282 clause 21.2.14A.1]

A client may update its subscription to notification in order to:

1) extend the life of the subscription;

2) restart the notification stream from where it left off.

Synchronization using subscriptions and notifications is described in clause 5.1.5.1 of OMA-TS-REST_NetAPI_NMS-V1_0-20190528-C [66]

To update a subscription to notifications about changes in the message store using the message store function, the message store client, acting as an HTTP client shall follow the procedure described in clause 6.21 of OMA-TS-REST_NetAPI_NMS-V1_0-20190528-C [66] the with following clarification:

1) shall generate an HTTP POST request as specified in clause 6.21.5 of OMA-TS-REST_NetAPI_NMS-V1_0-20190528-C [66] with the following clarifications:

   a) shall set the Host header field to a hostname identifying the message store function;

   b) shall include a valid MCData access token in the HTTP Authorization header; and

2) shall send the HTTP POST request towards the message store function.

Upon receipt of an HTTP response, the message store client should follow the procedure described in clause 6.21.2 of OMA-TS-REST_NetAPI_NMS-V1_0-20190528-C [66].

[TS 24.282 clause 21.2.13A.1]

To delete / cancel a subscription and stop corresponding notifications about changes in the message store using the message store function, the message store client, acting as an HTTP client shall follow the procedure described in clause 6.21 of OMA-TS-REST_NetAPI_NMS-V1_0-20190528-C [66] with the following clarification:

1) shall generate an HTTP DELETE request as specified in subclause 6.21.6 of OMA-TS-REST_NetAPI_NMS-V1_0-20190528-C [66] with the following clarifications:

   a) shall set the Host header field to a hostname identifying the message store function;

   b) shall include a valid MCData access token in the HTTP Authorization header; and

2) shall send the HTTP DELETE request identifying the subscription to be deleted towards the message store function.

Upon receipt of an HTTP response, the message store client should follow the procedure as described in clause 6.21.2 of OMA-TS-REST_NetAPI_NMS-V1_0-20190528-C [66].

6.8.3.3 Test description

6.8.3.3.1 Pre-test conditions

Test configuration:

- Single cell configuration according to TS 36.879-1 [2] clause 5.2.2.2.1.

Preamble:

- The UE has performed procedure 'Initial registration' as described in TS 36.879-1 [2] clause 5.4.2.
- UE States at the end of the preamble:
  - The UE is in RRC_IDLE state.
  - The client is registered for MCData.

6.8.3.3.2 Test procedure sequence

Table 6.8.3.3.2-1: Main Behaviour

St	Procedure	Message Sequence		TP	Verdict
		U - S	Message		
1	Make the UE (MCData client) create a subscription to notifications about changes in the message store function. (NOTE 1)	-	-	-	-
2	Check: Does the UE (MCData client) correctly perform procedure **'Message Store Function Object Upload using HTTP'** as described in TS 37.579-1 [2] Table 5.3C.14.2-1 to create a subscription to notifications about changes in the message store function?	-	-	1	P
3	Make the UE (MCData client) update the duration of the subscription created at step 2 to 10800 seconds. (NOTE 1)	-	-	-	-
4	Check: Does the UE (MCData client) correctly perform procedure **'Message Store Function Post Request using HTTP'** as described in TS 37.579-1 [2] Table 5.3C.17.2-1 to update a subscription to notifications about changes in the message store function?	-	-	2	P
5	Make the UE (MCData client) delete the subscription created at step 2. (NOTE 1)	-	-	-	-
6	Check: Does the UE (MCData client) correctly perform procedure **'Message Store Function Delete using HTTP'** as described in TS 37.579-1 [2] Table 5.3C.15.2-1 to delete a subscription to notifications about changes in the message store function?	-	-	3	P
NOTE 1: This is expected to be done via a suitable implementation dependent MMI.					

6.8.3.3.3 Specific message contents

Table 6.8.3.3.3-1: HTTP POST from the UE (Step 2, Table 6.8.3.3.2-1; step 2, TS 37.579-1 [2] Table 5.3C.14.2-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.4.3-1, condition MSG_STORE				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Request-Line				
Request-URI				
uri	tsc_MCData_MsgSF_BaseURL & "subscriptions"			
Content-Type				
media-type	"application/xml"			
Message-body: NMS nmsSubscription			RESTful Network API for NMS [40], clauses 6.20 and XML schema defined in [48]	
callbackReference				
notifyURL	any valid absolute http URI with hostname and path	URL provided by the client to be used in HTTP POST requests of notifications; e.g. "http://nmsClient.3gpp.org/nms/notifications"		
callbackData	any value if present			
notificationFormat	"XML" ifpresent	XML if not present		
duration	any value if present			
filter	Not present	(NOTE 1)		
clientCorrelator	any value if present			
resourceURL	Not present	shall not be included in POST requests by the client		
index	Not present	shall not be included in requests by the client		
restartToken	any value if present			
maxEvents	any value if present			
objectAttributeNames	Not present			
inlineImdn	false ifpresent			
NOTE 1 It is assumed that the MMI at step 1 does not require/provide any filter				

Table 6.8.3.3.3-2: HTTP 201 Created from the SS (step 2, Table 6.8.3.3.2-1; step 3, TS 37.579-1 [2] Table 5.3C.14.2-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.4.7-1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Location				
uri	tsc_MCData_MsgSF_AbsoluteBaseURL & "/subscriptions/subscriptId0001"	"subscriptId0001" arbitrarily selected		
Content-Type				
media-type	"application/xml"			
Message-body: NMS Subscription			RESTful Network API for NMS [40], clauses 6.20 and XML schema defined in [48]	
callbackReference				
notifyURL	same value as provided by the client in the POST request			
callbackData	Same value as provided by the client if present in the POST request otherwise not present			
notificationFormat	Same value as provided by the client if present in the POST request otherwise not present	Either "XML" or not present		
duration	Same value as provided by the client if present in the POST request otherwise "7200"	7200 seconds if no other value has been provided by the client		
filter	Not present			
clientCorrelator	Same value as provided by the client if present in the POST request otherwise not present			
resourceURL	tsc_MCData_MsgSF_AbsoluteBaseURL & "/subscriptions/subscriptId0001"	same as in Location		
index	1			
restartToken	Same value as provided by the client if present in the POST request otherwise not present			
maxEvents	Same value as provided by the client if present in the POST request otherwise "5"	"5" arbitrarily selected		
objectAttributeNames	Not present			
inlineImdn	Same value as provided by the client if present in the POST request otherwise not present	Either "false" or not present		

Table 6.8.3.3.3-3: HTTP POST from the UE (Step 4, Table 6.8.3.3.2-1; step 2, TS 37.579-1 [2] Table 5.3C.17.2-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.4.3-1, condition MSG_STORE				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Request-Line				
Request-URI				
uri	tsc_MCData_MsgSF_BaseURL & "subscriptions/subscriptId0001"			
Content-Type				
media-type	"application/xml"			
Message-body: NMS nmsSubscriptionUpdate			RESTful Network API for NMS [40], clauses 6.21 and XML schema defined in [48]	
duration	"10800"			
restartToken	Not present			

Table 6.8.3.3.3-4: HTTP 200 (OK) from the SS (step 4, Table 6.8.3.3.2-1; step 3, TS 37.579-1 [2] Table 5.3C.17.2-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.4.6-1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Content-Type				
media-type	"application/xml"			
Message-body: NMS nmsSubscription	Same nmsSubscription as specified in Table 6.8.3.3.3-2 with modification of the <duration> element as shown below		RESTful Network API for NMS [40], clauses 6.21 and XML schema defined in [48]	
duration	"10800"			

Table 6.8.3.3.3-5: HTTP DELETE from the UE (Step 6, Table 6.8.3.3.2-1; step 2, TS 37.579-1 [2] Table 5.3C.15.2-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.4.5-1, condition MSG_STORE				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Request-Line				
Request-URI				
uri	tsc_MCData_MsgSF_BaseURL & "subscriptions/subscriptId0001"	The subscription to be deleted		

6.8.4 On-network / MCData Message Store / Synchronization / Synchronization notifications / Search-based synchronization

6.8.4.1 Test Purpose (TP)

(1)

```
with { UE (MCData Client)registered and authorized for MCData service }
ensure that {
```

```
  when { UE (MCData Client) receives a notification about changes in the message store using using
the Message Store Function via an HTTP POST message }
    then { UE (MCData Client) responds with a HTTP 204 (No Content) message }
            }
```

(2)

```
with { UE (MCData Client)registered and authorized for MCData service }
ensure that {
  when { the MCDATA User requests to search for changes in the message store using the Message Store
Function }
    then { UE (MCData Client) requests to search for changes in the message store using the Message
Store Function via an HTTP POST message }
            }
```

6.8.4.2 Conformance requirements

References: The conformance requirements covered in the current TC are specified in: TS 24.282, clauses 21.2.16.2, 21.2.17.1. Unless otherwise stated, these are Rel-16 requirements.

[TS 24.282 clause 21.2.16.2]

Upon receipt of the HTTP POST request from the MCData message store, as per clause 21.2.16.1, the message store client acting as an HTTP server:

1) shall process the HTTP POST request by following the procedures described in clause 6.22.5 of OMA-TS-REST_NetAPI_NMS-V1_0-20190528-C [66]; and

   a) either use the notification content and the reported "restartToken" and "index" as specified in clause 5.1.5.1 of OMA-TS-REST_NetAPI_NMS-V1_0-20190528-C [66] to have the client's local message store updated accordingly; or

   b) use the notification as a trigger to subsequently search the MCData message store for the list of changes as specified in clause 21.2.11.1; and

2) shall generate and send an HTTP response towards the message store function indicating the result of the operation as per clause 6.22.2 of OMA-TS-REST_NetAPI_NMS-V1_0-20190528-C [66].

NOTE: The notifications about changes in the MCData message store can be used by the message store client to synchronize its local message store with the MCData message store in two distinguished ways which are listed in sub-bullets "a" and "b" above.

[TS 24.282 clause 21.2.17.1]

To search for changes (e.g. newly created objects, recently deleted objects, etc) in the MCData message store using the message store function, the message store client, acting as an HTTP client shall follow the procedure described in clause 21.2.2.1 with following clarification:

1) shall use the search criterion of "CreatedObjects", "VanishedObjects" or "Flag" in the HTTP POST request as specified in clause 5.1.5.2 and 5.4.2.2 of OMA-TS-REST_NetAPI_NMS-V1_0-20190528-C [66] in order to retrieve from the message store the list of the newly created object, recently deleted object and/or changes to flags respectively.

6.8.4.3 Test description

6.8.4.3.1 Pre-test conditions

Test configuration:

- Single cell configuration according to TS 36.879-1 [2] clause 5.2.2.2.1.

Preamble:

- The UE has performed procedure 'Initial registration' as described in TS 36.879-1 [2] clause 5.4.2.

- UE States at the end of the preamble:
  - The UE is in RRC_IDLE state.
  - The client is registered for MCData.

6.8.4.3.2 Test procedure sequence

Table 6.8.4.3.2-1: Main Behaviour

St	Procedure	Message Sequence		TP	Verdict
		U - S	Message		
1	Make the UE (MCData client) create a subscription to notifications about changes in the message store function. (NOTE 1)	-	-	-	-
2	The UE (MCData client) correctly performs procedure **'Message Store Function Object Upload using HTTP'** as described in TS 37.579-1 [2] Table 5.3C.14.2-1 to create a subscription to notifications about changes in the message store function?	-	-	-	-
3	Check: Does the UE (MCData client) correctly perform procedure **'Message Store Function Post Notification using HTTP'** as described in TS 37.579-1 [2] Table 5.3C.19.2-1 for notifications of changes in the message store using the message store function?	-	-	1	P
4	Make the UE (MCData client) search for recently created objects. (NOTE 1)	-	-	-	-
5	Check: Does the UE (MCData client) correctly perform procedure **'Message Store Function Post Request using HTTP'** as described in TS 37.579-1 [2] Table 5.3C.17.2-1 to search for changes in the message store function?	-	-	2	P
6	Make the UE (MCData client) delete the subscription created at step 2. (NOTE 1)	-	-	-	-
7	The UE (MCData client) correctly perform procedure **'Message Store Function Delete using HTTP'** as described in TS 37.579-1 [2] Table 5.3C.15.2-1 to delete a subscription to notifications about changes in the message store function?	-	-	-	-
NOTE 1: This is expected to be done via a suitable implementation dependent MMI.					

6.8.4.3.3 Specific message contents

Table 6.8.4.3.3-1: HTTP POST from the UE (Step 2, Table 6.8.4.3.2-1; step 2, TS 37.579-1 [2] Table 5.3C.14.2-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.4.3-1, condition MSG_STORE				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Request-Line				
Request-URI				
uri	tsc_MCData_MsgSF_BaseURL & "subscriptions"			
Content-Type				
media-type	"application/xml"			
Message-body: NMS nmsSubscription			RESTful Network API for NMS [40], clauses 6.20 and XML schema defined in [48]	
callbackReference				
notifyURL	any valid absolute http URI with hostname and path	URL provided by the client to be used in HTTP POST requests of notifications; e.g. "http://nmsClient.3gpp.org/nms/notifications"		
callbackData	any value if present			
notificationFormat	"XML" ifpresent	XML if not present		
duration	any value if present			
filter	Not present	(NOTE 1)		
clientCorrelator	any value if present			
resourceURL	Not present	shall not be included in POST requests by the client		
index	Not present	shall not be included in requests by the client		
restartToken	any value if present			
maxEvents	any value if present			
objectAttributeNames	Not present			
inlineImdn	false ifpresent			
NOTE 1 It is assumed that the MMI at step 1 does not require/provide any filter				

Table 6.8.4.3.3-2: HTTP 201 Created from the SS (step 2, Table 6.8.4.3.2-1; step 3, TS 37.579-1 [2] Table 5.3C.14.2-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.4.7-1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Location				
uri	tsc_MCData_MsgSF_AbsoluteBaseURL & "/subscriptions/subscriptId0001"	"subscriptId0001" arbitrarily selected		
Content-Type				
media-type	"application/xml"			
Message-body: NMS nmsSubscription			RESTful Network API for NMS [40], clauses 6.20 and XML schema defined in [48]	
callbackReference				
notifyURL	same value as provided by the client in the POST request			
callbackData	Same value as provided by the client if present in the POST request otherwise not present			
notificationFormat	Same value as provided by the client if present in the POST request otherwise not present	Either "XML" or not present		
duration	Same value as provided by the client if present in the POST request otherwise "7200"	7200 seconds if no other value has been provided by the client		
filter	Not present			
clientCorrelator	Same value as provided by the client if present in the POST request otherwise not present			
resourceURL	tsc_MCData_MsgSF_AbsoluteBaseURL & "/subscriptions/subscriptId0001"	same as in Location		
index	1			
restartToken	Same value as provided by the client if present in the POST request otherwise not present			
maxEvents	Same value as provided by the client if present in the POST request otherwise "5"	"5" arbitrarily selected		
objectAttributeNames	Not present			
inlineImdn	Same value as provided by the client if present in the POST request otherwise not present	Either "false" or not present		

Table 6.8.4.3.3-3: HTTP POST from the SS (Step 3, Table 6.8.4.3.2-1; step 2, TS 37.579-1 [2] Table 5.3C.19.2-1)

Derivation Path: RFC 2616 [44]				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Request-Line				
Method	"POST"			
Request-URI				
uri	URI path provided by the client as part of the <notifyURL> at subscription in step 2			
HTTP-Version	"HTTP/1.1"			
Accept				
media-range[1]	"application/xml"			
Host				
host	host name provided by the client as part of the <notifyURL> at subscription in step 2	hostname identifying the client	TS 24.282 [87], clause 21.2.16.1	
port	not present			
Content-Type				
media-type	"application/xml"			
Message-body: NMS nmsEventList			RESTful Network API for NMS [40], clauses 6.22 and XML schema defined in [48]	
nmsEvent[1]				
changedObject		object creation		
parentFolder	tsc_MCData_MsgSF_AbsoluteBaseURL & "/folders/folderId0000"	"folderId0000" arbitrarily selected		
flags	empty list			
imdns	Not present			
resourceURL	tsc_MCData_MsgSF_AbsoluteBaseURL & "/objects/objectId0001"	"objectId0001" arbitrarily selected		
attributes	Not present			
lastModSeq	"135"	arbitrarily selected		
correlationId	Not present			
correlationTag	Not present			
callBackData	same as in Table 6.8.4.3.3-2			
index	1			
restartToken	same as in Table 6.8.4.3.3-2			
link[1]				
rel	"NmsSubscription"			
hrel	tsc_MCData_MsgSF_AbsoluteBaseURL & "/subscriptions/subscriptId0001"			

Table 6.8.4.3.3-4: HTTP POST from the UE (Step 5, Table 6.8.4.3.2-1; step 2, TS 37.579-1 [2] Table 5.3C.17.2-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.4.3-1, condition MSG_STORE				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Request-Line				
Request-URI				
uri	tsc_MCData_MsgSF_BaseURL & "/objects/operations/search"			
Content-Type				
media-type	"application/xml"			
Message-body: NMS SelectionCriteria			RESTful Network API for NMS [40], clauses 6.8 and XML schema defined in [48]	
fromCursor	Not present			
maxEntries	any value			
searchCriteria				
Criterion [1]				
type	CreatedObjects			
name	Not present			
value	""	Searching for existing objects that were created in the store since a previous CreatedObjects search.		
operator	Not present			
searchScope	Not present			
nonRecursiveScope	Not present			
sortCriteria	Not present			
inlineImdn	Not present			

Table 6.8.4.3.3-5: HTTP 200 (OK) from the SS (step 5, Table 6.8.4.3.2-1; step 3, TS 37.579-1 [2] Table 5.3C.17.2-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.4.6-1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Content-Type				
media-type	"application/xml"			
Message-body: NMS ObjectList				
Object [1]				
parentFolder	tsc_MCData_MsgSF_AbsoluteBaseURL & "/folders/folderId0000"	as in create object in Table 6.8.4.3.3-3		
attributes	empty list			
flags	empty list			
imdns	Not present			
resourceURL	tsc_MCData_MsgSF_AbsoluteBaseURL & "/objects/objectId0001"	as in create object in Table 6.8.4.3.3-3		
path	Not present			
payloadURL	Not present			
payloadPart	Not present			
lastModSeq	"135"	as in create object in Table 6.8.4.3.3-3		
correlationId	Not present			
correlationTag	Not present			

Table 6.8.4.3.3-6: HTTP DELETE from the UE (Step 7, Table 6.8.4.3.2-1; step 2, TS 37.579-1 [2] Table 5.3C.15.2-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.4.5-1, condition MSG_STORE				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Request-Line				
Request-URI				
uri	tsc_MCData_MsgSF_BaseURL & "subscriptions/subscriptId0001"	The subscription to be deleted		

6.8.5 On-network / MCData Message Store / Notification Channel / Create / Open / Update / Delete

6.8.5.1 Test Purpose (TP)

(1)

```
with { UE (MCData Client)registered and authorized for MCData service }
ensure that {
  when { the MCDATA User requests to create a notification channel for PULL notification delivery
method }
    then { UE (MCData Client) requests to create a notification channel by sending an HTTP POST
message }
            }
```

(2)

```
with { UE (MCData Client)registered and authorized for MCData service }
ensure that {
  when { the MCDATA User requests to update a notification channel }
    then { UE (MCData Client) requests to update a notification channelby sending an HTTP PUT
message }
            }
```

(3)

```
with { UE (MCData Client)registered and authorized for MCData service }
ensure that {
  when { the MCDATA User requests to open a notification channel }
    then { UE (MCData Client) requests to open a notification channel by sending an HTTP POST
message }
            }
```

(4)

```
with { UE (MCData Client)registered and authorized for MCData service }
ensure that {
  when { the MCDATA User requests to delete a notification channel }
    then { UE (MCData Client) requests to delete a notification channel by sending an HTTP DELETE
message }
            }
```

6.8.5.2 Conformance requirements

References: The conformance requirements covered in the current TC are specified in: TS 24.282, clauses 21.2.19.1, 21.2.20.1, 21.2.21.1 and 21.2.22.1. Unless otherwise stated, these are Rel-17 requirements.

[TS 24.282 clause 21.2.19.1]

To create a notification channel, the Message notification client, acting as an HTTP client shall follow the procedure described in clause 6.1 of OMA-TS-REST_NetAPI_NotificationChannel-V1_0-20200319-C [76] as follows:

1) shall generate an HTTP POST request as specified in clause 6.1.5 of OMA-TS-REST_NetAPI_NotificationChannel-V1_0-20200319-C [76] as follows:

   a) shall set the Host header field to a hostname identifying the MCData Notification server;

   b) shall include a valid MCData access token in the Authorization header; and

   c) shall send the HTTP POST request towards the MCData Notification server.

Upon receipt of an HTTP response, the Message notification client should follow the procedure as described in clause 6.1.2 of OMA-TS-REST_NetAPI_NotificationChannel-V1_0-20200319-C [76].

[TS 24.282 clause 21.2.20.1]

To delete a notification channel, the Message notification client, acting as an HTTP client shall follow the procedure described in clause 6.2 of OMA-TS-REST_NetAPI_NotificationChannel-V1_0-20200319-C [76] as follows:

1) shall generate an HTTP DELETE request as specified in clause 6.2.6 of OMA-TS-REST_NetAPI_NotificationChannel-V1_0-20200319-C [76] with following the clarifications:

   a) shall set the Host header field to a hostname identifying the MCData Notification server;

   b) shall include a valid MCData access token in the Authorization header; and

   c) shall send the HTTP DELETE request towards the MCData Notification server.

Upon receipt of a HTTP response, the Message notification client should follow the procedure as described in clause 6.2.2 of OMA-TS-REST_NetAPI_NotificationChannel-V1_0-20200319-C [76].

NOTE: When the notification channel is deleted, the Message store client normally removes the notification subscription in the MCData Message store function as described in clause 21.2.13A.

[TS 24.282 clause 21.2.21.1]

To update a notification channel's lifetime, the Message notification client, acting as an HTTP client shall follow the procedure described in clause 6.4 of OMA-TS-REST_NetAPI_NotificationChannel-V1_0-20200319-C [76] as follows:

1) shall generate an HTTP PUT request as specified in clause 6.4.4 of OMA-TS-REST_NetAPI_NotificationChannel-V1_0-20200319-C [76] as follows:

   a) shall set the Host header field to a hostname identifying the MCData Notification server;

   b) shall include a valid MCData access token in the Authorization header; and

   c) shall send the HTTP PUT request towards the MCData Notification server.

Upon receipt of an HTTP response, the Message notification client should follow the procedure as described in clause 6.4.2 of OMA-TS-REST_NetAPI_NotificationChannel-V1_0-20200319-C [76].

NOTE: A successful HTTP response includes the new Channel's lifetime duration which can be used by the Message store client to update the lifetime of the notification subscription in the MCData message store function as described in clause 21.2.14A.

[TS 24.282 clause 21.2.22.1]

Based on the channel type created as part of the notification channel creation procedure (see clause 21.2.19. "Create notification channel"), the Message notification client would determine if and how it needs to open (interact with) the created channel for notification flow (i.e. using PULL or PUSH).

To open the notification channel for a PULL notification delivery method (i.e. created channel is of type LongPolling), the Message notification client, acting as an HTTP client shall follow the procedure described in clauses 6.3 of OMA-TS-REST_NetAPI_NotificationChannel-V1_0-20200319-C [76] as follows:

1) shall generate an HTTP POST request as specified in clause 6.3.5 of OMA-TS-REST_NetAPI_NotificationChannel-V1_0-20200319-C [76] as follows:

a) shall set the Host header field to a hostname identifying the Notification server extracted from the channelURL received from the Notification server during channel creation (see clause 21.2.19. "Create notification channel");

b) shall include a valid MCData access token in the Authorization header; and

c) shall send the HTTP POST request towards the MCData Notification server using the channelURL received from the MCData Notification server during channel creation procedure (see clause 21.2.19. "Create notification channel").

Upon receipt of a HTTP response, the Message notification client should follow the procedure as described in clause 6.3.2 of OMA-TS-REST_NetAPI_NotificationChannel-V1_0-20200319-C [76]; and

1) either use the notification content and the reported "restartToken" and "index" as specified in clause 5.1.5.1 of OMA-TS-REST_NetAPI_NMS-V1_0-20190528-C [66] to have the client's local message store updated accordingly; or

2) use the notification as a trigger to subsequently search the MCData message store for the list of changes as specified in clause 21.2.17;

NOTE: The notifications about changes in the MCData message store can be used by the message store client to synchronize its local message store with the MCData message store in two distinguished ways which are listed in bullets "1" and "2" above.

To open the notification channel for a PUSH notification delivery method over WebSocket (i.e. created channel is of type WebSocket), the Message notification client shall follow the procedure described in Appendix I of OMA-TS-REST_NetAPI_NotificationChannel-V1_0-20200319-C [76] and use the channelURL received from the MCData Notification server during the channel creation procedure (see clauses 21.2.19) to create a WebSocket connection with the MCData Notification server. The process of creating a WebSokect connection between the Message notification client and the MCData Notification server through which the MCData Notification server can send notifications to the Message notification client is not RESTful.

If the created channel is of type NativeChannel, the Message notification client, is not required to invoke the "Open notification channel" procedure as defined in this clause. See clauses 5, 5.3.13, 5.3.14 of OMA-TS-REST_NetAPI_NotificationChannel-V1_0-20200319-C [76] for description on receiving notification over a NativeChannel.

6.8.5.3 Test description

6.8.5.3.1 Pre-test conditions

Test configuration:

- Single cell configuration according to TS 36.879-1 [2] clause 5.2.2.2.1.

Preamble:

- The UE has performed procedure 'Initial registration' as described in TS 36.879-1 [2] clause 5.4.2.
- UE States at the end of the preamble:
  - The UE is in RRC_IDLE state.
  - The client is registered for MCData.

6.8.5.3.2 Test procedure sequence

Table 6.8.5.3.2-1: Main Behaviour

St	Procedure	Message Sequence		TP	Verdict
		U - S	Message		
1	Make the UE (MCData client) create a notification channel for a PULL notification delivery methods. (NOTE 1)	-	-	-	-
2	Check: Does the UE (MCData client) correctly perform procedure **'Message Store Function Object Upload using HTTP'** as described in TS 37.579-1 [2] Table 5.3C.14.2-1 to create a notification channel?	-	-	1	P
3	Make the UE (MCData client) update the lifetime of the notification channel created at step 2 to 10800 seconds. (NOTE 1)	-	-	-	-
4	Check: Does the UE (MCData client) correctly perform procedure **'Message Store Function Put Request using HTTP'** as described in TS 37.579-1 [2] Table 5.3C.18.2-1 to update the lifetime of the notification channel?	-	-	2	P
5	Make the UE (MCData client) open the notification channel. (NOTE 1)	-	-	-	-
6	Check: Does the UE (MCData client) correctly perform procedure **'Message Store Function Post Request using HTTP'** as described in TS 37.579-1 [2] Table 5.3C.17.2-1 to open the notification channel?	-	-	3	P
7	Make the UE (MCData client) delete the notification channel created at step 2. (NOTE 1)	-	-	-	-
8	Check: Does the UE (MCData client) correctly perform procedure **'Message Store Function Delete using HTTP'** as described in TS 37.579-1 [2] Table 5.3C.15.2-1 to delete a notification channel?	-	-	4	P
NOTE 1: This is expected to be done via a suitable implementation dependent MMI.					

6.8.5.3.3 Specific message contents

Table 6.8.5.3.3-1: HTTP POST from the UE (Step 2, Table 6.8.5.3.2-1; step 2, TS 37.579-1 [2] Table 5.3C.14.2-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.4.3-1, condition NOTIFICATION_CH				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Request-Line				
Request-URI				
uri	tsc_MCData_NS_BaseURL & "/" & px_MCData_ID_User_A & "/channels"			
Content-Type				
media-type	"application/xml"			
Message-body: NC notificationChannel			RESTful Network API for NC [46], clause 6.1 and XML schema defined in [47].	
clientCorrelator	any value if present			
applicationTag	any value if present			
channelType	LongPolling			
channelData	LongPollingData			
callbackURL	not present			
maxNotifications	1			
maxWaitTime	any value if present			
callbackURL	not present			
resourceURL	not present			
channelLifetime	any value if present			

Table 6.8.5.3.3-2: HTTP 201 Created from the SS (step 2, Table 6.8.5.3.2-1; step 3, TS 37.579-1 [2] Table 5.3C.14.2-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.4.7-1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Location				
uri	tsc_MCData_NS_Base URL & px_MCData_ID_User_A& "/channels/ch123"			
Content-Type				
media-type	"application/xml"			
Message-body: NC notificationChannel			RESTful Network API for NC [46], clause 6.1 and XML schema defined in [47].	
clientCorrelator	Same value as provided by the client if present in the POST request otherwise not present			
applicationTag	Same value as provided by the client if present in the POST request otherwise not present			
channelType	LongPolling			
channelData	LongPollingData			
channelURL	tsc_MCData_NS_Base URL & "/" & px_MCData_ID_User_A& "/channels/ch123/notifications"			
maxNotifications	1			
maxWaitTime	Same value as provided by the client if present in the POST request otherwise not present			
channelLifetime	Same value as provided by the client if present in the POST request otherwise not present			
callbackURL	not present			
resourceURL	tsc_MCData_NS_Base URL & px_MCData_ID_User_A & "/channels/ch123"	same as in Location		

Table 6.8.5.3.3-3: HTTP PUT from the UE (Step 4, Table 6.8.5.3.2-1; step 2, TS 37.579-1 [2] Table 5.3C.18.2-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.4.4-1, condition NOTIFICATION_CH				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Request-Line				
Request-URI				
uri	tsc_MCData_NS_BaseURL & "/" & px_MCData_ID_User_A & "/channels/ch123/channelLifetime"			
Content-Type				
media-type	"application/xml"			
Message-body: NC notificationChannelLifetime			RESTful Network API for NC [46], clause 6.4 and XML schema defined in [47].	
channelLifetime	“10800”			

Table 6.8.5.3.3-4: HTTP 200 (OK) from the SS (step 4, Table 6.8.5.3.2-1; step 3, TS 37.579-1 [2] Table 5.3C.18.2-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.4.6-1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Content-Type				
media-type	"application/xml"			
Message-body: NC notificationChannelLifetime			RESTful Network API for NC [46], clause 6.4 and XML schema defined in [47].	
channelLifetime	"10800"			

Table 6.8.5.3.3-5: HTTP POST from the UE (Step 6, Table 6.8.5.3.2-1; step 2, TS 37.579-1 [2] Table 5.3C.14.2-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.4.3-1, condition NOTIFICATION_CH				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Request-Line				
Request-URI				
uri	tsc_MCData_NS_BaseURL & "/" & px_MCData_ID_User_A & "/channels/ch123/notifications"	Same value as received in the channelURL IE in Table 6.8.5.3.3-2		
Content-Type				
media-type	"application/xml"			
Message-body: NC longPollingRequestParameters			RESTful Network API for NC [46], clause 6.3 and XML schema defined in [47].	

Table 6.8.5.3.3-6: HTTP 200 (OK) from the SS (step 6 Table 6.8.5.3.2-1; step 3, TS 37.579-1 [2] Table 5.3C.18.2-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.4.6-1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Content-Type				
media-type	"application/xml"			
Message-body: NC notificationList	empty list of notifications		RESTful Network API for NC [46], clause 6.3 and XML schema defined in [47].	
ncListComplete	not present			

Table 6.8.5.3.3-7: HTTP DELETE from the UE (Step 8, Table 6.8.5.3.2-1; step 2, TS 37.579-1 [2] Table 5.3C.15.2-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.4.5-1, condition NOTIFICATION_CH				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Request-Line				
Request-URI				
uri	tsc_MCData_NS_Base URL & "/" & px_MCData_ID_User_A& "/channels/ch123"	The notification channel to be deleted		

6.9 Regroup using a preconfigured group

6.9.1 On-network / Regroup using a preconfigured group / Requesting a group regroup using a preconfigured group / Removing a regroup using preconfigured group / Client Originated (CO)

6.9.1.1 Test Purpose (TP)

(1)

```
with { UE (MCData Client) registered and authorised for MCData Service }
ensure that {
  when { UE (MCData Client) receives a request to establish an MCData group regroup using a
preconfigured group }
    then { UE (MCData Client) sends a SIP MESSAGE message to establish an MCData group regroup using
a preconfigured group }
            }
```

(2)

```
with { UE (MCData Client) having established an MCData group regroup using a preconfigured group }
ensure that {
  when { UE (MCData Client) receives a request to establish an MCData On-demand Pre-arranged Group
Call using the group regroup }
    then { UE (MCData Client) sends a SIP INVITE message using the group regroup to establish an
MCData On-demand Pre-arranged Group Call }
            }
```

(3)

```
with { UE (MCData Client) having an ongoing On-demand Pre-arranged Group Call }
ensure that {
  when {MCData User requests to terminate the ongoing MCData Group Call}
    then { UE (MCData Client) sends a SIP BYE message and leaves the MCData session }
            }
```

(4)

```
with { UE (MCData Client) having an affiliation with an established MCData group regroup }
ensure that {
  when { UE (MCData Client) receives a request to remove the group regroup via a SIP MESSAGE message
}
    then { UE (MCData Client) responds with a SIP 200 (OK) message }
```

6.9.1.2 Conformance requirements

References: The conformance requirements covered in the present TC are specified in: TS 24.282 clauses 23.2.1.1, 23.2.1.2. Unless otherwise stated these are Rel-17 requirements.

[TS 24.282 clause 23.2.1.1]

Upon receiving a request from an MCData user to establish an MCData group regroup using a preconfigured group, the MCData client shall generate a SIP MESSAGE request in accordance with 3GPP TS 24.229 [5] and IETF RFC 3428 [6] and:

1) shall include an Accept-Contact header field containing the g.3gpp.mcdata media feature tag along with the "require" and "explicit" header field parameters according to IETF RFC 3841 [8];

2) shall include an Accept-Contact header field with the media feature tag g.3gpp.icsi-ref with the value of "urn:urn-7:3gpp-service.ims.icsi.mcdata" along with parameters "require" and "explicit" according to IETF RFC 3841 [8];

3) shall set the Request-URI to the public service identity identifying the originating participating MCData function serving the MCData user;

4) may include a P-Preferred-Identity header field in the SIP MESSAGE request containing a public user identity as specified in 3GPP TS 24.229 [5];

5) shall include the ICSI value "urn:urn-7:3gpp-service.ims.icsi.mcdata" (coded as specified in 3GPP TS 24.229 [5]), in a P-Asserted-Service-Id header field according to IETF RFC 6050 [7];

6) shall contain an application/vnd.3gpp.mcdata-info+xml MIME body with the <mcdatainfo> element containing the <mcdata-Params> element with:

   a) the <mcdata-client-id> element set to the MCData client ID of the originating MCData client; and

   b) if the MCData client is aware of active functional aliases, and an active functional alias is to be included in the SIP MESSAGE request, the <anyExt> element of the <functional-alias-URI> element set to the URI of the used functional alias;

7) shall contain an application/vnd.3gpp.mcdata-regroup+xml MIME body with:

   a) the <regroup-action> element set to the value "create";

   b) the <mcdata-regroup-uri> element set to a unique temporary group identity URI;

   NOTE: How the unique temporary group identity URI is formed is an implementation decision.

   c) the <preconfigured-group> element set to the group identity of the preconfigured group; and

   d) the <groups-for-regroup> element set to the list of MCData group identities of groups that are to be included in the regroup; and

8) shall send the SIP MESSAGE request according to 3GPP TS 24.229 [5].

On receiving a SIP 2xx response to the SIP MESSAGE request, the MCData client:

1) should notify the MCData user of the successful creation of the group regroup using preconfigured group.

On receiving a SIP 4xx response, a SIP 5xx response or a SIP 6xx response to the SIP INVITE request:

1) should notify the MCData user of the failure to create the group regroup using preconfigured group.

[TS 24.282 clause 23.2.1.2]

Upon receiving a request from an MCData user to remove a user or group regroup using a preconfigured group, the MCData client:

1) shall generate a SIP MESSAGE request in accordance with 3GPP TS 24.229 [5] and IETF RFC 3428 [6]:

2) shall include an Accept-Contact header field containing the g.3gpp.mcdata media feature tag along with the "require" and "explicit" header field parameters according to IETF RFC 3841 [8];

3) shall include an Accept-Contact header field with the media feature tag g.3gpp.icsi-ref with the value of "urn:urn-7:3gpp-service.ims.icsi.mcdata" along with parameters "require" and "explicit" according to IETF RFC 3841 [8];

4) shall set the Request-URI to the public service identity identifying the originating participating MCData function serving the MCData user;

5) may include a P-Preferred-Identity header field in the SIP INVITE request containing a public user identity as specified in 3GPP TS 24.229 [5];

6) shall include the ICSI value "urn:urn-7:3gpp-service.ims.icsi.mcdata" (coded as specified in 3GPP TS 24.229 [5]), in a P-Asserted-Service-Id header field according to IETF RFC 6050 [7];

7) shall contain an application/vnd.3gpp.mcdata-info+xml MIME body with the <mcdatainfo> element containing the <mcdata-Params> element with:

   a) the <mcdata-client-id> element set to the MCData client ID of the originating MCData client; and

   b) if the MCData client is aware of active functional aliases, and an active functional alias is to be included in the SIP MESSAGE request, the <anyExt> element of the <functional-alias-URI> element set to the URI of the used functional alias;

8) shall contain an application/vnd.3gpp.mcdata-regroup+xml MIME body with:

   a) the <mcdata-regroup-uri> element set to the unique temporary group identity URI representing the regroup to be removed; and

   b) the <regroup-action> element set to "remove"; and

9) shall send the SIP MESSAGE request according to 3GPP TS 24.229 [5].

On receiving a SIP 2xx response to the SIP MESSAGE request, the MCData client:

1) should notify the MCData user of the successful removal of the regroup using preconfigured group.

On receiving a SIP 4xx response, a SIP 5xx response or a SIP 6xx response to the SIP INVITE request:

1) should notify the MCData user of the failure to remove the regroup using preconfigured group.

6.9.1.3 Test description

6.9.1.3.1 Pre-test conditions

Test configuration:

- Single cell configuration according to TS 37.579-1 [2] clause 5.2.2.2.1.

Preamble:

- The UE has performed procedure 'Initial registration' as described in TS 37.579-1 [2] clause 5.4.2.
- UE States at the end of the preamble:
  - The UE is in RRC_IDLE state.

- The client is registered for MCData.

6.9.1.3.2 Test procedure sequence

Table 6.9.1.3.2-1: Main Behaviour

St	Procedure	Message Sequence		TP	Verdict
		U - S	Message		
-	EXCEPTION: Procedure 'MCX CO communication' as described in TS 37.579-1 [2] clause 5.4.3 is started to establish an RRC connection.	-	-	-	-
1	Make the UE (MCData client) request creation of a new group (group B). (NOTE 1)	-	-	-	-
2	The UE (MCData client) correctly performs procedure 'MCX CO Group Creation' as described in TS 37.579-1 [2] Table 5.3.26.3-1 to create group B.	-	-	-	-
3	The procedure 'MCX communication release' as described in TS 37.579-1 [2] clause 5.4.14 is performed to release the RRC connection.	-	-	-	-
4	Make the UE (MCData client) request to establish an MCData group regroup using a preconfigured group. (NOTE 1)	-	-	-	-
5	Check: Does the UE (MCData client) correctly perform procedure 'MCX SIP MESSAGE CO' as described in TS 37.579-1 [2] Table 5.3.32.3-1 to establish an MCData group regroup using a preconfigured group?	-	-	1	P
6	Make the UE (MCData client) request the establishment of a SDS group session using the group regroup. (NOTE 1)	-	-	-	-
7	Check: Does the UE (MCData client) correctly perform procedure 'CO MCData Call Establishment' as described in TS 37.579-1 [2] Table 5.3C.2.3-1 to establish a SDS group session using the group regroup?	-	-	2	P
8	Make the UE (MCData client) release the call. (NOTE 1)	-	-	-	-
9	Check: Does the UE (MCData client) correctly perform procedure ' CO MCData call release ' as described in TS 37.579-1 [2] Table 5.3C.6.3-1?	-	-	3	P
10	Make the UE (MCData client) request to remove the group regroup. (NOTE 1)	-	-	-	-
11	Check: Does the UE (MCData client) correctly perform procedure ‘MCX SIP MESSAGE CO' as described in TS 37.579-1 [2] Table 5.3.32.3-1 to remove the group regroup?	-	-	4	P
NOTE 1: This is expected to be done via a suitable implementation dependent MMI.					

6.9.1.3.3 Specific message contents

Table 6.9.1.3.3-1: HTTP PUT (step 2, Table 6.9.1.3.2-1; step 1, TS 37.579-1 [2], Table 5.3.26.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.4.4-1, condition GROUPCREATE

Table 6.9.1.3.3-2: SIP MESSAGE from the UE (Step 5, Table 6.9.1.3.2-1; Step 2, TS 37.579-1 [2], Table 5.3.32.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.7.1-1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Accept-Contact				
ac-value[2]				
feature-param	"+g.3gpp.mcdata"		TS 24.282 [31] clause 23.2.1.1	
req-param	"require"			
explicit-param	"explicit"			
P-Asserted-Service				
Service-ID	"urn:urn-7:3gpp-service.ims.icsi.mcdata"			
P-Preferred-Service	not present			
Message-body				
MIME body part		**MCData-Info**		
MIME-part-body	MCData-Info as described in Table 6.9.1.3.3-3		TS 24.282 [31] clause 23.2.1.1	
MIME body part		**MCData-Regroup**		
MIME-part-headers				
Content-Type	"application/vnd.3gpp.mcdata-regroup+xml"			
Content-ID	any value	Unique URL identifying the MCData-Regroup XML MIME body; used as reference in the signature MIME body		
MIME-part-body	MCData-Regroup as described in Table 6.9.1.3.3-4		TS 24.282 [31] clause 23.2.1.1	

Table 6.9.1.3.3-3: MCData-Info in SIP MESSAGE (Table 6.9.1.3.3-2)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.2.1-3				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
mcdatainfo				
mcdata-Params				
mcdata-client-id	Encrypted <mcdata-client-id> with mcdataString set to the client-id of the UE	Encryption according to NOTE 1 and NOTE 2 in TS 37.579-1 [2] Table 5.5.3.2.1-3	TS 24.282 [31] clause 23.2.1.1	

Table 6.9.1.3.3-4: MCData-Regroup in SIP MESSAGE (Table 6.9.1.3.3-2)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.16.2-3, condition GROUP_REGROUP

Table 6.9.1.3.3-5: SIP INVITE from the UE (step 7, Table 6.9.1.3.2-1; step 2, TS 37.579-1 [2] Table 5.3C.2.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.5.1-1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part		**SDP message**		
MIME-part-body	SDP Message as described in Table 6.9.1.3.3-6			
MIME body part		**MCData-Info**		
MIME-part-body	MCData-Info as described in Table 6.9.1.3.3-7			

Table 6.9.1.3.3-6: SDP in SIP INVITE (Table 6.9.1.3.3-5)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.1.1-3, condition INITIAL_SDP_OFFER, MCDATA_SDS, SDS_SESSION

Table 6.9.1.3.3-7: MCData-Info in SIP INVITE (Table 6.9.1.3.3-5)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.2.1-3, condition MCD_grp				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
mcdatainfo				
mcdata-Params				
request-type	"group-sds-session"			
mcdata-request-uri	Encrypted <mcdata-request-uri> with mcdataURI set to px_MCData_Group_T_ID	Encryption according to NOTE 1 and NOTE 2 in TS 37.579-1 [2] Table 5.5.3.2.1-3		

Table 6.9.1.3.3-8: SIP 200 (OK) from the SS (step 7, Table 6.9.1.3.2-1; step 4, TS 37.579-1 [2] Table 5.3C.2.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.17.1.2-1, condition INVITE-RSP				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
SDP Message	As described in Table 6.9.1.3.3-9			

Table 6.9.1.3.3-9: SDP in SIP 200 (OK) (Table 6.9.1.3.3-8)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.1.2-3, condition SDP_ANSWER, SDS_SESSION, MCDATA_SDS

Table 6.9.1.3.3-10: SIP MESSAGE from the UE (Step 11, Table 6.9.1.3.2-1; Step 2, TS 37.579-1 [2], Table 5.3.32.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.7.1-1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Accept-Contact				
ac-value[2]				
feature-param	"+g.3gpp.mcdata"		TS 24.282 [31] clause 23.2.1.2	
req-param	"require"			
explicit-param	"explicit"			
P-Asserted-Service				
Service-ID	"urn:urn-7:3gpp-service.ims.icsi.mcdata"			
P-Preferred-Service	not present			
Message-body				
MIME body part		**MCData-Info**		
MIME-part-body	MCData-Info as described in Table 6.9.1.3.3-3		TS 24.282 [31] clause 23.2.1.2	
MIME body part		**MCData-Regroup**		
MIME-part-headers				
Content-Type	"application/vnd.3gpp.mcdata-regroup+xml"			
Content-ID	any value	Unique URL identifying the MCData-Regroup XML MIME body; used as reference in the signature MIME body		
MIME-part-body	MCData-Regroup as described in Table 6.9.1.3.3-11		TS 24.282 [31] clause 23.2.1.2	

Table 6.9.1.3.3-11: MCData-Regroup in SIP MESSAGE (Table 6.9.1.3.3-10)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.16.2-3, condition REMOVE

6.9.2 On-network / Regroup using a preconfigured group / Receiving a notification of creation of a regroup using preconfigured group / Receiving notification of removal of a regroup using preconfigured group / Client Terminated (CT)

6.9.2.1 Test Purpose (TP)

(1)

```
with { UE (MCData Client) registered and authorised for MCData Service }
ensure that {
  when { UE (MCData Client) receives a request via a SIP MESSAGE message to create an MCData group
regroup using a preconfigured group }
    then { UE (MCData Client) responds with a SIP 200 (OK) message }
            }
```

(2)

```
with { UE (MCData Client) having established an MCData group regroup using a preconfigured group }
ensure that {
  when { UE (MCData Client) receives a request to establish an MCData On-demand Pre-arranged Group
Call using the group regroup }
    then { UE (MCData Client) sends a SIP INVITE message using the group regroup to establish an
MCData On-demand Pre-arranged Group Call }
```

```
            }
```

(3)

```
with { UE (MCData Client) having an ongoing On-demand Pre-arranged Group Call }
ensure that {
  when {MCData Group requests to terminate the ongoing MCData Group Call }
    then { UE (MCData Client) sends a SIP BYE message and leaves the MCData session }
            }
```

(4)

```
with { UE (MCData Client) having an affiliation with an established MCData group regroup }
ensure that {
  when { UE (MCData Client) receives a request to remove the group regroup via a SIP MESSAGE message
}
    then { UE (MCData Client) responds with a SIP 200 (OK) message }
            }
```

6.9.2.2 Conformance requirements

References: The conformance requirements covered in the present TC are specified in: TS 24.282 clauses 23.2.1.3, 23.2.1.4. Unless otherwise stated these are Rel-17 requirements.

[TS 24.282 clause 23.2.1.3]

Upon receiving a "SIP MESSAGE request to the MCData client to request creation of a regroup using preconfigured group", the MCData client:

1) should notify the MCData user of the creation of the regroup using preconfigured group;

2) shall send a 200 (OK) response to the MCData server according to 3GPP TS 24.229 [5];

3) in the application/vnd.3gpp.mcdata-regroup+xml MIME body contained in the incoming SIP MESSAGE request:

   a) shall store the value of the <mcdata-regroup-uri> element as the temporary group identity and associate that with the group identity received in the <mcdata-regroup-uri> element;

   b) if a <users-for-regroup> element is included in that MIME body, should store the contents of the <users-for-regroup> element as the list of the users that are part of that regroup and shall consider the regroup as a user regroup; and

NOTE 1: The MCData client can choose to display the list of users in the user regroup to the MCData user.

   c) if a <groups-for-regroup> element is included in that MIME body, should store the contents of the <groups-for-regroup> element as the list of groups that are part of that regroup and shall consider the regroup as a group regroup;

NOTE 2: The MCData client can choose to display the list of groups in the group regroup to the MCData user.

   a) if a <users-for-regroup> element is included in that MIME body, shall store the value of the <mcdata-regroup-uri> element as the temporary group identity and associate that with the group identity received in the <mcdata-regroup-uri> element, along with the information that the created regroup is a user regroup and should store the contents of the <users-for-regroup> element as the list of the users that are part of that user regroup: or

   b) if a <groups-for-regroup> element is included in that MIME body, shall store the value of the <mcdata-regroup-uri> element as the temporary group identity and associate that with the group identity received in the <mcdata-regroup-uri> element, along with the information that the created regroup is a group regroup and should store the contents of the <groups-for-regroup> element as the list of groups that are part of that group regroup:

4) shall consider that the MCData Client is affiliated with the regroup;

5) should not initiate calls targeting any of the constituent groups but instead target the regroup for the duration of a group regroup; and

6) if the regroup is a chat group, the MCData client should join the regroup when this notification of creation is received.

[TS 24.282 clause 23.2.1.4]

Upon receiving a "SIP MESSAGE request to the MCData client to request removal of a regroup using preconfigured group", the MCData client:

1) should notify the MCData user of the removal of the regroup using preconfigured group;

2) shall send a 200 (OK) response to the MCData server according to 3GPP TS 24.229 [5]; and

3) shall consider that the MCData client is de-affiliated from the regroup.

6.9.2.3 Test description

6.9.2.3.1 Pre-test conditions

Test configuration:

- Single cell configuration according to TS 37.579-1 [2] clause 5.2.2.2.1.

Preamble:

- The UE has performed procedure 'Initial registration' as described in TS 37.579-1 [2] clause 5.4.2.
- UE States at the end of the preamble:
  - The UE is in RRC_IDLE state.
  - The client is registered for MCData.

6.9.2.3.2 Test procedure sequence

Table 6.9.2.3.2-1: Main Behaviour

St	Procedure	Message Sequence		TP	Verdict
		U - S	Message		
-	EXCEPTION: Procedure 'MCX CO communication' as described in TS 37.579-1 [2] clause 5.4.3 is started to establish an RRC connection.	-	-	-	-
1	Make the UE (MCData client) request creation of a new group (group B). (NOTE 1)	-	-	-	-
2	The UE (MCData client) correctly performs procedure 'MCX CO Group Creation' as described in TS 37.579-1 [2] Table 5.3.26.3-1 to create group B.	-	-	-	-
3	The procedure 'MCX communication release' as described in TS 37.579-1 [2] clause 5.4.14 is performed to release the RRC connection.	-	-	-	-
4	Check: Does the UE (MCData client) correctly perform procedure 'MCX SIP MESSAGE CT' as described in TS 37.579-1 [2] Table 5.3.33.3-1 to establish an MCData group regroup using a preconfigured group?	-	-	1	P
5	Make the UE (MCData client) request the establishment of a SDS group session using the group regroup. (NOTE 1)	-	-	-	-
6	Check: Does the UE (MCData client) correctly perform procedure 'CO MCData Call Establishment' as described in TS 37.579-1 [2] Table 5.3C.2.3-1 to establish a SDS group session using the group regroup?	-	-	2	P
7	Make the UE (MCData client) release the call. (NOTE 1)	-	-	-	-
8	Check: Does the UE (MCData client) correctly perform procedure 'CO MCData call release' as described in TS 37.579-1 [2] Table 5.3C.6.3-1?	-	-	3	P
9	Check: Does the UE (MCData client) correctly perform procedure 'MCX SIP MESSAGE CT' as described in TS 37.579-1 [2] Table 5.3.33.3-1 to remove the group regroup?	-	-	4	P
NOTE 1: This is expected to be done via a suitable implementation dependent MMI.					

6.9.2.3.3 Specific message contents

Table 6.9.2.3.3-1: HTTP PUT (step 2, Table 6.9.2.3.2-1; step 1, TS 37.579-1 [2], Table 5.3.26.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.4.4-1, condition GROUPCREATE

Table 6.9.2.3.3-2: SIP MESSAGE from the SS (Step 4, Table 6.9.2.3.2-1; Step 2, TS 37.579-1 [2], Table 5.3.33.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.7.2-1, condition ACCEPT-CONTACT-WITH-MEDIA-FEATURE-TAG				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
P-Asserted-Identity				
name-addr	px_MCX_SIP_PublicUserId_B		TS 24.282 [31] clause 23.2.2.4	
Message-body				
MIME body part		**MCData-Info**		
MIME-part-body	MCData-Info as described in Table 6.9.2.3.3-3		TS 24.282 [31] clause 23.2.2.4	
MIME body part		**MCData-Regroup**		
MIME-part-headers				
Content-Type	"application/vnd.3gpp.mcdata-regroup+xml"			
Content-ID	Unique id in format of a Message-ID assigned by the SS	Unique URL identifying the MCData-Regroup XML MIME body; used as reference in the signature MIME body		
MIME-part-body	MCData-Regroup as described in Table 6.9.2.3.3-4		TS 24.282 [31] clause 23.2.2.4	

Table 6.9.2.3.3-3: MCData-Info in SIP MESSAGE (Table 6.9.2.3.3-2)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.2.2-3				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
mcdatainfo				
mcdata-Params				
mcdata-request-uri	not present			
mcdata-calling-user-id	not present			
mcdata-client-id	Encrypted <mcdata-client-id> with mcdataString set to px_MCX_Client_B_ID	Encryption according to NOTE 1 in TS 37.579-1 [2] Table 5.5.3.2.2-3	TS 24.282 [31] clause 23.2.2.4	

Table 6.9.2.3.3-4: MCData-Regroup in SIP MESSAGE (Table 6.9.2.3.3-2)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.16.3-3, condition GROUP_REGROUP

Table 6.9.2.3.3-5: SIP INVITE from the UE (step 6, Table 6.9.2.3.2-1; step 2, TS 37.579-1 [2] Table 5.3C.2.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.5.1-1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part		**SDP message**		
MIME-part-body	SDP Message as described in Table 6.9.2.3.3-6			
MIME body part		**MCData-Info**		
MIME-part-body	MCData-Info as described in Table 6.9.2.3.3-7			

Table 6.9.2.3.3-6: SDP in SIP INVITE (Table 6.9.2.3.3-5)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.1.1-3, condition INITIAL_SDP_OFFER, MCDATA_SDS, SDS_SESSION

Table 6.9.2.3.3-7: MCData-Info in SIP INVITE (Table 6.9.2.3.3-5)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.2.1-3, condition MCD_grp				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
mcdatainfo				
mcdata-Params				
request-type	"group-sds-session"			
mcdata-request-uri	Encrypted <mcdata-request-uri> with mcdataURI set to px_MCData_Group_T_ID	Encryption according to NOTE 1 and NOTE 2 in TS 37.579-1 [2] Table 5.5.3.2.1-3		

Table 6.9.2.3.3-8: SIP 200 (OK) from the SS (step 6, Table 6.9.2.3.2-1; step 4, TS 37.579-1 [2] Table 5.3C.2.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.17.1.2-1, condition INVITE-RSP				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
SDP Message	As described in Table 6.9.2.3.3-9			

Table 6.9.2.3.3-9: SDP in SIP 200 (OK) (Table 6.9.2.3.3-8)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.1.2-3, condition SDP_ANSWER, SDS_SESSION, MCDATA_SDS

Table 6.9.2.3.3-10: SIP MESSAGE from the SS (Step 9, Table 6.9.2.3.2-1; Step 2, TS 37.579-1 [2], Table 5.3.33.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.7.2-1, condition ACCEPT-CONTACT-WITH-MEDIA-FEATURE-TAG				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
P-Asserted-Identity				
name-addr	px_MCX_SIP_PublicUserId_B		TS 24.282 [31] clause 23.2.2.5	
Message-body				
MIME body part		**MCData-Info**		
MIME-part-body	MCData-Info as described in Table 6.9.2.3.3-3		TS 24.282 [31] clause 23.2.2.5	
MIME body part		**MCData-Regroup**		
MIME-part-headers				
Content-Type	"application/vnd.3gpp.mcdata-regroup+xml"			
Content-ID	Unique id in format of a Message-ID assigned by the SS	Unique URL identifying the MCData-Regroup XML MIME body; used as reference in the signature MIME body		
MIME-part-body	MCData-Regroup as described in Table 6.9.2.3.3-11		TS 24.282 [31] clause 23.2.2.5	

Table 6.9.2.3.3-11: MCData-Regroup in SIP MESSAGE (Table 6.9.2.3.3-10)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.16.3-3, condition REMOVE

6.9.3 On-network / Regroup using a preconfigured group / Requesting a user regroup using a preconfigured group / Removing a regroup using preconfigured group / Client Originated (CO)

6.9.3.1 Test Purpose (TP)

(1)

```
with { UE (MCData Client) registered and authorised for MCData Service }
ensure that {
  when { UE (MCData Client) receives a request to establish an MCData user regroup using a
preconfigured group }
    then { UE (MCData Client) sends a SIP MESSAGE message to establish an MCData user regroup using
a preconfigured group }
            }
```

(2)

```
with { UE (MCData Client) having established an MCData user regroup using a preconfigured group }
ensure that {
  when { UE (MCData Client) receives a request to establish an MCData On-demand Pre-arranged Group
Call using the user regroup }
    then { UE (MCData Client) sends a SIP INVITE message using the user regroup to establish an
MCData On-demand Pre-arranged Group Call }
            }
```

(3)

```
with { UE (MCData Client) having an ongoing On-demand Pre-arranged Group Call }
ensure that {
  when { MCData User requests to terminate the ongoing MCData Group Call }
    then { UE (MCData Client) sends a SIP BYE message and leaves the MCData session }
            }
```

(4)

```
with { UE (MCData Client) having an affiliation with an established MCData user regroup }
ensure that {
  when { UE (MCData Client) receives a request to remove the user regroup via a SIP MESSAGE message
}
    then { UE (MCData Client) responds with a SIP 200 (OK) message }
```

6.9.3.2 Conformance Requirements

References: The conformance requirements covered in the present TC are specified in: TS 24.282 clauses 23.3.1.1, 23.3.1.2, and 23.2.1.2. Unless otherwise stated these are Rel-17 requirements.

[TS 24.282, clause 23.3.1.1]

Upon receiving a request from an MCData user to establish an MCData user regroup using a preconfigured group, the MCData client shall generate a SIP MESSAGE request in accordance with 3GPP TS 24.229 [5] and IETF RFC 3428 [6] and:

1) shall include an Accept-Contact header field containing the g.3gpp.mcdata media feature tag along with the "require" and "explicit" header field parameters according to IETF RFC 3841 [8];

2) shall include an Accept-Contact header field with the media feature tag g.3gpp.icsi-ref with the value of "urn:urn-7:3gpp-service.ims.icsi.mcdata" along with parameters "require" and "explicit" according to IETF RFC 3841 [8];

3) shall set the Request-URI to the public service identity identifying the originating participating MCData function serving the MCData user;

4) may include a P-Preferred-Identity header field in the SIP MESSAGE request containing a public user identity as specified in 3GPP TS 24.229 [5];

5) shall include the ICSI value "urn:urn-7:3gpp-service.ims.icsi.mcdata" (coded as specified in 3GPP TS 24.229 [5]), in a P-Asserted-Service-Id header field according to IETF RFC 6050 [7];

6) shall contain an application/vnd.3gpp.mcdata-info+xml MIME body with the <mcdatainfo> element containing the <mcdata-Params> element with:

   a) the <mcdata-client-id> element set to the MCData client ID of the originating MCData client; and

   b) if the MCData client is aware of active functional aliases, and an active functional alias is to be included in the SIP MESSAGE request, the <functional-alias-URI> set to the URI of the used functional alias;

7) shall contain an application/vnd.3gpp.mcdata-regroup+xml MIME body with:

   a) the <mcdata-regroup-uri> element set to a unique temporary group identity URI;

NOTE: How the unique temporary group identity URI is formed is an implementation decision.

   b) the <preconfigured-group> element set to the group identity of the preconfigured group;

   c) the <regroup-action> element set to "create"; and

   d) the <users-for-regroup> element set to the list of MCData IDs of users that are to be included in the regroup; and

8) shall send the SIP MESSAGE request according to 3GPP TS 24.229 [5].

On receiving a SIP 2xx response to the SIP MESSAGE request, the MCData client:

1) should notify the MCData user of the successful creation of the user regroup using preconfigured group.

On receiving a SIP 4xx response, a SIP 5xx response or a SIP 6xx response to the SIP INVITE request:

1) should notify the MCData user of the failure to create the user regroup using preconfigured group.

[TS 24.282, clause 23.3.1.2]

When the user requests the MCData client to remove a user regroup, the MCData client uses the procedure in clause 23.2.1.2.

[TS 24.282, clause 23.2.1.2]

Upon receiving a request from an MCData user to remove a user or group regroup using a preconfigured group, the MCData client:

1) shall generate a SIP MESSAGE request in accordance with 3GPP TS 24.229 [5] and IETF RFC 3428 [6]:

2) shall include an Accept-Contact header field containing the g.3gpp.mcdata media feature tag along with the "require" and "explicit" header field parameters according to IETF RFC 3841 [8];

3) shall include an Accept-Contact header field with the media feature tag g.3gpp.icsi-ref with the value of "urn:urn-7:3gpp-service.ims.icsi.mcdata" along with parameters "require" and "explicit" according to IETF RFC 3841 [8];

4) shall set the Request-URI to the public service identity identifying the originating participating MCData function serving the MCData user;

5) may include a P-Preferred-Identity header field in the SIP INVITE request containing a public user identity as specified in 3GPP TS 24.229 [5];

6) shall include the ICSI value "urn:urn-7:3gpp-service.ims.icsi.mcdata" (coded as specified in 3GPP TS 24.229 [5]), in a P-Asserted-Service-Id header field according to IETF RFC 6050 [7];

7) shall contain an application/vnd.3gpp.mcdata-info+xml MIME body with the <mcdatainfo> element containing the <mcdata-Params> element with:

   a) the <mcdata-client-id> element set to the MCData client ID of the originating MCData client; and

   b) if the MCData client is aware of active functional aliases, and an active functional alias is to be included in the SIP MESSAGE request, the <functional-alias-URI> set to the URI of the used functional alias; and

8) shall contain an application/vnd.3gpp.mcdata-regroup+xml MIME body with:

   a) the <mcdata-regroup-uri> element set to the unique temporary group identity URI representing the regroup to be removed; and

   b) the <regroup-action> element set to "remove"; and

9) shall send the SIP MESSAGE request according to 3GPP TS 24.229 [5].

On receiving a SIP 2xx response to the SIP MESSAGE request, the MCData client:

1) should notify the MCData user of the successful removal of the regroup using preconfigured group.

On receiving a SIP 4xx response, a SIP 5xx response or a SIP 6xx response to the SIP INVITE request:

1) should notify the MCData user of the failure to remove the regroup using preconfigured group.

6.9.3.3 Test description

6.9.3.3.1 Pre-test conditions

Test configuration:

- Single cell configuration according to TS 37.579-1 [2] clause 5.2.2.2.1.

Preamble:

- The UE has performed procedure 'Initial registration' as described in TS 37.579-1 [2] clause 5.4.2.
- UE States at the end of the preamble:
  - The UE is in RRC_IDLE state.
  - The client is registered for MCData.

6.9.3.3.2 Test procedure sequence

Table 6.9.3.3.2-1: Main Behaviour

St	Procedure	Message Sequence		TP	Verdict
		U - S	Message		
-	EXCEPTION: Procedure 'MCX CO communication' as described in TS 37.579-1 [2] clause 5.4.3 is started to establish an RRC connection.	-	-	-	-
1	Make the UE (MCData client) request creation of a new group (group B). (NOTE 1)	-	-	-	-
2	The UE (MCData client) correctly performs procedure 'MCX CO Group Creation' as described in TS 37.579-1 [2] Table 5.3.26.3-1 to create group B.	-	-	-	-
3	The procedure 'MCX communication release' as described in TS 37.579-1 [2] clause 5.4.14 is performed to release the RRC connection.	-	-	-	-
4	Make the UE (MCData client) request to establish an MCData user regroup using a preconfigured group. (NOTE 1)	-	-	-	-
5	Check: Does the UE (MCData client) correctly perform procedure 'MCX SIP MESSAGE CO' as described in TS 37.579-1 [2] Table 5.3.32.3-1 to establish an MCData user regroup using a preconfigured group?	-	-	1	P
6	Make the UE (MCData client) request the establishment of a SDS group session using the user regroup. (NOTE 1)	-	-	-	-
7	Check: Does the UE (MCData client) correctly perform procedure 'CO MCData Call Establishment' as described in TS 37.579-1 [2] Table 5.3C.2.3-1 to establish an SDS group session using the user regroup?	-	-	2	P
8	Make the UE (MCData client) release the call. (NOTE 1)	-	-	-	-
9	Check: Does the UE (MCData client) correctly perform procedure 'CO MCData call release' as described in TS 37.579-1 [2] Table 5.3C.6.3-1?	-	-	3	P
10	Make the UE (MCData client) request to remove the user regroup. (NOTE 1)	-	-	-	-
11	Check: Does the UE (MCData client) correctly perform procedure ‘MCX SIP MESSAGE CO' as described in TS 37.579-1 [2] Table 5.3.32.3-1 to remove the user regroup?	-	-	4	P
NOTE 1: This is expected to be done via a suitable implementation dependent MMI.					

6.9.3.3.3 Specific message contents

Table 6.9.3.3.3-1: HTTP PUT (step 2, Table 6.9.3.3.2-1; step 1, TS 37.579-1 [2], Table 5.3.26.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.4.4-1, condition GROUPCREATE

Table 6.9.3.3.3-2: SIP MESSAGE from the UE (Step 5, Table 6.9.3.3.2-1; Step 2, TS 37.579-1 [2], Table 5.3.32.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.7.1-1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Accept-Contact				
ac-value[2]				
feature-param	"+g.3gpp.mcdata"		TS 24.282 [31] clause 23.3.1.1	
req-param	"require"		TS 24.282 [31] clause 23.3.1.1	
explicit-param	"explicit"		TS 24.282 [31] clause 23.3.1.1	
P-Asserted-Service				
Service-ID	"urn:urn-7:3gpp-service.ims.icsi.mcdata"		TS 24.282 [31] clause 23.3.1.1	
P-Preferred-Service	not present			
Message-body				
MIME body part		**MCData-Info**		
MIME-part-body	MCData-Info as described in Table 6.9.3.3.3-3		TS 24.282 [31] clause 23.3.1.1	
MIME body part		**MCData-Regroup**		
MIME-part-headers				
Content-Type	"application/vnd.3gpp.mcdata-regroup+xml"			
Content-ID	any value	Unique URL identifying the MCData-Regroup XML MIME body; used as reference in the signature MIME body		
MIME-part-body	MCData-Regroup as described in Table 6.9.3.3.3-4		TS 24.282 [31] clause 23.3.1.1	

Table 6.9.3.3.3-3: MCData-Info in SIP MESSAGE (Table 6.9.3.3.3-2)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.2.1-3				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
mcdatainfo				
mcdata-Params				
mcdata-client-id	Encrypted <mcdata-client-id> with mcdataString set to the client-id of the UE	Encryption according to NOTE 1 and NOTE 2 in TS 37.579-1 [2] Table 5.5.3.2.1-3	TS 24.282 [31] clause 23.3.1.1	

Table 6.9.3.3.3-4: MCData-Regroup in SIP MESSAGE (Table 6.9.3.3.3-2)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.16.2-3, condition USER_REGROUP

Table 6.9.3.3.3-5: SIP INVITE from the UE (step 7, Table 6.9.3.3.2-1; step 2, TS 37.579-1 [2] Table 5.3C.2.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.5.1-1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part		**SDP message**		
MIME-part-body	SDP Message as described in Table 6.9.3.3.3-6			
MIME body part		**MCData-Info**		
MIME-part-body	MCData-Info as described in Table 6.9.3.3.3-7			

Table 6.9.3.3.3-6: SDP in SIP INVITE (Table 6.9.3.3.3-5)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.1.1-3, condition INITIAL_SDP_OFFER, MCDATA_SDS, SDS_SESSION

Table 6.9.3.3.3-7: MCData-Info in SIP INVITE (Table 6.9.3.3.3-5)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.2.1-3, condition MCD_grp				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
mcdatainfo				
mcdata-Params				
request-type	"group-sds-session"			
mcdata-request-uri	Encrypted <mcdata-request-uri> with mcdataURI set to px_MCData_Group_T_ID	Encryption according to NOTE 1 and NOTE 2 in TS 37.579-1 [2] Table 5.5.3.2.1-3		

Table 6.9.3.3.3-8: SIP 200 (OK) from the SS (step 7, Table 6.9.3.3.2-1; step 4, TS 37.579-1 [2] Table 5.3C.2.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.17.1.2-1, condition INVITE-RSP				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
SDP Message	As described in Table 6.9.3.3.3-9			

Table 6.9.3.3.3-9: SDP in SIP 200 (OK) (Table 6.9.3.3.3-8)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.1.2-3, condition SDP_ANSWER, SDS_SESSION, MCDATA_SDS

Table 6.9.3.3.3-10: SIP MESSAGE from the UE (Step 11, Table 6.9.3.3.2-1; Step 2, TS 37.579-1 [2], Table 5.3.32.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.7.1-1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Accept-Contact				
ac-value[2]				
feature-param	"+g.3gpp.mcdata"		TS 24.282 [31] clause 23.3.1.2	
req-param	"require"		TS 24.282 [31] clause 23.3.1.2	
explicit-param	"explicit"		TS 24.282 [31] clause 23.3.1.2	
P-Asserted-Service				
Service-ID	"urn:urn-7:3gpp-service.ims.icsi.mcdata"		TS 24.282 [31] clause 23.3.1.2	
P-Preferred-Service	not present			
Message-body				
MIME body part		**MCData-Info**		
MIME-part-body	MCData-Info as described in Table 6.9.3.3.3-3		TS 24.282 [31] clause 23.3.1.2	
MIME body part		**MCData-Regroup**		
MIME-part-headers				
Content-Type	"application/vnd.3gpp.mcdata-regroup+xml"			
Content-ID	any value	Unique URL identifying the MCData-Regroup XML MIME body; used as reference in the signature MIME body		
MIME-part-body	MCData-Regroup as described in Table 6.9.3.3.3-11		TS 24.282 [31] clause 23.3.1.2	

Table 6.9.3.3.3-11: MCData-Regroup in SIP MESSAGE (Table 6.9.3.3.3-10)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.16.2-3, condition REMOVE

6.9.4 On-network / Regroup using a preconfigured group / Creating a user regroup using preconfigured group / Removing a user regroup using preconfigured group / Client Terminated (CT)

6.9.4.1 Test Purpose (TP)

(1)

```
with { UE (MCData Client) registered and authorised for MCData Service }
ensure that {
  when { UE (MCData Client) receives a request via a SIP MESSAGE message to create an MCData user
regroup using a preconfigured group }
    then { UE (MCData Client) responds with a SIP 200 (OK) message }
            }
```

(2)

```
with { UE (MCData Client) having established an MCData user regroup using a preconfigured group }
ensure that {
```

```
  when { UE (MCData Client) receives a request to establish an MCData On-demand Pre-arranged Group
Call using the user regroup }
    then { UE (MCData Client) sends a SIP INVITE message using the user regroup to establish an
MCData On-demand Pre-arranged Group Call }
            }
```

(3)

```
with { UE (MCData Client) having an ongoing On-demand Pre-arranged Group Call }
ensure that {
  when { MCData User requests to terminate the ongoing MCData Group Call }
    then { UE (MCData Client) sends a SIP BYE message and leaves the MCData session }
            }
```

(4)

```
with { UE (MCData Client) having an affiliation with an established MCData user regroup }
ensure that {
  when { UE (MCData Client) receives a request to remove the user regroup via a SIP MESSAGE message
}
    then { UE (MCData Client) responds with a SIP 200 (OK) message }
            }
```

6.9.4.2 Conformance requirements

References: The conformance requirements covered in the present TC are specified in: TS 24.282 clauses 23.3.1.3, 23.2.1.3, 23.3.1.4, 23.2.1.4. Unless otherwise stated these are Rel-17 requirements.

[TS 24.282 clause 23.3.1.3]

The procedure in clause 23.2.1.3 is used by the MCData client when the MCData server notifies the MCData client of the creation of a user regroup using preconfigured group.

[TS 24.282 clause 23.2.1.3]

Upon receiving a "SIP MESSAGE request to the MCData client to request creation of a regroup using preconfigured group", the MCData client:

1) should notify the MCData user of the creation of the regroup using preconfigured group;

2) shall send a 200 (OK) response to the MCData server according to 3GPP TS 24.229 [5];

3) in the application/vnd.3gpp.mcdata-regroup+xml MIME body contained in the incoming SIP MESSAGE request:

   a) if a <users-for-regroup> element is included in that MIME body, shall store the value of the <mcdata-regroup-uri> element as the temporary group identity and associate that with the group identity received in the <mcdata-regroup-uri> element, along with the information that the created regroup is a user regroup and should store the contents of the <users-for-regroup> element as the list of the users that are part of that user regroup: or

   b) if a <groups-for-regroup> element is included in that MIME body, shall store the value of the <mcdata-regroup-uri> element as the temporary group identity and associate that with the group identity received in the <mcdata-regroup-uri> element, along with the information that the created regroup is a group regroup and should store the contents of the <groups-for-regroup> element as the list of groups that are part of that group regroup:

4) shall consider that the MCData Client is affiliated with the regroup;

5) should not initiate calls targeting any of the constituent groups but instead target the regroup for the duration of a group regroup; and

6) if the regroup is a chat group, the MCData client should join the regroup when this notification of creation is received.

[TS 24.282 clause 23.3.1.4]

The procedure in clause 23.2.1.4 is used by the MCData client when the MCData server notifies the MCData client of the removal of a user regroup using preconfigured group.

[TS 24.282 clause 23.2.1.4]

Upon receiving a "SIP MESSAGE request to the MCData client to request removal of a regroup using preconfigured group", the MCData client:

1) should notify the MCData user of the removal of the regroup using preconfigured group;
2) shall send a 200 (OK) response to the MCData server according to 3GPP TS 24.229 [5]; and
3) shall consider that the MCData client is de-affiliated from the regroup.

6.9.4.3 Test description

6.9.4.3.1 Pre-test conditions

Test configuration:

- Single cell configuration according to TS 37.579-1 [2] clause 5.2.2.2.1.

Preamble:

- The UE has performed procedure 'Initial registration' as described in TS 37.579-1 [2] clause 5.4.2.
- UE States at the end of the preamble:
  - The UE is in RRC_IDLE state.
  - The client is registered for MCData.

6.9.4.3.2 Test procedure sequence

Table 6.9.4.3.2-1: Main Behaviour

St	Procedure	Message Sequence		TP	Verdict
		U - S	Message		
-	EXCEPTION: Procedure 'MCX CO communication' as described in TS 37.579-1 [2] clause 5.4.3 is started to establish an RRC connection.	-	-	-	-
1	Make the UE (MCData client) request creation of a new group (group B). (NOTE 1)	-	-	-	-
2	The UE (MCData client) correctly performs procedure 'MCX CO Group Creation' as described in TS 37.579-1 [2] Table 5.3.26.3-1 to create group B.	-	-	-	-
3	The procedure 'MCX communication release' as described in TS 37.579-1 [2] clause 5.4.14 is performed to release the RRC connection.	-	-	-	-
4	Check: Does the UE (MCData client) correctly perform procedure ‘MCX SIP MESSAGE CT' as described in TS 37.579-1 [2] Table 5.3.33.3-1 to establish an MCData user regroup using a preconfigured group?	-	-	1	P
5	Make the UE (MCData client) request the establishment of a SDS group session using the user regroup. (NOTE 1)	-	-	-	-
6	Check: Does the UE (MCData client) correctly perform procedure 'CO MCData Call Establishment' as described in TS 37.579-1 [2] Table 5.3C.2.3-1 to establish a SDS group session using the user regroup?	-	-	2	P
7	Make the UE (MCData client) release the call. (NOTE 1)	-	-	-	-
8	Check: Does the UE (MCData client) correctly perform procedure 'CO MCData call release' as described in TS 37.579-1 [2] Table 5.3C.6.3-1?	-	-	3	P
9	Check: Does the UE (MCData client) correctly perform procedure ‘MCX SIP MESSAGE CT' as described in TS 37.579-1 [2] Table 5.3.33.3-1 to remove the user regroup?	-	-	4	P
NOTE 1: This is expected to be done via a suitable implementation dependent MMI.					

6.9.4.3.3 Specific message contents

Table 6.9.4.3.3-1: HTTP PUT (step 2, Table 6.9.4.3.2-1; step 1, TS 37.579-1 [2], Table 5.3.26.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.4.4-1, condition GROUPCREATE

Table 6.9.4.3.3-2: SIP MESSAGE from the SS (Step 4, Table 6.9.4.3.2-1; Step 2, TS 37.579-1 [2], Table 5.3.33.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.7.2-1, condition ACCEPT-CONTACT-WITH-MEDIA-FEATURE-TAG				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
P-Asserted-Identity				
name-addr	px_MCX_SIP_PublicUserId_B		TS 24.282 [31] clause 23.3.2.4	
Message-body				
MIME body part		**MCData-Info**		
MIME-part-body	MCData-Info as described in Table 6.9.4.3.3-3		TS 24.282 [31] clause 23.3.2.4	
MIME body part		**MCData-Regroup**		
MIME-part-headers				
Content-Type	"application/vnd.3gpp.mcdata-regroup+xml"			
Content-ID	Unique id in format of a Message-ID assigned by the SS	Unique URL identifying the MCData-Regroup XML MIME body; used as reference in the signature MIME body		
MIME-part-body	MCData-Regroup as described in Table 6.9.4.3.3-4		TS 24.282 [31] clause 23.3.2.4	

Table 6.9.4.3.3-3: MCData-Info in SIP MESSAGE (Table 6.9.4.3.3-2)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.2.2-3				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
mcdatainfo				
mcdata-Params				
mcdata-request-uri	not present			
mcdata-calling-user-id	not present			
mcdata-client-id	Encrypted <mcdata-client-id> with mcdataString set to px_MCX_Client_B_ID	Encryption according to NOTE 1 in TS 37.579-1 [2] Table 5.5.3.2.2-3	TS 24.282 [31] clause 23.3.2.4	

Table 6.9.4.3.3-4: MCData-Regroup in SIP MESSAGE (Table 6.9.4.3.3-2)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.16.3-3, condition USER_REGROUP

Table 6.9.4.3.3-5: SIP INVITE from the UE (step 6, Table 6.9.4.3.2-1; step 2, TS 37.579-1 [2] Table 5.3C.2.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.5.1-1				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
MIME body part		**SDP message**		
MIME-part-body	SDP Message as described in Table 6.9.4.3.3-6			
MIME body part		**MCData-Info**		
MIME-part-body	MCData-Info as described in Table 6. 9. 4.3.3-7			

Table 6.9.4.3.3-6: SDP in SIP INVITE (Table 6.9.4.3.3-5)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.1.1-3, condition INITIAL_SDP_OFFER, MCDATA_SDS, SDS_SESSION

Table 6.9.4.3.3-7: MCData-Info in SIP INVITE (Table 6.9.4.3.3-5)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.2.1-3, condition MCD_grp				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
mcdatainfo				
mcdata-Params				
request-type	"group-sds-session"			
mcdata-request-uri	Encrypted <mcdata-request-uri> with mcdataURI set to px_MCData_Group_T_ID	Encryption according to NOTE 1 and NOTE 2 in TS 37.579-1 [2] Table 5.5.3.2.1-3		

Table 6.9.4.3.3-8: SIP 200 (OK) from the SS (step 6, Table 6.9.4.3.2-1; step 4, TS 37.579-1 [2] Table 5.3C.2.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.17.1.2-1, condition INVITE-RSP				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Message-body				
SDP Message	As described in Table 6.9.4.3.3-9			

Table 6.9.4.3.3-9: SDP in SIP 200 (OK) (Table 6.9.4.3.3-8)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.1.2-3, condition SDP_ANSWER, SDS_SESSION, MCDATA_SDS

Table 6.9.4.3.3-10: SIP MESSAGE from the SS (Step 9, Table 6.9.4.3.2-1; Step 2, TS 37.579-1 [2], Table 5.3.33.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.2.7.2-1, condition ACCEPT-CONTACT-WITH-MEDIA-FEATURE-TAG				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
P-Asserted-Identity				
name-addr	px_MCX_SIP_PublicUserId_B		TS 24.282 [31] clause 23.3.2.5	
Message-body				
MIME body part		**MCData-Info**		
MIME-part-body	MCData-Info as described in Table 6.9.4.3.3-3		TS 24.282 [31] clause 23.3.2.5	
MIME body part		**MCData-Regroup**		
MIME-part-headers				
Content-Type	"application/vnd.3gpp.mcdata-regroup+xml"			
Content-ID	Unique id in format of a Message-ID assigned by the SS	Unique URL identifying the MCData-Regroup XML MIME body; used as reference in the signature MIME body		
MIME-part-body	MCData-Regroup as described in Table 6.9.4.3.3-11		TS 24.282 [31] clause 23.3.2.5	

Table 6.9.4.3.3-11: MCData-Regroup in SIP MESSAGE (Table 6.9.4.3.3-10)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.16.3-3, condition REMOVE

7 Off-Network Test Scenarios

7.1 Short Data Service (SDS)

7.1.1 Off-network / Short Data Service (SDS) / Standalone SDS using signalling control plane / One-to-one SDS message / Client Originated (CO)

7.1.1.1 Test Purpose (TP)

(1)

```
with { UE (MCData Client) registered and authorized for MCData Service, including authorized for
MCData Service in off-network environment, and, the UE is in an off-network environment }
ensure that {
  when { the MCDATA User requests to send a standalone one-to-one SDS message with a disposition
request type of DELIVERY }
    then { UE (MCDATA Client) sends a SDS OFF-NETWORK MESSAGE message, and, initiates counter CFS1
(SDS retransmission) to 1 and starts timer TFS1 (SDS retransmission) }
            }
```

(2)

```
with { UE (MCData Client) having sent a SDS OFF-NETWORK MESSAGE message and started timer TFS1 (SDS
retransmission) }
ensure that {
  when { timer TFS1 (SDS retransmission) expires }
    then { UE (MCData Client) retransmits the SDS OFF-NETWORK MESSAGE message and, stops re-
transmitting if the counter CFS1 (SDS retransmission) has reached its maximum value and TFS1 (SDS
retransmission) has expired }
            }
```

(3)

```
with { UE (MCData Client) registered and authorized for MCData Service, including authorized for
MCData Service in off-network environment, and, the UE is in an off-network environment }
ensure that {
  when { the MCDATA User requests to send a standalone one-to-one SDS message with a disposition
request type of READ }
    then { UE (MCDATA Client) sends a SDS OFF-NETWORK MESSAGE message, and, initiates counter CFS1
(SDS retransmission) to 1 and starts timer TFS1 (SDS retransmission) }
            }
```

(4)

```
with { UE (MCData Client) registered and authorized for MCData Service, including authorized for
MCData Service in off-network environment, and, the UE is in an off-network environment }
ensure that {
  when { the MCDATA User requests to send a standalone one-to-one SDS message with a disposition
request type of DELIVERY AND READ }
    then { UE (MCDATA Client) sends a SDS OFF-NETWORK MESSAGE message, and, initiates counter CFS1
(SDS retransmission) to 1 and starts timer TFS1 (SDS retransmission) }
            }
```

7.1.1.2 Conformance requirements

References: The conformance requirements covered in the current TC are specified in:

TS 24.282 clauses 9.3.2.2, 9.3.2.3. Unless otherwise stated these are Rel-15 requirements.

[TS 24.282, clause 9.3.2.2]

Upon receiving an indication to send an SDS message, the MCData client:

1) if the request to send the SDS message is for a MCData group, shall check if the value of "/<*x*>/<x>/Common/MCData/AllowedSDS" leaf node, present in the group configuration as specified in 3GPP TS 24.483 [42], is set to "false". It the value is set to "false", shall reject the request to send the SDS message and not continue with the remaining procedures in this clause;

2) if:

   a) a one-to-one SDS message is to be sent then, shall store the MCData user ID of the intended recipient as the target MCData user ID; or

   b) a group SDS message is to be sent then, shall store the MCData group ID as the target MCData group ID;

3) may set the stored SDS disposition request type as:

   a) "DELIVERY", if only delivery disposition is requested;

   b) "READ", if only read disposition is requested; or

   c) "DELIVERY AND READ", if both delivery and read dispositions are requested;

4) if an existing conversation is indicated then, shall store the conversation identifier of the indicated conversation as SDS conversation ID. Otherwise, shall generate an UUID as described in IETF RFC 4122 [14] and store SDS conversation ID;

5) shall generate an UUID as described in IETF RFC 4122 [14] and store as the SDS message ID;

6) if indicated that the SDS message is in reply to another SDS message then, shall store the message identifier of the indicated message as SDS reply ID;

7) if indicated that the target recipient of the SDS message is an application then, shall store the application ID of the indicated application as the SDS application ID or as the SDS extended application ID;

8) shall store the received payload as the SDS payload;

9) shall store the received payload type as the SDS payload type;

10) shall store the current UTC time as the SDS transmission time;

11) shall generate a SDS OFF-NETWORK MESSAGE message as specified in clause 15.1.7. In the SDS OFF-NETWORK MESSAGE message, the MCData client:

   a) shall set the Sender MCData user ID IE to its own MCData user ID;

   b) if:

      i) a one-to-one SDS message is to be sent then shall set the Recipient MCData user ID IE to the stored target MCData user ID as specified in clause 15.2.15; or

      ii) a group SDS message is to be sent then, shall set the MCData group ID IE to the stored target MCData group ID as specified in clause 15.2.14;

   c) may set the SDS disposition request type IE to the stored the SDS disposition request type as specified in clause 15.2.3;

   d) shall set the Conversation ID IE to the stored conversation ID as specified in clause 15.2.9;

   e) shall set the Message ID IE to the stored SDS message ID as specified in clause 15.2.10;

   f) shall set the Date and time IE to the stored SDS transmission time as specified in clause 15.2.8;

   g) may include the InReplyTo message ID IE set to the stored SDS reply ID as specified in clause 15.2.11;

h) may include:

i) the Application ID IE set to the stored SDS application ID as specified in clause 15.2.7; or

ii) the Extended application ID IE set to the stored SDS extended application ID as specified in clause 15.2.24;

i) if end-to-end security is required for a one-to-one communication and the security context does not exist or if the existing security context has expired, shall include the Security parameters and Payload IE with security parameters as described in 3GPP TS 33.180 [26];

j) if

i) end-to-end security is not required for a one-to-one communication, or

ii) sending the SDS OFF-NETWORK MESSAGE message to a MCData group;

may include the Payload IE as specified in clause 15.2.13 with:

i) the Payload content type to the stored SDS payload type; and

ii) the Payload data set to the stored SDS payload;

12) if:

a) a one-to-one SDS message is to be sent then, shall send the SDS OFF-NETWORK MESSAGE message as specified in clause 9.3.1.1; or

b) a group SDS message is to be sent then, shall send the SDS OFF-NETWORK MESSAGE message as specified in clause 9.3.1.2;

13) shall initialise the counter CFS1 (SDS retransmission) with the value set to 1; and

14) shall start timer TFS1 (SDS retransmission).

[TS 24.282, clause 9.3.2.3]

Upon expiry of timer TFS1 (SDS retransmission), the MCData client:

1) shall generate a SDS OFF-NETWORK MESSAGE message as specified in clause 15.1.7. In the SDS OFF-NETWORK MESSAGE message, the MCData client:

a) shall set the Sender MCData user ID IE to its own MCData user ID;

b) if:

i) a one-to-one SDS message is to be sent then, shall set the Recipient MCData user ID IE to the stored target MCData user ID; or

ii) a group SDS message is to be sent then, shall set the MCData group ID IE to the stored target MCData group ID;

c) may set the SDS disposition request type IE to the stored the SDS disposition request type as specified in clause 15.2.3;

d) shall set the Conversation ID IE to the stored conversation ID as specified in clause 15.2.9;

e) shall set the Message ID IE to the stored SDS message ID as specified in clause 15.2.10;

f) shall set the Date and time IE to the stored the SDS transmission time as specified in clause 15.2.8;

g) may include the InReplyTo message ID IE set to the stored SDS reply ID as specified in clause 15.2.11;

h) may include:

i) the Application ID IE set to the stored SDS application ID as specified in clause 15.2.7; or

ii) the Extended application ID IE set to the stored SDS extended application ID as specified in clause 15.2.24;

i) if end-to-end security is required for a one-to-one communication and the security context does not exist or if the existing security context has expired, shall include the Security parameters IE with security parameters as described in 3GPP TS 33.180 [26]; and

j) if:

i) end-to-end security is not required for a one-to-one communication, or

ii) sending the SDS OFF-NETWORK MESSAGE message to a MCData group;

may include the Payload IE as specified in clause 15.2.13 with:

i) the Payload content type to the stored SDS payload type; and

ii) the Payload data set to the stored SDS payload;

2) if:

a) a one-to-one SDS message was sent then, shall send the SDS OFF-NETWORK MESSAGE message as specified in clause 9.3.1.1; or

b) a group SDS message was sent then, shall send the SDS OFF-NETWORK MESSAGE message as specified in clause 9.3.1.2;

3) shall increment the counter CFS1(SDS retransmission) by 1; and

4) shall start timer TFS1 (SDS retransmission) if the associated counter CFS1 (SDS retransmission) has not reached its upper limit.

7.1.1.3 Test description

7.1.1.3.1 Pre-test conditions

System Simulator:

- SS-UE1 (MCData Client)
  - For the underlying "transport bearer" over which the SS and the UE will communicate, the SS is behaving as SS-UE1 as defined in TS 36.508 [24], configured for and operating as ProSe Direct Communication transmitting and receiving device.
- GNSS simulator to simulate a location and provide a timing reference for the assistance of E-UTRAN off-network testing.

NOTE 1: For operation in off-network environment, it needs be ensured that after the UE is powered up it considers the Geographical area #1 that is simulated by the GNSS simulator as being one of the geographical areas set in the USIM for operation when UE is "not served by E-UTRAN".

- SS-NW (MCData server)
  - For the underlying "transport bearer" over which the SS and the UE will communicate Parameters are set to the default parameters for the basic E-UTRA Single cell network scenarios, as defined in TS 36.508 [24] clause 4.4. The simulated Cell 1 shall belong to PLMN1 (the PLMN specified for MCData operation in the MCData configuration document).

NOTE 2: The SS operation as NW (MCData server) is needed only for the preamble if the UE has to perform procedure 'MCX Authorization/Configuration and Key Generation' as specified in TS 37.579-1 [2] clause 5.3.2.

IUT:

- UE (MCData Client)

- The test USIM set as defined in TS 37.579-1 [2] clause 5.5.10 is inserted.
- For the underlying "transport bearer" over which the SS and the UE will communicate, the UE is behaving as a ProSe enabled UE as defined in TS 36.508 [24], configured for and operating as ProSe Direct Communication transmitting and receiving device.
- CFS1 (SDS retransmission) is set to the default value of 5.
- TFS1 (SDS retransmission) is set to the default value of 40 ms.

Preamble:

- The UE has performed procedure 'MCData UE registration' as specified in TS 37.579-1 [2] clause 5.4.2B.
- The UE has performed procedure 'MCX Authorization/Configuration and Key Generation' as specified in TS 37.579-1 [2] clause 5.3.2.
- The GNSS simulator is configured to simulate a location in the centre of Geographical area #1 and provide a timing reference, as defined in TS 36.508 [24] Table 4.11.2-2 scenario #1.
- The UE is switched-off.
- UE States at the end of the preamble
  - The UE is in state 'switched-off'.

7.1.1.3.2 Test procedure sequence

Table 7.1.1.3.2-1: Main behaviour

St	Procedure	Message Sequence		TP	Verdict
		U - S	Message		
1	Power up the UE.	-	-	-	-
2	Trigger the UE to reset UTC time and location. NOTE: The UTC time and location reset may be performed by MMI or AT command (+CUTCR).	-	-	-	-
3	Activate the MCData Client Application and register User A as the MCData User (TS 37.579-5 [5], px_MCX_User_A_username, px_MCX_User_A_password). (NOTE 1)	-	-	-	-
4	Make the MCData User request to send a standalone one-to-one SDS message to a single user with an SDS disposition request type of DELIVERY. (NOTE 1)	-	-	-	-
-	EXCEPTION: The E-UTRA/EPC actions which are related to the MCData call establishment are described in TS 37.579-1 [2] clause 5.4.5 'MCX CO communication over ProSe direct one-to-one communication out of E-UTRA coverage-establishment'. The test sequence below shows only the MCData relevant messages exchanged.	-	-	-	-
-	EXCEPTION: Steps 5-7 are repeated CFS1=5 times (CFS1 defined in 24.282 [31] Table G.3.1-1)	-	-	-	-
5	Check: Does the UE (MCData Client) send a SDS OFF-NETWORK MESSAGE message with a disposition request type of DELIVERY? NOTE: It is expected that the UE - shall initialize the counter CFS1 (SDS retransmission) with the value set to 1 on the first transmission, and, increase it by 1 with each re-transmission. - shall start timer TFS1 (SDS retransmission)	-->	SDS OFF-NETWORK MESSAGE	1,2	P
6	Start TFS1 (SDS retransmission) 40 milliseconds as defined in 24.282 [31] Table F.3.1-1.	-	-	-	-
7	TFS1 expires.	-	-	-	-
-	EXCEPTION: UE releases the E-UTRA connection. The E-UTRA/EPC actions which are related to the MCData call release are described in TS 37.579-1 [2] clause 5.4.8, 'MCX communication over ProSe direct one-to-one communication out of E-UTRA coverage - release by the UE'.	-	-	-	-
-	EXCEPTION: The E-UTRA/EPC actions which are related to the MCData call establishment are described in TS 37.579-1 [2] clause 5.4.6 'MCX CT communication over ProSe direct one-to-one communication out of E-UTRA coverage-establishment'. The test sequence below shows only the MCData relevant messages exchanged.	-	-	-	-
-	EXCEPTION: Steps 8-10 are repeated 5 times.	-	-	-	-
8	SS-UE1 (MCData Client) sends a SDS OFF-NETWORK NOTIFICATION message with disposition notification type of DELIVERED.	<--	SDS OFF-NETWORK NOTIFICATION	-	-
9	Start 40 millisecond timer.	-	-	-	-

10	40 millisecond timer expires	-	-	-	-
-	EXCEPTION: SS releases the E-UTRA connection. The E-UTRA/EPC actions which are related to the MCData call release are described in TS 37.579-1 [2] clause 5.4.7, 'MCX communication over ProSe direct one-to-one communication out of E-UTRA coverage - release by the SS'.	-	-	-	-
11	Make the MCData User request to send a standalone one-to-one SDS message to a single user with an SDS disposition request type of READ. (NOTE 1)	-	-	-	-
-	EXCEPTION: The E-UTRA/EPC actions which are related to the MCData call establishment are described in TS 37.579-1 [2] clause 5.4.5 'MCX CO communication over ProSe direct one-to-one communication out of E-UTRA coverage-establishment'. The test sequence below shows only the MCData relevant messages exchanged.	-	-	-	-
-	EXCEPTION: Steps 12-14 are repeated CFS1=5 times (CFS1 defined in 24.282 [31] Table G.3.1-1)	-	-	-	-
12	Check: Does the UE (MCData Client) send a SDS OFF-NETWORK MESSAGE message with a disposition request type of READ? NOTE: It is expected that the UE - shall initialize the counter CFS1 (SDS retransmission) with the value set to 1 on the first transmission, and, increase it by 1 with each re-transmission. - shall start timer TFS1 (SDS retransmission)	-->	SDS OFF-NETWORK MESSAGE	3,2	P
13	Start TFS1 (SDS retransmission) 40 milliseconds as defined in 24.282 [31] Table F.3.1-1.	-	-	-	-
14	TFS1 expires.	-	-	-	-
-	EXCEPTION: UE releases the E-UTRA connection. The E-UTRA/EPC actions which are related to the MCData call release are described in TS 37.579-1 [2] clause 5.4.8, 'MCX communication over ProSe direct one-to-one communication out of E-UTRA coverage - release by the UE'.	-	-	-	-
-	EXCEPTION: The E-UTRA/EPC actions which are related to the MCData call establishment are described in TS 37.579-1 [2] clause 5.4.6 'MCX CT communication over ProSe direct one-to-one communication out of E-UTRA coverage-establishment'. The test sequence below shows only the MCData relevant messages exchanged.	-	-	-	-
-	EXCEPTION: Steps 15-17 are repeated 5 times.	-	-	-	-
15	SS-UE1 (MCData Client) sends a SDS OFF-NETWORK NOTIFICATION message with disposition notification type of READ.	<--	SDS OFF-NETWORK NOTIFICATION	-	-
16	Start 40 millisecond timer.	-	-	-	-
17	40 millisecond timer expires	-	-	-	-

-	EXCEPTION: SS releases the E-UTRA connection. The E-UTRA/EPC actions which are related to the MCData call release are described in TS 37.579-1 [2] clause 5.4.7, 'MCX communication over ProSe direct one-to-one communication out of E-UTRA coverage - release by the SS'.	-	-	-	-
18	Make the MCData User request to send a standalone one-to-one SDS message to a single user with an SDS disposition request type of DELIVERY AND READ. (NOTE 1)	-	-	-	-
-	EXCEPTION: The E-UTRA/EPC actions which are related to the MCData call establishment are described in TS 37.579-1 [2] clause 5.4.5 'MCX CO communication over ProSe direct one-to-one communication out of E-UTRA coverage-establishment'. The test sequence below shows only the MCData relevant messages exchanged.	-	-	-	-
-	EXCEPTION: Steps 12-14 are repeated CFS1=5 times (CFS1 defined in 24.282 [31] Table G.3.1-1)	-	-	-	-
19	Check: Does the UE (MCData Client) send a SDS OFF-NETWORK MESSAGE message with a disposition request type of DELIVERY AND READ? NOTE: It is expected that the UE - shall initialize the counter CFS1 (SDS retransmission) with the value set to 1 on the first transmission, and, increase it by 1 with each re-transmission. - shall start timer TFS1 (SDS retransmission)	-->	SDS OFF-NETWORK MESSAGE	4,2	P
20	Start TFS1 (SDS retransmission) 40 milliseconds as defined in 24.282 [31] Table F.3.1-1.	-	-	-	-
21	TFS1 expires.	-	-	-	-
-	EXCEPTION: UE releases the E-UTRA connection. The E-UTRA/EPC actions which are related to the MCData call release are described in TS 37.579-1 [2] clause 5.4.8, 'MCX communication over ProSe direct one-to-one communication out of E-UTRA coverage - release by the UE'.	-	-	-	-
-	EXCEPTION: The E-UTRA/EPC actions which are related to the MCData call establishment are described in TS 37.579-1 [2] clause 5.4.6 'MCX CT communication over ProSe direct one-to-one communication out of E-UTRA coverage-establishment'. The test sequence below shows only the MCData relevant messages exchanged.	-	-	-	-
-	EXCEPTION: Steps 15-17 are repeated 5 times.	-	-	-	-
22	SS-UE1 (MCData Client) sends a SDS OFF-NETWORK NOTIFICATION message with disposition notification type of DELIVERED AND READ.	<--	SDS OFF-NETWORK NOTIFICATION	-	-
23	Start 40 millisecond timer.	-	-	-	-
24	40 millisecond timer expires	-	-	-	-

-	EXCEPTION: SS releases the E-UTRA connection. The E-UTRA/EPC actions which are related to the MCData call release are described in TS 37.579-1 [2] clause 5.4.7, 'MCX communication over ProSe direct one-to-one communication out of E-UTRA coverage - release by the SS'.	-	-	-	-
NOTE 1: This is expected to be done via a suitable implementation dependent MMI.					

7.1.1.3.3 Specific message contents

Table 7.1.1.3.3-1: SDS OFF-NETWORK MESSAGE (step 5, Table 7.1.1.3.2-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.9-1, condition DELIVERED, MCD_1to1

Table 7.1.1.3.3-2: SDS OFF-NETWORK NOTIFICATION (step 8, Table 7.1.1.3.2-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.12-1, condition DELIVERED

Table 7.1.1.3.3-3: SDS OFF-NETWORK MESSAGE (step 12, Table 7.1.1.3.2-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.9-1, condition READ, MCD_1to1

Table 7.1.1.3.3-4: SDS OFF-NETWORK NOTIFICATION (step 15, Table 7.1.1.3.2-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.12-1, condition READ

Table 7.1.1.3.3-5: SDS OFF-NETWORK MESSAGE (step 19, Table 7.1.1.3.2-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.9-1, condition DELIVERED_READ, MCD_1to1

Table 7.1.1.3.3-6: SDS OFF-NETWORK NOTIFICATION (step 22, Table 7.1.1.3.2-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.12-1, condition DELIVERED_READ

7.1.2 Off-network / Short Data Service (SDS) / Standalone SDS using signalling control plane / One-to-one SDS message / Client Terminated (CT)

7.1.2.1 Test Purpose (TP)

(1)

```
with { UE (MCData Client) registered and authorized for MCData Service, including authorized for
MCData Service in off-network environment, and, the UE is in an off-network environment }
ensure that {
  when { the UE (MCData Client) receives an SDS OFF-NETWORK MESSAGE message with a disposition of
DELIVERY }
    then { UE (MCDATA Client) sends SDS OFF-NETWORK NOTIFICATION message with a disposition
notification type of DELIVERED and, initiates counter CFS2 (SDS notification retransmission) to 1
and starts timer TFS2 (SDS notification retransmission) }
            }
```

(2)

```
with { UE (MCData Client) having sent a SDS OFF-NETWORK NOTIFICATION message and started timer TFS2
(SDS notification retransmission) }
ensure that {
  when { TFS2 (SDS notification retransmission) expires }
    then { UE (MCData Client) retransmits the SDS OFF-NETWORK NOTIFICATION message and, stops re-
transmitting if the counter CFS2 (SDS notification retransmission) has reached its maximum value and
TFS2 (SDS notification retransmission) }
            }
```

(3)

```
with { UE (MCData Client) registered and authorized for MCData Service, including authorized for
MCData Service in off-network environment, and, the UE is in an off-network environment }
ensure that {
  when { the UE (MCData Client) receives an SDS OFF-NETWORK MESSAGE message with a disposition of
READ }
    then { UE (MCDATA Client) sends a SDS OFF-NETWORK NOTIFICATION message with a disposition
notification type of READ upon receiving a display indication for the payload to the MCData User
and, initiates counter CFS2 (SDS notification retransmission) to 1 and starts timer TFS2 (SDS
notification retransmission) }
            }
```

(4)

```
with { UE (MCData Client) registered and authorized for MCData Service, including authorized for
MCData Service in off-network environment, and, the UE is in an off-network environment }
ensure that {
  when { the UE (MCData Client) receives an SDS OFF-NETWORK MESSAGE message with a disposition of
DELIVERY AND READ }
    then { UE (MCDATA Client) sends a SDS OFF-NETWORK NOTIFICATION message with a disposition
notification type of DELIVERED AND READ after the message is rendered to the user if the timer TFS3
(delivery and read) has not expired, or, if the timer TFS3 (delivery and read) expires before the
message is rendered to the MCData User, sends first a SDS OFF-NETWORK NOTIFICATION message with a
disposition notification type of DELIVERED and then sends a SDS OFF-NETWORK NOTIFICATION message
with a disposition notification type of READ after the payload is rendered to the MCData User, and,
initiates counter CFS2 (SDS notification retransmission) to 1 and starts timer TFS2 (SDS
notification retransmission) after each sending of the SDS OFF-NETWORK NOTIFICATION message }
            }
```

7.1.2.2 Conformance requirements

References: The conformance requirements covered in the current TC are specified in:

TS 24.282 clauses 9.3.2.4, 9.3.2.5, 9.3.2.6, 12.3.2, 12.3.3, 12.3.4, 12.3.5. Unless otherwise stated these are Rel-15 requirements.

[TS 24.282, clause 9.3.2.4]

Upon receiving an SDS OFF-NETWORK MESSAGE message with a SDS disposition request type IE, the MCData client:

1) shall store the value of Sender MCData user ID IE as the stored notification target MCData user ID;
2) shall store the value of Conversation ID IE as the stored conversation ID;
3) shall store the value of Message ID IE as the stored SDS message ID;
4) shall store the current UTC time as the stored SDS notification time;
5) if present, shall store the value of Application ID IE as the stored SDS application ID;
6) if present, shall store the value of the Extended application ID IE as the stored SDS extended application ID;
7) if present, shall store the value of MCData group ID IE to the stored target MCData group ID; and
8) if the SDS disposition request type IE is set to:
    a) "DELIVERY" then, shall send a SDS OFF-NETWORK NOTIFICATION message as described in clause 12.3.2;

b) "READ" then, shall send a SDS OFF-NETWORK NOTIFICATION message as described in clause 12.3.3; or

c) "DELIVERY AND READ" then, shall start timer TFS3 (delivery and read).

NOTE: Duplicate messages (re-transmissions) that are received by the MCData client should not be processed again.

[TS 24.282, clause 9.3.2.5]

Upon receiving a display indication before timer TFS3 (delivery and read) expires, the MCData client:

1) shall generate and send a SDS OFF-NETWORK NOTIFICATION message as described in clause 12.3.4.

[TS 24.282, clause 9.3.2.6]

Upon expiry of timer TFS3 (delivery and read), the MCData client:

1) shall generate and send a SDS OFF-NETWORK NOTIFICATION message as described in clause 12.3.2; and

2) upon receiving a display indication, shall generate and send a SDS OFF-NETWORK NOTIFICATION message as described in clause 12.3.3.

[TS 24.282, clause 12.3.2]

To send an off-network SDS delivery notification, the MCData client:

1) shall store "DELIVERED" as the disposition type;

2) shall generate a SDS OFF-NETWORK NOTIFICATION message as specified in clause 15.1.8. In the SDS OFF-NETWORK NOTIFICATION message, the MCData client:

a) shall set the Sender MCData user ID IE to its own MCData user ID as specified in clause 15.2.15;

b) shall set the Conversation ID IE as the stored conversation ID as specified in clause 15.2.9;

c) shall set the Message ID IE as the stored SDS message ID as specified in clause 15.2.10;

d) shall set the Date and time IE as the stored SDS notification time as specified in clause 15.2.8;

e) shall set the SDS disposition notification type IE to the stored disposition type as specified in clause 15.2.5; and

f) may set:

i) the Application ID IE to the stored SDS application ID as specified in clause 15.2.7; or

ii) the Extended application ID IE to the stored extended SDS application ID as specified in clause 15.2.24;

3) shall send the SDS OFF-NETWORK NOTIFICATION message to the stored notification target MCData user ID as specified in clause 9.3.1.1;

4) shall initialise the counter CFS2 (SDS notification retransmission) with the value set to 1; and

5) shall start timer TFS2 (SDS notification retransmission).

[TS 24.282, clause 12.3.3]

Upon receiving a display indication for the payload to the user or processing of the payload by the target application, the MCData client:

1) shall store "READ" as the disposition type;

2) shall store the current UTC time as the stored SDS notification time;

3) shall generate SDS OFF-NETWORK NOTIFICATION message as specified in clause 15.1.8. In the SDS OFF-NETWORK NOTIFICATION message, the MCData client:

a) shall set the Sender MCData user ID IE to its own MCData user ID as specified in clause 15.2.15;

b) shall set the Conversation ID IE as the stored conversation ID as specified in clause 15.2.9;

c) shall set the Message ID IE as the stored SDS message ID as specified in clause 15.2.10;

d) shall set the Data and time IE as the SDS notification time as specified in clause 15.2.8;

e) shall set the SDS disposition notification type IE to the stored disposition type as specified in clause 15.2.5; and

f) may set:

i) the Application ID IE set to the stored SDS application ID as specified in clause 15.2.7; or

ii) the Extended application ID IE to the stored extended SDS application ID as specified in clause 15.2.24;

4) shall send the SDS OFF-NETWORK NOTIFICATION message to the stored sender MCData user ID as specified in clause 9.3.1.1;

5) shall initialise the counter CFS2 (SDS notification retransmission) with the value set to 1; and

6) shall start timer TFS2 (SDS notification retransmission).

[TS 24.282, clause 12.3.4]

Upon receiving a display indication for the payload to the user or processing of the payload by the target application, the MCData client:

1) shall store "DELIVERED AND READ" as the disposition type and stop the timer TFS3 (display and read);

2) shall store the current UTC time as the stored SDS notification time;

3) shall generate SDS OFF-NETWORK NOTIFICATION message. In the SDS OFF-NETWORK NOTIFICATION message, the MCData client:

a) shall set the Sender MCData user ID IE to its own MCData user ID as specified in clause 15.2.15;

b) shall set the Conversation ID IE as the stored conversation ID as specified in clause 15.2.9;

c) shall set the Message ID IE as the stored SDS message ID as specified in clause 15.2.10;

d) shall set the Date and time IE as the SDS notification time as specified in clause 15.2.8;

e) shall set the SDS disposition notification type IE to the stored disposition type as specified in clause 15.2.5; and

f) may set:

i) the Application ID IE to the stored SDS application ID as specified in clause 15.2.7; or

ii) the Extended application ID IE to the stored extended SDS application ID as specified in clause 15.2.24;

4) shall send the SDS OFF-NETWORK NOTIFICATION message to the stored sender MCData user ID as specified in clause 9.3.1.1;

5) shall initialise the counter CFS2 (SDS notification retransmission) with the value set to 1; and

6) shall start timer TFS2 (SDS notification retransmission).

[TS 24.282, clause 12.3.5]

Upon expiry of timer TFS2 (SDS notification retransmission), the MCData client:

1) shall generate a SDS OFF-NETWORK NOTIFICATION message as specified in clause 15.1.8. In the SDS OFF-NETWORK NOTIFICATION message, the MCData client:

a) shall set the Sender MCData user ID IE to its own MCData user ID as specified in clause 15.2.15;

b) shall set the Conversation ID IE as the stored conversation ID as specified in clause 15.2.9;

c) shall set the Message ID IE as the stored SDS message ID as specified in clause 15.2.10;

d) shall set the Date and time IE as the stored SDS notification time as specified in clause 15.2.8;

e) shall set the SDS disposition type IE to the stored disposition type as specified in clause 15.2.5; and

f) may set:

i) the Application ID IE to the stored SDS application ID as specified in clause 15.2.7; or

ii) the Extended application ID IE to the stored extended SDS application ID as specified in clause 15.2.24;

2) shall send the SDS OFF-NETWORK NOTIFICATION message to the stored sender MCData user ID as specified in clause 9.3.1.1;

3) shall increment the counter CFS2 (SDS notification retransmission) by 1; and

4) shall start timer TFS2 (SDS notification retransmission) if the associated counter CFS2 (SDS notification retransmission) has not reached its upper limit.

7.1.2.3 Test description

7.1.2.3.1 Pre-test conditions

System Simulator:

- SS-UE1 (MCData Client)
  - For the underlying "transport bearer" over which the SS and the UE will communicate, the SS is behaving as SS-UE1 as defined in TS 36.508 [24], configured for and operating as ProSe Direct Communication transmitting and receiving device.
- GNSS simulator to simulate a location and provide a timing reference for the assistance of E-UTRAN off-network testing.

NOTE 1: For operation in off-network environment, it needs be ensured that after the UE is powered up it considers the Geographical area #1 that is simulated by the GNSS simulator as being one of the geographical areas set in the USIM for operation when UE is "not served by E-UTRAN".

- SS-NW (MCData server)
  - For the underlying "transport bearer" over which the SS and the UE will communicate Parameters are set to the default parameters for the basic E-UTRA Single cell network scenarios, as defined in TS 36.508 [24] clause 4.4. The simulated Cell 1 shall belong to PLMN1 (the PLMN specified for MCData operation in the MCData configuration document).

NOTE 2: The SS operation as NW (MCData server) is needed only for the preamble if the UE has to perform procedure 'MCX Authorization/Configuration and Key Generation' as specified in TS 37.579-1 [2] clause 5.3.2.

IUT:

- UE (MCData Client)
- The test USIM set as defined in TS 37.579-1 [2] clause 5.5.10 is inserted.
- For the underlying "transport bearer" over which the SS and the UE will communicate, the UE is behaving as a ProSe enabled UE as defined in TS 36.508 [24], configured for and operating as ProSe Direct Communication transmitting and receiving device.
- CFS2 (SDS notification retransmission)is set to the default value of 5.
- TFS2 (SDS notification retransmission)is set to the default value of 40 ms.

- TFS3 (delivery and read)is set to the default value of 120 ms.

Preamble:

- The UE has performed procedure 'MCData UE registration' as specified in TS 37.579-1 [2] clause 5.4.2B.
- The UE has performed procedure 'MCX Authorization/Configuration and Key Generation' as specified in TS 37.579-1 [2] clause 5.3.2.
- The GNSS simulator is configured to simulate a location in the centre of Geographical area #1 and provide a timing reference, as defined in TS 36.508 [24] Table 4.11.2-2 scenario #1.
- The UE is switched-off.
- UE States at the end of the preamble
  - The UE is in state 'switched-off'.

7.1.2.3.2 Test procedure sequence

Table 7.1.2.3.2-1: Main behaviour

St	Procedure	Message Sequence		TP	Verdict
		U - S	Message		
1	Power up the UE.	-	-	-	-
2	Trigger the UE to reset UTC time and location. NOTE: The UTC time and location reset may be performed by MMI or AT command (+CUTCR).	-	-	-	-
3	Activate the MCData Client Application and register User A as the MCData User (TS 37.579-5 [5], px_MCX_User_A_username, px_MCX_User_A_password). (NOTE 1)	-	-	-	-
-	EXCEPTION: The E-UTRA/EPC actions which are related to the MCData call establishment are described in TS 37.579-1 [2] clause 5.4.6 'MCX CT communication over ProSe direct one-to-one communication out of E-UTRA coverage-establishment'. The test sequence below shows only the MCData relevant messages exchanged.	-	-	-	-
4	SS-UE1 (MCData Client) sends a SDS OFF-NETWORK NOTIFICATION message with disposition request type of DELIVERY.	<--	SDS OFF-NETWORK MESSAGE	-	-
-	EXCEPTION: Steps 5-7 are repeated CFS1=5 times (CFS1 defined in 24.282 [31] Table G.3.1-1)	-	-	-	-
5	Check: Does the UE (MCData Client) send a SDS OFF-NETWORK MESSAGE message with disposition notification type of DELIVERED? NOTE: It is expected that the UE - shall initialize the counter CFS2 (SDS notification retransmission) with the value set to 1 on the first transmission, and, increase it by 1 with each re-transmission. - shall start timer TFS2 (SDS notification retransmission)	-->	SDS OFF-NETWORK NOTIFICATION	1,2	P
6	Start TFS2 (SDS notification retransmission)=40 milliseconds as defined in 24.282 [31] Table F.3.1-1.	-	-	-	-
7	TFS2 expires.	-	-	-	-
-	EXCEPTION: UE releases the E-UTRA connection. The E-UTRA/EPC actions which are related to the MCData call release are described in TS 37.579-1 [2] clause 5.4.8, 'MCX communication over ProSe direct one-to-one communication out of E-UTRA coverage - release by the UE'.	-	-	-	-
-	EXCEPTION: The E-UTRA/EPC actions which are related to the MCData call establishment are described in TS 37.579-1 [2] clause 5.4.6 'MCX CT communication over ProSe direct one-to-one communication out of E-UTRA coverage-establishment'. The test sequence below shows only the MCData relevant messages exchanged.	-	-	-	-
8	SS-UE1 (MCData Client) sends a SDS OFF-NETWORK NOTIFICATION message with disposition request type of READ.	<--	SDS OFF-NETWORK MESSAGE	-	-
-	EXCEPTION: Steps 9-11 are repeated CFS2=5 times (CFS2 defined in 24.282 [31] Table G.3.1-1)	-	-	-	-

9	Check: Does the UE (MCData Client) send a SDS OFF-NETWORK MESSAGE message with disposition notification type of READ upon receiving a display indication for the payload to the MCData User? NOTE: It is expected that the UE - shall initialize the counter CFS2 (SDS notification retransmission) with the value set to 1 on the first transmission, and, increase it by 1 with each re-transmission. - shall start timer TFS2 (SDS notification retransmission)	-->	SDS OFF-NETWORK NOTIFICATION	3,2	P
10	Start TFS2 (SDS notification retransmission)=40 milliseconds as defined in 24.282 [31] Table F.3.1-1.	-	-	-	-
11	TFS2 expires.	-	-	-	-
-	EXCEPTION: UE releases the E-UTRA connection. The E-UTRA/EPC actions which are related to the MCData call release are described in TS 37.579-1 [2] clause 5.4.8, 'MCX communication over ProSe direct one-to-one communication out of E-UTRA coverage - release by the UE'.	-	-	-	-
-	EXCEPTION: The E-UTRA/EPC actions which are related to the MCData call establishment are described in TS 37.579-1 [2] clause 5.4.6 'MCX CT communication over ProSe direct one-to-one communication out of E-UTRA coverage-establishment'. The test sequence below shows only the MCData relevant messages exchanged.	-	-	-	-
12	SS-UE1 (MCData Client) sends a SDS OFF-NETWORK NOTIFICATION message with disposition request type of DELIVERY AND READ. NOTE: Timer TFS3 (delivery and read).is started upon receipt of the SDS OFF-NETWORK MESSAGE message that contains a "DELIVERY AND READ" disposition request. TFS3 (delivery and read)=120ms according to the default value defined in TS 24.282 [31] Table F.3.1-1.	<--	SDS OFF-NETWORK MESSAGE	-	-
-	EXCEPTION: Steps 13a1-13b2 describe behaviour that depends on the UE implementation. Steps 13a1-13a6 describe the behaviour of the UE when the timer TFS3 (delivery and read) expires before the contents of the Payload IE are rendered to the MCData User. Steps 13b1-13b3 describe the behaviour of the UE when the contents of the Payload IE are rendered to the MCData User before the timer TFS3 (delivery and read) expires.	-	-	-	-
-	EXCEPTION: Steps 13a1-13a3 are repeated CFS1=5 times (CFS1 defined in 24.282 [31] Table G.3.1-1)	-	-	-	-

13a1	Check: Does the UE (MCData Client) send a SDS OFF-NETWORK MESSAGE message with disposition notification type of DELIVERED? NOTE: It is expected that the UE - shall initialize the counter CFS2 (SDS notification retransmission) with the value set to 1 on the first transmission, and, increase it by 1 with each re-transmission. - shall start timer TFS2 (SDS notification retransmission)	-->	SDS OFF-NETWORK NOTIFICATION	4,2	P
13a2	Start TFS2 (SDS notification retransmission)=40 milliseconds as defined in 24.282 [31] Table F.3.1-1.	-	-	-	-
13a3	TFS2 expires.	-	-	-	-
-	EXCEPTION: Steps 13a4-13a6 are repeated CFS2=5 times (CFS2 defined in 24.282 [31] Table G.3.1-1)	-	-	-	-
13a4	Check: Does the UE (MCData Client) send a SDS OFF-NETWORK MESSAGE message with disposition notification type of READ upon receiving a display indication for the payload to the MCData User? NOTE: It is expected that the UE - shall initialize the counter CFS2 (SDS notification retransmission) with the value set to 1 on the first transmission, and, increase it by 1 with each re-transmission. - shall start timer TFS2 (SDS notification retransmission)	-->	SDS OFF-NETWORK NOTIFICATION	4,2	P
13a5	Start TFS2 (SDS notification retransmission)=40 milliseconds as defined in 24.282 [31] Table F.3.1-1.	-	-	-	-
13a6	TFS2 expires.	-	-	-	-
-	EXCEPTION: Steps 13b1-13b3 are repeated CFS1=5 times (CFS1 defined in 24.282 [31] Table G.3.1-1)	-	-	-	-
13b1	Check: Does the UE (MCData Client) send a SDS OFF-NETWORK MESSAGE message with disposition notification type of DELIVERED AND READ? NOTE: It is expected that the UE - shall initialize the counter CFS2 (SDS notification retransmission) with the value set to 1 on the first transmission, and, increase it by 1 with each re-transmission. - shall start timer TFS2 (SDS notification retransmission)	-->	SDS OFF-NETWORK NOTIFICATION	4,2	P
13b2	Start TFS2 (SDS notification retransmission)=40 milliseconds as defined in 24.282 [31] Table F.3.1-1.	-	-	-	-
13b3	TFS2 expires.	-	-	-	-
-	EXCEPTION: UE releases the E-UTRA connection. The E-UTRA/EPC actions which are related to the MCData call release are described in TS 37.579-1 [2] clause 5.4.8, 'MCX communication over ProSe direct one-to-one communication out of E-UTRA coverage - release by the UE'.	-	-	-	-
NOTE 1: This is expected to be done via a suitable implementation dependent MMI.					

7.1.2.3.3 Specific message contents

Table 7.1.2.3.3-1: SDS OFF-NETWORK MESSAGE (step 4, Table 7.1.2.3.2-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.9-1, condition DELIVERED, MCD_1to1

Table 7.1.2.3.3-2: SDS OFF-NETWORK NOTIFICATION (steps 5, 13a1, Table 7.1.2.3.2-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.12-1, condition DELIVERED

Table 7.1.2.3.3-3: SDS OFF-NETWORK MESSAGE (step 8, Table 7.1.2.3.2-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.9-1, condition READ, MCD_1to1

Table 7.1.2.3.3-4: SDS OFF-NETWORK NOTIFICATION (steps 9, 13a4, Table 7.1.2.3.2-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.12-1, condition READ

Table 7.1.2.3.3-5: SDS OFF-NETWORK MESSAGE (step 8, Table 7.1.2.3.2-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.9-1, condition DELIVERED_READ, MCD_1to1

Table 7.1.2.3.3-6: SDS OFF-NETWORK NOTIFICATION (step 13b1, Table 7.1.2.3.2-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.12-1, condition DELIVERED_READ

7.1.3 Off-network / Short Data Service (SDS) / Standalone SDS using signalling control plane / Group SDS message / Client Originated (CO)

7.1.3.1 Test Purpose (TP)

(1)

```
with { UE (MCData Client) registered and authorized for MCData Service, including authorized for
MCData Service in off-network environment, and, the UE is in an off-network environment }
ensure that {
  when { the MCDATA User requests to send a standalone group SDS message with a disposition request
type of DELIVERY }
    then { UE (MCDATA Client) sends a SDS OFF-NETWORK MESSAGE message, and, initiates counter CFS1
(SDS retransmission) to 1 and starts timer TFS1 (SDS retransmission) }
            }
```

(2)

```
with { UE (MCData Client) having sent a SDS OFF-NETWORK MESSAGE message and started timer TFS1 (SDS
retransmission) }
ensure that {
  when { timer TFS1 (SDS retransmission) expires }
    then { UE (MCData Client) retransmits the SDS OFF-NETWORK MESSAGE message and, stops re-
transmitting if the counter CFS1 (SDS retransmission) has reached its maximum value and TFS1 (SDS
retransmission) has expired }
            }
```

(3)

```
with { UE (MCData Client) registered and authorized for MCData Service, including authorized for
MCData Service in off-network environment, and, the UE is in an off-network environment }
```

```
ensure that {
  when { the MCDATA User requests to send a standalone group SDS message with a disposition request
type of READ }
    then { UE (MCDATA Client) sends a SDS OFF-NETWORK MESSAGE message, and, initiates counter CFS1
(SDS retransmission) to 1 and starts timer TFS1 (SDS retransmission) }
            }
```

(4)

```
with { UE (MCData Client) registered and authorized for MCData Service, including authorized for
MCData Service in off-network environment, and, the UE is in an off-network environment }
ensure that {
  when { the MCDATA User requests to send a standalone group SDS message with a disposition request
type of DELIVERY AND READ }
    then { UE (MCDATA Client) sends a SDS OFF-NETWORK MESSAGE message, and, initiates counter CFS1
(SDS retransmission) to 1 and starts timer TFS1 (SDS retransmission) }
            }
```

7.1.3.2 Conformance requirements

References: The conformance requirements covered in the current TC are specified in:

TS 24.282 clauses 9.3.2.2, 9.3.2.3. Unless otherwise stated these are Rel-15 requirements.

[TS 24.282, clause 9.3.2.2]

Upon receiving an indication to send an SDS message, the MCData client:

1) if the request to send the SDS message is for a MCData group, shall check if the value of "/<*x*>/<*x*>/Common/MCData/AllowedSDS" leaf node, present in the group configuration as specified in 3GPP TS 24.483 [42], is set to "false". It the value is set to "false", shall reject the request to send the SDS message and not continue with the remaining procedures in this clause;

2) if:

   a) a one-to-one SDS message is to be sent then, shall store the MCData user ID of the intended recipient as the target MCData user ID; or

   b) a group SDS message is to be sent then, shall store the MCData group ID as the target MCData group ID;

3) may set the stored SDS disposition request type as:

   a) "DELIVERY", if only delivery disposition is requested;

   b) "READ", if only read disposition is requested; or

   c) "DELIVERY AND READ", if both delivery and read dispositions are requested;

4) if an existing conversation is indicated then, shall store the conversation identifier of the indicated conversation as SDS conversation ID. Otherwise, shall generate an UUID as described in IETF RFC 4122 [14] and store SDS conversation ID;

5) shall generate an UUID as described in IETF RFC 4122 [14] and store as the SDS message ID;

6) if indicated that the SDS message is in reply to another SDS message then, shall store the message identifier of the indicated message as SDS reply ID;

7) if indicated that the target recipient of the SDS message is an application then, shall store the application ID of the indicated application as the SDS application ID or as the SDS extended application ID;

8) shall store the received payload as the SDS payload;

9) shall store the received payload type as the SDS payload type;

10) shall store the current UTC time as the SDS transmission time;

11) shall generate a SDS OFF-NETWORK MESSAGE message as specified in clause 15.1.7. In the SDS OFF-NETWORK MESSAGE message, the MCData client:

a) shall set the Sender MCData user ID IE to its own MCData user ID;

b) if:

i) a one-to-one SDS message is to be sent then shall set the Recipient MCData user ID IE to the stored target MCData user ID as specified in clause 15.2.15; or

ii) a group SDS message is to be sent then, shall set the MCData group ID IE to the stored target MCData group ID as specified in clause 15.2.14;

c) may set the SDS disposition request type IE to the stored the SDS disposition request type as specified in clause 15.2.3;

d) shall set the Conversation ID IE to the stored conversation ID as specified in clause 15.2.9;

e) shall set the Message ID IE to the stored SDS message ID as specified in clause 15.2.10;

f) shall set the Date and time IE to the stored SDS transmission time as specified in clause 15.2.8;

g) may include the InReplyTo message ID IE set to the stored SDS reply ID as specified in clause 15.2.11;

h) may include:

i) the Application ID IE set to the stored SDS application ID as specified in clause 15.2.7; or

ii) the Extended application ID IE set to the stored SDS extended application ID as specified in clause 15.2.24;

i) if end-to-end security is required for a one-to-one communication and the security context does not exist or if the existing security context has expired, shall include the Security parameters and Payload IE with security parameters as described in 3GPP TS 33.180 [26];

j) if

i) end-to-end security is not required for a one-to-one communication, or

ii) sending the SDS OFF-NETWORK MESSAGE message to a MCData group;

may include the Payload IE as specified in clause 15.2.13 with:

i) the Payload content type to the stored SDS payload type; and

ii) the Payload data set to the stored SDS payload;

12) if:

a) a one-to-one SDS message is to be sent then, shall send the SDS OFF-NETWORK MESSAGE message as specified in clause 9.3.1.1; or

b) a group SDS message is to be sent then, shall send the SDS OFF-NETWORK MESSAGE message as specified in clause 9.3.1.2;

13) shall initialise the counter CFS1 (SDS retransmission) with the value set to 1; and

14) shall start timer TFS1 (SDS retransmission).

[TS 24.282, clause 9.3.2.3]

Upon expiry of timer TFS1 (SDS retransmission), the MCData client:

1) shall generate a SDS OFF-NETWORK MESSAGE message as specified in clause 15.1.7. In the SDS OFF-NETWORK MESSAGE message, the MCData client:

a) shall set the Sender MCData user ID IE to its own MCData user ID;

b) if:

i) a one-to-one SDS message is to be sent then, shall set the Recipient MCData user ID IE to the stored target MCData user ID; or

ii) a group SDS message is to be sent then, shall set the MCData group ID IE to the stored target MCData group ID;

c) may set the SDS disposition request type IE to the stored the SDS disposition request type as specified in clause 15.2.3;

d) shall set the Conversation ID IE to the stored conversation ID as specified in clause 15.2.9;

e) shall set the Message ID IE to the stored SDS message ID as specified in clause 15.2.10;

f) shall set the Date and time IE to the stored the SDS transmission time as specified in clause 15.2.8;

g) may include the InReplyTo message ID IE set to the stored SDS reply ID as specified in clause 15.2.11;

h) may include:

i) the Application ID IE set to the stored SDS application ID as specified in clause 15.2.7; or

ii) the Extended application ID IE set to the stored SDS extended application ID as specified in clause 15.2.24;

i) if end-to-end security is required for a one-to-one communication and the security context does not exist or if the existing security context has expired, shall include the Security parameters IE with security parameters as described in 3GPP TS 33.180 [26]; and

j) if:

i) end-to-end security is not required for a one-to-one communication, or

ii) sending the SDS OFF-NETWORK MESSAGE message to a MCData group;

may include the Payload IE as specified in clause 15.2.13 with:

i) the Payload content type to the stored SDS payload type; and

ii) the Payload data set to the stored SDS payload;

2) if:

a) a one-to-one SDS message was sent then, shall send the SDS OFF-NETWORK MESSAGE message as specified in clause 9.3.1.1; or

b) a group SDS message was sent then, shall send the SDS OFF-NETWORK MESSAGE message as specified in clause 9.3.1.2;

3) shall increment the counter CFS1(SDS retransmission) by 1; and

4) shall start timer TFS1 (SDS retransmission) if the associated counter CFS1 (SDS retransmission) has not reached its upper limit.

7.1.3.3 Test description

7.1.3.3.1 Pre-test conditions

System Simulator:

- SS-UE1 (MCData Client)
  - For the underlying "transport bearer" over which the SS and the UE will communicate, the SS is behaving as SS-UE1 as defined in TS 36.508 [24], configured for and operating as ProSe Direct Communication transmitting and receiving device.

- GNSS simulator to simulate a location and provide a timing reference for the assistance of E-UTRAN off-network testing.

NOTE 1: For operation in off-network environment, it needs be ensured that after the UE is powered up it considers the Geographical area #1 that is simulated by the GNSS simulator as being one of the geographical areas set in the USIM for operation when UE is "not served by E-UTRAN".

- SS-NW (MCData server)
  - For the underlying "transport bearer" over which the SS and the UE will communicate Parameters are set to the default parameters for the basic E-UTRA Single cell network scenarios, as defined in TS 36.508 [24] clause 4.4. The simulated Cell 1 shall belong to PLMN1 (the PLMN specified for MCData operation in the MCData configuration document).

NOTE 2: The SS operation as NW (MCData server) is needed only for the preamble if the UE has to perform procedure 'MCX Authorization/Configuration and Key Generation' as specified in TS 37.579-1 [2] clause 5.3.2.

IUT:

- UE (MCData Client)
- The test USIM set as defined in TS 37.579-1 [2] clause 5.5.10 is inserted.
- For the underlying "transport bearer" over which the SS and the UE will communicate, the UE is behaving as a ProSe enabled UE as defined in TS 36.508 [24], configured for and operating as ProSe Direct Communication transmitting and receiving device.
- CFS1 (SDS retransmission) is set to the default value of 5.
- TFS1 (SDS retransmission) is set to the default value of 40 ms.

Preamble:

- The UE has performed procedure 'MCData UE registration' as specified in TS 37.579-1 [2] clause 5.4.2B.
- The UE has performed procedure 'MCX Authorization/Configuration and Key Generation' as specified in TS 37.579-1 [2] clause 5.3.2.
- The GNSS simulator is configured to simulate a location in the centre of Geographical area #1 and provide a timing reference, as defined in TS 36.508 [24] Table 4.11.2-2 scenario #1.
- The UE is switched-off.
- UE States at the end of the preamble
  - The UE is in state 'switched-off'.

7.1.3.3.2 Test procedure sequence

Table 7.1.3.3.2-1: Main behaviour

St	Procedure	Message Sequence		TP	Verdict
		U - S	Message		
1	Power up the UE.	-	-	-	-
2	Trigger the UE to reset UTC time and location. NOTE: The UTC time and location reset may be performed by MMI or AT command (+CUTCR).	-	-	-	-
3	Activate the MCData Client Application and register User A as the MCData User (TS 37.579-5 [5], px_MCX_User_A_username, px_MCX_User_A_password). (NOTE 1)	-	-	-	-
4	Make the MCData User request to send a standalone group SDS message with an SDS disposition request type of DELIVERY. (NOTE 1)	-	-	-	-
-	EXCEPTION: The E-UTRA/EPC actions which are related to the MCData call establishment are described in TS 37.579-1 [2] clause 5.4.11 'MCX CO communication over ProSe direct one-to-many communication out of E-UTRA coverage / Monitoring/Discoverer procedure for group member discovery / One-to-many communication'. The test sequence below shows only the MCData relevant messages exchanged.	-	-	-	-
-	EXCEPTION: Steps 5-7 are repeated CFS1=5 times (CFS1 defined in 24.282 [31] Table G.3.1-1)	-	-	-	-
5	Check: Does the UE (MCData Client) send a SDS OFF-NETWORK MESSAGE message with a disposition request type of DELIVERY? NOTE: It is expected that the UE - shall initialize the counter CFS1 (SDS retransmission) with the value set to 1 on the first transmission, and, increase it by 1 with each re-transmission. - shall start timer TFS1 (SDS retransmission)	-->	SDS OFF-NETWORK MESSAGE	1,2	P
6	Start TFS1 (SDS retransmission) 40 milliseconds as defined in 24.282 [31] Table F.3.1-1.	-	-	-	-
7	TFS1 expires.	-	-	-	-
-	EXCEPTION: UE releases the E-UTRA connection. The E-UTRA/EPC actions which are related to the MCData call release are described in TS 37.579-1 [2] clause 5.4.8, 'MCX communication over ProSe direct one-to-one communication out of E-UTRA coverage - release by the UE'.	-	-	-	-
-	EXCEPTION: The E-UTRA/EPC actions which are related to the MCData call establishment are described in TS 37.579-1 [2] clause 5.4.10 'MCX CT communication over ProSe direct one-to-many communication out of E-UTRA coverage / Announcing/Discoveree procedure for group member discovery'. The test sequence below shows only the MCData relevant messages exchanged.	-	-	-	-
-	EXCEPTION: Steps 8-10 are repeated 5 times.	-	-	-	-

8	SS-UE1 (MCData Client) sends a SDS OFF-NETWORK NOTIFICATION message with disposition notification type of DELIVERED.	<--	SDS OFF-NETWORK NOTIFICATION	-	-
9	Start 40 millisecond timer.	-	-	-	-
10	40 millisecond timer expires	-	-	-	-
-	EXCEPTION: SS releases the E-UTRA connection. The E-UTRA/EPC actions which are related to the MCData call release are described in TS 37.579-1 [2] clause 5.4.7, 'MCX communication over ProSe direct one-to-one communication out of E-UTRA coverage - release by the SS'.	-	-	-	-
11	Make the MCData User request to send a standalone group SDS message with an SDS disposition request type of READ. (NOTE 1)	-	-	-	-
-	EXCEPTION: The E-UTRA/EPC actions which are related to the MCData call establishment are described in TS 37.579-1 [2] clause 5.4.11 'MCX CO communication over ProSe direct one-to-many communication out of E-UTRA coverage / Monitoring/Discoverer procedure for group member discovery / One-to-many communication'. The test sequence below shows only the MCData relevant messages exchanged.	-	-	-	-
-	EXCEPTION: Steps 12-14 are repeated CFS1=5 times (CFS1 defined in 24.282 [31] Table G.3.1-1)	-	-	-	-
12	Check: Does the UE (MCData Client) send a SDS OFF-NETWORK MESSAGE message with a disposition request type of READ? NOTE: It is expected that the UE - shall initialize the counter CFS1 (SDS retransmission) with the value set to 1 on the first transmission, and, increase it by 1 with each re-transmission. - shall start timer TFS1 (SDS retransmission)	-->	SDS OFF-NETWORK MESSAGE	3,2	P
13	Start TFS1 (SDS retransmission) 40 milliseconds as defined in 24.282 [31] Table F.3.1-1.	-	-	-	-
14	TFS1 expires.	-	-	-	-
-	EXCEPTION: UE releases the E-UTRA connection. The E-UTRA/EPC actions which are related to the MCData call release are described in TS 37.579-1 [2] clause 5.4.8, 'MCX communication over ProSe direct one-to-one communication out of E-UTRA coverage - release by the UE'.	-	-	-	-
-	EXCEPTION: The E-UTRA/EPC actions which are related to the MCData call establishment are described in TS 37.579-1 [2] clause 5.4.10 'MCX CT communication over ProSe direct one-to-many communication out of E-UTRA coverage / Announcing/Discoveree procedure for group member discovery'. The test sequence below shows only the MCData relevant messages exchanged.	-	-	-	-
-	EXCEPTION: Steps 15-17 are repeated 5 times.	-	-	-	-
15	SS-UE1 (MCData Client) sends a SDS OFF-NETWORK NOTIFICATION message with disposition notification type of READ.	<--	SDS OFF-NETWORK NOTIFICATION	-	-

16	Start 40 millisecond timer.	-	-	-	-
17	40 millisecond timer expires	-	-	-	-
-	EXCEPTION: SS releases the E-UTRA connection. The E-UTRA/EPC actions which are related to the MCData call release are described in TS 37.579-1 [2] clause 5.4.7, 'MCX communication over ProSe direct one-to-one communication out of E-UTRA coverage - release by the SS'.	-	-	-	-
18	Make the MCData User request to send a standalone group SDS message with an SDS disposition request type of DELIVERY AND READ. (NOTE 1)	-	-	-	-
-	EXCEPTION: The E-UTRA/EPC actions which are related to the MCData call establishment are described in TS 37.579-1 [2] clause 5.4.11 'MCX CO communication over ProSe direct one-to-many communication out of E-UTRA coverage / Monitoring/Discoverer procedure for group member discovery / One-to-many communication'. The test sequence below shows only the MCData relevant messages exchanged.	-	-	-	-
-	EXCEPTION: Steps 12-14 are repeated CFS1=5 times (CFS1 defined in 24.282 [31] Table G.3.1-1)	-	-	-	-
19	Check: Does the UE (MCData Client) send a SDS OFF-NETWORK MESSAGE message with a disposition request type of DELIVERY AND READ? NOTE: It is expected that the UE - shall initialize the counter CFS1 (SDS retransmission) with the value set to 1 on the first transmission, and, increase it by 1 with each re-transmission. - shall start timer TFS1 (SDS retransmission)	-->	SDS OFF-NETWORK MESSAGE	4,2	P
20	Start TFS1 (SDS retransmission) 40 milliseconds as defined in 24.282 [31] Table F.3.1-1.	-	-	-	-
21	TFS1 expires.	-	-	-	-
-	EXCEPTION: UE releases the E-UTRA connection. The E-UTRA/EPC actions which are related to the MCData call release are described in TS 37.579-1 [2] clause 5.4.8, 'MCX communication over ProSe direct one-to-one communication out of E-UTRA coverage - release by the UE'.	-	-	-	-
-	EXCEPTION: The E-UTRA/EPC actions which are related to the MCData call establishment are described in TS 37.579-1 [2] clause 5.4.10 'MCX CT communication over ProSe direct one-to-many communication out of E-UTRA coverage / Announcing/Discoveree procedure for group member discovery'. The test sequence below shows only the MCData relevant messages exchanged.	-	-	-	-
-	EXCEPTION: Steps 15-17 are repeated 5 times.	-	-	-	-
22	SS-UE1 (MCData Client) sends a SDS OFF-NETWORK NOTIFICATION message with disposition notification type of DELIVERED AND READ.	<--	SDS OFF-NETWORK NOTIFICATION	-	-

23	Start 40 millisecond timer.	-	-	-	-
24	40 millisecond timer expires	-	-	-	-
-	EXCEPTION: SS releases the E-UTRA connection. The E-UTRA/EPC actions which are related to the MCData call release are described in TS 37.579-1 [2] clause 5.4.7, 'MCX communication over ProSe direct one-to-one communication out of E-UTRA coverage - release by the SS'.	-	-	-	-
NOTE 1: This is expected to be done via a suitable implementation dependent MMI.					

7.1.3.3.3 Specific message contents

Table 7.1.3.3.3-1: SDS OFF-NETWORK MESSAGE (step 5, Table 7.1.3.3.2-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.9-1, condition DELIVERED, MCD_grp

Table 7.1.3.3.3-2: SDS OFF-NETWORK NOTIFICATION (step 8, Table 7.1.3.3.2-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.12-1, condition DELIVERED

Table 7.1.3.3.3-3: SDS OFF-NETWORK MESSAGE (step 12, Table 7.1.3.3.2-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.9-1, condition READ, MCD_grp

Table 7.1.3.3.3-4: SDS OFF-NETWORK NOTIFICATION (step 15, Table 7.1.3.3.2-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.12-1, condition READ

Table 7.1.3.3.3-5: SDS OFF-NETWORK MESSAGE (step 19, Table 7.1.3.3.2-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.9-1, condition DELIVERED_READ, MCD_grp

Table 7.1.3.3.3-6: SDS OFF-NETWORK NOTIFICATION (step 22, Table 7.1.3.3.2-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.12-1, condition DELIVERED_READ

7.1.4 Off-network / Short Data Service (SDS) / Standalone SDS using signalling control plane / Group SDS message / Client Terminated (CT)

7.1.4.1 Test Purpose (TP)

(1)

```
with { UE (MCData Client) registered and authorized for MCData Service, including authorized for
MCData Service in off-network environment, and, the UE is in an off-network environment }
ensure that {
  when { the UE (MCData Client) receives an SDS OFF-NETWORK MESSAGE message with a disposition of
DELIVERY }
    then { UE (MCDATA Client) sends SDS OFF-NETWORK NOTIFICATION message with a disposition
notification type of DELIVERED and, initiates counter CFS2 (SDS notification retransmission) to 1
and starts timer TFS2 (SDS notification retransmission) }
           }
```

(2)

with { UE (MCData Client) having sent a SDS OFF-NETWORK NOTIFICATION message and started timer TFS2 (SDS notification retransmission) }
ensure that {
  when { TFS2 (SDS notification retransmission) expires }
    then { UE (MCData Client) retransmits the SDS OFF-NETWORK NOTIFICATION message **and**, stops re-transmitting if the counter CFS2 (SDS notification retransmission) has reached its maximum value and TFS2 (SDS notification retransmission) }
            }

(3)

with { UE (MCData Client) registered and authorized for MCData Service, including authorized for MCData Service in off-network environment, and, the UE is in an off-network environment }
ensure that {
  when { the UE (MCData Client) receives an SDS OFF-NETWORK MESSAGE message with a disposition of READ }
    then { UE (MCDATA Client) sends a SDS OFF-NETWORK NOTIFICATION message with a disposition notification type of READ upon receiving a display indication for the payload to the MCData User **and,** initiates counter CFS2 (SDS notification retransmission) to 1 and starts timer TFS2 (SDS notification retransmission) }
            }

(4)

with { UE (MCData Client) registered and authorized for MCData Service, including authorized for MCData Service in off-network environment, and, the UE is in an off-network environment }
ensure that {
  when { the UE (MCData Client) receives an SDS OFF-NETWORK MESSAGE message with a disposition of DELIVERY AND READ }
    then { UE (MCDATA Client) sends a SDS OFF-NETWORK NOTIFICATION message with a disposition notification type of DELIVERED AND READ after the message is rendered to the user if the timer TFS3 (delivery and read) has not expired, **or**, if the timer TFS3 (delivery and read) expires before the message is rendered to the MCData User, sends first a SDS OFF-NETWORK NOTIFICATION message with a disposition notification type of DELIVERED and then sends a SDS OFF-NETWORK NOTIFICATION message with a disposition notification type of READ after the payload is rendered to the MCData User, **and,** initiates counter CFS2 (SDS notification retransmission) to 1 and starts timer TFS2 (SDS notification retransmission) after each sending of the SDS OFF-NETWORK NOTIFICATION message }
            }

7.1.4.2 Conformance requirements

References: The conformance requirements covered in the current TC are specified in:

TS 24.282 clauses 9.3.2.4, 9.3.2.5, 9.3.2.6, 12.3.2, 12.3.3, 12.3.4, 12.3.5. Unless otherwise stated these are Rel-15 requirements.

[TS 24.282, clause 9.3.2.4]

Upon receiving an SDS OFF-NETWORK MESSAGE message with a SDS disposition request type IE, the MCData client:

1) shall store the value of Sender MCData user ID IE as the stored notification target MCData user ID;

2) shall store the value of Conversation ID IE as the stored conversation ID;

3) shall store the value of Message ID IE as the stored SDS message ID;

4) shall store the current UTC time as the stored SDS notification time;

5) if present, shall store the value of Application ID IE as the stored SDS application ID;

6) if present, shall store the value of the Extended application ID IE as the stored SDS extended application ID;

7) if present, shall store the value of MCData group ID IE to the stored target MCData group ID; and

8) if the SDS disposition request type IE is set to:

   a) "DELIVERY" then, shall send a SDS OFF-NETWORK NOTIFICATION message as described in clause 12.3.2;

b) "READ" then, shall send a SDS OFF-NETWORK NOTIFICATION message as described in clause 12.3.3; or

c) "DELIVERY AND READ" then, shall start timer TFS3 (delivery and read).

NOTE: Duplicate messages (re-transmissions) that are received by the MCData client should not be processed again.

[TS 24.282, clause 9.3.2.5]

Upon receiving a display indication before timer TFS3 (delivery and read) expires, the MCData client:

1) shall generate and send a SDS OFF-NETWORK NOTIFICATION message as described in clause 12.3.4.

[TS 24.282, clause 9.3.2.6]

Upon expiry of timer TFS3 (delivery and read), the MCData client:

1) shall generate and send a SDS OFF-NETWORK NOTIFICATION message as described in clause 12.3.2; and

2) upon receiving a display indication, shall generate and send a SDS OFF-NETWORK NOTIFICATION message as described in clause 12.3.3.

[TS 24.282, clause 12.3.2]

To send an off-network SDS delivery notification, the MCData client:

1) shall store "DELIVERED" as the disposition type;

2) shall generate a SDS OFF-NETWORK NOTIFICATION message as specified in clause 15.1.8. In the SDS OFF-NETWORK NOTIFICATION message, the MCData client:

a) shall set the Sender MCData user ID IE to its own MCData user ID as specified in clause 15.2.15;

b) shall set the Conversation ID IE as the stored conversation ID as specified in clause 15.2.9;

c) shall set the Message ID IE as the stored SDS message ID as specified in clause 15.2.10;

d) shall set the Date and time IE as the stored SDS notification time as specified in clause 15.2.8;

e) shall set the SDS disposition notification type IE to the stored disposition type as specified in clause 15.2.5; and

f) may set:

i) the Application ID IE to the stored SDS application ID as specified in clause 15.2.7; or

ii) the Extended application ID IE to the stored extended SDS application ID as specified in clause 15.2.24;

3) shall send the SDS OFF-NETWORK NOTIFICATION message to the stored notification target MCData user ID as specified in clause 9.3.1.1;

4) shall initialise the counter CFS2 (SDS notification retransmission) with the value set to 1; and

5) shall start timer TFS2 (SDS notification retransmission).

[TS 24.282, clause 12.3.3]

Upon receiving a display indication for the payload to the user or processing of the payload by the target application, the MCData client:

1) shall store "READ" as the disposition type;

2) shall store the current UTC time as the stored SDS notification time;

3) shall generate SDS OFF-NETWORK NOTIFICATION message as specified in clause 15.1.8. In the SDS OFF-NETWORK NOTIFICATION message, the MCData client:

a) shall set the Sender MCData user ID IE to its own MCData user ID as specified in clause 15.2.15;

b) shall set the Conversation ID IE as the stored conversation ID as specified in clause 15.2.9;

c) shall set the Message ID IE as the stored SDS message ID as specified in clause 15.2.10;

d) shall set the Data and time IE as the SDS notification time as specified in clause 15.2.8;

e) shall set the SDS disposition notification type IE to the stored disposition type as specified in clause 15.2.5; and

f) may set:

i) the Application ID IE set to the stored SDS application ID as specified in clause 15.2.7; or

ii) the Extended application ID IE to the stored extended SDS application ID as specified in clause 15.2.24;

4) shall send the SDS OFF-NETWORK NOTIFICATION message to the stored sender MCData user ID as specified in clause 9.3.1.1;

5) shall initialise the counter CFS2 (SDS notification retransmission) with the value set to 1; and

6) shall start timer TFS2 (SDS notification retransmission).

[TS 24.282, clause 12.3.4]

Upon receiving a display indication for the payload to the user or processing of the payload by the target application, the MCData client:

1) shall store "DELIVERED AND READ" as the disposition type and stop the timer TFS3 (display and read);

2) shall store the current UTC time as the stored SDS notification time;

3) shall generate SDS OFF-NETWORK NOTIFICATION message. In the SDS OFF-NETWORK NOTIFICATION message, the MCData client:

a) shall set the Sender MCData user ID IE to its own MCData user ID as specified in clause 15.2.15;

b) shall set the Conversation ID IE as the stored conversation ID as specified in clause 15.2.9;

c) shall set the Message ID IE as the stored SDS message ID as specified in clause 15.2.10;

d) shall set the Date and time IE as the SDS notification time as specified in clause 15.2.8;

e) shall set the SDS disposition notification type IE to the stored disposition type as specified in clause 15.2.5; and

f) may set:

i) the Application ID IE to the stored SDS application ID as specified in clause 15.2.7; or

ii) the Extended application ID IE to the stored extended SDS application ID as specified in clause 15.2.24;

4) shall send the SDS OFF-NETWORK NOTIFICATION message to the stored sender MCData user ID as specified in clause 9.3.1.1;

5) shall initialise the counter CFS2 (SDS notification retransmission) with the value set to 1; and

6) shall start timer TFS2 (SDS notification retransmission).

[TS 24.282, clause 12.3.5]

Upon expiry of timer TFS2 (SDS notification retransmission), the MCData client:

1) shall generate a SDS OFF-NETWORK NOTIFICATION message as specified in clause 15.1.8. In the SDS OFF-NETWORK NOTIFICATION message, the MCData client:

a) shall set the Sender MCData user ID IE to its own MCData user ID as specified in clause 15.2.15;

b) shall set the Conversation ID IE as the stored conversation ID as specified in clause 15.2.9;

c) shall set the Message ID IE as the stored SDS message ID as specified in clause 15.2.10;

d) shall set the Date and time IE as the stored SDS notification time as specified in clause 15.2.8;

e) shall set the SDS disposition type IE to the stored disposition type as specified in clause 15.2.5; and

f) may set:

i) the Application ID IE to the stored SDS application ID as specified in clause 15.2.7; or

ii) the Extended application ID IE to the stored extended SDS application ID as specified in clause 15.2.24;

2) shall send the SDS OFF-NETWORK NOTIFICATION message to the stored sender MCData user ID as specified in clause 9.3.1.1;

3) shall increment the counter CFS2 (SDS notification retransmission) by 1; and

4) shall start timer TFS2 (SDS notification retransmission) if the associated counter CFS2 (SDS notification retransmission) has not reached its upper limit.

7.1.4.3 Test description

7.1.4.3.1 Pre-test conditions

System Simulator:

- SS-UE1 (MCData Client)
  - For the underlying "transport bearer" over which the SS and the UE will communicate, the SS is behaving as SS-UE1 as defined in TS 36.508 [24], configured for and operating as ProSe Direct Communication transmitting and receiving device.
- GNSS simulator to simulate a location and provide a timing reference for the assistance of E-UTRAN off-network testing.

NOTE 1: For operation in off-network environment, it needs be ensured that after the UE is powered up it considers the Geographical area #1 that is simulated by the GNSS simulator as being one of the geographical areas set in the USIM for operation when UE is "not served by E-UTRAN".

- SS-NW (MCData server)
  - For the underlying "transport bearer" over which the SS and the UE will communicate Parameters are set to the default parameters for the basic E-UTRA Single cell network scenarios, as defined in TS 36.508 [24] clause 4.4. The simulated Cell 1 shall belong to PLMN1 (the PLMN specified for MCData operation in the MCData configuration document).

NOTE 2: The SS operation as NW (MCData server) is needed only for the preamble if the UE has to perform procedure 'MCX Authorization/Configuration and Key Generation' as specified in TS 37.579-1 [2] clause 5.3.2.

IUT:

- UE (MCData Client)
- The test USIM set as defined in TS 37.579-1 [2] clause 5.5.10 is inserted.
- For the underlying "transport bearer" over which the SS and the UE will communicate, the UE is behaving as a ProSe enabled UE as defined in TS 36.508 [24], configured for and operating as ProSe Direct Communication transmitting and receiving device.
- CFS2 (SDS notification retransmission)is set to the default value of 5.
- TFS2 (SDS notification retransmission)is set to the default value of 40 ms.

- TFS3 (delivery and read)is set to the default value of 120 ms.

Preamble:

- The UE has performed procedure 'MCData UE registration' as specified in TS 37.579-1 [2] clause 5.4.2B.
- The UE has performed procedure 'MCX Authorization/Configuration and Key Generation' as specified in TS 37.579-1 [2] clause 5.3.2.
- The GNSS simulator is configured to simulate a location in the centre of Geographical area #1 and provide a timing reference, as defined in TS 36.508 [24] Table 4.11.2-2 scenario #1.
- The UE is switched-off.
- UE States at the end of the preamble
  - The UE is in state 'switched-off'.

7.1.4.3.2 Test procedure sequence

Table 7.1.4.3.2-1: Main behaviour

St	Procedure	Message Sequence		TP	Verdict
		U - S	Message		
1	Power up the UE.	-	-	-	-
2	Trigger the UE to reset UTC time and location. NOTE: The UTC time and location reset may be performed by MMI or AT command (+CUTCR).	-	-	-	-
3	Activate the MCData Client Application and register User A as the MCData User (TS 37.579-5 [5], px_MCX_User_A_username, px_MCX_User_A_password). (NOTE 1)	-	-	-	-
-	EXCEPTION: The E-UTRA/EPC actions which are related to the MCData call establishment are described in TS 37.579-1 [2] clause 5.4.10 'MCX CT communication over ProSe direct one-to-many communication out of E-UTRA coverage / Announcing/Discoveree procedure for group member discovery'. The test sequence below shows only the MCData relevant messages exchanged.	-	-	-	-
4	SS-UE1 (MCData Client) sends a SDS OFF-NETWORK NOTIFICATION message with disposition request type of DELIVERY.	<--	SDS OFF-NETWORK MESSAGE	-	-
-	EXCEPTION: Steps 5-7 are repeated CFS1=5 times (CFS1 defined in 24.282 [31] Table G.3.1-1)	-	-	-	-
5	Check: Does the UE (MCData Client) send a SDS OFF-NETWORK MESSAGE message with disposition notification type of DELIVERED? NOTE: It is expected that the UE - shall initialize the counter CFS2 (SDS notification retransmission) with the value set to 1 on the first transmission, and, increase it by 1 with each re-transmission. - shall start timer TFS2 (SDS notification retransmission)	-->	SDS OFF-NETWORK NOTIFICATION	1,2	P
6	Start TFS2 (SDS notification retransmission)=40 milliseconds as defined in 24.282 [31] Table F.3.1-1.	-	-	-	-
7	TFS2 expires.	-	-	-	-
-	EXCEPTION: UE releases the E-UTRA connection. The E-UTRA/EPC actions which are related to the MCData call release are described in TS 37.579-1 [2] clause 5.4.8, 'MCX communication over ProSe direct one-to-one communication out of E-UTRA coverage - release by the UE'.	-	-	-	-
-	EXCEPTION: The E-UTRA/EPC actions which are related to the MCData call establishment are described in TS 37.579-1 [2] clause 5.4.10 'MCX CT communication over ProSe direct one-to-many communication out of E-UTRA coverage / Announcing/Discoveree procedure for group member discovery'. The test sequence below shows only the MCData relevant messages exchanged.	-	-	-	-
8	SS-UE1 (MCData Client) sends a SDS OFF-NETWORK NOTIFICATION message with disposition request type of READ.	<--	SDS OFF-NETWORK MESSAGE	-	-
-	EXCEPTION: Steps 9-11 are repeated CFS2=5 times (CFS2 defined in 24.282 [31] Table G.3.1-1)	-	-	-	-

9	Check: Does the UE (MCData Client) send a SDS OFF-NETWORK MESSAGE message with disposition notification type of READ upon receiving a display indication for the payload to the MCData User? NOTE: It is expected that the UE - shall initialize the counter CFS2 (SDS notification retransmission) with the value set to 1 on the first transmission, and, increase it by 1 with each re-transmission. - shall start timer TFS2 (SDS notification retransmission)	-->	SDS OFF-NETWORK NOTIFICATION	3,2	P
10	Start TFS2 (SDS notification retransmission)=40 milliseconds as defined in 24.282 [31] Table F.3.1-1.	-	-	-	-
11	TFS2 expires.	-	-	-	-
-	EXCEPTION: UE releases the E-UTRA connection. The E-UTRA/EPC actions which are related to the MCData call release are described in TS 37.579-1 [2] clause 5.4.8, 'MCX communication over ProSe direct one-to-one communication out of E-UTRA coverage - release by the UE'.	-	-	-	-
-	EXCEPTION: The E-UTRA/EPC actions which are related to the MCData call establishment are described in TS 37.579-1 [2] clause 5.4.10 'MCX CT communication over ProSe direct one-to-many communication out of E-UTRA coverage / Announcing/Discoveree procedure for group member discovery'. The test sequence below shows only the MCData relevant messages exchanged.	-	-	-	-
12	SS-UE1 (MCData Client) sends a SDS OFF-NETWORK NOTIFICATION message with disposition request type of DELIVERY AND READ. NOTE: Timer TFS3 (delivery and read).is started upon receipt of the SDS OFF-NETWORK MESSAGE message that contains a "DELIVERY AND READ" disposition request. TFS3 (delivery and read)=120ms according to the default value defined in TS 24.282 [31] Table F.3.1-1.	<--	SDS OFF-NETWORK MESSAGE	-	-
-	EXCEPTION: Steps 13a1-13b2 describe behaviour that depends on the UE implementation. Steps 13a1-13a6 describe the behaviour of the UE when the timer TFS3 (delivery and read) expires before the contents of the Payload IE are rendered to the MCData User. Steps 13b1-13b3 describe the behaviour of the UE when the contents of the Payload IE are rendered to the MCData User before the timer TFS3 (delivery and read) expires.	-	-	-	-
-	EXCEPTION: Steps 13a1-13a3 are repeated CFS1=5 times (CFS1 defined in 24.282 [31] Table G.3.1-1)	-	-	-	-

13a1	Check: Does the UE (MCData Client) send a SDS OFF-NETWORK MESSAGE message with disposition notification type of DELIVERED? NOTE: It is expected that the UE - shall initialize the counter CFS2 (SDS notification retransmission) with the value set to 1 on the first transmission, and, increase it by 1 with each re-transmission. - shall start timer TFS2 (SDS notification retransmission)	-->	SDS OFF-NETWORK NOTIFICATION	4,2	P
13a2	Start TFS2 (SDS notification retransmission)=40 milliseconds as defined in 24.282 [31] Table F.3.1-1.	-	-	-	-
13a3	TFS2 expires.	-	-	-	-
-	EXCEPTION: Steps 13a4-13a6 are repeated CFS2=5 times (CFS2 defined in 24.282 [31] Table G.3.1-1)	-	-	-	-
13a4	Check: Does the UE (MCData Client) send a SDS OFF-NETWORK MESSAGE message with disposition notification type of READ upon receiving a display indication for the payload to the MCData User? NOTE: It is expected that the UE - shall initialize the counter CFS2 (SDS notification retransmission) with the value set to 1 on the first transmission, and, increase it by 1 with each re-transmission. - shall start timer TFS2 (SDS notification retransmission)	-->	SDS OFF-NETWORK NOTIFICATION	4,2	P
13a5	Start TFS2 (SDS notification retransmission)=40 milliseconds as defined in 24.282 [31] Table F.3.1-1.	-	-	-	-
13a6	TFS2 expires.	-	-	-	-
-	EXCEPTION: Steps 13b1-13b3 are repeated CFS1=5 times (CFS1 defined in 24.282 [31] Table G.3.1-1)	-	-	-	-
13b1	Check: Does the UE (MCData Client) send a SDS OFF-NETWORK MESSAGE message with disposition notification type of DELIVERED AND READ? NOTE: It is expected that the UE - shall initialize the counter CFS2 (SDS notification retransmission) with the value set to 1 on the first transmission, and, increase it by 1 with each re-transmission. - shall start timer TFS2 (SDS notification retransmission)	-->	SDS OFF-NETWORK NOTIFICATION	4,2	P
13b2	Start TFS2 (SDS notification retransmission)=40 milliseconds as defined in 24.282 [31] Table F.3.1-1.	-	-	-	-
13b3	TFS2 expires.	-	-	-	-
-	EXCEPTION: UE releases the E-UTRA connection. The E-UTRA/EPC actions which are related to the MCData call release are described in TS 37.579-1 [2] clause 5.4.8, 'MCX communication over ProSe direct one-to-one communication out of E-UTRA coverage - release by the UE'.	-	-	-	-
NOTE 1: This is expected to be done via a suitable implementation dependent MMI.					

7.1.4.3.3 Specific message contents

Table 7.1.4.3.3-1: SDS OFF-NETWORK MESSAGE (step 4, Table 7.1.4.3.2-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.9-1, condition DELIVERED, MCD_grp

Table 7.1.4.3.3-2: SDS OFF-NETWORK NOTIFICATION (steps 5, 13a1, Table 7.1.4.3.2-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.12-1, condition DELIVERED

Table 7.1.4.3.3-3: SDS OFF-NETWORK MESSAGE (step 8, Table 7.1.4.3.2-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.9-1, condition READ, MCD_grp

Table 7.1.4.3.3-4: SDS OFF-NETWORK NOTIFICATION (steps 9, 13a4, Table 7.1.4.3.2-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.12-1, condition READ

Table 7.1.4.3.3-5: SDS OFF-NETWORK MESSAGE (step 8, Table 7.1.4.3.2-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.9-1, condition DELIVERED_READ, MCD_grp

Table 7.1.4.3.3-6: SDS OFF-NETWORK NOTIFICATION (step 13b1, Table 7.1.4.3.2-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.12-1, condition DELIVERED_READ

7.2 Enhanced Status (ES)

7.2.1 Off-network / Enhanced Status (ES) / Client Originated (CO)

7.2.1.1 Test Purpose (TP)

(1)

```
with { UE (MCData Client) registered and authorized for MCData Service, including authorized for
MCData Service in off-network environment, and, the UE is in an off-network environment }
ensure that {
  when { the MCDATA User requests to send an Enhanced Status with a disposition of only Delivery }
    then { UE (MCDATA Client) sends an Enhanced Status with a disposition request of only Delivery
via the SDS OFF-NETWORK MESSAGE message, and, initiates counter CFS1 (SDS retransmission) to 1 and
starts timer TFS1 (SDS retransmission) }
            }
```

(2)

```
with { UE (MCData Client) having sent a SDS OFF-NETWORK MESSAGE message and started timer TFS1 (SDS
retransmission) }
ensure that {
  when { timer TFS1 (SDS retransmission) expires }
    then { UE (MCData Client) retransmits the SDS OFF-NETWORK MESSAGE message and, stops re-
transmitting if the counter CFS1 (SDS retransmission) has reached its maximum value and TFS1 (SDS
retransmission) has expired }
            }
```

7.2.1.2 Conformance requirements

References: The conformance requirements covered in the current TC are specified in:

TS 24.282 clauses 14.3.1, 9.3.2.2, 9.3.2.3. Unless otherwise stated these are Rel-15 requirements.

[TS 24.282, clause 14.3.1]

Upon receiving request from MCData user to share enhanced for selected group:

1) if the value of "/<x>/<x>/Common/MCData/AllowedEnhSvc" leaf node present in the group configuration as specified in 3GPP TS 24.483 [4] is set to "true" for the MCData group, the MCData client:

   a) shall use "/<x>/<x>/Common/MCData/EnhSvcOpValues/<x>/EnhSvcOpID" leaf node associated with user selected enhanced status operation value present in the group configuration as specified in 3GPP TS 24.483 [4] to generate a group standalone SDS message by following the procedure described in clause 9.3.2.2.

[TS 24.282, clause 9.3.2.2]

Upon receiving an indication to send an SDS message, the MCData client:

1) if the request to send the SDS message is for a MCData group, shall check if the value of "/<*x*>/<x>/Common/MCData/AllowedSDS" leaf node, present in the group configuration as specified in 3GPP TS 24.483 [42], is set to "false". It the value is set to "false", shall reject the request to send the SDS message and not continue with the remaining procedures in this clause;

2) if:

   a) a one-to-one SDS message is to be sent then, shall store the MCData user ID of the intended recipient as the target MCData user ID; or

   b) a group SDS message is to be sent then, shall store the MCData group ID as the target MCData group ID;

3) may set the stored SDS disposition request type as:

   a) "DELIVERY", if only delivery disposition is requested;

   b) "READ", if only read disposition is requested; or

   c) "DELIVERY AND READ", if both delivery and read dispositions are requested;

4) if an existing conversation is indicated then, shall store the conversation identifier of the indicated conversation as SDS conversation ID. Otherwise, shall generate an UUID as described in IETF RFC 4122 [14] and store SDS conversation ID;

5) shall generate an UUID as described in IETF RFC 4122 [14] and store as the SDS message ID;

6) if indicated that the SDS message is in reply to another SDS message then, shall store the message identifier of the indicated message as SDS reply ID;

7) if indicated that the target recipient of the SDS message is an application then, shall store the application ID of the indicated application as the SDS application ID or as the SDS extended application ID;

8) shall store the received payload as the SDS payload;

9) shall store the received payload type as the SDS payload type;

10) shall store the current UTC time as the SDS transmission time;

11) shall generate a SDS OFF-NETWORK MESSAGE message as specified in clause 15.1.7. In the SDS OFF-NETWORK MESSAGE message, the MCData client:

   a) shall set the Sender MCData user ID IE to its own MCData user ID;

   b) if:

      i) a one-to-one SDS message is to be sent then shall set the Recipient MCData user ID IE to the stored target MCData user ID as specified in clause 15.2.15; or

ii) a group SDS message is to be sent then, shall set the MCData group ID IE to the stored target MCData group ID as specified in clause 15.2.14;

c) may set the SDS disposition request type IE to the stored the SDS disposition request type as specified in clause 15.2.3;

d) shall set the Conversation ID IE to the stored conversation ID as specified in clause 15.2.9;

e) shall set the Message ID IE to the stored SDS message ID as specified in clause 15.2.10;

f) shall set the Date and time IE to the stored SDS transmission time as specified in clause 15.2.8;

g) may include the InReplyTo message ID IE set to the stored SDS reply ID as specified in clause 15.2.11;

h) may include:

i) the Application ID IE set to the stored SDS application ID as specified in clause 15.2.7; or

ii) the Extended application ID IE set to the stored SDS extended application ID as specified in clause 15.2.24;

i) if end-to-end security is required for a one-to-one communication and the security context does not exist or if the existing security context has expired, shall include the Security parameters and Payload IE with security parameters as described in 3GPP TS 33.180 [26];

j) if

i) end-to-end security is not required for a one-to-one communication, or

ii) sending the SDS OFF-NETWORK MESSAGE message to a MCData group;

may include the Payload IE as specified in clause 15.2.13 with:

i) the Payload content type to the stored SDS payload type; and

ii) the Payload data set to the stored SDS payload;

12) if:

a) a one-to-one SDS message is to be sent then, shall send the SDS OFF-NETWORK MESSAGE message as specified in clause 9.3.1.1; or

b) a group SDS message is to be sent then, shall send the SDS OFF-NETWORK MESSAGE message as specified in clause 9.3.1.2;

13) shall initialise the counter CFS1 (SDS retransmission) with the value set to 1; and

14) shall start timer TFS1 (SDS retransmission).

[TS 24.282, clause 9.3.2.3]

Upon expiry of timer TFS1 (SDS retransmission), the MCData client:

1) shall generate a SDS OFF-NETWORK MESSAGE message as specified in clause 15.1.7. In the SDS OFF-NETWORK MESSAGE message, the MCData client:

a) shall set the Sender MCData user ID IE to its own MCData user ID;

b) if:

i) a one-to-one SDS message is to be sent then, shall set the Recipient MCData user ID IE to the stored target MCData user ID; or

ii) a group SDS message is to be sent then, shall set the MCData group ID IE to the stored target MCData group ID;

c) may set the SDS disposition request type IE to the stored the SDS disposition request type as specified in clause 15.2.3;

d) shall set the Conversation ID IE to the stored conversation ID as specified in clause 15.2.9;

e) shall set the Message ID IE to the stored SDS message ID as specified in clause 15.2.10;

f) shall set the Date and time IE to the stored the SDS transmission time as specified in clause 15.2.8;

g) may include the InReplyTo message ID IE set to the stored SDS reply ID as specified in clause 15.2.11;

h) may include:

i) the Application ID IE set to the stored SDS application ID as specified in clause 15.2.7; or

ii) the Extended application ID IE set to the stored SDS extended application ID as specified in clause 15.2.24;

i) if end-to-end security is required for a one-to-one communication and the security context does not exist or if the existing security context has expired, shall include the Security parameters IE with security parameters as described in 3GPP TS 33.180 [26]; and

j) if:

i) end-to-end security is not required for a one-to-one communication, or

ii) sending the SDS OFF-NETWORK MESSAGE message to a MCData group;

may include the Payload IE as specified in clause 15.2.13 with:

i) the Payload content type to the stored SDS payload type; and

ii) the Payload data set to the stored SDS payload;

2) if:

a) a one-to-one SDS message was sent then, shall send the SDS OFF-NETWORK MESSAGE message as specified in clause 9.3.1.1; or

b) a group SDS message was sent then, shall send the SDS OFF-NETWORK MESSAGE message as specified in clause 9.3.1.2;

3) shall increment the counter CFS1(SDS retransmission) by 1; and

4) shall start timer TFS1 (SDS retransmission) if the associated counter CFS1 (SDS retransmission) has not reached its upper limit.

7.2.1.3 Test description

7.2.1.3.1 Pre-test conditions

System Simulator:

- SS-UE1 (MCData Client)
  - For the underlying "transport bearer" over which the SS and the UE will communicate, the SS is behaving as SS-UE1 as defined in TS 36.508 [24], configured for and operating as ProSe Direct Communication transmitting and receiving device.
- GNSS simulator to simulate a location and provide a timing reference for the assistance of E-UTRAN off-network testing.

NOTE 1: For operation in off-network environment, it needs be ensured that after the UE is powered up it considers the Geographical area #1 that is simulated by the GNSS simulator as being one of the geographical areas set in the USIM for operation when UE is "not served by E-UTRAN".

- SS-NW (MCData server)

- For the underlying "transport bearer" over which the SS and the UE will communicate Parameters are set to the default parameters for the basic E-UTRA Single cell network scenarios, as defined in TS 36.508 [24] clause 4.4. The simulated Cell 1 shall belong to PLMN1 (the PLMN specified for MCData operation in the MCData configuration document).

NOTE 2: The SS operation as NW (MCData server) is needed only for the preamble if the UE has to perform procedure 'MCX Authorization/Configuration and Key Generation' as specified in TS 37.579-1 [2] clause 5.3.2.

IUT:

- UE (MCData Client)
- The test USIM set as defined in TS 37.579-1 [2] clause 5.5.10 is inserted.
- For the underlying "transport bearer" over which the SS and the UE will communicate, the UE is behaving as a ProSe enabled UE as defined in TS 36.508 [24], configured for and operating as ProSe Direct Communication transmitting and receiving device.
- CFS1 (SDS retransmission) is set to the default value of 5.
- TFS1 (SDS retransmission) is set to the default value of 40 ms.

Preamble:

- The UE has performed procedure 'MCData UE registration' as specified in TS 37.579-1 [2] clause 5.4.2B.
- The UE has performed procedure 'MCX Authorization/Configuration and Key Generation' as specified in TS 37.579-1 [2] clause 5.3.2.
- The GNSS simulator is configured to simulate a location in the centre of Geographical area #1 and provide a timing reference, as defined in TS 36.508 [24] Table 4.11.2-2 scenario #1.
- The UE is switched-off.
- UE States at the end of the preamble
  - The UE is in state 'switched-off'.

7.2.1.3.2 Test procedure sequence

Table 7.2.1.3.2-1: Main behaviour

St	Procedure	Message Sequence		TP	Verdict
		U - S	Message		
1	Power up the UE.	-	-	-	-
2	Trigger the UE to reset UTC time and location. NOTE: The UTC time and location reset may be performed by MMI or AT command (+CUTCR).	-	-	-	-
3	Activate the MCData Client Application and register User A as the MCData User (TS 37.579-5 [5], px_MCX_User_A_username, px_MCX_User_A_password). (NOTE 1)	-	-	-	-
4	Make the MCDATA User request to send an enhanced status to Group A using Enhanced Status Id "1" with a disposition request type of "DELIVERY". (NOTE 1)	-	-	-	-
-	EXCEPTION: The E-UTRA/EPC actions which are related to the MCData call establishment are described in TS 37.579-1 [2] clause 5.4.11 'MCX CO communication over ProSe direct one-to-many communication out of E-UTRA coverage / Monitoring/Discoverer procedure for group member discovery / One-to-many communication'. The test sequence below shows only the MCData relevant messages exchanged.	-	-	-	-
-	EXCEPTION: Steps 5-7 are repeated CFS1=5 times (CFS1 defined in 24.282 [31] Table G.3.1-1)	-	-	-	-
5	Check: Does the UE (MCData Client) send an enhanced status via the SDS OFF-NETWORK MESSAGE message with a disposition request type of DELIVERY? NOTE: It is expected that the UE - shall initialize the counter CFS1 (SDS retransmission) with the value set to 1 on the first transmission, and, increase it by 1 with each re-transmission. - shall start timer TFS1 (SDS retransmission)	-->	SDS OFF-NETWORK MESSAGE	1,2	P
6	Start TFS1 (SDS retransmission) 40 milliseconds as defined in 24.282 [31] Table F.3.1-1.	-	-	-	-
7	TFS1 expires.	-	-	-	-
-	EXCEPTION: UE releases the E-UTRA connection. The E-UTRA/EPC actions which are related to the MCData call release are described in TS 37.579-1 [2] clause 5.4.8, 'MCX communication over ProSe direct one-to-one communication out of E-UTRA coverage - release by the UE'.	-	-	-	-
-	EXCEPTION: The E-UTRA/EPC actions which are related to the MCData call establishment are described in TS 37.579-1 [2] clause 5.4.10 'MCX CT communication over ProSe direct one-to-many communication out of E-UTRA coverage / Announcing/Discoveree procedure for group member discovery'. The test sequence below shows only the MCData relevant messages exchanged.	-	-	-	-
-	EXCEPTION: Steps 8-10 are repeated 5 times.	-	-	-	-

8	SS-UE1 (MCData Client) sends a SDS OFF-NETWORK NOTIFICATION message with disposition notification type of DELIVERED.	<--	SDS OFF-NETWORK NOTIFICATION	-	-
9	Start 40 millisecond timer.	-	-	-	-
10	40 millisecond timer expires	-	-	-	-
-	EXCEPTION: SS releases the E-UTRA connection. The E-UTRA/EPC actions which are related to the MCData call release are described in TS 37.579-1 [2] clause 5.4.7, 'MCX communication over ProSe direct one-to-one communication out of E-UTRA coverage - release by the SS'.	-	-	-	-
NOTE 1: This is expected to be done via a suitable implementation dependent MMI.					

7.2.1.3.3 Specific message contents

Table 7.2.1.3.3-1: SDS OFF-NETWORK MESSAGE (step 5, Table 7.2.1.3.2-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.9-1, condition DELIVERED, MCD_grp				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Payload	Payload as described in Table 7.2.1.3.3-2			

Table 7.2.1.3.3-2: Payload in the SDS OFF-NETWORK MESSAGE (Table 7.2.1.3.3-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.9-3				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Data payload message identity	'00000011'B	Data payload	TS 24.282 [31] clause 15.2.2	
Number of payloads	1	1 payload	TS 24.282 [31] clause 15.2.12	
Payload			TS 24.282 [31] clause 15.2.13	
Payload IEI	'78'O			
Length of Payload	length of the content			
Payload content type	'00000110'B	ENHANCED STATUS		
Payload data	"1"	The id as defined in the MCData Group Configuration Document	TS 37.579-1 [2], Table 5.5.7.3-1	

Table 7.2.1.3.3-3: SDS OFF-NETWORK NOTIFICATION (step 8, Table 7.2.1.3.2-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.12-1, condition DELIVERED

7.2.2 Off-network / Enhanced Status (ES) / Client Terminated (CT)

7.2.2.1 Test Purpose (TP)

(1)

```
with { UE (MCData Client) registered and authorized for MCData Service, including authorized for
MCData Service in off-network environment, and, the UE is in an off-network environment }
ensure that {
  when { the UE (MCData Client) receives an enhanced status via the SDS OFF-NETWORK MESSAGE message
with a disposition of DELIVERY }
    then { UE (MCDATA Client) sends SDS OFF-NETWORK NOTIFICATION message with a disposition
notification type of DELIVERED and, initiates counter CFS2 (SDS notification retransmission) to 1
```

```
and starts timer TFS2 (SDS notification retransmission), and, renders the operational value of the
received Enhanced Status ID as enhanced status to the MCDATA User }
            }
```

(2)

```
with { UE (MCData Client) having sent a SDS OFF-NETWORK NOTIFICATION message and started timer TFS2
(SDS notification retransmission) }
ensure that {
  when { TFS2 (SDS notification retransmission) expires }
    then { UE (MCData Client) retransmits the SDS OFF-NETWORK NOTIFICATION message and, stops re-
transmitting if the counter CFS2 (SDS notification retransmission) has reached its maximum value and
TFS2 (SDS notification retransmission) }
            }
```

7.2.2.2 Conformance requirements

References: The conformance requirements covered in the current TC are specified in:

TS 24.282 clauses 14.3.2, 9.3.2.4, 12.3.2, 12.3.5. Unless otherwise stated these are Rel-15 requirements.

[TS 24.282, clause 14.3.2]

Upon receipt of a SDS OFF-NETWORK MESSAGE message, the MCData client:

1) shall follow the procedure defined in clause 9.3.2.4;

2) shall attempt to match the received value with a "/<x>/<x>/Common/MCData/EnhSvcOpValues/<x>/EnhSvcOpID" leaf node present in the group configuration as specified in 3GPP TS 24.483 [4]; and

3) if a match is found, shall render the associated operational value from "/<x>/<x>/Common/MCData/EnhSvcOpValues/<x>/EnhSvcOpValue" leaf node as enhanced status to the MCData user.

[TS 24.282, clause 9.3.2.4]

Upon receiving an SDS OFF-NETWORK MESSAGE message with a SDS disposition request type IE, the MCData client:

1) shall store the value of Sender MCData user ID IE as the stored notification target MCData user ID;

2) shall store the value of Conversation ID IE as the stored conversation ID;

3) shall store the value of Message ID IE as the stored SDS message ID;

4) shall store the current UTC time as the stored SDS notification time;

5) if present, shall store the value of Application ID IE as the stored SDS application ID;

6) if present, shall store the value of the Extended application ID IE as the stored SDS extended application ID;

7) if present, shall store the value of MCData group ID IE to the stored target MCData group ID; and

8) if the SDS disposition request type IE is set to:

   a) "DELIVERY" then, shall send a SDS OFF-NETWORK NOTIFICATION message as described in clause 12.3.2;

   b) "READ" then, shall send a SDS OFF-NETWORK NOTIFICATION message as described in clause 12.3.3; or

   c) "DELIVERY AND READ" then, shall start timer TFS3 (delivery and read).

NOTE: Duplicate messages (re-transmissions) that are received by the MCData client should not be processed again.

[TS 24.282, clause 12.3.2]

To send an off-network SDS delivery notification, the MCData client:

1) shall store "DELIVERED" as the disposition type;

2) shall generate a SDS OFF-NETWORK NOTIFICATION message as specified in clause 15.1.8. In the SDS OFF-NETWORK NOTIFICATION message, the MCData client:

   a) shall set the Sender MCData user ID IE to its own MCData user ID as specified in clause 15.2.15;

   b) shall set the Conversation ID IE as the stored conversation ID as specified in clause 15.2.9;

   c) shall set the Message ID IE as the stored SDS message ID as specified in clause 15.2.10;

   d) shall set the Date and time IE as the stored SDS notification time as specified in clause 15.2.8;

   e) shall set the SDS disposition notification type IE to the stored disposition type as specified in clause 15.2.5; and

   f) may set:

      i) the Application ID IE to the stored SDS application ID as specified in clause 15.2.7; or

      ii) the Extended application ID IE to the stored extended SDS application ID as specified in clause 15.2.24;

3) shall send the SDS OFF-NETWORK NOTIFICATION message to the stored notification target MCData user ID as specified in clause 9.3.1.1;

4) shall initialise the counter CFS2 (SDS notification retransmission) with the value set to 1; and

5) shall start timer TFS2 (SDS notification retransmission).

[TS 24.282, clause 12.3.5]

Upon expiry of timer TFS2 (SDS notification retransmission), the MCData client:

1) shall generate a SDS OFF-NETWORK NOTIFICATION message as specified in clause 15.1.8. In the SDS OFF-NETWORK NOTIFICATION message, the MCData client:

   a) shall set the Sender MCData user ID IE to its own MCData user ID as specified in clause 15.2.15;

   b) shall set the Conversation ID IE as the stored conversation ID as specified in clause 15.2.9;

   c) shall set the Message ID IE as the stored SDS message ID as specified in clause 15.2.10;

   d) shall set the Date and time IE as the stored SDS notification time as specified in clause 15.2.8;

   e) shall set the SDS disposition type IE to the stored disposition type as specified in clause 15.2.5; and

   f) may set:

      i) the Application ID IE to the stored SDS application ID as specified in clause 15.2.7; or

      ii) the Extended application ID IE to the stored extended SDS application ID as specified in clause 15.2.24;

2) shall send the SDS OFF-NETWORK NOTIFICATION message to the stored sender MCData user ID as specified in clause 9.3.1.1;

3) shall increment the counter CFS2 (SDS notification retransmission) by 1; and

4) shall start timer TFS2 (SDS notification retransmission) if the associated counter CFS2 (SDS notification retransmission) has not reached its upper limit.

7.2.2.3 Test description

7.2.2.3.1 Pre-test conditions

System Simulator:

- SS-UE1 (MCData Client)
  - For the underlying "transport bearer" over which the SS and the UE will communicate, the SS is behaving as SS-UE1 as defined in TS 36.508 [24], configured for and operating as ProSe Direct Communication transmitting and receiving device.
- GNSS simulator to simulate a location and provide a timing reference for the assistance of E-UTRAN off-network testing.

NOTE 1: For operation in off-network environment, it needs be ensured that after the UE is powered up it considers the Geographical area #1 that is simulated by the GNSS simulator as being one of the geographical areas set in the USIM for operation when UE is "not served by E-UTRAN".

- SS-NW (MCData server)
  - For the underlying "transport bearer" over which the SS and the UE will communicate Parameters are set to the default parameters for the basic E-UTRA Single cell network scenarios, as defined in TS 36.508 [24] clause 4.4. The simulated Cell 1 shall belong to PLMN1 (the PLMN specified for MCData operation in the MCData configuration document).

NOTE 2: The SS operation as NW (MCData server) is needed only for the preamble if the UE has to perform procedure 'MCX Authorization/Configuration and Key Generation' as specified in TS 37.579-1 [2] clause 5.3.2.

IUT:

- UE (MCData Client)
- The test USIM set as defined in TS 37.579-1 [2] clause 5.5.10 is inserted.
- For the underlying "transport bearer" over which the SS and the UE will communicate, the UE is behaving as a ProSe enabled UE as defined in TS 36.508 [24], configured for and operating as ProSe Direct Communication transmitting and receiving device.
- CFS2 (SDS notification retransmission)is set to the default value of 5.
- TFS2 (SDS notification retransmission)is set to the default value of 40 ms.

Preamble:

- The UE has performed procedure 'MCData UE registration' as specified in TS 37.579-1 [2] clause 5.4.2B.
- The UE has performed procedure 'MCX Authorization/Configuration and Key Generation' as specified in TS 37.579-1 [2] clause 5.3.2.
- The GNSS simulator is configured to simulate a location in the centre of Geographical area #1 and provide a timing reference, as defined in TS 36.508 [24] Table 4.11.2-2 scenario #1.
- The UE is switched-off.
- UE States at the end of the preamble
  - The UE is in state 'switched-off'.

7.2.2.3.2 Test procedure sequence

Table 7.2.2.3.2-1: Main behaviour

St	Procedure	Message Sequence		TP	Verdict
		U - S	Message		
1	Power up the UE.	-	-	-	-
2	Trigger the UE to reset UTC time and location. NOTE: The UTC time and location reset may be performed by MMI or AT command (+CUTCR).	-	-	-	-
3	Activate the MCData Client Application and register User A as the MCData User (TS 37.579-5 [5], px_MCX_User_A_username, px_MCX_User_A_password). (NOTE 1)	-	-	-	-
-	EXCEPTION: The E-UTRA/EPC actions which are related to the MCData call establishment are described in TS 37.579-1 [2] clause 5.4.10 'MCX CT communication over ProSe direct one-to-many communication out of E-UTRA coverage / Announcing/Discoveree procedure for group member discovery'. The test sequence below shows only the MCData relevant messages exchanged.	-	-	-	-
-	EXCEPTION: Steps 4-6 are repeated 5 times.	-	-	-	-
4	SS-UE1 (MCData Client) sends an enhanced status via the SDS OFF-NETWORK NOTIFICATION message with disposition request type of DELIVERY.	<--	SDS OFF-NETWORK MESSAGE	-	-
5	Start 40 millisecond timer.	-	-	-	-
6	40 millisecond timer expires	-	-	-	-
-	EXCEPTION: Steps 7-9 are repeated CFS1=5 times (CFS1 defined in 24.282 [31] Table G.3.1-1)	-	-	-	-
7	Check: Does the UE (MCData Client) send a SDS OFF-NETWORK MESSAGE message with disposition notification type of DELIVERED? NOTE: It is expected that the UE - shall initialize the counter CFS2 (SDS notification retransmission) with the value set to 1 on the first transmission, and, increase it by 1 with each re-transmission. - shall start timer TFS2 (SDS notification retransmission)	-->	SDS OFF-NETWORK NOTIFICATION	1,2	P
8	Start TFS2 (SDS notification retransmission)=40 milliseconds as defined in 24.282 [31] Table F.3.1-1.	-	-	-	-
9	TFS2 expires.	-	-	-	-
-	EXCEPTION: UE releases the E-UTRA connection. The E-UTRA/EPC actions which are related to the MCData call release are described in TS 37.579-1 [2] clause 5.4.8, 'MCX communication over ProSe direct one-to-one communication out of E-UTRA coverage - release by the UE'.	-	-	-	-
10	Check: Does the UE (MCDATA Client) render the operational value of the received Enhanced Status ID as enhanced status to the MCDATA User? (NOTE 1)	-	-	1	P
NOTE 1: This is expected to be done via a suitable implementation dependent MMI.					

7.2.2.3.3 Specific message contents

Table 7.2.2.3.3-1: SDS OFF-NETWORK MESSAGE (step 4, Table 7.2.2.3.2-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.10-1, condition DELIVERED, MCD_grp				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Payload	Payload as described in Table 7.2.2.3.3-2			

Table 7.2.2.3.3-2: Payload in the SDS OFF-NETWORK MESSAGE (step 4, Table 7.2.2.3.2-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.10-3, condition DELIVERED, MCD_grp				
Information Element	**Value/remark**	**Comment**	**Reference**	**Condition**
Data payload message identity	'00000011'B	Data payload	TS 24.282 [31] clause 15.2.2	
Number of payloads	1	1 payload	TS 24.282 [31] clause 15.2.12	
Payload			TS 24.282 [31] clause 15.2.13	
Payload IEI	'78'O			
Length of Payload	length of the content			
Payload content type	'00000110'B	ENHANCED STATUS		
Payload data	"0"	The id as defined in the MCData Group Configuration Document	TS 37.579-1 [2], Table 5.5.7.3-1	

Table 7.2.2.3.3-3: SDS OFF-NETWORK NOTIFICATION (step 7, Table 7.2.2.3.2-1)

Derivation Path: TS 37.579-1 [2], Table 5.5.3.8.11-1, condition DELIVERED

7.3 Emergency Alert

7.3.1 Off-network / Group Call / Emergency Alert / Emergency Alert Retransmission / Cancel Emergency Alert / Client Originated (CO)

7.3.1.1 Test Purpose (TP)

(1)

```
with { UE (MCData Client) registered and authorised for MCData Service, including authorised to
initiate emergency alerts in off-network environment, and the UE (MCData Client) is in an off-
network environment }
ensure that {
  when { the MCData User requests to initiate an MCData emergency alert }
    then { UE (MCData Client) sends a GROUP EMERGENCY ALERT message and enters the "E2: Emergency
state" state }
           }
```

(2)

```
with { UE (MCData Client) in the "E2: Emergency state" state, and the UE (MCData Client) is in an
off-network environment }
ensure that {
  when { the timer TFE2 (emergency alert retransmission) expires }
    then { UE (MCData Client) retransmits the MCData emergency alert by sending a GROUP EMERGENCY
ALERT message}
```

```
            }
```

(3)

```
with { UE (MCData Client) in the "E2: Emergency state" state, and the UE (MCData Client) is in an
off-network environment }
ensure that {
  when { the MCData User requests to cancel the MCData emergency alert }
    then { UE (MCData Client) sends a GROUP EMERGENCY ALERT CANCEL message and enters the "E1: Not
in emergency state" state }
            }
```

7.3.1.2 Conformance requirements

References: The conformance requirements covered in the current TC are specified in: TS 24.282 clauses 16.3.3.1, 16.3.3.2, 16.3.3.5. Unless otherwise stated these are Rel-16 requirements.

[TS 24.282, clause 16.3.3.1]

When in state "E1: Not in emergency state", upon receiving an indication from the MCData user to transmit an emergency alert for an MCData group ID and the value of "/<*x*>/<*x*>/Common/AllowedActivateAlert" leaf node present in the user profile as specified in 3GPP TS 24.483 [42] is set to "true", the MCData client:

1) shall set the stored emergency state as "true";
2) shall set the stored MCData group ID to the indicated MCData group ID;
3) shall generate a GROUP EMERGENCY ALERT message as specified in subclause 15.1.14. In the GROUP EMERGENCY ALERT message, the MCData client:
   a) shall set the MCData group ID IE to the stored MCData group ID;
   b) shall set the Originating MCData user ID IE to own MCData user ID;
   c) may set the Organization name IE to own organization name; and
   d) may set the User location IE with client's current location, if requested;
4) shall send the GROUP EMERGENCY ALERT message as specified in subclause 9.3.1.2;
5) shall start timer TFE2 (emergency alert retransmission); and
6) shall enter "E2: Emergency state" state.

[TS 24.282, clause 16.3.3.2]

When in state "E2: Emergency state", upon expiry of timer TFE2 (emergency alert retransmission), the MCData client:

1) shall generate a GROUP EMERGENCY ALERT message as specified in subclause 15.1.14. In the GROUP EMERGENCY ALERT message, the MCData client:
   a) shall set the MCData group ID IE to the stored MCData group ID;
   b) shall set the originating MCData user ID IE to own MCData user ID;
   c) may set the Organization name IE to own organization name; and
   d) may set the Location IE with client's current location, if requested;
2) shall send the GROUP EMERGENCY ALERT message as specified in subclause 9.3.1.2;
3) shall start the timer TFE2 (emergency alert retransmission); and
4) shall remain in the current state.

[TS 24.282, clause 16.3.3.5]

When in "E2: Emergency state", upon receiving an indication from the MCData user to cancel an emergency alert and the value of "/<*x*>/<*x*>/Common/AllowedCancelAlert" leaf node present in the user profile as specified in 3GPP TS 24.483 [42] is set to "true", the MCData client:

1) shall set the stored emergency state as "false";

2) shall generate a GROUP EMERGENCY ALERT CANCEL message as specified in subclause 15.1.16. In the GROUP EMERGENCY ALERT CANCEL message, the MCData client:

   a) shall set the MCData group ID IE to the stored MCData group ID; and

   b) shall set the Originating MCData user ID IE to own MCData user ID;

3) shall send the GROUP EMERGENCY ALERT CANCEL message as specified in subclause 9.3.1.2;

4) shall stop timer TFE2 (emergency alert retransmission); and

5) shall enter "E1: Not in emergency state" state.

7.3.1.3 Test description

7.3.1.3.1 Pre-test conditions

System Simulator:

- SS-UE1 (MCData Client)

  - For the underlying "transport bearer" over which the SS and the UE will communicate, the SS is behaving as SS-UE1 as defined in TS 36.508 [24], configured for and operating as ProSe Direct Communication transmitting and receiving device.

- GNSS simulator to simulate a location and provide a timing reference for the assistance of E-UTRAN off-network testing.

NOTE 1: For operation in off-network environment, it needs be ensured that after the UE is powered up it considers the Geographical area #1 that is simulated by the GNSS simulator as being one of the geographical areas set in the USIM for operation when UE is "not served by E-UTRAN".

- SS-NW (MCData server)

  - For the underlying "transport bearer" over which the SS and the UE will communicate Parameters are set to the default parameters for the basic E-UTRA Single cell network scenarios, as defined in TS 36.508 [24] clause 4.4. The simulated Cell 1 shall belong to PLMN1 (the PLMN specified for MCData operation in the MCData configuration document).

NOTE 2: The SS operation as NW (MCData server) is needed only for the preamble if the UE has to perform procedure 'MCX Authorization/Configuration and Key Generation' as specified in TS 37.579-1 [2] clause 5.3.2.

IUT:

- UE (MCData Client)

- The test USIM set as defined in TS 37.579-1 [2] clause 5.5.10 is inserted.

- For the underlying "transport bearer" over which the SS and the UE will communicate, the UE is behaving as a ProSe enabled UE as defined in TS 36.508 [24], configured for and operating as ProSe Direct Communication transmitting and receiving device.

- CFS1 (SDS retransmission) is set to the default value of 5.

- TFS1 (SDS retransmission) is set to the default value of 40 ms.

Preamble:

- The UE has performed procedure 'MCData UE registration' as specified in TS 37.579-1 [2] clause 5.4.2B.
- The UE has performed procedure 'MCX Authorization/Configuration and Key Generation' as specified in TS 37.579-1 [2] clause 5.3.2.
- The GNSS simulator is configured to simulate a location in the centre of Geographical area #1 and provide a timing reference, as defined in TS 36.508 [24] Table 4.11.2-2 scenario #1.
- The UE is switched-off.
- UE States at the end of the preamble
  - The UE is in state 'switched-off'.

7.3.1.3.2 Test procedure sequence

Table 7.3.1.3.2-1: Main Behaviour

St	Procedure	Message Sequence		TP	Verdict
		U - S	Message		
1	Power up the UE.	-	-	-	-
2	Trigger the UE to reset UTC time and location. NOTE: The UTC time and location reset may be performed by MMI or AT command (+CUTCR).	-	-	-	-
3	Activate the MCData Client Application and register User A as the MCData User (TS 37.579-5 [5], px_MCX_User_A_username, px_MCX_User_A_password). (NOTE 1)	-	-	-	-
4	Make the UE (MCData Client) initiate an off-network emergency alert. (NOTE 1)	-	-	-	-
-	EXCEPTION: The E-UTRA/EPC actions which are related to the MCData call establishment are described in TS 37.579-1 [2] clause 5.4.5 'MCX CO communication over ProSe direct one-to-one communication out of E-UTRA coverage-establishment'. The test sequence below shows only the MCData relevant messages exchanged.	-	-	-	-
5	Check: Does the UE (MCData Client) send a GROUP EMERGENCY ALERT message? (NOTE 2)	-->	GROUP EMERGENCY ALERT	1	P
6	SS starts Timer=10s (TFE2 (emergency alert retransmission))	-	-	-	-
7	The SS-UE1 (MCData client) responds to the GROUP EMERGENCY ALERT by sending a GROUP EMERGENCY ALERT ACK	<--	GROUP EMERGENCY ALERT ACK	-	-
8	Timer=10s expires	-	-	-	-
9	Check: Does the UE (MCData Client) send a GROUP EMERGENCY ALERT message? (NOTE 2)	-->	GROUP EMERGENCY ALERT	2	P
10	Make the UE (MCData Client) cancel the emergency alert (NOTE 1), (NOTE 3)	-	-	-	-
11	Check: Does the UE (MCData Client) send a GROUP EMERGENCY ALERT CANCEL message? (NOTE 4)	-->	GROUP EMERGENCY ALERT CANCEL	3	P
12	The SS-UE1 (MCData client) responds to the GROUP EMERGENCY ALERT CANCEL by sending a GROUP EMERGENCY ALERT CANCEL ACK	<--	GROUP EMERGENCY ALERT CANCEL ACK	-	-

NOTE 1: This is expected to be done via a suitable implementation dependent MMI.
NOTE 2: Timer TFE2 (emergency alert retransmission) is started upon the sending of the GROUP EMERGENCY ALERT message. Timer TFE2 (emergency alert retransmission)=10s, as defined in TS 37.579-1 [2], Table 5.5.8.1-1. At the expire of TFE2, the MCData Client retransmits the GROUP EMERGENCY ALERT message.
NOTE 3: If the MCData User does not perform an action before the expiry of timer TFE2 (emergency alert retransmission), then the MCData Client will retransmit the GROUP EMERGENCY ALERT message and the remaining steps will not be valid. Timer TFE2 (emergency alert retransmission) is started upon the sending of the GROUP EMERGENCY ALERT message. Timer TFE2 (emergency alert retransmission)=10s, as defined in TS 37.579-1 [2], Table 5.5.8.1-1. At the expire of TFE2, the MCData Client retransmits the GROUP EMERGENCY ALERT message. If during test execution it is found that the specified timer value is not large enough, then a new value needs to be specified.
NOTE 4: The MCData Client stops the TFE2 (emergency alert retransmission) timer upon the sending of the GROUP EMERGENCY ALERT CANCEL message.

7.3.1.3.3 Specific message contents

None

7.3.2 Off-network / Group Call / Emergency Alert / Emergency Alert Retransmission / Cancel Emergency Alert / Client Terminated (CT)

7.3.2.1 Test Purpose (TP)

(1)

```
with { UE (MCData Client) registered and authorised for MCData Service, including authorised to
receive emergency alerts in off-network environment, and the UE (MCData Client) is in an off-network
environment }
ensure that {
  when { UE (MCData Client) receives an MCData emergency alert via a GROUP EMERGENCY ALERT message }
    then { UE (MCData Client) responds by sending a GROUP EMERGENCY ALERT ACK }
            }
```

(2)

```
with { UE (MCData Client) registered and authorised for MCData Service, having received an MCData
emergency alert, and the UE (MCData Client) is in an off-network environment }
ensure that {
  when { UE (MCData Client) receives a GROUP EMERGENCY ALERT message from the same MCData Client
that sent the previous GROUP EMERGENCY ALERT message, and the timer TFE1 (Emergency Alert) has yet
to expire }
    then { UE (MCData Client) shall not send a GROUP EMERGENCY ALERT ACK in response }
            }
```

(3)

```
with { UE (MCData Client) registered and authorised for MCData Service, having received an MCData
emergency alert, and the UE (MCData Client) is in an off-network environment }
ensure that {
  when { UE (MCData Client) receives a GROUP EMERGENCY ALERT message from the same MCData Client
that sent the previous GROUP EMERGENCY ALERT message, and the timer TFE1 (Emergency Alert) expired }
    then { UE (MCData Client) responds by sending a GROUP EMERGENCY ALERT ACK }
            }
```

(4)

```
with { UE (MCData Client) registered and authorised for MCData Service, having received an MCData
emergency alert, and the UE (MCData Client) is in an off-network environment }
ensure that {
  when { UE (MCData Client) receives a GROUP EMERGENCY ALERT CANCEL message from the same MCData
Client that sent the previous GROUP EMERGENCY ALERT message }
    then { UE (MCData Client) responds by sending a GROUP EMERGENCY ALERT CANCEL ACK }
            }
```

7.3.2.2 Conformance requirements

References: The conformance requirements covered in the current TC are specified in: TS 24.282 clauses 16.3.3.3, 16.3.3.4, 16.3.3.6, 16.3.3.7. Unless otherwise stated these are Rel-16 requirements.

[TS 24.282, clause 16.3.3.3]

When in state "E1: Not in emergency state" or in "E2: Emergency state", upon receiving a GROUP EMERGENCY ALERT message with the Originating MCData user ID IE not stored in the list of users in emergency, the MCData client:

1) shall store the Originating MCData user ID IE and location IE in the list of users in emergency;

2) shall generate a GROUP EMERGENCY ALERT ACK message as specified in subclause 15.1.15. In the GROUP EMERGENCY ALERT ACK message, the MCData client:

a) shall set the MCData group ID IE to the MCData group ID IE of the received GROUP EMERGENCY ALERT message;

b) shall set the Sending MCData user ID IE to own MCData user ID;

c) shall set the Originating MCData user ID IE to the Originating MCData user ID IE of the received GROUP EMERGENCY ALERT message; and

3) shall send the GROUP EMERGENCY ALERT ACK message as specified in subclause 9.3.1.2;

4) shall start timer TFE1 (Emergency Alert); and

5) shall remain in the current state.

NOTE: Each instance of timer TFE1 is per MCData user ID.

Editor's Note: [CR 0095, WI eMCData2] Use of timer TFE1 in case of several emergency alerts from multiple users is FFS.

[TS 24.282, clause 16.3.3.4]

When in state "E1: Not in emergency state" or in "E2: Emergency state", upon receiving a GROUP EMERGENCY ALERT message with the Originating MCData user ID IE stored in the list of users in emergency and Location IE different than the stored location of the user, the MCData client:

1) may update the stored location of the user with the received Location IE;

2) shall restart the associated timer TFE1 (Emergency Alert); and

3) shall remain in the current state.

[TS 24.282, clause 16.3.3.6]

When in state "E1: Not in emergency state" or in "E2: Emergency state", upon receiving a GROUP EMERGENCY ALERT CANCEL message with the Originating MCData user ID IE stored in the list of users in emergency, the MCData client:

1) shall remove the MCData user ID and associated location information from the stored list of users in emergency;

2) shall generate a GROUP EMERGENCY ALERT CANCEL ACK message as specified in subclause 15.1.17. In the GROUP EMERGENCY ALERT CANCEL ACK message, the MCData client:

a) shall set the MCData group ID IE to the MCData group ID IE of the received GROUP EMERGENCY ALERT CANCEL message;

b) shall set the Sending MCData user ID IE to own MCData user ID; and

c) shall set the Originating MCData user ID IE to the Originating MCData user ID IE of the received GROUP EMERGENCY ALERT message;

3) shall send the GROUP EMERGENCY ALERT CANCEL ACK message as specified in subclause 9.3.1.2;

4) shall stop the associated timer TFE1 (Emergency Alert); and

5) shall remain in the current state.

[TS 24.282, clause 16.3.3.7]

When in state "E1: Not in emergency state" or in "E2: Emergency state", upon expiry of timer TFE1 (Emergency Alert) associated with a stored MCData user ID, the MCData client:

1) shall remove the MCData user ID and associated location information from the stored list of users in emergency; and

2) shall remain in the current state.

7.3.2.3 Test description

7.3.2.3.1 Pre-test conditions

System Simulator:

- SS-UE1 (MCData Client)
  - For the underlying "transport bearer" over which the SS and the UE will communicate, the SS is behaving as SS-UE1 as defined in TS 36.508 [24], configured for and operating as ProSe Direct Communication transmitting and receiving device.
- GNSS simulator to simulate a location and provide a timing reference for the assistance of E-UTRAN off-network testing.

NOTE 1: For operation in off-network environment, it needs be ensured that after the UE is powered up it considers the Geographical area #1 that is simulated by the GNSS simulator as being one of the geographical areas set in the USIM for operation when UE is "not served by E-UTRAN".

- SS-NW (MCData server)
  - For the underlying "transport bearer" over which the SS and the UE will communicate Parameters are set to the default parameters for the basic E-UTRA Single cell network scenarios, as defined in TS 36.508 [24] clause 4.4. The simulated Cell 1 shall belong to PLMN1 (the PLMN specified for MCData operation in the MCData configuration document).

NOTE 2: The SS operation as NW (MCData server) is needed only for the preamble if the UE has to perform procedure 'MCX Authorization/Configuration and Key Generation' as specified in TS 37.579-1 [2] clause 5.3.2.

IUT:

- UE (MCData Client)
- The test USIM set as defined in TS 37.579-1 [2] clause 5.5.10 is inserted.
- For the underlying "transport bearer" over which the SS and the UE will communicate, the UE is behaving as a ProSe enabled UE as defined in TS 36.508 [24], configured for and operating as ProSe Direct Communication transmitting and receiving device.
- CFS1 (SDS retransmission) is set to the default value of 5.
- TFS1 (SDS retransmission) is set to the default value of 40 ms.

Preamble:

- The UE has performed procedure 'MCData UE registration' as specified in TS 37.579-1 [2] clause 5.4.2B.
- The UE has performed procedure 'MCX Authorization/Configuration and Key Generation' as specified in TS 37.579-1 [2] clause 5.3.2.
- The GNSS simulator is configured to simulate a location in the centre of Geographical area #1 and provide a timing reference, as defined in TS 36.508 [24] Table 4.11.2-2 scenario #1.
- The UE is switched-off.
- UE States at the end of the preamble
  - The UE is in state 'switched-off'.

7.3.2.3.2 Test procedure sequence

Table 7.3.2.3.2-1: Main Behaviour

St	Procedure	Message Sequence		TP	Verdict
		U - S	Message		
1	Power up the UE.	-	-	-	-
2	Trigger the UE to reset UTC time and location. NOTE: The UTC time and location reset may be performed by MMI or AT command (+CUTCR).	-	-	-	-
3	Activate the MCData Client Application and register User A as the MCData User (TS 37.579-5 [5], px_MCX_User_A_username, px_MCX_User_A_password). (NOTE 1)	-	-	-	-
-	EXCEPTION: The E-UTRA/EPC actions which are related to the MCData call establishment are described in TS 37.579-1 [2] clause 5.4.10 'MCX CT communication over ProSe direct one-to-many communication out of E-UTRA coverage / Announcing/Discoveree procedure for group member discovery / One-to-many communication'. The test sequence below shows only the MCData relevant messages exchanged.	-	-	-	-
4	SS-UE1 (MCData client) sends a GROUP EMERGENCY ALERT (NOTE 2), (NOTE 3), (NOTE 4)	<--	GROUP EMERGENCY ALERT	-	-
5	SS starts Timer=10s (TFE2 (emergency alert retransmission))	-	-	-	-
6	SS starts Timer=15s (TFE1 (Emergency Alert))	-	-	-	-
7	Check: Does the UE (MCData Client) respond to the GROUP EMERGENCY ALERT by sending a GROUP EMERGENCY ALERT ACK?	-->	GROUP EMERGENCY ALERT ACK	1	P
8	Timer=10s expires (TFE2 (emergency alert retransmission))	-	-	-	-
9	Upon expiry of the timer TFE2 (emergency alert retransmission), the SS-UE1 (MCData client) retransmits the emergency alert by sending a GROUP EMERGENCY ALERT	<--	GROUP EMERGENCY ALERT	-	-
10	SS starts Timer=10s (TFE2 (emergency alert retransmission))	-	-	-	-
11	Check: Does the UE (MCData Client) respond to the GROUP EMERGENCY ALERT by sending in the next 5 seconds a GROUP EMERGENCY ALERT ACK?	-->	GROUP EMERGENCY ALERT ACK	2	F
12	Wait 5 seconds for GROUP EMERGENCY ALERT ACK	-	-	-	-
13	Timer=15s expires (TFE1 (Emergency Alert)) (NOTE 5)	-	-	-	-
14	Wait 5 seconds for expiration of timer TFE2 (emergency alert retransmission)	-	-	-	-
15	Timer=10s expires (TFE2 (emergency alert retransmission))	-	-	-	-
16	SS-UE1 (MCData client) sends a GROUP EMERGENCY ALERT (NOTE 4)	<--	GROUP EMERGENCY ALERT	-	-
17	Check: Does the UE (MCData Client) respond to the GROUP EMERGENCY ALERT by sending a GROUP EMERGENCY ALERT ACK?	-->	GROUP EMERGENCY ALERT ACK	3	P
18	SS-UE1 (MCData client) sends a GROUP EMERGENCY ALERT	<--	GROUP EMERGENCY ALERT CANCEL	-	-
19	Check: Does the UE (MCData Client) respond to the GROUP EMERGENCY ALERT CANCEL by sending a GROUP EMERGENCY ALERT CANCEL ACK?	-->	GROUP EMERGENCY ALERT CANCEL ACK	4	P

NOTE 1:	This is expected to be done via a suitable implementation dependent MMI.
NOTE 2:	Timer TFE1(emergency alert) is started by the MCData Client upon the receiving of the GROUP EMERGENCY ALERT message. Timer TFE1 (emergency alert)=15s, as defined as defined in the Pre-test conditions. At the expire of TFE1, the MCData Client assumes the end of the emergency state and removes the associated user from the list.
NOTE 3:	Timer TFE2 (emergency alert retransmission) is started by the SS upon the sending of the GROUP EMERGENCY ALERT message. Timer TFE2 (emergency alert retransmission)=10s, as defined in TS 37.579-1 [2], Table 5.5.8.1-1. At the expire of TFE2, the SS retransmits the GROUP EMERGENCY ALERT message.
NOTE 4:	The UE (MCData Client) stores the Originating MCData user ID IE in the list of users in emergency.
NOTE 5:	Upon expiry of the timer TFE1 (Emergency Alert), the UE (MCData Client) removes the MCData user ID from the stored list of users in emergency

7.3.2.3.3 Specific message contents

None

Annex A (normative): Test Files

A.1 Introduction

This annex specifies the test files to be used for the MCData FD test cases specified in present document.

A.2 Test files for client originated file distribution

A.2.1 Test File 1 for CO FD

File type: text/plain

Content:

Test file 1 for MCData client originated file distribution

A.2.2 Test File 2 for CO FD

File type: text/plain

Content:

Test file 2 for MCData client originated file distribution

A.3 Test files for client terminated file distribution

A.3.1 Test File 1 for CT FD

File type: text/plain

Content:

Test file 1 for MCData client terminated file distribution

A.3.2 Test File 2 for CT FD

File type: text/plain

Content:

Test file 2 for MCData client terminated file distribution

Annex B (informative): Change history

Change history of TS 36.579-7							
Date	**Meeting**	**TDoc**	**CR**	**Rev**	**Cat**	**Subject/Comment**	**New version**
2018-08	RAN5#80	R5-184608	-	-	-	Introduction of TS 36.579-7	0.0.2
2018-08	RAN5#80	R5-185143	-	-	-	Draft TS 36.579-7 v003	0.0.3
2019-03	RAN5#82	R5-192245	-	-	-	Draft TS 36.579-7 v005	0.0.5
2019-09	RAN5#84	R5-196352	-	-	-	Draft TS 36.579-7 v010	0.1.0
2019-11	RAN5#85	R5-198829	-	-	-	Draft TS 36.579-7 v021	0.2.1
2020-05	RAN5#87	R5-202051	-	-	-	Draft TS 36.579-7 v030	0.3.0
2020-07	RAN#88	RP-200718	-	-	-	Draft version for information purposes to the RAN Plenary	1.0.0
2020-08	RAN5#88	R5-203529	-	-	-	draft TS 36.579-7 v1.1.0	1.1.0
2020-09	RAN#89	RP-201797	-	-	-	Draft version for approval to move the spec under revision control to the RAN Plenary	2.0.0
2020-09	RAN#89	-	-	-	-	upgraded to v14.0.0 with small editorial changes	14.0.0
2020-12	RAN#90	R5-206466	0001	1	F	Update of MCDATA TC 6.1.2	14.1.0
2020-12	RAN#90	R5-206467	0002	1	F	Update of MCDATA TC 6.2.1	14.1.0
2021-03	RAN#91	R5-211355	0003	1	F	Editorial for correcting heading styles	14.2.0
2021-06	RAN#92	R5-213420	0004	1	F	Addition of MCData Test Case 6.2.13	15.0.0
2021-12	RAN#94	R5-216754	0008	-	F	Correction of MCData test case 5.1	15.1.0
2021-12	RAN#94	R5-216755	0009	-	F	Correction of MCDATA Test Case 6.1.1	15.1.0
2021-12	RAN#94	R5-216756	0010	-	F	Correction of MCDATA Test Case 6.1.2	15.1.0
2021-12	RAN#94	R5-216757	0011	-	F	Correction of MCDATA Test Case 6.1.3	15.1.0
2021-12	RAN#94	R5-216758	0012	-	F	Correction of MCDATA Test Case 6.1.4	15.1.0
2021-12	RAN#94	R5-217914	0006	1	F	New Test Case - 6.3.1 MCData Enhanced Status CO	15.1.0
2021-12	RAN#94	R5-217915	0007	1	F	New Test Case - 6.3.2 MCData Enhanced Status CT	15.1.0
2022-03	RAN#95	R5-220495	0014	-	F	Correction of clause 2 - References	15.2.0
2022-03	RAN#95	R5-220496	0015	-	F	Correction of clause 6.1 - Short Data Service	15.2.0
2022-03	RAN#95	R5-220497	0016	-	F	Correction of clause 6.2 - File Distribution Test Cases	15.2.0
2022-03	RAN#95	R5-220498	0017	-	F	Correction of clause 6.3 - Enhanced Status Test Cases	15.2.0
2022-03	RAN#95	R5-220499	0018	-	F	Correction of MCData Test Case 5.2	15.2.0
2022-03	RAN#95	R5-220500	0019	-	F	Correction of MCData Test Case 5.3	15.2.0
2022-03	RAN#95	R5-220501	0020	-	F	Correction of MCData Test Case 5.4	15.2.0
2022-03	RAN#95	R5-220502	0021	-	F	MCData condition clarification	15.2.0
2022-03	RAN#95	R5-221404	0013	1	F	Addition of test files to annex A	15.2.0
2022-04	RAN#95	-	-	-	-	correction of missing changes of R5-220496-7-8	15.2.1
2022-06	RAN#96	R5-222143	0022	-	F	New MCData Test Case 7.1.1 Off-network SDS 1-to-1 call CO	15.3.0
2022-06	RAN#96	R5-222144	0023	-	F	New MCData Test Case 7.1.2 Off-network SDS 1-to-1 call CT	15.3.0
2022-06	RAN#96	R5-222145	0024	-	F	New MCData Test Case 7.1.3 Off-network SDS group call CO	15.3.0
2022-06	RAN#96	R5-222146	0025	-	F	New MCData Test Case 7.1.4 Off-network SDS group call CT	15.3.0
2022-06	RAN#96	R5-222147	0026	-	F	New MCData Test Case 7.2.1 Off-network Enhanced Status CO	15.3.0
2022-06	RAN#96	R5-222148	0027	-	F	New MCData Test Case 7.2.2 Off-network Enhanced Status CT	15.3.0
2022-12	RAN#98	R5-227627	0028	1	F	Correction of clause 6 - On-Network Test Scenarios	15.4.0
2023-03	RAN#99	R5-232005	0029	1	F	Correction of clause 6.1 - Short Data Service	15.5.0
2023-03	RAN#99	R5-232006	0030	1	F	Correction of clause 6.2 - File Distribution	15.5.0
2023-03	RAN#99	R5-232007	0031	1	F	Correction of clause 6.3 - Enhanced Status (ES)	15.5.0
2023-03	RAN#99	R5-232008	0032	1	F	Correction of clause 7 - Off-Network Test Scenarios	15.5.0
2023-06	RAN#100	R5-232594	0034	-	F	Addition of new test case 5.5 for Pre-established Session Configuration	16.0.0
2023-06	RAN#100	R5-232595	0035	-	F	Addition of new test case 5.6 for CSK Download	16.0.0
2023-06	RAN#100	R5-233493	0036	1	F	Addition of new test case 5.7 for Functional Alias	16.0.0
2023-09	RAN#101	R5-233831	0037	-	F	Correction of test case 5.6	16.1.0
2023-09	RAN#101	R5-233832	0038	-	F	Correction of test case 5.7	16.1.0
2023-09	RAN#101	R5-234583	0047	-	F	Addition of new test case 6.1.21 SDS 1-to-1 Signaling Functional Alias	16.1.0
2023-09	RAN#101	R5-235405	0039	1	F	Addition of new test case 6.1.13 Standalone SDS 1-to-1 Pre-established Session CO	16.1.0
2023-09	RAN#101	R5-235406	0040	1	F	Addition of new test case 6.1.14 Standalone SDS 1-to-1 Pre-established Session CT	16.1.0
2023-09	RAN#101	R5-235407	0041	1	F	Addition of new test case 6.1.15 Session SDS 1-to-1 Pre-established Session CO	16.1.0
2023-09	RAN#101	R5-235408	0042	1	F	Addition of new test case 6.1.16 Session SDS 1-to-1 Pre-established Session CT	16.1.0
2023-09	RAN#101	R5-235409	0043	1	F	Addition of new test case 6.1.17 Standalone SDS group Pre-established Session CO	16.1.0
2023-09	RAN#101	R5-235410	0044	1	F	Addition of new test case 6.1.18 Standalone SDS group Pre-established Session CT	16.1.0
2023-09	RAN#101	R5-235411	0045	1	F	Addition of new test case 6.1.19 Session SDS group Pre-established Session CO	16.1.0
2023-09	RAN#101	R5-235412	0046	1	F	Addition of new test case 6.1.20 Session SDS group Pre-established Session CT	16.1.0
2023-09	RAN#101	R5-235413	0048	1	F	Addition of new test case 6.1.22 SDS 1-to-1 Media Functional Alias	16.1.0
2023-12	RAN#102	R5-236299	0049	-	F	Correction of test case 5.5	16.2.0
2023-12	RAN#102	R5-236300	0050	-	F	Correction of test cases 6.1.15, 6.1.16, 6.1.19 and 6.1.20	16.2.0

2023-12	RAN#102	R5-236611	0052	-	F	Addition of new TC 6.2.15 FD Using Media Plane Active Functional Alias	16.2.0
2023-12	RAN#102	R5-237445	0051	1	F	Addition of new TC 6.2.14 FD Using HTTP Active Functional Alias	16.2.0
2024-03	RAN#103	R5-240584	0053	-	F	Corrections of references to 24.282	16.3.0
2024-03	RAN#103	R5-240647	0054	-	F	Editorial correction to the Scope description	16.3.0
2024-03	RAN#103	R5-241593	0055	1	F	Addition of new TC 6.4.1 Emergency Alert CO	16.3.0
2024-03	RAN#103	R5-241594	0056	1	F	Addition of new TC 6.4.2 Emergency Alert CT	16.3.0
2024-06	RAN#104	R5-242359	0058	-	F	Common correction of test cases in clauses 5 and 6	16.4.0
2024-06	RAN#104	R5-243272	0063	-	F	Correction of MCData TC 6.4.2 Emergency Alert	16.4.0
2024-06	RAN#104	R5-243570	0059	1	F	Addition of new TC 6.5.1 Location Information Request	16.4.0
2024-06	RAN#104	R5-243571	0060	1	F	Addition of new TC 6.5.2 Location Report triggering	16.4.0
2024-06	RAN#104	R5-243572	0061	1	F	Addition of new TC 5.8 Rules based affiliation status change	16.4.0
2024-06	RAN#104	R5-243573	0062	1	F	Addition of new TC 5.9 Location based functional alias status change	16.4.0
2024-09	RAN#105	R5-244964	0064	-	F	Addition of New Test Case 6.6.1 MBMS	16.5.0
2024-09	RAN#105	R5-244965	0065	-	F	Addition of New Test Case 6.7.1 IP Connectivity CO	16.5.0
2024-09	RAN#105	R5-244966	0066	-	F	Addition of New Test Case 6.7.2 IP Connectivity CT	16.5.0
2024-09	RAN#105	R5-244971	0071	-	F	Addition of New Test Case 7.3.1 Emergency Alert CO	16.5.0
2024-09	RAN#105	R5-244972	0072	-	F	Addition of New Test Case 7.3.2 Emergency Alert CT	16.5.0
2024-09	RAN#105	R5-245675	0067	1	F	Addition of New Test Case 6.8.1 Message Store Function Objects	16.5.0
2024-09	RAN#105	R5-245676	0068	1	F	Addition of New Test Case 6.8.2 Message Store Function Folders	16.5.0
2024-09	RAN#105	R5-245677	0069	1	F	Addition of New Test Case 6.8.3 Message Store Function Subscription	16.5.0
2024-09	RAN#105	R5-245678	0070	1	F	Addition of New Test Case 6.8.4 Message Store Function Synchronization	16.5.0
2024-09	RAN#105	R5-245679	0073	1	F	Addition of new references	16.5.0

NOTE: The table above will not be further updated in the future. It shows all TS 36.579-7 CRs taken over into TS 37.579-7 v0.0.1.

Change history of TS 37.579-7							
Date	**Meeting**	**TDoc**	**CR**	**Rev**	**Cat**	**Subject/Comment**	**New version**
2024-11	RAN5#105	R5-247094	-	-	-	TS 36.579-7 v16.5.0 content was transferred into this new TS 37.579-7 as by definition 36 series specifications cover LTE only aspects and multi-RAT aspects need to be covered in 37 series specifications. The only changes, compared to TS 36.579-7 v16.5.0, are: - "over LTE" has been removed from the TS title as beginning with Rel-17 the present document needs to cover also NR/5GC. - the Introduction clause has been removed and contents moved into the Foreword clause. - every instance of 36.579 has been replaced by 37.579, except in the Change history table of TS 36.579-7. - every instance of 36.579-3 has been either deleted or voided. - the CR history table of TS 36.579-7 was kept for easier reference of all changes included in TS 36.579-7, but a new Change history table was added for TS 37.579-7. - the 3GPP TS-TR template version 1.18.1 has been used.	0.0.1
2024-11	RAN5#105	R5-247099	-	-	-	RAN5 agreed 0.1.0 version R5-246646 Corrections of test case 6.8.1. (TS 36.579-7 CR 0074)	0.1.0
2024-12	RAN#106	RP-242647	-	-	-	For one-step approval at RAN#106	1.0.0
2024-12	RAN#106	-	-	-	-	raised to v17.0.0 with no change	17.0.0
2025-03	RAN#107	R5-250361	0001	-	F	Correction of test case 6.7.1	17.1.0
2025-03	RAN#107	R5-251330	0002	1	F	Updates to scope for 5G support	17.1.0
2025-03	RAN#107	R5-251331	0003	1	F	Updates to test cases to add 5G support	17.1.0
2025-06	RAN#108	R5-252757	0005	-	F	Updates to test case 6.7.2	17.2.0
2025-06	RAN#108	R5-253043	0004	1	F	Updates to test case 6.7.1	17.2.0
2025-09	RAN#109	R5-255025	0007	1	F	Addition of new test case 6.2.16	17.3.0
2025-09	RAN#109	R5-255026	0008	1	F	Addition of new test case 6.2.17	17.3.0
2025-09	RAN#109	R5-255076	0006	1	F	Addition of new test case 6.9.4	17.3.0
2025-09	RAN#109	R5-255104	0009	2	F	Addition of new test case 6.9.1	17.3.0
2025-12	RAN#110	R5-255757	0010	-	F	Addition of new test case 6.4.4	17.4.0
2025-12	RAN#110	R5-255765	0012	-	F	Updates to test case 6.9.4	17.4.0
2025-12	RAN#110	R5-255772	0013	-	F	Correction of MCData test case 6.9.1	17.4.0
2025-12	RAN#110	R5-255851	0015	-	F	Correction of MCData test case 6.2.16	17.4.0
2025-12	RAN#110	R5-255852	0016	-	F	Correction of MCData test case 6.2.17	17.4.0
2025-12	RAN#110	R5-256287	0021	-	F	Update of clause 6.9 title	17.4.0
2025-12	RAN#110	R5-256288	0022	-	F	Update to TC 6.4.1	17.4.0
2025-12	RAN#110	R5-256568	0023	-	F	Addition of new test case 6.4.3	17.4.0
2025-12	RAN#110	R5-256723	0017	1	F	Addition of new test case 6.9.3	17.4.0
2025-12	RAN#110	R5-256724	0018	1	F	Addition of new test case 6.9.2	17.4.0
2025-12	RAN#110	R5-256725	0020	1	F	Addition of new MCData test case 6.8.5	17.4.0
2025-12	RAN#110	R5-256727	0019	1	F	Addition of new test case 6.1.23	17.4.0
2026-03	RAN#111	R5-260297	0024	-	F	Correction of MCData Message Store test cases	17.5.0
2026-03	RAN#111	R5-260298	0025	-	F	Correction of MCData test cases with de-affiliation	17.5.0
2026-03	RAN#111	R5-260299	0026	-	F	Correction of test case 6.4.4	17.5.0
2026-03	RAN#111	R5-260300	0027	-	F	Correction of test case 6.9.2	17.5.0
2026-03	RAN#111	R5-260962	0028	-	F	Update to MCData TC 6.4.1	17.5.0
2026-06	RAN#112	R5-261957	0029		F	Correction of MCData emergency alert test cases	17.6.0
2026-06	RAN#112	R5-262072	0030		F	Correction of MCData test case 6.8.5	17.6.0

History

Version	Date	Status
V17.0.0	February 2025	Publication
V17.1.0	April 2025	Publication
V17.2.0	July 2025	Publication
V17.3.0	October 2025	Publication
V17.4.0	February 2026	Publication
V17.5.0	April 2026	Publication
V17.6.0	August 2026	Publication