EUROPEAN TELECOMMUNICATION STANDARD

ETS 300 083

March 1993

Source: ETSI TC-TE

Reference: T/TE 12-07

ICS: 33.080

Key words: ISDN, structured bearer service, speech information transfer, end-to-end compatibility

Integrated Services Digital Network (ISDN); Circuit mode structured bearer service category usable for speech information transfer Terminal requirements necessary for end-to-end compatibility

ETSI

European Telecommunications Standards Institute

ETSI Secretariat

Postal address: F-06921 Sophia Antipolis CEDEX - FRANCE
Office address: 650 Route des Lucioles - Sophia Antipolis - Valbonne - FRANCE
X.400: c=fr, a=atlas, p=etsi, s=secretariat - **Internet:** secretariat@etsi.fr

Tel.: +33 92 94 42 00 - Fax: +33 93 65 47 16

Copyright Notification: No part may be reproduced except as authorized by written permission. The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 1993. All rights reserved.

New presentation - see History box

Whilst every care has been taken in the preparation and publication of this document, errors in content, typographical or otherwise, may occur. If you have comments concerning its accuracy, please write to "ETSI Editing and Committee Support Dept." at the address shown on the title page.

Contents

Foreword 5

1 Scope 7

2 Normative references 7

3 Definitions 8

4 Symbols and abbreviations 8

5 D-channel characteristics 8
5.1 Outgoing call 8
5.2 Incoming call 8

6 B-channel characteristics 8
6.1 Relative level 8
6.2 Encoding 8
6.3 Speech band power level of signal from the terminal 9

Annex A (normative): Test methods 10

A.1 Test equipment 10

A.2 Speech band signal level 10

Annex B (informative): Bibliography 10

History 11

Blank page

Foreword

This European Telecommunication Standard (ETS) has been produced by the Terminal Equipment (TE) Technical Committee of the European Telecommunications Standards Institute (ETSI).

Blank page

1 Scope

This European Telecommunication Standard (ETS) specifies the requirements for a terminal to interwork with the circuit-mode 64 kbit/s 8 kHz structured bearer service with a category usable for Speech information transfer when connected by the pan-European Integrated Services Digital Network (ISDN).

The requirements of this ETS are additional to those of the ETSs for connection to the ISDN basic access interface or primary rate interface.

Annex A to this ETS specifies the method of testing required to identify conformance to this ETS as defined in ETS 300 109 [4].

NOTE : The characteristics of the ISDN User-Network Interface are specified in ETS 300 012 and ETS 300 104 [3] and the attachment requirements are specified in ETS 300 153 [5] (see Clause 2).

2 Normative references

This ETS incorporates by dated or undated reference, provision from other publications. These normative references are cited at the appropriate places in the text and the publications are listed hereafter. For dated references, subsequent amendments to or revisions of any of these publications apply to this ETS only when incorporated in it by amendment or revision. For undated references the latest edition of the publication referenced to applies.

[1] ETS 300 085 (1990): "Integrated Services Digital Network (ISDN); 3,1 kHz telephony teleservice, Attachment requirements for handset terminals (Candidate NET 33)".

[2] ETS 300 102-1 (1990): "Integrated Services Digital Network (ISDN); User-network Interface layer 3, Specifications for basic call control".

[3] ETS 300 104 (1991): "Integrated Services Digital Network (ISDN); Attachment requirements for terminal equipment to connect to an ISDN using ISDN basic access, Layer 3 aspects (Candidate NET 3, Part 2)".

[4] ETS 300 109 (1992): "Integrated Services Digital Network (ISDN); Circuit-mode 64 kbit/s 8 kHz structured bearer service category usable for speech information transfer, Service description".

[5] ETS 300 153 (1992): "Integrated Services Digital Network (ISDN); Attachment requirements for terminal equipment to connect to an ISDN using ISDN basic access (Candidate NET 3, Part 1)".

[6] CCITT Recommendation G.101 (1988): "The transmission plan".

[7] CCITT Recommendation G.701 (1988): "Vocabulary of digital transmission and multiplexing, and pulse code modulation (PCM) terms".

[8] CCITT Recommendation G.711 (1988): "Pulse code modulation (PCM) of voice frequencies".

[9] CCITT Recommendation I.112 (1988): "Vocabulary of terms for ISDNs".

[10] CCITT Recommendation I.230 (1988): "Definition of bearer service categories".

[11] CCITT Recommendation P.56 (1988): "Objective measurement of active speech level".

3 Definitions

For the purpose of this ETS, the relevant definitions used in CCITT Recommendations G.701 [7], I.112 [9] and I.230 [10] apply.

4 Symbols and abbreviations

For the purpose of this ETS, the symbols and abbreviations used in CCITT Recommendations G.701 [7], I.112 [9] and I.230 [10] apply.

5 D-channel characteristics

5.1 Outgoing call

When initiating a call on the Speech bearer service, the coding of the Bearer Capability (BC) information element in the SETUP message shall be in conformance with figure 1.

Compliance shall be checked by using the test specified in ETS 300 104 [3], Annex A, Section 3, Clause 9.

8	7	6	5	4	3	2	1	
0	Bearer Capability 0 0 0 0 1 0 0 Information element identifier							Octet 1
0	0 0 0 0 0 1 1 Length of information element							Octet 2
1	0 0 CCITT	0 0 0 0 0 Speech						Octet 3
1 Ext	Circuit 0 0 Mode	1 0 0 0 0 64 kbit/s						Octet 4
1 Ext	0 1 Layer 1	0 0 0 1 1 G.711 A-law						Octet 5

NOTE : The use of HLC and LLC information elements is optional. If they are used they are to be encoded according to the appropriate teleservice described in ETR 018.

Figure 1: Coding of Bearer Capability (BC) information element speech

5.2 Incoming call

An incoming call shall be considered as a request for the speech bearer service if the Bearer Capability (BC) information element in the incoming SETUP message is encoded as described in figure 1.

Compliance can be checked by using the test specified in ETS 300 104 [3], Annex A, Section 1, Clause 1.

NOTE: If HLC and/or LLC elements are present in an incoming call message, they may be used for compatibility checking according to ETS 300 102-1 [2].

6 B-channel characteristics

6.1 Relative level

The digital interface is a 0 dBr point according to CCITT Recommendation G.101 [6].

6.2 Encoding

The information shall be encoded using the A-law at 64 kbit/s as defined in CCITT Recommendation G.711 [8].

6.3 Speech band power level of signal from the terminal

During any period of 10 seconds the average active power level delivered at the digital interface at frequencies below 4 kHz shall not exceed - 13 dBm0.

Compliance shall be checked using the test described in Annex A.

NOTE: The requirements for two-way voice terminals are expressed as loudness rating requirements. These requirements can be found in ETS 300 082.

Annex A (normative): Test methods

A.1 Test equipment

The test equipment for measuring power level shall use one of the approaches described in ETS 300 085 [1], Annex A, subclause A.1.4.

The accuracy of the measurements shall meet the requirements of ETS 300 085 [1], Annex A, subclause A.1.6.

The environmental conditions for the testing laboratory can be found in ETS 300 153 [5].

A.2 Speech band signal level

The output signal power level at the digital interface shall be measured, unweighted, using a speech voltmeter conforming to CCITT Recommendation P.56 [11], method B, with an integration time of 10 seconds. The test shall be conducted in a quiet environment.

Annex B (informative): Bibliography

The following informative references are given in this ETS.

ETR 018 (1991): "Integrated Services Digital Network (ISDN); Application of the BC-HLC-, LLc information elements by terminals supporting ISDN services".

ETS 300 082 (1992): "Integrated Services Digital Network (ISDN); 3,1 kHz telephony teleservice End-to-end compatibility requirements for telephony terminals".

ETS 300 012 (1991): "Integrated Services Digital Network (ISDN); Basic user-network interface, Layer 1 specification and test principles".

History

	Document history
March 1993	First Edition
February 1996	Converted into Adobe Acrobat Portable Document Format (PDF)