Draft ETSI EN 319 142-1 V1.3.0 (2026-08)



EUROPEAN STANDARD

Electronic Signatures and Trust Infrastructures (ESI);
PAdES digital signatures;
Part 1: Building blocks and PAdES baseline signatures

Reference
REN/ESI-0019142-1v131

Keywords
electronic signature, PAdES, profile, security

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from the
ETSI Search & Browse Standards application.

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format on ETSI deliver repository.

Users should be aware that the present document may be revised or have its status changed, this information is available in the Milestones listing.

If you find errors in the present document, please send your comments to the relevant service listed under Committee Support Staff.

If you find a security vulnerability in the present document, please report it through our Coordinated Vulnerability Disclosure (CVD) program.

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.
No recommendation as to products and services or vendors is made or should be implied.
In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part of this document may be reproduced in any form, by any means and in any media, without the prior written authorization of ETSI and except as expressly permitted below.
By way of exception and when the document is a normative deliverable (European Standard (EN), Technical Specification (TS), Group Specification (GS) or ETSI Standard (ES)), ETSI authorizes to reproduce and incorporate into products, services and technical documentation only those extracts (e.g. templates) that are strictly necessary for the technical implementation of the normative deliverable, to ensure compliance with the latter.
Nothing in this notice shall be construed as limiting any mandatory exceptions to copyright provided by applicable law.

© ETSI 2026.
All rights reserved.

Contents

Intellectual Property Rights 4
Foreword 4
Modal verbs terminology 5
Introduction 5
1 Scope 6
2 References 6
2.1 Normative references 6
2.2 Informative references 7
3 Definition of terms, symbols and abbreviations 8
3.1 Terms 8
3.2 Symbols 8
3.3 Abbreviations 8
4 General syntax 9
4.1 General requirements for PAdES signatures based on PDF signatures 9
5 Attributes syntax and semantics 9
5.1 Introduction 9
5.2 CMS and CAdES defined attributes 10
5.3 ISO 32000 defined attributes 10
5.4 Validation data and archive validation data attributes 11
5.4.1 Overview 11
5.4.2 Document Security Store 13
5.4.2.1 Catalog 13
5.4.2.2 DSS Dictionary 13
5.4.2.3 Signature VRI Dictionary 15
5.4.3 Document Time-stamp 16
5.4.4 Validation of PAdES signatures 16
5.5 Requirements on encryption 17
5.6 Extensions dictionary and PDF 2.0 conformance 17
5.6.1 ISO 32000-1 (PDF 1.7) Compliant Documents 17
5.6.2 ISO 32000-2 (PDF 2.0) Compliant Documents 18
5.6.3 Version conformance across document revisions 18
6 PAdES baseline signatures 18
6.1 Signature levels 18
6.2 General requirements for PAdES baseline signatures 19
6.2.1 Algorithm requirements 19
6.2.2 Notation for requirements 19
6.3 PAdES baseline signatures 21
6.4 Legacy PAdES baseline signatures 26
Annex A (informative): Change history 27
History 28

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables (European Standard (EN), Technical Specification (TS), Group Specification (GS) or ETSI Standard (ES)) may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI IPR online database.

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™**, **LTE™** and **5G™** logo are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM**® and the GSM logo are trademarks registered and owned by the GSM Association.

Foreword

This draft European Standard (EN) has been produced by ETSI Technical Committee Electronic Signatures and Trust Infrastructures (ESI), and is now submitted for the combined Public Enquiry and Vote of the ETSI EN Approval Procedure (ENAP).

The present document is part 1 of a multi-part deliverable covering the PDF digital signatures (PAdES), as identified below:

ETSI EN 319 142-1: "Building blocks and PAdES baseline signatures";

ETSI EN 319 142-2: "Additional PAdES signatures profiles";

ETSI TS 119 142-3: "PAdES Document Time-stamp digital signatures (PAdES-DTS)".

Proposed national transposition dates	
Date of latest announcement of this EN (doa):	3 months after ETSI publication
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	6 months after doa
Date of withdrawal of any conflicting National Standard (dow):	6 months after doa

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the ETSI Drafting Rules (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Introduction

Electronic commerce has emerged as a frequent way of doing business between companies across local, wide area and global networks. Trust in this way of doing business is essential for the success and continued development of electronic commerce. It is therefore important that companies using this electronic means of doing business have suitable security controls and mechanisms in place to protect their transactions and to ensure trust and confidence with their business partners. In this respect digital signatures are an important security component that can be used to protect information and provide trust in electronic business.

The present document is intended to cover digital signatures supported by PKI and public key certificates, and aims to meet the general requirements of the international community to provide trust and confidence in electronic transactions, including, amongst other, applicable requirements from Regulation (EU) No 910/2014 [i.2].

The present document can be used for any transaction between an individual and a company, between two companies, between an individual and a governmental body, etc. The present document is independent of any environment. It can be applied to any environment e.g. smart cards, SIM cards, special programs for electronic signatures, etc.

The present document is part of a rationalized framework of standards (see ETSI TR 119 000 [i.3]).

ETSI TR 119 100 [i.4] provides guidance on how to use the present document within the aforementioned framework.

1 Scope

The present document specifies PAdES digital signatures. PAdES signatures build on PDF signature mechanisms defined in the ISO 32000 series. For documents conforming to ISO 32000-1 [1] PAdES utilizes an extended, alternative signature encoding. For documents conforming to ISO 32000-2 [9], these signature structures are incorporated natively by default within the core standard. Both approaches support digital signature formats equivalent to the signature format CAdES as specified in ETSI EN 319 122-1 [2], by incorporation of signed and unsigned attributes, which fulfil certain common requirements (such as the long term validity of digital signatures) in a number of use cases.

The present document specifies formats for PAdES baseline signatures, which provide the basic features necessary for a wide range of business and governmental use cases for electronic procedures and communications to be applicable to a wide range of communities when there is a clear need for interoperability of digital signatures used in electronic documents.

The present document defines four levels of PAdES baseline signatures addressing incremental requirements to maintain the validity of the signatures over the long term, in a way that a certain level always addresses all the requirements addressed at levels that are below it. Each level requires the presence of certain PAdES attributes, suitably profiled for reducing the optionality as much as possible.

Procedures for creation, augmentation, and validation of PAdES digital signatures are out of scope and specified in ETSI EN 319 102-1 [10]. Guidance on creation, augmentation and validation of PAdES digital signatures including the usage of the different attributes defined in the present document is provided in ETSI TR 119 100 [i.4]. The present document aims at supporting electronic signatures in different regulatory frameworks.

NOTE: Specifically but not exclusively, PAdES digital signatures specified in the present document aim at supporting electronic signatures, advanced electronic signatures, qualified electronic signatures, electronic seals, advanced electronic seals, and qualified electronic seals as per Regulation (EU) No 910/2014 [i.2].

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found in the ETSI docbox.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long-term validity.

The following referenced documents are necessary for the application of the present document.

[1] ISO 32000-1: "Document management — Portable document format — Part 1: PDF 1.7".

[2] ETSI EN 319 122-1: "Electronic Signatures and Infrastructures (ESI); CAdES digital signatures; Part 1: Building blocks and CAdES baseline signatures".

[3] IETF RFC 5652 (2009): "Cryptographic Message Syntax (CMS)".

[4] IETF RFC 5280 (2008): "Internet X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile".

[5] IETF RFC 6960 (2013): "X.509 Internet Public Key Infrastructure Online Certificate Status Protocol - OCSP".

[6] IETF RFC 3161 (2001): "Internet X.509 Public Key Infrastructure Time-Stamp Protocol (TSP)".

[7] W3C® Recommendation (2 May 2008): "Canonical XML Version 1.1".

[8] IETF RFC 5816 (2010): "ESSCertIDv2 Update for RFC 3161".

[9] ISO 32000-2: "Document management — Portable document format —Part 2: PDF 2.0".

[10] ETSI EN 319 102-1: "Electronic Signatures and Trust Infrastructures (ESI); Procedures for Creation and Validation of AdES Digital Signatures; Part 1: Creation and Validation".

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long-term validity.

The following referenced documents may be useful in implementing an ETSI deliverable or add to the reader's understanding, but are not required for conformance to the present document.

[i.1] Void.

[i.2] Regulation (EU) No 910/2014 of the European Parliament and of the Council of 23 July 2014 on electronic identification and trust services for electronic transactions in the internal market and repealing Directive 1999/93/EC.

[i.3] ETSI TR 119 000: "Electronic Signatures and Infrastructures (ESI); The framework for standardization of digital signatures and trust services; Overview".

[i.4] ETSI TR 119 100: "Electronic Signatures and Infrastructures (ESI); Guidance on the use of standards for signature creation and validation".

[i.5] Void.

[i.6] ETSI TS 119 312: "Electronic Signatures and Trust Infrastructures (ESI); Cryptographic Suites".

[i.7] Adobe® XFA: "XML Forms Architecture (XFA) Specification" version 2.5, (June 2007), Adobe Systems Incorporated".

[i.8] ETSI TS 103 172: "Electronic Signatures and Infrastructures (ESI); PAdES Baseline Profile".

[i.9] IETF RFC 2315 (1998): "PKCS #7: Cryptographic Message Syntax Version 1.5".

[i.10] ETSI TS 119 612: "Electronic Signatures and Trust Infrastructures (ESI); Trusted Lists".

[i.11] ETSI EN 319 142-2: "Electronic Signatures and Trust Infrastructures (ESI); PAdES digital signatures; Part 2: Additional PAdES signatures profiles".

[i.12] ETSI TR 119 001: "Electronic Signatures and Infrastructures (ESI); The framework for standardization of signatures; Definitions and abbreviations".

[i.13] ETSI TS 119 511: "Electronic Signatures and Trust Infrastructures (ESI); Policy and security requirements for trust service providers providing long-term preservation of digital signatures or general data using digital signature techniques".

3 Definition of terms, symbols and abbreviations

3.1 Terms

For the purposes of the present document, the terms given in ISO 32000-1 [1], ISO 32000-2 [9], ETSI TR 119 001 [i.12] and the following apply:

digital signature: data appended to, or a cryptographic transformation of a data unit that allows a recipient of the data unit to prove the source and integrity of the data unit and protect against forgery, e.g. by the recipient

digital signature value: result of the cryptographic transformation of a data unit that allows a recipient of the data unit to prove the source and integrity of the data unit and protect against forgery, e.g. by the recipient

electronic time-stamp: data in electronic form which binds other electronic data to a particular time establishing evidence that these data existed at that time

generator: any party which creates, or augments a digital signature

NOTE: This can be the signer or any party that initially validates or further maintains the signature.

legacy PAdES baseline signature: digital signature generated according to ETSI TS 103 172 [i.8]

PAdES signature: digital signature that satisfies the requirements specified within the present document or ETSI EN 319 142-2 [i.11]

proof of existence: evidence that proves that an object existed at a specific date/time

signature augmentation policy: set of rules, applicable to one or more digital signatures, that defines the technical and procedural requirements for their augmentation, in order to meet a particular business need, and under which the digital signature(s) can be determined to be conformant

signature creation policy: set of rules, applicable to one or more digital signatures, that defines the technical and procedural requirements for their creation, in order to meet a particular business need, and under which the digital signature(s) can be determined to be conformant

signature handler: software application, or part of a software application, that knows how to perform digital signature operations (e.g. signing and/or validating) in conformance with ISO 32000-1 [1] or ISO 32000-2 [9] and the requirements of the appropriate profile

signature policy: signature creation policy, signature augmentation policy, signature validation policy or any combination thereof, applicable to the same signature or set of signatures

signature validation policy: set of rules, applicable to one or more digital signatures, that defines the technical and procedural requirements for their validation, in order to meet a particular business need, and under which the digital signature(s) can be determined to be valid

trust service provider: natural or legal person who provides one or more trust services

validation data: data that is used to validate a digital signature

verifier: entity that wants to validate or verify a digital signature

3.2 Symbols

Void.

3.3 Abbreviations

For the purposes of the present document, the abbreviations given in ETSI TR 119 001 [i.12] and the following apply:

DSS Document Security Store

4 General syntax

4.1 General requirements for PAdES signatures based on PDF signatures

PAdES signatures profiled in the present document build on PDF signatures specified in either ISO 32000-1 [1] or ISO 32000-2 [9] with an alternative signature encoding to support digital signature formats equivalent to the signature format CAdES as specified in ETSI EN 319 122-1 [2], by incorporation of signed and unsigned attributes described in clause 5.

The following requirements apply:

a) A DER-encoded `SignedData` object as specified in ETSI EN 319 122-1 [2] shall be included as the PDF signature in the entry with the key `Contents` of the Signature Dictionary as described in ISO 32000-1 [1], clause 12.8.1 or ISO 32000-2 [9], clause 12.8.1. There shall only be a single signer (i.e. one single component of `SignerInfo` type within `signerInfos` element) in any PDF Signature. Regardless of the PDF version used, the byte-range covered by the signature shall comprise exactly the entire PDF revision being signed except for the Contents space itself, leaving no unmapped bytes outside the `ByteRange` definition.

b) Requirements for handling PDF Signatures specified in ISO 32000-1 [1], clause 12.8 or ISO 32000-2 [9], clause 12.8 shall apply except where overridden by the present document.
When signatures are generated based on ISO 32000-2 [9], cryptographically secure digest algorithms (defined in ETSI TS 119 312 [i.6]) shall be used, and legacy algorithms (MD5 and SHA-1) shall not be used for new signature creation. For signatures based on ISO 32000-1 [1], the use of SHA-256 or stronger algorithms is highly recommended for signature creation, while SHA-1 and MD5 may be supported solely for verification purposes of legacy documents.

NOTE 1: Given that PAdES signatures are enveloped inside a PDF document and are detached in the sense of a CMS signature, the signature placement is implied by ISO 32000-1 [1] or ISO 32000-2 [9].
In ISO 32000-1 [1], clause 12.8.3.3.1 reads "No data shall be encapsulated in the PKCS#7 `SignedData` field" whereas in ISO 32000-2 [9], the corresponding clause refers to the field as the CMS `SignedData` field.

NOTE 2: ISO 32000-2 [9] deprecates legacy SubFilter values like adbe.pkcs7.sha1. For maximum interoperability across PDF versions, the SubFilter value ETSI.CAdES.detached should be used, as it is natively supported by ISO 32000-2 [9] (Table 252) and widely implemented as an extension in ISO 32000-1 [1] compliant software.

c) Some signature attributes found in ETSI EN 319 122-1 [2] have the same or similar meaning as keys in the Signature Dictionary described in ISO 32000-1 [1] or ISO 32000-2 [9]. For signature attributes and keys that have the same or similar meaning only one of them should be used according to the requirements set in Table 1.

5 Attributes syntax and semantics

5.1 Introduction

This clause provides details on attributes specified within ISO 32000-1 [1], ISO 32000-2 [9], and ETSI EN 319 122-1 [2] and defines new attributes for building PAdES signatures.

The clause distinguishes between the following types of attributes: CMS and CAdES defined attributes, ISO 32000-1 [1] or ISO 32000-2 [9] defined attributes, validation data and archive validation data attributes.

- The first ones are the attributes that build the DER-encoded `SignedData` object included as the PDF signature in the entry with the key `Contents` of the Signature Dictionary as described in ISO 32000-1 [1], clause 12.8.1 or ISO 32000-2 [9], clause 12.8.1. Depending on the underlying PDF specification version, this object conforms either to the PKCS#7 format or the CMS (Cryptographic Message Syntax) format, respectively.

- The second ones are the attributes that build the Signature Dictionary as described in ISO 32000-1 [1] or ISO 32000-2 [9].
- The other ones are the attributes where to include validation data and archive validation data that can guarantee long term validity of digital signatures.

Clause 6.3 provides the requirements concerning how to use the attributes described above.

5.2 CMS and CAdES defined attributes

The attributes included in the following list may be used to generate the DER-encoded `SignedData` object included as the PDF signature in the entry with the key `Contents` of the Signature Dictionary as described in ISO 32000-1 [1], clause 12.8.1 or ISO 32000-2 [9], clause 12.8.1. Their syntax shall be as defined in ETSI EN 319 122-1 [2], clause 5.

- `content-type`
- `message-digest`
- Signing certificate reference attributes
  - `ESS signing-certificate`

    May be used for legacy compliance in ISO 32000-1 [1] signatures; shall not be used in ISO 32000-2 [9] signatures.
  - `ESS signing-certificate-v2`

    Shall be used for ISO 32000-2 [9] signatures and is strongly recommended for ISO 32000-1 [1] signatures using SHA-2 or stronger digest algorithms.
- `commitment-type-indication`
- `signer-attributes-v2`
- `content-time-stamp`
- `signature-policy-identifier`
- `signature-time-stamp`

5.3 ISO 32000 defined attributes

The entries of the Signature Dictionary shall be as defined in ISO 32000-1 [1], clause 12.8.1 (Table 252) or ISO 32000-2 [9], clause 12.8.1 (Table 254).

For the following signature dictionary entries, these additional requirements apply:

- **SubFilter**

  For signatures conforming to ISO 32000-2 [9], this shall be set to ETSI.CAdES.detached. For legacy compliance with ISO 32000-1 [1], adbe.pkcs7.detached may be supported for verification, but ETSI.CAdES.detached is preferred for new signature generation.
- **Contents**

  Shall contain the DER-encoded SignedData object as specified in clause 4.1.a).
- **ByteRange**

  Shall be used to identify the bytes of the document covered by the signature, conforming to the gapless requirement specified in clause 4.1.a).

- **M**

  The time of signing. The syntax shall conform to the Date format specified in ISO 32000-1 [1] or ISO 32000-2 [9]).

- **Name** (Optional)

  The name of the person or authority signing the document. This value should be used only when it is not possible to extract the name from the signature.

- **Location** (Optional)

  To prevent data redundancy and synchronization conflicts during validation, this key shall not be used if equivalent information is present within the CMS signed attributes of the signature: `signer-location`.

- **Reason** (Optional)

  To prevent data redundancy and synchronization conflicts during validation, this key shall not be used if equivalent information is present within the CMS signed attributes of the signature: `commitment-type-indication`.

- **ContactInfo** (Optional)

- **Prop_Build** (Optional in ISO 32000-1 [1], strongly recommended in ISO 32000-2 [9])

  In ISO 32000-2 [9] strongly recommended to build an internal dictionary containing the software application name, version, and operating system used to create the signature.

5.4 Validation data and archive validation data attributes

5.4.1 Overview

Validation of a digital signature requires data to validate the signature such as CA certificates, Certificate Revocation List (CRL) or Online Certificate Status Protocol (OCSP) commonly provided by online services (referred to in the present document as validation data).

This clause describes the mechanism to carry such validation data as necessary to validate a signature, optionally with Validation Related Information (VRI) which relates the validation data to a specific signature (see clause 5.4.2).

For signatures based on ISO 32000-1 [1], this mechanism is implemented via the Document Security Store (DSS) extension. For signatures based on ISO 32000-2 [9], this mechanism relies on the native Document Security Store (DSS) as formally standardized in ISO 32000-2 [9], clause 12.8.4.

The structure of DSS and VRI is illustrated in Figure 1.




Figure 1: Illustration of DSS and VRI structures

For PDF documents based on ISO 32000-1 [1], this clause also defines an extension called Document Time-stamp (see clause 5.4.3) to extend the life-time of protection to the document.

NOTE 1: ISO 32000-2 [9] includes this feature natively.

These extensions support Long Term Validation (LTV) of PDF Signatures. The structure of a PDF document with LTV data is illustrated in Figure 2.




Figure 2: Illustration of PDF document with extended life-time protection

The life-time of the protection can be further extended beyond the life-time of the last Document Time-stamp applied by adding further DSS information to validate the previous last Document Time-stamp along with a new Document Time-stamp. Every time a DSS Dictionary is updated during incremental update, it should contain the values from the previous DSS Dictionary.

NOTE 2: In general the DSS Dictionary will contain validation data from previous revisions plus validation data added for the current revision. If entries are removed from a DSS Dictionary during an incremental update the set of validation data might not be complete for validation of the signatures, but replacement of validation data - e.g. more up-to-date certificate status information - might be performed for optimization reasons.

This is illustrated in Figure 3.




Figure 3: Illustration of PDF Document with repeated LTV data

5.4.2 Document Security Store

5.4.2.1 Catalog

For documents conforming to ISO 32000-1 [1], the DSS entry is added to Table 28 ("Entries in catalogue dictionary").

Added to ISO 32000-1 [1], Table 28 "Entries in catalogue dictionary"		
KEY	**TYPE**	**VALUE**
DSS	Dictionary	*(Optional)* Document-wide security-related information.

For documents conforming to ISO 32000-2 [9], the DSS entry shall be populated in accordance with Table 31 ("Entries in the document catalog dictionary") of the PDF 2.0 specification.

5.4.2.2 DSS Dictionary

The Document Security Store (DSS) shall be a dictionary that shall have the value DSS as key in the document catalog dictionary. This dictionary is used to provide a single place where all of the VRI for some or all signatures in the document should be placed.

The DSS dictionary, if present, shall contain VRI only for document and time-stamps signatures represented in PKCS#7 and CMS (and its derivatives) format or for XAdES signatures of forms signing dynamic XFA [i.7].

NOTE 1: See ETSI EN 319 142-2 [i.11] for specification of XAdES signatures of forms signing dynamic XFA.

Entries in a DSS Dictionary (Conforming to ISO 32000-1 [1] extensions or natively to ISO 32000-2 [9], Table 256):

Entries in a DSS Dictionary		
KEY	**TYPE**	**VALUE**
Type	Name	*(Optional)* It shall be DSS for a document security store dictionary.
VRI	Dictionary	*(Optional)* This dictionary contains Signature VRI dictionaries in the document. For ISO 32000-1 [1] documents the key of each entry in this dictionary is the base-16-encoded (uppercase) SHA1 digest of the signature to which it applies and the value is the Signature VRI dictionary which contains the VRI for that signature. See additional requirements a), b), c) and d).
Certs	Array	*(Optional)* An array of indirect references to streams, each containing one DER-encoded X.509 certificate (that shall be as defined in IETF RFC 5280 [4]). This array contains certificates that can be used in the validation of any signatures in the document.
OCSPs	Array	*(Optional)* An array of indirect references to streams, each containing a DER-encoded Online Certificate Status Protocol (OCSP) response, which can be used in the validation of any signature in the document. The OCSP response shall be encoded by using the encoding of the `OCSPResponse` type as defined in IETF RFC 6960 [5] (see note 2).
CRLs	Array	*(Optional)* An array of indirect references to streams, each containing a DER-encoded Certificate Revocation List (CRL) (that shall be as defined in IETF RFC 5280 [4]). This array contains CRLs that can be used in the validation of any signatures in the document.
Additional requirements for VRI keys: a) For document signatures or Document Time-stamp signatures the bytes that are hashed shall be those of the complete hexadecimal string in the entry with the key `Contents` of the associated Signature Dictionary containing the signature's DER-encoded binary data object (e.g. PKCS#7, CMS or CAdES objects). b) For the signatures of CRLs and OCSP responses, the bytes that are hashed shall be the respective signature objects represented as a BER-encoded OCTET STRING encoded with primitive encoding. c) When computing the digest of a XAdES signature found in dynamic XFA [i.7], the contents of the ds:Signature shall be canonicalized using exclusive canonicalization (http://www.w3.org/2001/10/xml-exc-c14n#) as specified in [7] and then hashed.		

Any VRI dictionaries shall be located in document incremental update sections. If the Signature Dictionary to which a VRI dictionary applies is itself in an incremental update section (see clause 7.5.6 of ISO 32000-1 [1] or clause 7.5.6 of ISO 32000-2 [9]), the VRI update shall be done later than the signature update.

NOTE 2: To facilitate the verification of signatures created according to previous versions of the signature format specifications, a verifier can also accept OCSP responses encoded by using the encoding of the `BasicOCSPResponse` type as defined in IETF RFC 6960 [5].

5.4.2.3 Signature VRI Dictionary

The signature VRI dictionary shall contain Validation Related Information (VRI) for a specific signature in the document to which the validation information applies.

Entries in a Signature VRI Dictionary (Conforming to ISO 32000-1 [1] extensions or natively to ISO 32000-2 [9], Table 257):

Entries in a Signature VRI Dictionary		
KEY	**TYPE**	**VALUE**
Type	Name	*(Optional),*if present, it shall be VRI for a VRI dictionary.
Cert	Array	*(Optional,* if present, it shall not be an empty array*)* An array of indirect references to streams, each containing one DER-encoded X.509 certificate (that shall be as defined in IETF RFC 5280 [4]). This array should contain all certificates that were used in the validation of this signature.
CRL	Array	(*Optional*, if present, it shall not be an empty array) An array of indirect references to streams that are all CRLs used to determine the validity of the certificates in the chains related to this signature. Each stream shall reference a CRL that is an entry in the CRLs array in the DSS dictionary.
OCSP	Array	(*Optional*, if present shall not be an empty array) An array of indirect references to streams that are all OCSP responses used to determine the validity of the certificates in the chains related to this signature. Each stream shall reference an OCSP response that is an entry in the OCSPs array in the DSS dictionary.
TU	Date	*(Optional),* the date/time at which this signature VRI dictionary was created. A signature handler may ignore this entry and use a different time for the signature validation. This entry shall be absent when the TS entry is present. Date shall be a date string as defined in ISO 32000-1 [1], clause 7.9.4 or ISO 32000-2 [9], clause 7.9.4. See additional requirement a).
TS	Stream	*(Optional),* a stream containing the DER-encoded time-stamp token (that shall be as defined in IETF RFC 3161 [6] updated by IETF RFC 5816 [8] and which represents the secure time at which this signature VRI dictionary was created. This entry shall be absent when a TU entry is present. See note 1 and additional requirement b).
Additional requirements: a) The TU key should not be used. b) The TS key should not be used. c) Exactly one of the following methods to provide a VRI generation claimed time shall be used: the TU entry, the TS entry or a subsequent Document Time-stamp. NOTE 1: For PKCS#7 signatures conforming to ISO 32000-1 [1] the datum that is hashed and included in the `messageImprint` field of the DER-encoded time stamp stored in TS entry (see IETF RFC 3161 [6] updated by IETF RFC 5816 [8]) is the `encryptedDigest` field in the signature's PKCS#7 object (as defined in IETF RFC 2315 [i.9]). For CMS signatures conforming to ISO 32000-2 [9], the corresponding signature value field within the `SignerInfo` structure shall be used. NOTE 2: The VRI dictionary is optional, since all necessary data to validate the signature can be available from other sources like the DSS dictionary itself. The VRI dictionary offers possibilities for optimization of the validation process, since it relates the data to one specific signature. NOTE 3: The value of TS can be used as a proof of existence for the signature value itself.		

Any values in the `Cert`, `CRL` and `OCSP` arrays of a Signature VRI dictionary shall also be present in the DSS dictionary applicable to the signature for which this Signature VRI dictionary is associated. If this signature (e.g. PKCS#7, CMS or CAdES object) does not have any associated `Certs`, `CRLs` or `OCSPs`, then the corresponding key shall not be present in the VRI dictionary.

A Signature VRI dictionary shall not be used to record the information used in an unsuccessful validation attempt.

MDP restrictions (see ISO 32000-1 [1], clause 12.8.2.2 or ISO 32000-2 [9], clauses 12.8.2.2 and 12.7.5.5) shall not apply to incremental updates to a PDF document containing a DSS dictionary and associated `VRI`, `Certs`, `CRLs` and `OCSPs`.

NOTE: ISO 32000-1 [1], clause 12.8.2.2 and ISO 32000-2 [9], clauses 12.8.2.2 and 12.7.5.5, address the MDP (Modification, Detection and Prevention) feature whereby a set of permissions can be associated with a PDF in conjunction with a certification signature. The permissions of MDP are present in the entry with the `P` key of the DocMDP transform parameters dictionary and of the signature field lock dictionary, as an integer in the range 1 through 3. Values of 2 and 3 allow for additional signatures to be included after the certification but a value of 1 does not allow any change but allows Document Time-stamps.

5.4.3 Document Time-stamp

A Document Time-stamp dictionary shall be a standard Signature Dictionary (as defined in ISO 32000-1 [1], clause 12.8.1, Table 252) with the following changes.

Modifications to the standard Signature Dictionary for a Document Time-stamp Dictionary:

Modifications to Table 252 for a Document Time-stamp Dictionary of ISO 32000-1 [1]		
KEY	**TYPE**	**VALUE**
Type	Name	*(Required)* It shall be **DocTimeStamp**.
SubFilter	Name	*(Required)* The value of `SubFilter` identifies the format of the data contained in the stream. A conforming reader may use any signature handler that supports the specified format. The value of `SubFilter` should be **ETSI.RFC3161**. Other values may be defined by developers, and when used, shall be prefixed with the registered developer identification as described in ISO 32000-1 [1], annex E.
Contents	Byte string	*(Required)* When the value of `SubFilter` is **ETSI.RFC3161**, the value of `Contents` shall be the hexadecimal string (as defined in clause 7.3.4.3 in ISO 32000-1 [1]) representing the value of TimeStampToken as specified in IETF RFC 3161 [6] updated by IETF RFC 5816 [8]. The value of the `messageImprint` field within the TimeStampToken shall be a hash of the bytes of the document indicated by the `ByteRange`. The cryptographic digest algorithm used for the `messageImprint` shall comply with the algorithm requirements of the respective PDF version profile. The `ByteRange` shall cover the entire document, including the Document Time-stamp dictionary but excluding the TimeStampToken itself (the entry with key *Contents*).
V	Integer	(Optional) The version of the Signature Dictionary format. For Document Time-stamp dictionaries the value, if present, shall be 0. Default value: 0.
NOTE: Clause 7.3.4 in ISO 32000-1 [1] requires space for the `Contents` value to be allocated before the message digest is computed.		

In addition, the following keys shall not be present in a Document Time-stamp dictionary: `Cert`, `Reference`, `Changes`, `R`, `Prop_AuthTime`, and `Prop_AuthType`.

The following keys should not be present in a Document Time-stamp dictionary: `Name`, `M`, `Location`, `Reason`, and `ContactInfo`. Since this information can already be present inside of the TimeStampToken contained in `Contents`, a conforming reader should ignore these keys.

As the validation data for the last Document Time-stamp becomes at risk for obsolescence or when the encryption technology used for the Document Time-stamp signature becomes at risk for successful attack, there is the likely scenario that updates to the time stamp signature and its revocation information may need to take place. This process is done using the same LTV methodology already described.

When evaluating the MDP restrictions (see ISO 32000-1 [1], clause 12.8.2.2 or ISO 32000-2 [9], clauses 12.8.2.2 and 12.7.5.5) the presence of a Document Time-stamp dictionary item shall be ignored.

NOTE: See note in clause 5.4.2.3.

5.4.4 Validation of PAdES signatures

For the validation of PAdES signatures conforming to this document, the signature validation procedures and requirements specified in ETSI EN 319 102-1 [10] shall apply.

For signatures based on ISO 32000-2 [9], the generic signature validation rules defined in clauses 12.8.3.4.5 to 12.8.3.4.8 shall not be used to determine the validation status. In case of any contradiction regarding certificate, time-stamp, or revocation validation, the requirements of ETSI EN 319 102-1 [10] shall take precedence over ISO 32000-2 [9].

NOTE: Unlike ISO 32000-1 [1], which strictly defines the structural encapsulation of signatures, ISO 32000-2 [9] introduces generic signature validation rules based on basic IETF RFC 5280 [4] principles. To maintain clear architectural separation and support advanced trust models (e.g. Proof of Existence and Trust Lists), the requirement above delegates all cryptographic and semantic validation to ETSI EN 319 102-1 [10], superseding the baseline procedures of ISO 32000-2 [9].

5.5 Requirements on encryption

A PDF document can be encrypted to protect its contents from unauthorized access. When encryption and signatures are combined together in a single PDF document, encryption shall be applied to its content before any signature is incorporated into it.

Encryption shall apply to all strings and streams in the document's PDF file, with the following exceptions:

- The values for the ID entry in the trailer.
- Any strings in an `Encrypt` dictionary.
- Any strings that are inside streams such as content streams and compressed object streams, which themselves are encrypted.
- Any hexadecimal strings representing the value of the `Contents` key in a Signature Dictionary.

NOTE 1: For documents conforming to ISO 32000-1 [1], the use of AES-128 or AES-256 is strongly recommended, while RC4 may only be supported for the verification of existing legacy files.

NOTE 2: For documents conforming to ISO 32000-2 [9], the encryption mechanism complies with clause 7.6 of the PDF 2.0 specification. This implies that no legacy encryption algorithms, including RC4 and AES with key lengths shorter than 128 bits are in use. Conforming PDF 2.0 documents use AES-128 or AES-256 (Revision 5 or Revision 6) encryption engines.

5.6 Extensions dictionary and PDF 2.0 conformance

5.6.1 ISO 32000-1 (PDF 1.7) Compliant Documents

The extensions dictionary for ISO 32000-1 [1] compliant document shall include:

an entry

```
<</ESIC
       <</BaseVersion /1.7
          /ExtensionLevel 1
        >>
    >>
```

to identify that a PDF document includes extensions as identified in clause 5.4; and:

an entry

```
<</ESIC
       <</BaseVersion /1.7
          /ExtensionLevel 2
        >>
    >>
```

to identify that a PDF document includes extensions as identified in clause 6.3, requirement l).

Both the above entries should be included in the extensions dictionary when a PDF document includes both the extensions identified in clause 5.4 and in clause 6.3, requirement l).

NOTE: As an alternative to the above entries, use of extensions as identified in clause 5.4 and in clause 6.3, requirement l) can also be identified by the following entry from Adobe® (defining equivalent extensions to the PDF document format):

```
<</ADBE
<</BaseVersion /1.7
  /ExtensionLevel 8
    >>
>>
```

5.6.2 ISO 32000-2 (PDF 2.0) Compliant Documents

For documents conforming to ISO 32000-2 [9], the Extensions dictionary shall not be used to declare PAdES extensions (such as /ESIC or /ADBE).

NOTE: Since Document Security Store (DSS), Validation Related Information (VRI), and Document Time-stamps (DocTimeStamp) are native, fully standardized components of the PDF 2.0 core specification, a conforming PDF 2.0 reader will automatically recognize and process these structures based on the PDF version header (e.g. %PDF-2.0) without requiring secondary developer extension entries.

5.6.3 Version conformance across document revisions

Through the use of incremental updates, a PDF document's version may be modified (e.g. from PDF 1.x to PDF 2.0) by updating the Version entry in the document's Catalog dictionary (ISO 32000-2 [9], clause 7.7.2). As a result, a single PDF file may contain multiple document revisions governed by different base PDF specifications.

Version-dependent conformance requirements for signatures, Document Security Store (DSS), Validation Related Information (VRI), and Document Time-stamps shall be evaluated strictly against the document revision in which they were created.

A conforming reader or validator shall not apply the conformance requirements of a later document revision's PDF version to signatures or elements created in an earlier document revision.

6 PAdES baseline signatures

6.1 Signature levels

Clause 6 defines four levels of PAdES baseline signatures, intended to facilitate interoperability and to encompass the life cycle of PAdES signature, namely:

a) B-B level provides requirements for the incorporation of signed and some unsigned attributes when the signature is generated.

b) B-T level provides requirements for the generation and inclusion, for an existing signature, of a trusted token proving that the signature itself actually existed at a certain date and time.

c) B-LT level provides requirements for the incorporation of all the material required for validating the signature in the signature document. This level aims to tackle the long term availability of the validation material.

d) B-LTA level provides requirements for the incorporation of electronic time-stamps that allow validation of the signature long time after its generation. This level aims to tackle the long term availability and integrity of the validation material.

NOTE 1: ETSI TR 119 100 [i.4] provides a description on the life-cycle of a signature and the rationales on which level is suitable in which situation.

NOTE 2: The levels c) to d) are appropriate where the technical validity of signature needs to be preserved for a period of time after signature creation where certificate expiration, revocation and/or algorithm obsolescence is of concern.

NOTE 3: B-LTA level targets long term availability and integrity of the validation material of digital signatures over long term. The B-LTA level can help to validate the signature beyond many events that limit its validity (for instance, the weakness of used cryptographic algorithms, or expiration of validation data). The use of B-LTA level is considered an appropriate preservation and transmission technique for signed data.

NOTE 4: Conformance to B-LT level, when combined with appropriate additional preservation techniques tackling the long term availability and integrity of the validation material is sufficient to allow validation of the signature long time after its generation. The assessment of the effectiveness of preservation techniques for signed data other than implementing the B-LTA level are out of the scope of the present document. The reader is advised to consider legal instruments in force and/or other standards (for example ETSI TS 119 511 [i.13]) that can indicate other preservation techniques.

e) When signed data is exchanged between parties the sender should use at least signatures conforming to a level that allows the relying parties to trust the signature at the time the exchange takes place.

NOTE 5: The architectural implementation of the levels described above (particularly B-LT and B-LTA) depends on the PDF version of the specific document revision in which the level is constructed. It relies on PDF extensions for document revisions based on ISO 32000-1 [1], and on native features for document revisions based on ISO 32000-2 [9], as specified in clause 5.4. As a result of incremental updates, these implementation methods may co-exist within the same PDF file.

6.2 General requirements for PAdES baseline signatures

6.2.1 Algorithm requirements

The algorithms and key lengths used to generate and augment digital signatures should be as specified in ETSI TS 119 312 [i.6].

NOTE 1: ISO 32000-1 [1] and ISO 32000-2 [9] impose additional requirements.

NOTE 2: Cryptographic suites recommendations defined in ETSI TS 119 312 [i.6] can be superseded by national recommendations.

In addition the MD5 algorithm shall not be used as digest algorithm.

Furthermore, for signatures and time-stamps conforming to ISO 32000-2 [9], the SHA-1 algorithm shall not be used for new signature generation and shall only be used for the verification of legacy documents.

6.2.2 Notation for requirements

The present clause describes the notation used for defining the requirements of the different PAdES signature levels.

The requirements on the attributes and certain signature fields for each PAdES signature level are expressed in Table 1. A row in the table either specifies requirements for an attribute, a signature field or a service.

A service can be provided by different attributes, by certain signature fields, or by other mechanisms (service provision options hereinafter). In these cases, the specification of the requirements for a service is provided by two or more rows. The first row contains the requirements of the service. The requirements for the attributes, certain signature fields, and/or mechanisms used to provide the service are stated in the following rows.

Table 1 contains 8 columns. Below follows a detailed explanation of their meanings and contents.

1) Column "Attributes/Fields/Services":

   a) In the case where the cell identifies a Service, the cell content starts with the keyword "Service:" followed by the name of the service.

   b) In the case where the attribute or signature field provides a service, this cell contains "SPO:" (for Service Provision Option), followed by the name of the attribute or signature field.

   c) Otherwise, this cell contains the name of the attribute or signature field.

2) Column "Presence in B-B level". This cell contains the specification of the presence of the attribute or signature field, or the provision of a service, for PAdES-B-B signatures.

3) Column "Presence in B-T level". This cell contains the specification of the presence of the attribute or signature field, or the provision of a service, for PAdES-B-T signatures.

4) Column "Presence in B-LT level". This cell contains the specification of the presence of the attribute or signature field, or the provision of a service, for PAdES-B-LT signatures.

5) Column "Presence in B-LTA level". This cell contains the specification of the presence of the attribute or signature field, or the provision of a service, for PAdES-B-LTA signatures.

6) Below follows the values that can appear in columns "Presence in B-B", "Presence in B-T", "Presence in B-LT", and "Presence in B-LTA":

   - "shall be present": means that the attribute or signature field shall be incorporated to the signature, and shall be as specified in the document referenced in column "References", further profiled with the additional requirements referenced in column "Requirements", and with the cardinality indicated in column "Cardinality".

   - "shall not be present": means that the attribute or signature field shall not be incorporated to the signature.

   - "may be present": means that the attribute or signature field may be incorporated to the signature, and shall be as specified in the document referenced in column "References", further profiled with the additional requirements referenced in column "Requirements", and with the cardinality indicated in column "Cardinality".

   - "shall be provided": means that the service identified in the first column of the row shall be provided as further specified in the SPO-related rows. This value only appears in rows that contain requirements for services. It does not appear in rows that contain requirements for attributes or signature fields.

   - "conditioned presence": means that the incorporation to the signature of the item identified in the first column is conditioned as per the requirement(s) specified in column "Requirements" and requirements referenced by column "References" with the cardinality indicated in column "Cardinality".

   - "*": means that the attribute or signature field (service) identified in the first column should not be present (provided) in the corresponding level. Upper signature levels may specify other requirements.

7) Column "Cardinality". This cell indicates the cardinality of the attribute or signature field. If the cardinality is the same for all the levels, only the values listed below appear. Otherwise the content specifies the cardinality for each level. See the example at the end of the present clause showing this situation. Below follows the values indicating the cardinality:

   - **0**: The signature shall not incorporate any instance of the attribute or signature field.

   - **1**: The signature shall incorporate exactly one instance of the attribute or signature field.

   - **0 or 1**: The signature shall incorporate zero or one instance of the attribute or signature field.

   - ≥ **0**: The signature shall incorporate zero or more instances of the attribute or signature field.

   - ≥ **1**: The signature shall incorporate one or more instances of the attribute or signature field.

8) Column "References". This cell contains either the number of the clause specifying the attribute or signature field in the present document, or a reference to the document and clause that specifies the attribute or signature field.

9) Column "Additional notes and requirements". This cell contains numbers referencing notes and/or letters referencing additional requirements on the attribute or signature field. Both notes and additional requirements are listed below the table.

EXAMPLE: In Table 1, the row corresponding to SPO: DSS signature field has a value "*" in the cells in columns "Presence in B-B level" and "Presence in B-T level", and "shall be present" in cells in columns "Presence in B-LT level" and "Presence in B-LTA level". The cell in column "Cardinality" indicates the cardinality for each level as follows: "B-B, B-T: ≥0" indicates that PAdES-B-B and PAdES-B-T signatures can incorporate zero or more instances of SPO: DSS signature field; "B-LT, B-LTA: ≥1" indicates that PAdES-B-LT and PAdES-B-LTA incorporates one or more instances of SPO: DSS signature field.

6.3 PAdES baseline signatures

This clause defines requirements on attributes, fields and services that PAdES baseline signatures have to fulfil. The attributes defined in ETSI EN 319 122-1 [2] and not listed in Table 1 shall not be present.

Table 1 shows the presence and cardinality requirements on the signature fields, attributes and services indicated in the first column for the four PAdES baseline signature levels, namely: PAdES-B-B, PAdES-B-T, PAdES-B-LT, and PAdES-B-LTA. Additional requirements are detailed below the table suitably labelled with the letter indicated in the last column.

NOTE: PAdES-B-B signatures that incorporate only the signature fields/attributes that are mandatory in Table 1, and that implement the mandatory requirements, contain the lowest number of signature fields/attributes, with the consequent benefits for interoperability.

Table 1: Requirements on the main attributes for PAdES baseline signatures

Attributes/Fields/Services	Presence in B-B level	Presence in B-T level	Presence in B-LT level	Presence in B-LTA level	Cardinality	References	Additional requirements and notes
SignedData.certificates	shall be present	shall be present	shall be present	shall be present	1	IETF RFC 5652 [3], clause 5.1	a), b) notes 1 and 2
content-type	shall be present	shall be present	shall be present	shall be present	1	ETSI EN 319 122-1 [2], clause 5.1.1	c)
message-digest	shall be present	shall be present	shall be present	shall be present	1	ETSI EN 319 122-1 [2], clause 5.1.2	-
signer-attributes-v2	may be present	may be present	may be present	may be present	0 or 1	ETSI EN 319 122-1 [2], clause 5.2.6	-
content-time-stamp	may be present	may be present	may be present	may be present	≥ 0	ETSI EN 319 122-1 [2], clause 5.2.8	-
signature-policy-identifier	may be present	may be present	may be present	may be present	0 or 1	ETSI EN 319 122-1 [2], clause 5.2.9	-
commitment-type-indication	conditioned presence	conditioned presence	conditioned presence	conditioned presence	0 or 1	ETSI EN 319 122-1 [2], clause 5.2.3	d)
SERVICE: protection of signing certificate	shall be provided	shall be provided	shall be provided	shall be provided	-	-	e), f)
SPO: ESS signing-certificate	conditioned presence	conditioned presence	conditioned presence	conditioned presence	0 or 1	ETSI EN 319 122-1 [2], clause 5.2.2.2	e), f)
SPO: ESS signing-certificate-v2	conditioned presence	conditioned presence	conditioned presence	conditioned presence	0 or 1	ETSI EN 319 122-1 [2], clause 5.2.2.3	e), f)
Service: provide claimed time of signing	shall be provided	shall be provided	shall be provided	shall be provided	-	-	-
SPO: entry with the key *M* in the Signature Dictionary	conditioned presence	conditioned presence	conditioned presence	conditioned presence	0 or 1	ISO 32000-2 [9], clause 12.8.1 or ISO 32000-2 [9], clause 12.8.1	g)
SPO: signing-time attribute in CMS signature	conditioned presence	conditioned presence	conditioned presence	conditioned presence	0 or 1	-	-
entry with key *Contents* in the Signature Dictionary	shall be present	shall be present	shall be present	shall be present	1	ISO 32000-2 [9], clause 12.8.1 or ISO 32000-2 [9], clause 12.8.1	h), i)
entry with key *Filter* in the Signature Dictionary	shall be present	shall be present	shall be present	shall be present	1	ISO 32000-2 [9], clause 12.8.1 or ISO 32000-2 [9], clause 12.8.1	j)
entry with key *ByteRange* in the Signature Dictionary	shall be present	shall be present	shall be present	shall be present	1	ISO 32000-2 [9], clause 12.8.1 or ISO 32000-2 [9], clause 12.8.1	k)

Attributes/Fields/Services	Presence in B-B level	Presence in B-T level	Presence in B-LT level	Presence in B-LTA level	Cardinality	References	Additional requirements and notes
entry with key *SubFilter* in the Signature Dictionary	shall be present	shall be present	shall be present	shall be present	1	ISO 32000-2 [9], clause 12.8.1 or ISO 32000-2 [9], clause 12.8.1	l)
entry with key *Location* in the Signature Dictionary	may be present	may be present	may be present	may be present	0 or 1	ISO 32000-2 [9], clause 12.8.1 or ISO 32000-2 [9], clause 12.8.1	z)
entry with key *Reason* in the Signature Dictionary	conditioned presence	conditioned presence	conditioned presence	conditioned presence	0 or 1	ISO 32000-2 [9], clause 12.8.1 or ISO 32000-2 [9], clause 12.8.1	m), z)
entry with key *Name* in the Signature Dictionary	may be present	may be present	may be present	may be present	0 or 1	ISO 32000-2 [9], clause 12.8.1 or ISO 32000-2 [9], clause 12.8.1	z)
entry with key *ContactInfo* in the Signature Dictionary	may be present	may be present	may be present	may be present	0 or 1	ISO 32000-2 [9], clause 12.8.1 or ISO 32000-2 [9], clause 12.8.1	-
entry with key *Cert* in the Signature Dictionary	shall not be present	shall not be present	shall not be present	shall not be present	0	ISO 32000-2 [9], clause 12.8.1 or ISO 32000-2 [9], clause 12.8.1	-
SERVICE: provide trusted time for existence of the signature	*	shall be provided	shall be provided	shall be provided	-	-	n)
SPO: signature-time-stamp	*	conditioned presence	conditioned presence	conditioned presence	≥ 0	ETSI EN 319 122-1 [2], clause 5.3	o), p), q)
SPO: document-time-stamp	*	conditioned presence	conditioned presence	conditioned presence	≥ 0	clause 5.4.3	
SERVICE: provide certificate and revocation values	*	*	shall be provided	shall be provided	-	-	-
SPO: DSS	*	*	shall be present	shall be present	B-B, -T: ≥ 0 B-LT, -LTA: ≥ 1	clause 5.4.2.2	r), s), t), u), v)
SPO: DSS/VRI	*	*	conditioned presence	conditioned presence	≥ 0	clause 5.4.2.3	v)
SERVICE: provide trusted time for existence of the validation data	*	*	*	shall be provided	-	-	note 3

Attributes/Fields/Services	Presence in B-B level	Presence in B-T level	Presence in B-LT level	Presence in B-LTA level	Cardinality	References	Additional requirements and notes
SPO: document-time-stamp	*	*	*	shall be present	B-B, -T, -LT: ≥ 0 B-LTA: ≥ 1	clause 5.4.3	w), x), y)

Additional requirements:

a) The generator shall include the signing certificate in the `SignedData.certificates` field.

b) In order to facilitate path building, generators should include in the `SignedData.certificates` field all certificates not available to verifiers that can be used during path building. When the signature is to be validated through a Trusted List as specified in ETSI TS 119 612 [i.10], the generator should include all intermediary certificates forming a chain between the signer certificate and a CA present in the Trusted List, which are not available to verifiers.

NOTE 1: A certificate is considered available to the verifier if reliable information about its location is known and allows automated retrieval of the certificate (for instance through an Authority Info Access Extension or equivalent information present in a TSL).

NOTE 2: In the general case, different verifiers can have different trust parameters and can validate the signer certificate through different chains. Therefore, generators may not know which certificates will be relevant for path building. However, in practice, generators can often clearly identify such certificates. In this case, including them in the signature is a good practice, unless verifiers can automatically retrieve them.

c) The `content-type` attribute shall have value `id-data`.

d) The `commitment-type-indication` attribute may be incorporated in the CMS signature only if the entry with the key *Reason* is not used. Otherwise the `commitment-type-indication` shall not be incorporated in the CMS signature.

e) Generators shall use either the signing certificate or the signing-certificate v2 attribute, depending on the hash function, in accordance with ETSI EN 319 122-1 [2].

NOTE 3: ETSI TS 119 312 [i.6] effectively requires the use of signing-certificate-v2 for new signatures.

f) Generators should use ESS signing-certificate v2 in preference to ESS signing-certificate in line with the guidance given in ETSI TS 119 312 [i.6].

g) At least one of the `M` entry and the CMS `signing-time` attribute shall be present. The `M` entry should be present. If the document revision signed by the signature conforms to ISO 32000-2 [9] and the `M` entry is present, the CMS `signing-time` attribute shall not be present. If the document revision signed by the signature conforms to ISO 32000-1 [1], the CMS `signing-time` attribute should not be present; if both the `M` entry and the CMS `signing-time` attribute are present, their values shall specify the same date and time.

h) The Content key shall contain a DER-encoded `SignedData` object as specified in CMS (IETF RFC 5652 [3]) as the PDF signature. This CMS object forms a CAdES signature described in ETSI EN 319 122-1 [2].

i) Requirements specified in ISO 32000-2 [9], clauses 12.8.3.2 (PKCS#1) and 12.8.3.3 (PKCS#7) and ISO 32000-2 [9], clauses 12.8.3.2 and 12.8.3.3 (CMS) shall not be used.

j) A verifier may substitute a different signature handler, other than that specified in Filter, when verifying the signature, as long as it supports the specified SubFilter format.

k) The `ByteRange` shall cover the entire document revision being signed, including the Signature Dictionary but excluding the PDF Signature itself (the entry with key *Contents*). There shall be no unmapped bytes or gaps within the signed document revision, outside the defined `ByteRange`.

l) The Signature Dictionary shall contain a value of **ETSI.CAdES.detached** for the key SubFilter.

m) The entry with the key *Reason* shall not be used when the `commitment-type-indication` attribute is present in the CMS signature. The entry with the key *Reason* shall not be used if the `signature-policy-identifier` attribute is present in the CMS signature.

n) The trusted time shall be provided either by a `signature-time-stamp` attribute or a `document-time-stamp`.

o) The generator shall use DER encoding for any `signature-time-stamp` attribute.

p) A PAdES-B-T signature may contain several `signature-time-stamp` or `document-time-stamp` attributes.

q) If it is anticipated to propagate PAdES-B-B signatures to a higher conformance level, they can reserve space for the signature-time-stamp attribute that will be added to the DER-encoded SignedData object as specified in ETSI EN 319 122-1 [2]. Alternatively a document-time-stamp, which covers the whole document including the signature value, can serve this purpose.

r) In situations different than those ones identified in the present clause requirements a) and b), applications should include certificate values within the DSS. The full set of certificates, including the trust anchor when it is available in the form of a certificate, that have been used to validate the signature and which are not already present shall be included. This set includes certificates required for validating the signing certificate, for validating any attribute certificate present in the signature, and for validating any time-stamp token's signing certificate (i.e. a TSA certificate) already incorporated to the signature.

s) Duplication of certificate values within the signature should be avoided.

t) The full set of revocation data (CRL or OCSP responses) that have been used in the validation of the signer and CA certificates used in signature shall be included. This set includes all certificate status information required for validating the signing certificate, for validating any attribute certificate present in the signature, and for validating any time-stamp token's signing certificate (i.e. a TSA certificate) already incorporated to the signature.

u) The DER encoding shall be used for the certificate-values and the revocation-values.

v) For ISO 32000-1 [1] extensions, the VRI dictionary should not be used. The inclusion of VRI dictionary entries is optional. All validation material referenced in VRI entries is also referenced in DSS entries. For ISO 32000-2 [9] native implementations, the VRI dictionary may be populated to strictly bind validation material to specific signatures and optimize the validation process.

w) PAdES-B-LTA signatures may have more than one `document-time-stamp` applied after the `DSS` and `DSS/VRI`.

x) Before generating and incorporating a `document-time-stamp` attribute, applications shall include all the validation material, which are not already in the signature, required for validating the signature. This validation material includes all the certificates and all certificate status information (like CRLs or OCSP responses) required for:

- validating the signing certificate;
- validating any attribute certificate present in the signature; and
- validating any time-stamp token's signing certificate (i.e. a TSA certificate) already incorporated to the signature (including, of course, any previous `document-time-stamp`).

This validation material should be incorporated within `DSS`.

y) The value of `SubFilter` shall be **ETSI.RFC3161**.

z) For document revision conforming to ISO 32000-2 [9], the Signature Dictionary keys `Name`, `Location`, `Reason` have conditions to use:
`Name` - This value should be used only when it is not possible to extract the name from the signature.
`Location` - To prevent data redundancy and synchronization conflicts during validation, this key shall not be used if equivalent information is present within the CMS signed attributes of the signature: `signer-location`.
`Reason` - To prevent data redundancy and synchronization conflicts during validation, this key shall not be used if equivalent information is present within the CMS signed attributes of the signature: `commitment-type-indication`.

NOTE 4: A PAdES-B-LTA signature helps to validate the signature beyond any event that would otherwise limit its validity.

6.4 Legacy PAdES baseline signatures

When new unsigned elements (CAdES attributes or PDF dictionary entries) are incorporated to legacy PAdES baseline signatures, these elements shall comply with the present document.

Annex A (informative): Change history

Date	Version	Information about changes
April 2016	V1.1.1	Publication
October 2023	V1.2.0	Below is a non-exhaustive list of the changes carried out since V1.1.1: • Clarify usage of OCSPResponse ASN.1 type in DSS dictionary OCSPs entry. • Updated link to ISO 32000-1 specifications in the Normative references clause.
March 2026	V1.2.2	• Dual support for ISO 32000-1 (PDF 1.7) and ISO 32000-2 (PDF 2.0) with enhanced cryptographic requirements.

History

Version	Date	Status
V1.0.1	July 2015	Publication of ETSI TS 119 142-1 (Withdrawn)
V1.1.1	April 2016	Publication
V1.2.1	January 2024	Publication
V1.3.0	August 2026	ENAP Process AP 20261109: 2026-08-17 to 2026-11-09