API Document

Headers | 9 hidden

	Key	Value
☑	Content-Type	multipart/form-data
☑	Accept	application/json
	Key	Value

Fetch Operation

get http://127.0.0.1:8000/api/cars/


```json
[
    {
        "name": "Sunil",
        "type": "3000",
        "location": "Hyderabad",
        "price": "5000.00",
        "image": "portfolio-01-580x610.jpg"
    },
    {
        "name": "ABCD",
        "type": "Innova",
        "location": "KPHB",
        "price": "7000.00",
        "image": "portfolio-02-584x760.jpg"
```

Get Operation

get http://127.0.0.1:8000/api/cars/1


```json
{
    "name": "Sunil",
    "type": "3000",
    "location": "Hyderabad",
    "price": "5000.00",
    "image": "portfolio-01-580x610.jpg"
}
```

Insert Operation

Post http://127.0.0.1:8000/api/cars/

Update Operation

Post-->http://127.0.0.1:8000/api/cars/2

Delete Operation

delete--> http://127.0.0.1:8000/api/cars/4

http://127.0.0.1:8000/api/cars/4

Save

DELETE   http://127.0.0.1:8000/api/cars/4   Send

Docs   Params   Authorization   Headers (11)   Body •   Scripts   Settings   Cookies

○ none   ● form-data   ○ x-www-form-urlencoded   ○ raw   ○ binary   ○ GraphQL

☑	type	Text ∨	Benz	
☑	email	Text ∨	benz@gmail.com	
☑	location	Text ∨	kp	
☑	slot	Text ∨	23-11-2025 11:00	
☑	price	Text ∨	7000	
☑	image	File ∨	col-bgimage-12.png	
	Key	Text ∨	Value	Description

Body   Cookies (2)   Headers (7)   Test Results   ⟳   200 OK • 2.61 s • 273 B • ⊕ •••

{} JSON ∨   ▷ Preview   ⧉ Visualize ∨

```
1   {
2       "status": true,
3       "message": "Car deleted successfully"
4   }
```