# NIST Special Database 19 Handprinted Forms and Characters 2<sup>nd</sup> Edition

Patrick Grother Kayee Hanaoka



# NIST Special Database 19 Handprinted Forms and Characters 2<sup>nd</sup> Edition

Patrick Grother Kayee Hanaoka Information Technology Laboratory Information Access Division

August 2016



U.S. Department of Commerce Penny Pritzker, Secretary

National Institute of Standards and Technology Willie May, Under Secretary of Commerce for Standards and Technology and Director

# Table of Contents

1	Introduction		2
	1.1	Source Materials	2
		About 2 <sup>nd</sup> Edition	
2	Da	Oata Hierarchies	4
	2.1 /	4	
		<i>by_write</i> – By Author	
	2.3 by_field – By Field Type		
	2.4 by_class – By Hexadecimal Class		
	2.5 <i>l</i>	by_merge – By Merged Class	8
3	Re	eference	10

## NIST Special Database 19 Handprinted Forms and Characters Database

#### 1 Introduction

The updated web released NIST Special Database 19 (SD19) consist of 5 zipped files with a total of 3992357 Portable Network Graphics (PNG) [1] converted images. The original CD-ROM Special Database 19 was released in 1995. The original SD 19 contains the full page binary images of 3669 Handwriting Sample Forms (HSFs) and 814 255 segmented handprinted digit and alphabetic characters from those forms. Those segmented characters each occupy 128x128 pixel per raster and are labelled by one of 62 ASCII hexadecimal classes corresponding to "0"- "9", "A"- "Z" and "a"- "z" [3]. The segmented characters images are included in multiple organizations suited to different recognition applications. The characters are given by writer, by class, by caseless class, and by field origin.

#### 1.1 Source Materials


The SD 19 contains eight series of HSF images, denoted by *hsf\_{0,1,2,3,4,6,7,8}*. Characters segmented from all field types are included in this database. In 1<sup>st</sup> Edition, all images are binary and are stored in NIST's IHEAD format.

The publication statuses of the various writer partitions and field types are given in the Table 1. The partition of  $hsf_4$  were completed by the Bethesda high school students, and all those of partitions  $hsf_{\{0,1,2,3,6,7,8\}}$  were obtained from Census Bureau employees in Suitland, Maryland.

partition	writers	writer origin
hsf_0	0000-0499	Census Field
hsf_1	0500-0999	Census Field
hsf_2	1000-1499	Census Field
hsf_3	1500-2099	Census Field
hsf_4	2100-2599	High School
hsf_6	3100-3599	Census Field
hsf_7	3600-4099	Census Field
hsf_8	4100-4169	Census Field

Table 1: Break down of the partitions with the writer numbers.

#### HANDWRITING SAMPLE FORM



Please print the following text in the box below:

We, the People of the United States, in order to form a more perfect Union, establish Justice, insure domestic Tranquility, provide for the common Defense, promote the general Welfare, and secure the Blessings of Liberty to ourselves and our posterity, do ordain and establish this CONSTITUTION for the United States of America.

We, the people of the United States, In order to form a more perfect Union, establish Justice, insure domestic Tranquility, provide for the common Defense, promote the general Walfare, and secure the Blessings of Liberty to ourselves and our posterity, do ordain and setablish this parent TITIANI for the establish this CONSTITUTION For the United States of America.

Figure 1: Example HSF Image. This is the file hsf page/hsf 0/f0002 01.pct. Notice that the first field on this form, the name field, has been intentionally occluded, on some others it remains blank. All fields except those on the first line have been segmented and recognized by NIST.

#### 1.2 About 2<sup>nd</sup> Edition

The 2<sup>nd</sup> Edition of Special Database 19 converted all binary images in the 1<sup>st</sup> Edition dataset to PNG format images. The 2<sup>nd</sup> Edition SD19 data hierarchies are very similar to the 1<sup>st</sup> Edition which is describes in *Section 2*. The organization of the PNG images are consistent with the *mis* files where the original binary images originated. Each *mis* file (*Section 2*) is converted into multiple PNG images because the *mis* files consist of more than one segmented digit and/or alphabetic character per binary image. All PNG images are located in the directory that is named after the *mis* file from which the PNG images were converted. The *mis* file name is also the front naming of the PNG file followed by an underscore and a number, and the numbering of the files begins with 00000. For example, d0000\_14\_mis contains 235 characters images in binary format. 235 individual PNG files get converted from d0000\_14\_mis with filenames from d0000\_14\_00000.png to d0000\_14\_00234.png.

#### 2 Data Hierarchies

There are five directories in the *data* subtree. The first *hsf\_page* contains images of the full page HSF form. The other four directories, *by\_\**, each have alternative organizations of the segmented character images suited to different recognition applications. The characters are given by writer, by class, by field origin, and finally, and finally by caseless class.

These are the definitions of the file extensions correspond to particular files in 1<sup>st</sup> Edition.

.mis – a file containing binary format of multiple isolated character images.

.pct – a file containing a full page HSF IHEAD formatted image file.

.*cls* – a file containing the checked classes of the images held in the accompanying .*mis* file.

#### 2.1 hsf page – Full HSF Page Images

The 2<sup>nd</sup> Edition SD19 *hsf\_page* contains all PNG images of the HSF forms in the *hsf\_{0,1,2,3,4,6,7,8}* directories. They were converted from the *.pct* format of the HSF forms (Figure 1) in 1<sup>st</sup> Edition. The file hierarchies for 1<sup>st</sup> and 2<sup>nd</sup> Edition are very similar (Figure 2) except the *truerefs* directory holds the text reference files, and the *template* directory contains postscript (*.ps*) and LaTeX files (*.tex*) for the unfilled HSF forms are not included in the 2<sup>nd</sup> Edition. User can download the 1<sup>st</sup> Edition zip file to access that data.




Figure 2: 1st and 2nd Edition SD 19 file hierarchies for hsf page

### 2.2 by\_write - By Author

by\_write contains the segmented characters organized by hsf\_? partition then by writer. This organization is generally not particularly useful for OCR studies since the image files contain multiple classes. The files are, however, the primary output of the segmentation and checking process, and the other hierarchies that follow were derived from it.

Each writer directory contains files for each field type; digit, upper, lower and, constitution alphas. The 2<sup>nd</sup> Edition SD 19 contains all PNG images of individual characters that were converted from the .mis files in 1<sup>st</sup> Edition. Each .mis file in 1<sup>st</sup> Edition contains multiple characters images in binary format, for example, the u0000\_14.mis file in f0000\_14 directory, contains all uppercase alphabetic character images in binary format written by writer f0000\_14. The file hierarchies for 1<sup>st</sup> and 2<sup>nd</sup> Edition are given below (Figure 3).




Figure 3: Ist and 2nd Edition SD 19 file hierarchies for by\_write partition

#### 2.3 by field – By Field Type

by\_field contains characters organized by hsf\_? then partitioned by field type, and finally by class. Writer information is discarded though the files' entries are included by concatenation of the writer characters from the by\_write tree. The digit directory contained images from all digit fields from the form. The upper and lower directories contained images from the uppercase field and the lowercase field. The const directory contained all images of the characters from the constitution box.(Figure 1) All images in the digit/upper/lower/const directories are partitioned by the ASCII hexadecimal classes. The file hierarchies in 1st and 2nd Edition are very similar. The 2nd Edition SD 19 contains all PNG images of individual characters that were converted from the .mis files in 1st Edition. Each .mis file in 1st Edition contains multiple images in binary format of the same digit or alphabetic characters by field type. The file hierarchies for 1st Edition and 2nd Edition SD19 are given below. (Figure 4)




Figure 4: 1st and 2nd Edition SD 19 file hierarchies for by field partition.

#### 2.4 by class – By Hexadecimal Class

by\_class contains images organized by class, then by database. Both writer and field information are discarded: there is no distinction between an "e" from the constitution box of writer 0000 and one from the lower case field of writer 4044. In the directory structures that follow the second layer directories have labels which are the hexadecimal ASCII representations of the textual class labels.

The *train\_30* files contains the "0"s of all writers of partitions *hsf\_{0,1,2,3,6,7}*. The *train\_??* files comprise the suggested training set for OCR studies. The *hsf\_4* is likewise earmarked as a standard testing results reporting set. Note that the class files are redundant in this tree, since they contain only one unique hexadecimal class string, and the class has already been indicated in the parent directory name. The 2<sup>nd</sup> Edition SD 19 contains all PNG

images of individual characters that were converted from the .mis files in 1st Edition. Each .mis file in 1st Edition contains multiples images in binary format of the same digit or alphabetic characters by partition. The file hierarchies for 1st Edition and 2nd Edition SD29 are given below. (Figure 5)




Figure 5: 1st and 2nd Edition SD 19 file hierarchies for by\_class partition.

#### 2.5 by merge – By Merged Class

The class abundancies show up to an order of magnitude disparity between classes. This situation may be ameliorated for certain applications by folding the upper and lower case letters of some classes into one another; for instance, an upper case "W" is largely equivalent for recognition purposes to its lower case analogue "w". Indeed, it could be argued that a classifier could equally be trained to recognize classes of different appearance, "A" and "a" for example, on the basis that, although examples of the two classes may form separate clusters in a representative feature space, some classifiers will still perform well. For this hierarchy the upper and lower case examples of the following thirteen classes have been merged:

#### CIJKLMOPSUVWXYZ

The resulting tree hierarchy contains exact replicas of the files of the unmerged classes from the  $by\_class$  tree, and the merged classes labelled by the hexadecimal codes of the upper and lower case labels delimited by a period. The final number of classes is 37. The  $2^{nd}$  Edition SD 19 contains all PNG images of individual characters that were converted from the .mis files in  $1^{st}$  Edition. Each .mis file in  $1^{st}$  Edition contains multiples characters images in binary format. The file hierarchies for  $1^{st}$  Edition and  $2^{nd}$  Edition SD29 are given below.(Figure 6)




Figure 6:  $1^{st}$  and  $2^{nd}$  Edition SD 19 file hierarchies for by\_merge partition.

### 3 Reference

- [1] "Information technology Computer graphics and image processing Portable Network Graphics (PNG): Functional specification", International Organization for Standardization/International Electrotechnical Commission, ISO/IEC 15948:2004
- [2] Patrick J. Grother. NIST Special Database 19 Handprinted Forms and Characters Databas 1<sup>st</sup> Edition User's Guide, National Institute of Standards and Technology, March 1995
- [3] "ASCII Table and Description", www.asciitable.com