

Introduction to Data Pipelines

CLEANING DATA WITH APACHE SPARK IN PYTHON



Mike Metzger
Data Engineering Consultant

What is a data pipeline?

- A set of steps to process data from source(s) to final output
- Can consist of any number of steps or components
- Can span many systems
- We will focus on data pipelines within Spark

What does a data pipeline look like?

- Input(s)
 - CSV, JSON, web services, databases
- Transformations
 - `withColumn()` , `.filter()` , `.drop()`
- Output(s)
 - CSV, Parquet, database
- Validation
- Analysis

Pipeline details

- Not formally defined in Spark
- Typically all normal Spark code required for task

```
schema = StructType([
    StructField('name', StringType(), False),
    StructField('age', StringType(), False)
])
df = spark.read.format('csv').load('datafile').schema(schema)
df = df.withColumn('id', monotonically_increasing_id())
...
df.write.parquet('outdata.parquet')
df.write.json('outdata.json')
```

Let's Practice!

CLEANING DATA WITH APACHE SPARK IN PYTHON

Data handling techniques

CLEANING DATA WITH APACHE SPARK IN PYTHON



Mike Metzger
Data Engineering Consultant

What are we trying to parse?

- Incorrect data
 - Empty rows
 - Commented lines
 - Headers
- Nested structures
 - Multiple delimiters
- Non-regular data
 - Differing numbers of columns per row
- Focused on CSV data

```
width, height, image
```

```
# This is a comment
```

```
200      300      affenpinscher;0
```

```
600      450      Collie;307      Collie;101
600      449      Japanese_spaniel;23
```

Stanford ImageNet annotations

- Identifies dog breeds in images
- Provides list of all identified dogs in image
- Other metadata (base folder, image size, etc.)

Example rows:

```
02111277      n02111277_3206      500      375      Newfoundland,110,73,416,298
02108422      n02108422_4375      500      375      bull_mastiff,101,90,214,356 \
bull_mastiff,282,74,416,370
```


Removing blank lines, headers, and comments

Spark's CSV parser:

- Automatically removes blank lines
- Can remove comments using an optional argument

```
df1 = spark.read.csv('datafile.csv.gz', comment='#')
```

- Handles header fields
 - Defined via argument
 - Ignored if a schema is defined

```
df1 = spark.read.csv('datafile.csv.gz', header=True)
```

Automatic column creation

Spark will:

- Automatically create columns in a DataFrame based on `sep` argument

```
df1 = spark.read.csv('datafile.csv.gz', sep=',')
```

- Defaults to using `,`
- Can still successfully parse if `sep` is not in string

```
df1 = spark.read.csv('datafile.csv.gz', sep='*')
```

- Stores data in column defaulting to `_c0`
- Allows you to properly handle nested separators

Let's practice!

CLEANING DATA WITH APACHE SPARK IN PYTHON

Data validation

CLEANING DATA WITH APACHE SPARK IN PYTHON



Mike Metzger
Data Engineering Consultant

Definition

Validation is:

- Verifying that a dataset complies with the expected format
- Number of rows / columns
- Data types
- Complex validation rules

Validating via joins

- Compares data against known values
- Easy to find data in a given set
- Comparatively fast

```
parsed_df = spark.read.parquet('parsed_data.parquet')
company_df = spark.read.parquet('companies.parquet')
verified_df = parsed_df.join(company_df, parsed_df.company == company_df.company)
```

This *automatically* removes any rows with a company not in the `valid_df` !

Complex rule validation

Using Spark components to validate logic:

- Calculations
- Verifying against external source
- Likely uses a UDF to modify / verify the DataFrame

Let's practice!

CLEANING DATA WITH APACHE SPARK IN PYTHON

Final analysis and delivery

CLEANING DATA WITH APACHE SPARK IN PYTHON



Mike Metzger
Data Engineering Consultant

Analysis calculations (UDF)

Calculations using UDF

```
def getAvgSale(saleslist):  
    totalsales = 0  
    count = 0  
    for sale in saleslist:  
        totalsales += sale[2] + sale[3]  
        count += 2  
    return totalsales / count  
  
udfGetAvgSale = udf(getAvgSale, DoubleType())  
df = df.withColumn('avg_sale', udfGetAvgSale(df.sales_list))
```

Analysis calculations (inline)

Inline calculations

```
df = df.read.csv('datafile')  
  
df = df.withColumn('avg', (df.total_sales / df.sales_count))  
  
df = df.withColumn('sq_ft', df.width * df.length)  
  
df = df.withColumn('total_avg_size', udfComputeTotal(df.entries) / df.numEntries)
```

Let's practice!

CLEANING DATA WITH APACHE SPARK IN PYTHON

Congratulations and next steps

CLEANING DATA WITH APACHE SPARK IN PYTHON



Mike Metzger
Data Engineering Consultant

Next Steps

- Review Spark documentation
- Try working with data on actual clusters
- Work with various datasets

Thank you!

CLEANING DATA WITH APACHE SPARK IN PYTHON