

Aim:

To use different JUnit assertions to validate the expected results of test cases.

Scenario:

To use different assertions in JUnit to validate your test results.

Solution code:

```
import static org.junit.jupiter.api.Assertions.*;
import org.junit.jupiter.api.Test;
public class AssertionsTest {
    @Test
    void testAssertions() {

        // Assert equals
        assertEquals(5, 2 + 3);

        // Assert true
        assertTrue(5 > 3);

        // Assert false
        assertFalse(5 < 3);

        // Assert null
        assertNull(null);

        // Assert not null
        assertNotNull(new Object());
    }
}
```

Explanation

- assertEquals(expected, actual) checks whether the expected value is equal to the actual value.
- assertTrue(condition) verifies that the specified condition is true.
- assertFalse(condition) verifies that the specified condition is false.
- assertNull(object) checks whether the object reference is null.
- assertNotNull(object) checks whether the object reference is not null.

```
[INFO] -----
[INFO] T E S T S
[INFO] -----
[INFO] Running AssertionsTest
[INFO] Tests run: 1, Failures: 0, Errors: 0, Skipped: 0, Time elapsed: 0.081 s -- in AssertionsTest
[INFO] Results:
[INFO] Tests run: 1, Failures: 0, Errors: 0, Skipped: 0
[INFO] -----
[INFO] BUILD SUCCESS
[INFO] -----
[INFO] Total time: 6.608 s
[INFO] Finished at: 2026-06-16T18:42:38+05:30
[INFO] -----
PS C:\Users\Lenovo\OneDrive\Desktop\e3>
```

