

EXERCISE – 9

Question

Execute and display the results for the following Nmap Timing and Performance commands in Kali Linux Operating System:

1. Polite IDS Evasion
2. Normal IDS Evasion

Aim

To execute and display the results of Nmap timing and performance commands for polite and normal IDS evasion in Kali Linux.

1. POLITE IDS EVASION

Command:

```
nmap -T2 127.0.0.1
```

Use:

The -T2 option performs the Nmap scan at a slower and more polite speed to reduce network traffic and avoid affecting the target.

```
(pranathi@kali)-[~]  
$ nmap -T2 127.0.0.1  
Starting Nmap 7.99 ( https://nmap.org ) at 2026-  
10-07 08:46 +0530  
Nmap scan report for localhost (127.0.0.1)  
Host is up (0.000052s latency).  
All 1000 scanned ports on localhost (127.0.0.1)  
are in ignored states.  
Not shown: 1000 closed tcp ports (reset)  
  
Nmap done: 1 IP address (1 host up) scanned in 4  
06.66 seconds
```

2. NORMAL IDS EVASION

Command:

```
nmap -T3 127.0.0.1
```

Use:

The -T3 option performs the Nmap scan at the normal/default timing speed.

```
(pranathi@kali)-[~]  
$ nmap -T3 127.0.0.1  
Starting Nmap 7.99 ( https://nmap.org ) at 2026-  
10-07 08:55 +0530  
Nmap scan report for localhost (127.0.0.1)  
Host is up (0.0000010s latency).  
All 1000 scanned ports on localhost (127.0.0.1)  
are in ignored states.  
Not shown: 1000 closed tcp ports (reset)  
  
Nmap done: 1 IP address (1 host up) scanned in 0  
.05 seconds
```

Result

Thus, the Nmap timing and performance commands for polite and normal IDS evasion were successfully executed in Kali Linux and their results were displayed.