

Prayas at EmoInt 2017: An Ensemble of Deep Neural Architectures for Emotion Intensity Prediction in Tweets

Pranav Goel, Devang Kulshreshta, Prayas Jain, K.K Shukla

Department of Computer Science and Engineering
Indian Institute of Technology (BHU)
Varanasi, India-221005
Email: prayas.jain.cse14@iitbhu.ac.in

Friday 8th September, 2017

Outline

Prayas at
EmoInt 2017:
An Ensemble
of Deep
Neural
Architectures
for Emotion
Intensity
Prediction in
Tweets

Outline

Introduction -
EmoInt
Shared Task

Dataset

Proposed
System

Results

Future Work

1 Introduction - EmoInt Shared Task

2 Dataset

3 Proposed System

4 Results

5 Future Work

Introduction - EmoInt Shared Task

Prayas at
EmoInt 2017:
An Ensemble
of Deep
Neural
Architectures
for Emotion
Intensity
Prediction in
Tweets

Outline

Introduction -
EmoInt
Shared Task

Dataset

Proposed
System

Results

Future Work

- **Problem Statement** - Given a tweet which conveys an emotion E , what is the intensity of E ?
- Intensity is a real value ranging from 0 to 1 with 1 being the strongest intensity and 0 being the weakest intensity
- Fixed Set of Emotions - Anger, Fear, Joy, Sadness
- **Example** - *'I hate my lawn mower. If it had a soul, I'd condemn it to the fiery pits of Hell.'* has an intensity of 0.833 for the emotion Anger
- **Motivation** - Complement existing sentiment analysis systems with degree of sentiment. Useful for E-Commerce Companies.

Dataset

Prayas at
EmoInt 2017:
An Ensemble
of Deep
Neural
Architectures
for Emotion
Intensity
Prediction in
Tweets

Outline

Introduction -
EmoInt
Shared Task

Dataset

Proposed
System

Results

Future Work

| Emotion | Train | Dev | Test | All |
|------------|-------|-----|------|------|
| Anger | 857 | 84 | 760 | 1701 |
| Fear | 1147 | 110 | 995 | 2252 |
| Joy | 823 | 74 | 714 | 1611 |
| Sadness | 786 | 74 | 673 | 1533 |
| All | 3613 | 342 | 3142 | 7097 |

Proposed System

Prayas at
EmoInt 2017:
An Ensemble
of Deep
Neural
Architectures
for Emotion
Intensity
Prediction in
Tweets

Outline

Introduction -
EmoInt
Shared Task

Dataset

Proposed
System

Results

Future Work

Our system is an ensemble of three sets of approaches.

- Feed Forward Neural Networks
- MultiTask Deep Learning
- Sequence Modelling using CNN and LSTM

Feed Forward Neural Network

Prayas at
EmoInt 2017:
An Ensemble
of Deep
Neural
Architectures
for Emotion
Intensity
Prediction in
Tweets

Outline

Introduction -
EmoInt
Shared Task

Dataset

Proposed
System

Results

Future Work

- Convert each tweet to a 443 dimensional vector by using *Word2Vec* (400 dimensional vector) and *TweetToLexiconFeatureVector* (43 dimensional vector) and concatenating the results
- **Architecture** - A four hidden layer neural network with dropout after the first layer. *ReLU* activation function is used.
- **Training** - Minimize negative pearson correlation using Adam algorithm with mini-batches of size 8 and training epochs 30.

Feed Forward Neural Network

Prayas at
EmoInt 2017:
An Ensemble
of Deep
Neural
Architectures
for Emotion
Intensity
Prediction in
Tweets

Outline


Introduction -
EmoInt
Shared Task

Dataset

Proposed
System

Results

Future Work



MultiTask Deep Learning

Prayas at
EmoInt 2017:
An Ensemble
of Deep
Neural
Architectures
for Emotion
Intensity
Prediction in
Tweets

Outline

Introduction -
EmoInt
Shared Task

Dataset

Proposed
System


Results

Future Work

- The tweet is converted to 443 dimensional input vector like in Feed Forward NN (Approach 1)
- We consider predicting the intensity of the different emotions as different sub-tasks.
- **Architecture** - We again use a four hidden layer NN like Approach 1. The network's initial layers (layer 1 and 2) are shared among various sub-tasks, whereas layer 3 and layer 4 are learnt independently.
- Layer 1 & 2 learn task general features, whereas Layer 3 & 4 learn sub-task specific features.
- **Training** - We use same cost function, optimization algorithm, number of epochs etc as that in Approach 1. We iterate on the emotions in a cyclic order.

MultiTask Deep Learning

Prayas at
EmoInt 2017:
An Ensemble
of Deep
Neural
Architectures
for Emotion
Intensity
Prediction in
Tweets



Sequence Labelling using CNN & LSTM

Prayas at
EmoInt 2017:
An Ensemble
of Deep
Neural
Architectures
for Emotion
Intensity
Prediction in
Tweets

Outline

Introduction -
EmoInt
Shared Task

Dataset

Proposed
System

Results

Future Work

- The tweet is converted to a (50,400) dimensional input vector using Word2Vec. We concatenate the vectors of each words, and zero pad them to get a constant size of (50,400).
- **Architecture** - The input is first fed to a CNN or LSTM. These models give a sequential output. We can either feed this sequential output to another CNN/LSTM or pool the vectors to form a single 400 dimensional vector which can be fed to fully connected layers. The number of fully connected layers to use or whether to stack LSTMs/CNNs or not is decided based on cross validation results. Finally, a neuron with sigmoid activation gives the intensity.
- **Training** - We optimize the mean absolute error using Adam algorithm with batch size 8 and 15 training epochs.

Sequence Labelling using CNN & LSTM -2

Prayas at
EmoInt 2017:
An Ensemble
of Deep
Neural
Architectures
for Emotion
Intensity
Prediction in
Tweets

Outline


Introduction -
EmoInt
Shared Task

Dataset

Proposed
System

Results

Future Work



Sequence Labelling using CNN & LSTM -3

Prayas at
EmoInt 2017:
An Ensemble
of Deep
Neural
Architectures
for Emotion
Intensity
Prediction in
Tweets

Outline

Introduction -
EmoInt
Shared Task

Dataset

Proposed
System

Results

Future Work

- **The variations we tried** - Layers, max pooling versus average pooling for CNNs, LSTM vs Bi-LSTM vs GRU vs RNN, number of neurons, and dropout value. The best three architectures based on cross validation results are reported.

| Parameter/ Emotion | L1 | p | L2 | L3 |
|-----------------------|------------------|----|------------------|-----|
| Anger (1) | CNN (250,Max) | 0 | 125 | 50 |
| Anger (2) | CNN (256,Avg) | 0 | 100 | - |
| Anger (3) | LSTM (300) | 0 | CNN (200,Avg) | 100 |
| Fear (1) | LSTM (256) | .2 | CNN (150,Avg) | 100 |
| Fear (2) | CNN (250,Max) | 0 | 125 | 50 |
| Fear (3) | LSTM (250) | .2 | CNN (120,Avg) | 50 |
| Joy (1) | CNN (256,Max) | 0 | 100 | - |
| Joy (2) | LSTM (300) | 0 | CNN (200,Avg) | 100 |
| Joy (3) | LSTM (300) | .2 | CNN (200,Avg) | 100 |
| Sadness(1) | CNN (250,Max) | 0 | 125 | 50 |
| Sadness(2) | CNN (250,Max) | .2 | 125 | 50 |
| Sadness(3) | CNN (256,Max) | 0 | 100 | - |

Table: Network Parameters for Approach 3

Ensembling the Models

Prayas at
EmoInt 2017:
An Ensemble
of Deep
Neural
Architectures
for Emotion
Intensity
Prediction in
Tweets

Outline

Introduction -
EmoInt
Shared Task

Dataset

Proposed
System

Results

Future Work

- We combine 5 models (1 each from approach 1 & 2 and 3 from Approach 3) for each emotion.
- The final prediction is a weighted average of all the 5 models
- The weights are 1 for Approach 1, 3 for Approach 2, 3 each for top 2 systems from Approach 3, and 2 for the last system from Approach 3.
- Ensembling improved the performance by 2% over individual models.

Results

Prayas at
EmoInt 2017:
An Ensemble
of Deep
Neural
Architectures
for Emotion
Intensity
Prediction in
Tweets

Outline

Introduction -
EmoInt
Shared Task

Dataset

Proposed
System

Results

Future Work

Our submitted ensemble model achieves an average (or overall) score of 75.26% and 74.70%, which beats the baseline model by about 14% and 10% on cross validation and test sets respectively.

| Approach | Average | | Anger | | Fear | | Joy | | Sadness | |
|------------------------|--------------|--------------|--------------|-------------|--------------|--------------|--------------|--------------|--------------|--------------|
| | CV | Test | CV | Test | CV | Test | CV | Test | CV | Test |
| Feed Forward NN | 69.75 | 69.58 | 66.22 | 67.88 | 72.71 | 72.42 | 72.08 | 68.26 | 67.99 | 69.77 |
| Multitask DL | 66.30 | 66.20 | 63.73 | 64.49 | 68.07 | 67.74 | 66.80 | 65.37 | 66.65 | 67.22 |
| CNN+LSTM Seq. Modeling | 70.70 | 71.79 | 69.22 | 70.15 | 72.08 | 72.95 | 73.22 | 69.14 | 68.29 | 74.93 |
| CNN+LSTM Seq. Modeling | 70.25 | 72.15 | 69.08 | 69.86 | 70.95 | 73.27 | 72.93 | 69.86 | 68.04 | 75.6 |
| CNN+LSTM Seq. Modeling | 70.03 | 71.81 | 68.90 | 69.71 | 70.67 | 72.92 | 72.81 | 69.57 | 67.74 | 75.06 |
| Ensemble Model | 75.26 | 74.70 | 72.94 | 73.2 | 76.78 | 76.20 | 74.42 | 73.20 | 76.90 | 76.50 |
| Baseline | 61.10 | 64.8 | 60.50 | 63.9 | 57.40 | 65.2 | 70.30 | 65.4 | 56.20 | 64.8 |

Table: Results showing Pearson Correlation

Results

Prayas at
EmoInt 2017:
An Ensemble
of Deep
Neural
Architectures
for Emotion
Intensity
Prediction in
Tweets

Outline

Introduction -
EmoInt
Shared Task

Dataset

Proposed
System

Results

Future Work

The ensemble model achieves about 3-5% improvement over the average scores.

| Approach | Average | | Anger | | Fear | | Joy | | Sadness | |
|------------------------|--------------|--------------|--------------|-------------|--------------|--------------|--------------|--------------|--------------|--------------|
| | CV | Test | CV | Test | CV | Test | CV | Test | CV | Test |
| Feed Forward NN | 69.75 | 69.58 | 66.22 | 67.88 | 72.71 | 72.42 | 72.08 | 68.26 | 67.99 | 67.77 |
| Multitask DL | 66.30 | 66.20 | 63.73 | 64.49 | 68.07 | 67.74 | 66.80 | 65.37 | 66.65 | 67.22 |
| CNN+LSTM Seq. Modeling | 70.70 | 71.79 | 69.22 | 70.15 | 72.08 | 72.95 | 73.22 | 69.14 | 68.29 | 74.93 |
| CNN+LSTM Seq. Modeling | 70.25 | 72.15 | 69.08 | 69.86 | 70.95 | 73.27 | 72.93 | 69.86 | 68.04 | 75.6 |
| CNN+LSTM Seq. Modeling | 70.03 | 71.81 | 68.90 | 69.71 | 70.67 | 72.92 | 72.81 | 69.57 | 67.74 | 75.06 |
| Ensemble Model | 75.26 | 74.70 | 72.94 | 73.2 | 76.78 | 76.20 | 74.42 | 73.20 | 76.90 | 76.50 |
| Baseline | 61.10 | 64.8 | 60.50 | 63.9 | 57.40 | 65.2 | 70.30 | 65.4 | 56.20 | 64.8 |

Table: Results showing Pearson Correlation

Results

Prayas at
EmoInt 2017:
An Ensemble
of Deep
Neural
Architectures
for Emotion
Intensity
Prediction in
Tweets

Approach 2 (Multitask DL) achieves the lowest scores among the three sets of approaches. Among Approach 1 (Feed Forward NN) and Approach 3 (CNN+LSTM Seq. Modeling), approach 3 has a best test score of 72.15 compared to approach 1's 69.58.

| Approach | Average | | Anger | | Fear | | Joy | | Sadness | |
|------------------------|--------------|--------------|--------------|-------------|--------------|--------------|--------------|--------------|--------------|--------------|
| | CV | Test | CV | Test | CV | Test | CV | Test | CV | Test |
| Feed Forward NN | 69.75 | 69.58 | 66.22 | 67.88 | 72.71 | 72.42 | 72.08 | 68.26 | 67.99 | 69.77 |
| Multitask DL | 66.30 | 66.20 | 63.73 | 64.49 | 68.07 | 67.74 | 66.80 | 65.37 | 66.65 | 67.22 |
| CNN+LSTM Seq. Modeling | 70.70 | 71.79 | 69.22 | 70.15 | 72.08 | 72.95 | 73.22 | 69.14 | 68.29 | 74.93 |
| CNN+LSTM Seq. Modeling | 70.25 | 72.15 | 69.08 | 69.86 | 70.95 | 73.27 | 72.93 | 69.86 | 68.04 | 75.6 |
| CNN+LSTM Seq. Modeling | 70.03 | 71.81 | 68.90 | 69.71 | 70.67 | 72.92 | 72.81 | 69.57 | 67.74 | 75.06 |
| Ensemble Model | 75.26 | 74.70 | 72.94 | 73.2 | 76.78 | 76.20 | 74.42 | 73.20 | 76.90 | 76.50 |
| Baseline | 61.10 | 64.8 | 60.50 | 63.9 | 57.40 | 65.2 | 70.30 | 65.4 | 56.20 | 64.8 |

Table: Results showing Pearson Correlation

Outline

Introduction -
EmoInt
Shared Task

Dataset

Proposed
System

Results

Future Work

Results

Prayas at
EmoInt 2017:
An Ensemble
of Deep
Neural
Architectures
for Emotion
Intensity
Prediction in
Tweets

Outline

Introduction -
EmoInt
Shared Task

Dataset

Proposed
System

Results

Future Work

Among the individual emotions, our ensemble model gives the best performance for 'Sadness', followed very closely by 'Fear', then 'Joy' and finally 'Anger'.

| Approach | Average | | Anger | | Fear | | Joy | | Sadness | |
|------------------------|--------------|--------------|--------------|-------------|--------------|--------------|--------------|--------------|--------------|--------------|
| | CV | Test | CV | Test | CV | Test | CV | Test | CV | Test |
| Feed Forward NN | 69.75 | 69.58 | 66.22 | 67.88 | 72.71 | 72.42 | 72.08 | 68.26 | 67.99 | 69.77 |
| Multitask DL | 66.30 | 66.20 | 63.73 | 64.49 | 68.07 | 67.74 | 66.80 | 65.37 | 66.65 | 67.22 |
| CNN+LSTM Seq. Modeling | 70.70 | 71.79 | 69.22 | 70.15 | 72.08 | 72.95 | 73.22 | 69.14 | 68.29 | 74.93 |
| CNN+LSTM Seq. Modeling | 70.25 | 72.15 | 69.08 | 69.86 | 70.95 | 73.27 | 72.93 | 69.86 | 68.04 | 75.6 |
| CNN+LSTM Seq. Modeling | 70.03 | 71.81 | 68.90 | 69.71 | 70.67 | 72.92 | 72.81 | 69.57 | 67.74 | 75.06 |
| Ensemble Model | 75.26 | 74.70 | 72.94 | 73.2 | 76.78 | 76.20 | 74.42 | 73.20 | 76.90 | 76.50 |
| Baseline | 61.10 | 64.8 | 60.50 | 63.9 | 57.40 | 65.2 | 70.30 | 65.4 | 56.20 | 64.8 |

Table: Results showing Pearson Correlation

Future Work

Prayas at
EmoInt 2017:
An Ensemble
of Deep
Neural
Architectures
for Emotion
Intensity
Prediction in
Tweets

Outline

Introduction -
EmoInt
Shared Task

Dataset

Proposed
System

Results

Future Work

- User hand-crafted features as additional input to the model
- Use other filters provided in the AffectiveTweets Package, provided with the shared task. [Example](#) - TweetToSentiStrengthFeatureVector, TweetNLPTokenizer
- Try Ensembling the models in a different fashion

Thank You : Questions?

For any questions or queries, email us
pranav.goel.cse14@iitbhu.ac.in
prayas.jain.cse14@iitbhu.ac.in
devang.kulshreshta.cse14@iitbhu.ac.in