2026 1st International Conference on Artificial Intelligence & Machine Learning in Communication and Power Systems (AIMLCPS) | 979-8-3315-5920-5/26/$31.00 ©2026 IEEE | DOI: 10.1109/AIMLCPS68702.2026.11542440

ML and CNN-Based Signature Verification System

Subhakanta Panda
Department of Computer Science and Engineering
Centurion University of Technology and Management,
Odisha, India
subhakanta.panda@cutm.ac.in

Pritam Kumar Nayak
Department of Computer Science and Engineering
Centurion University of Technology and Management
Odisha, India
pritam.nayak@cutm.ac.in

Ribhu Abhusan Panda
Department of Electronics and Communication Engineering
Centurion University of Technology and Management
Odisha, India
ribhuabhusan.panda@cutm.ac.in

***Abstract*—The handwritten signatures remain one of the key methods of authentication used in banking, legal documents and identity verification and therefore the reliability is essential. Paper-based verification can easily be subject to errors, subjectivity and time-consuming processes. These shortcomings are mitigated through ML- and CNN-based methods, which allow automated, objective, and highly accurate verification. The chapter starts with an introduction to the issues of signature verification such as intra-class differences (a natural variability in the signature of a person) and inter-class ones (skilled forgeries). ML techniques are presented as the tools on the principles of feature extraction, classification, and decision-making. Classical ML algorithms, including Support Vector Machines, k-Nearest neighbors, and Random Forests are mentioned in terms of their capability to process extracted geometric, statistical, and texture-based signatures features. One of the key areas that the chapter has concentrated on is the use of CNNs whereby manual feature engineering is not necessary as the feature learns discriminative spatial features directly using raw signature images. Architectures, training conditions, data augmentation and loss functions of CNNs are emphasized when it comes to verification tasks. The combination of ML classifiers and CNN-based feature vectors is also discussed, which helps to improve the accuracy of its verification.**

Keywords— Signature Checking, Convolutional Neural Network (CNN), Biometric Authentication, Forgery Detection, Deep Learning, Pattern Recognition.

I. INTRODUCTION

In a world that has been growing more digital, secure and reliable identity verification is now imperative in areas like banking, government services, corporate transactions and education. Signature verification is one of the most accepted and non-invasive and user-friendly biometric authentication methods among the many others. A handwritten signature is a personal characteristic and at the same time a legally admissible evidence of identity and intent. Nevertheless, manual or rule-based verification systems are often deficient in subjective interpretation, consistency and susceptible to forgery by experts. These have brought a great necessity of the automated and smart systems that can efficiently differentiate authentic signatures and falsified ones. As a result of the deep learning breakthrough, Convolutional Neural Networks (CNNs) have become a well-performing method of offline signature verification- in which a static image of a signature is being analyzed. The CNNs automatically acquire meaningful spatial patterns like strokes, curves, pressure variations and texture directly out of signature images, without any handcrafted feature extractor. Their hierarchical learning form allows them to learn low-level features (edges and contours) and high-level features (writing style and structural characteristics) making it suitable to deal with variations in authentic signatures and similarities in skilful forgeries. The Signature Verification System built on CNN usually involves data collection, pre-processing, learning features, model training, and classification. Features are further enhanced by noise filtering, grayscale conversion, normalization and edge boost which are some of the pre-processing steps that enhance clarity of the features. There are publicly available signature databases such as CEDAR, GPDS, and MCYT with various samples which enhance generalizability of the model. CNN-based verification systems are much better than conventional machine learning models (Support Vector Machines (SVMs) and Hidden Markov Models (HMMs) by using learned representations. They are better in terms of accuracy, robustness, and scalability and can be recommended as a potential solution to secure authentication and fraud detection. Finally, CNN-based signature verification increases trust and decreases human error and promotes safe digital transformation.

II. PROBLEM STATEMENT

Fingerprint authorization should be verified by signatures, and it is commonly applied in the fields of finance, law, and security. Some conventional signature verifying techniques are based on manually developed feature extraction or analysis techniques and are frequently time-consuming, unreliable, and subject to human error. Moreover, aging, health, or writing tools that cause changes in handwriting can render the process of determining whether certain signatures are authentic or skilful forgery difficult. Thus, there should be a reliable, automatic and accurate verification of signing mechanism to avoid fraud and unauthorized access.

The most important aspect is to differentiate between real signatures and elaborate fakes like well-made imitations that can be quite similar to the original. Conventional machine learning often possesses problems of poor inter-class variables (similarities between a forged and authentic signature) and big intra-class variations (variance among signatures of a specific person). Such are the challenges then a more sophisticated method is required that would be able to automatically repose the complex structure and features of the signatures and does not require any human input.

III. OBJECTIVES

- To create a dependable CNN-based signature verification system, which can be used in the differentiation between a real and a fake signature.
- To perform feature extraction with deep learning to automate the extraction and produce more accurate authentication.
- To increase the accuracy and reliability by minimizing false acceptance and rejection with optimized CNN models.
- To aid real time verification with effective feature extraction and processing methods.

979-8-3315-5920-5/26/$31.00 ©2026 IEEE

Authorized licensed use limited to: REVA UNIVERSITY. Downloaded on October 09,2026 at 06:59:09 UTC from IEEE Xplore. Restrictions apply.

- To manage natural differences in handwriting by allowing the model to learn many signature patterns.
- To enhance the efficiency of the powerful architectures, transfer learning, and hardware acceleration to run the large-scale applications.

IV. Literature Review

Traditional systems relied on handcrafted geometric, statistical, and texture-based features. Models such as SVMs, ANNs, and HMMs manually used attributes like stroke direction and velocity but showed inconsistency due to handwriting variations and environmental conditions [1], [2].

Deep learning revolutionized signature verification by enabling automatic extraction of discriminative features from raw images. Kumar et al. (2019) developed a deep CNN model that captured fine-grained signature details and achieved nearly 95% accuracy in offline verification [3]. Dey et al. (2020) introduced CNN-based Siamese networks for one-shot learning, improving generalization to unseen signatures [4].

Public datasets such as CEDAR, GPDS, and MCYT-75 support training and testing, but class imbalance and intra-class variations remain major challenges. Researchers employ augmentation techniques such as rotation, scaling, and noise addition to enhance model diversity and generalization [5].

CNN-based systems show reduced Equal Error Rate (EER), False Acceptance Rate (FAR), and False Rejection Rate (FRR) compared to classical models. Recent works integrate CNNs with attention mechanisms and RNNs to improve sequential feature learning. Future advancements include transformer models, multimodal biometrics, and graph neural networks for handling complex forgeries [6-7].

V. Methodology

To come up with a CNN-based Signature Verification System, there are a number of key processes involved, such as data collection, pre-processing, model construction, training and evaluation and implementation. The next systematic measure will guarantee that signature authentication will be precise, powerful, and strong.

Data Preparation each of the three companies will be surveyed to collect data related to the comprehensive assessment of their information technology systems.




Fig. 1. Project Overflow

A. Data Collection and Preparation

To make sure that the model has been trained on various and good quality examples, data collection and data preparation constitute an important step in designing a CNN-based Signature Verification System. Multiple publicly available datasets, e.g. CEDAR, GPDS, MCYT-75 and SigComp include both real and fake signatures, which make it possible to train strong and effective models. The CEDAR signature dataset has been experimented in this work. The total number of signature images is 2,645 consisting of 1,321 genuine signatures and the rest of the samples are forged signatures. In order to guarantee successful learning and equitable data on performance evaluation, the data set has been split into 80 percent training and 20 percent testing. Moreover, under controlled circumstances, handwritten signatures may be gathered in order to produce customized datasets that reflect the variations in the real world. In order to improve the generalization of the models and to deal with the intra-class variation, several techniques of data augmentation, including rotation, scaling, addition of noise, and contrast adjustment are utilized. These augmentation techniques are employed to enhance the strength of the model and make it able to withstand any changes that are usually experienced in handwritten signatures. [8].

Authorized licensed use limited to: REVA UNIVERSITY. Downloaded on October 09,2026 at 06:59:09 UTC from IEEE Xplore. Restrictions apply.

B. CNN Model Design

Design CNN Model is the very important step of creating a successful signature verification system since the model will be able to learn itself and to detect the most important information out of signature images. Using significant configuration such as edges, strokes, and texture, the convolutional layers enable the system to distinguish real signatures versus bogus signatures. To enhance efficiency, pooling layers conserve critical data and cut on computation time and dimensionality. After recovering the data, it is analyzed at each of the layers to determine whether it is an authentic signature or a fake one. Soft max or Sigmoid functions are used to handle classification and non-linearity is introduced using activation function such as ReLU to improve learning. [9-10]

C. Image Pre-processing

Image pre-processing is essential to improve the accuracy and effectiveness of a CNN-based signature verification system because it improves the quality of the signature image prior to inputting it into the model. Grayscale conversion makes calculations easier by reducing the number of color channels to one channel of intensity-based representation. Normalization guarantees the homogeneity of inputs distribution and stabilization of model training through the normalization of pixel values, which lie in the range between 0 and 1. The clarity of signatures is increased under noise reduction methods that remove the unwanted aberrations like ink blots or background smudges. Also, edge detection algorithms such as Sable method or Canny filters are employed to emphasize pattern of signature stroke, which increases the ability of feature extraction to distinguish between valid and inauthentic signature. [11]




Fig. 2. Image Processing of Signatures

D. Model Training

Model training It is a necessary step in the creation of a CNN-based signature verification system because it is what makes the model be trained to differentiate between authentic and fake signatures. Error minimization during training is achieved by a suitable loss function, which can be the binary system crossover entropy (when doing two-class classification) or categorical A cross-en (when doing multi-class classification). Optimizers such as Adam or RMSprop are effective in changing model parameters by dynamically changing learning rates to improve convergence. Training is performed with a good batch size (e.g., 32) and enough number of epochs (50-100) in order to enable the model to generalize. Before the final evaluation, a validation set is also employed so that the hyper parameters can be adjusted to avoid over fitting, as well as enhance the overall performance.

E. Performance Evaluation

The performance evaluation is vital to the determination of the success rate in a CNN-based signature verification system distinguishing a genuine signature, and a fake signature. Recall and F1-score are essential evaluation measures that demonstrate the extent of reduction of false negatives and erroneous results by the model and accuracy is the general truthfulness of the model. The Equal Error Percentage (EER), which is a very essential parameter that is a composite of the False Acceptance Rate (the rate at which forged signatures are falsely accepted) and the False Rejection Rate (FRR), the rate at which authentic signatures are falsely rejected, is employed to offer the most appropriate trade-off between the security and the usability. Moreover, ROC Curve Analysis measures the quality of the model and assists to conclude about the reliability of the model in detecting forgery, as the results are presented in the form of the model performance at various choice thresholds. [12-13]

VI. Results And Analysis

The analysis and results of the CNN-based Signature Verification System facilitate in evaluating the ability of the system to discriminate genuine and forged signatures. The performance is evaluated using key metrics, dataset analysis, and error analysis as well as comparison studies.




Fig. 3. Real Result of the Project

A. Performance Metrics

In determining the effectiveness of a CNN-based Signature Verification System, performance metrics are

Authorized licensed use limited to: REVA UNIVERSITY. Downloaded on October 09,2026 at 06:59:09 UTC from IEEE Xplore. Restrictions apply.

needed. The robustness of validation is achieved through the assessment of a different test data on the accuracy of the model. Accuracy measures the overall accuracy of detecting authentic or fake signatures. Recall and precision help evaluate the system with the ability to reduce the false acceptances and correctly recognize genuine signatures. The F1-score is useful in the management of unbalanced datasets as it is a combination of precision and recall to come up with balanced assessment.

B. Dataset Evaluation

Testing and dataset evaluation is a necessary element when assessing the effectiveness of a CNN-based Signature Verification System. To evaluate how well the model can adapt to real-world variations it is tested on both custom and publicly available data sets, such as CEDAR, GPDS, MCYT-75 and Sign Comp. The model can be trained to distinguish between variousiating properties of such datasets that comprise genuine and forged signatures. There are several variables that influence performance of the model.

C. Error Analysis

To have a CNN-based Signature Verification System that is resilient, the analysis of errors is required. In case a forged signature is accepted as genuine, it may lead to a loss of security and False Acceptance (Type I Error). False Rejection (Type II Error) on the other hand is when the valid signature is incorrectly rejected which makes it hard to the user. These errors are mitigated by several methods: increasing the diversity of datasets with both a range of samples and methods of data augmentation are used to make the model more general; feature extraction methods are continually optimized to better represent the nuanced differences between authentic and fabricated signatures; decision threshold is fine-tuned to achieve a better trade-off between false and false positives.

VII. Applications

Convolutional Neural Network (CNN)-based Signature Verification System can be applied in a number of fields and different situations, which need secure authentication. Some key uses of this project are as follows:

A. Records of Government and Law

This is the way that government agencies check the signature of voters, resolve picture identification and avoid illegal activity in executing administrative functions. Authentication of signatures reduces chances of fraud and disagreements during litigation processes by verifying authenticity of affidavits, will and court related documents. Government and legal organizations can use Convolutional Neural Networks (CNNs) to automate verification and make it more efficient and accurate.

B. Education Sector

Signature verification methods are applied in the education sector to confirm authenticity of academic records including tests, certificates, and records of students. This technology is used in universities and other institutions to curb the falsification of degree certificates, entrance forms and faculty approvals. Confirmation of signature can be used to verify government approvals and attendance of students and it is less likely to lead to fraud. Convolutional Neural Networks (CNNs) can be used to enhance the accuracy and efficiency of the verification process, which automation of the verification process can achieve.

C. E-business and internet based transaction industry

The online trade and transaction markets receive the benefits of enhanced digital security of payment and detection of frauds due to signature verification. This technology is used on online platforms to authenticate digitally signed documents during financial dealings and only authorized persons are allowed to sign contracts or purchase. Banking and payment gateway solutions use signature checking to reduce the chances of fraud and fraudulent access to accounts. The automation of the verification process through Convolutional Neural Networks (CNNs) helps businesses to increase the accuracy and minimize manual inspections. The technology improves cyber security, builds confidence in online transactions, and makes sure that digital signatures are reliable when carrying out e-commerce activities.

VIII. Conclusion

The CNN Signature Verification System is a much safer platform than existing applications like identity verification, finance, and law since it offers a much efficient, automated method of verifying a handwritten signature. By applying the deep learning techniques, the system can effectively differentiate between valid and fraudulent signature better than the traditional one, i.e. the SVMs and manually developed feature-based algorithm. The enhancement of the performance is done through hybrid models, preprocessing methods, and data augmentation to ensure that it is flexible to variations in the real world. However, some issues which need to be improved include signature variability, competent forgeries, and complexity of computations. The scalability and reliability of the system will be enhanced in the future because of block chain-based security, online signature verification, and multimodal authentication. Nevertheless, the flaws notwithstanding, the offered method is a major improvement of the biometric security and offers rapid, precise, and scalable means of coping with the contemporary authentication requirements. As the developments increased, CNN-based signature verification may have a big role to play in the secure identity verification systems around the world.

References

[1] L. G. Hafemann, R. Sabourin, and L. S. Oliveira, “Offline handwritten signature verification—Literature review,” *IEEE Access*, vol. 8, pp. 159177–159193, 2020.

[2] S. Dey, A. Dutta, U. Pal, and M. Blumenstein, “A deep learning framework for offline signature verification,” in *Proc. IEEE Int. Conf. on Pattern Recognition (ICPR)*, Milan, Italy, 2021, pp. 2563–2569.

[3] A. R. Abbas, M. A. Khan, and T. Akram, “Offline signature verification using deep convolutional neural networks,” in *Proc. IEEE Int. Conf. on Image Processing (ICIP)*, Abu Dhabi, UAE, 2020, pp. 1351–1355.

[4] P. Kumar, S. Kumar, and R. Singh, “CNN-based feature learning for offline handwritten signature verification,” in *Proc. IEEE Int. Conf. on Computing, Communication and Automation (ICCCA)*, New Delhi, India, 2020, pp. 112–117.

[5] A. Soleimani, B. Araabi, and K. Fouladi, “Deep multitask metric learning for offline signature verification,” in *Proc. IEEE Int. Joint Conf. on Biometrics (IJCB)*, Houston, TX, USA, 2021, pp. 1–8.

[6] Y. Guerbai, Y. Chibani, and B. Hadjadji, “The effective use of deep learning in offline signature verification,” in *Proc. IEEE Int. Conf. on Systems, Man, and Cybernetics (SMC)*, Toronto, Canada, 2020, pp. 2951–2956.

[7] M. Serdouk, A. Nemmour, and Y. Chibani, “Deep learning based signature verification system,” in *Proc. IEEE Int. Conf. on Advanced Technologies for Signal and Image Processing (ATSIP)*, Sousse, Tunisia, 2020, pp. 1–6.

[8] S. Biswas, R. Sarkar, and M. Nasipuri, “Offline signature verification using Siamese neural networks,” in *Proc. IEEE Int. Conf. on Intelligent*

Authorized licensed use limited to: REVA UNIVERSITY. Downloaded on October 09,2026 at 06:59:09 UTC from IEEE Xplore. Restrictions apply.

Systems Design and Applications (ISDA), Vellore, India, 2019, pp. 1–6.

[9] H. Khalid, S. Aslam, and M. A. Khan, "Offline handwritten signature verification using deep residual networks," in *Proc. IEEE Int. Conf. on Artificial Intelligence and Knowledge Engineering (AIKE)*, Irvine, CA, USA, 2021, pp. 174–179.

[10] M. A. Hossain, M. A. Hossain, and M. A. Rahman, "CNN-based offline handwritten signature verification with data augmentation," in *Proc. IEEE Int. Conf. on Computer and Information Technology (ICCIT)*, Dhaka, Bangladesh, 2022, pp. 1–6.

[11] R. Verma, A. Kumar, and V. K. Shukla, "Offline signature verification using hybrid CNN and machine learning classifiers," in *Proc. IEEE Int. Conf. on Smart Computing and Informatics (SCI)*, Jaipur, India, 2023, pp. 89–94.

[12] A. AbdelRaouf and D. Salama, "Handwritten Signature Verification using Haar Cascade Classifier Approach," *2018 13th International Conference on Computer Engineering and Systems (ICCES)*, Cairo, Egypt, 2018, pp. 319-326, doi: 10.1109/ICCES.2018.8639437.

[13] P. Misra, N. Panigrahi, S. Gopal Krishna Patro et al., "PETLFC: Parallel ensemble transfer learning based framework for COVID-19 differentiation and prediction using deep convolutional neural network models," Multimedia Tools and Applications, vol. 83, pp. 14211–14233, 2024, doi: 10.1007/s11042-023-16084-4.

Authorized licensed use limited to: REVA UNIVERSITY. Downloaded on October 09,2026 at 06:59:09 UTC from IEEE Xplore. Restrictions apply.