

Experiment no. 5

Name: Pranav Chindage

Div: D15B

Roll no.: 10

Aim: To apply navigation, routing and gestures in Flutter

App Theory:

Navigation and Routing Navigation and routing are some of the core concepts of all mobile application, which allows the user to move between different pages. We know that every mobile application contains several screens for displaying different types of information. For example, an app can have a screen that contains various products. When the user taps on that product, immediately it will display detailed information about that product.

In Flutter, the screens and pages are known as routes, and these routes are just a widget.

In Android, a route is similar to an Activity, whereas, in iOS, it is equivalent to a ViewController. In any mobile app, navigating to different pages defines the workflow of the application, and the way to handle the navigation is known as routing. Flutter provides a basic routing class `MaterialPageRoute` and two methods `Navigator.push()` and `Navigator.pop()` that shows how to navigate between two routes. The following steps are required to start navigation in your application.

Navigation: Navigation in Flutter refers to the ability to move between different screens or pages within an app. Flutter provides a `Navigator` widget to manage the navigation stack and perform common navigation operations.

Navigation Operations:

Pushing a Screen: Use `Navigator.push` to navigate to a new screen.

Example:

```
Navigator.push(context, MaterialPageRoute(builder: (context) => DetailsScreen()));
```

Popping a Screen: Use `Navigator.pop` to go back to the previous screen.

Example:

```
Navigator.pop(context);
```

Routing: Routing:

In the context of Flutter, involves defining the paths or routes that lead to different screens in your app. It allows you to organize and structure the flow of your application. Flutter supports both named routes and unnamed (or default) routes.

Named Routes:

Named routes are routes identified by a unique string identifier. They provide a more organized and maintainable way to navigate between screens. You can define named routes in the MaterialApp widget using the routes property.

Example:

```
MaterialApp( routes: { '/': (context) => HomeScreen(), '/details': (context) =>
DetailsScreen(), }, )
```

```
import 'package:firebase_core/firebase_core.dart';
import 'package:flutter/material.dart';
import 'package:sports_tracker/firebase_funcs.dart';
import 'package:sports_tracker/firebase_options.dart';
import 'package:sports_tracker/home_main.dart';
import 'package:http/http.dart' as http;
import 'dart:convert';
```

```
import 'package:sports_tracker/home_tab.dart';
import 'package:sports_tracker/matches_tab.dart';
import 'package:sports_tracker/points_table.dart';
import 'package:sports_tracker/profile_tab.dart';
```

```
Future <void> main() async {
```

```
  WidgetsFlutterBinding.ensureInitialized();
```

```
  await Firebase.initializeApp(options: DefaultFirebaseOptions.currentPlatform,);
  fetch_data();
  runApp(MaterialApp(
    home: Home(),
    theme: ThemeData(
      fontFamily: 'Teko',
    ),
    initialRoute: '/',
    routes: {
      '/home_tab': (context) => Home_tab(),
      '/matches_tab': (context) => Matches_tab(),
      '/profile_tab': (context) => Profile_tab(),
    }
  ));
}
```

```

    '/home_tab_points_table': (context) => Points_table(),
  },
));

}

```

```

import 'package:firebase_database/firebase_database.dart';
import 'package:flutter/material.dart';
import 'package:sports_tracker/firebase_funcs.dart';
import 'package:sports_tracker/points_table.dart';
import 'package:sports_tracker/squad.dart';
import 'package:sports_tracker/stats.dart';

```

```

class Home_tab extends StatefulWidget {
  const Home_tab({super.key});
  // final dynamic home_tab_squad;
  //
  // const Home_tab({Key? key, required this.home_tab_squad}) : super(key: key);

```

```

@override
State<Home_tab> createState() => _Home_tabState();
}

```

```

class _Home_tabState extends State<Home_tab> {

```

```

  var entire_squad;

```

```

  Future<Object?> getsquad() async {

```

```
FirebaseDatabase database = FirebaseDatabase.instance;  
final ref = FirebaseDatabase.instance.ref();
```

```
try {  
    final snapshot = await ref.child('Squad').get();  
    var sd = snapshot.value;  
    return sd; // Return the fetched data  
} catch (error) {  
    // Handle error if needed  
    return null;  
}  
}
```

```
int selected_index=0;  
void change (int index) {  
    setState(() {  
        selected_index = index;  
    })  
};  
}
```

```
@override
```

```
Widget build(BuildContext context) {
```

```
return SingleChildScrollView(  
    child:Column(  
        children: [  
            Container(  
                child: Row(  
                    mainAxisAlignment: MainAxisAlignment.spaceAround,  
  
                    children: [  
  
                        ElevatedButton( // for player stats  
  
                            onPressed: () {  
                                change(0);  
                            }  
                        )  
                    ]  
                )  
            )  
        ]  
    )  
);  
}
```

```

},
child: Column(
  mainAxisAlignment: MainAxisAlignment.min,
  // Ensure that the column only occupies the space required by its children
  children: [
    Icon(Icons.people, color: Colors.red[700]), // Icon widget
    SizedBox(height: 8), // Spacer between icon and text
    Text('Squad',
      style: TextStyle(
        color: Colors.black,
      )),
    // Text widget
  ],
), // Specify the label
),

```

```

ElevatedButton( //for squad stats
  onPressed: () {
    change(1);
  },
  child: Column(
    mainAxisAlignment: MainAxisAlignment.min,
    // Ensure that the column only occupies the space required by its children
    children: [
      Icon(Icons.person, color: Colors.red[700]), // Icon widget
      SizedBox(height: 8), // Spacer between icon and text
      Text('Stats',
        style: TextStyle(
          color: Colors.black,
        )), // Text widget
    ],
  ), // Specify the label
),

```

```

ElevatedButton( //for points table
  onPressed: () {
    //change(2);
    Navigator.pushNamed(context, 'home_tab_points_table');
  },
  child: Column(

```

```

mainAxisSize: MainAxisSize.min,
// Ensure that the column only occupies the space required by its children
children: [
  Icon(Icons.table_rows_outlined, color: Colors.red[700]),
  // Icon widget
  SizedBox(height: 8),
  // Spacer between icon and text
  Text('Points table',
    style: TextStyle(
      color: Colors.black,
    )),
  // Text widget
],
), // Specify the label
),
],
),
),
SizedBox(height: 30),
Container(
  // children: [
  // FutureBuilder<Object?>(
  //   future: getsquad(), // Call getsquad() to fetch data
  //   builder: (BuildContext context, AsyncSnapshot<Object?> snapshot) {
  //     // Check if the Future has completed
  //     if (snapshot.connectionState == ConnectionState.done) {
  //       // Check if data has been successfully fetched
  //       if (snapshot.hasData) {
  //         // Data has been fetched successfully, use it
  //         entire_squad = snapshot.data;
  //         List<Widget> textWidgets = [];
  //         //
  //         for (var i in entire_squad) {
  //           textWidgets.add(
  //             ExpansionTile(
  //               title: Row(
  //                 children: [
  //                   Icon(Icons.sports_soccer),
  //                   SizedBox(width: 10), // Add some spacing between the icon
  //                   and the text

```

```

//          Text('${i['name']}'),
//      ],
//  ),
//  children: <Widget>[
//      // Content widgets inside the ExpansionTile
//      ListTile(
//          title: Text('Name: ${i['name']}\n\n'
//              'Position: ${i['position']}\n\n'
//              'Nationality: ${i['nationality']}'),
//          ),],
//  ),
//  );
//  }
//
//  return Column(
//      children: textWidgets,
//  );
//  } else {
//      // Data fetch failed or is null, handle error or show loading indicator
//      return Center(child: CircularProgressIndicator()); // Or display an error
message
//  }
//  } else {
//      // Future is still loading, show a loading indicator
//      return Center(child: CircularProgressIndicator());
//  }
//  },
//  ),
// ]
child: _getBodyWidget(selected_index),
),
],
);

```

```
}
```

```
Widget _getBodyWidget(int index) {
```

```
  switch (index) {
```

```
    case 0:
```

```
      return Squad_details();
```

```
    case 1:
```

```
      return Stats();
```

```
    case 2:
```

```
      return Points_table();
```

```
    default:
```

```
      return SizedBox.shrink();
```

```
  }
```

```
}
```

```
}
```




Premier League

English championship

Results

Table

Goals



Liverpool

3 - 1

Arsenal



Man. City

4 - 0

Chelsea



Tottenham

2 - 1

Newcastle



Man. U

5 - 2

C. Palace



Leicester

3 - 1

A. Villa



Conclusion: Hence, we have successfully implemented the required functionalities for our app.