

What happens to the address space after the fork system call is made ?

----- a copy of the address space is created ----- the child's copy

**EXEC system call** ---- Exec takes command over existing process

Did you start a C program from another C program ?  
TO run a linux command from a C program ?

Exec Family of Functions / System calls

execl ,execlp , execv, execvp

---

Every Linux command is a process that runs !  
The C program we run is also a process

Exec will RUN the ls process within the C process  
The Exec process HIJACKS the Current C process

The Exec process takes control of the address space of the C program

As a thumb rule --- The C program calling exec must not write its own code !!!

Usually exec is used along with fork -----

---

execl = give the location of the command as first argument and other command options as comma separated argument list  
execl( "/bin/ls", "-l", NULL );

---

The execlp , execvp tries to find the ls command in the PATH environment variable  
execlp ( "ls", "-l" , NULL );  
execvp( "ls" , arr )

---

```
char * arr[] = { "ls " , "-l", NULL } ;
```

```
execv ( "/bin/ls" , arr )
```

---

execl	First arg = name of command with location	Comma sepearated options
execv	Same with location	Array of options
execlp	Name of command , location taken from PATH	Comma separated options

---

HW ---

Write a c program that forks and creates 2 child processes

The first process runs the ls -l command } execl

The second child process runs the ps -ef command } execv

The parent should wait (WAIT ) for a signal from both the children that they are done.

After that the parent should print GOOD BYE and end

---

**Wait = is a way to make the parent wait for child to finish.**

**This is a good programming practice where programs are using fork !!!**

If parents waits till the child finishes then parent cleans up the process tables for terminated children quickly , NO orphans , no zombies !!!!

HW --- read the Linux MAN PAGE for wait()

---

**Fork() , getpid, getppid, wait , exec family !!!!**

---

**Signals in linux !!!**

Software interrupts / exceptions

Can be sent by Kernel process to user process

By user process to process

**Signals are a way of communicating BETWEEN processes ---- Inter process communication**

Signals have Signal Handlers !!!

Signal handlers are **functions** that will do something when signal occurs !!!

Default signal handlers for all Signals !!!!!

If we want to change the default signal handler , we can give our own signal handler!!!!

We must register OUR signal handler with the kernel ----- system call **signal ()**

**signal( which signal , which handler )** [system call](#)

---

**Kill command can send a signal to the process**

Kill -signalnumber pid

Kill pid }} the default signal is 15 SIGTERM Maskable

Kill -9 pid }} SIGKILL -9 non maskable

Ctrl C = SIGINT 2 Maskable

Kill -2 pid

---

Kill -l }} find the list of signals and write handlers for whichever you like !!!

---

We executed the kill command from a C program !!!!

---

