Name: Pranav Arun lahitkar
Class: FYMCA - A Roll No: 31
Batch: A2
Subject: Web Technology

• Assignment 2 •

Q1. PHP program to find area of rectangle
→

```
<html>
 <body>
  <form method="post">
   Width: <input type="number" name="width">
    <br> <br>
   length: <input type="number" name="length">
    <br>
   <input type="submit" name="submit"
              value="calculate">
  </form>
 </body>
</html>
<? php
  if (isset ($_POST['submit']))
     {
       $width= $_POST['width'];
       $length= $_POST['length';
       $area= $width* $length;
     } echo " Area: $area";
?>
```

Q2: Explain any three Angular directives. (3)

→

* Directives are classes that add additional behaviour to elements in your Angular appl^n.

① NgClass:

→ it dynamically binds one or more CSS classes to an HTML element.

→ the value of ng-class directives can be a string, an object, or an array.

→ if it is a string, it should contain one or more, space-separated class names.

→ object contains key-value pair

→ Array can be combination of both.

Syntax: <element ng-class="expression"></element>

② Ng-Style:

→ it specifies the style attribute for HTML element

→ value must be an object or an expression returning object

→ object consists of CSS properties & values in key value pairs.

Syntax: <element ng-style="expression">></element>

) Ng-model:

→ directive can provide status for application data

→ you can bind value of input field to a variable created in Angular JS.

→ can provide type validation for appl^n data

→ it provides CSS classes for HTML elements

Syntax:

<element ng-model="nani"> </element>