Lab2
CS211

Name-Pranav Tambe
Roll No-2106339



Interface before loading any file

Q.1) Complete the following code snippet to add 10 numbers stored consecutively in data memory.
Print the result

```
.data
array : .word 10, 12, 15, -10, 13, 82, -9, 4, 3, -7  # load the array
length: .word 10 # load the length of the array as 10
```

```
sum: .word 0 # initialize sum to 0
out_s: .asciiz "\nSum of elements in the array is :"
out_st: .asciiz "\n------This program does the sum of all the  elements in
an array------\n"

.text  # tells assembler to switch to the text segment or succeeding lines
contains instructions

main:  # start of code section

li $v0,4   # system call for  the printing string
la $a0,out_st    # load address of string to printed in $a0
syscall    # call operating system to perform operation
la $t3, array   # load base address of the array
# $t3 has the base address of data. All the subsequent data can be
accessed using respective offset values
lw $t4,length # load array size
li $t5,0  # for index of array, i=0
li $t6,0 # load sum initialized with 0

sumloop:
    lw $t7 ,($t3) # get array's  number at ith position  or array[i]
    add $t6,$t6,$t7 # do sum+=array[i]
    add $t5,$t5,1 # i++ increment in i
    add $t3,$t3,4 # update array address by adding 4 as every integer is
stored  consecutively after 4 bytes
    bne $t5,$t4,sumloop # if $t5 is not equal to $t4 loop again
    sw $t6,sum # store sum in $t6
    li $v0,4 # system call for printing string
    la $a0,out_s # load address of string to be printed in a0
    syscall # call OS to  execute the operation
    li $v0,1 # system call for printing the integer
    move $a0,$t6 # move result to $ a0
    syscall # call OS to  execute the operation
    li $v0,10 # terminate program
    syscall
```

Brief overview of the code section

Array contains 10 integers stored in 16 bit word format ,the starting address is represented by name array
Array length is 10
Sum is initiated with value 0
Some strings to be printed on the console

In main section array address is stored in $t3 by la(load address)
 $t4 contains length of the array
$t5 for index of array, i=0
$t6 to store sum initialized with 0

Loop section
Array address is loaded in $t7
then it is added with $t6
Index is incremented by 1
Address is incremented by adding 4 in the previous address as integers are 4 bits long
Then if index is not equal to length we again branch to the loop by bne instruction
And at last the result is stored and printed on the console.

After loading the first file



Registers after execution of the code



Console after execution of the program



Loop instructions

1) lw $t7 ,($t3) # get array's number at ith position or array[i]

2) add $t6,$t6,$t7 # do sum+=array[i]

3) add $t5,$t5,1 # i++ increment in i

4)add $t3,$t3,4 # update array address by adding 4 as every integer is stored consecutively after 4 bytes

5)bne $t5,$t4,sumloop # if $t5 is not equal to $t4 loop again

5 loop instructions for each number

So total loop instructions to be executed =length X instructions for a single number= 10 X 5=50

other instructions for printing strings or integers on console loading them etc. for once

Can be calculated by pc value(program counter)

Pc value at the start of the program



Pc value at the end of the program



Other instructions =(4194436-4194344)/4 - loop instructions
=92/4-5=23-5=18

So **total instructions = total loop instructions + other instructions =50 +18= 68**

Q.2) Include the following numbers in the array data segment of question 1.
10,20,30,40,50,77

```
.data
array : .word 10, 12, 15, -10, 13, 82, -9, 4, 3, -7   # load the array
        .word 10, 20, 30, 40, 50, 77
length: .word 16 # load the length of the array as 10
sum: .word 0 # initialize sum to 0
out_s: .asciiz "\nSum of elements in the array is :"
out_st: .asciiz "\n------This program does the sum of all the  elements in
an array------\n"

.text  # tells assembler to switch to the text segment or succeeding lines
contains instructions

main: # start of code section
```

```
li $v0,4 # system call for printing string =4
la $a0,out_st # load address of string to be printed in $a0
syscall # call operating system to perform operation
la $t3, array # load base address of the array
# $t3 has the base address of data. All the subsequent data can be
accessed using respective offset values
lw $t4,length # load array size
li $t5,0  # for index of array, i=0
li $t6,0 # load sum initialized with 0

sumloop:
    lw $t7 ,($t3) # get array's  number at i or array[i]
    add $t6,$t6,$t7 # do sum=sum+array[i]
    add $t5,$t5,1 # i++
    add $t3,$t3,4 # update array address
    bne $t5,$t4,sumloop
    sw $t6,sum
    li $v0,4 # system call for printing string =4
    la $a0,out_s # load address of string to be printed in $a0
    syscall # call operating system to perform operation
    li $v0,1
    move $a0,$t6
    syscall # call operating system to perform operation
    li $v0,10 # terminate program
    syscall
```

Brief overview of the code section

Array size is made to 16 and 6 new integers are added at the back of the array rest of the code is exact same as Q.1

Now the total loop instructions to be executed =length X instructions for a single number= 16 X 5=80

18 other instructions for printing strings or integers on console loading them etc. for once ,same as Q.1

So total instructions = total loop instructions + other instructions =80 +18= 98

The total loop instructions are now increased by 30 from before as we have added 6 elements at the back of the array

So 6 X loop instructions for a single entity = 6 X 5 =30 are increased from before as Those corresponds to increased array size

After loading the second file



Console after execution of the program


Console
------This program does the sum of all the elements in an array------
Sum of elements in the array is :340

Registers after execution of the code

Int Regs [10]

```
EPC       = 0
Cause     = 0
BadVAddr  = 0
Status    = 805371664

HI        = 0
LO        = 0

R0  [r0] = 0
R1  [at] = 268500992
R2  [v0] = 10
R3  [v1] = 0
R4  [a0] = 340
R5  [a1] = 2147480960
R6  [a2] = 2147480968
R7  [a3] = 0
R8  [t0] = 0
R9  [t1] = 0
R10 [t2] = 0
R11 [t3] = 268501056
R12 [t4] = 16
R13 [t5] = 16
R14 [t6] = 340
R15 [t7] = 77
R16 [s0] = 0
R17 [s1] = 0
R18 [s2] = 0
R19 [s3] = 0
R20 [s4] = 0
R21 [s5] = 0
R22 [s6] = 0
```

Q.3) Euler's Phi function for an input n.
Compute the Euler Phi function for the number 21.

```
.data
num1: .word 21 # num1 as 21
num2: .word 1 # num2 as 1
ans: .word 0 # initialise ans from  0
input_s: .asciiz "\nEnter a number n :"
out_s: .asciiz "\nphi(n)is :"
out_st: .asciiz "\n------This program computes the Euler Phi function for
the number------\n"

.text  # tells assembler to switch to the text segment or succeeding lines
contains instructions

main:  # start of code section
    li $v0,4 # system call for printing string =4
    la $a0,out_st # load address of string to be printed in $a0
    syscall # call operating system to perform operation
    li $v0, 4 # System call code for print_str
    la $a0, input_s # Load address of prompt string
    syscall # Print the input_s

    # Read integer from user
    li $v0, 5 # System call code for read integer
    syscall # Read integer from user and store in $v0
    move $t4, $v0 # Move input integer from $v0 to $t4
    lw $t1,num2 # store 1 in $t1
    lw $t3,ans # store ans in $t3

    loop:
        add $a0,$t4,0 # Load n into $a0
        add $a1,$t1,0 # Load 0 into $a1
        jal gcd # Jump to gcd subroutine
        check:
            beq $a0,1,equal # if gcd is equal to 1 jump to the equal block
        keep:
            add $t1,$t1,1 # increment $t1 by 1
            bne $t1,$t4,loop # branch if $t1 is not equal to $t4 i.e. n
```

```
      li $v0,4 # system call for printing string = 4
      la $a0,out_s # load address of string to be printed in $a0
      syscall # call operating system to perform operation

      li $v0, 1 # System call code for print_int
      move $a0, $t3 # Load result into $a0 from $t3
      syscall # Print the result

      li $v0, 10 # System call code for exit
      syscall # Exit program

    #
-------------------------------------------------------------------------
-----------------------------------------------------#
    # gcd function
    # Recursive definition
    # gcd(m,n)==gcd(n,(m%n))
    #
-------------------------------------------------------------------------
-----------------------------------------------------#
    gcd:
      # Base case
      beq $a1, $0, end # If second number is 0, return first number
      move $t0, $a0 # Save first number
      move $a0,$a1 # move second  number in $a0 it is now our first number
      div $t0, $a1 # Divide first number by second number
      mfhi $a1 # Store the remainder in $a1(remainder is now second
number)

      j gcd # Recursively call the gcd function

    end:
      j check # Return to check block  our gcd is stored in $a0
    equal:
          add $t3,$t3,1 # increment $t3 by 1
          j keep # jump to keep block
```

Brief overview of the code section

With system call and li $v0, 5 read an integer n from the user move the stored value to $t4
Load 1 in $t1

Loop section

Add $t4 with 0 and store in $a0
Store value in $t1 into $a1
Call gcd with $a0 and $a1

Now in the **gcd block**

Check for the base case if $a1 equal to zero then jump to the end block and gcd is stored in $a0

else

store $a0 in $t0
Move $a1 in $a0
Div $t0 by $a1
Store the remainder in $a1

And call gcd function recursively

Here in gcd function gcd is calculated by Euclidean method
gcd(m,n)==gcd(n,(m%n))

From the end block we jump to check where code checks whether gcd is equal to 1 or not, if it is then ans in $t3 is incremented by one as we have found a number whose gcd with n is 1 and keep moving in the loop
Else we keep moving in the loop without incrementing ans in $t3
Increment $t1 by one
Iterate through the loop till $t1 is less than equal n for each $t1 incremented by 1 each time
Print the ans on the console

After loading the second file



Console waiting for the user input for number n



Result after putting 21



Register values



Let's find Euler Phi function for some other integers



We know phi(n) if n is prime is n-1 , 97 is a prime number so phi(97)==96



phi(96)=32



phi(1000)=400



phi(7895)=6312



phi(9973)=9972



phi(84658)=36276



phi(99991)=99990

Note -we can also use this program to find whether the given number is prime or not
If phi(n)=n-1 then prime else composite