

TECHNICAL DATA SHEET

Activator

Art. no. 0893 301 23

P. Qty.: 1

Accelerates the curing of superglues

Typical applications include the field of filter production, where screens are glued to frames and the large open screen surface is subsequently cured.

Chemical basis	Mix of organic solvents
Density	0.8 g/cm ³
Smell/fragrance	Characteristic
Colour	Colourless
Shelf life from production/conditions	36 Month/at room temperature
Contents	150 ml



Application area

The accelerated curing of superglues is recommended if:

- work results must be reliable within single-digit seconds.
- inactive or porous materials are used, such as metals, wood, ceramics etc.
- there are large gaps, which extend the curing time.

Application information

Spray the activator on one of the two adhesive surfaces from a distance of approx. 20 cm, allow to evaporate completely and then apply adhesive (Klebfix, Klebfix Flex, Klebfix Plasto, Klebfix 4 in 1, Klebfix Gel) to the other adhesive surface. When used on plastics, it is recommended to test the compatibility in a non-visible area.

Notice

Spray the activator on one of the two adhesive surfaces from a distance of approximately 20 cm. When used on plastics, it is recommended to test the compatibility in a non-visible area. Using the activator may reduce the final strength of the adhesive used by about 20 % compared to ideal values.

The usage instructions are recommendations based on the tests we have conducted and our experience. Carry out your own tests before each application. Due to the large number of applications as well as storage and usage conditions, we do not assume any liability for a specific application result. Any technical information or advice provided by our free customer service shall be provided to the exclusion of any liability, unless the advice or information is part of our contractually agreed scope of services or the advisor was acting wilfully. We ensure the consistent quality of our products. We reserve the right to make technical changes and further developments to our products. Please observe the technical data sheet!