

TECHNICAL DATA SHEET

Movement detection paint

Art. no. 0893 741 453

P. Qty.: 1 / 12

Solvent-free locking, marking and sealing lacquer with good adhesion to virtually all materials

Suitable for brass, copper, iron, steel, bronze, aluminium, ceramics, silver and numerous other substrates.

Colour	Light blue RAL 5012
Contents	50 ml
Density/conditions	0.99 g/cm ³ /at 20 °C, 50% relative humidity
Min. initial strength	30 min
Min./max. final strength	12 h-24 h
Min./max. processing temperature	5 to 30 °C
Min./max. temperature resistance	-40 to 145 °C
Silicone-free	Yes
Solvent-free	Yes
Shelf life from production/conditions	24 Month/cool and frost-free storage area, in sealed original container



Application area

The screw retainer varnish is suitable for visually checking all possible movements between connected adjusted parts, and thus documents quality assurance, manufacturing control and product testing with a lacquer seal and protects against intrusion by third parties. The screw retainer varnish is applied to stud bolts, pressure fittings, nuts and other threaded connections once they have been properly pre-stressed and adjusted.

The product can also be used for masking electrically conductive parts to protect against corrosion and influence by touch. And for colour-coding tools. For mechanics who often work in other workshops or who work together with several colleagues in a workshop.

Application information

For optimum adhesion, the substrate must be thoroughly cleaned of oil, grease, moisture and rust with Metal Cleaner 7063 (art. no. 0890 107 063).

Apply/drip directly onto the area to be secured. Product residues and impurities can be removed with acetone cleaner (art. no. 0893 460). The bottle should be tightly closed after each use.

Disposal instructions

Dispose of paints and paint residues in compliance with regional regulations.

TECHNICAL DATA SHEET

The usage instructions are recommendations based on the tests we have conducted and on our experience; carry out your own tests before each application. Due to the large number of applications and storage and processing conditions, we do not assume any liability for a specific application result. Insofar as our free customer service provides technical information or acts as an advisory service, no responsibility is assumed by the provision of this service except where the advice or information given falls within the scope of our specified, contractually agreed service or the advisor was acting deliberately. We guarantee the consistent quality of our products. We reserve the right to make technical changes and further develop products. Please observe the technical data sheet!