

# TECHNICAL DATA SHEET

## REPLAST® Easy Universal plastic adhesive

**Art. no. 0893 500 4**

### For REPLAST® Easy plastic repair system

|                                  |                            |
|----------------------------------|----------------------------|
| Contents                         | 50 ml                      |
| Chemical basis                   | Two-component polyurethane |
| Processing time                  | 3.5 min                    |
| Colour                           | Black                      |
| Density                          | 1.225 g/cm <sup>3</sup>    |
| Min. initial strength            | 30 min                     |
| Min./max. processing temperature | 15 to 25 °C                |
| Min./max. temperature resistance | -30 to +100 °C             |
| Silicone-free                    | Yes                        |
| Shore D hardness                 | 79                         |
| Can be sanded after              | 30 min                     |
| Sanding conditions               | 23 °C                      |



## Application area

### Cars:

Spoilers, radiator grilles, panel clips, bumpers, brackets on headlights and radiators etc.

### HGVs and buses:

Aprons, bumpers, air intake pipes, wheel arches etc.

### Motorcycles:

All panelling

## Notice

There may be adhesion problems in individual cases due to the coatings and release agents used in some cases in the plastic production process. Not suitable for PE (polyethylene), PP (polypropylene) or PTFE (polytetrafluoroethylene) plastics. Check material compatibility on an invisible area if necessary.

The usage instructions are recommendations based on the tests we have conducted and are based on our experience; carry out your own tests before each application. We do not assume any liability for a specific application result due to the large number of applications and storage and processing conditions. Insofar as our free customer service provides technical information or acts as an advisory service, no responsibility is assumed by this service except where the advice or information given falls within the scope of our specified, contractually agreed service or the advisor was acting deliberately. We guarantee consistent quality of our products. We reserve the right to make technical changes and further develop products.