Computer Network Security

UE23CS343AB6

5th Semester, Academic Year 2023

Date: 12/08/2025

Name: Roshini Ramesh	SRN: PES1UG23CS488	Section: H

TASK 1.1A STEP-1: SNIFF IP PACKETS USING SCAPY (WITH ROOT PRIVILEGES)

Terminal Output:




```
###[ Ethernet ]###
  dst       = 02:42:12:dd:f6:96
  src       = 02:42:0a:09:00:05
  type      = IPv4
###[ IP ]###
     version   = 4
     ihl       = 5
     tos       = 0x0
     len       = 84
     id        = 39422
     flags     = DF
     frag      = 0
     ttl       = 64
     proto     = icmp
     chksum    = 0x868d
     src       = 10.9.0.5
     dst       = 8.8.8.8
     \options   \
###[ ICMP ]###
        type      = echo-request
        code      = 0
        chksum    = 0xed61
        id        = 0x1d
        seq       = 0x1
###[ Raw ]###
           load      = '\x85\xe0\x9ah\x00\x00\x00\x00&d\x05\x00\x00\x00\x00\x00\x10\x11\x12\x13\x14\x15\x16\x17\x18\x19\x1a\x1b\x1c\x1d\x1e\x
1f !"#$%&\'()*+,-./01234567'

###[ Ethernet ]###
  dst       = 02:42:0a:09:00:05
  src       = 02:42:12:dd:f6:96
```


```
###[ Ethernet ]###
  dst       = 02:42:0a:09:00:05
  src       = 02:42:12:dd:f6:96
  type      = IPv4
###[ IP ]###
     version   = 4
     ihl       = 5
     tos       = 0x0
     len       = 84
     id        = 98
     flags     = DF
     frag      = 0
     ttl       = 254
     proto     = icmp
     chksum    = 0x6229
     src       = 8.8.8.8
     dst       = 10.9.0.5
     \options   \
###[ ICMP ]###
        type      = echo-reply
        code      = 0
        chksum    = 0xf561
        id        = 0x1d
        seq       = 0x1
###[ Raw ]###
           load      = '\x85\xe0\x9ah\x00\x00\x00\x00&d\x05\x00\x00\x00\x00\x00\x10\x11\x12\x13\x14\x15\x16\x17\x18\x19\x1a\x1b\x1c\x1d\x1e\x
1f !"#$%&\'()*+,-./01234567'

###[ Ethernet ]###
  dst       = 02:42:12:dd:f6:96
  src       = 02:42:0a:09:00:05
```


```
###[ Ethernet ]###
  dst       = 02:42:12:dd:f6:96
  src       = 02:42:0a:09:00:05
  type      = IPv4
###[ IP ]###
     version   = 4
     ihl       = 5
     tos       = 0x0
     len       = 84
     id        = 39669
     flags     = DF
     frag      = 0
     ttl       = 64
     proto     = icmp
     chksum    = 0x8596
     src       = 10.9.0.5
     dst       = 8.8.8.8
     \options   \
###[ ICMP ]###
        type      = echo-request
        code      = 0
        chksum    = 0xae4f
        id        = 0x1d
        seq       = 0x2
###[ Raw ]###
           load      = '\x86\xe0\x9ah\x00\x00\x00\x00du\x05\x00\x00\x00\x00\x00\x10\x11\x12\x13\x14\x15\x16\x17\x18\x19\x1a\x1b\x1c\x1d\x1e\x
1f !"#$%&\'()*+,-./01234567'

###[ Ethernet ]###
  dst       = 02:42:0a:09:00:05
  src       = 02:42:12:dd:f6:96
```

Wireshark Output:



Explanation:

The python code given uses the sniff function to sniff packets on the network. This requires root privileges, which are given by default to the docker container. So, when host A pings 8.8.8.8, the attacker sniffs the ICMP echo request and reply, as seen in the Wireshark as well as terminal output. The contents of the packets are also clearly visible through this process.

TASK 1.1A STEP-2: SNIFF IP PACKETS USING SCAPY (WITHOUT ROOT PRIVILEGES)

Terminal Output:

Wireshark Output:

No Wireshark output.

Explanation:

Before executing the code, root privileges are removed. So, when the program is run, we get PermissionError. Therefore, packet sniffing can be done only when attacker has root privileges.

TASK 1.1 B: APPLYING PACKET FILTERS TO CAPTURE ICMP PACKETS

Terminal Output:




```
 !"#$%&\'()*+,-./01234567'

^Croot@VM:/volumes/Week-1 Code# export PS1="seed-attacker:PES1UG23CS488:RoshiniRamesh:\w\n\$>"
seed-attacker:PES1UG23CS488:RoshiniRamesh:/volumes/Week-1 Code
$>python3 Task1.1B-ICMP.py
SNIFFING PACKETS...
###[ Ethernet ]###
  dst       = 02:42:12:dd:f6:96
  src       = 02:42:0a:09:00:05
  type      = IPv4
###[ IP ]###
     version   = 4
     ihl       = 5
     tos       = 0x0
     len       = 84
     id        = 40872
     flags     = DF
     frag      = 0
     ttl       = 64
     proto     = icmp
     chksum    = 0x80e3
     src       = 10.9.0.5
     dst       = 8.8.8.8
     \options   \
###[ ICMP ]###
        type      = echo-request
        code      = 0
        chksum    = 0xfb8d
        id        = 0x20
        seq       = 0x1
###[ Raw ]###
           load      = '\x9f\xe5\x9ah\x00\x00\x00\x00\xf9/\n\x00\x00\x00\x00\x00\x10\x11\x12\x13\x14\x15\x16\x17\x18\x19\x1a\x1b\x1c\x1d\x1e\
```


```
        id        = 0x20
        seq       = 0x1
###[ Raw ]###
           load      = '\x9f\xe5\x9ah\x00\x00\x00\x00\xf9/\n\x00\x00\x00\x00\x00\x10\x11\x12\x13\x14\x15\x16\x17\x18\x19\x1a\x1b\x1c\x1d\x1e\
x1f !"#$%&\'()*+,-./01234567'

###[ Ethernet ]###
  dst       = 02:42:0a:09:00:05
  src       = 02:42:12:dd:f6:96
  type      = IPv4
###[ IP ]###
     version   = 4
     ihl       = 5
     tos       = 0x0
     len       = 84
     id        = 203
     flags     = DF
     frag      = 0
     ttl       = 254
     proto     = icmp
     chksum    = 0x61c0
     src       = 8.8.8.8
     dst       = 10.9.0.5
     \options   \
###[ ICMP ]###
        type      = echo-reply
        code      = 0
        chksum    = 0x38e
        id        = 0x20
        seq       = 0x1
###[ Raw ]###
           load      = '\x9f\xe5\x9ah\x00\x00\x00\x00\xf9/\n\x00\x00\x00\x00\x00\x10\x11\x12\x13\x14\x15\x16\x17\x18\x19\x1a\x1b\x1c\x1d\x1e\
```




```
x1f !"#$%&\'()*+,-./01234567'

###[ Ethernet ]###
  dst       = 02:42:12:dd:f6:96
  src       = 02:42:0a:09:00:05
  type      = IPv4
###[ IP ]###
     version   = 4
     ihl       = 5
     tos       = 0x0
     len       = 84
     id        = 40880
     flags     = DF
     frag      = 0
     ttl       = 64
     proto     = icmp
     chksum    = 0x80db
     src       = 10.9.0.5
     dst       = 8.8.8.8
     \options   \
###[ ICMP ]###
        type      = echo-request
        code      = 0
        chksum    = 0x6085
        id        = 0x20
        seq       = 0x2
###[ Raw ]###
           load      = '\xa0\xe5\x9ah\x00\x00\x00\x00\x937\n\x00\x00\x00\x00\x00\x10\x11\x12\x13\x14\x15\x16\x17\x18\x19\x1a\x1b\x1c\x1d\x1e\
x1f !"#$%&\'()*+,-./01234567'

###[ Ethernet ]###
  dst       = 02:42:0a:09:00:05
```



```
  src       = 02:42:12:dd:f6:96
  type      = IPv4
###[ IP ]###
     version   = 4
     ihl       = 5
     tos       = 0x0
     len       = 84
     id        = 204
     flags     = DF
     frag      = 0
     ttl       = 254
     proto     = icmp
     chksum    = 0x61bf
     src       = 8.8.8.8
     dst       = 10.9.0.5
     \options   \
###[ ICMP ]###
        type      = echo-reply
        code      = 0
        chksum    = 0x6885
        id        = 0x20
        seq       = 0x2
###[ Raw ]###
           load      = '\xa0\xe5\x9ah\x00\x00\x00\x00\x937\n\x00\x00\x00\x00\x00\x10\x11\x12\x13\x14\x15\x16\x17\x18\x19\x1a\x1b\x1c\x1d\x1e\
x1f !"#$%&\'()*+,-./01234567'

###[ Ethernet ]###
  dst       = 02:42:12:dd:f6:96
  src       = 02:42:0a:09:00:05
  type      = IPv4
###[ IP ]###
     version   = 4
```



Wireshark Output:



Explanation:

In the given code, the filter feature of sniff to capture only ICMP packets is used. Hence, both the terminal and Wireshark output display only sniffed ICMP echo request and reply packets which Host A sends while pinging 8.8.8.8.

TASK 1.1 B: APPLYING PACKET FILTERS TO CAPTURE SUBNET PACKETS

Terminal Output:



```
seed@VM: ~/.../Labsetup
seed@VM: ~/.../Labsetup   seed@VM: ~/.../Labsetup   seed@VM: ~
\x1e\x1f !"#$%&\'()*+,-./01234567'

^Cseed-attacker:PES1UG23CS488:RoshiniRamesh:/volumes/Week-1 Code
$>python3 Task1.1B-Subnet.py
SNIFFING PACKETS...
###[ Ethernet ]###
  dst       = 02:42:0a:09:00:05
  src       = 02:42:12:dd:f6:96
  type      = IPv4
###[ IP ]###
     version   = 4
     ihl       = 5
     tos       = 0x0
     len       = 84
     id        = 272
     flags     = DF
     frag      = 0
     ttl       = 254
     proto     = icmp
     chksum    = 0xb2e0
     src       = 192.168.254.1
     dst       = 10.9.0.5
     \options   \
###[ ICMP ]###
        type      = echo-reply
        code      = 0
        chksum    = 0x8487
        id        = 0x24
        seq       = 0x1
###[ Raw ]###
           load      = '\xa9\xeb\x9ah\x00\x00\x00\x00j,\x0e\x00\x00\x00\x00\x00\x10\x11\x12\x13\x14\x15\x16\x17\x18\x19\x1a\x1b\x1c\x1d\x1e\x
1f !"#$%&\'()*+,-./01234567'
```



```
seed@VM: ~/.../Labsetup
seed@VM: ~/.../Labsetup   seed@VM: ~/.../Labsetup   seed@VM: ~

###[ Ethernet ]###
  dst       = 02:42:0a:09:00:05
  src       = 02:42:12:dd:f6:96
  type      = IPv4
###[ IP ]###
     version   = 4
     ihl       = 5
     tos       = 0x0
     len       = 84
     id        = 273
     flags     = DF
     frag      = 0
     ttl       = 254
     proto     = icmp
     chksum    = 0xb2df
     src       = 192.168.254.1
     dst       = 10.9.0.5
     \options   \
###[ ICMP ]###
        type      = echo-reply
        code      = 0
        chksum    = 0xda7e
        id        = 0x24
        seq       = 0x2
###[ Raw ]###
           load      = '\xaa\xeb\x9ah\x00\x00\x00\x00\x134\x0e\x00\x00\x00\x00\x00\x10\x11\x12\x13\x14\x15\x16\x17\x18\x19\x1a\x1b\x1c\x1d\x1
e\x1f !"#$%&\'()*+,-./01234567'

###[ Ethernet ]###
  dst       = 02:42:0a:09:00:05
  src       = 02:42:12:dd:f6:96
```




```
  type      = IPv4
###[ IP ]###
     version   = 4
     ihl       = 5
     tos       = 0x0
     len       = 84
     id        = 274
     flags     = DF
     frag      = 0
     ttl       = 254
     proto     = icmp
     chksum    = 0xb2de
     src       = 192.168.254.1
     dst       = 10.9.0.5
     \options   \
###[ ICMP ]###
        type      = echo-reply
        code      = 0
        chksum    = 0xff7b
        id        = 0x24
        seq       = 0x3
###[ Raw ]###
           load      = '\xab\xeb\x9ah\x00\x00\x00\x00\xed5\x0e\x00\x00\x00\x00\x10\x11\x12\x13\x14\x15\x16\x17\x18\x19\x1a\x1b\x1c\x1d\x1
e\x1f !"#$%&\'()*+,-./01234567'

###[ Ethernet ]###
  dst       = 02:42:0a:09:00:05
  src       = 02:42:12:dd:f6:96
  type      = IPv4
###[ IP ]###
     version   = 4
     ihl       = 5
```


```
     tos       = 0x0
     len       = 84
     id        = 275
     flags     = DF
     frag      = 0
     ttl       = 254
     proto     = icmp
     chksum    = 0xb2dd
     src       = 192.168.254.1
     dst       = 10.9.0.5
     \options   \
###[ ICMP ]###
        type      = echo-reply
        code      = 0
        chksum    = 0x5179
        id        = 0x24
        seq       = 0x4
###[ Raw ]###
           load      = '\xac\xeb\x9ah\x00\x00\x00\x00\x9a7\x0e\x00\x00\x00\x00\x00\x10\x11\x12\x13\x14\x15\x16\x17\x18\x19\x1a\x1b\x1c\x1d\x1
e\x1f !"#$%&\'()*+,-./01234567'

###[ Ethernet ]###
  dst       = 02:42:0a:09:00:05
  src       = 02:42:12:dd:f6:96
  type      = IPv4
###[ IP ]###
     version   = 4
     ihl       = 5
     tos       = 0x0
     len       = 84
     id        = 276
     flags     = DF
```

Wireshark Output:



Explanation:

In the given code, the filter feature of sniff to capture only packets on a given subnet. Hence, both the terminal and Wireshark output display only sniffed ICMP echo request and reply packets which Host A sends while pinging 192.168.254.1.

TASK 1.1 B: APPLYING PACKET FILTERS TO CAPTURE TCP PACKETS USING TELNET

Terminal Output:


seed@VM: ~/.../Labsetup
seed@VM: ~/.../Labsetup
seed@VM: ~/.../Labsetup
seed@VM: ~
options = [('NOP', None), ('NOP', None), ('Timestamp', (4011854205, 539476127))]
^Cseed-attacker:PES1UG23CS488:RoshiniRamesh:/volumes/Week-1 Code
$>python3 Task1.1B-TCP.py
SNIFFING PACKETS...
###[Ethernet]###
dst = 02:42:12:dd:f6:96
src = 02:42:0a:09:00:05
type = IPv4
###[IP]###
version = 4
ihl = 5
tos = 0x10
len = 53
id = 45479
flags = DF
frag = 0
ttl = 64
proto = tcp
chksum = 0x74f4
src = 10.9.0.5
dst = 10.9.0.1
\options \
###[TCP]###
sport = 41012
dport = telnet
seq = 940915190
ack = 3719046738
dataofs = 8
reserved = 0
flags = PA
window = 501


seed@VM: ~/.../Labsetup
seed@VM: ~/.../Labsetup
seed@VM: ~/.../Labsetup
seed@VM: ~
chksum = 0x143f
urgptr = 0
options = [('NOP', None), ('NOP', None), ('Timestamp', (4011875297, 539476127))]
###[Raw]###
load = 't'
###[Ethernet]###
dst = 02:42:12:dd:f6:96
src = 02:42:0a:09:00:05
type = IPv4
###[IP]###
version = 4
ihl = 5
tos = 0x10
len = 52
id = 45480
flags = DF
frag = 0
ttl = 64
proto = tcp
chksum = 0x74f4
src = 10.9.0.5
dst = 10.9.0.1
\options \
###[TCP]###
sport = 41012
dport = telnet
seq = 940915191
ack = 3719046739
dataofs = 8
reserved = 0
flags = A


```
        window    = 501
        chksum    = 0x143e
        urgptr    = 0
        options   = [('NOP', None), ('NOP', None), ('Timestamp', (4011875298, 539497220))]

###[ Ethernet ]###
  dst       = 02:42:12:dd:f6:96
  src       = 02:42:0a:09:00:05
  type      = IPv4
###[ IP ]###
     version   = 4
     ihl       = 5
     tos       = 0x10
     len       = 53
     id        = 45481
     flags     = DF
     frag      = 0
     ttl       = 64
     proto     = tcp
     chksum    = 0x74f2
     src       = 10.9.0.5
     dst       = 10.9.0.1
     \options   \
###[ TCP ]###
        sport     = 41012
        dport     = telnet
        seq       = 940915191
        ack       = 3719046739
        dataofs   = 8
        reserved  = 0
        flags     = PA
        window    = 501
```


```
        chksum    = 0x143f
        urgptr    = 0
        options   = [('NOP', None), ('NOP', None), ('Timestamp', (4011875423, 539497220))]
###[ Raw ]###
           load      = 'e'

###[ Ethernet ]###
  dst       = 02:42:12:dd:f6:96
  src       = 02:42:0a:09:00:05
  type      = IPv4
###[ IP ]###
     version   = 4
     ihl       = 5
     tos       = 0x10
     len       = 52
     id        = 45482
     flags     = DF
     frag      = 0
     ttl       = 64
     proto     = tcp
     chksum    = 0x74f2
     src       = 10.9.0.5
     dst       = 10.9.0.1
     \options   \
###[ TCP ]###
        sport     = 41012
        dport     = telnet
        seq       = 940915192
        ack       = 3719046740
        dataofs   = 8
        reserved  = 0
        flags     = A
```

Wireshark Output:



Explanation:

In the given code, the filter feature of sniff is used to capture only TCP packets. This is done while host A sets up a Telnet connection to 8.8.8.8. Telnet works on port 23.

TASK 1.2A: PACKET SPOOFING

Terminal Output:



Wireshark:



Explanation:

In the given code, a spoofed ICMP echo request packet is sent using an IP on the network. The packet is being sent from 10.9.0.1 to 10.9.0.5. An ICMP echo reply is received, showing that spoofing has been successful.

TASK 1.2B: PACKET SPOOFING

Terminal Output:



Wireshark:



Explanation:

In the given code, a spoofed ICMP echo request packet is sent using an arbitrary IP (which is non-existent on the network). The packet is being sent from 10.9.0.11 to 10.9.0.99. An ICMP echo reply is received, showing that spoofing has been successful.

TASK 1.3: TRACEROUTE

Terminal Output:

```
seed-attacker:PES1UG23CS488:RoshiniRamesh:/volumes/Week-1 Code
$>python3 Task1.3.py 8.8.8.8
Traceroute 8.8.8.8
1 hops away:  8.8.8.8
Done 8.8.8.8
```

Wireshark:



Explanation:

In the given code, a simple traceroute program is implemented. The program sends ICMP Echo Requests with increasing TTL values. When ICMP Echo Request reaches the destination, destination sends ICMP Echo Reply. Here, Echo Request has been sent to 8.8.8.8 and after one hop, it responds with an Echo Reply as seen in the Wireshark output.

TASK 1.4: SNIFFING AND-THEN SPOOFING

Terminal Output:



```
seed-attacker:PES1UG23CS488:RoshiniRamesh:/volumes/Week-1 Code
$>python3 Task1.4.py
original packet.........
source IP : 10.9.0.5
Destination IP : 1.2.3.4
spoofed packet........
Source IP: 1.2.3.4
Destination IP: 10.9.0.5
original packet.........
source IP : 10.9.0.5
Destination IP : 1.2.3.4
spoofed packet........
Source IP: 1.2.3.4
Destination IP: 10.9.0.5
original packet.........
source IP : 10.9.0.5
Destination IP : 1.2.3.4
spoofed packet........
Source IP: 1.2.3.4
Destination IP: 10.9.0.5
original packet.........
source IP : 10.9.0.5
Destination IP : 1.2.3.4
spoofed packet........
Source IP: 1.2.3.4
Destination IP: 10.9.0.5
original packet.........
source IP : 10.9.0.5
Destination IP : 1.2.3.4
spoofed packet........
Source IP: 1.2.3.4
Destination IP: 10.9.0.5
```

Wireshark:



Explanation:

This combines all the concepts done so far. Here, Host A pings 1.2.3.4. This is sniffed by the attacker, who then sends a spoofed packet back to Host A. This is how spoofing attacks take place.