

Deployment Server

1. App Deployment Server

Created/updated an app on Deployment Server and ran

`./splunk reload deploy-server`

New Search

```
index="_internal" host=redhat4 source="/opt/splunk/var/log/splunk/splunkd.log" "Deployment Server"
```

i	Time	Event
>	9/24/26 10:06:05.672 AM	09-24-2026 10:06:05.672 +0530 INFO DeploymentServer - Deployment Server has shut down. host = redhat4 source = /opt/splunk/var/log/splunk/splunkd.log sourcetype = splunkd splunk_server = redhat4

2. When we redeploy the existing apps from deployment server

New Search

```
index="_internal" host=redhat4 source="/opt/splunk/var/log/splunk/splunkd.log" Reloading OR Attempting
```

i	Time	Event
>	9/24/26 11:33:22.617 AM	09-24-2026 11:33:22.617 +0530 INFO Serverclass - Reloading serverclass=IdxServer from repository='/opt/splunk/etc/deployment-apps' host = redhat4 source = /opt/splunk/var/log/splunk/splunkd.log sourcetype = splunkd splunk_server = redhat4
>	9/24/26 11:33:22.617 AM	09-24-2026 11:33:22.617 +0530 INFO Serverclass - Reloading application=IdxApp from location='/opt/splunk/etc/deployment-apps' host = redhat4 source = /opt/splunk/var/log/splunk/splunkd.log sourcetype = splunkd splunk_server = redhat4
>	9/24/26 11:33:22.600 AM	09-24-2026 11:33:22.600 +0530 INFO DeploymentServer - Attempting to reload serverclass='IdxServer'; reason='editServerclass' host = redhat4 source = /opt/splunk/var/log/splunk/splunkd.log sourcetype = splunkd splunk_server = redhat4

3. when we create a new app from deployment server and it successfully created

New Search

```
index="_internal" host=redhat4 source="/opt/splunk/var/log/splunk/splunkd.log" Download OR Install
```

i	Time	Event
>	9/24/26 11:43:40.178 AM	09-24-2026 11:43:40.178 +0530 INFO ClientSessionsManager - ip=192.168.152.133 name=7E4C4FD5-AA22-45EF-8480-8AEDFDE71CF7 New record for sc=newAppClass app=newApp: action=Download result=0k checksum=1235953662895335511 host = redhat4 source = /opt/splunk/var/log/splunk/splunkd.log sourcetype = splunkd splunk_server = redhat4
>	9/24/26 11:43:40.178 AM	09-24-2026 11:43:40.178 +0530 INFO ClientSessionsManager - ip=192.168.152.133 name=7E4C4FD5-AA22-45EF-8480-8AEDFDE71CF7 Updating record for sc=newAppClass app=newApp: action=Install result=0k checksum=1235953662895335511 host = redhat4 source = /opt/splunk/var/log/splunk/splunkd.log sourcetype = splunkd splunk_server = redhat4

4. when we create a new app from deployment server but client Ip is not added in clients:

5.3.1 In case of existing deployment:

SearchAnalyticsDatasetsReportsAlertsDashboards

Search & Reporting

New Search

Save AsCreate Table ViewClose

index=_internal host="redhat4" "UF_Server" source="/opt/splunk/var/log/splunk/splunkd.log"5 minute window

2 of 9 events matchedNo Event Sampling

JobPauseStopRefreshDownloadVerbose Mode

Events (2)PatternsStatisticsVisualization

Format TimelineZoom OutZoom to SelectionDeselect1 minute per column

< Hide Fields

All Fields

SELECTED FIELDS

a host 1

a source 1

a sourcetype 1

INTERESTING FIELDS

i	Time	Event
>	24/09/2026 11:46:09.249	09-24-2026 11:46:09.249 +0530 INFO Serverclass - Reloading serverclass=UF_server from repository='/opt/splunk/etc/deployment-apps' host = redhat4 source = /opt/splunk/var/log/splunk/splunkd.log sourcetype = splunkd
>	24/09/2026 11:46:09.235	09-24-2026 11:46:09.235 +0530 INFO DeploymentServer - Attempting to reload serverclass='UF_server'; reason='editServerclass' host = redhat4 source = /opt/splunk/var/log/splunk/splunkd.log sourcetype = splunkd

5.3.2 In case of New Deployment:

splunk>enterpriseApps

AdministratorMessagesSettingsActivityHelpFind

SearchAnalyticsDatasetsReportsAlertsDashboards

Search & Reporting

New Search

Save AsCreate Table ViewClose

index=_internal host="redhat4" "NewLogTestAppServer" source="/opt/splunk/var/log/splunk/splunkd.log"Last 15 minutes

14 events (24/09/2026 11:49:20.000 to 24/09/2026 12:04:20.000)No Event Sampling

JobPauseStopRefreshDownloadVerbose Mode

Events (14)PatternsStatisticsVisualization

Format TimelineZoom OutZoom to SelectionDeselect1 minute per column

< Hide Fields

All Fields

SELECTED FIELDS

a host 1

a source 1

a sourcetype 1

INTERESTING FIELDS

a app 2

a component 5

i	Time	Event
>	24/09/2026 11:57:33.992	09-24-2026 11:57:33.992 +0530 INFO ClientSessionsManager - ip=192.168.152.132 name=9FED2E57-38E4-498D-AB2A-C32791482763 Updating record for sc=NewLogTestAppServer app=LogTestApp: action=Install result=Ok checksum=17812598853994496314 host = redhat4 source = /opt/splunk/var/log/splunk/splunkd.log sourcetype = splunkd
>	24/09/2026 11:57:33.992	09-24-2026 11:57:33.992 +0530 INFO ClientSessionsManager - ip=192.168.152.132 name=9FED2E57-38E4-498D-AB2A-C32791482763 New record for sc=NewLogTestAppServer app=LogTestApp: action=Download result=Ok checksum=17812598853994496314 host = redhat4 source = /opt/splunk/var/log/splunk/splunkd.log sourcetype = splunkd
>	24/09/2026 11:57:33.846	09-24-2026 11:57:33.846 +0530 INFO PackazeDownloadRestHandler - peer=192.168.152.132:54970 Download started and completed for oa