

# TASK-1&2

```
pranay@LAPTOP-OP7R42IK:~$ nano week.c
pranay@LAPTOP-OP7R42IK:~$ gcc week.c -o week
pranay@LAPTOP-OP7R42IK:~$ ./week
Error opening File1.txt: No such file or directory
pranay@LAPTOP-OP7R42IK:~$ nano weekt2.c
pranay@LAPTOP-OP7R42IK:~$ gcc weekt2.c -o weekt2
pranay@LAPTOP-OP7R42IK:~$ ./weekt2
Error opening File1.txt: No such file or directory
pranay@LAPTOP-OP7R42IK:~$ |
```

```
#include <stdio.h>
#include <string.h>

int main() {
    char command[100];

    while (1) {
        printf("\nEnter command (type 'exit' to quit): ");
        fgets(command, sizeof(command), stdin);

        // Remove newline
        command[strcspn(command, "\n")] = '\0';

        if (strcmp(command, "exit") == 0) {
            printf("Exiting program...\n");
            break;
        }

        printf("You entered: %s\n", command);
    }

    return 0;
}
```

```
#include <stdio.h>
#include <fcntl.h>
#include <unistd.h>
#include <stdlib.h>

int main() {
    int fd1, fd2;
    char buffer[1024];
    int bytesRead;

    // Open source file
    fd1 = open("File1.txt", O_RDONLY);
    if (fd1 < 0) {
        perror("Error opening File1.txt");
        return 1;
    }

    // Create/Open destination file
    fd2 = open("File2.txt", O_CREAT | O_WRONLY | O_TRUNC, 0644);
    if (fd2 < 0) {
        perror("Error opening File2.txt");
        close(fd1);
        return 1;
    }

    // Copy contents
    while ((bytesRead = read(fd1, buffer, sizeof(buffer))) > 0) {
        write(fd2, buffer, bytesRead);
    }

    // Close files
    close(fd1);
    close(fd2);

    printf("File copied successfully.\n");

    return 0;
}

pranay@LAPTOP-OP7R421K:~$ nano week3.c
pranay@LAPTOP-OP7R421K:~$ gcc week3.c -o week3
pranay@LAPTOP-OP7R421K:~$ ./week3

Enter command (type 'exit' to quit): exit
Exiting program...
pranay@LAPTOP-OP7R421K:~$ nano week3.c
pranay@LAPTOP-OP7R421K:~$ |
```