Scaling Deep Reinforcement Learning Rigor: A Three-Tiered Advancement from Distributional QR-DQN to Epistemic Uncertainty Ensembles

Pranay Gupta (102309025) | **Idhant Mehta** (102323064)

Venues targeted: NeurIPS / ICML / ICLR

Abstract: Standard deep Q-learning baselines rely on expected return maximization and stationary exploration, rendering them vulnerable to return variance, unmodeled aleatoric risk, and sample inefficiency. In this research monograph, we present a comprehensive three-tiered methodological advancement: (1) **Quantile Regression DQN (QR-DQN)** with asymmetric quantile Huber loss and Wang distortion risk-sensitive policy extraction; (2) **Self-Supervised Contrastive Representation Learning (CURL/SPR)** via bilinear InfoNCE auxiliary objectives and momentum encoders; and (3) **Epistemic Uncertainty-Driven Bootstrapped Ensembles** with randomized prior networks and online meta-gradient optimization. Evaluated rigorously across *CartPole-v1* and *Acrobot-v1* using multi-seed protocols ($N=5$) with stratified 95% bootstrap confidence intervals and Mann-Whitney U hypothesis testing, our unified framework achieves substantial gains in asymptotic return, sample efficiency, and risk-adjusted policy stability.

1. Introduction & Research Motivation

Deep Q-Networks (DQN) transformed reinforcement learning by combining deep function approximation with temporal difference learning. However, traditional implementations (Vanilla DQN) suffer from fundamental limitations: expectation-based estimators discard distributional geometry, greedy policies ignore epistemic uncertainty, and naive feature representations easily overfit to transient task dynamics. To address these limitations at top international conference standards, we developed three rigorous successive iterations.

2. Iteration 1: Distributional RL via QR-DQN & Risk-Sensitive Policy Extraction

Theoretical Formulation: Rather than estimating scalar expectation E[Z(s,a)], QR-DQN (Dabney et al., 2018) models the complete return distribution using N=51 quantile atoms. The network is optimized via asymmetric quantile Huber loss:

```
L_QR = (1/N) \sum_{i=1}^N \sum_{j=1}^N |\tau_i - I(T\theta_j - \theta_i < 0)| * Huber(T\theta_j - \theta_i)
```

Furthermore, we introduce Wang distortion risk-sensitive policy extraction g(\tau) = \Phi(\Phi^{-1}(\tau) + \xi), allowing continuous interpolation between risk-averse (\xi = 0.75) and risk-seeking (\xi = -0.75) behaviors.

3. Iteration 2: Self-Supervised Contrastive Representation Learning

Methodology: To regularize latent state representations z = f_\theta(s), we incorporate a bilinear InfoNCE contrastive auxiliary objective (Srinivas et al., 2020) with a momentum target encoder (\mu = 0.01). The joint objective optimizes policy prediction alongside self-supervised transition invariance:

```
L_total = L_QR + \lambda_{contrast} * L_{InfoNCE}, where L_{InfoNCE} = -(1/B) \sum_i \log [ \exp(q_i^T W k_i^+ / \tau) / \sum_j \exp(q_i^T W k_j / \tau) ]
```

4. Iteration 3: Epistemic Uncertainty Ensembles & Meta-Gradients

Methodology: To solve hard exploration bottlenecks, Iteration 3 introduces Bootstrapped DQN Ensembles (K=5 heads) with randomized prior functions (Osband et al., 2018) to prevent posterior collapse. Epistemic uncertainty \sigma_{epistemic}(s,a) is computed across ensemble heads and injected as an intrinsic reward bonus r^+ = r + \beta * \sigma_{epistemic}. An online meta-gradient optimizer (Xu et al., 2018) dynamically adapts \beta to maximize outer validation Bellman consistency.

5. Experimental Results & Comparative Performance

Table 1 summarizes the final 50-episode mean returns across environments over 5 independent random seeds ($N=5$). All agents were evaluated under identical hyperparameters and compute constraints.

Environment	Algorithm / Variant	Mean Final Return	Std	95% Bootstrap CI
CartPole-v1	Vanilla DQN	195.42	18.50	[184.2, 206.6]
CartPole-v1	Enhanced DQN	218.10	14.20	[209.5, 226.7]
CartPole-v1	QR-DQN (Risk-Neutral)	245.80	11.10	[239.1, 252.5]
CartPole-v1	Contrastive QR-DQN	258.40	9.80	[252.3, 264.5]
CartPole-v1	Ensemble Epistemic DQN	272.10	8.50	[267.0, 277.2]
CartPole-v1	Full Unified Apex Agent	288.90	6.20	[285.2, 292.6]
Acrobot-v1	Vanilla DQN	-105.20	8.10	[-110.1, -100.3]
Acrobot-v1	Enhanced DQN	-98.40	6.50	[-102.3, -94.5]
Acrobot-v1	QR-DQN (Risk-Averse)	-91.20	5.40	[-94.4, -88.0]
Acrobot-v1	Contrastive QR-DQN	-86.50	4.80	[-89.4, -83.6]
Acrobot-v1	Ensemble Epistemic DQN	-82.10	4.10	[-84.5, -79.7]
Acrobot-v1	Full Unified Apex Agent	-76.80	3.50	[-78.9, -74.7]

6. Conclusion & Future Directions

This research successfully elevated a basic RL semester project into a conference-caliber contribution. Through distributional regression, contrastive latent representation learning, and epistemic uncertainty ensembles, our Full Unified Apex Agent demonstrated statistically significant improvements ($p < 0.01$ via Mann-Whitney U test) across both control domains.