

Synthetic Supplier Datasheet - VXS-24 On/Off Valve

Supplier document	VD-VXS24
Revision	B
Date	05 Feb 2026
Applicable project tags	XV-101, XV-102, XV-103

1. Product Family

Synthetic VXS-24 spring-return, two-position liquid isolation valve with 24 VDC actuator. Project tags XV-101, XV-102 and XV-103 use this family.

Characteristic	XV-101	XV-102	XV-103
Project service	Feed to Tank 1	Tank 1 transfer	Tank 2 drain
De-energized position	Closed	Closed	Closed
Nominal demo flow coefficient equivalent	0.0060 m ³ /s	0.0045 m ³ /s	0.0050 m ³ /s
Full open stroke time	0.8 s	0.8 s	0.8 s
Full close stroke time	0.6 s	0.6 s	0.6 s
Command	24 VDC energized=open	24 VDC energized=open	24 VDC energized=open

2. Functional Safety Note

Loss of electrical power removes actuator energy and the spring returns the valve to the closed position. This datasheet does not define process sequencing or whether two valves may be open concurrently; that is a system-controls decision.

3. Installation Note

For the hackathon simulation the dynamic valve stroke is neglected and each valve is treated as an ideal Boolean flow switch. The physical stroke times remain useful as equipment properties in the system model.