SAFETY DATA SHEET

According to Regulation (EC) No 1907/2006 (REACH) and (EU) 2020/878. Document SDS-AN-3301 - Revision 3.7 - Date of issue 2026-04-15.

SECTION 1: Identification of the substance/mixture and of the company

Product name	International Interthane 990 Polyurethane Topcoat
Product code	SDS-AN-3301
Product type	Industrial / professional coating
Relevant identified uses	Two-component aliphatic acrylic polyurethane finish for steelwork.
Supplier	AkzoNobel N.V., Christian Neefestraat 2, 1077 WW Amsterdam, The Netherlands
Emergency telephone	+31 (0)20 502 7555 (24h)

SECTION 2: Hazards identification

Classification (CLP)	Flammable Liquid, Category 3
Signal word	Danger
Hazard statements	GHS02, GHS07; H226; H319; H335; H336.
Precautionary statements	P210 Keep away from heat/sparks. P280 Wear protective gloves/eye protection. P403-

SECTION 3: Composition / information on ingredients

Chemical name	CAS No.	Conc.	Classification
Acrylic polyol resin	Proprietary	35 - 50%	Not classified
n-Butyl acetate	123-86-4	15 - 25%	Flam. Liq. 3; H226; STOT SE 3
Solvent naphtha (aromatic, light)	64742-95-6	8 - 15%	Flam. Liq. 3; H304; H336
Titanium dioxide (rutile)	13463-67-7	8 - 15%	Carc. 2 (inhalable dust)

SECTION 4: First-aid measures

Inhalation: Move to fresh air. If symptoms persist, obtain medical attention. **Skin contact:** Wash with soap and water; remove contaminated clothing. **Eye contact:** Rinse cautiously with water for several minutes. **Ingestion:** Do not induce vomiting; seek medical advice.

SECTION 5: Fire-fighting measures

Flash point	27 deg C (closed cup)
Suitable extinguishing media	Foam, CO2, dry powder, water spray. Do not use water jet.
Special hazards	Combustion may release CO, CO2 and nitrogen oxides. Powders may form explosive

SECTION 6: Accidental release measures

Eliminate ignition sources. Use personal protection as in Section 8. Collect mechanically; avoid dust generation. Prevent entry into drains and watercourses.

SECTION 7: Handling and storage

Safe handling	Avoid inhalation of dust/vapour. Ensure adequate ventilation. No smoking.
Storage conditions	Store in original closed container in a dry, well-ventilated area.
Storage temperature	5 to 30 deg C
Incompatible materials	Strong oxidising agents, strong acids and bases.
Shelf life	24 months from date of manufacture under recommended conditions.

SECTION 8: Exposure controls / personal protection

Occupational exposure limits	Observe local OEL/WEL values for solvents, dusts and TiO2 (inhalable).
Engineering controls	Provide local exhaust ventilation; maintain airborne levels below OEL.
Required PPE	Nitrile gloves, organic-vapour respirator A2, goggles, coverall

SECTION 9: Physical and chemical properties

Property	Value
Form	Liquid
Colour	Various (pigmented)
Odour	Solvent
pH	Not applicable
Density	1.1 - 1.3 g/cm3
Solubility (water)	Immiscible
VOC content	420 g/L
Flash point	27 deg C

SECTION 10: Stability and reactivity

Stable under normal conditions. Avoid heat, sparks and open flame. Hazardous polymerisation does not occur.

SECTION 11: Toxicological information

May cause irritation of eyes, skin and respiratory tract. Titanium dioxide classified Carc. 2 by inhalation of dust. See Section 3 for sensitisers.

SECTION 12: Ecological information

Do not allow to enter drains, soil or watercourses. Aquatic toxicity depends on components; see Section 3 classifications.

SECTION 13: Disposal considerations

Dispose of contents/container in accordance with local, regional and national regulations. European Waste Catalogue code per use.

SECTION 14: Transport information

Classify for transport (ADR/IMDG/IATA) according to flammability and environmental hazard. Non-flammable water-based products are generally not regulated.

SECTION 15: Regulatory information

Complies with REACH (EC) 1907/2006 and CLP (EC) 1272/2008. VOC content stated in Section 9 per Directive 2004/42/EC.

SECTION 16: Other information

Revision 3.7. This SDS is a SYNTHETIC document created for a Databricks document-intelligence demo and does not describe a real product formulation.